## TObject

| | | |
|---|---|---|
| fUniqueID | kIsReferenced | kZombie |
| fBits | kHasUUID | kBitMask |
| fgDtorOnly | kCannotPick | kSingleKey |
| fgObjectStat | kNoContextMenu | kOverwrite |
| kCanDelete | kInvalidObject | kWriteDelete |
| kMustCleanup | kIsOnHeap | fgIsA |
| kObjInCanvas | kNotDeleted | |

| | | |
|---|---|---|
| @~TObject | GetOption | operator new |
| MakeZombie | GetObjectInfo | operator new@[@] |
| DoError | GetTitle | operator delete |
| TObject | HandleTimer | operator delete@[@ |
| TObject | Hash | operator delete |
| operator= | InheritsFrom | operator delete@[@ |
| AppendPad | InheritsFrom | SetBit |
| Browse | Inspect | SetBit |
| ClassName | IsFolder | ResetBit |
| Clear | IsEqual | TestBit |
| Clone | IsSortable | TestBits |
| Compare | IsOnHeap | InvertBit |
| Copy | IsZombie | Info |
| Delete | Notify | Warning |
| DistancetoPrimitive | Write | Error |
| Draw | Paint | SysError |
| DrawClass | Pop | Fatal |
| DrawClone | Print | AbstractMethod |
| Dump | Read | MayNotUse |
| Execute | RecursiveRemove | SetDtorOnly |
| Execute | SavePrimitive | SetDtorOnly |
| ExecuteEvent | SetDrawOption | GetObjectStat |
| FindObject | SetUniqueID | SetObjectStat |
| FindObject | UseCurrentStyle | Class |
| GetDrawOption | Write | Class_Name |
| GetUniqueID | Write | IsA |
| GetName | operator new | ShowMembers |
| GetIconName | operator new@[@] | |

## TNamed

| | |
|---|---|
| fName | |
| fTitle | |
| fgIsA | |

| | |
|---|---|
| @~TNamed | |
| TNamed | |
| TNamed | |
| TNamed | |
| TNamed | |
| operator= | |
| Clear | |
| Clone | |
| Compare | |
| Copy | |
| FillBuffer | |
| GetName | |
| GetTitle | |
| Hash | |
| IsSortable | |
| SetName | |
| SetNameTitle | |
| SetTitle | |
| Is | |
| Print | |
| Sizeof | |
| Class | |
| Class_Name | |
| IsA | |
| ShowMembers | |

## TVirtualX

| | | | | |
|---|---|---|---|---|
| kCopy | kHollow | kOpaque | fDrawMode | |
| kXor | kFilled | kCheck | fgIsA | |
| kInvert | kClear | kLoad | | |

| | | | | |
|---|---|---|---|---|
| @~TVirtualX | ResizePixmap | RaiseWindow | QueryColor | GetPrimarySelectionOwner |
| TVirtualX | ResizeWindow | LowerWindow | FreeColor | SetPrimarySelectionOwner |
| TVirtualX | SelectWindow | MoveWindow | EventsPending | ConvertPrimarySelection |
| Init | SelectPixmap | MoveResizeWindow | NextEvent | LookupString |
| ClearWindow | SetCharacterUp | ResizeWindow | Bell | GetPasteBuffer |
| ClosePixmap | SetClipOFF | IconifyWindow | CopyArea | TranslateCoordinates |
| CloseWindow | SetClipRegion | ReparentWindow | ChangeWindowAttributes | GetWindowSize |
| CopyPixmap | SetCursor | SetWindowBackgrd | ChangeProperty | FillPolygon |
| CreateOpenGLContext | SetDoubleBuffer | SetWindowBackgrdPix | DrawLine | QueryPointer |
| DeleteOpenGLContext | SetDoubleBufferOFF | CreateWindow | ClearArea | SetForeground |
| DrawBox | SetDoubleBufferON | OpenDisplay | CheckEvent | SetClipRectangles |
| DrawCellArray | SetDrawMode | CloseDisplay | SendEvent | Update |
| DrawFillArea | SetFillColor | GetDisplay | WMDeleteNotify | CreateRegion |
| DrawLine | SetFillStyle | GetVisual | SetKeyAutoRepeat | DestroyRegion |
| DrawPolyLine | SetLineColor | GetScreen | GrabKey | UnionRectWithRegion |
| DrawPolyMarker | SetLineType | GetDepth | GrabButton | PolygonRegion |
| DrawText | SetLineStyle | GetColormap | GrabPointer | UnionRegion |
| ExecCommand | SetLineWidth | InternAtom | SetWindowName | IntersectRegion |
| GetCharacterUp | SetMarkerColor | GetDefaultRootWindow | GetWinName | SubtractRegion |
| GetDrawMode | SetMarkerSize | GetParent | SetIconPixmap | XorRegion |
| GetDoubleBuffer | SetMarkerStyle | LoadQueryFont | SetClassHints | EmptyRegion |
| GetGeometry | SetOpacity | GetFontHandle | SetMWMHints | PointInRegion |
| DisplayName | SetRGB | DeleteFont | SetWMPosition | EqualRegion |
| GetNativeEvent | SetTextAlign | CreateGC | SetWMSize | GetRegionBox |
| GetPixel | SetTextColor | ChangeGC | SetWMSizeHints | ListFonts |
| GetPlanes | SetTextFont | CopyGC | SetWMState | FreeFontNames |
| GetRGB | SetTextFont | DeleteGC | SetWMTransientHint | CreateImage |
| GetTextExtent | SetTextMagnitude | CreateCursor | DrawString | GetImageSize |
| GetTextMagnitude | SetTextSize | SetCursor | TextWidth | PutPixel |
| GetWindowID | UpdateWindow | CreatePixmap | GetFontProperties | PutImage |
| HasTTFonts | Warp | CreatePixmap | GetGCValues | DeleteImage |
| InitWindow | WriteGIF | CreateBitmap | GetFontStruct | GetColorBits |
| AddWindow | WritePixmap | DeletePixmap | FreeFontStruct | IsCmdThread |
| RemoveWindow | GetCurrentWindow | CreatePictureFromFile | MapWindow | Instance |
| MoveWindow | GetWindowAttributes | CreatePictureFromData | KeysymToKeycode | Class |
| OpenPixmap | MapWindow | CreatePixmapFromData | FillRectangle | Class_Name |
| QueryPointer | MapSubwindows | ReadPictureDataFromFile | DrawRectangle | IsA |
| ReadGIF | MapRaised | DeletePictureData | DrawSegments | ShowMembers |
| RequestLocator | UnmapWindow | SetDashes | SelectInput | Streamer |
| RequestString | DestroyWindow | ParseColor | GetInputFocus | StreamerNVirtual |
| RescaleWindow | DestroySubwindows | AllocColor | SetInputFocus | |

## TAttLine

| | | | |
|---|---|---|---|
| fLineColor | fLineStyle | fLineWidth | fgIsA |

| | | | | |
|---|---|---|---|---|
| @~TAttLine | GetLineColor | SaveLineAttributes | Class | StreamerNVirtual |
| TAttLine | GetLineStyle | SetLineAttributes | Class_Name | |
| TAttLine | GetLineWidth | SetLineColor | IsA | |
| Copy | Modify | SetLineStyle | ShowMembers | |
| DistancetoLine | ResetAttLine | SetLineWidth | Streamer | |