TObject

Data members:
fUniqueID, fBits, fgDtorOnly, fgObjectStat, kCanDelete, kMustCleanup, kObjInCanvas, kIsReferenced, kHasUUID, kCannotPick, kNoContextMenu, kInvalidObject, kIsOnHeap, kNotDeleted, kZombie, kBitMask, kSingleKey, kOverwrite, kWriteDelete, fgIsA

Methods:
@~TObject, MakeZombie, DoError, TObject, TObject, operator=, AppendPad, Browse, ClassName, Clear, Clone, Compare, Copy, Delete, DistancetoPrimitive, Draw, DrawClass, DrawClone, Dump, Execute, Execute, ExecuteEvent, FindObject, FindObject, GetDrawOption, GetUniqueID, GetName, GetIconName, GetOption, GetObjectInfo, GetTitle, HandleTimer, Hash, InheritsFrom, InheritsFrom, Inspect, IsFolder, IsEqual, IsSortable, IsOnHeap, IsZombie, Notify, Is, Paint, Pop, Print, Read, RecursiveRemove, SavePrimitive, SetDrawOption, SetUniqueID, UseCurrentStyle, Write, Write, operator new, operator new@[@], operator new, operator new@[@], operator delete, operator delete@[@], operator delete, operator delete@[@], SetBit, SetBit, ResetBit, TestBit, TestBits, InvertBit, Info, Warning, Error, SysError, Fatal, AbstractMethod, MayNotUse, GetDtorOnly, SetDtorOnly, GetObjectStat, SetObjectStat, Class, Class_Name, IsA, ShowMembers

TNamed

Data members:
fName, fTitle, fgIsA

Methods:
@~TNamed, TNamed, TNamed, TNamed, TNamed, operator=, Clear, Clone, Compare, Copy, FillBuffer, GetName, GetTitle, Hash, IsSortable, SetName, SetNameTitle, SetTitle, Is, Print, Sizeof, Class, Class_Name, IsA, ShowMembers

TSocket

Data members:
kRead, kWrite, kSOCKD, kROOTD, kPROOFD, fAddress, fBytesRecv, fBytesSent, fCompress, fLocalAddress, fRemoteProtocol, fSecContext, fService, fServType, fSocket, fTcpWindowSize, fUrl, fgBytesRecv, fgBytesSent, fgIsA

Methods:
@~TSocket, TSocket, Authenticate, SetDescriptor, operator=, GetOption, RecvHostAuth, SecureRecv, SecureSend, SendHostAuth, TSocket, TSocket, TSocket, TSocket, TSocket, TSocket, Close, GetDescriptor, GetInetAddress, GetLocalInetAddress, GetPort, GetService, GetServType, GetLocalPort, GetBytesSent, GetBytesRecv, GetCompressionLevel, GetErrorCode, GetOption, GetRemoteProtocol, GetSecContext, GetTcpWindowSize, GetUrl, IsAuthenticated, IsValid, Recv, Recv, Recv, Recv, RecvRaw, Select, Send, Send, Send, Send, SendObject, SendRaw, SetCompressionLevel, SetOption, SetRemoteProtocol, SetSecContext, SetService, SetUrl, GetSocketBytesSent, GetSocketBytesRecv, CreateAuthSocket, CreateAuthSocket, Class, Class_Name, IsA, ShowMembers

TServerSocket

Data members:
fSecContexts, fgSrvAuthHook, fgSrvAuthClupHook, fgAcceptOpt, kDefaultBacklog, fgIsA

Methods:
@~TServerSocket, TServerSocket, TServerSocket, operator=, Authenticate, TServerSocket, TServerSocket, Accept, GetLocalInetAddress, GetLocalPort, Send, Send, Send, Send, SendObject, SendRaw, Recv, Recv, Recv, Recv, RecvRaw, GetAcceptOptions, SetAcceptOptions, ShowAcceptOptions, Class, Class_Name, IsA, ShowMembers