

PICKLED PAPAYA

Introduction

This pickle is more like a chutney since it is prepared by adding sugar, vinegar and salt to the fruits, followed by boiling which reduces the water content and increases the total soluble solids. The final product is a thick, slightly acidic spicy fruit preserve. Green papaya is required to make the pickle. The time of harvest of green papaya is crucial to the success of the pickle. It should be green and very firm and harvested before the fruit begins to ripen. Once the papaya starts to ripen the acidity decreases and the flesh becomes too soft. However, if it is harvested too early the pickle will have a bitter milky flavour. The yield of usable fruit from whole green papaya is approximately 70%.

Preservation principles

The acetic acid (vinegar) stops the pickle deteriorating once the jar has been opened. The amount of acetic acid required in the recipe can be calculated using the following formula, known as the preservation index. Acetic acid is used instead of vinegar because it is much cheaper.

 $\frac{\text{Total acidity x } 100}{(100 - \text{total solids})}$ = preservation index (should be no less than 3.6%)

Reference: Pearson (1976). The Chemical Analysis of Foods 7th edition Churchill Livingstone.

When making vinegar-based chutneys and pickles, it is essential that the preservation index is above 3.6. This helps to ensure that there is the correct balance of acidity and total solids (sugars) to preserve the pickle and give it a reasonable shelf life. However, the formula does not work for pickles with a sugar content above 55% total solids. For this recipe the total solids are approximately 60% so the formula cannot be applied. Pickles with a higher sugar content produce a sweeter product than those that have a higher vinegar content. The sugar has a preserving effect as in a jam.

The product can he packed in glass jars or polythene bags (at least 100 micron, preferably a thicker gauge) for smaller quantities. Polythene bags are a cheap form of packaging that can be made into various sizes, which is useful for marketing to different consumer groups. However, polythene is not a very good barrier for containing aromas, which can attract insects which will eat through the polythene and spoil the product.

This technical brief should be read together with the brief 'Pickles and chutneys' which gives an overview of the process and the quality assurance points. As with all products, it is important to carry out a market and technical feasibility study before starting production.

Practical Action, The Schumacher Centre for Technology and Development, Bourton on Dunsmore, Rugby, Warwickshire, CV23 9QZ, UK

T +44 (0)1926 634400 | F +44 (0)1926 634401 | E infoserv@practicalaction.org.uk | W www.practicalaction.org



Recipe

54%	27kg
36%	18kg
3%	1.5kg
0.5%	250g
0.3%	150g
0.3%	150g
0.4%	200g
0.8%	400g
0.1 %	50g
2%	1kg
0.3%	150g
2%	1kg
	36% 3% 0.5% 0.3% 0.4% 0.8% 0.1 % 2% 0.3%

If limes are not available when the papaya is in season, the juice can be extracted and stored in bulk until it is required. Sulphur dioxide or benzoic acid (1000-1500ppm) is added to preserve it. Garlic can be ground in bulk and kept for long periods by mixing it with the salt which is required in the recipe.

To make 100 x 1lb (450g) jars of papaya pickle requires approximately 18kg of sugar and 27kg of green papaya.

Method

Wash the whole papaya in clean water and discard any which is bad.

Remove the skin with a stainless steel knife. Cut the fruit into longitudinal segments and remove the seeds, then cut the segments into very small pieces (5mm cubes). This can be done by hand or more quickly using a fruit dicing machine such as the Kenwood dicer.

Stainless steel equipment is preferred for fruit as it does not stain the flesh and does not react with the acidity of the juice. If stainless steel is not available, make sure the knives and spoons are not rusted.

Mix the papaya pieces with the sugar in a stainless steel saucepan. Leave the mixture for 10 minutes so the sugar draws out the water from the fruit pieces. Boil the mixture for 10 minutes to evaporate off some of the water from the papaya, and soften the fruit pieces. Add all the dry spices to the saucepan and continue cooking. Add the lime juice and acetic acid at the end of the cooking process. This prevents the loss of volatiles, which is very important in the case of the acetic acid.

The whole batch should be boiled down to 90% of the initial total weight of the ingredients in the saucepan. To do this, weigh the saucepan before starting to boil and at intervals until it is 90% of the original weight. With practice, an experienced processor will know how long to boil for and the desired consistency of the pickle. This will ensure that the pickle will have the correct consistency. Boiling down to the same finishing weight means that the same number of jars will be filled each time and produce a standard product.


Hot fill the pickle into jars which have been cleaned and steam sterilised. Make sure the jars are still hot so they do not crack when they are filled. The lip of the jar should be clean and dry (wipe with clean tissue paper or steam) before placing the lid on it. Polythene bags do not need to be steamed inside as they are usually clean. Do not use recycled polythene bags. The pickle should not be hotter than 90°C as this will soften the polythene. When filling the bags make sure that the pickle does not come into contact with the top of the bag otherwise it will not heat seal. The simplest way to do this is to use a wide neck funnel (which the pickle can be pushed down through) which slips inside a tube placed in the opening of the bag. The hot filling of the pickle into hermetically sealed jars will preserve the product until the jar is opened.



Practical Action Pickled Papaya

Equipment list

Jars or polythene bags (at least 100 micron), and labels Omnia lids or heat sealer Cooking facilities, gas ring, electric ring, etc Stainless steel saucepan Thermometer in protective jacket Stainless steel cutting knife Wooden spoon for stirring Steam generator (if jars are used) Cutting board Scales Dicing machine Funnel Measuring cylinder



Note: This is a selective list of suppliers and does not imply endorsement by Practical Action

Cutting and slicing equipment

A range of manual and powered cutting and slicing machinery is available.

Eastend Engineering Company

173/1 Gopal Lal Thakur Road Calcutta 700 035 India

Tel: +91 33 2553 6397

Gardners Corporation

158 Golf Links New Delhi 110003

Tel: +91 11 2334 4287/2336 3640

Fax: +91 11 2371 7179

Narangs Corporation

P-25 Connaught Place New Delhi 110001

Tel: +91 11 2336 3547 Fax: +91 11 2374 6705

Kenwood Limited

New Lane Havant Hampshire P09 2NH United Kingdom

Tel: +44 (0) 23 9247 6000 Fax: +44 (0) 23 9239 2400 Website: http://www.kenwood.co.uk

Weighing machines

It is important to have accurate weighing machines. Quite often more than one machine is required - -a large one to weigh the fruit and a small one for weighing out the spices.

Fischer Scientific

Bishop Meadow Road Loughborough LE11 5RG UK

Tel: +44 1509 231166 Fax: +44 1509 231893 Email: fisher@fisher.co.uk Web: www.fisher.co.uk

Alvan Blanch

UK (see above)

Gardners Corporation

India (see above)

Essae-Teraoka Ltd

377/22 6th Cross Wilson Garden Bangalore 560027 India

Tel: =91 80 2216185/2241165

Narangs Corporation

India (see above)



For boiling

Boiling pans should be made of aluminium, enamelled metal or stainless steel. For larger quantities it is necessary to buy equipment which does not cause burning or sticking of the product to the bottom of the pan. Stainless steel steam jacketed kettles, which are double walled pans are suitable for boiling large quantities and are available in a range of sizes (from 5 to 500 litres).

Gardners Corporation

India (See above)

HRS Process Systems Pvt Ltd

Asia Division, Praj House, Bavdhan, Pune Maharashtra 411021 India

Tel: +91 20- 22951511 Fax: +91 20- 22951718 Website: www.hrsasia.co.in

Raylons Metal Works

Kondivita Lane J. B. Nagar Post Office Post Box No. 17426 Andheri (E) Andheri - Kurla Road, Mumbai - 400 059 India

Tel: +91 22 26323288 / 6325932

Sri Rajalakshmi Commercial Kitchen Equipment

No.57, (old No. 30/1) Silver Jubilee Park Road

Bangalore - 560 002 India

Tel: +91 (0)812 2222 1054/223 9738

Fax: +91 (0)812 2222 2047

United Engineering (Eastern) Corporation

Shantiniketan Site No.2 & 3 (10th Floor) 8 Camac Street Kolkata, West Bengal 700017 India

Tel: +91 33-22823914, 22820157

Fax: +91 33-22823742

Bottle filling and packaging equipment

H Erben Limited

Lady Lane Hadleigh Suffolk IP7 6AS United Kingdom

Tel: +44 (0)1473 823011 Fax: +44 (0)1473 828252 Website: http://www.erben.co.uk

Alvan Blanch

United Kingdom (See above)

Israel Newton Limited

Summerley Works All Alone Road Bradford West Yorkshire BD10 8TT United Kingdom

Tel: +44 (0)1274 612059 Fax:+44 (0)1274 612059

APV Baker Limited

Manor Drive Paston Parkway Peterborough Cambridgeshire PE4 7AP United Kingdom

Tel: +44 (0)1733 283000 Fax: +44 (0)1733 283005

T Giusti and Son Limited

Rixon Road, Finedon Road Industrial Estate Wellingborough, Northamptonshire NN8 4BA United Kingdom

Tel: + 44 (0)1933 229933 Fax: + 44 (0)1933 272363 Website: <u>www.giusti.co.uk</u>





Orbit Equipments Pvt Ltd

175 - B, Plassy Lane Bowenpally Secunderabad - 500011, Andhra Pradesh India

Tel: +91 40 32504222 Fax: +91 40 27742638

Website: http://www.orbitequipments.com

Sussex and Berkshire Machinery Company PLC

Blacknest Alton, Hants GU34 4PX United Kingdom

Tel: + 44 (0)1420 22669 Fax: + 44 (0)1420 22687 E-mail: technical@sabplc.uk Website: http://www.sabplc.co.uk/

Acufil Machines

S. F. No. 120/2, Kalapatty Post Office Coimbatore - 641 035 Tamil Nadu. India

Tel: +91 422 2666108/2669909

Fax: +91 422 2666255

Email: acufilmachines@yahoo.co.in,

acufilmachines@hotmail.com

http://www.indiamart.com/acufilmachines/#products

Autopack Machines Pvt Ltd

101-C Poonam Cambers A Wing, 1st Floor Dr Annie Besant Road, Worli Mumbai 400018 India

Tel: +91 22 2493 4406/2497 4800/2492 4806

Fax: +91 22 2496 4926

E-mail: <u>autopack@bom3.vsml.net.in</u> <u>www.autopackmachines.com</u>

Bombay Engineering Industry

R NO 6 (Extn) Sevantibai Bhavan Chimatpada Marol Naka Andheri (East) Mumbai 400059 India

Tel: +91 22 2836 9368/2821 5795

Fax: +91 22 2413 5828

MMM Buxabhoy & Co

140 Sarang Street 1st Floor, Near Crawford Market Mumbai, India

Tel: +91 22 2344 2902 Fax: +91 22 2345 2532

yusufs@vsnl.com; mmmb@vsnl.com;

yusuf@mmmb.in

Gardners Corporation

India (see above)

Pharmaco Machines

Unit No. 4, S.No.25 A Opp Savali Dhaba, Nr.Indo-Max Nanded Phata, Off Sinhagad Rd. Pune – 411041, India

Tel: +91 20 65706009 Fax: +91 20 24393377

Rank and Company

A-p6/3, Wazirpur Industrial Estate

Delhi - 110 052

India

Tel: +91 11 27376101 Fax: +91 11 7234126 Rank@poboxes.com

Banyong Engineering

94 Moo 4 Sukhaphibaon No 2 Rd Industrial Estate Bangchan

Bankapi Thailand

Tel: +66 2 5179215-9

Alfa Technology Transfer Centre

301 Cach Mang Thang 8 Tan Binh District Ho Chi Minh City Vietnam

Tel: +84 8 9700868 Fax: +84 8 8640252

Technology and Equipment Development Centre (LIDUTA)

360 Bis Ben Van Don St District 4 Ho Chi Minh City

Vietnam

Tel: +84 8 9400906 Fax: +84 8 9400906

Mark Industries (Pvt) Ltd

Bangladesh (See above)





Gurdeep Packaging Machines

Harichand Mill compound LBS Marg, Vikhroli Mumbai 400 079

India

Tel: +91 22 2578 3521/577 5846/579 5982

Fax: +91 22 2577 2846

Eastend Engineering Company

India (See above)

Narangs Corporation

India (see above)

Refractometers and pH meters

The refractometer is used to measure the sugar content. A pH meter is used to measure the

acidity.

Bellingham + Stanley Ltd.

Longfield Road, North Farm Industrial Estate

Tunbridge Wells, Kent TN2 3EY

United Kingdom

Tel: +44 1892 500400 Fax: +44 1892 543115 E-mail: sales@bs-ltd.com

Website: http://www.bs-ltd.com

Fisher Scientific UK Ltd

UK (see above)

References and further reading

Practical Action technical briefs:

Food labelling

Pickled Cucumbers

Pickled Dry Salted Lime

Pickled Cabbage (Kimchi)

Pickles of Bangladesh, ITDG Publishing 1994

Pickled Fruits

Pickles and chutneys

John Kojo Arthur

University of Science and Technology

Ghana

Alvan Blanch

UK (see above)

International Ripening Company

1185 Pnieridge Road

Norfoplk

Virginia 23502-2095

USA

Tel: +1 757 855 3094

Fax: +1 757 855 4155 Email: info@QAsupplies.com

Web: www.gasupplies.com

Gardners Corporation

India (see above)

Preservation of Fruit and Vegetables: Agrodok 3, Agromisa 1997





Useful organisations and contacts

Agromisa

Postbus 41 6700 AA Wageningen Netherlands

Tel: +31 (0)317 412217 Fax: +31 (0)317 419178 E-mail: agromisa@wxs.nl

Web: http://www.agralin.nl/agromisa

Agromisa is a Dutch non-profit organisation affiliated with the Agricultural University of Wageningen in the Netherlands. Agromisa provides information and advice on small-scale sustainable agriculture and related topics in order to support and strengthen self-reliance of the rural populations in the South.

Food and Agriculture Organization of the United Nations Viale Terme di Caracalla 00100 Rome Italy http://www.fao.org/

Information network on post harvest operations (INPhO). Website on post harvest information includes a virtual library, post harvest compendium and decision support tools to assist entrepreneurs in establishing agro enterprises

(www.fao.org/ag/ags/subjects/en/harves t/inpho.html) Inpho@fao.org



This document was produced by Dr. S Azam Ali for Practical Action March 2009. Dr. S Azam-Ali is a consultant in food processing and nutrition with over 15 years experience of working with small-scale processors in developing countries.

Practical Action

The Schumacher Centre for Technology and Development

Bourton-on-Dunsmore

Rugby, Warwickshire, CV23 9QZ

United Kingdom

Tel: +44 (0)1926 634400 Fax: +44 (0)1926 634401

E-mail: inforserv@practicalaction.org.uk

Website: http://practicalaction.org/practicalanswers/

Practical Action is a development charity with a difference. We know the simplest ideas can have the most profound, life-changing effect on poor people across the world. For over 40 years, we have been working closely with some of the world's poorest people - using simple technology to fight poverty and transform their lives for the better. We currently work in 15 countries in Africa, South Asia and Latin America.

