IBM posts leadership SPEC CPU2000 score for AMD Opteron processor-based blade server

March 7, 2006 ... The AMD Opteron LS20 for the IBM® BladeCenter® is a dual-processor blade server that features AMD Opteron processors running at speeds of 2.4, 2.6, or 2.8 GHz single-core, and 2.0 or 2.2 GHz dual-core \mid all with 1 MB L2 cache per core. Now the LS20 is available with the dual-core AMD Opteron 280 processor running at 2.4GHz. (1)

The LS20, configured with the AMD Opteron 280 (2.4GHz dual-core) processor with 1MB L2 cache per core, has delivered a leadership SPECint_rate2000 score for a blade server. The other scores for the LS20, which are summarized in the table, demonstrate competitive blade performance.

Benchmark	LS20 2.4GHz/1MB (Dual-Core) Scores
SPECint	1,688
SPECint_rate2000 (2 Processors)	75.25
SPECfp	2,012
SPECfp_rate2000 (2 Processors)	73.4

The LS20 blade achieved these results using 64-bit SUSE Linux Enterprise Server 9 SP2.

Results are current as of March 7, 2006. The LS20 blade's scores have been submitted to SPEC for review and will be posted on their Web site upon successful completion of the review. For all SPEC CPU2000 benchmark results, visit www.spec.org.

(1) Planned availability is March 17, 2006.

IBM and BladeCenter are registered trademarks of International Business Machines Corporation. AMD and Opteron are trademarks or registered trademarks of Advanced Micro Devices, Inc. Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both. Microsoft is a registered trademark of Microsoft Corporation in the United States, other countries, or both. SPEC, SPECfp, and SPECint are registered trademarks of the Standard Performance Evaluation Corporation.

All other company/product names and service marks may be trademarks or registered trademarks of their respective companies.