
Enabling/Disabling Autostart

The server created for you by the Infoprint Installer will start automatically when the system reboots. You may enable or disable the automatic starting of any Infoprint servers present on your AIX system.

Enabling Autostart

To enable the automatic starting of a server, do the following:

1. Access the **Infoprint Utilities** main menu by:
 - If you do not have an **Infoprint Manager** icon on your front panel, open the **Infoprint** folder in the Application Manager and double click on the **Infoprint SMIT** icon. Then click **Infoprint Utilities**.
 - If you do have an **Infoprint Manager** icon on your front panel, open Infoprint Manager's popup menu and click on the **Infoprint SMIT** icon. Then click **Infoprint Utilities**.
2. Click **Enable/Disable Autostart**.
3. Select **on** in response to the question, "Do you wish to turn autostart on or off?"
4. Click **List** and select the Infoprint server you wish to start automatically on reboot.
5. Enter the port number which this server uses for communication with other programs. (Leave blank to use the default port number.)
6. Click **List** and select the locale (language environment) in which you want the server to run.
7. Click **OK**.

Disabling Autostart

To disable the automatic starting of a server, do the following:

1. Access the **Infoprint Utilities** main menu by:
 - If you do not have an **Infoprint Manager** icon on your front panel, open the **Infoprint** folder in the Application Manager and double click on the **Infoprint SMIT** icon. Then click **Infoprint Utilities**.
 - If you do have an **Infoprint Manager** icon on your front panel, open Infoprint Manager's popup menu and click on the **Infoprint SMIT** icon. Then click **Infoprint Utilities**.
2. Click **Enable/Disable Autostart**.
3. Select **off** in response to the question, "Do you wish to turn autostart on or off?"
4. If prompted, select the server you want to disable for automatic starting.