IBM Infoprint 70 Plus





Highlights

- High quality, high volume, cutsheet printer with compact footprint
- Advanced IBM controller and imaging technology
- Remote management, including real-time e-mail and pager alerts
- Flexible finishing capabilities
- Standard AFP/IPDS support with optional support for Adobe PostScript and PCL
- Automated conversion of 240, 300, or 600 dpi AFP/IPDS applications

The IBM Infoprint® 70 Plus provides fast, high-quality, Internet-ready output capabilities that enable you to keep pace in an e-business world. With the Infoprint 70 Plus you can produce up to 600,000 impressions per month¹, and even complex jobs can run at or near the rated speed of 70 impressions per minute.

State-of-the-art technologies

Advanced controller technology ensures native support for IBM Advanced Function Presentation[™] (AFP[™]) and Intelligent Printer Data Stream[™] (IPDS[™]). Page level error detection and recovery capabilities help prevent job resends, minimize human intervention and streamline printing.

Lower operational costs

Using the Infoprint 70 Plus' internal Web pages and Network Printer Manager (NPM) software, network administrators can easily set up, configure and manage the printer. E-mail and pager alerts can be sent when the printer needs attention, maximizing up-time and reducing overall resource consumption and therefore total cost of ownership.

The base maintenance plan² for the Infoprint 70 Plus now includes toner, drum units and fuser cleaning webs, thereby minimizing operating costs and impact on procurement.

Ready for e-business

Through standard Internet Printing Protocol (IPP), print jobs can be submitted over the Internet. In addition, the printer's resident Web server enables pull printing, where users provide the Web address of PDF, PCL or PostScript[®] files, and the printer will access and print them. This saves download and file-print submission time.



Maximize flexibility

An input capacity of up to 6,150 sheets through five trays provides the ability to choose from different media sizes, weights and stocks-including large paper sizes and heavier paper weightswithout delay.

For more information

To learn more, contact your local IBM Printing Systems representative or call (800) 358-6661. You may also visit ibm.com/printers.



© International Business Machines Corporation 2002

IBM Printing Systems 6300 Diagonal Highway Boulder, Colorado 80301

Printed in the United States of America. 09-02 All Rights Reserved

The following terms are trademarks of IBM Corporation in the United States and/or other countries: Advanced Function Presentation, AFP, AS/400, the e-business logo, IBM, Infoprint, Intelligent Printer Data Stream, IPDS, iSeries, Netfinity, pSeries, RS/6000, S/390, xSeries and zSeries.

Adobe, PostScript and PostScript Level 3 are trademarks or registered trademarks of Adobe Systems Incorporated.

ENERGY STAR is a U.S. registered mark. The ENERGY STAR Emblem does not represent EPA endorsement of any product or service.

Other company, product and service names may be trademarks or service marks of others.

References in this publication to IBM products or services do not imply that IBM intends to make them available outside the United States.

IBM hardware products are manufactured from new parts, or new and used parts. Regardless, our warranty terms apply.

Visit the IBM Printing Systems home page at ibm.com/printers

The IBM home page can be found on the Internet at ibm.com

Printed on an IBM Infoprint Color System Full-Color Digital Printer.

IBM Infoprint 70 Plus at a glance For expanded specifications visit ibm.com /printers/70plus	
Print Speed/Usage ¹	Up to 70 impressions per minute/up to 600,000 impressions per month
Resolution	600 dpi (printer will convert 240/300 dpi AFP/IPDS to 600 dpi)
Processor/Memory	400MHz RISC/128 MB standard (256 MB maximum)
Paper Handling Standard input capacity: Optional input capacity: Standard output capacity:	 —Two 500 sheet trays —One 2000 sheet tray —One 150 sheet auxiliary tray —3000-sheet high capacity feeder (A4 or letter size only) —One 200-sheet top stacker; one 2000-sheet side stacker with up to 50-sheet stapling capability
Media Sizes/Types/Weights	A5 (148 x 210 mm) through 12"x 18" (304.8 x 457.2 mm) ³ Copier/xerographic papers and labels: 16 to 53 lb., 110 lb. index (60–200 gsm)
Datastream Support	Standard: IPDS Optional: Adobe® PostScript 3™, PCL5e, PCL6, PDF
Printer Attachments Standard: Optional NIC:	(One Required) —None —Fast Ethernet 10/100 Base TX (Auto Switching) or Token-Ring (TCP/IP only)
Server Platform Support	zSeries (S/390 [®]), iSeries (AS/400 [®]), pSeries (RS/6000 [®]) servers and workstations, xSeries (Netfinity [®]) servers, PC servers and IBM compatibles
Physical Characteristics Base model: Fully configured:	Depth Height Width Weight 26.5"/672 mm 40.7"/1,035 mm 59.0"/1,499 mm 521 lb./235 kg 26.5"/672 mm 40.7"/1,035 mm 73.7"/1,873 mm 563 lb./254 kg
Power Requirements	Voltage: 200–240V, 50/60 Hz
Environmental Conditions	 —Operating Temperature: 50° to 90° F (10° to 32° C) —Altitude: 0–7,000 feet (0–2,133 meters) —Relative Humidity: 20% to 80% RH; 26° C max. wet bulb —Acoustics: 63 dBA (operating), 53 dBA (standby)

¹IBM does not recommend reaching this monthly maximum on a consistent basis.

²Varies by country; please contact your IBM sales representative for details.

³Letter/A4 (long edge feed) or smaller paper sizes run at up to 70 ipm. Other paper sizes run at up to 35 ipm. * For more information on the implications of the euro, visit the IBM euro Web site at ibm.com/euro.









B



