

Enabling JAWS for IBM SPSS Modeler Text Analytics (Windows Only)

IBM® SPSS® Modeler Text Analytics offers accessibility for all users, as well as specific support for users with visual and other functional impairments. This document describes how to enable JAWS® screen-reading software to work with this product.

To enable JAWS on Microsoft Windows, you need to:

- ▶ Enable the Java Access Bridge.

Enabling the Java Access Bridge

To enable the Java Access Bridge, you need to:

- Set the location of the Java Access Bridge.
- Replace the default Java *accessibility.properties* file.

Setting the Location of the Java Access Bridge

- ▶ From the Start menu, open the Control Panel.
- ▶ Double-click the System icon.
- ▶ In the System Properties dialog box, click the Advanced tab.
- ▶ Click Environment Variables.
- ▶ In the Environment Variables dialog box, scroll through the System Variables list and select the Path variable.
- ▶ Click Edit.
- ▶ At the beginning of the Variable Value text box, type the path to the IBM® SPSS® Modeler Text Analytics installation folder followed by \JRE\bin;. For example, if IBM SPSS Modeler Text Analytics is installed in *C:\Program Files\IBM\SPSS\Modeler\15*, type:

C:\Program Files\IBM\SPSS\Modeler\15\JRE\bin;

- ▶ Click OK.

Replacing the Java accessibility.properties File

- ▶ Go to the \JRE\lib folder in the IBM SPSS Modeler Text Analytics installation folder. For example, if IBM SPSS Modeler Text Analytics is installed in the folder *C:\Program Files\IBM\SPSS\Modeler\15*, go to *C:\Program Files\IBM\SPSS\Modeler\15\JRE\lib*.
- ▶ Rename the *accessibility.properties* file or move it to a different folder.
- ▶ Go to the Accessibility folder on the CD-ROM and copy the *accessibility.properties* file.

- ▶ Paste the file into the `\JRE\lib` folder in the IBM SPSS Modeler Text Analytics installation folder.

The Java Access Bridge will load the next time you launch IBM SPSS Modeler Text Analytics .