



# **SupportPac LA71: IBM WebSphere Operational Decision Management Integration for WebSphere Process Server**

## **Getting started with IBM Business Process Manager**

### **Task 3 - Business Process Author re-uses an HTDS Managed Decision as part of a BPMN Process**

# Copyright

## Copyright notice

© Copyright IBM Corp. 1987, 2012

US Government Users Restricted Rights - Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

## Trademarks

IBM, the IBM logo, ibm.com, WebSphere, and ILOG are trademarks or registered trademarks of International Business Machines Corp., in many jurisdictions worldwide.

Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at *Copyright and trademark information*.

Adobe, the Adobe logo, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

Java and all Java-based trademarks and logos are trademarks of Sun Microsystems, Inc. in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.

---

## Overview

In this task, the Business Process Author uses the HTDS Managed Decision service as part of their process. This allows them to run a process using the rules in the managed decision rather defining their own embedded rules. In this task you will use the Eligibility Managed Decision Service.

Readers who want to skip the exercise should import the solution as a Snapshot from **[SupportPac LA71 Path]\BPMTutorial\task3\Insurance\_Sample\_-\_HTDS\_Reuse - Completed.twx** and continue at Step 6 to test the HTDS service in the process.

### Step 1. Create a Process Application to host the HTDS Decision Service

This task starts by creating a new Process Application to host the HTDS Decision Service.


Open Process Designer and login.

For **User Name** type **admin**


For **Password** type **admin**.



Click the Process Center icon.



Click Create New Process App.




Fill in the Process App details as shown below.

For **Process App Name** type **Insurance Sample – HTDS Reuse**

For the **Acronym** type **LA71TT3**


**Note:** If you have already imported the completed Task 3 you will have to either rename the imported Process App or give this one a different acronym.

For the **Description** provide details as shown below.



Click **Create**.

In the list of Process Apps, in the entry for **LA71TT3** click the **Open in Designer** link.




Process Designer opens on the newly created Process App.




## Step 2. Register the Rule Execution Server

In order to access the rule applications you must register the rule application server hosting your HTDS Managed Decisions.

Select **Process App Settings** Screen.



In the **Servers** Screen click the **Add** button  
 Set the **Name** to **BPMRES**.  
 Set the **Type** to **ILOG Rules Server** by selecting from the pulldown list.  
 Set the **Default URL** to <http://localhost:9080> or the port on which the Rule Execution Server is available.



Save your changes


### Step 3. Create the Decision Service for the Eligibility Managed Decision.

In the Decisions navigator click the + sign to create a new Decision Service.



Click **Decision Service**.

In the Name field type **Eligibility\_ManagedDecision** and click **Finish**.



Open the Diagram tab of the **Eligibility\_ManagedDecision** Decision Service.  
 Drag a **JRules Decision Service** onto the Canvas and rename it **Eligibility**.

Select the **Sequence Flow** icon.




Connect the **Start** node to the **Eligibility** node.  
Connect the **Eligibility** node to the **End** node.  
Reselect the **Selection Flow** icon,



Click in the canvas – right click and select **Tidy Layout**.

Save your work.

The new decision service should look as below.



#### Step 4. Bind the Decision Services to the Hosted Transparent Decision Services from WODM.

Open the **Eligibility\_ManagedDecision** Diagram.  
Select the **Eligibility** node and in the **Properties** panel select the **Implementation** Tab.  
In the **Discovery** panel you define the the Rule Execution Server hosting the HTDS Decisions.  
In the **Server** Field select the **BPMRES** server you defined earlier.  
In **Username** field type **resAdmin**.  
In the **Password** field type **resAdmin**.

Step	Discovery
Implementation	Server: BPMRES
Data Mapping	SOAP Port: 8880
Pre & Post	Username: resAdmin
	Password: *****

Connect

Click **Connect**.

In the **Rules** Panel the available Rule Apps and Rules are displayed.

From the **Rule App** pulldown select **InsuranceSampleRuleApp**.

From the **Ruleset** pulldown select **Eligibility**.

Leave the **Version** fields at **Latest**. This means that the most recent versions of the managed decisions will always be used.




The screenshot shows a configuration panel for a rule. It has a dropdown menu labeled 'Rule' which is expanded. Below it, there are two rows of configuration. The first row is for 'Rule App', with a dropdown menu showing 'InsuranceSampleRuleApp' and a 'Version' dropdown showing 'Latest'. The second row is for 'Ruleset', with a dropdown menu showing 'Eligibility' and a 'Version' dropdown showing 'Latest'. Below these fields are two buttons: 'View' and 'Generate Types...'.

Now we will import the information models used by the rules.

Click **Generate Types...**

In the screen that results leave all options deselected as we only need the minimum of new types.




The screenshot shows a dialog box titled 'Generate Types Wizard'. The main heading is 'Generating Types' and the instruction is 'Click Next to begin type generation'. There are two checkboxes: 'Generate all types' (unchecked) and 'Generate request/response wrapper types' (unchecked). Below the checkboxes is a list box with the text 'Select operation(s) for which you want types to be generated:' and the list contains 'Eligibility'. At the bottom of the dialog are four buttons: '< Back', 'Next >', 'Finish', and 'Cancel'.

Click **Next >**.

The Mapping Types generation screen shows the types generated and any naming conflicts.

Click **Next >**.

The **Type Generation Summary** screen shows the types generated.



Note:

The duplicated **AutoQuoteRequest** in the [www.ibm.com/rules/decisionsservice/InsuranceSampleRuleApp/Eligibility/param](http://www.ibm.com/rules/decisionsservice/InsuranceSampleRuleApp/Eligibility/param) namespace is mapped to **AutoQuoteRequest\_1**.

The duplicated **EligibilityResponse** in the [www.ibm.com/rules/decisionsservice/InsuranceSampleRuleApp/Eligibility/param](http://www.ibm.com/rules/decisionsservice/InsuranceSampleRuleApp/Eligibility/param) namespace is mapped to **EligibilityResponse\_2**.


Click **Finish** to exit the wizard.



Navigate to the **Data** entry where you will see the list of Business Objects that have been created.

Examine the Business Objects to check that the information model has been correctly retained.

Double Click **AutoQuoteRequest\_1** and examine it in the Business Object Editor.



## Step 5. Mapping decision service variables manually.

Because the HTDS managed decision services use wrapper types, we need to map these HTDS parameters to decision service variables that only use the INSDEMO business objects.

First you need to define the private variables that will be used to invoke the decision service. These variables use the wrapper types from the decision service.

In the Variables Screen click **Add Private**.

In the **Name:** field, type **autoQuoteRequest**.

In the **Variable Type:** field, click **Select...** and select the **AutoQuoteRequest\_1** Business Object.

Select the **Has Default** checkbox.

Browse down to the **NumberOfAccidents** field and set the value to **5**.

The screenshot shows the 'Variables' screen in the IBM Business Architect tool. The window title is 'Eligibility\_ManagedDecision'. The 'Variables' tab is active, showing a tree view on the left with 'autoQuoteRequest (AutoQuoteRequest\_1)' selected. The 'Details' pane on the right shows the following configuration:

- Name:** autoQuoteRequest
- Documentation:** Click [Edit](#) to add or edit text.
- Is List:**
- Variable Type:** AutoQuoteRequest\_1 (with 'Select...' and 'New ...' buttons)
- Default Value:**

The 'Default Value' section contains a table with the following properties and values:


Property	Value
DrivingLicenseNumber	""
FirstDrivingLicenseDt	new TWDate ()
VehicleVandalizedOrStole	false
LicenseSuspendedOrRevoked	false
DUI	false
NumberOfAccidents	5
NumberOfTrafficTicket	0
Vehicle	
Coverage	

In the Variables Screen click **Add Private**.

In the **Name:** field, type **eligibilityResponse**

In the **Variable Type:** field, click **Select...** and select the **EligibilityResponse\_2** Business Object.


Select the **Has Default** checkbox.



In the Variables Screen click **Add Private**.  
 In the **Name:** field, type **decisionID**  
 In the **Variable Type:** field, leave the selection as **String**.  
 Select the **Has Default** checkbox.


Having created the variables these now need to be mapped to the decision service.

Select the **Eligibility** node and open the **Properties** screen.




Select the **Data Mapping** tab.


On the **Input Mapping** panel click the mapping icon associated with the **DecisionID** parameter.




In the pop-up select the **decisionID** private variable that you have just created.




This should then select this variable to be mapped to the parameter.



Repeat this for the **AutoQuoteRequest** and **EligibilityResponse** input parameters.



On the **Output Mapping** panel repeat the steps above to map the output parameters as shown.




You have now mapped the private variables to the ODM HTDS decision service call.


## Step 6. Mapping decision service variables using AutoMapping.

There is an automatic mapping feature provided in Process Designer that can be used as described below. This facility is however not fully functional in BPM 8.0 so readers should use the approach described in step 5. Open the **Eligibility\_ManagedDecision** Diagram. Select the **Eligibility** node and open the **Properties** screen. Select the **Data Mapping** tab.

On the **Input Mapping** panel click the Auto-map icon.




Select all three of the parameters to map.




Click **OK**.

On the **Output Mapping** panel click the Auto-map icon.




Select the remaining two parameters – as all parameters are inout parameters, variables already exist for the rest of the output parameters.



Click **OK**.

Selecting the Variables tab shows all the local variables that have been created from the imported Business Objects.



## Step 7. Creating the Decision inputs and outputs.

Now you need to create the input and output parameters to the **Eligibility\_ManagedDecision** decision service using the shared business objects and map them to the private wrapper variables used to invoke the ODM service..


In the Variables Screen click **Add Input**.

In the **Name:** field, type **AutoQuoteRequest\_In**.

In the **Variable Type:** field, click **Select...** and select the **AutoQuoteRequest** Business Object.


Select the **Has Default** checkbox.

Browse down to the **NumberOfAccidents** field and set the value to **5**.



In the Variables Screen click **Add Output**.  
 In the **Name:** field type **EligibilityResponse\_Out**.  
 In the **Variable Type:** field click **Select...** and select the **EligibilityResponse** Business Object.

Save your work.



Finally you need to map between these input and output parameters and the private variables.


In the Diagram tab select the **Eligibility** Node and in the **Properties** screen select the **Pre & Post** Tab.

In the **Pre-execution Assignments** panel type:

```
tw.local.autoQuoteRequest.AutoQuoteRequest = tw.local.AutoQuoteRequest_In;
```

In the **Post-execution Assignments** panel type:

```
tw.local.EligibilityResponse_Out = tw.local.eligibilityResponse.EligibilityResponse;
```



Save your work and you have now completed the variable mapping.

## Step 8. Test the Decision Service.

You can now test the decision service in isolation.

Open the **Diagram** tab for the **Eligibility\_ManagedDecision** and click the Debug icon.



A browser opens showing the node and variable values.  
Navigate down the variables to check that the NumberOfAccidents field has been correctly set.

**IBM Business Process Manager Service Debug**

**Service** Eligibility\_ManagedDecision  
**Item Type** ILOGConnector  
**Item Name** Eligibility

Namespace: local		
Name	Type	Value
autoQuoteRequest	AutoQuoteRequest_1	<object type="AutoQuoteRequest_1"> <property name="AutoQuoteRequest" type="AutoQuoteRequest"> <property name="Driver" type="Driver"> <property name="NumberOfTrafficTicket" type="Integer" tw-id="id:0">0</property> <property name="NumberOfAccidents" type="Integer">5</property> <property name="DUI" type="Boolean">>false</property> <property name="LicenseSuspendedOrRevoked" type="Boolean">>false</property> <property name="VehicleVandalizedOrStolen" type="Boolean">>false</property>

Click **Step** to invoke the HTDS service.

The browser will be updated to show the result of invoking the HTDS decision service.

**IBM Business Process Manager Service Debug**

**Service** Eligibility\_ManagedDecision  
**Item Type** Exit Point  
**Item Name** End

Namespace: local		
Name	Type	Value
autoQuoteRequest	AutoQuoteRequest_1	<object type="AutoQuoteRequest_1"> <property name="AutoQuoteRequest" type="AutoQuoteRequest">

Scroll down to the **EligibilityResponse\_Out** variable to observe the Rules response.

EligibilityResponse_Out	EligibilityResponse	<pre> &lt;object type="EligibilityResponse"&gt;   &lt;property name="Eligible" type="Boolean"&gt;false&lt;/property&gt;   &lt;property name="MainMessage" type="String"&gt;&lt;del&gt;The driver has had too many accidents&lt;/del&gt;/property&gt;   &lt;property name="ErrorMessages" type="String[]"&gt;     &lt;arrayElement size="1"&gt;       &lt;item type="String"&gt;&lt;/item&gt;     &lt;/arrayElement&gt;   &lt;/property&gt;   &lt;metadata&gt;     &lt;property name="dirty" type="Boolean"&gt;&gt;true&lt;/property&gt;     &lt;property name="shared" type="Boolean"&gt;&gt;false&lt;/property&gt;     &lt;property name="key" /&gt;     &lt;property name="version" /&gt;   &lt;/metadata&gt; &lt;/object&gt; </pre>
-------------------------	---------------------	--

You have now successfully tested the decision service.

### Step 9. Using the Managed Decision Service in a Process.


This final steps are optional and involves developing a Human process that invokes the managed decision.

Create a new Human Interface




Give it the name **Insurance Eligibility**.

Create the following structure in the canvas. Note that you cannot yet connect the Eligibility Nested service to the Coach.




Select the **Eligibility** nested Service and navigate to the **Properties** View and **Implementation** tab.


Click the **Select** Button and select the **Eligibility\_ManagedDecision** in the Services section.





Navigate to the **Data Mapping** tab and click each of the Automap icons to generate local variables for the input and output parameters of the service.




Initialize the variables that have been created with default values



Create the two Coaches mapping the fields to the private Variables generated by the mapping.



Connect up the final wire and establish the gateway conditions.



Save your work.

### Step 10. Running the Managed Decision Service in a Process.

Run the **Insurance Eligibility** Human Service.  
 The default values are shown initially.

#### Auto Quote Request

##### Driver

First Name:

Last Name:

Age:

Gender:  ▼

Number Of Accidents:

##### Vehicle

Vehicle Identification Number:

Make:

Model:


Value:

Click **OK** and these get rejected as Not eligible.



The dialog box is titled "Eligibility Response". It contains a sub-section also titled "Eligibility Response". Inside this sub-section, there is a label "Eligible:" followed by an unchecked checkbox. Below that is a "Main Message:" label followed by a text input field containing the text "The driver has had too many accidents". At the bottom right of the dialog box is an "OK" button.

Click **OK** again and enter a lower number of accidents e.g. **2**.



The dialog box is titled "Auto Quote Request". It is divided into two sections: "Driver" and "Vehicle".

**Driver Section:**


- First Name: John
- Last Name: Smith
- Age: 25
- Gender: Male (dropdown menu)
- Number Of Accidents: 2

**Vehicle Section:**

- Vehicle Identification Number: 1234
- Make: Lemon
- Model: Yellow
- Value: 0

At the bottom right of the dialog box is an "OK" button.

Click **OK** and this time the Quote is eligible.



Click **OK** again and the service exits.

You have now used an HTDS managed decision service within a BPMN process.