



SupportPac LA71: IBM Operational Decision Manager Integration for WebSphere Process Server

Getting started with IBM Business Process Manager

Task 3 - Business Process Author re-uses an HTDS Managed Decision as part of a BPMN Process

Copyright

Copyright notice

© Copyright IBM Corp. 1987, 2012

US Government Users Restricted Rights - Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Trademarks

IBM, the IBM logo, ibm.com, WebSphere, and ILOG are trademarks or registered trademarks of International Business Machines Corp., in many jurisdictions worldwide.

Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at *Copyright and trademark information*.

Adobe, the Adobe logo, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

Java and all Java-based trademarks and logos are trademarks of Sun Microsystems, Inc. in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.

Overview

In this task, the Business Process Author uses the HTDS Managed Decision service as part of their process. This allows them to run a process using the rules in the managed decision rather than defining their own embedded rules. In this task you will use the Eligibility Managed Decision Service.

Readers who want to skip the exercise should import the solution as a Snapshot from **[SupportPac LA71 Path]\BPMTutorial\task3\Insurance_Sample_-_HTDS_Reuse - Completed.twx** and continue at Step 6 to test the HTDS service in the process.

Step 1. Create a Process Application to host the HTDS Decision Service

This task starts by creating a new Process Application to host the HTDS Decision Service.


Open Process Designer and login.

For **User Name** type **admin**


For **Password** type **admin**.



Click the Process Center icon.



Click Create New Process App.




Fill in the Process App details as shown below.

For **Process App Name** type **Insurance Sample – HTDS Reuse**

For the **Acronym** type **LA71TT3**


Note: If you have already imported the completed Task 3 you will have to either rename the imported Process App or give this one a different acronym.

For the **Description** provide details as shown below.



Click **Create**.

In the list of Process Apps, in the entry for **LA71TT3** click the **Open in Designer** link.




Process Designer opens on the newly created Process App.



Step 2. Register the Rule Execution Server

In order to access the rule applications you must register the rule application server hosting your HTDS Managed Decisions.

Select **Process App Settings** Screen.




On the **Servers** tab click the **Add** button

Set the **Name** to **BPMRES**.

Set the **Type** to **ILOG Rules Server** by selecting from the pulldown list.

Set the **Default** URL to <http://localhost:9080> or the port on which the Rule Execution Server is available.



Use the menu option **File > Save All** to save your changes.


Step 3. Create the Decision Service for the Eligibility Managed Decision.

Hover your mouse over the Decisions icon and click the '+' sign that appears to its right to create a new Decision Service.



Click **Decision Service**.

In the Name field type **Eligibility_ManagedDecision** and click **Finish**.



Open the Diagram tab of the **Eligibility_ManagedDecision** Decision Service.
 Drag a **JRules Decision Service** onto the Canvas from the list of Common elements on the right-hand side, and rename it **Eligibility**.
 Select the **Sequence Flow** icon.




Connect the **Start** node to the **Eligibility** node.
 Connect the **Eligibility** node to the **End** node.
 Reselect the **Selection Flow** icon,



Click in the canvas – right click and select **Tidy Layout**.

Use the menu option **File > Save All** to save your changes.

The new decision service should look as below.



Step 4. Bind the Decision Services to the Hosted Transparent Decision Services from ODM.

Open the **Eligibility_ManagedDecision** Diagram.
 Select the **Eligibility** node and in the **Properties** panel select the **Implementation** Tab.
 In the **Discovery** panel you define the the Rule Execution Server hosting the HTDS Decisions.
 In the **Server** Field select the **BPMRES** server you defined earlier.
 Type **admin** in both **Username** field and **Password** field.

Properties Validation Errors Where Used

Step: **Discovery**

Implementation: Server: BPMRES

Data Mapping: SOAP Port: 8880

Pre & Post: Username: admin

Password: js *****

Connect

Click **Connect**.

In the adjacent Rules Panel, the available Rule Apps and Rules are then displayed.

From the **Rule App** pulldown select **InsuranceSampleRuleApp**.

From the **Ruleset** pulldown select **Eligibility**.

Leave the **Version** fields at **Latest**. This means that the most recent versions of the managed decisions will always be used.

Rule

Rule App: InsuranceSampleRuleApp Version: Latest

Ruleset: Eligibility Version: Latest

View Generate Types...

Now we will import the information models used by the rules.

Click **Generate Types...**

In the screen that results leave all options deselected as we only need the minimum of new types.

Generate Types Wizard

Generating Types

Click Next to begin type generation

☐ Generate all types

Select operation(s) for which you want types to be generated:

Eligibility

☐ Generate request/response wrapper types

< Back Next > Finish Cancel

Click **Next >**.

The Mapping Types generation screen shows the types generated and any naming conflicts.

Click **Next >**.

The **Type Generation Summary** screen shows the types generated.

Generate Types Wizard

Mapping Types

Type generation is complete.

Types:

Namespace	Type	IBM BPM Type
http://INSDemo	AirbagType	AirbagType
http://INSDemo	AutoQuoteRequest	AutoQuoteRequest
http://INSDemo	CoverageItem	CoverageItem
http://INSDemo	CoverageType	CoverageType
http://INSDemo	Driver	Driver
http://INSDemo	EligibilityResponse	EligibilityResponse
http://INSDemo	GenderType	GenderType
http://INSDemo	Vehicle	Vehicle
http://INSDemo	VehicleType	VehicleType
http://www.ibm...	EligibilityException	EligibilityException
http://www.ibm...	AutoQuoteRequest	AutoQuoteRequest_1

Warnings:

Description	Location
Message: xs.import.warning.DuplicateTypeName Arguments: Eligibility...	/ns1:EligibilityR...
Message: xs.import.warning.DuplicateTypeName Arguments: AutoQu...	/ns1:AutoQuot...
Message: xs.import.warning.DuplicateTypeName Arguments: Eligibility...	/ns2:EligibilityR...


< Back **Next >** Finish Cancel

Note:

The duplicated **AutoQuoteRequest** in the www.ibm.com/rules/decisionservice/InsuranceSampleRuleApp/Eligibility/param namespace is mapped to **AutoQuoteRequest_1**.

The duplicated **EligibilityResponse** in the www.ibm.com/rules/decisionservice/InsuranceSampleRuleApp/Eligibility/param namespace is mapped to **EligibilityResponse_1**.


Click **Finish** to exit the wizard.



Click on the **Data** icon where you will see the list of Business Objects that have been created.

Examine the Business Objects to check that the information model has been correctly retained.

Double Click **AutoQuoteRequest_1** and examine it in the Business Object Editor.



Step 5. Mapping decision service variables manually.

Because the HTDS managed decision services use wrapper types, we need to map these HTDS parameters to decision service variables that only use the INSDEMO business objects.

First you need to define the private variables that will be used to invoke the decision service. These variables use the wrapper types from the decision service.

Click on the **Decisions** icon and then double-click on **Eligibility_ManagedDecision**.

In the Variables tab click **Add Private**.

In the **Name:** field, type **autoQuoteRequest**.

In the **Variable Type:** field, click **Select...** and select the **AutoQuoteRequest_1** Business Object.

Select the **Has Default** checkbox.

In the Default Value property list, expand **Driver** and find the **NumberOfAccidents** field, and set the value to **5**.

The screenshot shows the IBM Design Center interface for the 'Eligibility_ManagedDecision' project. The 'Variables' tab is active, displaying a tree view on the left with categories: Variables, Local, Input, Output, Private, autoQuoteRequest (AutoQuoteRequest_1), Exposed Process Variables, and Localization Resources. The 'Details' panel on the right shows the configuration for the 'autoQuoteRequest' variable. The 'Name' field is set to 'autoQuoteRequest'. The 'Documentation' field contains the text 'Click [Edit](#) to add or edit text.' The 'Is List' checkbox is unchecked. The 'Variable Type' is set to 'AutoQuoteRequest_1'. The 'Default Value' section shows the 'Has Default' checkbox checked. Below this, a table lists properties and their values:


Property	Value
DrivingLicenseNumber	""
FirstDrivingLicenseDt	new TWDate ()
VehicleVandalizedOrStolen	false
LicenseSuspendedOrRevoked	false
DUI	false
NumberOfAccidents	5
NumberOfTrafficTicket	0
Vehicle	
Coverage	

In the Variables tab click **Add Private**.


In the **Name:** field, type **eligibilityResponse**

In the **Variable Type:** field, click **Select...** and select the **EligibilityResponse_1** Business Object.

Select the **Has Default** checkbox.




In the Variables Screen click **Add Private**.
 In the **Name:** field, type **decisionID**
 In the **Variable Type:** field, leave the selection as **String**.
 Select the **Has Default** checkbox.




Having created the variables these now need to be mapped to the decision service.
 Return to the Diagram tab. Select the **Eligibility** node and open the **Properties** screen.

Select the **Data Mapping** tab.


On the **Input Mapping** panel click the mapping icon associated with the **DecisionID** parameter.




In the pop-up select the **decisionID** private variable that you have just created.




This should then select this variable to be mapped to the parameter.



Repeat this to map the **autoQuoteRequest** private variable to the **AutoQuoteRequest** input parameter, and the **eligibilityResponse** private variable to the **EligibilityResponse** input parameter.



On the **Output Mapping** panel repeat the steps above to map the output parameters as shown.



You have now mapped the private variables to the ODM HTDS decision service call.

Step 6. Mapping decision service variables using AutoMapping.


There is an automatic mapping feature provided in Process Designer that can be used as described below. It is an alternative to step 5.

Open the **Eligibility_ManagedDecision** Diagram.


Select the **Eligibility** node and open the **Properties** screen.

Select the **Data Mapping** tab.

On the **Input Mapping** panel click the Auto-map icon.




Select all three of the parameters to map.



Click **OK**.

On the **Output Mapping** panel click the Auto-map icon.



Selecting the Variables tab shows all the local variables that have been created from the imported Business Objects.

You still have to set the default value for local variables manually as described in step 5.

The screenshot displays the 'Eligibility_ManagedDecision' application window. The 'Variables' tab is active, showing a tree view of variables. The 'Details' panel on the right shows the configuration for the 'autoQuoteRequest' variable. The 'Default Value' section is expanded, showing a table of properties and their values.

Property	Value
Married	false
Graduated	false
FullTimeStuc	false
GoodStuden	false
DrivingLicen	" "
FirstDrivingL	new TWDate ()
VehicleVand	false
LicenseSusp	false
DUI	false
NumberOfAx	0
NumberOfTr	0
Vehicle	
Coverage	

The bottom of the window shows the 'Properties' tab with 'Input Mapping' and 'Output Mapping' sections. The 'Input Mapping' section shows three mappings: 'tw.local.decisionID' to 'DecisionID', 'tw.local.autoQuoteRequest' to 'AutoQuoteRequest', and 'tw.local.eligibilityResponse' to 'EligibilityResponse'. The 'Output Mapping' section shows three mappings: 'DecisionID' to 'tw.local.decisionID', 'AutoQuoteRequest' to 'tw.local.autoQuoteRequest', and 'EligibilityResponse' to 'tw.local.eligibilityResponse'.

Step 7. Creating the Decision inputs and outputs.


Now you need to create the input and output parameters to the **Eligibility_ManagedDecision** decision service using the shared business objects and map them to the private wrapper variables used to invoke the ODM service.

Click on the **Decisions** icon and then double-click on **Eligibility_ManagedDecision**.


In the Variables tab click **Add Input**.

In the **Name:** field, type **AutoQuoteRequest_In**.

In the **Variable Type:** field, click **Select...** and select the **AutoQuoteRequest** Business Object.
 Select the **Has Default** checkbox.
 In the Default Value property list find the **NumberOfAccidents** field under Driver, and set the value to **5**.



In the Variables tab click **Add Output**.
 In the **Name:** field type **EligibilityResponse_Out**.
 In the **Variable Type:** field click **Select...** and select the **EligibilityResponse** Business Object.
 Use the menu option **File > Save All** to save your changes.



Finally you need to map between these input and output parameters and the private variables.


In the Diagram tab select the **Eligibility** Node and in the **Properties** screen select the **Pre & Post** Tab.

In the **Pre-execution Assignments** panel type:

```
tw.local.autoQuoteRequest.AutoQuoteRequest = tw.local.AutoQuoteRequest_In;
```

In the **Post-execution Assignments** panel type:

```
tw.local.EligibilityResponse_Out = tw.local.eligibilityResponse.EligibilityResponse;
```




Use the menu option **File > Save All** to save your changes.
You have now completed the variable mapping.

Step 8. Test the Decision Service.

You can now test the decision service in isolation.

Open the **Diagram** tab for the **Eligibility_ManagedDecision** and click the Debug icon.



A browser opens showing the node and variable values.
 Navigate down the variables to check that the NumberOfAccidents field has been correctly set.

IBM Business Process Manager Service Debug			
		Step	Run
Service Eligibility_ManagedDecision Item Type ILOGConnector Item Name Eligibility			
Namespace: local			
Name	Type	Value	
autoQuoteRequest	AutoQuoteRequest_1	<pre> <object type="AutoQuoteRequest_1"> <property name="AutoQuoteRequest" type="AutoQuoteRequest"> <property name="Driver" type="Driver"> <property name="NumberOfTrafficTicket" type="Integer" tw-id="id:0">0</property> <property name="NumberOfAccidents" type="Integer">5</property> <property name="DUI" type="Boolean">false</property> <property name="LicenseSuspendedOrRevoked" type="Boolean">false</property> <property name="VehicleVandalizedOrStolen" type="Boolean">false</property> </property> </object> </pre>	

Click **Step** to invoke the HTDS service.

The browser will be updated to show the result of invoking the HTDS decision service.

IBM Business Process Manager Service Debug			
		Step	Run
Service Eligibility_ManagedDecision Item Type Exit Point Item Name End			
Namespace: local			
Name	Type	Value	
autoQuoteRequest	AutoQuoteRequest_1	<pre> <object type="AutoQuoteRequest_1"> <property name="AutoQuoteRequest" type="AutoQuoteRequest"> </pre>	

Scroll down to the **EligibilityResponse_Out** variable to observe the Rules response.


EligibilityResponse_Out	EligibilityResponse	<pre> <object type="EligibilityResponse"> <property name="Eligible" type="Boolean">false</property> <property name="MainMessage" type="String">The driver has had too many accidents</property> <property name="ErrorMessage" type="String[]"> <arrayElement size="1"> <item type="String"></item> </arrayElement> </property> <metadata> <property name="dirty" type="Boolean">true</property> <property name="shared" type="Boolean">false</property> <property name="key" /> <property name="version" /> </metadata> </object> </pre>
-------------------------	---------------------	--

You have now successfully tested the decision service.

Step 9. Using the Managed Decision Service in a Process.


This final steps are optional and involves developing a Human process that invokes the managed decision.

Hover your mouse over the **User Interface** icon and click the '+' sign that appears to its right to create a new Human Service.




Give it the name **Insurance Eligibility**.

Go to the Diagram tab and create the following structure in the canvas.



The yellow boxes are **Heritage Coaches** (different from Coaches), the diamond is a **Decision Gateway**, and the gray box is a **Nested Service**.

After dragging those diagram elements from the Common palette onto the canvas, go to the Coaches tab and create a button in each of the Coaches with the label **OK**.




You can then connect all the elements together using the Sequence Flow Tool.

To name the lines **Yes** and **No** emanating from the Decision Gateway then select a line, enter its name in the Name field, and check the Name Visible box.


Note that you cannot yet connect the Eligibility Nested service to the Coach.

Select the **Eligibility** nested Service and navigate to the **Properties** View and **Implementation** tab.


Click the **Select** Button and select the **Eligibility_ManagedDecision** in the Services section. If the Service is not visible, press the small arrow in the bottom-right corner of the dialog to reveal it.



Navigate to the **Data Mapping** tab and click each of the **Automap** icons to generate private variables for the input and output parameters of the service. Check the box in the dialog that appears and click **OK**. Uncheck the **Use Default** checkbox after creating the private variable for the Input Mapping.



On the Variables tab, click on the **AutoQuoteRequest_In** private variable and check the Has Default checkbox. Initialize the **Driver**, **Vehicle** and **Coverage** with some default values.




Edit the two Heritage Coaches mapping fields to the private variables generated by the mappings. You can drag Business Objects such as Driver and Vehicle from the Variables palette on the right-hand side of the Coaches tab in order to create Sections for them. To remove any unwanted fields, right-click on them and select Delete. Then in each Heritage Coach, drag a One Column Section

from the Sections palette to the bottom and then drag a Button Group from the Controls palette into the new Section.


The screenshot shows the 'Insurance Eligibility' application window with the 'Coaches' tab selected. The main form is titled 'Auto Quote Request' and contains two sections: 'Driver' and 'Vehicle'. The 'Driver' section includes fields for First Name, Last Name, Age, Gender (set to Male), and Number Of Accidents. The 'Vehicle' section includes fields for Vehicle Identification Number, Make, Model, and Value. An 'OK' button is located at the bottom right of the form. On the left sidebar, 'Auto Quote Request' is selected. The right-hand palette shows 'Sections' and 'Controls' categories, with 'Button Group' highlighted under 'Controls'. The 'Variables' section at the bottom right lists 'AutoQuoteRequest' and 'EligibilityResponse'.

The screenshot shows the 'Insurance Eligibility' application window with the 'Coaches' tab selected. The main form is titled 'Eligibility Response' and contains a section with the same title. This section includes an 'Eligible' checkbox (checked) and a 'Main Message' text area. An 'OK' button is located at the bottom right of the form. On the left sidebar, 'Eligibility Response' is selected. The right-hand palette shows 'Sections' and 'Controls' categories, with 'Text Area' highlighted under 'Controls'. The 'Variables' section at the bottom right lists 'AutoQuoteRequest' and 'EligibilityResponse'.

Click on the Button Group and give the button the label OK in the Button Details panel of the Presentation view of the Properties tab, and make sure the **Create Flow** checkbox for Button OK is selected.



Connect the **Eligibility** Nested Service and the **Eligibility Response** Heritage Coach using the Sequence Flow tool. Finally, establish the Decision Gateway conditions as shown below.



Use the menu option **File > Save All** to save your changes.

Step 10. Running the Managed Decision Service in a Process.

Click on the **User Interface** icon and double-click the **Insurance Eligibility** Human Service. Click on the **Run** icon. The default values are shown initially.

Auto Quote Request

Driver

First Name:

Last Name:

Age:

Gender: ▼

Number Of Accidents:

Vehicle

Vehicle Identification Number:

Make:

Model:

Value:

Click **OK** and these get rejected as Not eligible.


Eligibility Response

Eligibility Response

Eligible: ☐

Main Message:

Click **OK** again and enter a lower number of accidents e.g. **2**.



Auto Quote Request

Driver

First Name:

Last Name:

Age:

Gender: ▼

Number Of Accidents:

Vehicle


Vehicle Identification Number:

Make:

Model:

Value:

Click **OK** and this time the Quote is eligible.



Eligibility Response

Eligibility Response

Eligible: ☒

Main Message:

Click **OK** again and the service exits.

You have now used an HTDS managed decision service within a BPMN process.