

IBM SurePOS 500 Series



Highlights

- Advanced technology helps you improve speed, performance and reliability
- Open, industry-standard platform accommodates a wide range of POS applications, operating systems and peripherals
- Retail-hardened components, systems management tools and world-class service all help protect your long-term investment
- Elegant, integrated design saves space.

The right choice for restaurants

Engineered for food service and hospitality operators, the IBM Sure-POS™ 500 Series delivers an ideal combination of affordability and performance. It is Web-enabled and can support sales tracking, loyalty programs or supply chain transactions. Its retail-hardened construction can withstand the harsh conditions of food service, for outstanding investment protection. And its space-saving design is suitable for any environment, from fast food to fine dining.

Advanced POS technology

An easy-to-use, integrated touchscreen display helps you keep transaction times low and train employees faster. Cooling-pipe technology protects electronics from grease and airborne food particles. The expansion slot enables wireless LAN access. The SurePOS 500 Series is also designed to use the IBM SurePoint™ Solution as a second display for automated upselling, scrolling receipts or advertising.

Unmatched flexibility

Five unique system units and a long list of easy-to-integrate peripherals – including cash drawers, printers, speakers, magnetic stripe readers and customer displays – let you configure the SurePOS 500 Series to meet your specific needs.

Broad software offering

An open platform and broad OS support let you choose from a diverse number of StoreProven™ POS applications from IBM Business Partners. StoreProven applications are tested to work with the SurePOS 500 Series Just look for the StoreProven emblem to find the right one for your restaurant, hotel, bar or café.





Innovations designed for a demanding retail world





IBM SureMark™ Printer provides fast, quiet, color thermal printing

PCMCIA expansion slot for wireless POS (561 and 551 only)

Cooling pipe technology protects sensitive electronics

Ethernet 10/100 LAN, RS-232 and USB ports

Wired for Management (WfM) compliance enables remote management

Multiple cash drawer options

Integration tray keeps peripherals organized







Second customer display for automatic upselling and promotions

Wide tilt range for optimal viewing



Integrated MSR

Spill-proof design safeguards system unit and touch-screen display

Presence sensor wakes system to conserve energy and extend equipment life





Model 561	Premium multimedia system with ultra-bright LCD	
	 Dual-bulb, active matrix touch-screen LCD Stereo speaker port PCMCIA Type II expansion slot Audio system 	 64 MB standard (up to 512 MB capable) Presence sensor Microphone port Widest viewing angle
Model 551	Standard multimedia system	
	 Single-bulb, active matrix touch-screen LCD Stereo speaker port Microphone port Wide viewing angle 	 32 MB standard (up to 512 MB capable) PCMCIA Type II expansion slot Audio system
Model 541	Premium system with ultra-bright LCD	
	 Dual-bulb, ultra-bright, active matrix touch-screen LCD 	32 MB standard (up to 512 MB capable)Widest viewing angle
Model 531	Standard system	
	Single-bulb, active matrix touch-screen LCDWide viewing angle	• 32 MB standard (up to 512 MB capable)
Model 521	Value system	
	Dual-bulb, passive touch-screen LCD	• 32 MB standard (up to 512 MB capable)

IBM SurePOS 500 Series at a	giance	
Hardware		
Processor ¹	• 400 MHz AMD-K6-2® socketed proce	essor or faster
Video memory	• 2, 4 or 8 MB UMA	
Maximum colors	• 16 million	
Hard disk drive ²	• 10.1 GB (or larger) 3.5" IDE	
Floppy drive	• 1.44 MB (optional)	
Ports	 Customer display, video (VGA), RS232-serial (3), USB (2), parallel, external floppy, MSR, PS/2 keyboard/PC mouse, cash drawer (2), Ethernet 	
Tilt adjustment	Counter: 30° to 90° Wall-mount: -10° to 15° on wall from vertical surface	
Dimension (HxWxD)	 Countertop: 13.4 to 15" x 12.8 to 13.9" x 12.6" (340 to 381 mm x 325 to 353 mm x 321 mm) Wall-mount: 18 to 18.3" x 12.8 to 13.9" x 12.8 to 13.9" x 8.9 to 10.4" (457 to 464 mm x 325 to 353 mm x 227 to 265 mm) 	
Weight	System unit: 9.5kg (21 lbs)MSR: 0.16kg (.35 lbs)	• Speaker (561 & 551 only): 0.5kg (1.1 lbs)
Peripherals		
Customer Displays	IBM SurePoint SolutionDistributed character display	Integrated character display
Printers	IBM SureMark Printer Fiscal printers (ask your local representative for details)	
Keyboards	87-key SpaceSaver II PS/2 Keyboard	
Integration trays	Full-size cash drawerCountertop	Compact cash drawer
Additional features	 1.44 MB diskette drive Tills and locking covers Cash drawer lock Stereo speaker kit 	Cash drawers (full-size or compact)Kitchen systemMSR

Operating systems supported	DOS 2000 Microsoft Windows® NT 4.0	Microsoft® Windows® 98, 2000Linux (available for evaluation)
Drivers supported	POS Suite (available for download at ibm.com/industries/retail/store)	

Industry Standards

Systems Management	Wired for Management 1.1, SMBIOS 2.3
Power Management	APM 1.2, Advanced Configuration and Power Interface (ACPI) 1.0, Preboot Execution Environment (PXE) 1.X, Wake on LAN® (WOL)

IBM SurePOS 500 Series at a glance (continued)

Services

Limited warranty	One year
Technical support	 24x7 phone support (during warranty period) and Web-based help
Options	Both depot and on-site service are available. For more information, contact your local IBM representative.

¹ MHz/GHz only measures microprocessor internal clock speed; many factors affect application performance

For more information

To learn more about the IBM SurePOS 500 Series and other IBM POS solutions, contact your local IBM representative or find us on the Web at:

ibm.com/industries/retail/store

To place an order, call 1 800 IBM-CALL (1800 426-2255) or 1770 863-1000 outside the U.S. and Canada.



© Copyright IBM Corporation 2001 IBM Corporation Department C6PA 5601 Six Forks Road Raleigh, NC 27609

Printed in the United States of America 08-01

All Rights Reserved

References in this publication to IBM products or services do not imply that IBM intends to make them available in all countries in which IBM operates. Copying or downloading the images contained in this document is expressly prohibited without the written consent of IBM.

IBM will continue to enhance products and services as new technologies emerge. Therefore, IBM reserves the right to alter specifications and other product information without prior notice. Please contact your IBM marketing representative or an authorized reseller for information on specific standard configuration and options.

IBM assumes no responsibility of liability for any use of the information contained herein. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of IBM or third parties. No warranties of any kind including but not limited to the implied warranties of merchantability or fitness for a particular purpose are offered in this document.

The e-business logo, IBM, the IBM logo, StoreProven, SureMark, SurePoint, SurePOS and Wake on LAN are trademarks or registered trademarks of International Business Machines Corporation in the United States and/or other countries.

Microsoft, Windows and Windows NT are registered trademarks of Microsoft Corporation.

AMD-K6-2 is a registered trademark of Advanced Micro Devices, Inc.

All other company names or product names are trademarks or registered trademarks of their respective companies.

For a copy of the terms and conditions of IBM's Statement of Limited Warranty, please contact your IBM representative or authorized reseller.



Printed on recycled paper containing 10% recovered post-consumer fiber.

² MB/GB/TB equals one million/billion/trillion bytes when referring to storage capacity; accessibility may be less