IBM SurePOS 500 Series



Highlights

- Advanced POS technology improves transaction speed
- All-in-one, space-saving design with touchscreen interface
- Retail-hardened components, systems management tools and world-class service all help protect your long-term investment
- Open, industry-standard platform accommodates a wide range of POS applications, operating systems and peripherals

Fast, durable and dependable

The IBM SurePOS[™] 500 Series delivers a powerful combination of speed, affordability and reliability that is ideal for food service, hospitality, gas and convenience, and many other markets. Its 1.2 GHz processor is among the fastest in the industry. This Web-enabled system can also support sales tracking, loyalty programs or supply chain transactions. It is retail-hardened to withstand harsh conditions and provide exceptional investment protection. And its space-saving design fits well in virtually any environment.

Innovative POS technology

An easy-to-use, integrated touchscreen display helps you keep transaction times low and train employees faster. Cooling-pipe technology protects electronics from grease, dirt, dust and other contaminants. And the expansion slot enables wireless LAN access. The SurePOS 500 Series is also designed to use the IBM SurePoint[™] Solution as an optional second display to show a scrolling receipt or other data from the POS application.

Flexible configurations

Choose from four new system units and easy-to-integrate peripherals – including cash drawers, printers, speakers, magnetic stripe readers and customer displays – to configure a POS system that matches your specific requirements. The SurePOS 500 Series also includes seven industry-standard ports for attaching third-party devices.


Broad software offering

An open platform and broad OS support let you choose from a portfolio of StoreProven[™] POS applications from IBM Business Partners. These applications have been tested to work with the SurePOS 500 Series – just look for the StoreProven emblem to find the right one for your business.¹





Advanced capabilities for demanding applications



IBM SureMark[™] Printers provide fast, quiet, color thermal printing

PCMCIA expansion slot enables wireless POS (562 and 552)

Cooling-pipe technology protects sensitive electronics

Ethernet 10/100 LAN, RS-232 and USB ports provide industry-standard connectivity

Wired for Management (WfM) compliance for remote management

Full-size or compact cash drawer — accommodates range of POS needs

Integration tray ensures a clean, organized appearance



Wall-mount for areas where space is limited (542 and 532)

Second display keeps customers engaged

Wide tilt range for ergonomically correct viewing



Integrated MSR (optional)

Spill-resistant design safeguards system unit and touchscreen display

Presence sensor wakes system to conserve energy (562)

Touchscreen LCD available in 15" (special order) or 12" (standard)



NEW Model 562	Premium multimedia system with ultra-bright LCD	
	 Dual-bulb, active matrix touchscreen LCD improves visibility in extremely bright or low-light conditions Stereo speaker port Presence sensor 	 PCMCIA Type II expansion slot Headphone and microphone ports On-board audio system Widest viewing angle
NEW Model 552	Standard multimedia system	
	 Single-bulb, active matrix touchscreen LCD Stereo speaker port Headphone and microphone ports 	 Wide viewing angle PCMCIA Type II expansion slot On-board audio system
NEW Model 542	Premium system with ultra-bright LCD	
	 Dual-bulb, active matrix touchscreen LCD improves visibility in extremely bright or low-light conditions 	Widest viewing angle
EW Model 532	Standard system	
	Single-bulb, active matrix touchscreen LCDWide viewing angle	Optional compact flash memory eliminates the need for a hard disk drive

IBM SurePOS 500 Series at a glance

Hardware

Processor	 1.2 GHz Intel[®] Celeron[™] (or faster) 	
Memory	• 64 MB (expandable to 512 MB)	
Video memory	• 8 MB UMA (16 or 32 MB UMA can be defined)	
Maximum colors	• 32-bit true color at 800 x 600 resolution (1024 x 768 available)	
Hard disk drive ²	• 20 GB (or larger) 3.5" IDE	
Alternative storage	Compact flash with 64 or 128 MB (532)	
Ports	 Customer display, video (SVGA), RS-232 (3), USB (4), parallel, external diskette, MSR, PS/2 keyboard/PC mouse, cash drawer (2), Ethernet 	
Tilt adjustment	 Counter: 30° to 90° Wall-mount: -10° to 15° on wall from vertical surface 	
Dimensions ³ (HxWxD)	 Countertop: 13.4 to 15" x 12.8 to 13.9" x 12.6" (340 to 381 mm x 325 to 353 mm x 321 mm) Wall-mount: 18 to 18.3" x 12.8 to 13.9" x 8.9 to 10.4" (457 to 464 mm x 325 to 353 mm x 227 to 265 mm) 	
Weight	 System unit: 21 lbs (9.5kg) MSR: 0.35 lbs (0.16kg) Speaker (562 and 552): 1.1 lbs (0.5kg) 	
Power consumption	• 45 W typical, 23 W standby, Energy Star compliant	

Optional Peripherals

	Customer displays	IBM SurePoint SolutionDistributed 40-character display	 Integrated 40-character display All Points Addressable character graphics display
	Printers	IBM SureMark PrintersFiscal printers (ask your local representative for	details)
EW	Keyboards	Compact Alphanumeric POS keyboard (CANPOS) (includes 32 programmable keys, numeric keypad and pointing device)	
	Integration trays	Full-size cash drawerCountertop	Compact cash drawer
	Additional options	 External 1.44 MB diskette drive Tills and locking covers Stereo speaker kit (562 and 552) 	 Cash drawers (full-size or compact) External USB CD-ROM drive MSR

Software

NE\

Operating systems supported	 DOS 2000 Microsoft Windows NT[®] 4.0 Linux (RedHat 7.1) 	 Microsoft[®] Windows[®] 98, 2000 Microsoft Windows XP Microsoft Windows XP Embedded⁴
Drivers supported	OPOS 1.5.0 and Java [™] POS 1.5.1	
Management tools	 Remote Deployment Manager (RDM) 3.1 IBM Director 3.1 	

IBM SurePOS 500 Series at a glance (continued)

Industry Standards

Systems management	 Wired for Management (WfM) 2.0, SMBIOS 2.3/Desktop Management Interface (DMI), Preboot Execution Environment (PXE) 2.0, Wake on LAN[®] (WOL) 		
Power management	 Advanced Power Management (APM) 1.2, Advanced Configuration and Power Interface (ACPI) 1.0 		
Services			
Limited warranty⁵	• One year		
Service life	Up to seven years after withdrawal from market		
Technical support ⁶	 24x7 phone support (during warranty period, response times may vary) and Web-based help Both depot and onsite service are available 		
IBM makes no warranties, expressed or implied, regarding StoreProven products and	³ Measurements assume standard 12" display, not 15" display available by special order.		
services, including any implied warranties of merchantability or fitness for a particular purpose. Statements made by IBM Business Partners that offer StoreProven applications are provided by the relevant third-party company and not IBM.	⁴ IBM will provide hardware support for customers who create unique Windows XP Embedded images. Field problems for XP Embedded will need to be recreated under Windows XP Professional.		
² MB/GB/TB equals one million/billion/trillion bytes when referring to storage capacity; accessibility may be less.	⁵ For a copy of the terms and conditions of IBM's Statement of Limited Warranty, please contact your IBM representative or authorized reseller.		

⁶ Geography dependent.

For more information

To learn more about the IBM SurePOS 500 Series and other IBM POS solutions, contact your local IBM representative or find us on the Web at: **ibm.com**/industries/retail/store

To place an order, call 1 800 IBM-CALL (1 800 426-2255) or 1 770 863-1000 outside the U.S. and Canada.



© Copyright IBM Corporation 2002 IBM Corporation Department C6PA 5601 Six Forks Road Raleigh, NC 27609

Printed in the United States of America 04-02 All Rights Reserved

References in this publication to IBM products or services do not imply that IBM intends to make them available in all countries in which IBM operates. Copying or downloading the images contained in this document is expressly prohibited without the written consent of IBM.

IBM will continue to enhance products and services as new technologies emerge. Therefore, IBM reserves the right to alter specifications and other product information without prior notice. Please contact your IBM marketing representative or an authorized reseller for information on specific standard configuration and options.

IBM assumes no responsibility of liability for any use of the information contained herein. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of IBM or third parties. No warranties of any kind including but not limited to the implied warranties of merchantability or fitness for a particular purpose are offered in this document.

- Intervention Provided Automatical States and Content and Conten
- Intel and Celeron are trademarks or registered trademarks of the Intel Corporation in the United States and/or other countries.
- [™] Java is a trademark of Sun Microsystems, Inc. in the United States, other countries or both.
- Microsoft, Windows and Windows NT are registered trademarks of Microsoft Corporation, in the United States, other countries, or both.
 - All other company names or product names are trademarks or registered trademarks of their respective companies.

For a copy of the terms and conditions of IBM's Statement of Limited Warranty, please contact your IBM representative or authorized reseller.

Printed on recycled paper containing 10% recovered post-consumer fiber.

Front cover shows an IBM SurePOS 562 with MSR.