IBM SurePOS 300 Express at a glance - Canada	
Hardware	Model 4910-32H
Processor <sup>1</sup>	• VIA C3 1.2GHz
Video memory	4MB UMA (8MB UMA can be defined)
Memory <sup>2</sup>	<ul> <li>256MB (expandable to 512MB)</li> </ul>
Ports	<ul> <li>Video display (SVGA), Ethernet, powered RS-232 (2),</li> </ul>
	RS-232 (4), USB (4), PS/2 keyboard, PC mouse, headphone, microphone in, line out, cash drawer
Slots	One half-size PCI adapter slot
Dimensions (WxDxH)	• 11.8" x 8.5" x 3.6" (300mm x 216mm x 90mm)
Weight	• 8lbs (3.6kg)
Power consumption	35W typical, 100W maximum
Peripherals	
Printer	<ul> <li>IBM SureMark<sup>™</sup> Printer TF6</li> </ul>
Keyboard	PS/2® AlphaNumeric (ANPOS) keyboard with built-in Magnetic
	Stripe Reader (MSR) and pointing device
Cashdrawer <sup>3</sup>	Full-size cash drawer
Display <sup>4</sup>	<ul> <li>ThinkVision<sup>™ 4</sup> 12" monitor L150 (included in suggested retail price. If not available at time of purchase, monitor included will be of equal or greater value).</li> </ul>
Software	
Operating systems supported <sup>5</sup>	<ul> <li>Microsoft<sup>®</sup> Windows<sup>®</sup> XP Professional Edition<sup>6</sup></li> </ul>
	<ul> <li>Microsoft Windows XP Embedded<sup>7</sup></li> </ul>
	Microsoft Windows 2000
	<ul> <li>IBM Retail Environment for SUSE LINUX (IRES)</li> </ul>
	• DOS 2000
Drivers supported	<ul> <li>OPOS 1.7.0 and JavaPOS<sup>™</sup> 1.7.0</li> </ul>
Management tools	IBM Director 3.2 or higher
Industry standards	
Systems management <sup>8</sup>	Wired for Management (WfM) 1.1
	• SMBIOS 2.3
	Preboot Execution Environment (PXE) 2.0
D	Wake on LAN® (WOL)
Power management <sup>8</sup>	<ul> <li>Advanced Power Management (APM) 1.2</li> <li>Advanced Configuration and Power Interface (ACPI) 1.0</li> </ul>
Services	
Limited warrantv <sup>9</sup>	One year
Service life	Up to seven years after withdrawal from market
Technical support <sup>10</sup>	<ul> <li>24x7 phone support (during warranty period, response times may vary; may exclude some holidays) and Web-based help</li> <li>Both depot and onsite service are available</li> </ul>
1. MHz/GHz only measures mic	roprocessor internal clock speed; many factors affect
<ul> <li>be less. Memory supports be installed memory size less tl</li> <li>Cash drawer connects throug</li> <li>The ThinkVision display is a referenced here, it is design more about the innovative for ThinkVision, please visit www</li> <li>Operating system is not incluing</li> <li>Microsoft Windows XP Professional</li> <li>IBM will provide hardware su images. Field problems for X Professional.</li> <li>No battery option available.</li> </ul>	uded and can be purchased separately. Isional Preload with restrictive use described in the End User upport for customers who create unique Windows XP Embedded (P Embedded will need to be recreated under Windows XP ditions of IBM's Statement of Limited Warranty, please contact
10. Geography dependent.	