| IBM SurePOS 300 Express at a glance - Hungary |                                                                                                                                                                                                                                        |
|-----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hardware                                      | Model 4910-32E                                                                                                                                                                                                                         |
| Processor <sup>1</sup>                        | • VIA C3 1.2GHz                                                                                                                                                                                                                        |
| Video memory                                  | 4MB UMA (8MB UMA can be defined)                                                                                                                                                                                                       |
| Memory <sup>2</sup>                           | 256MB (expandable to 512MB)                                                                                                                                                                                                            |
| Ports                                         | <ul> <li>Video display (SVGA), Ethernet, powered RS-232 (2),</li> <li>RS-232 (4), USB (4), PS/2 keyboard, PC mouse, headphone,</li> <li>microphone in, line out, cash drawer</li> </ul>                                                |
| Slots                                         | One half-size PCI adapter slot                                                                                                                                                                                                         |
| Dimensions (WxDxH)                            | • 11.8" x 8.5" x 3.6" (300mm x 216mm x 90mm)                                                                                                                                                                                           |
| Weight                                        | • 8lbs (3.6kg)                                                                                                                                                                                                                         |
| Power consumption                             | 35W typical, 100W maximum                                                                                                                                                                                                              |
| Peripherals                                   |                                                                                                                                                                                                                                        |
| Printer                                       | IBM SureMark™ Printer KD5                                                                                                                                                                                                              |
| Display                                       | SurePoint 5GN (15" IR touch)                                                                                                                                                                                                           |
| Cashdrawer <sup>3</sup>                       | Compact cash drawer                                                                                                                                                                                                                    |
| Software                                      |                                                                                                                                                                                                                                        |
| Operating systems supported <sup>4</sup>      | <ul> <li>Microsoft® Windows® XP Professional Edition<sup>5</sup></li> <li>Microsoft Windows XP Embedded<sup>6</sup></li> <li>Microsoft Windows 2000</li> <li>IBM Retail Environment for SUSE LINUX (IRES)</li> <li>DOS 2000</li> </ul> |
| Drivers supported                             | • OPOS 1.7.0 and JavaPOS™ 1.7.0                                                                                                                                                                                                        |
| Management tools                              | IBM Director 3.2 or higher                                                                                                                                                                                                             |
| Industry standards                            |                                                                                                                                                                                                                                        |
| Systems management <sup>7</sup>               | <ul> <li>Wired for Management (WfM) 1.1</li> <li>SMBIOS 2.3</li> <li>Preboot Execution Environment (PXE) 2.0</li> <li>Wake on LAN® (WOL)</li> </ul>                                                                                    |
| Power management <sup>7</sup>                 | <ul><li>Advanced Power Management (APM) 1.2</li><li>Advanced Configuration and Power Interface (ACPI) 1.0</li></ul>                                                                                                                    |
| Services                                      |                                                                                                                                                                                                                                        |
| Limited warranty <sup>8</sup><br>Service life | <ul><li>One year</li><li>Up to seven years after withdrawal from market</li></ul>                                                                                                                                                      |
| Technical support <sup>9</sup>                | <ul> <li>24x7 phone support (during warranty period, response times may vary; may exclude some holidays) and Web-based help</li> <li>Both depot and onsite service are available</li> </ul>                                            |

- 1. MHz/GHz only measures microprocessor internal clock speed; many factors affect application performance.
- 2. MB/GB equals one million/billion bytes when referring to storage capacity; accessibility may be less. Memory supports both system and video. Accessible system memory will be the installed memory size less the amount defined for video.
- ${\it 3. Cash\ drawer\ connects\ through\ an\ IBM\ SureMark\ Printer,\ which\ must\ be\ purchased\ separately.}$
- 4. Operating system is not included and can be purchased separately.
- 5. Microsoft Windows XP Professional Preload with restrictive use described in the End User License Agreement.
- 6. IBM will provide hardware support for customers who create unique Windows XP Embedded images. Field problems for XP Embedded will need to be recreated under Windows XP Professional.
- 7. No battery option available.
- 8. For a copy of terms and conditions of IBM's Statement of Limited Warranty, please contact your local IBM representative or reseller.
- 9. Geography dependent.