| IBM SurePOS 300 Express at a glance - Italy | |
|---|--|
| Hardware | Model 4910-32E |
| Processor ¹ | • VIA C3 1.2GHz |
| Video memory | 4MB UMA (8MB UMA can be defined) |
| Memory ² | 256MB (expandable to 512MB) |
| Ports | Video display (SVGA), Ethernet, powered RS-232 (2), RS-232 (4), USB (4), PS/2 keyboard, PC mouse, headphone, microphone in, line out, cash drawer |
| Slots | One half-size PCI adapter slot |
| Dimensions (WxDxH) | • 11.8" x 8.5" x 3.6" (300mm x 216mm x 90mm) |
| Weight | • 8lbs (3.6kg) |
| Power consumption | 35W typical, 100W maximum |
| Peripherals | |
| Printer | IBM SureMark™ Printer KD5 |
| Display | SurePoint 5GN (15" IR touch) |
| Cashdrawer ³ | Compact cash drawer |
| Software | |
| Operating systems supported ⁴ | Microsoft® Windows® XP Professional Edition⁵ Microsoft Windows XP Embedded⁶ Microsoft Windows 2000 IBM Retail Environment for SUSE LINUX (IRES) DOS 2000 |
| Drivers supported | • OPOS 1.7.0 and JavaPOS™ 1.7.0 |
| Management tools | IBM Director 3.2 or higher |
| Industry standards | |
| Systems management ⁷ | Wired for Management (WfM) 1.1 SMBIOS 2.3 Preboot Execution Environment (PXE) 2.0 Wake on LAN® (WOL) |
| Power management ⁷ | Advanced Power Management (APM) 1.2 Advanced Configuration and Power Interface (ACPI) 1.0 |
| Services | |
| Limited warranty ⁸ | One year |
| Service life | Up to seven years after withdrawal from market |
| Technical support ⁹ | 24x7 phone support (during warranty period, response times may vary; may exclude some holidays) and Web-based help Both depot and onsite service are available |

- 1. MHz/GHz only measures microprocessor internal clock speed; many factors affect application performance.
- 2. MB/GB equals one million/billion bytes when referring to storage capacity; accessibility may be less. Memory supports both system and video. Accessible system memory will be the installed memory size less the amount defined for video.
- 3. Cash drawer connects through an IBM SureMark Printer, which must be purchased separately.
- 4. Operating system is not included and can be purchased separately.
- 5. Microsoft Windows XP Professional Preload with restrictive use described in the End User License Agreement.
- 6. IBM will provide hardware support for customers who create unique Windows XP Embedded images. Field problems for XP Embedded will need to be recreated under Windows XP Professional.
- 7. No battery option available.
- 8. For a copy of terms and conditions of IBM's Statement of Limited Warranty, please contact your local IBM representative or reseller.
- 9. Geography dependent.