IBM SurePOS 300 Express at a glance - Venezuela, Uruguay	
Hardware	Model 4910-32H
Processor ¹	• VIA C3 1.2GHz
Video memory	4MB UMA (8MB UMA can be defined)
Memory ²	256MB (expandable to 512MB)
Ports	 Video display (SVGA), Ethernet, powered RS-232 (2), RS-232 (4), USB (4), PS/2 keyboard, PC mouse, headphone, microphone in, line out, cash drawer
Slots	One half-size PCI adapter slot
Dimensions (WxDxH)	• 11.8" x 8.5" x 3.6" (300mm x 216mm x 90mm)
Weight	• 8lbs (3.6kg)
Power consumption	35W typical, 100W maximum
Peripherals	
Printer	IBM SureMark™ Printer TN3
Keyboard	Compact AlphaNumeric (ANPOS) keyboard (Spanish)
Cashdrawer ³	Full-size cash drawer
Software	
Operating systems supported ⁴	 Microsoft® Windows® XP Professional Edition⁵ Microsoft Windows XP Embedded⁶ Microsoft Windows 2000 IBM Retail Environment for SUSE LINUX (IRES) DOS 2000
Drivers supported	• OPOS 1.7.0 and JavaPOS™ 1.7.0
Management tools	IBM Director 3.2 or higher
Industry standards	
Systems management ⁷	Wired for Management (WfM) 1.1 SMBIOS 2.3 Preboot Execution Environment (PXE) 2.0 Wake on LAN® (WOL)
Power management ⁷	Advanced Power Management (APM) 1.2Advanced Configuration and Power Interface (ACPI) 1.0
Services	
Limited warranty ⁸ Service life	One yearUp to seven years after withdrawal from market
Technical support ⁹	 24x7 phone support (during warranty period, response times may vary; may exclude some holidays) and Web-based help Both depot and onsite service are available

- 1. MHz/GHz only measures microprocessor internal clock speed; many factors affect application performance.
- 2. MB/GB equals one million/billion bytes when referring to storage capacity; accessibility may be less. Memory supports both system and video. Accessible system memory will be the installed memory size less the amount defined for video.
- 3. Cash drawer connects through an IBM SureMark Printer, which must be purchased separately.
- 4. Operating system is not included and can be purchased separately.
- 5. Microsoft Windows XP Professional Preload with restrictive use described in the End User License Agreement.
- 6. IBM will provide hardware support for customers who create unique Windows XP Embedded images. Field problems for XP Embedded will need to be recreated under Windows XP Professional.
- 7. No battery option available.
- 8. For a copy of terms and conditions of IBM's Statement of Limited Warranty, please contact your local IBM representative or reseller.
- 9. Geography dependent.