| SurePOS 514 – Chile                         |   |
|---|---|
| Model number                                | 4951-514  |
| Processor <sup>1</sup>                      | 1.2GHz VIA Processor (133MHz FSB)   |
| Display <sup>2</sup>                        | Integrated 12", 5-wire resistive touch  |
| Storage                                     |   |
| System memory <sup>3</sup>                  | 256MB   |
| Video memory 4 (shared with system memory)  | 8MB to 64MB UMA   |
| Hard disk drive                             | 40GB Serial ATA or higher   |
| Connectivity Ports                          |   |
| Powered USB (24V)                           | 1   |
| Standard PC USB                             | 4   |
| RS-232 9-pin standard                       | 3   |
| RS-232 powered                              | 1   |
| PS/2 keyboard                               | 1 back  |
| PS/2 mouse                                  | 1 back  |
| RJ45 Ethernet                               | 1   |
| Cash drawer port (24V)                      | 2   |
| Peripherals <sup>5</sup>                    |   |
| Printers                                    | None specified  |
| Cash drawer                                 | Full-size   |
| MSRs  | Three track   |
| Integrated Character Display                | None  |
| Industry standards                          |   |
| Systems management                          | Wired for Management (WfM) SMBIOS   |
|   | Wake on LAN® (WOL)  |
|   | Preboot Execution Environment (PXE)   |
| Power management                            | Advanced Power Management (APM)   |
|   | Advanced Configuration and Power Interface (ACPI  |
| Systems dimensions and weight (without MSR) |   |
| Maximum dimensions                          | 12": 12.6x12.8x15.1" / 321x325x384mm  |
| Weight                                      | 12": 23lbs / 10.5kg   |
| Power requirements                          |   |
| Power requirements                          | Universal Switched Power Supply (76W typical/200W maximum)                              |
| 0.0   |   |
| Software                                    |   |
| Operating systems supported <sup>6</sup>    | •Microsoft® Windows® 2000   |
|   | •IBM Retail Environment for SUSE LINUX  |
|   | •IBM PC DOS 2000  |
|   | •Microsoft Windows XP Professional Edition  |
|   | •Microsoft Windows Embedded for Point of Service (WEPOS)                                |
| Drivers supported                           | <ul> <li>Novell SUSE LINUX Retail Solution (SLRS)</li> <li>OPOS and JavaPOS™</li> </ul> |
| Services                                    | 1 · OI OS aliu Javar OS   |
| Limited warranty service <sup>7</sup>       | One year depot or onsite services   |
| Technical support <sup>8</sup>              | 24x7 phone support (during limited warranty period) and Web-                            |
| recillical support                          | based help  |
|   | มิของนักเป็น  |

- 1. MHz/GHz only measures microprocessor internal clock speed; many factors affect application performance.
- 2. Screen sizes: 12" offers 800x600 pixels.
- 3. MB/GB equals one million/billion bytes when referring to storage capacity; accessibility may be less.
- 4. Memory supports both system and video. Accessible system memory will be the installed memory size less the amount defined for video.
- 5. Only available in some countries. Ask your IBM representative for details.
- 6. With the exception of the Microsoft Windows XP Professional and Microsoft Windows Embedded for Point of Service Preload models, an operating system is not included and can be purchased separately.
- 7. For a copy of the terms and conditions of IBM's Statement of Limited Warranty, please contact your IBM representative or authorized reseller.
- 8. Geography dependent.