



IBM Cúram Social Program Management

Cúram Web Client Error Message Guide

Version 6.0.4

Note

Before using this information and the product it supports, read the information in Notices at the back of this guide.

This edition applies to version 6.0.4 of IBM Cúram Social Program Management and all subsequent releases and modifications unless otherwise indicated in new editions.

Licensed Materials - Property of IBM

Copyright IBM Corporation 2012. All rights reserved.

US Government Users Restricted Rights - Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

© Copyright 2012 IBM Corporation

Table of Contents

Chapter 1 Introduction	1
1.1 Introduction	1
1.2 Prerequisites	1
1.3 Structure	1
Chapter 2 Error Messages	2
2.1 Objective	2
2.2 Introduction	2
2.2.1 Errors from Web Application vs. Application Server	3
2.3 -110000 ERR_TXTHLP_NO_NAME	3
2.3.1 Message	3
2.3.2 Description	3
2.3.3 Resolution	3
2.4 -110001 ERR_TXTHLP_NOT_FOUND	3
2.4.1 Message	3
2.4.2 Description	4
2.4.3 Resolution	4
2.5 -110002 ERR_TXTHLP_FIELD_ACCESS	4
2.5.1 Message	4
2.5.2 Description	4
2.5.3 Resolution	5
2.6 -110003 ERR_TXTHLP_MULTIPLE_ASSIGN	5
2.6.1 Message	5
2.6.2 Description	5
2.6.3 Resolution	5
2.7 -110004 ERR_TXTHLP_NO_CLASS	6
2.7.1 Message	6
2.7.2 Description	6
2.7.3 Resolution	6
2.8 -110005 ERR_TXTHLP_NEW_INST_FAIL	6
2.8.1 Message	6
2.8.2 Description	6
2.8.3 Resolution	6
2.9 -110007 ERR_TXTHLP_FIELD_NOT_FOUND	7
2.9.1 Message	7
2.9.2 Description	7

2.9.3 Resolution	7
2.10 -110008 ERR_TXTHLP_MANDATORY_FIELD_EMPTY	7
2.10.1 Message	7
2.10.2 Description	8
2.10.3 Resolution	8
2.11 -110010 ERR_TXTHLP_BAD_LIST_FIELD_ACCESS	8
2.11.1 Message	8
2.11.2 Description	8
2.11.3 Resolution	8
2.12 -110011 ERR_TXTHLP_UNRECOGNISED_FORMAT	8
2.12.1 Message	8
2.12.2 Description	9
2.12.3 Resolution	9
2.13 -110012 ERR_TXTHLP_BAD_SINGLE_FIELD_ACCESS	9
2.13.1 Message	9
2.13.2 Description	9
2.13.3 Resolution	9
2.14 -111000 ERR_TAG_NO_SRC_BF	9
2.14.1 Message	9
2.14.2 Description	10
2.14.3 Resolution	10
2.15 -111001 ERR_TAG_NO_SEL_SRC_BF	10
2.15.1 Message	10
2.15.2 Description	10
2.15.3 Resolution	10
2.16 -111002 ERR_TAG_NO_TRG_BF	10
2.16.1 Message	10
2.16.2 Description	10
2.16.3 Resolution	11
2.17 -111003 ERR_TAG_NOT_ENCLOSED	11
2.17.1 Message	11
2.17.2 Description	11
2.17.3 Resolution	11
2.18 -111004 ERR_TAG_BAD_LOOP_IND	11
2.18.1 Message	11
2.18.2 Description	12
2.18.3 Resolution	12
2.19 -111005 ERR_TAG_BAD_SCOPE	12
2.19.1 Message	12
2.19.2 Description	12
2.19.3 Resolution	12
2.20 -111006 ERR_TAG_NO_NAME	12
2.20.1 Message	12
2.20.2 Description	12
2.20.3 Resolution	13
2.21 -111007 ERR_TAG_RESOURCE_ACCESS	13
2.21.1 Message	13
2.21.2 Description	13
2.21.3 Resolution	13

2.22	-111008 ERR_TAG_NO_URL	13
2.22.1	Message	13
2.22.2	Description	14
2.22.3	Resolution	14
2.23	-111009 ERR_TAG_BAD_DATA_FORMAT	14
2.23.1	Message	14
2.23.2	Description	14
2.23.3	Resolution	14
2.24	-111010 ERR_TAG_NO_SRC	14
2.24.1	Message	14
2.24.2	Description	15
2.24.3	Resolution	15
2.25	-111011 ERR_TAG_SRC_NULL	15
2.25.1	Message	15
2.25.2	Description	15
2.25.3	Resolution	15
2.26	-111012 ERR_TAG_WITH_NAME_NOT_ENCLOSED	15
2.26.1	Message	15
2.26.2	Description	16
2.26.3	Resolution	16
2.27	-111013 ERR_TAG_UNKNOWN	16
2.27.1	Message	16
2.27.2	Description	16
2.27.3	Resolution	16
2.28	-111014 ERR_TAG_INTERNAL	16
2.28.1	Message	17
2.28.2	Description	17
2.28.3	Resolution	17
2.29	-111015 ERR_TAG_NO_SRC_PARAM	17
2.29.1	Message	17
2.29.2	Description	17
2.29.3	Resolution	17
2.30	-111016 ERR_TAG_MISSING_ATTRIB	18
2.30.1	Message	18
2.30.2	Description	18
2.30.3	Resolution	18
2.31	-111017 ERR_TAG_NO_SORTFIELD	18
2.31.1	Message	18
2.31.2	Description	18
2.31.3	Resolution	18
2.32	-111018 ERR_TAG_NO_PAGE_LOCALE	19
2.32.1	Message	19
2.32.2	Description	19
2.32.3	Resolution	19
2.33	-111019 ERR_TAG_NO_CONTENT_BF	19
2.33.1	Message	19
2.33.2	Description	19
2.33.3	Resolution	19
2.34	-111020 ERR_TAG_NO_META_DATA_BF	19

2.34.1	Message	19
2.34.2	Description	20
2.34.3	Resolution	20
2.35	-111021 ERR_TAG_NO_DETAILS_BF	20
2.35.1	Message	20
2.35.2	Description	20
2.35.3	Resolution	20
2.36	-111022 ERR_TAG_IMAGE_MAP	20
2.36.1	Message	20
2.36.2	Description	20
2.36.3	Resolution	21
2.37	-111023 ERR_TAG_IMAGE_MAP_NO_DOMAIN	21
2.37.1	Message	21
2.37.2	Description	21
2.37.3	Resolution	21
2.38	-111024 ERR_TAG_IMAGE_MAP_NO_LOCALE	21
2.38.1	Message	21
2.38.2	Description	21
2.38.3	Resolution	22
2.39	-111025 ERR_TAG_IMAGE_MAP_NO_MAPPING	22
2.39.1	Message	22
2.39.2	Description	22
2.39.3	Resolution	22
2.40	-111027 ERR_TAG_AGENDA_CONFIG	22
2.40.1	Message	22
2.40.2	Description	22
2.40.3	Resolution	23
2.41	-111028 ERR_TAG_NO_CONFIG	23
2.41.1	Message	23
2.41.2	Description	23
2.41.3	Resolution	23
2.42	-111029 ERR_TAG_PH_INVALID_OP	23
2.42.1	Message	23
2.42.2	Description	23
2.42.3	Resolution	23
2.43	-111030 ERR_TAG_CAL_NO_TYPE_ATTR	24
2.43.1	Message	24
2.43.2	Description	24
2.43.3	Resolution	24
2.44	-111031 ERR_TAG_CAL_BAD_TYPE_ATTR	24
2.44.1	Message	24
2.44.2	Description	24
2.44.3	Resolution	24
2.45	-111032 ERR_TAG_CAL_PARSE_FAILED	25
2.45.1	Message	25
2.45.2	Description	25
2.45.3	Resolution	25
2.46	-111033 ERR_TAG_WKFLOW_NO_PARAM	25
2.46.1	Message	25

2.46.2	Description	25
2.46.3	Resolution	25
2.47	-111034 ERR_TAG_WKFLOW_NO_MATCH	26
2.47.1	Message	26
2.47.2	Description	26
2.47.3	Resolution	26
2.48	-111035 ERR_TAG_INVALID_DECISION_MATRIX_XML_DATA	26
2.48.1	Message	26
2.48.2	Description	26
2.48.3	Resolution	27
2.49	-111036 ERR_TAG_NO_SOURCE_PATH	27
2.49.1	Message	27
2.49.2	Description	27
2.49.3	Resolution	27
2.50	-111500 ERR_TAG_PAGE_CONTENT_WRITE_FAILED	27
2.50.1	Message	27
2.50.2	Description	27
2.50.3	Resolution	28
2.51	-111501 ERR_TAG_RENDERED_OUTPUT_WRITE_FAILED	28
2.51.1	Message	28
2.51.2	Description	28
2.51.3	Resolution	28
2.52	-111502 ERR_TAG_FIELD_RENDER_FAILED	28
2.52.1	Message	28
2.52.2	Description	28
2.52.3	Resolution	29
2.53	-111503 ERR_TAG_GET_SRC_FAILED	29
2.53.1	Message	29
2.53.2	Description	29
2.53.3	Resolution	29
2.54	-111504 ERR_TAG_SET_TGT_FAILED	29
2.54.1	Message	29
2.54.2	Description	29
2.54.3	Resolution	30
2.55	-112001 ERR_SEC_AR_CACHE_NOT_FOUND	30
2.55.1	Message	30
2.55.2	Description	30
2.55.3	Resolution	30
2.56	-112002 ERR_SEC_NO_ACCESS_RIGHTS	30
2.56.1	Message	30
2.56.2	Description	30
2.56.3	Resolution	30
2.57	-112003 ERR_SEC_NO_USERNAME	31
2.57.1	Message	31
2.57.2	Description	31
2.57.3	Resolution	31
2.58	-112005 ERR_SEC_AR_NO_CLASS_NAME	31
2.58.1	Message	31
2.58.2	Description	31

2.58.3 Resolution	31
2.59 -115000 ERR_FLOW_NO_LINK_TAG	31
2.59.1 Message	31
2.59.2 Description	31
2.59.3 Resolution	32
2.60 -115001 ERR_FLOW_NO_LOOP_SIZE	32
2.60.1 Message	32
2.60.2 Description	32
2.60.3 Resolution	32
2.61 -116001 ERR_SVR_NO_CONNECTION_SPECIFIED	32
2.61.1 Message	32
2.61.2 Description	32
2.61.3 Resolution	32
2.62 -116002 ERR_SVR_BAD_CONNECTION_TYPE	33
2.62.1 Message	33
2.62.2 Description	33
2.62.3 Resolution	33
2.63 -116003 ERR_SVR_CONNECTION_CLASS_FAIL	33
2.63.1 Message	33
2.63.2 Description	33
2.63.3 Resolution	33
2.64 -116004 ERR_SVR_GET_PROXY_FAIL	34
2.64.1 Message	34
2.64.2 Description	34
2.64.3 Resolution	34
2.65 -116005 ERR_SVR_INIT_FAIL	34
2.65.1 Message	34
2.65.2 Description	34
2.65.3 Resolution	34
2.66 -116007 ERR_SAP_CONN_FAIL	34
2.66.1 Message	34
2.66.2 Description	34
2.66.3 Resolution	35
2.67 -116008 ERR_JSON_CMD_UNSUPPORTED	35
2.67.1 Message	35
2.67.2 Description	35
2.67.3 Resolution	35
2.68 -116009 ERR AJAX_PROCESSING_FAIL	35
2.68.1 Message	35
2.68.2 Description	35
2.68.3 Resolution	35
2.69 -117001 ERR_WDGT_POPUP_RM_NO_TRG	35
2.69.1 Message	35
2.69.2 Description	36
2.69.3 Resolution	36
2.70 -117005 ERR_WDGT_ASSESS_BAD_PARAMS	36
2.70.1 Message	36
2.70.2 Description	36
2.70.3 Resolution	37

2.71	-117006 ERR_WDGT_UNKNOWN_NODE_TYPE	37
	2.71.1 Message	37
	2.71.2 Description	37
	2.71.3 Resolution	37
2.72	-117007 ERR_WDGT_CONFIG_NOT_FOUND	37
	2.72.1 Message	37
	2.72.2 Description	37
	2.72.3 Resolution	38
2.73	-117008 ERR_WDGT_WRONG_DATA	38
	2.73.1 Message	38
	2.73.2 Description	38
	2.73.3 Resolution	38
2.74	-117009 ERR_TREE_BAD_DATA	38
	2.74.1 Message	38
	2.74.2 Description	39
	2.74.3 Resolution	39
2.75	-117010 ERR_TREE_BAD_STRUCT	39
	2.75.1 Message	39
	2.75.2 Description	39
	2.75.3 Resolution	39
2.76	-117011 ERR_TREE_INCOMPLETE	39
	2.76.1 Message	39
	2.76.2 Description	39
	2.76.3 Resolution	40
2.77	-117012 ERR_TREE_DUPLICATED_PARAMS	40
	2.77.1 Message	40
	2.77.2 Description	40
	2.77.3 Resolution	40
2.78	-117013 ERR_TREE_MISSING_TYPE	40
	2.78.1 Message	40
	2.78.2 Description	40
	2.78.3 Resolution	40
2.79	-117014 ERR_TREE_BAD_CONFIG	41
	2.79.1 Message	41
	2.79.2 Description	41
	2.79.3 Resolution	41
2.80	-117500 ERR_REQUEST_UNKNOWN	41
	2.80.1 Message	41
	2.80.2 Description	41
	2.80.3 Resolution	41
2.81	-117501 ERR_REQUEST_MERGE_PARAM	41
	2.81.1 Message	41
	2.81.2 Description	42
	2.81.3 Resolution	42
2.82	-117502 ERR_REQUEST_ITEM_CREATION_FAILED	42
	2.82.1 Message	42
	2.82.2 Description	42
	2.82.3 Resolution	42
2.83	-117503 ERR_REQUEST_HANDLING_FAILED	42

2.83.1	Message	42
2.83.2	Description	42
2.83.3	Resolution	43
2.84	-117504 ERR_REQUEST_WRONG_ITEM_CLASS	43
2.84.1	Message	43
2.84.2	Description	43
2.84.3	Resolution	43
2.85	-117505 ERR_REQUEST_PARAMETER_BAD_NAME	43
2.85.1	Message	43
2.85.2	Description	43
2.85.3	Resolution	43
2.86	-117506 ERR_REQUEST_TH_NO_INSTANCE_NAME	44
2.86.1	Message	44
2.86.2	Description	44
2.86.3	Resolution	44
2.87	-117507 ERR_REQUEST_EXPIRED	44
2.87.1	Message	44
2.87.2	Description	44
2.87.3	Resolution	44
2.88	-117508 ERR_REQUEST_UNKNOWN_ACTION	44
2.88.1	Message	44
2.88.2	Description	45
2.88.3	Resolution	45
2.89	-117509 ERR_REQUEST_UNKNOWN_TYPE	45
2.89.1	Message	45
2.89.2	Description	45
2.89.3	Resolution	45
2.90	-117510 ERR_REQUEST_FU_BAD_MAX_SIZE	45
2.90.1	Message	45
2.90.2	Description	46
2.90.3	Resolution	46
2.91	-117511 ERR_REQUEST_FU_BAD_THRESHOLD_SIZE	46
2.91.1	Message	46
2.91.2	Description	46
2.91.3	Resolution	46
2.92	-117512 ERR_REQUEST_FU_BAD_PATH	46
2.92.1	Message	47
2.92.2	Description	47
2.92.3	Resolution	47
2.93	-117513 ERR_REQUEST_MERGE_FIELDS	47
2.93.1	Message	47
2.93.2	Description	47
2.93.3	Resolution	47
2.94	-117514 ERR_REQUEST_MISSING_CONTEXT	48
2.94.1	Message	48
2.94.2	Description	48
2.94.3	Resolution	48
2.95	-117515 ERR_REQUEST_BASE_64_DECODE	48
2.95.1	Message	48

2.95.2 Description	48
2.95.3 Resolution	48
2.96 -117516 ERR_REQUEST_BAD_COMPOSITE_TYPE	49
2.96.1 Message	49
2.96.2 Description	49
2.96.3 Resolution	49
2.97 -117517 ERR_REQUEST_VALIDATION_FAILED	49
2.97.1 Message	49
2.97.2 Description	49
2.97.3 Resolution	50
2.98 -117519 ERR_REQUEST_ENCODING_NOT_SUPPORTED	50
2.98.1 Message	50
2.98.2 Description	50
2.98.3 Resolution	50
2.99 -117520 ERR_REQUEST_XSS_RPU_DETECTED	50
2.99.1 Message	50
2.99.2 Description	50
2.99.3 Resolution	50
2.100 -117550 ERR_REQUEST_METADATA_CORRUPT	50
2.100.1 Message	51
2.100.2 Description	51
2.100.3 Resolution	51
2.101 -117551 ERR_REQUEST_INVALID_FORM_TARGET	51
2.101.1 Message	51
2.101.2 Description	51
2.101.3 Resolution	51
2.102 -117600 ERR_REQUEST_INVALID_RECENT_ITEM	51
2.102.1 Message	51
2.102.2 Description	52
2.102.3 Resolution	52
2.103 -118000 ERR_DOC_XML_LOAD_FAILED	52
2.103.1 Message	52
2.103.2 Description	52
2.103.3 Resolution	52
2.104 -118001 ERR_DOC_XSL_LOAD_FAILED	52
2.104.1 Message	52
2.104.2 Description	53
2.104.3 Resolution	53
2.105 -119000 ERR_EJB_CONN_PROPERTY_MISSING	53
2.105.1 Message	53
2.105.2 Description	53
2.105.3 Resolution	53
2.106 -119001 ERR_EJB_NAMING_EXCEPTION	53
2.106.1 Message	53
2.106.2 Description	54
2.106.3 Resolution	54
2.107 -119002 ERR_EJB_NAMING_COMM_EXCEPTION	54
2.107.1 Message	54
2.107.2 Description	54

2.107.3 Resolution	54
2.108 -119003 ERR_EJB_REMOTE_EXCEPTION	54
2.108.1 Message	54
2.108.2 Description	54
2.108.3 Resolution	54
2.109 -119004 ERR_EJB_NO_CALLBACK_OBJECT	55
2.109.1 Message	55
2.109.2 Description	55
2.109.3 Resolution	55
2.110 -120000 ERR_CANNOT_READ_CONFIG_FILE	55
2.110.1 Message	55
2.110.2 Description	55
2.110.3 Resolution	55
2.111 -120001 ERR_REQUIRED_PARAM_MISSING	55
2.111.1 Message	55
2.111.2 Description	56
2.111.3 Resolution	56
2.112 -121000 ERR_CT_LOAD_NO_CT_NAME	56
2.112.1 Message	56
2.112.2 Description	56
2.112.3 Resolution	56
2.113 -121001 ERR_CT_LOAD_NO_LOCALE	56
2.113.1 Message	56
2.113.2 Description	56
2.113.3 Resolution	56
2.114 -121002 ERR_CT_CODE_NOT_FOUND	57
2.114.1 Message	57
2.114.2 Description	57
2.114.3 Resolution	57
2.115 -121003 ERR_CT_CODE_NAME_ERROR	57
2.115.1 Message	57
2.115.2 Description	57
2.115.3 Resolution	57
2.116 -121004 ERR_CT_LOAD_CHILD_FAILED	58
2.116.1 Message	58
2.116.2 Description	58
2.116.3 Resolution	58
2.117 -121005 ERR_CT_LOAD_SELECTED_CODES_FAILED	58
2.117.1 Message	58
2.117.2 Description	59
2.117.3 Resolution	59
2.118 -121006 ERR_CT_LOAD_NO_PARENT_CODE	59
2.118.1 Message	59
2.118.2 Description	59
2.118.3 Resolution	59
2.119 -121007 ERR_CT_LOAD_NO_SELECTED_CODE	59
2.119.1 Message	59
2.119.2 Description	60
2.119.3 Resolution	60

2.120 -121010 ERR_CT_NOT_FOUND	60
2.120.1 Message	60
2.120.2 Description	60
2.120.3 Resolution	60
2.121 -121100 ERR_RES_LOAD_FAILED	61
2.121.1 Message	61
2.121.2 Description	61
2.121.3 Resolution	61
2.122 -121101 ERR_RES_ENCODING_INVALID	61
2.122.1 Message	61
2.122.2 Description	61
2.122.3 Resolution	62
2.123 -121102 ERR_RES_TYPE_OR_DISP_INVALID	62
2.123.1 Message	62
2.123.2 Description	62
2.123.3 Resolution	62
2.124 -121120 ERR_RES_PROP_NOT_FOUND	62
2.124.1 Message	62
2.124.2 -121122 ERR_PROP_NOT_FOUND	63
2.124.3 Description	63
2.124.4 Resolution	63
2.125 -121121 ERR_RES_PROPS_LOAD_FAILED	63
2.125.1 Message	63
2.125.2 Description	63
2.125.3 Resolution	64
2.126 -121150 ERR_RES_SERVLET_NO_RES_NAME	64
2.126.1 Message	64
2.126.2 Description	64
2.126.3 Resolution	64
2.127 -121151 ERR_RES_SERVLET_NO_PROP_RES_NAME	64
2.127.1 Message	64
2.127.2 Description	64
2.127.3 Resolution	65
2.128 -121152 ERR_RES_SERVLET_FAILED	65
2.128.1 Message	65
2.128.2 Description	65
2.128.3 Resolution	65
2.129 -121153 ERR_RES_SERVLET_INTERNAL	65
2.129.1 Message	65
2.129.2 Description	66
2.129.3 Resolution	66
2.130 -121154 ERR_RES_SERVLET_CONTENT_ERROR	66
2.130.1 Message	66
2.130.2 Description	66
2.130.3 Resolution	66
2.131 -1212010 ERR_PATH_SERVLET_FAILED	66
2.131.1 Message	67
2.131.2 Description	67
2.131.3 Resolution	67

2.132 -1212001 ERR_PATH_SERVLET_NO_PATH	67
2.132.1 Message	67
2.132.2 Description	67
2.132.3 Resolution	67
2.133 -12120012 ERR_PATH_SERVLET_UNSUPPORTED_PATH	67
2.133.1 Message	68
2.133.2 Description	68
2.133.3 Resolution	68
2.134 -121500 ERR_PLUG_IN_NO_NAME	68
2.134.1 Message	68
2.134.2 Description	68
2.134.3 Resolution	68
2.135 -121501 ERR_PLUG_IN_UNNAMED	68
2.135.1 Message	68
2.135.2 Description	69
2.135.3 Resolution	69
2.136 -121502 ERR_PLUG_IN_UNIDENTIFIED	69
2.136.1 Message	69
2.136.2 Description	69
2.136.3 Resolution	69
2.137 -121503 ERR_PLUG_IN_WRONG_TYPE	69
2.137.1 Message	69
2.137.2 Description	70
2.137.3 Resolution	70
2.138 -121504 ERR_PLUG_IN_MISMATCH	70
2.138.1 Message	70
2.138.2 Description	71
2.138.3 Resolution	71
2.139 -121505 ERR_PLUG_IN_INACCESSIBLE	71
2.139.1 Message	71
2.139.2 Description	71
2.139.3 Resolution	71
2.140 -121506 ERR_PLUG_IN_ABSTRACT	72
2.140.1 Message	72
2.140.2 Description	72
2.140.3 Resolution	72
2.141 -121507 ERR_PLUG_IN_NOT_FOUND	72
2.141.1 Message	72
2.141.2 Description	72
2.141.3 Resolution	72
2.142 -121508 ERR_PLUG_IN_NO_PLUG_IN	73
2.142.1 Message	73
2.142.2 Description	73
2.142.3 Resolution	73
2.143 -121509 ERR_PLUG_IN_NO_TARGET	73
2.143.1 Message	73
2.143.2 Description	73
2.143.3 Resolution	73
2.144 -121510 ERR_PLUG_IN_PURPOSE_DUPLICATE	74

2.144.1	Message	74
2.144.2	Description	74
2.144.3	Resolution	74
2.145	-121511 ERR_PLUG_IN_PURPOSE_BAD_REF	74
2.145.1	Message	74
2.145.2	Description	74
2.145.3	Resolution	75
2.146	-121512 ERR_PLUG_IN_PURPOSE_UNDEFINED	75
2.146.1	Message	75
2.146.2	Description	75
2.146.3	Resolution	75
2.147	-121513 ERR_PLUG_IN_PURPOSE_BAD_ATTRS	75
2.147.1	Message	75
2.147.2	Description	76
2.147.3	Resolution	76
2.148	-121514 ERR_PLUG_IN_PURPOSE_BAD_CLASS	76
2.148.1	Message	76
2.148.2	Description	76
2.148.3	Resolution	76
2.149	-121515 ERR_PLUG_IN_PURPOSE_BAD_REUSE	76
2.149.1	Message	76
2.149.2	Description	77
2.149.3	Resolution	77
2.150	-121520 ERR_PLUG_IN_INIT_PARSE_FAILED	77
2.150.1	Message	77
2.150.2	Description	77
2.150.3	Resolution	77
2.151	-121521 ERR_PLUG_IN_PARSER_INIT_FAILED	78
2.151.1	Message	78
2.151.2	Description	78
2.151.3	Resolution	78
2.152	-121522 ERR_PLUG_IN_RESOURCE_NOT_FOUND	78
2.152.1	Message	78
2.152.2	Description	78
2.152.3	Resolution	79
2.153	-121523 ERR_PLUG_IN_UNKNOWN_SCHEMA	79
2.153.1	Message	79
2.153.2	Description	79
2.153.3	Resolution	79
2.154	-121524 ERR_PLUG_IN_INIT_FAILED	79
2.154.1	Message	80
2.154.2	Description	80
2.154.3	Resolution	80
2.155	-121525 ERR_PLUG_IN_NO_CONFIGS	80
2.155.1	Message	80
2.155.2	Description	80
2.155.3	Resolution	80
2.156	-121526 ERR_PLUG_IN_NO_PROPERTY	80
2.156.1	Message	80

2.156.2 Description	81
2.156.3 Resolution	81
2.157 -121527 ERR_PLUG_IN_NO_LOCAL_PLUG_IN	81
2.157.1 Message	81
2.157.2 Description	81
2.157.3 Resolution	81
2.158 -121528 ERR_PLUG_IN_BAD_LOCAL_PLUG_IN	81
2.158.1 Message	82
2.158.2 Description	82
2.158.3 Resolution	82
2.159 -121529 ERR_PLUG_IN_REJECTED_CONFIG	82
2.159.1 Message	82
2.159.2 Description	82
2.159.3 Resolution	83
2.160 -121530 ERR_PLUG_IN_REJECTED_DATA	83
2.160.1 Message	83
2.160.2 Description	83
2.160.3 Resolution	83
2.161 -121600 ERR_PATH_PLUG_IN_INVALID	83
2.161.1 Message	83
2.161.2 Description	84
2.161.3 Resolution	84
2.162 -121601 ERR_PATH_PLUG_IN_NAME_INVALID	84
2.162.1 Message	84
2.162.2 Description	84
2.162.3 Resolution	84
2.163 -121602 ERR_PATH_RESOLVER_NOT_FOUND	84
2.163.1 Message	84
2.163.2 Description	85
2.163.3 Resolution	85
2.164 -121603 ERR_PATH_BAD_NAME_OR_PURPOSE	85
2.164.1 Message	85
2.164.2 Description	85
2.164.3 Resolution	85
2.165 -121604 ERR_PATH_NO_PATH_FACTORY	85
2.165.1 Message	85
2.165.2 Description	85
2.165.3 Resolution	86
2.166 -121605 ERR_PATH_NO_PATHS	86
2.166.1 Message	86
2.166.2 Description	86
2.166.3 Resolution	86
2.167 -121606 ERR_PATH_INIT_FACTORY_FAILED	86
2.167.1 Message	86
2.167.2 Description	86
2.167.3 Resolution	86
2.168 -121607 ERR_PATH_INIT_FAILED	87
2.168.1 Message	87
2.168.2 Description	87

2.168.3 Resolution	87
2.169 -121608 ERR_PATH_INIT_PARSE_FAILED	87
2.169.1 Message	87
2.169.2 Description	87
2.169.3 Resolution	87
2.170 -121609 ERR_PATH_INVALID_PREFIX	88
2.170.1 Message	88
2.170.2 Description	88
2.170.3 Resolution	88
2.171 -121610 ERR_PATH_NO_PREFIX	88
2.171.1 Message	88
2.171.2 Description	88
2.171.3 Resolution	88
2.172 -121611 ERR_PATH_NO_RESOLVER	89
2.172.1 Message	89
2.172.2 Description	89
2.172.3 Resolution	89
2.173 -121612 ERR_PATH_ACCESS_DENIED	89
2.173.1 Message	89
2.173.2 Description	89
2.173.3 Resolution	89
2.174 -121613 ERR_PATH_ACCESS_INVALID	90
2.174.1 Message	90
2.174.2 Description	90
2.174.3 Resolution	90
2.175 -121614 ERR_PATH_ACCESS_FAILED	90
2.175.1 Message	90
2.175.2 Description	91
2.175.3 Resolution	91
2.176 -121615 ERR_PATH_RESOLUTION_FAILED	91
2.176.1 Message	91
2.176.2 Description	91
2.176.3 Resolution	91
2.177 -121616 ERR_PATH_DATA_NOT_FOUND	92
2.177.1 Message	92
2.177.2 Description	92
2.177.3 Resolution	92
2.178 -121617 ERR_PATH_EXECUTE_INVALID	92
2.178.1 Message	92
2.178.2 Description	92
2.178.3 Resolution	93
2.179 -121618 ERR_PATH_EXECUTE_FAILED	93
2.179.1 Message	93
2.179.2 Description	93
2.179.3 Resolution	93
2.180 -121650 ERR_PATH_XPATH_BAD_STEP	93
2.180.1 Message	93
2.180.2 Description	94
2.180.3 Resolution	94

2.181 -121651 ERR_PATH_XPATH_BAD_FUNCTION	94
2.181.1 Message	94
2.181.2 Description	94
2.181.3 Resolution	94
2.182 -121652 ERR_PATH_XPATH_BAD_INDEX	94
2.182.1 Message	94
2.182.2 Description	95
2.182.3 Resolution	95
2.183 -121653 ERR_PATH_XPATH_BAD_DOC	95
2.183.1 Message	95
2.183.2 Description	95
2.183.3 Resolution	95
2.184 -121701 ERR_DOMAIN_NO_CONVERTER	95
2.184.1 Message	95
2.184.2 Description	96
2.184.3 Resolution	96
2.185 -121702 ERR_DOMAIN_NO_COMPARATOR	96
2.185.1 Message	96
2.185.2 Description	96
2.185.3 Resolution	96
2.186 -121703 ERR_DOMAIN_NO_RENDERER	96
2.186.1 Message	96
2.186.2 Description	97
2.186.3 Resolution	97
2.187 -121704 ERR_DOMAIN_NO_MARSHAL	97
2.187.1 Message	97
2.187.2 Description	97
2.187.3 Resolution	97
2.188 -121705 ERR_DOMAIN_NO_DEFAULT	97
2.188.1 Message	97
2.188.2 Description	98
2.188.3 Resolution	98
2.189 -121706 ERR_DOMAIN_NULL_DEFAULT	98
2.189.1 Message	98
2.189.2 Description	98
2.189.3 Resolution	98
2.190 -121707 ERR_DOMAIN_OPTION_INVALID_VALUE	98
2.190.1 Message	98
2.190.2 Description	99
2.190.3 Resolution	99
2.191 -121708 ERR_DOMAIN_NO_CODE_TABLE	99
2.191.1 Message	99
2.191.2 Description	99
2.191.3 Resolution	99
2.192 -121710 ERR_DOMAIN_NO_DOMAIN_FACTORY	100
2.192.1 Message	100
2.192.2 Description	100
2.192.3 Resolution	100
2.193 -121711 ERR_DOMAIN_NO_OPTIONS	100

2.193.1	Message	100
2.193.2	Description	100
2.193.3	Resolution	100
2.194	-121712 ERR_DOMAIN_NO_DOMAINS	100
2.194.1	Message	100
2.194.2	Description	100
2.194.3	Resolution	101
2.195	-121713 ERR_DOMAIN_NO_DOMAIN	101
2.195.1	Message	101
2.195.2	Description	101
2.195.3	Resolution	101
2.196	-121714 ERR_DOMAIN_DUPLICATE	101
2.196.1	Message	101
2.196.2	Description	101
2.196.3	Resolution	102
2.197	-121715 ERR_DOMAIN_INVALID_NAME	102
2.197.1	Message	102
2.197.2	Description	102
2.197.3	Resolution	102
2.198	-121716 ERR_DOMAIN_NO_NAME	102
2.198.1	Message	102
2.198.2	Description	102
2.198.3	Resolution	103
2.199	-121717 ERR_DOMAIN_NOT_FOUND	103
2.199.1	Message	103
2.199.2	Description	103
2.199.3	Resolution	103
2.200	-121720 ERR_DOMAIN_BAD_NAME_OR_PURPOSE	103
2.200.1	Message	103
2.200.2	Description	104
2.200.3	Resolution	104
2.201	-121721 ERR_DOMAIN_NOT_CONFIGURABLE	104
2.201.1	Message	104
2.201.2	Description	104
2.201.3	Resolution	104
2.202	-121722 ERR_DOMAIN_PLUG_IN_FAILURE	104
2.202.1	Message	104
2.202.2	Description	104
2.202.3	Resolution	105
2.203	-121723 ERR_DOMAIN_PLUG_IN_INVALID	105
2.203.1	Message	105
2.203.2	Description	105
2.203.3	Resolution	105
2.204	-121724 ERR_DOMAIN_CHILD_INVALID	105
2.204.1	Message	105
2.204.2	Description	105
2.204.3	Resolution	106
2.205	-121725 ERR_DOMAIN_INIT_FACTORY_FAILED	106
2.205.1	Message	106

2.205.2 Description	106
2.205.3 Resolution	106
2.206 -121726 ERR_DOMAIN_INIT_FAILED	106
2.206.1 Message	106
2.206.2 Description	106
2.206.3 Resolution	107
2.207 -121727 ERR_DOMAIN_INIT_PARSE_FAILED	107
2.207.1 Message	107
2.207.2 Description	107
2.207.3 Resolution	107
2.208 -121750 ERR_DOMAIN_MARSHAL_FATAL	107
2.208.1 Message	107
2.208.2 Description	108
2.208.3 Resolution	108
2.209 -121751 ERR_DOMAIN_MARSHAL_FAILED	108
2.209.1 Message	108
2.209.2 Description	108
2.209.3 Resolution	108
2.210 -121752 ERR_DOMAIN_MARSHAL_XPATH_BAD_NODE	109
2.210.1 Message	109
2.210.2 Description	109
2.210.3 Resolution	109
2.211 -121800 ERR_RENDER_INVALID_FORM_FIELD	109
2.211.1 Message	109
2.211.2 Description	110
2.211.3 Resolution	110
2.212 -121801 ERR_RENDER_INVALID_FIELD_TARGET	110
2.212.1 Message	110
2.212.2 Description	110
2.212.3 Resolution	110
2.213 -121802 ERR_RENDER_EMPTY_CONTAINER	110
2.213.1 Message	110
2.213.2 Description	111
2.213.3 Resolution	111
2.214 -121803 ERR_RENDER_NO_STYLE_OR_DOMAIN	111
2.214.1 Message	111
2.214.2 Description	111
2.214.3 Resolution	111
2.215 -121804 ERR_RENDER_LOCAL_REJECTED_DATA	111
2.215.1 Message	112
2.215.2 Description	112
2.215.3 Resolution	112
2.216 -121805 ERR_RENDER_INITIAL_VALUE_FAILURE	112
2.216.1 Message	112
2.216.2 Description	112
2.216.3 Resolution	113
2.217 -121806 ERR_RENDER_PROPERTY_RESOURCE_ID_NOT_SPECIFIED	113
2.217.1 Message	113
2.217.2 Description	113

2.218 -121807 ERR_RENDER_PROPERTY_MUST_BE_NUMERIC	113
2.218.1 Message	113
2.218.2 Description	114
2.218.3 Resolution	114
2.219 -121808 ERR_RENDER_PROPERTY_MUST_BE_GREATER_THAN_ZERO	114
2.219.1 Message	114
2.219.2 Description	114
2.219.3 Resolution	115
2.220 -121810 ERR_RENDER_FAILED	115
2.220.1 Message	115
2.220.2 Description	115
2.220.3 Resolution	115
2.221 -121820 ERR_RENDER_CT_NOT_HIERARCHY	115
2.221.1 Message	115
2.221.2 Description	115
2.221.3 Resolution	116
2.222 -121900 ERR_STYLE_PLUG_IN_INVALID	116
2.222.1 Message	116
2.222.2 Description	116
2.222.3 Resolution	116
2.223 -121901 ERR_STYLE_PLUG_IN_NAME_INVALID	116
2.223.1 Message	116
2.223.2 Description	116
2.223.3 Resolution	117
2.224 -121902 ERR_STYLE_NO_RENDERER	117
2.224.1 Message	117
2.224.2 Description	117
2.224.3 Resolution	117
2.225 -121903 ERR_STYLE_NO_NAME	117
2.225.1 Message	117
2.225.2 Description	117
2.225.3 Resolution	117
2.226 -121904 ERR_STYLE_NOT_FOUND	118
2.226.1 Message	118
2.226.2 Description	118
2.226.3 Resolution	118
2.227 -121905 ERR_STYLE_BAD_NAME_OR_PURPOSE	118
2.227.1 Message	118
2.227.2 Description	118
2.227.3 Resolution	118
2.228 -121906 ERR_STYLE_NO_STYLE_FACTORY	119
2.228.1 Message	119
2.228.2 Description	119
2.228.3 Resolution	119
2.229 -121907 ERR_STYLE_NO_STYLES	119
2.229.1 Message	119
2.229.2 Description	119
2.229.3 Resolution	119

2.230 -121908 ERR_STYLE_INIT_FAILED	119
2.230.1 Message	119
2.230.2 Description	119
2.230.3 Resolution	120
2.231 -121909 ERR_STYLE_INIT_PARSE_FAILED	120
2.231.1 Message	120
2.231.2 Description	120
2.231.3 Resolution	120
2.232 -122100 ERR_CONV_PARSE_INVALID	120
2.232.1 Message	120
2.232.2 Description	121
2.232.3 Resolution	121
2.233 -122101 ERR_CONV_PARSE_FAILED	121
2.233.1 Message	121
2.233.2 Description	121
2.233.3 Resolution	121
2.234 -122102 ERR_CONV_PARSE_FAILED_DATE	121
2.234.1 Message	121
2.234.2 Description	122
2.234.3 Resolution	122
2.235 -122103 ERR_CONV_PARSE_FAILED_DATE_TIME	122
2.235.1 Message	122
2.235.2 Description	122
2.235.3 Resolution	122
2.236 -122104 ERR_CONV_PARSE_FAILED_TIME	122
2.236.1 Message	122
2.236.2 Description	123
2.236.3 Resolution	123
2.237 -122105 ERR_CONV_PARSE_FAILED_MONEY	123
2.237.1 Message	123
2.237.2 Description	123
2.237.3 Resolution	123
2.238 -122106 ERR_CONV_PARSE_FAILED_CHAR	123
2.238.1 Message	123
2.238.2 Description	124
2.238.3 Resolution	124
2.239 -122107 ERR_CONV_PARSE_FAILED_INT	124
2.239.1 Message	124
2.239.2 Description	124
2.239.3 Resolution	124
2.240 -122108 ERR_CONV_PARSE_FAILED_FLOAT	124
2.240.1 Message	124
2.240.2 Description	124
2.240.3 Resolution	125
2.241 -122109 ERR_CONV_PARSE_FAILED_BOOL	125
2.241.1 Message	125
2.241.2 Description	125
2.241.3 Resolution	125
2.242 -122110 ERR_CONV_PARSE_FAILED_CT	125

2.242.1	Message	125
2.242.2	Description	125
2.242.3	Resolution	126
2.243	-122111 ERR_CONV_PARSE_FAILED_BLOB	126
2.243.1	Message	126
2.243.2	Description	126
2.243.3	Resolution	126
2.244	-122112 ERR_CONV_PARSE_FAILED_TIME_EX	126
2.244.1	Message	126
2.244.2	Description	127
2.244.3	Resolution	127
2.245	-122121 ERR_CONV_OVERFLOW	127
2.245.1	Message	127
2.245.2	Description	127
2.245.3	Resolution	127
2.246	-122122 ERR_CONV_OUT_OF_RANGE	127
2.246.1	Message	128
2.246.2	Description	128
2.246.3	Resolution	128
2.247	-122123 ERR_CONV_TOO_HIGH	128
2.247.1	Message	128
2.247.2	Description	128
2.247.3	Resolution	128
2.248	-122124 ERR_CONV_TOO_LOW	129
2.248.1	Message	129
2.248.2	Description	129
2.248.3	Resolution	129
2.249	-122125 ERR_CONV_WRONG_SIZE	129
2.249.1	Message	129
2.249.2	Description	129
2.249.3	Resolution	130
2.250	-122126 ERR_CONV_TOO_SHORT	130
2.250.1	Message	130
2.250.2	Description	130
2.250.3	Resolution	130
2.251	-122127 ERR_CONV_TOO_LONG	130
2.251.1	Message	130
2.251.2	Description	131
2.251.3	Resolution	131
2.252	-122128 ERR_CONV_NO_MATCH	131
2.252.1	Message	131
2.252.2	Description	131
2.252.3	Resolution	131
2.253	-122129 ERR_CONV_TOO_LARGE	131
2.253.1	Message	131
2.253.2	Description	132
2.253.3	Resolution	132
2.254	-122130 ERR_CONV_INVALID_TIME_ZONE	132
2.254.1	Message	132

2.254.2 Description	132
2.254.3 Resolution	132
2.255 -122202 ERR_CONV_GENERIC_PARSE_FAILED	132
2.255.1 Message	132
2.255.2 Description	132
2.255.3 Resolution	133
2.256 -122203 ERR_CONV_MESSAGE_L10N_FAILURE	133
2.256.1 Message	133
2.256.2 Description	133
2.256.3 Resolution	133
2.257 -122204 ERR_CONV_FMT_WRONG_TYPE	133
2.257.1 Message	133
2.257.2 Description	134
2.257.3 Resolution	134
2.258 -122205 ERR_CONV_FMT_NULL_VALUE	134
2.258.1 Message	134
2.258.2 Description	134
2.258.3 Resolution	135
2.259 -122206 ERR_CONV_FMTGEN_WRONG_TYPE	135
2.259.1 Message	135
2.259.2 Description	135
2.259.3 Resolution	135
2.260 -122207 ERR_CONV_FMTGEN_NULL_VALUE	135
2.260.1 Message	136
2.260.2 Description	136
2.260.3 Resolution	136
2.261 -122208 ERR_CONV_FMT_FAILED	136
2.261.1 Message	136
2.261.2 Description	136
2.261.3 Resolution	136
2.262 -122209 ERR_CONV_FMT_BAD_VALUE_FORMAT	136
2.262.1 Message	136
2.262.2 Description	137
2.262.3 Resolution	137
2.263 -122210 ERR_CONV_CUSTOM_METHOD_FATAL	137
2.263.1 Message	137
2.263.2 Description	137
2.263.3 Resolution	137
2.264 -122211 ERR_CONV_CUSTOM_METHOD_FAILED	137
2.264.1 Message	137
2.264.2 Description	138
2.264.3 Resolution	138
2.265 -123000 ERR_PH_NOT_FOUND	138
2.265.1 Message	138
2.265.2 Description	138
2.265.3 Resolution	138
2.266 -123001 ERR_PH_INVALID	138
2.266.1 Message	138
2.266.2 Description	139

2.266.3 Resolution	139
2.267 -123002 ERR_PH_APP_UNDEFINED	139
2.267.1 Message	139
2.267.2 Description	139
2.267.3 Resolution	139
2.268 -123003 ERR_PH_APP_NOT_FOUND	139
2.268.1 Message	139
2.268.2 Description	139
2.268.3 Resolution	140
2.269 -130000 ERR_BAD_SVR_MSG_FORMAT	140
2.269.1 Message	140
2.269.2 Description	140
2.269.3 Resolution	140
2.270 -130002 ERR_SVR_EXCEPTION	140
2.270.1 Message	140
2.270.2 Description	140
2.270.3 Resolution	140
2.271 -130003 ERR_DECISION_ID_CONFIG	140
2.271.1 Message	141
2.271.2 Description	141
2.271.3 Resolution	141
2.272 -131001 ERR_MSG_INVALID	141
2.272.1 Message	141
2.272.2 Description	141
2.272.3 Resolution	141
2.273 -131002 ERR_MSG_INVALID_PLACEHOLDER	141
2.273.1 Message	141
2.273.2 Description	142
2.273.3 Resolution	142
2.274 -131003 ERR_MSG_NO_ARGUMENTS	142
2.274.1 Message	142
2.274.2 Description	142
2.274.3 Resolution	142
2.275 -131004 ERR_MSG_INVALID_INDEX	142
2.275.1 Message	142
2.275.2 Description	143
2.275.3 Resolution	143
2.276 -131005 ERR_MSG_INVALID_TYPE_CODE	143
2.276.1 Message	143
2.276.2 Description	143
2.276.3 Resolution	143
2.277 -131006 ERR_MSG_NOT_CUSTOM_MESSAGE	143
2.277.1 Message	143
2.277.2 Description	144
2.277.3 Resolution	144
2.278 -131007 ERR_MSG_NOT_UIM_VALIDATION_MESSAGE	144
2.278.1 Message	144
2.278.2 Description	144
2.278.3 Resolution	144

2.279 -131008 ERR_MSG_BAD_UIM_VALIDATION_FORMAT	144
2.279.1 Message	144
2.279.2 Description	144
2.279.3 Resolution	144
2.280 -131009 ERR_MSG_INVALID_ERROR_NAME	145
2.280.1 Message	145
2.280.2 Description	145
2.280.3 Resolution	145
2.281 -132000 ERR_UNKNOWN	145
2.281.1 Message	145
2.281.2 Description	145
2.281.3 Resolution	145
2.282 -133000 ERR_APP_CONFIG_PARAM_MISSING	145
2.282.1 Message	146
2.282.2 Description	146
2.282.3 Resolution	146
2.283 -133001 ERR_APP_CONFIG_VERSION_ERROR	146
2.283.1 Message	146
2.283.2 Description	146
2.283.3 Resolution	146
2.284 -134000 ERR_CARRIER	146
2.284.1 Message	146
2.284.2 Description	146
2.284.3 Resolution	147
2.285 -135000 ERR_TAB_CONFIG	147
2.285.1 Message	147
2.285.2 Description	147
2.285.3 Resolution	147
2.286 -135001 ERR_TAB_VALIDATION_FAILED	147
2.286.1 Message	147
2.286.2 Description	147
2.286.3 Resolution	147
2.287 -135002 ERR_TAB_CONFIG_ACCESS_PROBLEM	147
2.287.1 Message	147
2.287.2 Description	147
2.287.3 Resolution	148
2.288 -135003 ERR_TAB_UNKNOWN_CONFIG_TYPE	148
2.288.1 Message	148
2.288.2 Description	148
2.288.3 Resolution	148
2.289 -135004 ERR_TAB_CONFIG_BASE	148
2.289.1 Message	148
2.289.2 Description	148
2.289.3 Resolution	149
2.290 -135005 ERR_TAB_CONFIG_NO_BASE	149
2.290.1 Message	149
2.290.2 Description	149
2.290.3 Resolution	149
2.291 -135006 ERR_TAB_CONFIG_REFRESH_DUPLICATE	149

2.291.1 Message	149
2.291.2 Description	149
2.291.3 Resolution	150
2.292 -135008 ERR_TAB_ID	150
2.292.1 Message	150
2.292.2 Description	150
2.292.3 Resolution	150
2.293 -135009 ERR_TAB_DUPLICATE_ID	150
2.293.1 Message	150
2.293.2 Description	151
2.293.3 Resolution	151
2.294 -135010 ERR_TAB_MISSING_ATTRIBUTE	151
2.294.1 Message	151
2.294.2 Description	151
2.294.3 Resolution	151
2.295 -135011 ERR_TAB_MISSING_NODE	151
2.295.1 Message	151
2.295.2 Description	152
2.295.3 Resolution	152
2.296 -135012 ERR_TAB_MISSING_ATTRIBUTES	152
2.296.1 Message	152
2.296.2 Description	152
2.296.3 Resolution	152
2.297 -135013 ERR_TAB_INCORRECT_ATTRIBUTES	152
2.297.1 Message	152
2.297.2 Description	153
2.297.3 Resolution	153
2.298 -135014 ERR_TAB_NAVIGATION_ID	153
2.298.1 Message	153
2.298.2 Description	153
2.298.3 Resolution	153
2.299 -135015 ERR_TAB_NAVIGATION_ID_FILENAME	153
2.299.1 Message	153
2.299.2 Description	154
2.299.3 Resolution	154
2.300 -135016 ERR_TAB_MISSING_LOADER	154
2.300.1 Message	154
2.300.2 Description	154
2.300.3 Resolution	154
2.301 -135017 ERR_TAB_NAVIGATION_ATTRIBUTES	154
2.301.1 Message	154
2.301.2 Description	155
2.301.3 Resolution	155
2.302 -135018 ERR_TAB_DUPLICATE_LOADER	155
2.302.1 Message	155
2.302.2 Description	155
2.302.3 Resolution	155
2.303 -135019 ERR_TAB_LOADER_COMPONENTS	155
2.303.1 Message	155

2.303.2 Description	156
2.303.3 Resolution	156
2.304 -135020 ERR_TAB_HAS_DYNAMIC_ITEMS_MISSING_LOADER	156
2.304.1 Message	156
2.304.2 Description	156
2.304.3 Resolution	156
2.305 -135021 ERR_TAB_UNKNOWN_CONFIG_ELEMENT	157
2.305.1 Message	157
2.305.2 Description	157
2.305.3 Resolution	157
2.306 -135022 ERR_TAB_DUPLICATE_ATTRIBUTE	157
2.306.1 Message	157
2.306.2 Description	157
2.306.3 Resolution	158
2.307 -135023 ERR_TAB_CONFIG_NO_INDEX	158
2.307.1 Message	158
2.307.2 Description	158
2.307.3 Resolution	158
2.308 -135024 ERR_TAB_RESOURCE_STORE_ERROR	158
2.308.1 Message	158
2.308.2 Description	158
2.308.3 Resolution	158
2.309 -135025 ERR_TAB_CONFIG_NAVIGATION_FOLDER_IN_FOLDER	159
2.309.1 Message	159
2.310 -135026 ERR_TAB_CONFIG_NAVIGATION_CHILD_IN_LEAF	159
2.310.1 Message	159
2.311 -135027 ERR_TAB_CONFIG_NAVIGATION_DUPLICATE_ID	159
2.311.1 Message	159
2.312 -135028 ERR_TAB_MISSING_TAB_NAME_ATTRIBUTE	160
2.312.1 Message	160
2.312.2 Description	160
2.312.3 Resolution	160
2.313 -135029 ERR_TAB_SUBMENU_EMPTY	160
2.313.1 Message	160
2.313.2 Description	161
2.313.3 Resolution	161
2.314 -135030 ERR_TAB_HAS_NO_CHILD_ELEMENTS	161
2.314.1 Message	161
2.314.2 Description	161
2.314.3 Resolution	161
2.315 -135031 ERR_TAB_HAS_EXTRA_ATTRIBUTE	161
2.315.1 Message	162
2.315.2 Description	162
2.315.3 Resolution	162
2.316 -135032 ERR_TAB_HAS_CHILD_ELEMENTS	162
2.316.1 Message	162
2.316.2 Description	162
2.316.3 Resolution	163
2.317 -135033 ERR_TAB_HAS_EXTRA_CHILD_ELEMENT	163

2.317.1 Message	163
2.317.2 Description	163
2.317.3 Resolution	163
2.318 -135034 ERR_TAB_ELEMENT_ID_ONLY	163
2.318.1 Message	163
2.318.2 Description	164
2.318.3 Resolution	164
2.319 -135035 ERR_EXPAND_LIST_NO_PARAMETER	164
2.319.1 Message	164
2.319.2 Description	164
2.319.3 Resolution	164
2.320 -135036 ERR_TAB_MISSING_OPTIONAL_ATTRIBUTE	164
2.320.1 Message	164
2.320.2 Description	165
2.320.3 Resolution	165
2.321 -135037 ERR_PARENT_ELEMENT_ID_ONLY	165
2.321.1 Message	165
2.321.2 Description	165
2.321.3 Resolution	166
2.322 -136000 ERR_LOCALE_NOT_CONFIGURED	166
2.322.1 Message	166
2.322.2 Description	166
2.322.3 Resolution	166
2.323 -136001 ERR_APP_REQUIRED_ATTRIBUTE_NOT_PRESENT_OR_EMPTY	166
2.323.1 Message	166
2.323.2 Description	167
2.323.3 Resolution	167
2.324	-136002
ERR_APP_APPLICATION_SEARCH_ATTRIBUTES_NOT_REQUIRED	167
2.324.1 Message	167
2.324.2 Description	167
2.324.3 Resolution	168
2.325	-136003
ERR_APP_SEARCH_PAGES_INCORRECT_NUM_DEFAULT_ATTRIBUTE	168
2.325.1 Message	168
2.325.2 Description	168
2.325.3 Resolution	168
2.326 -136004 ERR_APP_SEARCH_PAGE_TYPE_ATTR_VALUE_NOT_UNIQUE	169
2.326.1 Message	169
2.326.2 Description	169
2.326.3 Resolution	169
2.327 -136005 ERR_SEC_CONFIG_BASE	169
2.327.1 Message	170
2.327.2 Description	170
2.327.3 Resolution	170
2.328 -136006 ERR_APP_CONFIG_BASE	170
2.328.1 Message	170

2.328.2 Description	170
2.328.3 Resolution	171
2.329 -136007 ERR_MERGE_APP_CONFIG_DUPLICATE_NODES	171
2.329.1 Message	171
2.329.2 Description	171
2.329.3 Resolution	171
2.330 -136008 ERR_MERGE_APP_SEARCH_NO_TARGET_NODE	171
2.330.1 Message	171
2.330.2 Description	172
2.330.3 Resolution	172
2.331 -136009 ERR_MERGE_APP_SEARCH_PAGE_DUPLICATE_NODE_VALUE	172
2.331.1 Message	172
2.331.2 Description	173
2.331.3 Resolution	173
2.332 -136010 ERR_SSP_DUPLICATE_LEAF_NODE	173
2.332.1 Message	173
2.332.2 Description	173
2.332.3 Resolution	173
2.333 -136011 ERR_SSP_CONFIG_TITLE	174
2.333.1 Message	174
2.333.2 Description	174
2.333.3 Resolution	174
2.334 -136012 ERR_APP_CONFIG_APP_MENU	174
2.334.1 Message	174
2.334.2 Description	175
2.334.3 Resolution	175
2.335 -136013 ERR_APP_CONFIG_ATTRIB_CONFLICT	175
2.335.1 Message	175
2.335.2 Description	175
2.335.3 Resolution	175
2.336 -136014 ERR_SEC_CONFIG_SHORTCUT_PANEL_REF	175
2.336.1 Message	176
2.336.2 Description	176
2.336.3 Resolution	176
2.337 -136015 ERR_APP_ATTRIBUTE_EMPTY	176
2.337.1 Message	176
2.337.2 Description	176
2.337.3 Resolution	177
2.338 -136016 ERR_MULTIPLE_INSTANCE_ELEMENT	177
2.338.1 Message	177
2.338.2 Description	177
2.338.3 Resolution	177
2.339 -136017 ERR_RELATED_ATTR_EMPTY	177
2.339.1 Message	177
2.339.2 Description	178
2.339.3 Resolution	178
2.340 -136018 ERR_FILENAME_ID_MISMATCH	178
2.340.1 Message	178

2.340.2 Description	178
2.340.3 Resolution	178
2.341 -136019 ERR_DUPLICATE_TABS_FOUND	178
2.341.1 Message	178
2.341.2 Description	179
2.341.3 Resolution	179
2.342 -136500 ERR_FILE_DOWNLOAD_CONFIG_MISSING	179
2.342.1 Message	179
2.342.2 Description	179
2.342.3 Resolution	179
2.343 -136501 ERR_BAD_JSON_FORMAT	179
2.343.1 Message	179
2.343.2 Description	179
2.343.3 Resolution	180
Chapter 3 Cúram Generator Error Messages	181
3.1 Objective	181
3.2 Introduction	181
3.3 -120001 ERR_ACTCTL_SUBMIT_NO_ACTION	181
3.3.1 Message	181
3.3.2 Description	181
3.3.3 Resolution	181
3.4 -120002 ERR_ACTCTL_INVALID_CHILD	182
3.4.1 Message	182
3.4.2 Description	182
3.4.3 Resolution	182
3.5 -120003 ERR_ACTCTL_INVALID_DEFAULT	182
3.5.1 Message	182
3.5.2 Description	182
3.5.3 Resolution	182
3.6 -120004 ERR_ACTCTL_MULTIPLE_SUBMITS	182
3.6.1 Message	182
3.6.2 Description	182
3.6.3 Resolution	183
3.7 -120005 ERR_ACTCTL_INVALID_LINK	183
3.7.1 Message	183
3.7.2 Description	183
3.7.3 Resolution	183
3.8 -120006 ERR_ACTCTL_CLIP_MISSING_ATT	183
3.8.1 Message	183
3.8.2 Description	183
3.8.3 Resolution	183
3.9 -120007 ERR_ACTCTL_CLIP_MULTIPLE_SOURCES	183
3.9.1 Message	183
3.9.2 Description	184
3.9.3 Resolution	184
3.10 -120008 ERR_ACTCTL_INVALID_SUBMIT	184
3.10.1 Message	184
3.10.2 Description	184

3.10.3 Resolution	184
3.11 -120009 ERR_ACTCTL_FE_SOURCE_ACTION	184
3.11.1 Message	184
3.11.2 Description	184
3.11.3 Resolution	185
3.12 -120010 ERR_ACTCTL_INVALID_TYPE_DISMISS	185
3.12.1 Message	185
3.12.2 Description	185
3.12.3 Resolution	185
3.13 -120011 ERR_ACTCTL_INVALID_LINK_CONDITION	185
3.13.1 Message	185
3.13.2 Description	185
3.13.3 Resolution	185
3.14 -120025 ERR_ADDRESS_FORMAT_NOT_FOUND	186
3.14.1 Message	186
3.14.2 Description	186
3.14.3 Resolution	186
3.15 -120030 ERR_ATTRIBUTE_INVALID_VALUE	186
3.15.1 Message	186
3.15.2 Description	186
3.15.3 Resolution	186
3.16 -120031 ERR_ATTRIBUTE_UNKNOWN	186
3.16.1 Message	186
3.16.2 Description	187
3.16.3 Resolution	187
3.17 -120040 ERR_BEAN_META_PROP_DIR	187
3.17.1 Message	187
3.17.2 Description	187
3.17.3 Resolution	187
3.18 -120041 ERR_BEAN_NOT_EXIST	187
3.18.1 Message	187
3.18.2 Description	187
3.18.3 Resolution	188
3.19 -120050 ERR_CLUSTER_INVALID_ACTSET	188
3.19.1 Message	188
3.19.2 Description	188
3.19.3 Resolution	188
3.20 -120051 ERR_CLUSTER_INVALID_ELEMENTS	188
3.20.1 Message	188
3.20.2 Description	188
3.20.3 Resolution	188
3.21 -120060 ERR_CONNECT_INVALID_NAME	188
3.21.1 Message	188
3.21.2 Description	189
3.21.3 Resolution	189
3.22 -120061 ERR_CONNECT_INVALID_TARGET	189
3.22.1 Message	189
3.22.2 Description	189
3.22.3 Resolution	189

3.23	-120062 ERR_CONNECT_MULTIPLE_SOURCES	189
	3.23.1 Message	189
	3.23.2 Description	189
	3.23.3 Resolution	189
3.24	-120063 ERR_CONNECT_MULTIPLE_TARGETS	190
	3.24.1 Message	190
	3.24.2 Description	190
	3.24.3 Resolution	190
3.25	-120064 ERR_CONNECT_MULTIPLE_INITIALS	190
	3.25.1 Message	190
	3.25.2 Description	190
	3.25.3 Resolution	190
3.26	-120065 ERR_CONNECT_UNDECLARED_NAME	190
	3.26.1 Message	190
	3.26.2 Description	190
	3.26.3 Resolution	191
3.27	-120066 ERR_CONNECT_INVALID_NUM_FIELDS	191
	3.27.1 Message	191
	3.27.2 Description	191
	3.27.3 Resolution	191
3.28	-120067 ERR_CONNECT_FLD_ONE_EP	191
	3.28.1 Message	191
	3.28.2 Description	191
	3.28.3 Resolution	191
3.29	-120068 ERR_CONNECT_INVALID_PAGE_PARAM	192
	3.29.1 Message	192
	3.29.2 Description	192
	3.29.3 Resolution	192
3.30	-120069 ERR_CONNECT_INCOMPATIBLE_LIST	192
	3.30.1 Message	192
	3.30.2 Description	192
	3.30.3 Resolution	192
3.31	-120070 ERR_CONNECT_PAGE_PARAM_AND_TARGET	193
	3.31.1 Message	193
	3.31.2 Description	193
	3.31.3 Resolution	193
3.32	-120071 ERR_CONNECT_MISSING_ENDPOINT	193
	3.32.1 Message	193
	3.32.2 Description	193
	3.32.3 Resolution	193
3.33	-120072 ERR_CONNECT_INVALID_CHILD	193
	3.33.1 Message	193
	3.33.2 Description	193
	3.33.3 Resolution	194
3.34	-120073 ERR_CONNECT_INVALID_EP	194
	3.34.1 Message	194
	3.34.2 Description	194
	3.34.3 Resolution	194
3.35	-120074 ERR_CONNECT_UNKNOWN_PROP	194

3.35.1	Message	194
3.35.2	Description	194
3.35.3	Resolution	194
3.36	-120075 ERR_CONNECT_AMBIGUOUS_PROP	195
3.36.1	Message	195
3.36.2	Description	195
3.36.3	Resolution	195
3.37	-120076 ERR_CONNECT_WIDGET_PARAM_NUM_CONNS	195
3.37.1	Message	195
3.37.2	Description	195
3.37.3	Resolution	196
3.38	-120077 ERR_CONNECT_WIDGET_PARAM_ONE_EP	196
3.38.1	Message	196
3.38.2	Description	196
3.38.3	Resolution	196
3.39	-120078 ERR_CONNECT_WIDGET_PARAM_NO_EP	196
3.39.1	Message	196
3.39.2	Description	196
3.39.3	Resolution	196
3.40	-120079 ERR_CONNECT_WIDGET_PARAM_INVALID_EP	196
3.40.1	Message	197
3.40.2	Description	197
3.40.3	Resolution	197
3.41	-120080 ERR_CONNECT_WIDGET_PARAM_NO_CONNS	197
3.41.1	Message	197
3.41.2	Description	197
3.41.3	Resolution	197
3.42	-120081 ERR_CONNECT_INVALID_PATH	197
3.42.1	Message	197
3.42.2	Description	198
3.42.3	Resolution	198
3.43	-120090 ERR_DOMAIN_EXPANSION_FAILED	198
3.43.1	Message	198
3.43.2	Description	198
3.43.3	Resolution	198
3.44	-120100 ERR_DUPLICATE_PAGE_ID	198
3.44.1	Message	198
3.44.2	Description	199
3.44.3	Resolution	199
3.45	-120101 ERR_DUPLICATE_GROUP_ID	199
3.45.1	Message	199
3.45.2	Description	199
3.45.3	Resolution	199
3.46	-120102 ERR_DUPLICATE_PARAM_NAME	199
3.46.1	Message	199
3.46.2	Description	199
3.46.3	Resolution	199
3.47	-120103 ERR_DUPLICATE_BEAN_NAME	200
3.47.1	Message	200

3.47.2	Description	200
3.47.3	Resolution	200
3.48	-120104 ERR_HIERARCHY_MISSING_PARAM	200
3.48.1	Message	200
3.48.2	Description	200
3.48.3	Resolution	200
3.49	-120110 ERR_ELEMENT_UNKNOWN	201
3.49.1	Message	201
3.49.2	Description	201
3.49.3	Resolution	201
3.50	-120111 ERR_ELEMENT_NOT_EMPTY	201
3.50.1	Message	201
3.50.2	Description	201
3.50.3	Resolution	201
3.51	-120112 ERR_ELEMENT_MISSING_CHILD	201
3.51.1	Message	201
3.51.2	Description	202
3.51.3	Resolution	202
3.52	-120113 ERR_ELEMENT_EMPTY	202
3.52.1	Message	202
3.52.2	Description	202
3.52.3	Resolution	202
3.53	-120114 ERR_ELEMENT_MISSING_ATTRIBUTE	202
3.53.1	Message	202
3.53.2	Description	203
3.53.3	Resolution	203
3.54	-120115 ERR_ELEMENT_INVALID_ATT	203
3.54.1	Message	203
3.54.2	Description	203
3.54.3	Resolution	203
3.55	-120116 ERR_ELEMENT_UNEXPECTED_CHILD	203
3.55.1	Message	203
3.55.2	Description	204
3.55.3	Resolution	204
3.56	-120130 ERR_FIELD_HOME_INVALID_SOURCE	204
3.56.1	Message	204
3.56.2	Description	204
3.56.3	Resolution	204
3.57	-120131 ERR_FIELD_INVALID_LINK	204
3.57.1	Message	204
3.57.2	Description	204
3.57.3	Resolution	205
3.58	-120132 ERR_FIELD_MULTIPLE_LINKS	205
3.58.1	Message	205
3.58.2	Description	205
3.58.3	Resolution	205
3.59	-120133 ERR_FIELD_MULTIPLE_SOURCES	205
3.59.1	Message	205
3.59.2	Description	205

3.59.3 Resolution	205
3.60 -120134 ERR_FIELD_MULTIPLE_TARGETS	205
3.60.1 Message	205
3.60.2 Description	205
3.60.3 Resolution	206
3.61 -120135 ERR_FIELD_MULTIPLE_INITIALS	206
3.61.1 Message	206
3.61.2 Description	206
3.61.3 Resolution	206
3.62 -120136 ERR_FIELD_SINGLE_AS_MULTIPLE	206
3.62.1 Message	206
3.62.2 Description	206
3.62.3 Resolution	206
3.63 -120140 ERR_INFORMATIONAL_INVALID_SOURCE	207
3.63.1 Message	207
3.63.2 Description	207
3.63.3 Resolution	207
3.64 -120151 ERR_INVALID_XML	207
3.64.1 Message	207
3.64.2 Description	207
3.64.3 Resolution	207
3.65 -120152 ERR_GEN_INVALID_XSL	207
3.65.1 Message	208
3.65.2 Description	208
3.65.3 Resolution	208
3.66 -120153 ERR_GEN_INVALID_XSL_DETAILED	208
3.66.1 Message	208
3.66.2 Description	208
3.66.3 Resolution	208
3.67 -120154 ERR_INVALID_NAME	209
3.67.1 Message	209
3.67.2 Description	209
3.67.3 Resolution	209
3.68 -120155 ERR_GEN_INVALID_UIM	209
3.68.1 Message	209
3.68.2 Description	209
3.68.3 Resolution	209
3.69 -120156 ERR_GEN_INVALID_MESSAGE	209
3.69.1 Message	209
3.69.2 Description	209
3.69.3 Resolution	209
3.70 -120160 ERR_LINK_INVALID_ATT	210
3.70.1 Message	210
3.70.2 Description	210
3.70.3 Resolution	210
3.71 -120161 ERR_LINK_INVALID_SOURCE	210
3.71.1 Message	210
3.71.2 Description	210
3.71.3 Resolution	210

3.72	-120162 ERR_LINK_INVALID_CONNS	210
3.72.1	Message	210
3.72.2	Description	211
3.72.3	Resolution	211
3.73	-120163 ERR_LINK_NO_CONNS	211
3.73.1	Message	211
3.73.2	Description	211
3.73.3	Resolution	211
3.74	-120164 ERR_LINK_NO_ATTRIBUTES	211
3.74.1	Message	211
3.74.2	Description	211
3.74.3	Resolution	211
3.75	-120165 ERR_LINK_MISSING_SOURCE_ATT	212
3.75.1	Message	212
3.75.2	Description	212
3.75.3	Resolution	212
3.76	-120166 ERR_SUBMIT_LINK_WITH_URI	212
3.76.1	Message	212
3.76.2	Description	212
3.76.3	Resolution	212
3.77	-120180 ERR_LIST_EMPTY	212
3.77.1	Message	212
3.77.2	Description	213
3.77.3	Resolution	213
3.78	-120181 ERR_LIST_MULTIPLE_ACTSETS	213
3.78.1	Message	213
3.78.2	Description	213
3.78.3	Resolution	213
3.79	-120182 ERR_LIST_INVALID_EDITABLE_FIELD	213
3.79.1	Message	213
3.79.2	Description	213
3.79.3	Resolution	214
3.80	-120183 ERR_LIST_INVALID_EDITABLE_FIELD_DOMAIN	214
3.80.1	Message	214
3.80.2	Description	214
3.80.3	Resolution	214
3.81	-120184 ERR_LIST_INVALID_EDITABLE_FIELD_HEIGHT	214
3.81.1	Message	214
3.81.2	Description	214
3.81.3	Resolution	214
3.82	-120185 ERR_LIST_INVALID_EDITABLE_FIELD_CONNECTION	215
3.82.1	Message	215
3.82.2	Description	215
3.82.3	Resolution	215
3.83	-120200 ERR_MENU_INVALID_CHILD	215
3.83.1	Message	215
3.83.2	Description	215
3.83.3	Resolution	215
3.84	-120201 ERR_MENU_DYN_INVALID_CHILD	215

3.84.1	Message	216
3.84.2	Description	216
3.84.3	Resolution	216
3.85	-120202 ERR_MENU_INVALID_SOURCE	216
3.85.1	Message	216
3.85.2	Description	216
3.85.3	Resolution	216
3.86	-120203 ERR_FIELD_ADDRESS_CLUSTER	216
3.86.1	Message	216
3.86.2	Description	216
3.86.3	Resolution	217
3.87	-120204 ERR_FIELD_DUPLICATE_FOCUS	217
3.87.1	Message	217
3.87.2	Description	217
3.87.3	Resolution	217
3.88	-120220 ERR_PAGE_MISSING_SUBMIT	217
3.88.1	Message	217
3.88.2	Description	217
3.88.3	Resolution	217
3.89	-120221 ERR_PAGE_INVALID_ACTSET	217
3.89.1	Message	217
3.89.2	Description	218
3.89.3	Resolution	218
3.90	-120222 ERR_PAGE_INVALID_TITLE	218
3.90.1	Message	218
3.90.2	Description	218
3.90.3	Resolution	218
3.91	-120223 ERR_PAGE_INVALID_SHORTCUT	218
3.91.1	Message	218
3.91.2	Description	218
3.91.3	Resolution	218
3.92	-120224 ERR_PAGE_MISSING_PAGE_TITLE	219
3.92.1	Message	219
3.92.2	Description	219
3.92.3	Resolution	219
3.93	-120225 ERR_PAGE_MISSING_SCRIPT_FILE	219
3.93.1	Message	219
3.93.2	Description	219
3.93.3	Resolution	219
3.94	-120226 ERR_PAGE_MULTIPLE_INFORMATIONALS	219
3.94.1	Message	219
3.94.2	Description	219
3.94.3	Resolution	220
3.95	-120227 ERR_PAGE_ID_FILENAME	220
3.95.1	Message	220
3.95.2	Description	220
3.95.3	Resolution	220
3.96	-120228 ERR_PAGE_ID_REQUIRED	220
3.96.1	Message	220

3.96.2 Description	220
3.96.3 Resolution	220
3.97 -120240 ERR_PAGE_REF_MISSING_ATT	220
3.97.1 Message	220
3.97.2 Description	220
3.97.3 Resolution	221
3.98 -120241 ERR_PAGE_REF_INVALID_VISIBLE	221
3.98.1 Message	221
3.98.2 Description	221
3.98.3 Resolution	221
3.99 -120250 ERR_PAGE_GROUP_INVALID_PARENT	221
3.99.1 Message	221
3.99.2 Description	221
3.99.3 Resolution	221
3.100 -120260 ERR_PAGE_TITLE_INVALID_CONN	221
3.100.1 Message	222
3.100.2 Description	222
3.100.3 Resolution	222
3.101 -120261 ERR_PAGE_TITLE_MISSING_SOURCE	222
3.101.1 Message	222
3.101.2 Description	222
3.101.3 Resolution	222
3.102 -120270 ERR_PROP_NOT_LIST	222
3.102.1 Message	222
3.102.2 Description	222
3.102.3 Resolution	222
3.103 -120280 ERR_SCRIPT_MULTIPLE_EVENTS	223
3.103.1 Message	223
3.103.2 Description	223
3.103.3 Resolution	223
3.104 -120290 ERR_SHORTCUT_HAS_TARGET	223
3.104.1 Message	223
3.104.2 Description	223
3.104.3 Resolution	223
3.105 -120291 ERR_SHORTCUT_MISSING_SOURCE	223
3.105.1 Message	223
3.105.2 Description	223
3.105.3 Resolution	224
3.106 -120300 ERR_SI_INVALID_NAME	224
3.106.1 Message	224
3.106.2 Description	224
3.106.3 Resolution	224
3.107 -120310 ERR_TARGET_NOT_ALLOWED	224
3.107.1 Message	224
3.107.2 Description	224
3.107.3 Resolution	224
3.108 -120320 ERR_UIM_INVALID_ROOT	224
3.108.1 Message	225
3.108.2 Description	225

3.108.3 Resolution	225
3.109 -120330 ERR_BEAN_META_TAG	225
3.109.1 Message	225
3.109.2 Description	225
3.109.3 Resolution	225
3.110 -120340 ERR_WIDGET_INVALID_PARAMETER	225
3.110.1 Message	225
3.110.2 Description	226
3.110.3 Resolution	226
3.111 -120341 ERR_WIDGET_MISSING_PARAMETER	226
3.111.1 Message	226
3.111.2 Description	226
3.111.3 Resolution	226
3.112 -120350 ERR_PAGE_DETAILS_INVALID_TAB_NAME_NUMBER	226
3.112.1 Message	226
3.112.2 Description	226
3.112.3 Resolution	226
3.113 -120351 ERR_PAGE_INVALID_TAB_NAME	227
3.113.1 Message	227
3.113.2 Description	227
3.113.3 Resolution	227
3.114 -120352 ERR_PAGE_DETAILS_INVALID_PAGE_TITLE_NUMBER	227
3.114.1 Message	227
3.114.2 Description	227
3.114.3 Resolution	227
3.115 -120353 ERR_TAB_NAME_HAS_TARGET	227
3.115.1 Message	227
3.115.2 Description	227
3.115.3 Resolution	228
3.116 -120354 ERR_TAB_NAME_MISSING_SOURCE	228
3.116.1 Message	228
3.116.2 Description	228
3.116.3 Resolution	228
3.117 -120355 ERR_SI_INVALID_PHASE	228
3.117.1 Message	228
3.117.2 Description	228
3.117.3 Resolution	228
3.118 -120356 ERR_ACTCTL_INVALID_TYPE	228
3.118.1 Message	229
3.118.2 Description	229
3.118.3 Resolution	229
3.119 -120357 ERR_PAGE_TITLE_INVALID_ELEMENTS	229
3.119.1 Message	229
3.119.2 Description	229
3.119.3 Resolution	229
3.120 -120358 ERR_PAGE_TITLE_INVALID_ATTRIBUTES	229
3.120.1 Message	229
3.120.2 Description	229
3.120.3 Resolution	230

3.121 -120359 ERR_PAGE_INVALID_ELEMENT	230
3.121.1 Message	230
3.121.2 Description	230
3.121.3 Resolution	230
3.122 -120400 ERR_GEN_UNKNOWN	230
3.122.1 Message	230
3.122.2 Description	230
3.122.3 Resolution	230
3.123 -120401 ERR_PROCESSING_FAILED	230
3.123.1 Message	230
3.123.2 Description	231
3.123.3 Resolution	231
3.124 -120402 ERR_FILE_NOT_FOUND	231
3.124.1 Message	231
3.124.2 Description	231
3.124.3 Resolution	231
3.125 -120403 ERR_FOLDER_NOT_FOUND	231
3.125.1 Message	231
3.125.2 Description	232
3.125.3 Resolution	232
3.126 -120404 ERR_PROPS_IMAGE_UNDEFINED	232
3.126.1 Message	232
3.126.2 Description	232
3.126.3 Resolution	232
3.127 -120405 ERR_PROPS_CONSTANT_UNDEFINED	232
3.127.1 Message	232
3.127.2 Description	233
3.127.3 Resolution	233
3.128 -120406 ERR_PROPS_TEXT_NO_FILE	233
3.128.1 Message	233
3.128.2 Description	233
3.128.3 Resolution	233
3.129 -120407 ERR_PROPS_TEXT_UNDEFINED	233
3.129.1 Message	233
3.129.2 Description	234
3.129.3 Resolution	234
3.130 -120408 ERR_PROPS_PAGE_ID_REF_UNDEFINED	234
3.130.1 Message	234
3.130.2 Description	234
3.130.3 Resolution	234
3.131 -120409 ERR_PROPS_URI_REF_UNDEFINED	235
3.131.1 Message	235
3.131.2 Description	235
3.131.3 Resolution	235
3.132 -120410 ERR_PROPS_HIERARCHY_NO_FILE	235
3.132.1 Message	235
3.132.2 Description	235
3.132.3 Resolution	235
3.133 -120411 ERR_PROPS_HIERARCHY_TITLE_UNDEFINED	236

3.133.1 Message	236
3.133.2 Description	236
3.133.3 Resolution	236
3.134 -120412 ERR_PROPS_FILE_NOT_LOADED	236
3.134.1 Message	236
3.134.2 Description	236
3.134.3 Resolution	236
3.135 -120413 ERR_PROPS_WIDGET_PROP_NAME	236
3.135.1 Message	237
3.135.2 Description	237
3.135.3 Resolution	237
3.136 -120500 ERR_STAGING_ATTR_MISSING	237
3.136.1 Message	237
3.136.2 Description	237
3.136.3 Resolution	237
3.137 -120501 ERR_STAGING_DUPLICATE	237
3.137.1 Message	237
3.137.2 Description	238
3.137.3 Resolution	238
3.138 -120502 ERR_MULTIPLE_CONDITIONS	238
3.138.1 Message	238
3.138.2 Description	238
3.138.3 Resolution	238
3.139 -120503 ERR_INVALID_FOOTER_ROW	238
3.139.1 Message	238
3.139.2 Description	238
3.139.3 Resolution	238
3.140 -120504 ERR_INVALID_VIM_REFERENCE	239
3.140.1 Message	239
3.140.2 Description	239
3.140.3 Resolution	239
3.141 -120505 ERR_INVALID_WINDOW_OPTION_NAME	239
3.141.1 Message	239
3.141.2 Description	239
3.141.3 Resolution	239
3.142 -120506 ERR_INVALID_WINDOW_OPTION_VALUE	240
3.142.1 Message	240
3.142.2 Description	240
3.142.3 Resolution	240
3.143 -120507 ERR_INVALID_WINDOW_OPTION_CHARACTER	241
3.143.1 Message	241
3.143.2 Description	241
3.143.3 Resolution	241
3.144 -120508 ERR_PROPERTY_NAME_TOO_LONG	241
3.144.1 Message	241
3.144.2 Description	242
3.144.3 Resolution	242
3.145 -120509 ERR_SI_ACTID_PROP_ONLY_ON_ACTION	242
3.145.1 Message	242

3.145.2 Description	242
3.145.3 Resolution	242
3.146 -120510 ERR_SI_NOT_ALL_ACTID_PROPS_SPECIFIED	242
3.146.1 Message	242
3.146.2 Description	242
3.146.3 Resolution	242
3.147 -120511 ERR_ACTCTL_NOT_ALL_IDS_SPECIFIED	243
3.147.1 Message	243
3.147.2 Description	243
3.147.3 Resolution	243
3.148 -120512 ERR_SI_ACTCTL_IDS_NOT_SPECIFIED	243
3.148.1 Message	243
3.148.2 Description	243
3.148.3 Resolution	243
3.149 -120513 ERR_ACTCTL_SI_ACTID_PROPS_NOT_SPECIFIED	243
3.149.1 Message	243
3.149.2 Description	244
3.149.3 Resolution	244
3.150 -120514 ERR_ACTCTL_WRONG_TYPE_FOR_ACTID	244
3.150.1 Message	244
3.150.2 Description	244
3.150.3 Resolution	244
3.151 -120515 ERR_ACTCTL_ACTID_NOT_UNIQUE	244
3.151.1 Message	244
3.151.2 Description	244
3.151.3 Resolution	244
3.152 -120520 ERR_INVALID_CONFIRMED_WIDGET	245
3.152.1 Message	245
3.152.2 Description	245
3.152.3 Resolution	245
3.153 -120521 ERR_CONFIRMED_WIDGET_WRONG_CONTEXT	245
3.153.1 Message	245
3.153.2 Description	245
3.153.3 Resolution	245
3.154 -120522 ERR_CONNECT_INCOMPATIBLE_PAGE	246
3.154.1 Message	246
3.154.2 Description	246
3.154.3 Resolution	246
3.155 -120523 ERR AJAX_UNEXPECTED_ELEMENT	246
3.155.1 Message	246
3.155.2 Description	246
3.155.3 Resolution	246
3.156 -120524 ERR AJAX_SERVER_INTF	246
3.156.1 Message	246
3.156.2 Description	247
3.156.3 Resolution	247
Notices	248

Chapter 1

Introduction

1.1 Introduction

This guide is intended as a reference document to help with diagnosing errors with the Cúram Web Client and Cúram Client Development Environment (CDEJ).

1.2 Prerequisites

The Cúram User Interface Developers Guide and Cúram Web Client Reference Manual are prerequisites before consulting this guide.

1.3 Structure

There are two chapters in this guide:

- Chapter 2, *Error Messages* lists all messages that can be reported by the Cúram web application at run-time, what they mean, and how they can be resolved.
- Chapter 3, *Cúram Generator Error Messages* lists all messages that can be reported by the Cúram Client Development Environment (CDEJ) development tools at design time, what they mean, and how they can be resolved.

Chapter 2

Error Messages

2.1 Objective

This chapter describes all the errors that may be generated from the Cúram web application at runtime. In general, when using JavaServer Pages (JSP) pages generated from User Interface Meta-data (UIM) source, the errors described below are unlikely to occur at runtime. Most of them refer to underlying JSP objects, thus they can only approximately be related to UIM pages elements. More likely, errors are the generation-time ones described in Chapter 3, *Cúram Generator Error Messages*.

2.2 Introduction

The following sections describe each error message that can be displayed by the Cúram web application at runtime. Each section provides the error number, the error message and a description of any placeholders that occur in the message. Placeholders are represented by `%nS` where `n` is a number that represents the order of the placeholder in the translated message.

Resolution instructions are also provided for fixing the error. The following general instructions should be applied to every error:

- For some errors described below, the developer can perhaps do no more than retry the page or restart the web application. If these problems persist, technical support should be notified.
- Errors should be reported by keeping a copy of the error page source. Since we are in a browser environment, this is achieved by simply selecting *File*→*Save As...* from the menu, or selecting *View*→*Source* to bring up a text editor and then saving the document. The information in the source of the page may be useful in identifying and resolving the error.

`PageUnderQuestion.uim` refers to any UIM file whose JSP counterpart (`PageUnderQuestion.jsp`) failed to execute with one of the error messages listed.

2.2.1 Errors from Web Application vs. Application Server

Error messages from the Cúram web application will have a negative number less than -110000.

Errors from the application server are easily recognizable as database errors such as *Record Not Found* and application business logic validation errors such as “The start date must be less than the end date”, and so on.

2.3 -110000 ERR_TXTHLP_NO_NAME

2.3.1 Message

ERROR: %1s: TextHelper name not specified.

Message placeholders:

%1s

The class name of the custom tag the error occurred on.

2.3.2 Description

The instance name of a `TextHelper` bean, required by a custom JSP tag was not specified. In terms of UIM this means that one of the `SERVER_INTERFACE` tags in `PageUnderQuestion.uim` lacks the mandatory `NAME` attribute.

2.3.3 Resolution

On the `PageUnderQuestion.uim`, examine all `SERVER_INTERFACE` tags of the type identified by the error message (corresponds to tag `CLASS` attribute value). Ensure all `SERVER_INTERFACE` tags have a `NAME` attribute value specified.

2.4 -110001 ERR_TXTHLP_NOT_FOUND

2.4.1 Message

ERROR: %1s: TextHelper bean '%2s' not found on this page.

Message placeholders:

%1s

The name of the class on which the error occurred.

%2s

The instance name of the `TextHelper`.

2.4.2 Description

For UIM, this error message means that either a required `SERVER_INTERFACE` tag is absent on the page or another page element refers to the wrong `SERVER_INTERFACE` element. When executing server calls using the path resolvers, this means that the server interface was not declared.

2.4.3 Resolution

On the UIM page, ensure all `SOURCE`, `TARGET` and `INITIAL` elements have valid `NAME` attribute values matching either one of the `SERVER_INTERFACE` `NAME` values or another valid name (e.g. `PAGE`, `DISPLAY`, etc., according to XML schema). Note that the name in question may originate from another UIM page imported by the current page, which means that all the related (imported) UIM pages should be checked for the corresponding `SERVER_INTERFACE` name and corrected, if appropriate.

If calling server interfaces using the path resolvers, ensure that the server interface has been previously declared, or that the name does not conflict with a named used in the UIM page or for another attribute of the current request.

2.5 -110002 ERR_TXTHLP_FIELD_ACCESS

2.5.1 Message

ERROR: %1s: An error occurred when accessing the TextHelper named '%2s' and field '%3s'.

Message placeholders:

%1s

The class name of the custom tag the error occurred on.

%2s

The instance name of the `TextHelper`.

%3s

The field of the `TextHelper` being accessed.

2.5.2 Description

The majority of the CDEJ custom tags access `TextHelper` fields in some way. This is a general error message indicating that the field could not be accessed. The specific error that occurred is reported with this error.

2.5.3 Resolution

The most common cause of this error is a *ERR_TXTHLP_FIELD_NOT_FOUND* error (-110007). Ensure you have the latest *ServerAccessBeans.xml* in the build folder of your web application project. If you have the latest version of this file, it is possible that a field has been removed from a *TextHelper*. Check *ServerAccessBeans.xml* for a list of all fields on a *TextHelper*. If the field you are referencing is not there, check with the server developer to confirm that the field has been removed and is no longer required. Then simply remove its reference from *PageUnderQuestion.uim*. It will be in a *SOURCE*, *TARGET* or *INITIAL* element under the *PROPERTY* attribute (do not forget to check that the *NAME* attribute of the tag in question matches the instance name, reported in error message).

2.6 -110003 ERR_TXTHLP_MULTIPLE_ASSIGN

2.6.1 Message

ERROR: Multiple values (%1s) have been mapped to '%2s.%3s'.

Message placeholders:

%1s

The values that have been mapped to the field.

%2s

The instance name of the *TextHelper*.

%3s

The name of the field.

2.6.2 Description

This error indicates that multiple form widget tags have been mapped to a single field thus causing ambiguity in assignment. The situation in terms of UIM means that there are at least two identical *TARGET* elements in *SERVER_INTERFACE* with attribute *PHASE* set to *ACTION* (used when submitting form data).

2.6.3 Resolution

In *PageUnderQuestion.uim* try to spot identical *TARGET* sub-elements belonging or referring to different *SERVER_INTERFACE* elements with *ACTION* as their *PHASE* attribute value. Resolve the situation by appropriate correction, deletion, or redesign.

2.7 -110004 ERR_TXTHLP_NO_CLASS

2.7.1 Message

ERROR: %1s: TextHelper class not specified.

Message placeholders:

%1s

The class name of the custom tag the error occurred on.

2.7.2 Description

This error indicates that one of `SERVER_INTERFACE` tags on `PageInQuestion.uim` lacks the mandatory `CLASS` attribute or its value does not match fully-scoped class name.

2.7.3 Resolution

This is a highly unlikely situation at runtime when dealing with generated JSP pages. On `PageInQuestion.uim`, locate `SERVER_INTERFACE` tags of the specified type and ensure each has the fully scoped class name specified as its `CLASS` attribute value.

2.8 -110005 ERR_TXTHLP_NEW_INST_FAIL

2.8.1 Message

ERROR: %1s: An error occurred when creating an instance of TextHelper '%2s'.

Message placeholders:

%1s

The name of the class in which the error occurred.

%2s

The class name of the `TextHelper` bean.

2.8.2 Description

This error indicates that an instance of a `TextHelper`, corresponding to a `SERVER_INTERFACE` element in UIM, or a executed path, could not be created.

2.8.3 Resolution

The most common reason for this error to occur is a *Java*® `ClassNotFoundException`. In this case ensure you have the latest `ServerAccessBeans.xml` for the server you are connecting to, in the build directory of your project.

If any other specific error message is displayed, the error should be reported to technical support for the project.

2.9 -110007 ERR_TXTHLP_FIELD_NOT_FOUND

2.9.1 Message

ERROR: Field not found (*%1s* : *%2s*)

Message placeholders:

%1s

The name of the field that was requested in error.

%2s

The name of the `TextHelper` class.

2.9.2 Description

This message should never be seen on its own. It should always be part of the more general message -110002.

2.9.3 Resolution

Ensure you have the latest `ServerAccessBeans.xml` for the server you are connecting to, in the build directory of your project. If you have the latest file, it is possible that a field has been removed from a `TextHelper`. Check `ServerAccessBeans.xml` for a list of all fields on a `TextHelper`. If the field you are referencing is not there, check with the server developer to confirm that the field has been removed and is no longer required. Then simply remove the custom tag that is referencing it.

2.10 -110008

ERR_TXTHLP_MANDATORY_FIELD_EMPTY

2.10.1 Message

'*%0s*' must be entered.

Message placeholders:

%0s

The label of the field.

2.10.2 Description

A mandatory field was not assigned a value.

2.10.3 Resolution

Mandatory fields on a page are marked by an * icon beside the field label. Ensure this value has been entered before submitting the page.

2.11 -110010 ERR_TXTHLP_BAD_LIST_FIELD_ACCESS

2.11.1 Message

ERROR: The field '*%1s*' on TextHelper named '*%2s*' was accessed as a list field but is a single field.

Message placeholders:

%1s

The name of the field

%2s

The instance name of the TextHelper

2.11.2 Description

In UIM terms, this can occur in a LIST element if a FIELD has a source connection to a field that is not an array/list.

2.11.3 Resolution

Check your UIM and ensure any fields in a LIST element that need to be displayed as columns of the list are in fact list fields.

2.12 -110011 ERR_TXTHLP_UNRECOGNISED_FORMAT

2.12.1 Message

ERROR: The format of the TextHelper class name '*%1s*' is not recognized.

Message placeholders:

%1s

The TextHelper class name.

2.12.2 Description

Generated `TextHelper` classes are named according to a certain format. This error means the `TextHelper` being referenced does not match that format and therefore cannot be used.

2.12.3 Resolution

Report the problem along with the name of the `TextHelper` that was reported.

2.13 -110012

ERR_TXTHLP_BAD_SINGLE_FIELD_ACCESS

2.13.1 Message

ERROR: The field '*%1s*' on `TextHelper` named '*%2s*' was accessed as a single field but is a list field.

Message placeholders:

%1s

The name of the field.

%2s

The instance name of the `TextHelper`.

2.13.2 Description

In UIM terms, this can occur in a `FIELD` element if it has a source connection to a field which is an array/list.

2.13.3 Resolution

Check your UIM and ensure any single fields are not parts of `LIST` element and are not connected to a field which provides values for a list.

2.14 -111000 ERR_TAG_NO_SRC_BF

2.14.1 Message

ERROR: *%1s*: Source Bean or Field not specified.

Message placeholders:

%1s

The class name of the custom tag the error occurred on.

2.14.2 Description

One of the `SOURCE` tags lacks a required attribute, either `NAME` or `PROPERTY`.

2.14.3 Resolution

On the `PageInQuestion.uim`, check all instances of `SOURCE` tag to ensure both of the required attributes are specified.

2.15 -111001 ERR_TAG_NO_SEL_SRC_BF

2.15.1 Message

ERROR: %1s: Selection Source Bean or Field not specified.

Message placeholders:

%1s

The class name of the custom tag the error occurred on.

2.15.2 Description

Currently can only occur when processing custom tags generated from a `CONNECT` within a `LIST` on a UIM page. It indicates that the corresponding element requires both of the `INITIAL` sub-element attributes to be specified.

2.15.3 Resolution

On the `PageInQuestion.uim`, check all `INITIAL` sub-elements, ensuring that both the `NAME` and `PROPERTY` attributes have been specified.

2.16 -111002 ERR_TAG_NO_TRG_BF

2.16.1 Message

ERROR: %1s: Target Bean or Field not specified.

Message placeholders:

%1s

The class name of the custom tag the error occurred on

2.16.2 Description

Both `NAME` and `PROPERTY` attributes should be specified for every `TARGET`.

2.16.3 Resolution

On the `PageInQuestion.uim`, check all `TARGET` tag instances and ensure both the `NAME` and `PROPERTY` attributes have been specified.

2.17 -111003 ERR_TAG_NOT_ENCLOSED

2.17.1 Message

ERROR: Tag '`%1s`' must be enclosed by a '`%2s`' tag.

Message placeholders:

%1s

The class name of the custom tag that should be enclosed.

%2s

The class name of the custom tag that must enclose the first tag.

2.17.2 Description

This indicates a situation when one JSP tag is required to be nested within another, but the enclosing tag is missing.

2.17.3 Resolution

The nesting relationship between generated custom tags is not directly related to the relationship among UIM elements. Report this error to technical support as it should not occur.

2.18 -111004 ERR_TAG_BAD_LOOP_IND

2.18.1 Message

ERROR: '`%1s`' is not a valid loop index for tag '`%2s`'.

Message placeholders:

%1s

The value that was used as the loop index

%2s

The class name of the custom tag the error occurred on

2.18.2 Description

The situation refers to irregularity in flow parameters on JSP page.

2.18.3 Resolution

There is no control over a JSP page executing flow at the UIM level. Report this error to technical support as it should not occur.

2.19 -111005 ERR_TAG_BAD_SCOPE

2.19.1 Message

ERROR: Invalid scope specified on tag '*%1s*'.

Message placeholders:

%1s

The class name of the custom tag the error occurred on

2.19.2 Description

Scope management is internal to the JSP page, it should not cause an error at runtime and is not to be corrected at the UIM level.

2.19.3 Resolution

Report this error to technical support as it should not occur.

2.20 -111006 ERR_TAG_NO_NAME

2.20.1 Message

ERROR: name attribute not specified on tag '*%1s*'.

Message placeholders:

%1s

The class name of the custom tag that requires its name attribute to be specified.

2.20.2 Description

The specified custom tag requires its name attribute to be specified. This error cannot be dealt with at UIM level.

2.20.3 Resolution

Report this error to technical support as it should not occur.

2.21 -111007 ERR_TAG_RESOURCE_ACCESS

2.21.1 Message

ERROR: *%1s*: An error occurred when accessing resource '*%2s*' from catalog '*%3s*'.

Message placeholders:

%1s

The class name of the custom tag this error occurred in.

%2s

The resource identifier of the message.

%3s

The resource catalog file identifier which corresponds to a java properties file.

2.21.2 Description

A message could not be loaded from a resource file.

2.21.3 Resolution

The most common error is an incorrect catalog or resource identifier. Ensure that the identifiers for both the resource catalog file and the resource itself are correct. Ensure the properties file exists in the `JavaSource` folder of the web application project. If the file is placed in a sub-folder of this location, the file is located in the same way as a Java class and the fully qualified identifier is required. All properties files under the `JavaSource` will be copied to the `WEB-INF/classes` folder when you build the application in from the command line. When an EAR file is built for deployment, the properties files end up in a file called `project-name_classes.jar` (e.g. `Curam_classes.jar`) in the `WEB-INF/lib` folder of the application WAR contained within the EAR. (The project name is specified in the `CLIENT_PROJECT_NAME` environment variable.)

2.22 -111008 ERR_TAG_NO_URL

2.22.1 Message

ERROR: Tag '*%1s*' must specify a URL.

Message placeholders:

%1s

The class name of the custom tag the error occurred on.

2.22.2 Description

The generated custom tag requires a URL to be specified among its parameters. In UIM, a URL is specified using the LINK element's PAGE_ID attribute.

2.22.3 Resolution

On `PageInQuestion.uim`, check the LINK elements' PAGE_ID attributes. Since, according to the UIM Schema, PAGE_ID is a mandatory attribute, this error should not happen at runtime.

2.23 -111009 ERR_TAG_BAD_DATA_FORMAT

2.23.1 Message

ERROR: The data passed to the tag '*%1s*' is invalid, '*%2s*' was expected.

Message placeholders:

%1s

The class name of the custom tag the error occurred on.

%2s

The token or element that was expected during parsing.

2.23.2 Description

The custom JSP tag requires that data is passed to it in a particular format (different tags require different formats), but the expected content was not found. This is nearly always an error in the application server code that passes the data to the client application.

2.23.3 Resolution

Check that the application server code is passing data in the correct format.

2.24 -111010 ERR_TAG_NO_SRC

2.24.1 Message

ERROR: No source specified for tag '*%1s*'.

Message placeholders:

%1s

The class name of the custom tag the error occurred on.

2.24.2 Description

A general message indicating that the attributes of a custom tag that specify where to get its source value have not been specified.

2.24.3 Resolution

Check if relevant elements on `PageUnderQuestion.uim` contain `SOURCE` sub-elements where they are required.

2.25 -111011 ERR_TAG_SRC_NULL

2.25.1 Message

ERROR: Specified source for tag '*%1s*' evaluates to null.

Message placeholders:

%1s

The class name of the custom tag the error occurred on.

2.25.2 Description

A general message indicating the source value retrieved for a custom tag is null, which is not permitted by the tag in question.

2.25.3 Resolution

Check the UIM elements which are allowed to have `SOURCE` sub-elements and add `SOURCE` for elements they are mandatory in, or correct these sub-elements if their `NAME` or `PROPERTY` attributes contain invalid values.

2.26 -111012 ERR_TAG_WITH_NAME_NOT_ENCLOSED

2.26.1 Message

ERROR: Tag '*%1s*' with name attribute '*%2s*', must be enclosed by a '*%3s*' tag.

Message placeholders:

%1s

The class name of the custom tag that must be enclosed.

%2s

The name attribute of the custom tag that must be enclosed.

%3s

The class name of the custom tag that must enclose the first tag.

2.26.2 Description

This indicates when one tag is required to be enclosed by another, but the enclosing tag is missing. Enclosing relationships in JSP page are not related to those in the UIM page and there is no control at UIM level to check or correct them.

2.26.3 Resolution

Report this error to technical support as it should not occur.

2.27 -111013 ERR_TAG_UNKNOWN

2.27.1 Message

ERROR: %1s: An unknown or unexpected error occurred when requesting the current page.

Message placeholders:

%1s

The class name of the custom tag that the error occurred on.

2.27.2 Description

This indicates a fatal error when processing a tag. For example, an IO error in the JSP container or a failed server call. The error will be reported with another error that was the actual cause of the problem. If the cause of the error was external to the client framework, the message reporting the underlying cause may not be correctly localized.

2.27.3 Resolution

Re-try the page in question. If that fails, restart the web application.

2.28 -111014 ERR_TAG_INTERNAL

2.28.1 Message

ERROR: %1s: An error occurred when requesting the current page.

Message placeholders:

%1s

The class name of the custom tag that the error occurred on.

2.28.2 Description

This indicates a fatal error in the client infrastructure when processing a tag. For example, a failed server call or a configuration problem. The error will be reported with another error that was the actual cause of the problem.

2.28.3 Resolution

Re-try the page in question. If that fails, restart the web application.

2.29 -111015 ERR_TAG_NO_SRC_PARAM

2.29.1 Message

ERROR: %1s: The specified request parameter '%2s' does not exist.

Message placeholders:

%1s

The class name of the custom tag that the error occurred on.

%2s

The name of request parameter missing.

2.29.2 Description

Message indicates the request for the page did not provide an expected parameter value.

2.29.3 Resolution

In UIM files from which the page reporting this error is requested, check LINK elements where PAGE_ID specifies PageUnderQuestion. Every such LINK should have a CONNECT sub-element whose TARGET NAME is PAGE and whose PROPERTY attribute specifies the missing request parameter. It might be that the parameter specified by the PROPERTY attribute is not properly sourced if the SOURCE element is missing or specified incorrectly.

2.30 -111016 ERR_TAG_MISSING_ATTRIB

2.30.1 Message

ERROR: %1s: The tag is missing a required attribute.

Message placeholders:

%1s

The class name of the custom tag that the error occurred on.

2.30.2 Description

This error indicates that a parameter required for adding an item to the Recent Items List was omitted. The error message is specific to tag class `AddRecentItem`.

2.30.3 Resolution

This could be the consequence of the unlikely event that a UIM page with the `SHORTCUT_TITLE` element is missing its mandatory `PAGE_ID` attribute in its `PAGE` element. Report this error to technical support as it should not occur at runtime.

2.31 -111017 ERR_TAG_NO_SORTFIELD

2.31.1 Message

ERROR: Tag '%1s' must specify a sortField.

Message placeholders:

%1s

The class name of the custom tag that the error occurred on.

2.31.2 Description

This error indicates that a required attribute, `sortField`, on the `curam:sortList` custom tag is missing.

2.31.3 Resolution

Report this error to technical support. It cannot be caused by any error in UIM.

2.32 -111018 ERR_TAG_NO_PAGE_LOCALE

2.32.1 Message

ERROR: The page locale was not specified.

2.32.2 Description

The required attribute `localeCode` on the `curam:locale` custom tag is missing from the generated JSP document.

2.32.3 Resolution

This is an internal error; report it to technical support.

2.33 -111019 ERR_TAG_NO_CONTENT_BF

2.33.1 Message

ERROR: *%1s*: Target Bean or Field not specified for the file content.

Message placeholders:

%1s

The class name of the custom tag that the error occurred on.

2.33.2 Description

This error indicates that a `targetBean` or `targetField` attribute is missing from a custom tag.

2.33.3 Resolution

In the UIM, ensure that `WIDGET` tags are correctly defined with all of their required connections.

2.34 -111020 ERR_TAG_NO_META_DATA_BF

2.34.1 Message

ERROR: *%1s*: Source Bean or Field not specified for the meta-data.

Message placeholders:

%1s

The class name of the custom tag that the error occurred on.

2.34.2 Description

This error indicates that a `sourceBean` or `sourceField` attribute is missing from a custom tag.

2.34.3 Resolution

In the UIM, ensure that `WIDGET` tags are correctly defined with all of their required connections.

2.35 -111021 ERR_TAG_NO_DETAILS_BF

2.35.1 Message

ERROR: %1s: Source Bean or Field not specified for the document template details.

Message placeholders:

%1s

The class name of the custom tag that the error occurred on.

2.35.2 Description

This error indicates that a `sourceBean` or `sourceField` attribute is missing from a custom tag.

2.35.3 Resolution

In the UIM, ensure that `WIDGET` tags are correctly defined with all of their required connections.

2.36 -111022 ERR_TAG_IMAGE_MAP

2.36.1 Message

ERROR: The ImageMapConfig.xml file is missing or not correctly configured.

2.36.2 Description

This error indicates that a required resource file is missing from your web application or its contents could not be interpreted properly.

2.36.3 Resolution

See the *Image Mapping* section in the *Development* chapter in the *Cúram Web Client Reference Manual* for details on this file.

2.37 -111023 ERR_TAG_IMAGE_MAP_NO_DOMAIN

2.37.1 Message

ERROR: The ImageMapConfig.xml has no configuration for the '%1s' domain.

%1s

The name of the domain for which a configuration was expected.

2.37.2 Description

A field in the specified domain was defined to be displayed as an image, but no configuration mapping images to values in the domain was defined in the ImageMapConfig.xml file.

2.37.3 Resolution

You must configure the images to be displayed for the domain values. See the *Image Mapping* section in the *Development* chapter in the *Cúram Web Client Reference Manual* for details on this file.

2.38 -111024 ERR_TAG_IMAGE_MAP_NO_LOCALE

2.38.1 Message

ERROR: The ImageMapConfig.xml has no configuration for the '%1s' locale and the '%2s' domain.

%1s

The locale code for which the configuration is required.

%2s

The name of the domain for which a configuration was expected.

2.38.2 Description

A field in the specified domain was defined to be displayed as an image, but no configuration mapping images to values in the domain was defined in the ImageMapConfig.xml file for the specified locale.

2.38.3 Resolution

You must configure the images to be displayed for the domain values in each locale. See the *Image Mapping* section in the *Development* chapter in the *Cúram Web Client Reference Manual* for details on this file.

2.39 -111025 ERR_TAG_IMAGE_MAP_NO_MAPPING

2.39.1 Message

ERROR: The ImageMapConfig.xml has no mapping for the value '*%1s*' in the '*%2s*' locale and '*%3s*' domain.

%1s

The value that was missing the mapping.

%2s

The locale code for which the configuration is required.

%3s

The name of the domain for which a configuration was expected.

2.39.2 Description

A field in the specified domain was defined to be displayed as an image, but no configuration mapping images to values in the domain was defined in the ImageMapConfig.xml file for the specified locale and value.

2.39.3 Resolution

You must configure the images to be displayed for the domain values. See the *Image Mapping* section in the *Development* chapter in the *Cúram Web Client Reference Manual*.

2.40 -111027 ERR_TAG_AGENDA_CONFIG

2.40.1 Message

ERROR: The AgendaConfig.xml file is missing or not correctly configured.

2.40.2 Description

This error indicates that a required resource file is missing from your web application or its contents could not be interpreted properly.

2.40.3 Resolution

See development manual for details on Agenda player configuration.

2.41 -111028 ERR_TAG_NO_CONFIG

2.41.1 Message

ERROR: There is no configuration for this tag. Please consult the documentation to configure the tag correctly.

2.41.2 Description

This error indicates that a rules tree or tree control was not supplied by an appropriate configuration file.

2.41.3 Resolution

See the *Rules Trees* section in the *Domain Specific Controls* chapter in the *Cúram Web Client Reference Manual* for more details on rules and their configuration files or documentation on tree controls.

2.42 -111029 ERR_TAG_PH_INVALID_OP

2.42.1 Message

ERROR: %1s: An unsupported or invalid page hierarchy operation was attempted.

Message placeholders:

%1s

The class name of the custom tag that the error occurred on.

2.42.2 Description

The page hierarchy was configured to show a return link for a page group but no link URI was specified.

2.42.3 Resolution

Ensure that the page hierarchy has been correctly defined and that no inadvertent changes were made to the page templates used for generation.

2.43 -111030 ERR_TAG_CAL_NO_TYPE_ATTR

2.43.1 Message

ERROR: %1s: The calendar data is missing the TYPE attribute on the CURAM_CALENDAR_DATA element.

Message placeholders:

%1s

The class name of the custom tag that the error occurred on.

2.43.2 Description

The calendar data returned by the application server has a CURAM_CALENDAR_DATA element that is missing the required TYPE attribute.

2.43.3 Resolution

Ensure that the XML data being supplied by the server has an attribute TYPE and that its value matches a type defined in the calendar configuration file.

2.44 -111031 ERR_TAG_CAL_BAD_TYPE_ATTR

2.44.1 Message

ERROR: %1s: The calendar data TYPE attribute value '%2s' is not defined in the calendar configuration.

Message placeholders:

%1s

The class name of the custom tag that the error occurred on.

%2s

The value of the TYPE attribute for which there is no configuration.

2.44.2 Description

The calendar data returned by the application server has a CURAM_CALENDAR_DATA element whose TYPE attribute value does not correspond to a type defined in the calendar configuration file.

2.44.3 Resolution

Ensure that the XML data being supplied by the server contains a `TYPE` attribute value that corresponds to a type defined in the calendar configuration file.

2.45 -111032 ERR_TAG_CAL_PARSE_FAILED

2.45.1 Message

ERROR: %1s: The calendar data could not be parsed.

Message placeholders:

%1s

The class name of the custom tag that the error occurred on.

2.45.2 Description

The calendar data returned from the application server could not be parsed.

2.45.3 Resolution

Check that the application server code has created the calendar XML data correctly.

2.46 -111033 ERR_TAG_WKFLOW_NO_PARAM

2.46.1 Message

ERROR: The request parameter %1s does not exist.

Message placeholders:

%1s

The value of the `HIGHLIGHT_ACTIVITY_PARAM` attribute.

2.46.2 Description

The UIM contains a field specifying the ID of a `CONFIG` element contained in `WorkflowConfig.xml` (`WorkflowConfig.xml` is located in `WebContent\WEB-INF\CDEJ\config` of your web application). This element contains an `HIGHLIGHT_ACTIVITY_PARAM` attribute which is used to specify a page parameter used to locate the current activity in a workflow. This activity is highlighted in the graphical view of the workflow.

2.46.3 Resolution

Ensure that the `HIGHLIGHT_ACTIVITY_PARAM` attribute value is passed to the page as a page parameter and specified in the UIM.

2.47 -111034 ERR_TAG_WKFLOW_NO_MATCH

2.47.1 Message

ERROR: The request parameter `%1s` with a value of `%2s` does not exist in the XML data returned from the application server.

Message placeholders:

%1s

The request parameter name.

%2s

The request parameter value.

2.47.2 Description

The request parameter is used to locate the current activity in a workflow. This is done by searching nodes in the XML data returned from the application server. The XML data represents the graphical workflow diagram and the nodes represent specific activities. The name value pair of the request parameter is checked against the name value pair of the attributes in the nodes. A match specifies that this particular activity should be highlighted as the current activity. This error occurs when no match is found on any node.

2.47.3 Resolution

Ensure that the parameter value is correct and the XML data returned is as expected.

2.48 -111035

ERR_TAG_INVALID_DECISION_MATRIX_XML_DATA

2.48.1 Message

ERROR: The XML data that represents the Decision Matrix cannot contain an `OUTCOME` element without also containing a `QUESTION` element.

2.48.2 Description

The XML data that represents the Decision Matrix cannot contain an OUT-COME element without also containing a QUESTION element.

2.48.3 Resolution

Review the XML data.

2.49 -111036 ERR_TAG_NO_SOURCE_PATH

2.49.1 Message

ERROR: %1s: The FIELD element requires a valid source path.

Message placeholders:

%1s

The class name of the custom tag that the error occurred on.

2.49.2 Description

A valid source path is needed to correctly bind a FIELD to a value. This error message indicates that a valid source path has not been set.

2.49.3 Resolution

In UIM files from which the page reporting this error is requested, check the CONNECT elements to ensure they contain a valid SOURCE or a TARGET element.

2.50 -111500 ERR_TAG_PAGE_CONTENT_WRITE_FAILED

2.50.1 Message

ERROR: Could not write the common content to the page '%1s'.

Message placeholders:

%1s

The ID of the page.

2.50.2 Description

A problem occurred when writing the common content to the identified page. This content includes the references to all of the JavaScript files requested by the domain renderer plug-ins. An associated error message will

provide more details.

2.50.3 Resolution

If the associated error message does not provide the information needed to resolve this problem, report the error to your administrator.

2.51 -111501

ERR_TAG_RENDERED_OUTPUT_WRITE_FAILED

2.51.1 Message

ERROR: Could not write the rendered content to the page for renderer class '*%1s*' configured for domain '*%2s*'.

Message placeholders:

%1s

The name of the renderer class.

%2s

The name of the domain configured to use the renderer class.

2.51.2 Description

A problem occurred when writing the output of a renderer to the page. The content is the serialized output of the document fragment populated by the renderer class. An associated error message will provide more details.

2.51.3 Resolution

Check that the domain and renderer class are the expected ones and see the associated error message for more details.

2.52 -111502 ERR_TAG_FIELD_RENDER_FAILED

2.52.1 Message

ERROR: Failed to render the data for a field.

2.52.2 Description

A problem occurred when rendering the data for a field. The rendering process adds the HTML markup to the field value. An associated error message will provide more details.

2.52.3 Resolution

See the associated error message for more details.

2.53 -111503 ERR_TAG_GET_SRC_FAILED

2.53.1 Message

ERROR: The custom tag '*%1s*' failed to get a value from a source identified by the path '*%2s*'.

Message placeholders:

%1s

The name of the tag class.

%2s

The source path.

2.53.2 Description

A problem occurred when getting a source value from a source path or when counting the number of source values. An associated error message will provide more details.

2.53.3 Resolution

See the associated error message for more details.

2.54 -111504 ERR_TAG_SET_TGT_FAILED

2.54.1 Message

ERROR: The custom tag '*%1s*' failed to set a value on a target identified by the path '*%2s*'.

Message placeholders:

%1s

The name of the tag class.

%2s

The target path.

2.54.2 Description

A problem occurred when setting a target value on a target path. An associated error message will provide more details.

2.54.3 Resolution

See the associated error message for more details.

2.55 -112001 ERR_SEC_AR_CACHE_NOT_FOUND

2.55.1 Message

ERROR: %1s: Security Access Rights cache could not be found.

Message placeholders:

%1s

The class name of the custom tag that the error occurred on.

2.55.2 Description

Once function access privileges have been downloaded from the application server, they are cached. This error indicates the cache could not be located.

2.55.3 Resolution

Restart the web application.

2.56 -112002 ERR_SEC_NO_ACCESS_RIGHTS

2.56.1 Message

ERROR: You do not have sufficient privileges to view this page.

2.56.2 Description

The user does not have privileges to view the page. This message originates from Curam specific security checks rather than any standard Servlet/JSP page access rights specified in `web.xml`. The security checks ensure a user has access to a particular server function. If not, it is deemed that the user does not have access to the entire page in the Cúram application.

2.56.3 Resolution

Ensure the user's security privileges have been configured correctly on the Cúram application server. See the Cúram Application Administration User Manual for full details of configuring security for users.

2.57 -112003 ERR_SEC_NO_USERNAME

2.57.1 Message

ERROR: The user home page could not be opened because no user name was available. Please contact your administrator.

2.57.2 Description

The application is not aware of the user's identity.

2.57.3 Resolution

Restart the web application and login again. If the problem persists, contact technical support.

2.58 -112005 ERR_SEC_AR_NO_CLASS_NAME

2.58.1 Message

ERROR: No server interface was specified for the access rights check.

2.58.2 Description

The access rights check on a page was called without any server interface specified.

2.58.3 Resolution

Check the UIM for the page in question and rebuild your application.

2.59 -115000 ERR_FLOW_NO_LINK_TAG

2.59.1 Message

ERROR: Link parameter tag with name '%1s', must be enclosed by a Link tag.

Message placeholders:

%1s

The name of the link parameter tag.

2.59.2 Description

This error message indicates that the custom tags in the JSP file generated from the UIM are invalid.

2.59.3 Resolution

Regenerate the application and, if the problem persists, report the error.

2.60 -115001 ERR_FLOW_NO_LOOP_SIZE

2.60.1 Message

ERROR: Number of loop iterations not set.

2.60.2 Description

To display a list, the number of rows in the list must be calculated from the size of one of the fields in the list, but the size could not be calculated.

2.60.3 Resolution

Regenerate the application and, if the problem persists, report the error.

2.61 -116001 ERR_SVR_NO_CONNECTION_SPECIFIED

2.61.1 Message

ERROR: An attempt has been made to use a server interface but no server connection is available. Please check the '%1s' property in the application configuration file and fix any errors at web server startup.

Message placeholders:

%1s

The name of the application configuration parameter.

2.61.2 Description

The web application attempted to make a server call but no server connection is available.

2.61.3 Resolution

Ensure a server connection has been specified correctly in the application configuration file (`ApplicationConfiguration.properties`). Check the web server/JSP container logs and start-up windows to ensure no errors occurred. Ensure that the `ApplicationController` servlet has

been correctly specified to load on start-up in the `web.xml` file of the application.

2.62 -116002 ERR_SVR_BAD_CONNECTION_TYPE

2.62.1 Message

ERROR: '*%1s*' is not a valid server connection type. Please check '*%2s*' in the application configuration file.

Message placeholders:

%1s

The server connection type specified

%2s

The name of the application configuration parameter.

2.62.2 Description

An incorrect server connection type was specified in the `Application-Configuration.properties` file.

2.62.3 Resolution

Check the specified parameter in the application configuration file. The file contains documentation on what are valid values.

2.63 -116003 ERR_SVR_CONNECTION_CLASS_FAIL

2.63.1 Message

ERROR: An error occurred when creating the server connection class '*%1s*'.

Message placeholders:

%1s

The server connection class.

2.63.2 Description

Different server connection types are implemented by different classes in the infrastructure. This is a fatal error for a Cúram web application. An additional message will provide more detail.

2.63.3 Resolution

Restart the web application.

2.64 -116004 ERR_SVR_GET_PROXY_FAIL

2.64.1 Message

ERROR: An error occurred when locating a proxy object for a server interface.

2.64.2 Description

Cúram applications are distributed and so “proxy” objects that represent server interfaces are used to make server calls. This error indicates the proxy objects could not be located. The message will be accompanied by another providing more detail.

2.64.3 Resolution

Ensure the application has been successfully generated and compiled.

2.65 -116005 ERR_SVR_INIT_FAIL

2.65.1 Message

ERROR: An error occurred when initializing the client application.

2.65.2 Description

An error occurred during the initialization of the client application. The message will be accompanied by another providing more detail.

2.65.3 Resolution

Check the accompanying messages for more details.

2.66 -116007 ERR_SAP_CONN_FAIL

2.66.1 Message

ERROR: ApplicationController: Unable to initialize and invalidate the Users SAP session.

2.66.2 Description

An error occurred during the initialization or invalidation of the Users SAP session. The message will be accompanied by another providing more detail.

2.66.3 Resolution

Check the accompanying messages for more details.

2.67 -116008 ERR_JSON_CMD_UNSUPPORTED

2.67.1 Message

ERROR: The JSON command '*%1s*' is not supported.

2.67.2 Description

The specified JSON command is not supported.

2.67.3 Resolution

Contact your administrator for more information.

2.68 -116009 ERR_AJAX_PROCESSING_FAIL

2.68.1 Message

ERROR: Processing of the AJAX request failed.

2.68.2 Description

Check the accompanying messages for more details.

2.68.3 Resolution

Contact your administrator for more information.

2.69 -117001 ERR_WDGT_POPUP_RM_NO_TRG

2.69.1 Message

ERROR: No target widget specified for pop-up result mapping named '*%1s*'.

Message placeholders:

%1s

The name attribute of the pop-up result mapping tag.

2.69.2 Description

This error occurs when data from a pop-up page cannot be send back to the originating page. It indicates that the JSP file generated from the UIM file is invalid.

2.69.3 Resolution

Regenerate the application and, if the problem persists, report the error.

2.70 -117005 ERR_WDGT_ASSESS_BAD_PARAMS

2.70.1 Message

ERROR: The assessment could not be created because not all of the required parameters are available. (%1s=%2s, %3s=%4s, %5s=%6s, %7s=%8s).

Message placeholders:

%1s

Assessment ID parameter name.

%2s

Assessment ID parameter value.

%3s

Case ID parameter name.

%4s

Case ID parameter value.

%5s

Concern Role ID parameter name.

%6s

Concern Role ID parameter value.

%7s

Assessment Config ID parameter name.

%8s

Assessment Config ID parameter value.

2.70.2 Description

The assessment widget is configured incorrectly or the parameters to the

page containing the assessment widget are missing.

2.70.3 Resolution

Check the configuration of the assessment widget and ensure that the browser's location bar was not interfered with by the user during the assessment process.

2.71 -117006 ERR_WDGT_UNKNOWN_NODE_TYPE

2.71.1 Message

ERROR: The rules result node of type '*%1s*' was not recognized.

Message placeholders:

%1s

The type of the node in the rules data obtained from the server.

2.71.2 Description

There was an error in the rules data passed from the application server to the client application.

2.71.3 Resolution

Rules data are supplied by the application server and such an error indicates a programming error that should be reported to the local application developers or to technical support.

2.72 -117007 ERR_WDGT_CONFIG_NOT_FOUND

2.72.1 Message

ERROR: The XML configuration file '*%1s*' could not be found for the class '*%2s*'.

Message placeholders:

%1s

Name of missing configuration file.

%2s

Name of the tag class which requested the missing configuration file.

2.72.2 Description

One of the tags performing an XSL transformation could not find the XML file with the configuration data for that tag or its transformation.

2.72.3 Resolution

Ensure that the mentioned file is among other configuration files invoked at runtime. Check the sub-folder `WebContent\WEB-INF\CDEJ\config` of your web application. If the file is not there, try regenerating your application.

2.73 -117008 ERR_WDGT_WRONG_DATA

2.73.1 Message

ERROR: Invalid rules or evidence data for '*%1s*', item '*%2s*'. Please check that all the rules and evidence items have valid (not empty) descriptions.

Message placeholders:

%1s

The class name of the custom tag the error occurred on.

%2s

Name of rules/evidence item containing wrong data.

2.73.2 Description

The rules tag displaying data from the application server encountered invalid data that could not be displayed.

2.73.3 Resolution

This kind of error could be caused by wrong rules or evidence item description in the UML model. Check the model and ensure the description for rules or evidence item reported in the error contains valid data according to the rules or evidence data format. It is also advisable to check other rules or evidence item descriptions.

2.74 -117009 ERR_TREE_BAD_DATA

2.74.1 Message

ERROR: *%1s*: wrong XML data from application server.

Message placeholders:

%1s

The class name of the custom tag that the error occurred on.

2.74.2 Description

The data from application server for displaying tree control contained invalid data (i.e., empty required attribute values) that could not be processed.

2.74.3 Resolution

Please contact your administrator.

2.75 -117010 ERR_TREE_BAD_STRUCT

2.75.1 Message

ERROR: %1s: wrong application server supplied tree control data structure. Missing required attributes.

2.75.2 Description

The data for displaying tree control did not matched expected format and could not be processed.

2.75.3 Resolution

Please contact your administrator.

2.76 -117011 ERR_TREE_INCOMPLETE

2.76.1 Message

ERROR: %1s: wrong XML data from application server. Not all the nodes provided with required parameters.

Message placeholders:

%1s

The class name of the custom tag that the error occurred on.

2.76.2 Description

The data from application server for displaying tree control contained incomplete data that could not be further processed. At least one of the nodes did not have values for all the required parameters. One particular reason might be "not enclosed" node, inheriting parameters from type which is not among its parents.

2.76.3 Resolution

Please contact your administrator.

2.77 -117012 ERR_TREE_DUPLICATED_PARAMS

2.77.1 Message

ERROR: *%1s*: wrong XML data from application server. Parameter re-defined.

Message placeholders:

%1s

The class name of the custom tag that the error occurred on.

2.77.2 Description

The data from application server for displaying tree control contains inconsistent data. This error indicates that a node contains initialization data for inherited parameter which must be initialized by its ancestor.

2.77.3 Resolution

Please contact your administrator.

2.78 -117013 ERR_TREE_MISSING_TYPE

2.78.1 Message

ERROR: The XML data from the application server contains the type '*%1s*' which is not defined in the tree control configuration file.

Message placeholders:

%1s

The type name which is not defined or does not match a type in the relevant tree control configuration.

2.78.2 Description

The data from the application server for displaying a tree control contained a data type that did not match any of the types defined in the tree control configuration file.

2.78.3 Resolution

Please contact your administrator.

2.79 -117014 ERR_TREE_BAD_CONFIG

2.79.1 Message

ERROR: The tree control configuration data is missing or invalid.

2.79.2 Description

The configuration data for displaying tree control could not be read or parsed.

2.79.3 Resolution

Ensure that the `TreeControlConfig.xml` is among other configuration files invoked at runtime. Check the sub-folder `WebContent\WEB-INF\CDEJ\config` of your web application. If the file is not there, try regenerating your application. If the file is present, check if it contains proper data according to the XML specification and the documentation on tree control configuration.

2.80 -117500 ERR_REQUEST_UNKNOWN

2.80.1 Message

ERROR: An unexpected error occurred when processing a request.

2.80.2 Description

An unexpected error occurred during the action phase of a page when the form data sent in the request was being processed.

2.80.3 Resolution

See the associated error message for more details.

2.81 -117501 ERR_REQUEST_MERGE_PARAM

2.81.1 Message

ERROR: Request items could not be merged for item '*%1s*' and classes '*%2s*' and '*%3s*'.

Message placeholders:

%1s

The name of the request item that could not be merged.

%2s

The class of the existing request item with this name.

%3s

The class of the new request item with this name

2.81.2 Description

To be “merged”, a new request item with the same name as an already existing request item must be of the same class.

2.81.3 Resolution

This error might arise if a UIM page contains a duplicate mapping to an output parameter.

2.82 -117502

ERR_REQUEST_ITEM_CREATION_FAILED

2.82.1 Message

ERROR: A request item could not be created due to an internal error.

2.82.2 Description

This is an internal configuration problem. See the associated error message for more details.

2.82.3 Resolution

Contact technical support.

2.83 -117503 ERR_REQUEST_HANDLING_FAILED

2.83.1 Message

ERROR: A request could not be handled due to an unexpected error.

2.83.2 Description

This error can occur during a file upload attempt. See the associated error message for more details.

2.83.3 Resolution

Try uploading the file again. If the problem persists, contact technical support.

2.84 -117504 ERR_REQUEST_WRONG_ITEM_CLASS

2.84.1 Message

ERROR: An error occurred handling an uploaded file: wrong item class *%1s*.

Message placeholders:

%1s

The incorrect class name.

2.84.2 Description

This is an internal configuration error.

2.84.3 Resolution

Contact technical support.

2.85 -117505 ERR_REQUEST_PARAMETER_BAD_NAME

2.85.1 Message

ERROR: An error occurred handling the request parameter '*%1s*'.

Message placeholders:

%1s

The name of the parameter that caused the error.

2.85.2 Description

A multi-part parameter could not be parsed.

2.85.3 Resolution

Contact technical support.

2.86 -117506

ERR_REQUEST_TH_NO_INSTANCE_NAME

2.86.1 Message

ERROR: Attempt to set a text helper field '%1s' when there was no instance name.

Message placeholders:

%1s

The name of the `TextHelper` field.

2.86.2 Description

Internal error.

2.86.3 Resolution

Contact technical support.

2.87 -117507 ERR_REQUEST_EXPIRED

2.87.1 Message

ERROR: This page has expired. Please cancel this operation and try again.

2.87.2 Description

There is an optional protection built into the application that prevents the same form from being submitted twice. This can happen, for example, if the user submits a form, then presses the browser back button and submits the form again.

This message indicates that this form may no longer be submitted.

2.87.3 Resolution

Press the *Cancel* button or select a new menu item and continue.

2.88 -117508 ERR_REQUEST_UNKNOWN_ACTION

2.88.1 Message

ERROR: An unknown submit action was found in the request ('%1s'). Please contact your administrator.

Message placeholders:

%1s

Name of the submit action.

2.88.2 Description

This should not happen after the application has been cleanly generated. But if modifications have been made and deployed, the application may be in an inconsistent state.

2.88.3 Resolution

Regenerate the application.

2.89 -117509 ERR_REQUEST_UNKNOWN_TYPE

2.89.1 Message

ERROR: An unknown type of request was submitted ('%1s'). Please contact your administrator.

Message placeholders:

%1s

The name of the unknown request.

2.89.2 Description

Internal error.

2.89.3 Resolution

Contact technical support.

2.90 -117510 ERR_REQUEST_FU_BAD_MAX_SIZE

2.90.1 Message

ERROR: The maximum file size for uploaded files is invalid: '%1s'. Please check the '%2s' property in the ApplicationConfiguration.properties file or contact your administrator.

Message placeholders:

%1s

The invalid size.

%2s

The name of the configuration property.

2.90.2 Description

The size is specified in the ApplicationConfiguration.properties file. It has been specified incorrectly.

2.90.3 Resolution

Check the value set in the ApplicationConfiguration.properties file. Consult the application setup documentation if necessary.

2.91 -117511

ERR_REQUEST_FU_BAD_THRESHOLD_SIZE

2.91.1 Message

ERROR: The memory threshold size for uploaded files is invalid: '*%1s*'. Please check the '*%2s*' property in the ApplicationConfiguration.properties file or contact your administrator.

Message placeholders:

%1s

The invalid size.

%2s

The name of the configuration property.

2.91.2 Description

The size is specified in the ApplicationConfiguration.properties file. It has been specified incorrectly.

2.91.3 Resolution

Check the value set in the ApplicationConfiguration.properties file. Consult the application setup documentation if necessary.

2.92 -117512 ERR_REQUEST_FU_BAD_PATH

2.92.1 Message

ERROR: The path to temporary storage of uploaded files is invalid or does not exist: '%1s'. Please check the '%2s' property in the ApplicationConfiguration.properties file or contact your administrator.

Message placeholders:

%1s

The invalid path.

%2s

The name of the configuration property.

2.92.2 Description

The path is specified in the ApplicationConfiguration.properties file. It has been specified incorrectly.

2.92.3 Resolution

Check the path set in the ApplicationConfiguration.properties file and ensure the folder exists. Consult the application setup documentation if necessary.

2.93 -117513 ERR_REQUEST_MERGE_FIELDS

2.93.1 Message

ERROR: The property '%2s' of the server interface '%1s' is a target for more than one field.

Message placeholders:

%1s

The name of the server interface.

%2s

The name of the property.

2.93.2 Description

This error may occur if there is more than one TARGET element in the UIM file that sets the same property of a server interface.

2.93.3 Resolution

Check that each TARGET element in the UIM file sets a different server in-

terface property.

2.94 -117514 ERR_REQUEST_MISSING_CONTEXT

2.94.1 Message

ERROR: The page was opened without first following the correct sequence of pages. Either follow the correct sequence or, if you have done so, report this error to your administrator.

2.94.2 Description

Certain pages in the application Cúram required context information that can only be supplied from other pages within the application. For example, a *Cancel* button may link the user back to the previous page. If you enter a page directly, by typing a URL directly into the browser or following a link from an external application, the application does not have a previous page to go back to and therefore the Cancel button cannot work.

2.94.3 Resolution

Follow the correct sequence of pages to get to the page you wish to see. If you were directed to this page directly from an external application, then report this error since the page may need to be redesigned to make it compatible with direct links from external applications.

2.95 -117515 ERR_REQUEST_BASE_64_DECODE

2.95.1 Message

ERROR: An error occurred decoding an base-64 encoded request parameter '%1s'.

Message placeholders:

%1s

The name of the request item.

2.95.2 Description

This is an internal error indicating a problem handling a large binary data value.

2.95.3 Resolution

Report the error.

2.96 -117516 ERR_REQUEST_BAD_COMPOSITE_TYPE

2.96.1 Message

ERROR: Bad or missing type information for composite request item '*%1s*' of class '*%2s*'.

Message placeholders:

%1s

The name of the request item.

%2s

The name of the request item class.

2.96.2 Description

This error may occur when validating data with a domain type whose value is composed of several parts (e.g., address data). It indicates that the format of the data is incorrect. As the data is formatted by the application server, this is probably a problem with the application server.

2.96.3 Resolution

Check that the data is being formatted correctly by the application server code.

2.97 -117517 ERR_REQUEST_VALIDATION_FAILED

2.97.1 Message

ERROR: Validation failed for composite request item '*%1s*' of class '*%2s*'.

Message placeholders:

%1s

The name of the request item.

%2s

The name of the request item handling class.

2.97.2 Description

This error is an internal error used to record validation information for data of domain types that are composed of several values. It should not be seen at runtime and will be translated automatically into a standard validation message.

2.97.3 Resolution

Report the error.

2.98 -117519

ERR_REQUEST_ENCODING_NOT_SUPPORTED

2.98.1 Message

ERROR: The character encoding '*%1s*' is not supported.

Message placeholders:

%1s

The specified encoding.

2.98.2 Description

This error occurs when the character encoding used to process a request is not supported.

2.98.3 Resolution

This indicates an internal error. Please contact Technical Support.

2.99 -117520 ERR_REQUEST_XSS_RPU_DETECTED

2.99.1 Message

ERROR: An XSS attempt has been detected in the URL. Contact the system administrator.

2.99.2 Description

An Cross-site Scripting (XSS) attack has been detected on an infrastructure request parameter in the current URL.

2.99.3 Resolution

Contact the System Administrator to examine the system logs.

2.100 -117550 ERR_REQUEST_METADATA_CORRUPT

2.100.1 Message

ERROR: The form metadata was found but could not be read.

2.100.2 Description

Each form page contains hidden metadata that is used to associate the data entered on the form with the correct target for that data. This error indicates that this data was found but could not be read. The data is likely to be corrupt. An associated error message may provide more details.

2.100.3 Resolution

Open the form page again and re-try the operation. If the error persists, contact technical support.

2.101 -117551 ERR_REQUEST_INVALID_FORM_TARGET

2.101.1 Message

ERROR: An item in the form has an invalid target path '*%1s*'.

Message placeholders:

%1s

The target path.

2.101.2 Description

When processing the items submitted from a form, an item was found that did not have a target path that identified a server interface property. Each item must have an associated target path and the path may only target a server interface property.

2.101.3 Resolution

Try to submit the form again. If that fails, it may be a problem in a custom domain renderer that is adding an invalid form item to the form or an attempt by a user (or a script running in the web browser) to modify the form metadata. If these can be ruled out, contact technical support for assistance.

2.102 -117600 ERR_REQUEST_INVALID_RECENT_ITEM

2.102.1 Message

ERROR: The Recent Item link selected is no longer valid.

2.102.2 Description

The Recent Item link selected is no longer valid. This is as a result of the removal of the recent item link from another browser window in the same session.

2.102.3 Resolution

Refresh the page to update the list of recent items.

2.103 -118000 ERR_DOC_XML_LOAD_FAILED

2.103.1 Message

ERROR: The XML document '*%1s*' could not be loaded.

Message placeholders:

%1s

The URI of the document that could not be loaded.

2.103.2 Description

An attempt was made to load the XML document at the specified URI but the document could not be loaded. The document could be missing or its contents could be invalid.

2.103.3 Resolution

If the indicated document is a configuration file, check that the file is in the correct location and that the contents are well-formed. If you do not recognize the document, try rebuilding the client application to ensure that all system files are present and in the correct location. If the problem persists, report it.

2.104 -118001 ERR_DOC_XSL_LOAD_FAILED

2.104.1 Message

ERROR: The XSL stylesheet '*%1s*' could not be loaded.

Message placeholders:

%1s

The URI of the document that could not be loaded.

2.104.2 Description

An attempt was made to load the XSL stylesheet at the specified URI but the stylesheet could not be loaded. The stylesheet could be missing or its contents could be invalid.

2.104.3 Resolution

If the indicated document is a customized stylesheet file, check that the file is in the correct location and that the contents are well-formed. If you do not recognize the stylesheet, try rebuilding the client application to ensure that all system files are present and in the correct location. If the problem persists, report it.

2.105 -119000 ERR_EJB_CONN_PROPERTY_MISSING

2.105.1 Message

ERROR: The required property '*%1s*' was not found in the connection configuration during initialization.

Message placeholders:

%1s

The name of the configuration property.

2.105.2 Description

When establishing a connection with the server, a required configuration property was missing. These configuration properties are usually set automatically and differ between different application server vendors.

2.105.3 Resolution

Ensure that the application is being deployed to the application server for which it was built. Regenerate the EAR files and if the problem persists, report it.

2.106 -119001 ERR_EJB_NAMING_EXCEPTION

2.106.1 Message

ERROR: An EJB naming exception occurred.

2.106.2 Description

When establishing a connection with the server, a name could not be correctly resolved.

2.106.3 Resolution

Ensure that the application is being deployed to the application server for which it was built. Regenerate the EAR files and if the problem persists, report it.

2.107 -119002 ERR_EJB_NAMING_COMM_EXCEPTION

2.107.1 Message

ERROR: An EJB communication exception occurred.

2.107.2 Description

When communicating with the server, a name could not be correctly resolved.

2.107.3 Resolution

Ensure that the application is being deployed to the application server for which it was built. Regenerate the EAR files and if the problem persists, report it.

2.108 -119003 ERR_EJB_REMOTE_EXCEPTION

2.108.1 Message

ERROR: An EJB remote exception occurred.

2.108.2 Description

When establishing a connection with the server, the server rejected the connection attempt.

2.108.3 Resolution

Ensure that the application is being deployed to the application server for which it was built. Regenerate the EAR files. Ensure that the authentication settings are correct. If the problem persists, report it.

2.109 -119004 ERR_EJB_NO_CALLBACK_OBJECT

2.109.1 Message

ERROR: The system was unable to determine the username and password for authentication.

2.109.2 Description

The login routine could not find the username and password required for authentication.

2.109.3 Resolution

Ensure that the application is being deployed to the application server for which it was built. Regenerate the EAR files. Ensure that the authentication settings are correct. If the problem persists, report it.

2.110 -120000 ERR_CANNOT_READ_CONFIG_FILE

2.110.1 Message

ERROR: Could not read curam-config.xml file

2.110.2 Description

The curam-config.xml file could not be read at application startup.

2.110.3 Resolution

Check that the curam-config.xml file is present and that it consists of well-formed xml.

2.111 -120001 ERR_REQUIRED_PARAM_MISSING

2.111.1 Message

ERROR: Required parameter '%1s' missing

Message placeholders:

%1s

The name of the required parameter.

2.111.2 Description

A parameter required to download a file is not available.

2.111.3 Resolution

Check that the parameters supplied by the download link on the page are the same as those specified in curam-config.xml for that page.

2.112 -121000 ERR_CT_LOAD_NO_CT_NAME

2.112.1 Message

ERROR: No code-table name was specified when loading a code-table.

2.112.2 Description

A code-table was requested without specifying a name. This error indicates either a mis-configuration of the application, or an internal error.

2.112.3 Resolution

Check that the code-table names are set correctly for the application domain types and that code-table hierarchies are correctly defined. Report the error if problems are found.

2.113 -121001 ERR_CT_LOAD_NO_LOCALE

2.113.1 Message

ERROR: No locale was specified when loading the code-table '%1s'.

Message placeholders:

%1s

The name of the code-table.

2.113.2 Description

A code-table was requested without specifying a locale. This error indicates either a mis-configuration of the application locales, or an internal error.

2.113.3 Resolution

Check that the locales are set correctly for the application. Report the error

if no locale configuration problems are found.

2.114 -121002 ERR_CT_CODE_NOT_FOUND

2.114.1 Message

ERROR: The code '%1s' was not found in the code-table '%2s'.

Message placeholders:

%1s

The code that could not be found.

%2s

The name of the code-table.

2.114.2 Description

An attempt was made to fetch a code description from a code-table using an invalid code.

2.114.3 Resolution

Check the code-table definition and ensure that the required code is present.

2.115 -121003 ERR_CT_CODE_NAME_ERROR

2.115.1 Message

ERROR: The code-table '%1s' for the locale '%2s' could not be loaded.

Message placeholders:

%1s

The name of the code-table.

%2s

The requested locale.

2.115.2 Description

There was an error when attempting to load a code-table from the database.

2.115.3 Resolution

Check that the name of the code-table is valid and has the correct case. Check that the code-table exists on the database for that name and locale.

An associated error message may provide more information.

2.116 -121004 ERR_CT_LOAD_CHILD_FAILED

2.116.1 Message

ERROR: A child code-table subset in a code-table hierarchy could not be loaded for the parent code-table '*%1s*' and parent code '*%2s*' in the locale '*%3s*'.

Message placeholders:

%1s

The name of the parent code-table.

%2s

The name of the parent code.

%3s

The requested locale.

2.116.2 Description

When processing a code-table hierarchy, the subset of child code-table codes in the child code-table that were associated with a single parent code of a parent code-table could not be loaded.

2.116.3 Resolution

Check that the code-table hierarchy is defined correctly for the named locale. An associated error message may provide more information.

2.117 -121005 ERR_CT_LOAD_SELECTED_CODES_FAILED

2.117.1 Message

ERROR: The selected codes for a code-table hierarchy could not be loaded for the code-table '*%1s*' and code '*%2s*' in the locale '*%3s*'.

Message placeholders:

%1s

The name of the lowest-level code-table in the hierarchy.

%2s

The selected code in the lowest-level code-table.

%3s

The requested locale.

2.117.2 Description

When processing a code-table hierarchy, the selected codes for the code-tables at each level in the hierarchy could not be determined for the given code-table and selected code. The given code-table must be the lowest-level code-table in the hierarchy and its selected code is used to determine which code at each higher level in the hierarchy must be selected for that code to be selected.

2.117.3 Resolution

Check that the code-table hierarchy is defined correctly for the named locale, that the given code-table name is the lowest-level code-table in a hierarchy, and that the selected code exists on that code-table. An associated error message may provide more information.

2.118 -121006 ERR_CT_LOAD_NO_PARENT_CODE

2.118.1 Message

ERROR: A child code-table subset in a code-table hierarchy could not be loaded for the parent code-table '*%1s*' because no parent code was specified.

Message placeholders:

%1s

The name of the parent code-table.

2.118.2 Description

When processing a code-table hierarchy, the subset of child code-table codes in the child code-table that were associated with a single parent code of a parent code-table could not be loaded because the parent code was not provided.

2.118.3 Resolution

Check that the code-table hierarchy is defined correctly. If the error persists, report it to your administrator; it may be an internal problem.

2.119 -121007 ERR_CT_LOAD_NO_SELECTED_CODE

2.119.1 Message

ERROR: The selected codes for a code-table hierarchy could not be loaded for the code-table '*%1s*' as no selected code was specified.

Message placeholders:

%1s

The name of the lowest-level code-table in the hierarchy.

2.119.2 Description

When processing a code-table hierarchy, the selected codes for the code-tables at each level in the hierarchy could not be determined for the given code-table, as no selected code in that code-table was provided. The given code-table must be the lowest-level code-table in the hierarchy and its selected code is used to determine which code at each higher level in the hierarchy must be selected for that code to be selected.

2.119.3 Resolution

Check that the code-table hierarchy is defined correctly. If the error persists, report it to your administrator; it may be an internal problem.

2.120 -121010 ERR_CT_NOT_FOUND

2.120.1 Message

ERROR: The code-table '*%1s*' for the locale '*%2s*' could not be found.

Message placeholders:

%1s

The name of the code-table.

%2s

The requested locale.

2.120.2 Description

An error occurred when loading the named code-table for the named locale. It is possible that no code-table exists with this name or that the named code-table has not been localized to provide descriptions for the indicated locale. An associated error message will provide more details.

2.120.3 Resolution

Check the name of the code-table is valid and that the code-table exists on the database and is localized for the indicated locale. See the associated error message for more details.

2.121 -121100 ERR_RES_LOAD_FAILED

2.121.1 Message

ERROR: No resource named '*%1s*' that was compatible with the locale '*%2s*' could found.

Message placeholders:

%1s

The name of the resource.

%2s

The requested locale of the resource.

2.121.2 Description

When loading a resource, no resource was found in the resource store with the given name that was compatible with the requested locale.

2.121.3 Resolution

Check that the resource name is correct and that there is a resource in the resource store that matches that name and that is associated with the requested locale or with one of the fallback locales that will be derived from that locale.

2.122 -121101 ERR_RES_ENCODING_INVALID

2.122.1 Message

ERROR: The resource '*%1s*' for the locale '*%2s*' could not be read as the character encoding '*%3s*' was not valid.

Message placeholders:

%1s

The name of the resource.

%2s

The locale associated with the resource.

%3s

The character encoding.

2.122.2 Description

When accessing the content of a resource for the given locale and interpreting the content using the given character encoding, an error occurred. The most likely cause is that the character encoding was not specified or is not an encoding that is supported by the Java Runtime Environment in use.

2.122.3 Resolution

Check that the encoding name is valid and correct or set the encoding on the resource's content type in the resource store.

2.123 -121102 ERR_RES_TYPE_OR_DISP_INVALID

2.123.1 Message

ERROR: The resource '*%1s*' for the locale '*%2s*' could not be loaded as the content type or content disposition of the resource is invalid.

Message placeholders:

%1s

The name of the resource.

%2s

The locale associated with the resource.

2.123.2 Description

When loading a resource from the resource store, there was a problem parsing the content type or content disposition. An associated error message will provide more information.

2.123.3 Resolution

Check that the content type and content disposition set in the resource store are valid.

2.124 -121120 ERR_RES_PROP_NOT_FOUND

2.124.1 Message

ERROR: The property '*%1s*' in the properties resource '*%2s*' for the locale '*%3s*' could not be found.

Message placeholders:

%1s

The property key.

%2s

The name of the properties resource.

%3s

The locale associated with the resource.

2.124.2 -121122 ERR_PROP_NOT_FOUND

Message

ERROR: The property '*%1s*' in the properties resource CDEJResources.properties could not be found.

Message placeholders:

%1s

The property key.

2.124.3 Description

The property key was not defined in the named properties resource for the given locale or any of the fallback locales.

2.124.4 Resolution

Check that the resource is a valid properties file and that the property key is defined in a resource compatible with the requested locale, this may include resources for fallback locales.

2.125 -121121 ERR_RES_PROPS_LOAD_FAILED

2.125.1 Message

ERROR: Properties for the properties resource '*%1s*' for the locale '*%2s*' could not be loaded due to an error parsing the resource.

Message placeholders:

%1s

The name of the properties resource.

%2s

The locale associated with the resource.

2.125.2 Description

On loading a properties resource, an error occurred when parsing the properties defined in that resource. An associated error message may provide

more detail.

2.125.3 Resolution

Check that the resource in the resource store is a valid properties file and that the encoding is set correctly in the content type for that resource.

2.126 -121150 ERR_RES_SERVLET_NO_RES_NAME

2.126.1 Message

ERROR: The application resource servlet '*%1s*' was not given a resource name.

Message placeholders:

%1s

The name of the servlet class.

2.126.2 Description

The resource servlet is used to serve resources to a user's browser (or other external client) from the application resource store, but a request to the servlet did not specify the name of the resource. Resource names are passed to the resource servlet and the template resource servlet; the servlet class name will indicate which servlet handled the request.

2.126.3 Resolution

Check that the resource URI contains the resource name as the value of the *r* parameter to the URI.

2.127 -121151 ERR_RES_SERVLET_NO_PROP_RES_NAME

2.127.1 Message

ERROR: The application template resource servlet '*%1s*' was not given a properties resource name.

Message placeholders:

%1s

The name of the servlet class.

2.127.2 Description

The template resource servlet is used to serve resources to a user's browser (or other external client) from the application resource store, but a request to the servlet did not specify the name of the properties resource to apply to the template resource.

2.127.3 Resolution

Check that the resource URI contains the resource name as the value of the *pr* parameter to the URI.

2.128 -121152 ERR_RES_SERVLET_FAILED

2.128.1 Message

ERROR: The application resource servlet '*%1s*' failed to serve the requested resource '*%2s*'.

Message placeholders:

%1s

The name of the servlet class.

%2s

The name of the resource.

2.128.2 Description

The resource servlet is used to serve resources to a user's browser (or other external client) from the application resource store, but a request to the servlet failed. The reason for the failure will be given in an associated error message.

2.128.3 Resolution

Check the associated error message for more details about the problem.

2.129 -121153 ERR_RES_SERVLET_INTERNAL

2.129.1 Message

ERROR: A request was made to the application resource servlet '*%1s*' for the resource '*%2s*', but that resource that is for internal use only.

Message placeholders:

%1s

The name of the servlet class.

%2s

The name of the resource.

2.129.2 Description

The resource servlet is used to serve resources to a user's browser (or other external client) from the application resource store, but a request to the servlet specified a resource that was marked for internal use only and that cannot be served to an external client.

2.129.3 Resolution

Check that the resource URI contains the current resource name and that the resource is not mistakenly marked for internal use only.

2.130 -121154 ERR_RES_SERVLET_CONTENT_ERROR

2.130.1 Message

ERROR: The application resource servlet encountered a problem handling the content for the requested resource '*%1s*' in the '*%2s*' locale.

Message placeholders:

%1s

The path of the resource. This is an internal path representation, not the URI.

%2s

The locale code.

2.130.2 Description

The resource servlet is used to serve resources to a user's browser (or other external client) from the application resource store, but a request to the servlet specified a resource that could not be handled. This may be because the content type, content disposition, character encoding, or other property of the resource is invalid or missing. The reason for the failure will be given in an associated error message.

2.130.3 Resolution

Check the associated error message for more details about the problem.

2.131 -1212010 ERR_PATH_SERVLET_FAILED

2.131.1 Message

ERROR: The path resolver servlet '*%1s*' failed to resolve the requested path '*%2s*'.

Message placeholders:

%1s

The name of the servlet class.

%2s

The path.

2.131.2 Description

The path resolver servlet is used to retrieve data represented by a path., but a request to the servlet failed. The reason for the failure will be given in an associated error message.

2.131.3 Resolution

Check the associated error message for more details about the problem.

2.132 -1212001 ERR_PATH_SERVLET_NO_PATH

2.132.1 Message

ERROR: The path resolver servlet '*%1s*' was not given a path.

Message placeholders:

%1s

The name of the servlet class.

2.132.2 Description

The path resolver servlet is used to retrieve data represented by a path. A request to the servlet did not specify the path.

2.132.3 Resolution

Check that the path URI contains the path as the value of the *p* parameter to the URI.

2.133 -12120012 ERR_PATH_SERVLET_UNSUPPORTED_PATH

2.133.1 Message

ERROR: The path resolver servlet '*%1s*' does not support the supplied path .

Message placeholders:

%1s

The name of the servlet class.

2.133.2 Description

The path resolver servlet is used to retrieve data represented by a path. A request to the servlet did not specify the path.

2.133.3 Resolution

Check that the path URI contains the path as the value of the *p* parameter to the URI.

2.134 -121500 ERR_PLUG_IN_NO_NAME

2.134.1 Message

ERROR: No plug-in name was given when loading the plug-in class '*%1s*'.

Message placeholders:

%1s

The name of the plug-in class being loaded.

2.134.2 Description

When loading a plug-in, no plug-in name was provided for checking against the loaded plug-in's reported name. This is usually caused by a missing name in a configuration file. An accompanying message will indicate which configuration file contains the error.

2.134.3 Resolution

See the accompanying error message for more details on the source of this error message. Once located, check that the configuration file contains a valid plug-in name where the identified plug-in class is configured.

2.135 -121501 ERR_PLUG_IN_UNNAMED

2.135.1 Message

ERROR: The plug-in class '%1s' does not report a valid plug-in name.

Message placeholders:

%1s

The name of the plug-in class.

2.135.2 Description

All plug-in classes must report a name that identifies the kind of plug-in represented by that class, but the identified plug-in class did not report a valid name. An accompanying message will indicate the context in which the error occurred.

2.135.3 Resolution

Locate the identified plug-in class and ensure that it was written to report a valid plug-in name. If the plug-in class is not a custom plug-in, report this problem to your administrator.

2.136 -121502 ERR_PLUG_IN_UNIDENTIFIED

2.136.1 Message

ERROR: A request for a plug-in did not specify a plug-in name.

2.136.2 Description

A internal error that indicates that a request for a plug-in did not indicate the name of the required plug-in. Typically, this indicates a problem with the code generators or the corruption of the generated files. An accompanying error message will identify the context in which the error occurred.

2.136.3 Resolution

Check the domain and plug-in configuration data to ensure that all plug-in elements have a name attribute that is set to the name of the plug-in. Regenerate all code if necessary. If the error persists, report it to your administrator; it may indicate an internal problem.

2.137 -121503 ERR_PLUG_IN_WRONG_TYPE

2.137.1 Message

ERROR: The plug-in class '%1s' cannot be loaded because it does not extend the required class '%2s'.

Message placeholders:

%1s

The name of the plug-in class being configured.

%2s

The name of the plug-in base class that must be extended.

2.137.2 Description

When loading a plug-in, the plug-in class was found to be of an unsupported type. Depending on the kind of plug-in, a plug-in class must implement specific plug-in interfaces by extending certain plug-in base classes. All plug-ins must implement the `curam.util.common.plugin.PlugIn` interface by extending (directly or indirectly) the `curam.util.common.plugin.AbstractPlugIn` base class. Domain plug-ins must further implement the `curam.util.common.domain.DomainPlugIn` interface by extending (directly or indirectly) the `curam.util.common.domain.AbstractDomainPlugIn` base class. The error message will indicate what is required and may be accompanied by other error messages providing more details on further requirements and on the context in which the error occurred.

2.137.3 Resolution

Check that the reported plug-in class extends the correct base class for that kind of plug-in. Check that the plug-in was configured in the correct context (for example, ensure that a non-domain plug-in was not used where a domain plug-in was expected).

2.138 -121504 ERR_PLUG_IN_MISMATCH

2.138.1 Message

ERROR: The plug-in class '*%1s*' cannot be loaded because its plug-in name '*%2s*' does not match the expected plug-in name '*%3s*'.

Message placeholders:

%1s

The name of the plug-in class.

%2s

The plug-in name reported by the plug-in class.

%3s

The expected plug-in name.

2.138.2 Description

When loading a plug-in, the plug-in class reported a plug-in name that was different to the name that was expected. Typically, the configuration of the plug-in will declare the plug-in class name and the plug-in name together. Once loaded, the plug-in class must report the same plug-in name as defined in the configuration or this mismatch error occurs. This check ensures that the correct kind of plug-in (identified by its name) has been used in the correct context. For example, it ensures that a domain converter plug-in class was configured as the “converter” plug-in and not as the “comparator” plug-in.

An associated error message will identify the configuration context in which this error occurred.

2.138.3 Resolution

Check the configuration identified by the associated error message to ensure that the plug-in class specified is the intended kind of plug-in, that its reported name is correct, and that the configuration has used the correct name.

2.139 -121505 ERR_PLUG_IN_INACCESSIBLE

2.139.1 Message

ERROR: The plug-in class '*%1s*' cannot be loaded because its constructor cannot be accessed.

Message placeholders:

%1s

The name of the plug-in class.

2.139.2 Description

The configuration data contains a plug-in configuration that specifies a plug-in class that is not public or does not implement a public default constructor.

An associated error message will identify the configuration context in which this error occurred.

2.139.3 Resolution

Check the domain configuration data to ensure that the plug-in class specified has been declared public and has a public default constructor. If the plug-in class is not a domain plug-in, this may be an internal error; report it to your administrator.

2.140 -121506 ERR_PLUG_IN_ABSTRACT

2.140.1 Message

ERROR: The plug-in class '*%1s*' cannot be loaded because it is an abstract class.

Message placeholders:

%1s

The name of the plug-in class.

2.140.2 Description

The configuration data contains a plug-in configuration that specifies a plug-in class that is an abstract class that cannot be instantiated.

An associated error message will identify the configuration context in which this error occurred.

2.140.3 Resolution

Check the configuration data to ensure that the correct plug-in class was specified. If so, ensure that the plug-in class is not an abstract class by changing it as required. If the plug-in class is not a domain plug-in, this may be an internal error; report it to your administrator.

2.141 -121507 ERR_PLUG_IN_NOT_FOUND

2.141.1 Message

ERROR: The plug-in class '*%1s*' cannot be found.

Message placeholders:

%1s

The name of the plug-in class.

2.141.2 Description

The plug-in configuration data references a plug-in class that cannot be found. An accompanying error message will provide more details on the context in which this error occurred.

2.141.3 Resolution

Identify the source of the problem from the accompanying error message and ensure that the class name is correct and that the plug-in is available on the classpath. If the plug-in is not a custom domain plug-in, this may be an internal error; report it to your administrator.

2.142 -121508 ERR_PLUG_IN_NO_PLUG_IN

2.142.1 Message

ERROR: An attempt was made to add a null plug-in.

2.142.2 Description

An internal error indicating that an attempt was made to add a null plug-in object to a plug-in container. An associated error message will provide more details about the context of the error.

2.142.3 Resolution

Check that the domain- and plug-in-related configuration files are well-formed and have not been corrupted; re-generate all code if necessary. If the error persists, report it to your administrator; it may indicate an internal problem.

2.143 -121509 ERR_PLUG_IN_NO_TARGET

2.143.1 Message

ERROR: An attempt was made to add a plug-in without indicating any targets for that plug-in.

2.143.2 Description

When plug-ins are loaded, they are associated with particular plug-in containers such as domain objects. This error occurs when no target containers were identified, or where they were identified incorrectly. An accompanying error message will provide more details about the context of the error.

When associating a plug-in with a container, the target containers for that plug-in must be specified. For example, a plug-in can be added to a container but only target descendants of that container and not the container itself.

2.143.3 Resolution

Check the domain configuration file and ensure that anywhere the `target` attribute of the `domain` element is used, that the value is valid. Valid val-

ues are `self`, `descendant`, and `descendant-or-self`. If the error is reported against a domain element that does not have any `target` attribute, then this could be an internal error and you should report it to your administrator, as it may indicate a corrupt XML schema file or a problem with the versions of the third-party libraries used by the infrastructure.

2.144 -121510 ERR_PLUG_IN_PURPOSE_DUPLICATE

2.144.1 Message

ERROR: The plug-in configuration contains a duplicate definition for the purpose '*%1s*'.

Message placeholders:

%1s

The purpose that was re-defined.

2.144.2 Description

The plug-in configuration contains a definition of a purpose that has already been defined earlier in the same file or in another configuration file that has already been loaded.

2.144.3 Resolution

In the plug-in configuration, remove or rename the purpose identified in the message.

2.145 -121511 ERR_PLUG_IN_PURPOSE_BAD_REF

2.145.1 Message

ERROR: The plug-in configuration defines a purpose '*%1s*' that references a purpose '*%2s*' that is not defined.

Message placeholders:

%1s

The purpose that references the undefined purpose.

%2s

The undefined purpose.

2.145.2 Description

The plug-in configuration contains the definition of a purpose that extends a

purpose that is defined, or a local purpose that uses a plug-in with a purpose that is defined. The referenced purpose is either missing, or it is defined only after it is first referenced.

2.145.3 Resolution

In the plug-in configuration, check that the correct purpose has been referenced and, if correct, ensure that purpose is defined in the configuration file before any purpose that references it. It is also possible to reference purposes defined in other configuration files, as long as these are loaded first.

2.146 -121512 ERR_PLUG_IN_PURPOSE_UNDEFINED

2.146.1 Message

ERROR: The configuration references a plug-in purpose '*%1s*' that is not defined.

Message placeholders:

%1s

The undefined purpose.

2.146.2 Description

The path resolver configuration or domain configuration contains a plug-in element that refers to a plug-in purpose that has not been defined in the plug-in configuration. An associated error message will provide more details on the location of the problem.

2.146.3 Resolution

For the domain configuration, check that the plug-in purpose is spelled correctly and check the plug-in configuration to ensure that the purpose is defined. For the path resolver configuration, this is an internal error; contact your administrator.

2.147 -121513 ERR_PLUG_IN_PURPOSE_BAD_ATTRS

2.147.1 Message

ERROR: The plug-in configuration for the purpose '*%1s*' is invalid: either an 'extends' attribute must be given, or both a 'class' and 'name' attribute must be given.

Message placeholders:

%1s

The plug-in configuration purpose.

2.147.2 Description

The plug-in configuration has defined a purpose incorrectly. When defining a purpose, the `plug-in` element must have a `purpose` attribute. It then either extends another purpose and must have an `extends` attribute, or it does not extend another purpose and must have both a `class` and a `name` attribute. Only one of these combinations is allowed.

2.147.3 Resolution

Check the plug-in configuration to ensure that the definition of the named purpose has the required attributes.

2.148 -121514 ERR_PLUG_IN_PURPOSE_BAD_CLASS

2.148.1 Message

ERROR: The plug-in class configured for the purpose '*%1s*' is invalid.

Message placeholders:

%1s

The plug-in configuration purpose.

2.148.2 Description

The plug-in configuration has defined a purpose that refers to a plug-in class that is not valid. The message indicates the purpose that references the invalid plug-in class, or the purpose that extends a purpose that references the invalid plug-in class. An accompanying error message will provide more details.

2.148.3 Resolution

The information in the accompanying error message will diagnose the problem further.

2.149 -121515 ERR_PLUG_IN_PURPOSE_BAD_REUSE

2.149.1 Message

ERROR: The plug-in configuration purpose '*%1s*' re-uses an invalid pur-

pose '%2s' for the local purpose '%3s'.

Message placeholders:

%1s

The plug-in configuration purpose.

%2s

The invalid plug-in configuration purpose re-used in this purpose.

%3s

The local purpose name assigned to the re-used purpose.

2.149.2 Description

A plug-in configuration purpose re-used another plug-in for a local purpose, but the re-used plug-in purpose is not valid. Accompanying error messages will provide more details.

2.149.3 Resolution

The information in the accompanying error messages will diagnose the problem further.

2.150 -121520 ERR_PLUG_IN_INIT_PARSE_FAILED

2.150.1 Message

ERROR: Invalid content in the domain definition or plug-in configuration resource '%1s'.

Message placeholders:

%1s

The resource containing the invalid content.

2.150.2 Description

The contents of a domain definition or plug-in configuration resource is not valid: it may not be well-formed XML or it may contain other errors. If this error occurs, a Cúram web application cannot function. The message may be followed by a more detailed description of the problem, or may be preceded by specific error messages in the server log.

2.150.3 Resolution

Domain and plug-in information is loaded from “resources”: copies of the original files that are placed on the application's classpath. The file name part of the resource name should indicate the name of the original file that

contains the error. The error indicates a problem either in the syntax of the file, or in the semantics of the information. The file might contain XML that is not well-formed, or it might not conform to the required XML schema. The values provided may not be valid or supported, or, in the case of plug-in configurations, the referenced plug-ins may not be valid.

Identify the problems from the accompanying information, correct them, and rebuild the application.

2.151 -121521 ERR_PLUG_IN_PARSER_INIT_FAILED

2.151.1 Message

ERROR: Domain or plug-in information could not be loaded because the parser could not be initialized.

2.151.2 Description

A internal error that indicates that a parser for the domain or plug-in information could not be created or configured. This may indicate a problem with the classpath settings or parser configuration. A more specific error message will accompany this one.

2.151.3 Resolution

Report the error to your administrator; it may indicate an internal problem.

2.152 -121522 ERR_PLUG_IN_RESOURCE_NOT_FOUND

2.152.1 Message

Domain or plug-in information was not loaded: the resource '*%1s*' was not found.

Message placeholders:

%1s

The name of the resource that was not found.

2.152.2 Description

A domain definition or plug-in configuration resource could not be found. Domain or plug-in information is loaded from “resources”: copies of the original files that are placed on the application's classpath. Failure to load a resource may indicate that the original file was missing, that the copying process failed, that the resource was deleted after it was copied, that the re-

source was incorrectly identified, or that the classpath was configured incorrectly.

Failure to locate a resource is not always a problem. Some resources represent custom configuration files that are optional and their absence is not an error: the system will search for these custom resources in their expected location and report this message if they are not present. Only when the message is accompanied by other error messages is it a problem that needs to be resolved.

2.152.3 Resolution

Ensure that the necessary domain and plug-in configuration files are in the right locations and that there is sufficient disk space available to build the application. Perform a clean rebuild of the application to restore any resources that may have been deleted accidentally.

The name of some of the resources includes the client application project name defined by the `CLIENT_PROJECT_NAME` environment variable. If this environment variable is not set, some required resources may not be found. Check that this variable is set correctly.

2.153 -121523 ERR_PLUG_IN_UNKNOWN_SCHEMA

2.153.1 Message

ERROR: Domain or plug-in information could not be loaded: a request was made to resolve an unknown XML schema '%1s'.

Message placeholders:

%1s

The system identifier of the unknown XML schema.

2.153.2 Description

A internal error that indicates that a parser for the domain or plug-in information was not configured correctly.

2.153.3 Resolution

Check that the domain definitions meta-data file and plug-in configuration files are well-formed and has not been corrupted; re-generate all code again if necessary. If the error persists, report it to your administrator; it may indicate an internal problem.

2.154 -121524 ERR_PLUG_IN_INIT_FAILED

2.154.1 Message

ERROR: Domain definition or plug-in initialization failed before loading '*%1s*'.

Message placeholders:

%1s

The resource that was being loaded.

2.154.2 Description

An error occurred while attempting to load the named domain definition or plug-in configuration resource. The message will be accompanied by a more detailed description of the problem.

2.154.3 Resolution

This error may indicate an internal configuration problem; report this to your administrator.

2.155 -121525 ERR_PLUG_IN_NO_CONFIGS

2.155.1 Message

ERROR: No plug-in configurations look-up table is available.

2.155.2 Description

An internal error that indicates that the domain configuration or path resolver configuration could not be loaded because there was no plug-in configurations look-up table provided to the parser to use when resolving the purposes of the plug-ins.

2.155.3 Resolution

This is an internal error; report it to your administrator.

2.156 -121526 ERR_PLUG_IN_NO_PROPERTY

2.156.1 Message

ERROR: The plug-in class '*%1s*' requires a configuration property '*%2s*', but that property was not set or was set incorrectly.

Message placeholders:

%1s

The name of the plug-in class.

%2s

The name of the missing or incorrect configuration property.

2.156.2 Description

A configuration property required by a plug-in class was not provided in the plug-in configuration or the value provided is not supported. Associated error messages may provide more details.

2.156.3 Resolution

If this is a domain or style plug-in, check that the plug-in was correctly configured and that the named property was set to a valid value. If this is a path resolver plug-in, report the error to your administrator.

2.157 -121527 ERR_PLUG_IN_NO_LOCAL_PLUG_IN

2.157.1 Message

ERROR: The plug-in class '*%1s*' requires a local plug-in to be configured for the local purpose '*%2s*', but no local plug-in was configured for that purpose.

Message placeholders:

%1s

The name of the plug-in class.

%2s

The local purpose.

2.157.2 Description

A local plug-in required by a plug-in class was not provided in the plug-in configuration. Associated error messages will provide more details.

2.157.3 Resolution

If this is a domain or style plug-in, check that the plug-in was correctly configured and that a local plug-in with the correct name was configured for the named local purpose. If this is a path resolver plug-in, report the error to your administrator.

2.158 -121528 ERR_PLUG_IN_BAD_LOCAL_PLUG_IN

2.158.1 Message

ERROR: The plug-in class '*%1s*' requires a local plug-in with the name '*%2s*' to be configured for the local purpose '*%3s*', but no local plug-in was configured or the reported name is incorrect.

Message placeholders:

%1s

The name of the plug-in class.

%2s

The expected name of the plug-in.

%3s

The local purpose.

2.158.2 Description

A local plug-in required by a plug-in class was not provided in the plug-in configuration or the plug-in provided does not report the expected name. Associated error messages may provide more details.

2.158.3 Resolution

If this is a domain or style plug-in, check that the plug-in was correctly configured and that a local plug-in with the correct name was configured for the named local purpose. If this is a path resolver plug-in, report the error to your administrator.

2.159 -121529 ERR_PLUG_IN_REJECTED_CONFIG

2.159.1 Message

ERROR: The plug-in class '*%1s*' could not be loaded as it rejected its configuration.

Message placeholders:

%1s

The name of the plug-in class.

2.159.2 Description

When a plug-in class was loaded a check was made to ensure that it was configured correctly, but the plug-in rejected the configuration and the loading did not complete. Each plug-in can accept or reject its configuration; some may provide more details on the reason for the rejection in an associ-

ated error message.

2.159.3 Resolution

Locate the configuration of the named plug-in class and ensure that it is configured with all of the required configuration properties and local plug-ins.

2.160 -121530 ERR_PLUG_IN_REJECTED_DATA

2.160.1 Message

ERROR: The plug-in class '*%1s*' rejected data of type '*%2s*'.

Message placeholders:

%1s

The name of the plug-in class.

%2s

The class name of the data, or “null” if the data was null.

2.160.2 Description

Before a plug-in class was invoked a check was made to ensure that it could handle the data that was to be passed to it, but the plug-in rejected the data. Each plug-in can accept or reject data. A plug-in will usually reject data if it is null or is of a type that it cannot handle. Some plug-ins may provide more details on the reason for the rejection in an associated error message.

2.160.3 Resolution

Locate the configuration of the named plug-in class and ensure that it is used in a context in which the data provided will be acceptable. For example, ensure that a domain plug-in is associated with a domain definition of a compatible type.

2.161 -121600 ERR_PATH_PLUG_IN_INVALID

2.161.1 Message

ERROR: A path resolver plug-in for the prefix path '*%1s*' could not be loaded because it was invalid.

Message placeholders:

%1s

The prefix path with which the plug-in was associated.

2.161.2 Description

A path resolver plug-in could not be loaded for the named prefix path. An associated error message will provide more details on the reason for the failure.

2.161.3 Resolution

See the associated error message for more details. This is an internal error; contact your administrator.

2.162 -121601 ERR_PATH_PLUG_IN_NAME_INVALID

2.162.1 Message

ERROR: A path resolver plug-in for the prefix path '*%1s*' could not be loaded because the plug-in name '*%2s*' is not valid.

Message placeholders:

%1s

The prefix path with which the plug-in is associated.

%2s

The name of the plug-in configured for this path.

2.162.2 Description

A path resolver plug-in could not be loaded for the named prefix path because the path resolver configuration specified an invalid plug-in name. The path resolver configuration supports only one type of plug-in named “path-resolver”; any other plug-in name in the configuration is invalid.

2.162.3 Resolution

See the associated error message for more details on the location of the error. This is an internal error; contact your administrator.

2.163 -121602 ERR_PATH_RESOLVER_NOT_FOUND

2.163.1 Message

ERROR: A path resolver plug-in for the '*%1s*' path could not be found.

Message placeholders:

%1s

The path used to find the plug-in.

2.163.2 Description

A path resolver plug-in could not be found to handle the named path.

2.163.3 Resolution

Check that the path is valid and correct it if necessary. If the error persists, contact your administrator.

2.164 -121603 ERR_PATH_BAD_NAME_OR_PURPOSE

2.164.1 Message

ERROR: The path resolver for the prefix path '*%1s*' cannot be configured: a 'purpose' or 'class' attribute must be given, but not both.

Message placeholders:

%1s

The prefix path being configured.

2.164.2 Description

The path resolver configuration data contains a path resolver plug-in configuration that has no `purpose` or `class` attribute, or has both a `purpose` and a `class` attribute. One, and only one, of these attributes must be present.

2.164.3 Resolution

Check the path resolver configuration data to ensure that the plug-in element for the prefix path has the required attributes.

2.165 -121604 ERR_PATH_NO_PATH_FACTORY

2.165.1 Message

ERROR: No path resolver container factory is available.

2.165.2 Description

An internal error that indicates that the path resolver configuration could not

be loaded because there was no path resolver container factory object provided to the parser.

2.165.3 Resolution

This is an internal error; report it to your administrator.

2.166 -121605 ERR_PATH_NO_PATHS

2.166.1 Message

ERROR: No path resolvers look-up table is available.

2.166.2 Description

An internal error that indicates that the path resolver configuration could not be loaded because there was no path resolvers look-up table provided to the parser and to which the parser would add the loaded path resolver configurations.

2.166.3 Resolution

This is an internal error; report it to your administrator.

2.167 -121606 ERR_PATH_INIT_FACTORY_FAILED

2.167.1 Message

ERROR: A path resolver-related factory class could not be created: '%1s'.

Message placeholders:

%1s

The name of the factory class that could not be created.

2.167.2 Description

A factory class used internally to build the repository of path resolver information could not be created. This is an internal error; see the accompanying error messages for more information.

2.167.3 Resolution

This is an internal error; report it to your administrator.

2.168 -121607 ERR_PATH_INIT_FAILED

2.168.1 Message

ERROR: Path resolver initialization failed before loading '*%1s*'.

Message placeholders:

%1s

The resource that was being loaded.

2.168.2 Description

An error occurred while attempting to load the named path resolver configuration resource. The message will be accompanied by a more detailed description of the problem.

2.168.3 Resolution

This error may indicate an internal configuration problem; report this to your administrator.

2.169 -121608 ERR_PATH_INIT_PARSE_FAILED

2.169.1 Message

ERROR: Invalid content in the path resolver configuration resource '*%1s*'.

Message placeholders:

%1s

The resource containing the invalid content.

2.169.2 Description

The contents of a path resolver configuration resource is not valid: it may not be well-formed XML or it may contain other errors. If this error occurs, a Cúram web application cannot function. The message may be followed by a more detailed description of the problem, or may be preceded by specific error messages in the server log.

2.169.3 Resolution

Path resolver information is loaded from “resources”: copies of the original files that are placed on the application's classpath. The file name part of the resource name should indicate the name of the original file that contains the

error. The error indicates a problem either in the syntax of the file, or in the semantics of the information. The file might contain XML that is not well-formed, or it might not conform to the required XML schema. The values provided may not be valid or supported, or, in the case of plug-in configurations, the referenced plug-ins may not be valid.

This is an internal error; report this error to your administrator.

2.170 -121609 ERR_PATH_INVALID_PREFIX

2.170.1 Message

ERROR: A path configuration for prefix '*%1s*' is invalid or ambiguous.

Message placeholders:

%1s

The prefix path that is invalid.

2.170.2 Description

The path resolver configuration associates a path resolver plug-in with a prefix path that is too short or that is ambiguous with respect to another prefix path in the configuration. Each prefix path must have at least one path step and no prefix path may match another prefix path. For example, the prefix path `/a` matches the first step of the prefix path `/a/b` and so is ambiguous and invalid.

2.170.3 Resolution

This is an internal error; report this error to your administrator.

2.171 -121610 ERR_PATH_NO_PREFIX

2.171.1 Message

ERROR: The path configuration defines a path with no prefix.

2.171.2 Description

The path resolver configuration defines a path resolver without providing any prefix path via the `prefix` attribute. The attribute is either missing or is set to an empty string value.

2.171.3 Resolution

This is an internal error; report it to your administrator.

2.172 -121611 ERR_PATH_NO_RESOLVER

2.172.1 Message

ERROR: No path resolver plug-in was specified for the '*%1s*' prefix path.

Message placeholders:

%1s

The prefix path of the path resolver that is missing a plug-in.

2.172.2 Description

A path resolver was configured for a prefix path, but no path resolver plug-in was associated with that prefix.

2.172.3 Resolution

This is an internal error; report it to your administrator.

2.173 -121612 ERR_PATH_ACCESS_DENIED

2.173.1 Message

ERROR: The path resolver plug-in class '*%1s*' denied access to the requested data for the partial path '*%2s*'.

Message placeholders:

%1s

The name of the path resolver plug-in class.

%2s

The partial path being resolved by the plug-in.

2.173.2 Description

When resolving the data identified by a partial path, a path resolver plug-in denied access to the data. This may occur when writing a value to a data source that is read-only or when accessing other protected values for which the user does not have sufficient access privileges. Associated error messages will provide more details.

2.173.3 Resolution

See the associated error messages for more details. The error is likely to be in the code of a custom plug-in that is using the `DataAccessor` class to set a value for a data source that is read-only. Alternatively, the user may not have sufficient security privileges to read the requested data, in which case assigning them the correct user role should correct the issue.

2.174 -121613 ERR_PATH_ACCESS_INVALID

2.174.1 Message

ERROR: The path resolver plug-in class '*%1s*' attempted to access data for the partial path '*%2s*' in an invalid manner.

Message placeholders:

%1s

The name of the path resolver plug-in class.

%2s

The partial path being resolved by the plug-in.

2.174.2 Description

When resolving the data identified by a path, a path resolver plug-in reported that the manner of access was invalid. This happens when an attempt is made to access a single value as a list of values or *vice versa*. It may also happen if list access is not supported for that type of path, or if the path represents not data, but an action that can be executed. Associated error messages may provide more details on the context in which this error occurred.

2.174.3 Resolution

See the associated error messages for more details. The cause of this error is likely to be in the code of a custom plug-in that is using the `DataAccessor` class to get a single value represented by a path that resolves to a list, or to get a list of values represented by a path that does not resolve to a list.

2.175 -121614 ERR_PATH_ACCESS_FAILED

2.175.1 Message

ERROR: The path resolver plug-in class '*%1s*' failed to access the requested data for the partial path '*%2s*'.

Message placeholders:

%1s

The name of the path resolver plug-in class.

%2s

The partial path being resolved by the plug-in.

2.175.2 Description

When resolving the data identified by a path, a path resolver plug-in failed to access the data. This happens when a path is missing or invalid with respect to the data source being accessed, or when the plug-in is not correctly configured. It may also occur if the path is shorter than the minimum path size expected by the plug-in. Associated error messages will provide more details on the context in which this error occurred.

2.175.3 Resolution

See the associated error messages for more details. The cause of this error is likely to be in the code of a custom plug-in that is using the `DataAccessor` class to get a value represented by an invalid path, or in the plug-in configuration information.

2.176 -121615 ERR_PATH_RESOLUTION_FAILED

2.176.1 Message

ERROR: The data accessor failed to resolve the data, or execute the action, specified by the path '**%1s**'.

Message placeholders:

%1s

The full path being resolved by the data accessor.

2.176.2 Description

When resolving the data, or executing the action, identified by a path, an error occurred either in the selection of an appropriate path resolver plug-in or in the operation of that plug-in. Associated error messages will provide more details on the context in which this error occurred.

2.176.3 Resolution

See the associated error messages for more details. The cause of this error is likely to be in the code of a custom plug-in that is using the `DataAccessor` class to get a value represented by an invalid path, or in the plug-in configuration information.

2.177 -121616 ERR_PATH_DATA_NOT_FOUND

2.177.1 Message

ERROR: The path resolver plug-in class '*%1s*' could not find the data identified by the partial path '*%2s*'.

Message placeholders:

%1s

The name of the path resolver plug-in class.

%2s

The partial path being resolved by the plug-in.

2.177.2 Description

When resolving the data identified by a path, no data was found. Associated error messages will provide more details on the context in which this error occurred.

2.177.3 Resolution

See the associated error messages for more details. The error is likely to be caused by a path that identifies data that does not exist. For example, a value in a properties file may not have been found, or a server interface may have no such property. Ensure that the path used is correct.

2.178 -121617 ERR_PATH_EXECUTE_INVALID

2.178.1 Message

ERROR: The path resolver plug-in class '*%1s*' attempted to execute the partial path '*%2s*', but that path is not executable.

Message placeholders:

%1s

The name of the path resolver plug-in class.

%2s

The partial path being executed by the plug-in.

2.178.2 Description

When executing an action described by a path, the path resolver rejected the path, as it is not valid to execute such paths. Associated error messages will

provide more details on the context in which this error occurred.

2.178.3 Resolution

See the associated error messages for more details. The error is likely to be caused by a malformed path or an attempt to execute a path that refers to data and not to an executable action. Ensure that the path used is correct.

2.179 -121618 ERR_PATH_EXECUTE_FAILED

2.179.1 Message

ERROR: The path resolver plug-in class '*%1s*' failed to execute the partial path '*%2s*'.

Message placeholders:

%1s

The name of the path resolver plug-in class.

%2s

The partial path being executed by the plug-in.

2.179.2 Description

When executing an action described by a path, a path resolver failed to execute the action. This happens when a path is missing or invalid with respect to the action being executed, when the plug-in is not correctly configured, or when the underlying execution fails. It may also occur if the path is shorter than the minimum path size expected by the plug-in. Associated error messages will provide more details on the context in which this error occurred.

2.179.3 Resolution

See the associated error messages for more details. The error is likely to be caused by a malformed path or an attempt to execute a path that refers to data and not to an executable action. Ensure that the path used is correct.

2.180 -121650 ERR_PATH_XPATH_BAD_STEP

2.180.1 Message

ERROR: Invalid step or invalid position for the step '*%1s*' in a simple XPath expression represented by a path.

Message placeholders:

%1s

The string representation of the invalid step.

2.180.2 Description

When evaluating a simple XPath expression represented by a path object, a step in the path was invalid or was in a position within the path that is invalid for that type of step. This occurs if the syntax of the step is invalid, if a function step is present, but is not the last step, or if an attribute selection step is present and is not the last step or is not followed by a function step. A step may be considered invalid if it does not contain a selector that is a qualified or un-qualified attribute or element name, if it contains more than one predicate, or if the predicate value is invalid or unsupported.

2.180.3 Resolution

Determine where the request was made to evaluate the path and correct the invalid step.

2.181 -121651 ERR_PATH_XPATH_BAD_FUNCTION

2.181.1 Message

ERROR: The function step '*%1s*' is invalid or unsupported in a simple XPath expression represented by a path.

Message placeholders:

%1s

The string representation of the invalid function step.

2.181.2 Description

When evaluating a simple XPath expression represented by a path object, a step in the path representing an XPath function was invalid or the function is not supported.

2.181.3 Resolution

Determine where the request was made to evaluate the path and correct the invalid function step.

2.182 -121652 ERR_PATH_XPATH_BAD_INDEX

2.182.1 Message

ERROR: The step '*%1s*' in a simple XPath expression represented by a path contains an index predicate that is not a positive integer value.

Message placeholders:

%1s

The string representation of the invalid step.

2.182.2 Description

When evaluating a simple XPath expression represented by a path object, a step in the path contains an index predicate that is not a positive integer value (greater than zero). Only positive integer predicates are allowed.

2.182.3 Resolution

Determine where the request was made to evaluate the path and correct the invalid predicate value.

2.183 -121653 ERR_PATH_XPATH_BAD_DOC

2.183.1 Message

ERROR: An attempt was made to evaluate a simple XPath expression represented by a path using a context node that was not within the document identified when the XPath engine was created.

2.183.2 Description

When evaluating a simple XPath expression represented by a path object, the given context node was not within the document that was identified at the time that the XPath engine object was created. In order to permit optimizations, the context nodes passed to any given instance of the XPath engine must be within the same DOM document.

2.183.3 Resolution

Locate the code that invoked the XPath engine and ensure that the correct context node is passed to the correct instance of the XPath engine. If the error is not in custom code, report it to technical support.

2.184 -121701 ERR_DOMAIN_NO_CONVERTER

2.184.1 Message

ERROR: No data converter was specified for the '*%1s*' domain.

Message placeholders:

%1s

The name of the domain that is missing the converter.

2.184.2 Description

A domain definition configuration does not specify a data converter plug-in. Every domain definition must have an associated converter plug-in class that performs the formatting of values in the domain for display and the parsing of values in the domain when entered by the user. The converter plug-in can be specified for each domain definition, or it can be inherited from an ancestor domain definition.

2.184.3 Resolution

Check that the named domain is properly configured.

2.185 -121702 ERR_DOMAIN_NO_COMPARATOR

2.185.1 Message

ERROR: No data comparator was specified for the '*%1s*' domain.

Message placeholders:

%1s

The name of the domain that is missing the comparator.

2.185.2 Description

A domain definition configuration does not specify a data comparator plug-in. Every domain definition must have an associated comparator plug-in class that is used when checking maximum and minimum values in a domain and when sorting data. The comparator plug-in can be specified for each domain definition, or it can be inherited from an ancestor domain definition.

2.185.3 Resolution

Check that the named domain is properly configured.

2.186 -121703 ERR_DOMAIN_NO_RENDERER

2.186.1 Message

ERROR: No data renderer was specified for the '*%1s*' domain.

Message placeholders:

%1s

The name of the domain that is missing the renderer.

2.186.2 Description

A domain definition configuration does not specify a data renderer plug-in. Every domain definition must have an associated renderer plug-in class that renders the formatted values in the domain for display on a page using the appropriate markup. The renderer plug-in can be specified for each domain definition, or it can be inherited from an ancestor domain definition.

2.186.3 Resolution

Check that the named domain is properly configured.

2.187 -121704 ERR_DOMAIN_NO_MARSHAL

2.187.1 Message

ERROR: No data marshal was specified for the '*%1s*' domain.

Message placeholders:

%1s

The name of the domain that is missing the marshal.

2.187.2 Description

A domain definition configuration does not specify a data marshal plug-in. Every domain definition must have an associated marshal plug-in class that extracts values from complex domain values and assembles values that are separated when edited in a form. The marshal plug-in can be specified for each domain definition, or it can be inherited from an ancestor domain definition.

2.187.3 Resolution

Check that the named domain is properly configured.

2.188 -121705 ERR_DOMAIN_NO_DEFAULT

2.188.1 Message

ERROR: No default data value was specified for the '*%1s*' domain.

Message placeholders:

%1s

The name of the domain that has no default value.

2.188.2 Description

A domain definition configuration does not specify a default value plug-in. Every domain definition must have an associated default value plug-in class that provides the default value for use when a user enters no data in a form field. The default value plug-in can be specified for each domain definition, or it can be inherited from an ancestor domain definition.

2.188.3 Resolution

Check that the named domain is properly configured.

2.189 -121706 ERR_DOMAIN_NULL_DEFAULT

2.189.1 Message

ERROR: The default value of the '*%1s*' domain is null, but that is not permitted.

Message placeholders:

%1s

The name of the domain that has a null default value.

2.189.2 Description

Although a domain definition has a properly configured default value plug-in, the plug-in is returning an illegal `null` value as the default.

2.189.3 Resolution

Check that the default value plug-in specified for, or inherited by, the named domain does not return a `null` default value.

2.190 -121707 ERR_DOMAIN_OPTION_INVALID_VALUE

2.190.1 Message

ERROR: The domain definition option value '*%1s*' is not in a recognized

format.

Message placeholders:

%1s

The string value of the option.

2.190.2 Description

The value of a domain definition option could not be parsed because it was not in the expected format for that option. There are four types of domain definition option value: size values that must be integers; pattern values that must be regular expressions; default and range values that must be in the generic format specific to the base type of the domain; and string values that are not restricted.

For default and range values, the value must be in the correct generic format; this error may be reported along with *ERR_CONV_GENERIC_PARSE_FAILED* if the generic format has not been used.

2.190.3 Resolution

Locate the value in the UML model and enter it in the correct format.

2.191 -121708 ERR_DOMAIN_NO_CODE_TABLE

2.191.1 Message

ERROR: The domain '*%1s*' is not associated with a code-table or the code-table name is null or empty.

Message placeholders:

%1s

The domain name.

2.191.2 Description

The named domain definition was expected to have an associated code-table name, but that domain is either not associated with a code-table or the code-table name was reported as null or empty. This may occur in a context where a domain plug-in, such as a renderer plug-in, expects to be associated with a domain that represents a code-table value but has instead been associated with a non-code-table domain. Associated error messages will provide more details about the context of the error.

2.191.3 Resolution

See the associated error messages for more details about the context of the error and the likely resolution.

2.192 -121710 ERR_DOMAIN_NO_DOMAIN_FACTORY

2.192.1 Message

ERROR: No domain object factory is available.

2.192.2 Description

An internal error that indicates that the meta-data for the domain definitions could not be loaded because there was no domain object factory provided to the parser.

2.192.3 Resolution

Report the error to your administrator.

2.193 -121711 ERR_DOMAIN_NO_OPTIONS

2.193.1 Message

ERROR: No domain options object is available.

2.193.2 Description

An internal error that indicates that the meta-data for the domain definitions is incomplete because there are no domain definition options accessible to the infrastructure.

2.193.3 Resolution

Report the error to your administrator.

2.194 -121712 ERR_DOMAIN_NO_DOMAINS

2.194.1 Message

ERROR: No domains look-up table is available.

2.194.2 Description

An internal error that indicates that the meta-data for the domain definitions

or the domain configurations could not be loaded because there was no domains look-up table provided to the parser and to which the parser would add the loaded domains or locate the domains requiring configuration.

This can also indicate that an attempt was made to look up domain information before that information was loaded.

2.194.3 Resolution

Report the error to your administrator.

2.195 -121713 ERR_DOMAIN_NO_DOMAIN

2.195.1 Message

ERROR: An attempt was made to add information about a null domain.

2.195.2 Description

An attempt was made to add a null domain to the domains look-up table or the domain hierarchy. This operation is usually performed by the domain definitions meta-data parser.

2.195.3 Resolution

Check that the domain definitions meta-data file is well-formed and has not been corrupted; re-generate the file if necessary. If the error persists, report it to your administrator; it may indicate an internal problem.

2.196 -121714 ERR_DOMAIN_DUPLICATE

2.196.1 Message

ERROR: The information for the '%1s' domain was already added and cannot be added again.

Message placeholders:

%1s

The name of the domain definition.

2.196.2 Description

An attempt was made to add a domain object to the domains look-up table or the domain hierarchy, but a domain object with the same name was already present or the same domain object was already present. This opera-

tion is normally performed when parsing the domain definitions meta-data.

2.196.3 Resolution

Check that the domain definition is not defined twice in the UML model or that the name of a domain definition does not conflict with a domain definition in the application infrastructure model. Check that the domain definitions meta-data file is well-formed and has not been corrupted; re-generate the file if necessary. If the error persists, report it to your administrator; it may indicate an internal problem.

2.197 -121715 ERR_DOMAIN_INVALID_NAME

2.197.1 Message

ERROR: The domain name '*%1s*' is not a valid name.

Message placeholders:

%1s

The invalid name of the domain definition.

2.197.2 Description

A domain name was encountered that was not in a valid form for a domain name. The name of a domain is subject to the same rules governing the construction of Java identifiers. A domain name that matches a Java keyword is not considered invalid. Consult the *Java Language Specification* [<http://java.sun.com/docs/books/jls>] for more details on the characters that can be used to form identifiers.

2.197.3 Resolution

Check that the domain name is a valid Java identifier. Check that the domains configuration file does not contain any invalid domain names. Check that the domain definitions meta-data file is well-formed and has not been corrupted; re-generate the file if necessary. If the error persists, report it to your administrator; it may indicate an internal problem.

2.198 -121716 ERR_DOMAIN_NO_NAME

2.198.1 Message

ERROR: A request for domain information did not specify a domain name.

2.198.2 Description

A internal error that indicates that a request to the domains look-up table for information about a domain did not specify the name of a domain. Typically, this indicates a problem with the code generators or the corruption of the generated files.

2.198.3 Resolution

Check that the domains configuration file does not contain any domain configurations that are missing the name attribute or have an empty name attribute. Check that the domain definitions meta-data file is well-formed and has not been corrupted; re-generate all code again if necessary. If the error persists, report it to your administrator; it may indicate an internal problem.

2.199 -121717 ERR_DOMAIN_NOT_FOUND

2.199.1 Message

ERROR: Domain information for the domain '*%1s*' could not be found.

Message placeholders:

%1s

The name of the domain definition.

2.199.2 Description

A internal error that indicates that a request to the domains look-up table for information about a domain did not yield a result. Typically, this indicates a problem with the code generators or the corruption of the generated files.

2.199.3 Resolution

Check that the domain definitions meta-data file is well-formed and has not been corrupted; re-generate all code again if necessary. If the error persists, report it to your administrator; it may indicate an internal problem.

2.200 -121720 ERR_DOMAIN_BAD_NAME_OR_PURPOSE

2.200.1 Message

ERROR: The '*%1s*' domain cannot be configured: a 'purpose' or 'class' attribute must be given, but not both.

Message placeholders:

%1s

The name of the domain definition.

2.200.2 Description

The domain configuration data contains a domain plug-in configuration that has no `purpose` or `class` attribute, or has both a `purpose` and a `class` attribute. One, and only one, of these attributes must be present.

2.200.3 Resolution

Check the domain configuration data to ensure that all plug-in elements for the named domain each have the required attributes.

2.201 -121721 ERR_DOMAIN_NOT_CONFIGURABLE

2.201.1 Message

ERROR: The '*%1s*' domain cannot be configured because it is immutable.

Message placeholders:

%1s

The name of the domain definition.

2.201.2 Description

An internal error that indicates that a domain configuration could not be loaded because the corresponding domain object is immutable.

2.201.3 Resolution

Report the error to your administrator.

2.202 -121722 ERR_DOMAIN_PLUG_IN_FAILURE

2.202.1 Message

ERROR: A plug-in for the '*%1s*' domain needed during data conversion was inaccessible or failed.

Message placeholders:

%1s

The name of the domain definition.

2.202.2 Description

During data conversion, a variety of plug-ins are used but when a necessary plug-in was requested, it was unavailable or incorrectly configured. A specific error message will accompany this one.

2.202.3 Resolution

See the associated error message for more details.

2.203 -121723 ERR_DOMAIN_PLUG_IN_INVALID

2.203.1 Message

ERROR: A domain plug-in for the '*%1s*' domain could not be loaded because it was invalid.

Message placeholders:

%1s

The name of the domain definition.

2.203.2 Description

A domain plug-in could not be loaded for the named domain. An associated error message will provide more details on the reason for the failure.

2.203.3 Resolution

See the associated error message for more details and then correct the domain configuration, the plug-in configuration, or the plug-in class as appropriate.

2.204 -121724 ERR_DOMAIN_CHILD_INVALID

2.204.1 Message

ERROR: A domain '*%1s*' could not be added as a child of the '*%2s*'.

Message placeholders:

%1s

The name of the child domain definition.

%2s

The name of the parent domain definition.

2.204.2 Description

A domain definition could not be added as a child of its parent domain definition due to an error. An associated error message will provide more details on the reason for the failure.

2.204.3 Resolution

See the associated error message for more details. Regenerate all code if necessary.

2.205 -121725 ERR_DOMAIN_INIT_FACTORY_FAILED

2.205.1 Message

ERROR: A domain-related factory class could not be created: '%1s'.

Message placeholders:

%1s

The name of the factory class that could not be created.

2.205.2 Description

A factory class used internally to build the repository of domain information could not be created. This is an internal error; see the accompanying error messages for more information.

2.205.3 Resolution

This is an internal error; report it to your administrator.

2.206 -121726 ERR_DOMAIN_INIT_FAILED

2.206.1 Message

ERROR: Domain definition initialization failed before loading '%1s'.

Message placeholders:

%1s

The resource that was being loaded.

2.206.2 Description

An error occurred while attempting to load the named domain definition or configuration resource. The message will be accompanied by a more detailed description of the problem.

2.206.3 Resolution

This error may indicate an internal configuration problem; report this to your administrator.

2.207 -121727 ERR_DOMAIN_INIT_PARSE_FAILED

2.207.1 Message

ERROR: Invalid content in the domain definition or configuration resource '*%1s*'.

Message placeholders:

%1s

The resource containing the invalid content.

2.207.2 Description

The contents of a domain definition or configuration resource is not valid: it may not be well-formed XML or it may contain other errors. If this error occurs, a Cúram web application cannot function. The message may be followed by a more detailed description of the problem, or may be preceded by specific error messages in the server log.

2.207.3 Resolution

Domain information is loaded from “resources”: copies of the original files that are placed on the application's classpath. The file name part of the resource name should indicate the name of the original file that contains the error. The error indicates a problem either in the syntax of the file, or in the semantics of the information. The file might contain XML that is not well-formed, or it might not conform to the required XML schema. The values provided may not be valid or supported, or, in the case of plug-in configurations, the referenced plug-ins may not be valid.

Identify the problems from the accompanying information, correct them, and rebuild the application.

2.208 -121750 ERR_DOMAIN_MARSHAL_FATAL

2.208.1 Message

ERROR: Marshaling of form items for the path '*%1s*' failed.

Message placeholders:

%1s

The path being resolved.

2.208.2 Description

Marshal plug-ins are used to assemble multiple form items into a single value. This message indicates that an error occurred *before* the marshal plug-in could be invoked to assemble the data. A nested exception will be provided with this message to assist in trouble shooting the issue.

2.208.3 Resolution

This message wraps a nested exception which prevent the marshal plug-in from being invoked. Consult the documentation of the nested exception to assist in troubleshooting the issue.

2.209 -121751 ERR_DOMAIN_MARSHAL_FAILED

2.209.1 Message

ERROR: Failed to resolve the extended path '*%1s*' in the domain marshal class '*%2s*'.

Message placeholders:

%1s

The extended path being resolved by the marshal.

%2s

The name of the domain marshal plug-in class.

2.209.2 Description

When a domain marshal was invoked to resolve the extended part of a path against the value of a server interface property, it failed to resolve any value. This may be due to an invalid path or an invalid value. An associated error message may provide more information.

2.209.3 Resolution

Read the associated error message (if any) for further information about the cause of the problem. If the named domain marshal plug-in is a custom plug-in class, then check that class to ensure that it is correct. Check that the data is in the correct form for that type of domain marshal. If the plug-in class is not a custom plug-in and the data is correct, report the error to technical support.

2.210 -121752

ERR_DOMAIN_MARSHAL_XPATH_BAD_NODE

2.210.1 Message

ERROR: Failed to resolve the extended path '*%1s*' in the domain marshal class '*%2s*' because the simple XPath expression represented by the path selected a type of node '*%3s*' not supported by the marshal.

Message placeholders:

%1s

The extended path being resolved by the marshal.

%2s

The name of the domain marshal plug-in class.

%3s

The name of the unsupported node class.

2.210.2 Description

When a domain marshal was invoked to resolve the extended part of a path against the value of a server interface property, it failed to resolve the value because the simple XPath expression represented by the path selected a type of DOM node that the marshal plug-in class does not support. This may be due to an invalid path or an incompatible customization to the XPath-based marshal plug-ins and support classes. Only nodes that are elements or attributes may be selected by simple XPath expressions; all non-node types are supported (for example, atomic values returned from XPath functions).

2.210.3 Resolution

If the named domain marshal plug-in is a custom plug-in class, then check that class to ensure that it is passing the correct values to the base class for data conversion. Check that the data is in the correct form for that type of domain marshal. If the plug-in class is not a custom plug-in and the data and paths are correct, report the error to technical support.

2.211 -121800 ERR_RENDER_INVALID_FORM_FIELD

2.211.1 Message

ERROR: An attempt was made to add an invalid field to a form or retrieve the initial value of an invalid field.

2.211.2 Description

A domain renderer attempted to add a field to a form or retrieve the value of a field from a form, but the field was null or was missing the required information. Each form field must define a domain and a target path.

2.211.3 Resolution

Associated error information will indicate which domain renderer class caused the error to occur. Ensure that the renderer only adds valid fields to the form and only attempts to retrieve the initial value of valid fields. If the renderer is not a custom renderer, contact technical support.

2.212 -121801 ERR_RENDER_INVALID_FIELD_TARGET

2.212.1 Message

ERROR: An attempt was made to add a field with an invalid target path '*%1s*' to a form or to retrieve the initial value of that field.

Message placeholders:

%1s

The target path.

2.212.2 Description

A domain renderer attempted to add a field to a form or retrieve the value of a field from a form, but the field did not have a target path that identified a server interface property. Each field must define a target path and the path may only target a server interface property.

2.212.3 Resolution

Associated error information will indicate which domain renderer class caused the error to occur. Ensure that the renderer only adds fields with valid target paths to the form and only attempts to retrieve the initial value of valid fields. If the renderer is not a custom renderer, contact technical support.

2.213 -121802 ERR_RENDER_EMPTY_CONTAINER

2.213.1 Message

ERROR: The container provided to the renderer '*%1s*' does not have child

components and therefore cannot be rendered.

Message placeholders:

%1s

The renderer class name.

2.213.2 Description

A `Container` renderer has specific requirements of the `Container` model supplied to it for rendering. For example, the default cluster renderer always outputs a cluster header and body. Therefore it expects the `Container` object supplied to it will have child components so the cluster body can be constructed.

2.213.3 Resolution

Associated error information will indicate which renderer class caused the error to occur. Consult the renderer class JavaDoc for its specific requirements of `Container` models supplied to it for rendering.

2.214 -121803 ERR_RENDER_NO_STYLE_OR_DOMAIN

2.214.1 Message

ERROR: A component of type '`%1s`' has no domain or style associated with it, so no renderer can be selected to render the component.

Message placeholders:

%1s

The component class name.

2.214.2 Description

A component has no associated domain or style information, so the system cannot determine what renderer to use to render the component to HTML.

2.214.3 Resolution

Check that any custom renderer classes that create component objects for further rendering do so correctly and do not omit the necessary domain or style information. If no problems can be found, report the error to your administrator.

2.215 -121804 ERR_RENDER_LOCAL_REJECTED_DATA

2.215.1 Message

ERROR: The renderer class '*%1s*' failed to render data for its local purpose '*%2s*' because the renderer class '*%3s*' configured for that local purpose rejected the data.

Message placeholders:

%1s

The name of the main renderer class.

%2s

The local purpose name.

%3s

The name of the local renderer class.

2.215.2 Description

The main renderer was configured to invoke a local renderer for some purpose, but the local renderer rejected the data that was passed to it for some reason. Typically, the data will be of a type that is not supported by the local renderer or will be null. An associated error message may provide more details.

2.215.3 Resolution

Locate the configuration for renderer or check the implementation of the renderer and ensure that the chosen local renderer plug-in is compatible and that it was invoked correctly.

2.216 -121805 ERR_RENDER_INITIAL_VALUE_FAILURE

2.216.1 Message

ERROR: Failed to get an initial value for the target path '*%1s*' and domain '*%2s*'.

Message placeholders:

%1s

The target path.

%2s

The name of the domain definition.

2.216.2 Description

When getting the initial value for a form field, an error occurred. This is most likely an error when falling back to use the default value for the associated domain or when formatting the default value for display. An associated error message will provide more details.

2.216.3 Resolution

Ensure that the named domain is configured correctly with a non-null default value and the correct converter plug-in.

2.217 -121806

ERR_RENDER_PROPERTY_RESOURCE_ID_NOT_SPECIFIED

2.217.1 Message

ERROR: The renderer '*%1s*' cannot continue as the property resource identifier required by it has not been specified.

Message placeholders:

%1s

The renderer class name.

2.217.2 Description

The progress wizard bar renderer requires a property resource identifier to be specified to allow it to retrieve the required properties to draw the wizard progress bar. This identifier may be specified in the associated UIM as either a constant from a constants file, a page parameter passed to that UIM page or a display phase bean parameter on the UIM page. If none of these sources resolve to a valid property resource identifier, then this exception will be thrown by the renderer as it cannot continue.

2.218 -121807

ERR_RENDER_PROPERTY_MUST_BE_NUMERIC

2.218.1 Message

ERROR: The value of the property '*%1s*' required by the renderer '*%2s*' must be numeric. Its current value is '*%3s*'.

Message placeholders:

%1s

The name of the property required by the renderer.

%2s

The renderer class name.

%3s

The current value of the required property.

2.218.2 Description

The progress wizard bar renderer requires a property called 'Number.Wizard.Pages' that specifies the number of pages contained in the wizard. The value of this property must be numeric and if not the renderer will throw this exception.

2.218.3 Resolution

Check the property resource that is specified for the wizard progress bar that is being rendered and ensure that the value of the 'Number.Wizard.Pages' property is numeric.

2.219 -121808

ERR_RENDER_PROPERTY_MUST_BE_GREATER_THAN_ZERO

2.219.1 Message

ERROR: The value of the property '*%1s*' required by the renderer '*%2s*' must be a number greater than zero. Its current value is '*%3s*'.

Message placeholders:

%1s

The name of the property required by the renderer.

%2s

The renderer class name.

%3s

The current value of the required property.

2.219.2 Description

The progress wizard bar renderer requires a property called 'Number.Wizard.Pages' that specifies the number of pages contained in the wizard. The value of this property must be a whole number greater than zero and if not the renderer will throw this exception.

2.219.3 Resolution

Check the property resource that is specified for the wizard progress bar that is being rendered and ensure that the value of the 'Number.Wizard.Pages' property is a whole number greater than zero.

2.220 -121810 ERR_RENDER_FAILED

2.220.1 Message

ERROR: An unknown or unexpected error occurred in the '%1s' renderer.

Message placeholders:

%1s

The renderer class name.

2.220.2 Description

An unknown or expected error occurred in a renderer plug-in. This is a non-specific error message that is usually accompanied by a more detailed error message.

2.220.3 Resolution

See the associated error message for more details.

2.221 -121820 ERR_RENDER_CT_NOT_HIERARCHY

2.221.1 Message

ERROR: The renderer class '%1s' failed to render a code-table field as the code-table '%2s' is not part of a hierarchy.

Message placeholders:

%1s

The renderer class name.

%2s

The name of the code-table associated with the field's domain.

2.221.2 Description

A renderer plug-in class that expected to render the controls for a code-table hierarchy selection detected that the code-table associated with the field's

domain was not part of a code-table hierarchy.

2.221.3 Resolution

Check that the named code-table is part of a code-table hierarchy and that the hierarchy contains more than one code-table. Check that the named renderer class was not configured accidentally for the wrong domain.

2.222 -121900 ERR_STYLE_PLUG_IN_INVALID

2.222.1 Message

ERROR: A style plug-in for the style '*%1s*' could not be loaded because it was invalid.

Message placeholders:

%1s

The name of the style with which the plug-in was associated.

2.222.2 Description

A style plug-in could not be loaded for the named style name. An associated error message will provide more details on the reason for the failure.

2.222.3 Resolution

See the associated error message for more details and then correct the style configuration, the plug-in configuration, or the plug-in class as appropriate.

2.223 -121901 ERR_STYLE_PLUG_IN_NAME_INVALID

2.223.1 Message

ERROR: A style plug-in for the style '*%1s*' could not be loaded because the plug-in name '*%2s*' is not valid.

Message placeholders:

%1s

The name of the style with which the plug-in is associated.

%2s

The name of the plug-in configured for this style.

2.223.2 Description

A style plug-in could not be loaded for the named style because the path resolver configuration specified an invalid plug-in name. The path resolver configuration supports only one type of plug-in named “component-renderer”; any other plug-in name in the configuration is invalid.

2.223.3 Resolution

See the associated error message for more details on the location of the error and correct the plug-in name.

2.224 -121902 ERR_STYLE_NO_RENDERER

2.224.1 Message

ERROR: No renderer was specified for the '*%1s*' style.

Message placeholders:

%1s

The name of the style that is missing the renderer.

2.224.2 Description

A style configuration does not specify a renderer plug-in. Every style must have an associated renderer plug-in class that renders the markup for the component with that style.

2.224.3 Resolution

Check that the named style is properly configured.

2.225 -121903 ERR_STYLE_NO_NAME

2.225.1 Message

ERROR: The style configuration defines a style with no name.

2.225.2 Description

The style configuration defines a style without providing any name via the name attribute. The attribute is either missing or is set to an empty string value.

2.225.3 Resolution

Correct the style configuration.

2.226 -121904 ERR_STYLE_NOT_FOUND

2.226.1 Message

ERROR: Style information for the style '*%1s*' could not be found.

Message placeholders:

%1s

The name of the style.

2.226.2 Description

A style was associated with a component to select how that component should be rendered, but no style with that name was found in the style configuration.

2.226.3 Resolution

Check that the style name is correct and that the style is defined in the style configuration file.

2.227 -121905 ERR_STYLE_BAD_NAME_OR_PURPOSE

2.227.1 Message

ERROR: A plug-in for the style '*%1s*' cannot be configured: a 'purpose' or 'class' attribute must be given, but not both.

Message placeholders:

%1s

The name of the style being configured.

2.227.2 Description

The style configuration data contains a plug-in configuration that has no `purpose` or `class` attribute, or has both a `purpose` and a `class` attribute. One, and only one, of these attributes must be present.

2.227.3 Resolution

Check the style configuration data to ensure that the plug-in element for the named style has the required attributes.

2.228 -121906 ERR_STYLE_NO_STYLE_FACTORY

2.228.1 Message

ERROR: No style factory is available.

2.228.2 Description

An internal error that indicates that the style configuration could not be loaded because there was no style factory object provided to the parser.

2.228.3 Resolution

This is an internal error; report it to your administrator.

2.229 -121907 ERR_STYLE_NO_STYLES

2.229.1 Message

ERROR: No styles look-up table is available.

2.229.2 Description

An internal error that indicates that the styles configuration could not be loaded because there was no styles look-up table provided to the parser and to which the parser would add the loaded style configurations.

2.229.3 Resolution

This is an internal error; report it to your administrator.

2.230 -121908 ERR_STYLE_INIT_FAILED

2.230.1 Message

ERROR: Style initialization failed before loading '%1s'.

Message placeholders:

%1s

The resource that was being loaded.

2.230.2 Description

An error occurred while attempting to load the named style configuration resource. The message will be accompanied by a more detailed description of the problem.

2.230.3 Resolution

This error may indicate an internal configuration problem; report this to your administrator.

2.231 -121909 ERR_STYLE_INIT_PARSE_FAILED

2.231.1 Message

ERROR: Invalid content in the style configuration resource '*%1s*'.

Message placeholders:

%1s

The resource containing the invalid content.

2.231.2 Description

The contents of a style configuration resource is not valid: it may not be well-formed XML or it may contain other errors. If this error occurs, a Cúram web application cannot function. The message may be followed by a more detailed description of the problem, or may be preceded by specific error messages in the server log.

2.231.3 Resolution

Style information is loaded from “resources”: copies of the original files that are placed on the application's classpath. The file name part of the resource name should indicate the name of the original file that contains the error. The error indicates a problem either in the syntax of the file, or in the semantics of the information. The file might contain XML that is not well-formed, or it might not conform to the required XML schema. The values provided may not be valid or supported, or, in the case of plug-in configurations, the referenced plug-ins may not be valid. The required namespace may not be present or may be wrong, or elements from other namespaces may be present.

2.232 -122100 ERR_CONV_PARSE_INVALID

2.232.1 Message

'*%0s*' is not a valid value.

Message placeholders:

%0s

The label of the field.

2.232.2 Description

A codetable field was assigned an invalid value.

2.232.3 Resolution

Ensure the value that has been entered/selected for a codetable field is valid before submitting the page.

2.233 -122101 ERR_CONV_PARSE_FAILED

2.233.1 Message

The field '*%0s*' contains a value '*%1s*' that is not in a recognized format.

Message placeholders:

%0s

The label of the field in error.

%1s

The value entered by the user in string format.

2.233.2 Description

A value entered by a user was not in the correct format and could not be parsed to a value of the expected data-type.

2.233.3 Resolution

Enter the value in a valid format.

2.234 -122102 ERR_CONV_PARSE_FAILED_DATE

2.234.1 Message

The field '*%0s*' is not valid. A date must be in the format '*%1s*', you have entered '*%2s*'.

Message placeholders:

%0s

The label of the field in error.

%1s

The accepted date format.

%2s

The value entered by the user in date format.

2.234.2 Description

A value entered by a user was not in the correct format for a date value and could not be recognized.

2.234.3 Resolution

Enter the value in the format shown.

2.235 -122103 ERR_CONV_PARSE_FAILED_DATE_TIME

2.235.1 Message

The field '*%0s*' is not valid. A date and time must be in the format '*%1s*', you have entered '*%2s*'.

Message placeholders:

%0s

The label of the field in error.

%1s

The accepted date-time format.

%2s

The value entered by the user in date-time format.

2.235.2 Description

A value entered by a user was not in the correct format for a date-time value and could not be recognized.

2.235.3 Resolution

Enter the value in the format shown.

2.236 -122104 ERR_CONV_PARSE_FAILED_TIME

2.236.1 Message

The field '*%0s*' must be a time in the format '*%1s*'.

Message placeholders:

%0s

The label of the field in error.

%1s

The accepted time format.

2.236.2 Description

A value entered by a user was not in the correct format for a time value and could not be recognized.

2.236.3 Resolution

Enter the value in the format shown.

2.237 -122105 ERR_CONV_PARSE_FAILED_MONEY

2.237.1 Message

The field '*%0s*' must be a valid money value.

Message placeholders:

%0s

The label of the field in error.

2.237.2 Description

A value entered by a user was not in the correct format for a money value and could not be recognized.

2.237.3 Resolution

Enter the value in the correct format.

2.238 -122106 ERR_CONV_PARSE_FAILED_CHAR

2.238.1 Message

The field '*%0s*' must be a single character, e.g., "a", "b".

Message placeholders:

%0s

The label of the field in error.

2.238.2 Description

A value entered by a user was not a single character as required.

2.238.3 Resolution

Enter the value correctly.

2.239 -122107 ERR_CONV_PARSE_FAILED_INT

2.239.1 Message

The field '*%0s*' must be a whole number.

Message placeholders:

%0s

The label of the field in error.

2.239.2 Description

A value entered by a user was not a whole number; no decimal point is allowed.

2.239.3 Resolution

Enter the value correctly.

2.240 -122108 ERR_CONV_PARSE_FAILED_FLOAT

2.240.1 Message

The field '*%0s*' must be a decimal number.

Message placeholders:

%0s

The label of the field in error.

2.240.2 Description

A value entered by a user was not a decimal number.

2.240.3 Resolution

Enter the value correctly.

2.241 -122109 ERR_CONV_PARSE_FAILED_BOOL

2.241.1 Message

The field '*%0s*' cannot be converted to a true or false, or yes or no, value.

Message placeholders:

%0s

The label of the field in error.

2.241.2 Description

A value entered by a user was not a boolean `true` or `false` value.

2.241.3 Resolution

Enter the value correctly.

2.242 -122110 ERR_CONV_PARSE_FAILED_CT

2.242.1 Message

The field '*%0s*' contains a code value '*%1s*' that is not a recognized code in the '*%2s*' code-table for the '*%3s*' locale.

Message placeholders:

%0s

The label of the field in error.

%1s

The code-table item code value.

%2s

The code-table name associated with the domain.

%3s

The locale for which translation was requested.

2.242.2 Description

This error can occur during the display phase of a page when values are be-

ing formatted, or during the action phase of a page when values are being parsed. It indicates that the code-table item code or the code-table name are invalid, that there is no code-table defined for the indicated locale, or that the code-table item code is not defined for that locale.

2.242.3 Resolution

Check that the code-table name is correctly defined in the UML model for the domain and that the domain is derived from a code-table root domain. Check that the code-tables have been loaded into the database for the specified locale. Check that the specified code is defined for the code-table and locale. Regenerate the application if necessary.

2.243 -122111 ERR_CONV_PARSE_FAILED_BLOB

2.243.1 Message

The field '*%0s*' must be a binary value encoded in base-64.

Message placeholders:

%0s

The label of the field in error.

2.243.2 Description

It would be highly unusual to have an input field that takes base-64-encoded binary data as the value, so either this error is due to the incorrect mapping of values between non-visible fields (for example, direct page connections), or the BLOB data-type has been used in error.

2.243.3 Resolution

Ensure that the correct data-type is being used and that mappings between fields are of compatible types.

2.244 -122112 ERR_CONV_PARSE_FAILED_TIME_EX

2.244.1 Message

The field '*%0s*' must be a time in the format '*%1s*', i.e. '*%3s*'

Message placeholders:

%0s

The label of the field in error.

%1s

The accepted time format.

%3s

Example of the time value in the accepted format.

2.244.2 Description

A value entered by a user was not in the correct format for a time value and could not be recognized.

2.244.3 Resolution

Enter the value in the format shown.

2.245 -122121 ERR_CONV_OVERFLOW

2.245.1 Message

The value of the field '*%0s*' cannot be stored; it must be between '*%1s*' and '*%2s*'.

Message placeholders:

%0s

The label of the field in error.

%1s

The minimum value allowed for this type.

%2s

The maximum value allowed for this type.

2.245.2 Description

When maximum and minimum values for a numeric domain definition are not explicitly specified in the UML model, the maximum and minimum values are determined by the data-type used to represent those values. Exceeding the allowable range for the data-type results in an error.

2.245.3 Resolution

A value with a smaller magnitude must be entered or the domain definition must be changed to support values with a larger magnitude.

2.246 -122122 ERR_CONV_OUT_OF_RANGE

2.246.1 Message

The field '*%0s*' must be between '*%1s*' and '*%2s*'.

Message placeholders:

%0s

The label of the field in error.

%1s

The minimum value allowed for this domain.

%2s

The maximum value allowed for this domain.

2.246.2 Description

When maximum and minimum values for a numeric domain definition are specified in the UML model, the user must enter values within that range. Most ranges are inclusive ranges, but the range for values such as money values is exclusive of the limits.

2.246.3 Resolution

Enter a value within the allowable range.

2.247 -122123 ERR_CONV_TOO_HIGH

2.247.1 Message

The field '*%0s*' must be less than or equal to '*%1s*'.

Message placeholders:

%0s

The label of the field in error.

%1s

The maximum value allowed for this domain.

2.247.2 Description

When only a maximum value for a numeric domain definition is specified in the UML model, the user must enter a value less than or equal to that value.

2.247.3 Resolution

Enter a value that does not exceed the maximum allowed.

2.248 -122124 ERR_CONV_TOO_LOW

2.248.1 Message

The field '*%0s*' must be greater than or equal to '*%1s*'.

Message placeholders:

%0s

The label of the field in error.

%1s

The minimum value allowed for this domain.

2.248.2 Description

When only a minimum value for a numeric domain definition is specified in the UML model, the user must enter a value greater than or equal to that value.

2.248.3 Resolution

Enter a value that is not less than the minimum allowed.

2.249 -122125 ERR_CONV_WRONG_SIZE

2.249.1 Message

The field '*%0s*' must have between '*%1s*' and '*%2s*' characters; you entered '*%3s*'.

Message placeholders:

%0s

The label of the field in error.

%1s

The minimum size allowed for this domain.

%2s

The maximum size allowed for this domain.

%3s

The number of characters or bytes entered.

2.249.2 Description

When the maximum and minimum number of characters or bytes for a string or BLOB domain definition are specified in the UML model, the user must enter values within that size range. For string values, double-byte characters are used, so the number of characters is half of the number of bytes. For BLOB values, the number of characters is equal to the number of bytes.

2.249.3 Resolution

Enter a value within the allowable size range.

2.250 -122126 ERR_CONV_TOO_SHORT

2.250.1 Message

The field '*%0s*' must have at least '*%1s*' characters; you entered '*%2s*'.

Message placeholders:

%0s

The label of the field in error.

%1s

The minimum length allowed.

%2s

The length of the value entered.

2.250.2 Description

When only a minimum number of characters or bytes for a string or BLOB domain definition are specified in the UML, the user must enter a value that meets that length requirement.

2.250.3 Resolution

Enter a value that is not shorter than the minimum length allowed.

2.251 -122127 ERR_CONV_TOO_LONG

2.251.1 Message

The value entered in the field '*%0s*' is too long (*%2s*) - maximum allowed is '*%1s*'.

Message placeholders:

%0s

The label of the field in error.

%1s

The maximum length allowed.

%2s

The length of the value entered.

2.251.2 Description

When only a maximum number of characters or bytes for a string or BLOB domain definition are specified in the UML, the user must enter a value that meets that length requirement.

2.251.3 Resolution

Enter a value that is not longer than the maximum length allowed.

2.252 -122128 ERR_CONV_NO_MATCH

2.252.1 Message

The field '*%0s*' does not match the expected pattern for that type of value.

Message placeholders:

%0s

The label of the field in error.

2.252.2 Description

When a regular expression pattern is set in the domain definition options in the UML model, the user must enter a value that matches that pattern.

2.252.3 Resolution

Enter a value that matches the expected pattern.

2.253 -122129 ERR_CONV_TOO_LARGE

2.253.1 Message

The uploaded data is too large (*%2s*) - Maximum size allowed is '*%1s*'.

Message placeholders:

%1s

The maximum size allowed.

%2s

The size of the uploaded data.

2.253.2 Description

When a maximum size of uploaded data for a string or BLOB domain definition is specified in the UML, the user must upload data that meets that size requirement.

2.253.3 Resolution

Upload data that is not larger than the maximum size allowed.

2.254 -122130 ERR_CONV_INVALID_TIME_ZONE

2.254.1 Message

ERROR: The time zone entered was invalid. Your changes to preference values have not been saved.

2.254.2 Description

The time zone string entered must be recognized by `java.util.TimeZone.getTimeZone()` as valid.

2.254.3 Resolution

Enter a valid time zone.

2.255 -122202 ERR_CONV_GENERIC_PARSE_FAILED

2.255.1 Message

ERROR: The value '*%1s*' is not in a recognized generic format.

Message placeholders:

%1s

The generically formatted string value.

2.255.2 Description

A value was not in the correct generic format and could not be parsed to a value of the expected data-type. Typically, generically formatted values are

used in the UML model to specify the domain definition options for the default, maximum and minimum values of data in that domain. The generic format used in the UML model is not specific to a locale, so values may need to be formatted differently to the format that would be used when entering data on an application page. For example, date-times use the ISO 8601 format “yyyyMMddThhmmss”.

2.255.3 Resolution

Enter the value in a valid generic format in the appropriate place in the UML model.

2.256 -122203 ERR_CONV_MESSAGE_L10N_FAILURE

2.256.1 Message

ERROR: The formatting of an externalized message failed. The message details were '*%1s*'.

Message placeholders:

%1s

The encoded message string on which localization was attempted.

2.256.2 Description

During the localization of an encoded message received from the application server, there was a failure in the parsing or localization of the message when formatting it for display. This message may be reported with more detailed messages describing the exact nature of the failure.

2.256.3 Resolution

Check the message string displayed and ensure that it is correctly formatted by the application server code. The detailed message should provide more assistance. Check that the message catalog containing the message is correctly located and that the message is defined within that message catalog.

2.257 -122204 ERR_CONV_FMT_WRONG_TYPE

2.257.1 Message

ERROR: The formatting of a value in the '*%1s*' domain failed because the type ('*%2s*') of the value to be formatted was incompatible with the type ('*%3s*') supported by the converter ('*%4s*').

Message placeholders:

%1s

The domain name for the value.

%2s

The class name of the object that was to be formatted.

%3s

The class name of the type supported by the formatter.

%4s

The class name of the formatter (converter).

2.257.2 Description

During the display phase of a page when the values were being formatted for presentation, a value could not be formatted because its type was incompatible with the formatting routine of the converter associated with the value's domain. For the types to be compatible, the type of the value must be assignable to the type supported by the converter. This indicates an error in the configuration of the domains or an error in the converter class.

2.257.3 Resolution

Check that the domain configuration is correct and that the correct converter classes have been associated with the correct domains. For a custom converter class, ensure that the class returns the correct type from the `getDomainClass` method.

2.258 -122205 ERR_CONV_FMT_NULL_VALUE

2.258.1 Message

ERROR: The formatting of a value in the '*%1s*' domain failed because the value was null.

Message placeholders:

%1s

The domain name for the value.

2.258.2 Description

During the display phase of a page when the values were being formatted for presentation, the value of a field could not be formatted because the value was null.

2.258.3 Resolution

The application server should never return a `null` value, so check that the server code is correct. If it is, report the problem; it may be an internal error.

2.259 -122206 ERR_CONV_FMTGEN_WRONG_TYPE

2.259.1 Message

ERROR: The generic formatting of a value in the '*%1s*' domain failed because the type ('*%2s*') of the value to be formatted was incompatible with the type ('*%3s*') supported by the converter ('*%4s*').

Message placeholders:

%1s

The domain name for the value.

%2s

The class name of the object that was to be formatted.

%3s

The class name of the type supported by the formatter.

%4s

The class name of the formatter (converter).

2.259.2 Description

When embedding values in an XML document being returned to the server, a value could not be formatted because its type was incompatible with the generic formatting routine of the converter associated with the value's domain. For the types to be compatible, the type of the value must be assignable to the type supported by the converter. This indicates an error in the configuration of the domains, an error in the converter class, or an internal error in the XML processing.

2.259.3 Resolution

Check that the domain configuration is correct and that the correct converter classes have been associated with the correct domains. For a custom converter class, ensure that the class returns the correct type from the `getDomainClass` method. If all these are correct, report the problem; it may be an internal error.

2.260 -122207 ERR_CONV_FMTGEN_NULL_VALUE

2.260.1 Message

ERROR: The generic formatting of a value in the '%1s' domain failed because the value was null.

Message placeholders:

%1s

The domain name for the value.

2.260.2 Description

When embedding values in an XML document being returned to the server, the value of a field could not be formatted because the value was null.

2.260.3 Resolution

Report the problem; it is likely that it is an internal error.

2.261 -122208 ERR_CONV_FMT_FAILED

2.261.1 Message

ERROR: The formatting or validation of a value in the '%1s' domain failed.

Message placeholders:

%1s

The domain name for the value.

2.261.2 Description

During the display phase of a page when the values were being formatted for presentation, the value of a field could not be formatted for some reason.

2.261.3 Resolution

See the associated error message for more details.

2.262 -122209 ERR_CONV_FMT_BAD_VALUE_FORMAT

2.262.1 Message

ERROR: The formatting of the value '%1s' for the domain '%2s' failed.

Message placeholders:

%1s

The invalid value to be formatted.

%2s

The domain associated with the value.

2.262.2 Description

The value from the server could not be formatted correctly because it does not conform to the format expected by the named domain.

2.262.3 Resolution

Report the problem; it is likely that it is an internal error.

2.263 -122210 ERR_CONV_CUSTOM_METHOD_FATAL

2.263.1 Message

ERROR: The value '*%1s*' could not be formatted or validated because the custom method '*%2s*' failed.

Message placeholders:

%1s

The value that was being formatted or validated.

%2s

The name of the custom method that failed.

2.263.2 Description

During the display phase of a page when the values were being formatted for presentation, or during the action phase when the values were being parsed, the custom validation function associated with a domain definition failed to be invoked.

2.263.3 Resolution

See the associated error message reported from the custom method for more details.

2.264 -122211 ERR_CONV_CUSTOM_METHOD_FAILED

2.264.1 Message

ERROR: %1s

Message placeholders:

%1s

The text of exception thrown from the custom validation function.

2.264.2 Description

A custom validation function has failed validation on a value. As the validation method is written by the application developer, the reason is dependent on what the method was performing.

2.264.3 Resolution

See the associated error message reported from the custom method for more details.

2.265 -123000 ERR_PH_NOT_FOUND

2.265.1 Message

ERROR: No page hierarchy definition was found for the locale '%1s'.

Message placeholders:

%1s

The locale code.

2.265.2 Description

When the application is initialized, the page hierarchy definitions are loaded for each supported locale. This error occurs if the page hierarchy definition cannot be found for a specific locale.

2.265.3 Resolution

Perform a clean build of the client application to restore any files that may have been accidentally deleted. Check that all classpath setting for the application are correct. If the problem persists, contact technical support.

2.266 -123001 ERR_PH_INVALID

2.266.1 Message

ERROR: The page hierarchy definition for the locale '%1s' is invalid.

Message placeholders:

%1s

The locale code.

2.266.2 Description

When the application is initialized, the page hierarchy definitions are loaded for each supported locale. This error occurs if the page hierarchy definition is invalid or corrupt when loaded. An associated error message may provide more details.

2.266.3 Resolution

Perform a clean build of the client application to restore any files that may have been accidentally deleted. Check that the application's page hierarchy definition is valid. If the problem persists, contact technical support.

2.267 -123002 ERR_PH_APP_UNDEFINED

2.267.1 Message

ERROR: No application has been defined for this user.

2.267.2 Description

No application has been defined for the user, so the appropriate page hierarchy cannot be identified and the navigation panel cannot be displayed.

2.267.3 Resolution

Ensure that the user's account is properly configured and that an application ID has been associated with the user.

2.268 -123003 ERR_PH_APP_NOT_FOUND

2.268.1 Message

ERROR: No application with the ID '%1s' was found.

Message placeholders:

%1s

The application identifier.

2.268.2 Description

An application has been defined for the user, but there is no corresponding application in the page hierarchy with that application ID, so the navigation panel cannot be displayed.

2.268.3 Resolution

Ensure that the application identifier is correct and that it matches an existing application in the page hierarchy definition.

2.269 -130000 ERR_BAD_SVR_MSG_FORMAT

2.269.1 Message

ERROR: Invalid server message format:

2.269.2 Description

A server message was received in an unexpected format and cannot be displayed correctly by the web application. The server message is appended to the error message.

2.269.3 Resolution

Report the error, as the application will need to be changed to use the correct message format.

2.270 -130002 ERR_SVR_EXCEPTION

2.270.1 Message

ERROR: The application server reported one or more exceptions.

2.270.2 Description

The server reported one or more exceptions when a call was made to the server. This is a “carrier” message that will contain messages with more detail about the problem.

2.270.3 Resolution

See the detailed messages for more information.

2.271 -130003 ERR_DECISION_ID_CONFIG

2.271.1 Message

ERROR: The rules configuration file is incorrect. The CONFIG element should contain only a DECISION-ID-SOURCE attribute or DECISION-ID-SOURCE-BEAN and DECISION-ID-SOURCE-FIELD attributes.

2.271.2 Description

Each link on a rules display widget can have a parameter specified in the rules configuration file. This parameter can be set based on an existing page parameter or based on a field of a server bean. It is an error if both are specified in the configuration file.

2.271.3 Resolution

Remove either the DECISION-ID-SOURCE attribute or the DECISION-ID-SOURCE-BEAN and DECISION-ID-SOURCE-FIELD attributes from the CONFIG element.

2.272 -131001 ERR_MSG_INVALID

2.272.1 Message

ERROR: The format of an error message is invalid or the placeholder substitution failed:

2.272.2 Description

When an attempt was made to report an error, the format of the error message was found to be invalid or the placeholders for the message arguments could not be substituted with the formatted argument values. The full text of the error message will be appended to this error message; it is not inserted via a placeholder.

2.272.3 Resolution

If the message is a custom error message, locate the message and correct the invalid formatting or ensure that the arguments to the message are correct. If the message is not a custom message, report the problem.

2.273 -131002 ERR_MSG_INVALID_PLACEHOLDER

2.273.1 Message

ERROR: An invalid character was found within a message argument placeholder:

2.273.2 Description

When an attempt was made to report an error, the format of a placeholder within an error message was found to be invalid. The invalid placeholder character will be appended to this error message; it is not inserted via a placeholder.

2.273.3 Resolution

If the message is a custom error message, locate the message and correct the invalid formatting. The placeholders must take the form “%*n**t*” where *n* is a positive integer indicating the argument number and *t* is a supported formatting type code character. If the message is not a custom message, report the problem. When a literal “%” character is required, it should be entered as “\%”.

2.274 -131003 ERR_MSG_NO_ARGUMENTS

2.274.1 Message

ERROR: No arguments were provided to a message containing placeholders.

2.274.2 Description

When an attempt was made to report an error, the message contained placeholders but no arguments were provided to substitute for those placeholders.

2.274.3 Resolution

If the message is a custom error message, or a system message used from custom code, locate the code that reports that error message (probably by throwing an exception) and ensure the arguments are correct. It is also possible that the placeholders in the message are unintended. If the message is not a custom message and is not reported from custom code, report the problem.

2.275 -131004 ERR_MSG_INVALID_INDEX

2.275.1 Message

ERROR: An invalid index was used within a message argument placeholder.

er:

2.275.2 Description

When an attempt was made to report an error, the index value used within a placeholder was not a valid index value. The invalid index value will be appended to this error message; it is not inserted via a placeholder.

2.275.3 Resolution

If the message is a custom error message, locate the message and correct the invalid formatting. The placeholders must take the form “%*nt*” where *n* is a positive integer indicating the argument number and *t* is a supported formatting type code character. If the message is not a custom message, report the problem. When a literal “%” character is required, it should be entered as “\%”.

2.276 -131005 ERR_MSG_INVALID_TYPE_CODE

2.276.1 Message

ERROR: An invalid formatting type code was used within a message argument placeholder:

2.276.2 Description

When an attempt was made to report an error, the formatting type code used within a placeholder was not a valid type code character. The type code character will be appended to this error message; it is not inserted via a placeholder.

2.276.3 Resolution

If the message is a custom error message, locate the message and correct the invalid formatting. The placeholders must take the form “%*nt*” where *n* is a positive integer indicating the argument number and *t* is a supported formatting type code character. If the message is not a custom message, report the problem. When a literal “%” character is required, it should be entered as “\%”.

2.277 -131006 ERR_MSG_NOT_CUSTOM_MESSAGE

2.277.1 Message

ERROR: An attempt was made to localize a non-custom message using a

custom message localizer:

2.277.2 Description

When localizing a non-custom message a custom message localizer was invoked and the two objects are not compatible. The message will be followed by the identifier of the non-custom message.

2.277.3 Resolution

This is an internal error; report the problem if it occurs.

2.278 -131007

ERR_MSG_NOT_UIM_VALIDATION_MESSAGE

2.278.1 Message

ERROR: An attempt was made to localize a non-UIM validation message using a UIM validation message localizer:

2.278.2 Description

When localizing a non-UIM validation message a UIM validation message localizer was invoked and the two objects are not compatible. The message will be followed by the identifier of the non-UIM validation message.

2.278.3 Resolution

This is an internal error; report the problem if it occurs.

2.279 -131008

ERR_MSG_BAD_UIM_VALIDATION_FORMAT

2.279.1 Message

ERROR: The format of a UIM validation message is invalid:

2.279.2 Description

During the validation of a UIM page, a validation error message was reported, but the format of the message was invalid.

2.279.3 Resolution

Check that the Client Development Environment was installed correctly. If the error persists, contact technical support.

2.280 -131009 ERR_MSG_INVALID_ERROR_NAME

2.280.1 Message

ERROR: The error name indicated in a UIM validation message does not exist:

2.280.2 Description

During the validation of a UIM page, a validation error message was reported, but the name of the error indicated by the message was not recognized and the error could not be reported.

2.280.3 Resolution

Check that the Client Development Environment was installed correctly. If the error persists, contact technical support.

2.281 -132000 ERR_UNKNOWN

2.281.1 Message

ERROR: %1s: An unknown or unexpected error occurred.

Message placeholders:

%1s

The name of the class in which the error occurred.

2.281.2 Description

An unknown or unexpected error occurred during processing. The specific cause will be reported with this error message.

2.281.3 Resolution

See the specific error message reported with this one for more information. Report the problem if it cannot be resolved.

2.282 -133000 ERR_APP_CONFIG_PARAM_MISSING

2.282.1 Message

ERROR: A default value for the '*%1s*' configuration parameter could not be found.

Message placeholders:

%1s

The name of the configuration parameter.

2.282.2 Description

The specified configuration parameter requires a value.

2.282.3 Resolution

Check the application configuration file (`ApplicationConfiguration.properties`) for the specified parameter. Note that the CDEJ provides defaults for all settings. If a parameter is left empty and this error still occurs, there is a problem with the CDEJ. This can be temporarily avoided by explicitly setting a value in the `ApplicationConfiguration.properties` in the Java Source folder.

2.283 -133001 ERR_APP_CONFIG_VERSION_ERROR

2.283.1 Message

ERROR: The CDEJ version information could not be found.

2.283.2 Description

The CDEJ version information displayed at start up cannot be found.

2.283.3 Resolution

Check the `omega3-coreinf.jar` was generated properly with the appropriate manifest file.

2.284 -134000 ERR_CARRIER

2.284.1 Message

ERROR: One or more errors occurred.

2.284.2 Description

An error that indicated that other errors have occurred and will be reported.

2.284.3 Resolution

See the reported error messages for details.

2.285 -135000 ERR_TAB_CONFIG

2.285.1 Message

ERROR: processing the tabbed UI configuration

2.285.2 Description

A problem occurred processing the tabbed UI configuration. See the nested exception for more details.

2.285.3 Resolution

Examine the nested exception and fix the problem.

2.286 -135001 ERR_TAB_VALIDATION_FAILED

2.286.1 Message

ERROR: Validation of the Tabbed UI configuration has failed with one or more errors.

2.286.2 Description

The tabbed UI configuration is invalid.

2.286.3 Resolution

Examine the validation errors and fix the described problems.

2.287 -135002 ERR_TAB_CONFIG_ACCESS_PROBLEM

2.287.1 Message

ERROR: There was a problem accessing the tab configuration information.

2.287.2 Description

The tabbed UI configuration could not be accessed.

2.287.3 Resolution

Examine the nested exception and for further details.

2.288 -135003 ERR_TAB_UNKNOWN_CONFIG_TYPE

2.288.1 Message

ERROR: The specified configuration type (*%1s*) is unknown.

Message placeholders:

%1s

The configuration type identifier.

2.288.2 Description

The tabbed UI configuration could not be accessed.

2.288.3 Resolution

Ensure that the application identifier is correct and that it matches an existing application in the page hierarchy definition.

2.289 -135004 ERR_TAB_CONFIG_BASE

2.289.1 Message

ERROR: processing the tabbed UI configuration. A page-param, menu, navigation, smart-panel or context element exists for *%1s* in components '*%2s*' and '*%3s*'.

Message placeholders:

%1s

Tab File Name.

%2s

Component Name.

%3s

Component Name.

2.289.2 Description

More than one tabbed UI configuration contains a page-param, menu, navigation, smart-panel or context element.

2.289.3 Resolution

Remove the page-param, menu, navigation, smart-panel or context node from the UI tabbed configuration in one of the specified components.

2.290 -135005 ERR_TAB_CONFIG_NO_BASE

2.290.1 Message

ERROR: processing the tabbed UI configuration. No base tab configuration exists for '*%1s*'.

%1s

Tab File Name.

2.290.2 Description

A navigation or details node does not exist in any of the tabbed UI configurations.

2.290.3 Resolution

One UI tabbed configuration must contain a navigation and details node.

2.291 -135006 ERR_TAB_CONFIG_REFRESH_DUPLICATE

2.291.1 Message

ERROR: processing the tabbed UI configuration. An attempt was made to add child items with the same id ('*%1s*') to the refresh node in the tab configuration file with id '*%2s*'. Duplicate id's are not allowed.

Message placeholders:

%1s

Name of the duplicate configuration artifact.

%2s

ID of the element.

2.291.2 Description

An attempt is being made to merge the tab-refresh node of an tab artifact which contain duplicate page id attribute values. The value of a page id attribute uniquely identifies that page and hence duplicates are not allowed.

2.291.3 Resolution

Check the files being merged and ensure that the page id attribute value is unique for each of the entries defined. If not, update the values of these attributes to be unique.

2.292 -135008 ERR_TAB_ID

2.292.1 Message

ERROR: Tab configuration IDs must be the same in order to successfully merge files. The tabbed UI configuration IDs in components '*%1s*' and '*%2s*' did not match.

Message placeholders:

%1s

Component Name.

%2s

Component Name.

2.292.2 Description

Tabbed UI configurations with different IDs attempted to merge.

2.292.3 Resolution

Ensure the 'id' attribute on the 'tab-config' element is correct.

2.293 -135009 ERR_TAB_DUPLICATE_ID

2.293.1 Message

ERROR: A configuration artifact '*%1s*' with duplicate ID '*%2s*' was found in the configuration.

Message placeholders:

%1s

Name of the duplicate configuration artifact.

%2s

ID of the element.

2.293.2 Description

There are two or more elements with the same ID in your configuration.

2.293.3 Resolution

ID of the menu must be unique throughout single configuration. Make sure there are no duplicate IDs.

2.294 -135010 ERR_TAB_MISSING_ATTRIBUTE

2.294.1 Message

ERROR: A configuration artifact '*%1s*' is missing the '*%2s*' attribute.

Message placeholders:

%1s

Name of the element.

%2s

Name of the attribute.

2.294.2 Description

A required attribute is missing from an element in your configuration.

2.294.3 Resolution

Provide the required attribute.

2.295 -135011 ERR_TAB_MISSING_NODE

2.295.1 Message

ERROR: The '*%2s*' configuration artifact is missing from the tab configuration *%1s*.

Message placeholders:

%1s

The identifier of the tab configuration.

%2s

The name of the missing element.

2.295.2 Description

A required element is missing from an element in your configuration.

2.295.3 Resolution

Provide the required element.

2.296 -135012 ERR_TAB_MISSING_ATTRIBUTES

2.296.1 Message

ERROR: The configuration artifact '*%2s*' is missing the '*%3s*' or '*%4s*' attribute in tab configuration *%1s*.

Message placeholders:

%1s

The identifier of the tab configuration.

%2s

Name of the element.

%3s

Name of the attribute.

%4s

Name of the other attribute.

2.296.2 Description

Required attributes are missing from an element in your configuration.

2.296.3 Resolution

Provide the required attributes.

2.297 -135013 ERR_TAB_INCORRECT_ATTRIBUTES

2.297.1 Message

ERROR: The configuration artifact '*%2s*' contains conflicting attributes in tab configuration '*%1s*'.

Message placeholders:

%1s

Identifier of the tab configuration.

%2s

Name of the element.

2.297.2 Description

There are conflicting attributes set on an element in configuration.

2.297.3 Resolution

Remove conflicting attributes.

2.298 -135014 ERR_TAB_NAVIGATION_ID

2.298.1 Message

ERROR: Tab navigation configuration IDs must be the same in order to successfully merge files. The tabbed UI navigation configuration IDs in components '*%1s*' and '*%2s*' did not match.

Message placeholders:

%1s

Component Name.

%2s

Component Name.

2.298.2 Description

Tabbed UI navigation configurations with different IDs attempted to merge.

2.298.3 Resolution

Ensure the 'id' attribute on the 'navigator' element is correct.

2.299 -135015 ERR_TAB_NAVIGATION_ID_FILENAME

2.299.1 Message

ERROR: Tab navigation configuration ID must match the file name. The tabbed UI navigation configuration ID in component '*%1s*' do not match its filename.

Message placeholders:

%1s

Component Name.

2.299.2 Description

Tabbed UI navigation configuration with navigator id different from file name.

2.299.3 Resolution

Ensure the 'id' attribute on the 'navigator' element is the same as the file where it is defined (without the extension).

2.300 -135016 ERR_TAB_MISSING_LOADER

2.300.1 Message

ERROR: The element ' %1s ' contains an event id not referenced in the loaders: ' %2s '.

Message placeholders:

%1s

Name of the element.

%2s

Value of the event id.

2.300.2 Description

An event id set on an element in your configuration cannot be found in the loaders.

2.300.3 Resolution

Make sure that the event id is listed in the loaders.

2.301 -135017 ERR_TAB_NAVIGATION_ATTRIBUTES

2.301.1 Message

ERROR: processing the tabbed UI navigation configuration. Cannot override %1s attribute value in the UI tabbed navigation configuration in the ' %2s ' and ' %3s ' component on the ' %4s ' element.

Message placeholders:

%1s

Attribute Name.
%2s
Component Name.
%3s
Component Name.
%4s
The element.

2.301.2 Description

A tabbed UI navigation configuration attempted to override an attribute value on an element.

2.301.3 Resolution

Remove the attribute from the element in the tabbed UI navigation configuration from one of the specified components.

2.302 -135018 ERR_TAB_DUPLICATE_LOADER

2.302.1 Message

ERROR: A configuration artifact ' *%1s* ' with duplicate class ' *%2s* ' was found in the navigation configuration.

Message placeholders:

%1s
Name of the duplicate element.
%2s
Handler.

2.302.2 Description

There are two or more loaders with the same class in your configuration.

2.302.3 Resolution

A loader class must be unique throughout a single navigation configuration. Make sure there are no duplicate loaders.

2.303 -135019 ERR_TAB_LOADER_COMPONENTS

2.303.1 Message

ERROR: processing the tabbed UI navigation configuration. Cannot add events to the loader ' %1s ' from the component ' %2s ' as it is already defined in another component.

Message placeholders:

%1s

Loader class.

%2s

Component Name.

2.303.2 Description

A tabbed UI configuration attempted to add events to a loader already defined in another component.

2.303.3 Resolution

Remove the loader from this component.

2.304 -135020

ERR_TAB_HAS_DYNAMIC_ITEMS_MISSING_LOADERS

2.304.1 Message

ERROR: The menu bar configuration ' %1s ' contains dynamic menu items, but there are no loaders defined.

Message placeholders:

%1s

Menu bar configuration ID.

2.304.2 Description

The configuration which defines dynamic menu items (they have 'dynamic' attribute set to true) also has to specify a loader class to be queried for the dynamic state of the flagged menu items.

2.304.3 Resolution

Add a definition of a dynamic menu state loader in the configuration or remove the 'dynamic' flag from all menu items.

2.305 -135021

ERR_TAB_UNKNOWN_CONFIG_ELEMENT

2.305.1 Message

ERROR: An unknown configuration element '*%1s*' was encountered when processing menu bar configuration '*%2s*'.

Message placeholders:

%1s

Name of the unknown element.

%2s

Menu bar configuration ID.

2.305.2 Description

The configuration contains an element which is unknown to the merger.

2.305.3 Resolution

Remove the specified element from the configuration.

2.306 -135022 ERR_TAB_DUPLICATE_ATTRIBUTE

2.306.1 Message

ERROR: A duplicate attribute '*%1s*' was encountered in <submenu> elements with ID '*%2s*'.

Message placeholders:

%1s

Name of the duplicate attribute.

%2s

Element ID.

2.306.2 Description

The configuration contains <submenu> elements which define the same attributes. This usually happens when two components contribute items in a submenu. In this case only one of the submenu definitions can specify the attributes.

2.306.3 Resolution

Remove the duplicate attributes from one of the elements.

2.307 -135023 ERR_TAB_CONFIG_NO_INDEX

2.307.1 Message

ERROR: Inconsistent configuration information: a required index '*%1s*' of configuration fragments '*%2s*' was not found.

Message placeholders:

%1s

Name of the index.

%2s

Name of the resource.

2.307.2 Description

The configuration access API was looking for a fragment index, but is was not available in the resource store.

2.307.3 Resolution

Ensure the configuration information is properly loaded into the resource store.

2.308 -135024 ERR_TAB_RESOURCE_STORE_ERROR

2.308.1 Message

ERROR: An error occurred accessing the resource store content on the database. See nested exception for further information.

2.308.2 Description

There were problems accessing the resource store database content.

2.308.3 Resolution

Consult the nested exception for resolution details.

2.309 -135025

ERR_TAB_CONFIG_NAVIGATION_FOLDER_IN_FOLDER

2.309.1 Message

ERROR: processing the tabbed UI configuration. Cannot add the folder '*%1s*' to the folder '*%2s*' in the navigation file with id '*%3s*'. A folder element can only contain leaf elements.

Message placeholders:

%1s

Child Folder id.

%2s

Parent Folder id.

%3s

The id of the navigation file.

2.310 -135026

ERR_TAB_CONFIG_NAVIGATION_CHILD_IN_LEAF

2.310.1 Message

ERROR: processing the tabbed UI configuration. Cannot add the item with id '*%1s*' to the leaf with id '*%2s*' in the navigation file with id '*%3s*'. A leaf element cannot contain any child elements.

Message placeholders:

%1s

Child element id.

%2s

Leaf id.

%3s

The id of the navigation file.

2.311 -135027

ERR_TAB_CONFIG_NAVIGATION_DUPLICATE_ID

2.311.1 Message

ERROR: processing the tabbed UI configuration. An attempt was made to add child items with the same id ('%1s') to the item with id '%2s' in the navigation file with id '%3s'. Duplicate id's are not allowed.

Message placeholders:

%1s

Child element id.

%2s

Parent Element id.

%3s

The id of the navigation file.

2.312 -135028

ERR_TAB_MISSING_TAB_NAME_ATTRIBUTE

2.312.1 Message

ERROR: The configuration artifact '%2s' is missing the '%3s' attribute in tab configuration %1s.

Message placeholders:

%1s

The identifier of the tab configuration.

%2s

Name of the element.

%3s

Name of the attribute.

2.312.2 Description

The tab-name attribute is missing from an element in your configuration.

2.312.3 Resolution

Provide the required attribute.

2.313 -135029 ERR_TAB_SUBMENU_EMPTY

2.313.1 Message

ERROR: An empty submenu element '%1s' with ID '%2s' was found in the configuration file '%3s'.

Message placeholders:

%1s

Name of the submenu element.

%2s

ID of the element.

%3s

Tab File Name.

2.313.2 Description

There is an empty submenu element in your configuration.

2.313.3 Resolution

An empty submenu should not exist in the final configuration. Ensure that all submenu elements are populated.

2.314 -135030 ERR_TAB_HAS_NO_CHILD_ELEMENTS

2.314.1 Message

ERROR: A node of type '*%1s*', with ID '*%2s*', must contain at least one node of type "leaf" or "folder" in the configuration file '*%3s*'.

Message placeholders:

%1s

Attribute Type.

%2s

Section Shortcut Panel Configuration ID.

%3s

Name of the resource.

2.314.2 Description

The Section Shortcut Panel node of type "folder" must always contain one node of type "leaf" or "folder".

2.314.3 Resolution

Add at least one node of type "leaf" or "folder".

2.315 -135031 ERR_TAB_HAS_EXTRA_ATTRIBUTE

2.315.1 Message

ERROR: A node of type '*%1s*', with ID '*%2s*', must not contain '*%3s*' attribute in the configuration file '*%4s*'.

Message placeholders:

%1s

Attribute Type

%2s

Section Shortcut Panel Configuration ID.

%3s

Attribute name.

%4s

Name of the resource.

2.315.2 Description

The "visible", "open-as" and "page-id" attributes applies only to node of type "leaf". All these attributes are superfluous for other types of nodes

2.315.3 Resolution

Remove the extra attributes from the nodes other than of type "leaf".

2.316 -135032 ERR_TAB_HAS_CHILD_ELEMENTS

2.316.1 Message

ERROR: A node of type '*%1s*', with ID '*%2s*', must not contain child nodes in the configuration file '*%3s*'.

Message placeholders:

%1s

Attribute Type

%2s

Section Shortcut Panel Configuration ID.

%3s

Name of the resource.

2.316.2 Description

The node of type "leaf" should not contain any child elements.

2.316.3 Resolution

Remove the child elements from the node of type "leaf".

2.317 -135033 ERR_TAB_HAS_EXTRA_CHILD_ELEMENT

2.317.1 Message

ERROR: A node of type '*%1s*', with ID '*%2s*', must not contain any child node of type 'group' in the configuration file '*%3s*'.

Message placeholders:

%1s

Attribute Type

%2s

Section Shortcut Panel Configuration ID.

%3s

Name of the resource.

2.317.2 Description

The node of type "group" or "folder" must not contain any child node of type "group".

2.317.3 Resolution

Remove the child node of type "group" from the node of type "group" or "folder".

2.318 -135034 ERR_TAB_ELEMENT_ID_ONLY

2.318.1 Message

ERROR: The configuration fragment ID '*%2s*' within component '*%1s*' contains an error. A contributing element '*%1s*' with ID '*%2s*' cannot contain additional attributes.

Message placeholders:

%1s

Name of the component.

%2s

Name of the contributing file.

%3s

Name of the element.

%4s

ID of the element.

2.318.2 Description

Contributing elements used to reorder existing elements can only contain the ID attribute in your configuration.

2.318.3 Resolution

Elements used to reorder existing defined elements can only contain the ID attribute and no other. Modifying existing elements attributes is forbidden. Ensure that any contributing elements used to reorder existing elements can only contain the ID attribute.

2.319 -135035 ERR_EXPAND_LIST_NO_PARAMETER

2.319.1 Message

ERROR: The renderer is missing the parameter:'%1s'.

Message placeholders:

%1s

Parameter name.

2.319.2 Description

The renderer must be provided with required page parameters, if not the exception is thrown

2.319.3 Resolution

Provide the required page parameter requested by the renderer.

2.320 -135036 ERR_TAB_MISSING_OPTIONAL_ATTRIBUTE

2.320.1 Message

ERROR: The '%4s' attribute must be populated if the '%3s' attribute is not set within the '%2s' configuration element of %1s.

Message placeholders:

%1s

The identifier of the tab configuration.

%2s

Name of the configuration artifact.

%3s

Name of the element.

%4s

Name of the element.

2.320.2 Description

The details element of a tab configuration must have either a page-id attribute specified or the tab-name and tab-title attributes. If page-id is specified, tab-name and tab-title are treated as optional.

2.320.3 Resolution

Provide the required optional attribute.

2.321 -135037 ERR_PARENT_ELEMENT_ID_ONLY

2.321.1 Message

ERROR: The configuration fragment ID '*%2s*' within component '*%1s*' contains an error. A contributing element '*%3s*' with ID '*%4s*' must be of type '*%5s*'.

Message placeholders:

%1s

Name of the component.

%2s

Name of the contributing file.

%3s

Name of the element.

%4s

ID of the element.

%5s

Type of valid parent element.

2.321.2 Description

Contributing elements used to reorder existing elements can only contain the ID attribute of a parent element in your configuration.

2.321.3 Resolution

Elements used to reorder existing defined elements can only contain the ID attribute of a parent element. The use of the ID from other element types is forbidden. Ensure that any contributing elements used to contribute can only contain the ID attribute from an existing parent element.

2.322 -136000 ERR_LOCALE_NOT_CONFIGURED

2.322.1 Message

ERROR: The selected locale '*%1s*' is not configured in the system.

Message placeholders:

%1s

The code of the selected locale.

2.322.2 Description

The locales presented to the user in the locale selector dialog come from the list of locales the client has been built with. The same list of locales must be configured in the system using the Administration application. This error means that the above is not the case and the user selected a locale that is not configured.

2.322.3 Resolution

Use the administration application to add the missing locale in the Locale code table.

2.323 -136001

ERR_APP_REQUIRED_ATTRIBUTE_NOT_PRESENT
_OR_EMPTY

2.323.1 Message

ERROR: The configuration artifact '*%1s*' with ID '*%2s*' contains an error. The element '*%3s*' must have the '*%4s*' attribute set and the value must not be empty.

Message placeholders:

%1s

The name of the configuration file.

%2s

The identifier of the configuration artifact.

%3s

The name of the element.

%4s

The name of the attribute.

2.323.2 Description

The specified configuration file contains an element that is missing a required attribute or the attribute has been specified but its value is empty.

2.323.3 Resolution

Specify the required element attribute and populate it with a valid value.

2.324 -136002

ERR_APP_APPLICATION_SEARCH_ATTRIBUTES_NOT_REQUIRED

2.324.1 Message

ERROR: The configuration artifact '*%1s*' with ID '*%2s*' contains an error. The element '*%3s*' must not contain the '*%4s*' attribute as search pages have been defined for this application search.

Message placeholders:

%1s

The name of the configuration file.

%2s

The identifier of the configuration artifact.

%3s

The name of the element.

%4s

The name of the attribute.

2.324.2 Description

The specified configuration file contains an application search that contains

search pages. When search pages have been defined, then no attributes should be defined for the root application search element.

2.324.3 Resolution

Decide whether search pages should be defined for the application search and if so, remove any attributes that have been specified on the root application search element.

2.325 -136003

ERR_APP_SEARCH_PAGES_INCORRECT_NUM_DEFAULT_ATTRIBUTE

2.325.1 Message

ERROR: The configuration artifact '*%1s*' with ID '*%2s*' contains an error. The '*%3s*' element must contain one and only one '*%4s*' element with a '*%5s*' attribute specified.

Message placeholders:

%1s

The name of the configuration file.

%2s

The identifier of the configuration artifact.

%3s

The name of the search pages element.

%4s

The name of the search page element.

%5s

The name of the default attribute.

2.325.2 Description

The specified configuration file contains an application search that contains search pages. The default attribute must be specified on one and only one of these search pages. This exception is thrown when the attribute has not been specified on any of the search pages or has been specified on more than one of the search pages.

2.325.3 Resolution

Check the search pages defined for the application search configuration and ensure that the default attribute has been specified for one and only one of

the search pages.

2.326 -136004

ERR_APP_SEARCH_PAGE_TYPE_ATTR_VALUE_NOT_UNIQUE

2.326.1 Message

ERROR: The configuration artifact '*%1s*' with ID '*%2s*' contains an error. The '*%3s*' element contains a '*%4s*' attribute value of '*%5s*' that is not unique within the overall list of '*%6s*' elements.

Message placeholders:

%1s

The name of the configuration file.

%2s

The identifier of the configuration artifact.

%3s

The name of the search page element.

%4s

The name of the type attribute.

%5s

The value of the search page type attribute.

%6s

The name of the search pages element.

2.326.2 Description

The specified configuration file contains an application search that contains search pages. Each one of these search page elements contains a type attribute and the value of this type attribute is not unique within the overall list of search pages.

2.326.3 Resolution

Check the search pages defined for the application search configuration and ensure that the value of the type attribute is unique within the overall list of search pages.

2.327 -136005 ERR_SEC_CONFIG_BASE

2.327.1 Message

ERROR: processing the tabbed UI configuration. A shortcut-panel-ref exists for %1s in components '%2s' and '%3s'.

Message placeholders:

%1s

Section File Name.

%2s

Component Name.

%3s

Component Name.

2.327.2 Description

More than one tabbed UI configuration contains a shortcut-panel-ref element.

2.327.3 Resolution

Remove the shortcut-panel-ref from the UI tabbed configuration in one of the specified components.

2.328 -136006 ERR_APP_CONFIG_BASE

2.328.1 Message

ERROR: processing the tabbed UI configuration. The application-menu element exists for %1s in components '%2s' and '%3s'.

Message placeholders:

%1s

Section File Name.

%2s

Component Name.

%3s

Component Name.

2.328.2 Description

More than one tabbed UI configuration contains a application-menu element.

2.328.3 Resolution

Remove the application-menu from the UI tabbed configuration in one of the specified components.

2.329 -136007

ERR_MERGE_APP_CONFIG_DUPLICATE_NODES

2.329.1 Message

ERROR: merging the application configuration. The '%1s' node exists for '%2s' in the components '%3s' and '%4s'. This node must only be present in one of the files for a successful merge to occur.

Message placeholders:

%1s

The name of the element which exists in both of the files involved in the merge.

%2s

The name of the application view configuration file.

%3s

The name of the first component involved in the merge.

%4s

The name of the second component involved in the merge.

2.329.2 Description

The two files from the two components involved in the application search merge both contain the further options link node. This node cannot exist in both files involved in the merge.

2.329.3 Resolution

Remove the further options link node from the application search configuration in one of the specified components.

2.330 -136008

ERR_MERGE_APP_SEARCH_NO_TARGET_NODE

2.330.1 Message

ERROR: merging the application configuration. The '*%1s*' node does not exist for '*%2s*' in the component '*%3s*'. This node must exist in the target file for a successful merge to occur.

Message placeholders:

%1s

The name of the element which does not exist in the target file of the merge.

%2s

The name of the application view configuration file.

%3s

The name of the component containing the file which does not contain the required element.

2.330.2 Description

An attempt is being made to merge a complete application search component from a source file into a target file. This is not allowed as only individual elements within the overall application search element can be merged, not the complete search component.

2.330.3 Resolution

Ensure that the target file being merged to has an application search element specified for it or the same element must be removed from the source file in order for the merge to complete successfully.

2.331 -136009

ERR_MERGE_APP_SEARCH_PAGE_DUPLICATE_NO
DE_VALUE

2.331.1 Message

ERROR: merging the application configuration. The value of the '*%1s*' attribute for the '*%2s*' node already exists for '*%3s*' in the components '*%4s*' and '*%5s*'. The value of this node attribute must be unique for a successful merge to occur.

Message placeholders:

%1s

The value of the attribute that is duplicated within the component files being merged.

%1s

The name of the node that contains the attribute which contains a duplicate value.

%3s

The name of the application view configuration file.

%4s

The name of the first component involved in the merge.

%5s

The name of the second component involved in the merge.

2.331.2 Description

An attempt is being made to merge the search pages of an application search which contain duplicate search page type attribute values. The value of a search page type attribute uniquely identifies that search page and hence duplicates are not allowed.

2.331.3 Resolution

Check the files being merged and ensure that the type attribute value is unique for each of the search pages defined. If not, update the values of these attributes to be unique.

2.332 -136010 ERR_SSP_DUPLICATE_LEAF_NODE

2.332.1 Message

ERROR:Merge Section Shortcut Panel configuration. The configuration file in '%2s' component must not contain the leaf node with ID '%1s'. The leaf node with the same ID already exists in the base component '%3s'.

Message placeholders:

%1s

Leaf node ID of merge component.

%2s

Merge component Name.

%3s

Base component Name.

2.332.2 Description

More than one section shortcut panel configuration contains a duplicate leaf node.

2.332.3 Resolution

Remove or rename the specified leaf node ID in one of the specified components.

2.333 -136011 ERR_SSP_CONFIG_TITLE

2.333.1 Message

ERROR: Merge Section Shortcut Panel configuration. Cannot override title attribute in '*%1s*' and '*%2s*' components on the node with ID '*%3s*'

Message placeholders:

%1s

Base Component Name.

%2s

Merge Component Name.

%3s

The id on the node.

2.333.2 Description

A tabbed UI configuration attempted to override the title attribute value on a specified node.

2.333.3 Resolution

Remove the title attribute from the specified node in the tabbed UI configuration from one of the specified components.

2.334 -136012 ERR_APP_CONFIG_APP_MENU

2.334.1 Message

ERROR: Merging the application view configuration. Application '*%1s*' has defined the application-menu node in '*%2s*'. The element application-menu in the component '*%3s*' is not a valid contribution.

%1s

The identifier of the base fragment.

%2s

The name of the component containing the base fragment

%3s

The name of the component containing the merging fragment.

2.334.2 Description

An application-menu node cannot exist in a contributing configuration file.

2.334.3 Resolution

Remove the contributing application-menu node.

2.335 -136013 ERR_APP_CONFIG_ATTRIB_CONFLICT

2.335.1 Message

ERROR: Merging the %6s configuration. '%6s' '%1s' is already defined in component '%2s'. Found attribute '%3s' on '%4s' in the component '%5s' which is not allowed. Attributes of a previously defined application cannot be overridden.

%1s

The identifier of the base fragment

%2s

The name of the component containing the base fragment

%3s

Name of the attribute

%4s

The identifier of the fragment to be merged

%5s

The name of the component containing the merging fragment

%6s

The name of the configuration item

2.335.2 Description

Attributes that are already defined the base component cannot be overridden by any of the component which contributes to the base component.

2.335.3 Resolution

Remove any extra attribute present in the component which contributes to the base component.

2.336 -136014

ERR_SEC_CONFIG_SHORTCUT_PANEL_REF

2.336.1 Message

ERROR: Merging the section configuration. Section '*%1s*' has an existing defined shortcut-panel-ref node in '*%2s*'. Found the element shortcut-panel-ref in the component '*%3s*' which is not allowed.

%1s

The identifier of the base fragment.

%2s

The name of the component containing the base fragment

%3s

The name of the component containing the merging fragment.

2.336.2 Description

A shortcut-panel-ref node cannot be contributed to the base section configuration.

2.336.3 Resolution

Contributing section configuration must contain a shortcut-panel-ref node.

2.337 -136015 ERR_APP_ATTRIBUTE_EMPTY

2.337.1 Message

ERROR: The configuration artifact '*%1s*' with ID '*%2s*' contains an error. The element '*%3s*' must have the '*%4s*' attribute set and the value must not be empty.

Message placeholders:

%1s

The name of the configuration file.

%2s

The identifier of the configuration artifact.

%3s

The name of the element.

%4s

The name of the attribute.

2.337.2 Description

The specified configuration file contains an element that has the attribute

specified but its value is empty.

2.337.3 Resolution

Specify the element attribute and populate it with a valid value.

2.338 -136016 ERR_MULTIPLE_INSTANCE_ELEMENT

2.338.1 Message

ERROR: The '%2s' element may only appear once in configuration, %1s.

Message placeholders:

%1s

The identifier of the tab configuration.

%2s

The name of the element.

2.338.2 Description

The configuration file contains more than one instance of a specified element.

2.338.3 Resolution

Ensure specified element exists as a single instance.

2.339 -136017 ERR_RELATED_ATTR_EMPTY

2.339.1 Message

ERROR: The configuration artifact '%1s' with ID '%2s' contains an error. Within the '%3s' element, if the '%4s' attribute is populated, the '%5s' attribute must also be set.

Message placeholders:

%1s

The name of the configuration file.

%2s

The identifier of the configuration artifact.

%3s

The name of the element.

%4s

The name of the attribute.

%4s

The name of the related attribute.

2.339.2 Description

The specified configuration file contains an element that requires if a certain attribute is populated, then a second related attribute must also be set.

2.339.3 Resolution

Populate the related second attribute with a valid value.

2.340 -136018 ERR_FILENAME_ID_MISMATCH

2.340.1 Message

ERROR: The ID '*%3s*' of the '*%2s*' element should match the filename of resource *%1s*.

Message placeholders:

%1s

The identifier of the tab configuration.

%2s

The name of the element.

2.340.2 Description

The configuration file contains more than one instance of a specified element.

2.340.3 Resolution

Ensure specified element exists as a single instance.

2.341 -136019 ERR_DUPLICATE_TABS_FOUND

2.341.1 Message

ERROR: The page, '*%1s*' is associated with more than one tab within the '*%2s*' application view.

Message placeholders:

%1s

The UIM page identifier.

%2s

The tab application identifier.

2.341.2 Description

More than one tab is associated with a particular page within an application view.

2.341.3 Resolution

Ensure only one tab association exists for the specified page.

2.342 -136500 ERR_FILE_DOWNLOAD_CONFIG_MISSING

2.342.1 Message

ERROR: The file cannot be downloaded because the page '*%1s*' has not been configured in the FILE_DOWNLOAD_CONFIG section of curam-config.xml.

Message placeholders:

%1s

The UIM page identifier.

2.342.2 Description

An attempt has been made to download a file from the specified page, but the page has not been configured for file downloads.

2.342.3 Resolution

Ensure the specified page has an entry in the FILE_DOWNLOAD_CONFIG section of curam-config.xml.

2.343 -136501 ERR__BAD_JSON_FORMAT

2.343.1 Message

ERROR: Badly formed JSON data.

2.343.2 Description

The value can not be converted into JSON format

2.343.3 Resolution

Contact your administrator for more information.

Chapter 3

Cúram Generator Error Messages

3.1 Objective

This chapter describes all the errors reported by the Cúram CDEJ development tools.

3.2 Introduction

The following sections describe each error message that can be displayed by the Cúram CDEJ development tools. Each description provides the error number, the error messages and a description of any place holders that occur in the message. Place holders are represented by “ %s ” and are described in the order they appear in the string.

Resolution instructions are also provided for fixing the error.

3.3 -120001 ERR_ACTCTL_SUBMIT_NO_ACTION

3.3.1 Message

A connection in a link from a SUBMIT action must have an ACTION phase bean, a page parameter or a CONSTANT as its source.

3.3.2 Description

A submit action link must source its parameters from an action phase bean or a SOURCE of type PAGE or CONSTANT.

3.3.3 Resolution

On the identified UIM page, ensure that each link within a submit action

control specifies either a valid action phase bean, a `PAGE` parameter or a `CONSTANT` as its `SOURCE` connection.

3.4 -120002 ERR_ACTCTL_INVALID_CHILD

3.4.1 Message

An action control of this type must contain only `LINK` or `SCRIPT` elements.

3.4.2 Description

An action control of this type may contain `SCRIPT` elements and, at most, one `LINK` element.

3.4.3 Resolution

On the identified UIM page, ensure that `ACTION_CONTROL` elements that are not of type `CLIPBOARD` only contain `SCRIPT` elements along with, at most, a single `LINK` element.

3.5 -120003 ERR_ACTCTL_INVALID_DEFAULT

3.5.1 Message

`DEFAULT` attribute is not allowed for non-submitting action control.

3.5.2 Description

The `DEFAULT` attribute is only applicable for a submit action control.

3.5.3 Resolution

Remove the `DEFAULT` attribute from the action control or change the action control type to `SUBMIT`.

3.6 -120004 ERR_ACTCTL_MULTIPLE_SUBMITS

3.6.1 Message

Multiple default submit controls are not allowed.

3.6.2 Description

A UIM page has more than one default submit control defined.

3.6.3 Resolution

On the identified UIM page, ensure that only one `ACTION_CONTROL` element of type `SUBMIT` has the `DEFAULT` attribute set to `true`.

3.7 -120005 ERR_ACTCTL_INVALID_LINK

3.7.1 Message

Only an `ACTION_CONTROL` of type `SUBMIT` may have a `LINK` element with a `PAGE_ID` of "THIS".

3.7.2 Description

Only an `ACTION_CONTROL` of type `SUBMIT` may have a `LINK` element with a `PAGE_ID` of `THIS`.

3.7.3 Resolution

On the identified UIM page, ensure that a `LINK` element with a `PAGE_ID` of `THIS` is only used within an `ACTION_CONTROL` of type `SUBMIT`.

3.8 -120006 ERR_ACTCTL_CLIP_MISSING_ATT

3.8.1 Message

A clipping `ACTION_CONTROL` must have a `LABEL` or `IMAGE` attribute specified.

3.8.2 Description

Action controls that define a clipboard action must specify either a label or an image.

3.8.3 Resolution

On the identified UIM page, add a `LABEL` or `IMAGE` attribute to the action control of type `CLIPBOARD`.

3.9 -120007 ERR_ACTCTL_CLIP_MULTIPLE_SOURCES

3.9.1 Message

The CONNECT element within a clipping ACTION_CONTROL must contain only single SOURCE connection.

3.9.2 Description

Only one source connection is allowed within an ACTION_CONTROL of type CLIPBOARD.

3.9.3 Resolution

On the identified UIM page, ensure that each ACTION_CONTROL of type CLIPBOARD has no more than one source connection.

3.10 -120008 ERR_ACTCTL_INVALID_SUBMIT

3.10.1 Message

An ACTION_CONTROL element of type "SUBMIT" requires an ACTION phase SERVER_INTERFACE element defined on the page.

3.10.2 Description

An ACTION_CONTROL element cannot contain a TYPE attribute equal to SUBMIT without a SERVER_INTERFACE element with a PHASE attribute equal to ACTION.

3.10.3 Resolution

On the identified UIM page, ensure that SERVER_INTERFACE element with a PHASE attribute equal to ACTION exists.

3.11 -120009 ERR_ACTCTL_FE_SOURCE_ACTION

3.11.1 Message

When using a FILE_EDIT widget, no property of an action-phase server interface may be used as the source of a connection for a LINK in the SUBMIT ACTION_CONTROL.

3.11.2 Description

When a FILE_EDIT widget is used on a page, the action-phase server interface will not be invoked when returning to the Cúram application after the *Microsoft® Word* document is closed. Because of this, no property of an action-phase server interface may be used as the source of a connection

within the `LINK` element of a `SUBMIT ACTION_CONTROL` when a `FILE_EDIT` widget is present.

3.11.3 Resolution

On the identified UIM page, ensure that the `ACTION_CONTROL` of type `SUBMIT` does not have a `LINK` that contains `SOURCE` connections from the properties of an action-phase server interface.

3.12 -120010 ERR_ACTCTL_INVALID_TYPE_DISMISS

3.12.1 Message

If an action set contains a `TYPE="DISMISS"` then there must be a `POPUP_PAGE` attribute set to `"true"`.

3.12.2 Description

An `ACTION_CONTROL` element cannot contain a `TYPE` attribute equal to `DISMISS` without a `PAGE` element with a `POPUP_PAGE` attribute equal to `true`.

3.12.3 Resolution

On the identified UIM page, ensure that `PAGE` element with a `POPUP_PAGE` attribute equal to `true` exists.

3.13 -120011 ERR_ACTCTL_INVALID_LINK_CONDITION

3.13.1 Message

A `LINK` within an `ACTION_CONTROL` cannot contain a `CONDITION` element.

3.13.2 Description

A `LINK` within an `ACTION_CONTROL` cannot contain a `CONDITION` element.

3.13.3 Resolution

Only a `FIELD` element can contain a `LINK` with a `CONDITION` as its child.

3.14 -120025 ERR_ADDRESS_FORMAT_NOT_FOUND

3.14.1 Message

The configuration does not contain an address format matching the default address format name.

3.14.2 Description

There is no address format matching the default address format name.

3.14.3 Resolution

Check the address format specified in `curam-config.xml` for the field in question.

3.15 -120030 ERR_ATTRIBUTE_INVALID_VALUE

3.15.1 Message

The attribute `%1s` may only take one of the following values: `%2s`.

Message placeholders:

%1s

The name of the attribute.

%2s

List of values that this attribute can take.

3.15.2 Description

This attribute can take only one of a fixed set of values.

3.15.3 Resolution

On the identified UIM page, set the attribute to one of the listed, allowed values.

3.16 -120031 ERR_ATTRIBUTE_UNKNOWN

3.16.1 Message

Invalid attribute: `%1s`

Message placeholders:

%1s

The name of the attribute.

3.16.2 Description

An unexpected attribute has been encountered in the UIM file, i.e. the attribute is not allowed on this element.

3.16.3 Resolution

On the identified UIM page, change or remove the invalid attribute. See the UIM Schema for allowed attributes on this element.

3.17 -120040 ERR_BEAN_META_PROP_DIR

3.17.1 Message

Invalid parameter direction attribute value: *%1s*

Message placeholders:

%1s

Attribute name that triggered the error.

3.17.2 Description

An attribute of a parameter definition in the server access beans definition file is invalid.

3.17.3 Resolution

Change the name of, or remove, the specified attribute.

3.18 -120041 ERR_BEAN_NOT_EXIST

3.18.1 Message

The server interface is unknown.

3.18.2 Description

The bean referenced in the UIM page cannot be found in the server access beans definition file.

3.18.3 Resolution

Change the indicated server interface (CLASS and OPERATION attributes on the SERVER_INTERFACE element).

3.19 -120050 ERR_CLUSTER_INVALID_ACTSET

3.19.1 Message

Cluster can have only one action set.

3.19.2 Description

Only one action set can be defined for a cluster.

3.19.3 Resolution

On the identified UIM page, ensure that each cluster has no more than one action set defined.

3.20 -120051 ERR_CLUSTER_INVALID_ELEMENTS

3.20.1 Message

Cluster must have one of the following elements: ACTION_SET, FIELD, WIDGET, CONTAINER, CLUSTER, LIST.

3.20.2 Description

Cluster is missing a compulsory element.

3.20.3 Resolution

On the identified UIM page, ensure that each cluster has at least one of the following elements: ACTION_SET, FIELD, WIDGET, CONTAINER, CLUSTER, LIST.

3.21 -120060 ERR_CONNECT_INVALID_NAME

3.21.1 Message

The value '%1s' is not allowed for the NAME attribute. The values 'CONSTANT' and 'TEXT' are only permitted on a SOURCE connection.

Message placeholders:

%1s

The current value of the NAME attribute.

3.21.2 Description

An INITIAL or TARGET element has been encountered with NAME set to CONSTANT or TEXT. This is only allowed on a SOURCE element.

3.21.3 Resolution

On the identified UIM page, ensure that only SOURCE elements have a NAME attribute set to CONSTANT or TEXT.

3.22 -120061 ERR_CONNECT_INVALID_TARGET

3.22.1 Message

Page level connection cannot have a PAGE parameter as its TARGET.

3.22.2 Description

A connection defined at page level cannot write a value to a page parameter.

3.22.3 Resolution

On the identified UIM page, ensure that page level connections do not contain a TARGET element with NAME set to PAGE.

3.23 -120062 ERR_CONNECT_MULTIPLE_SOURCES

3.23.1 Message

CONNECT element must not have multiple sources.

3.23.2 Description

A CONNECT element may have no more than one SOURCE child element.

3.23.3 Resolution

On the identified UIM page, ensure that there is no more than one SOURCE element within each CONNECT.

3.24 -120063 ERR_CONNECT_MULTIPLE_TARGETS

3.24.1 Message

CONNECT element must not have multiple targets.

3.24.2 Description

A CONNECT element may have no more than one TARGET child element.

3.24.3 Resolution

On the identified UIM page, ensure that there is no more than one TARGET element within each CONNECT.

3.25 -120064 ERR_CONNECT_MULTIPLE_INITIALS

3.25.1 Message

CONNECT element must not have multiple initials.

3.25.2 Description

A CONNECT element may have no more than one INITIAL child element.

3.25.3 Resolution

On the identified UIM page, ensure that there is no more than one INITIAL element within each CONNECT.

3.26 -120065 ERR_CONNECT_UNDECLARED_NAME

3.26.1 Message

NAME '*%1s*' used in connection has not been declared as a SERVER_INTERFACE.

Message placeholders:

%1s

Attribute value that triggered the error.

3.26.2 Description

The `NAME` attribute on a connection must be one of: `PAGE`, `TEXT`, `CONSTANT` or a name defined by a `SERVER_INTERFACE` element on the same UIM page.

3.26.3 Resolution

On the identified UIM page, check that all names defined on connection endpoints refer to a particular server interface or are one of the reserved values: `PAGE`, `TEXT` or `CONSTANT`.

3.27 -120066 ERR_CONNECT_INVALID_NUM_FIELDS

3.27.1 Message

Invalid number of connections for field (must be between 1 and 3).

3.27.2 Description

Unless the `CONTROL` attribute on the field is set to `SKIP`, a field must contain at least one, and at most three, `CONNECT` child elements.

3.27.3 Resolution

On the identified UIM page, check that each `FIELD` element is either a skipped field within a cluster or has from one to three nested `CONNECT` elements.

3.28 -120067 ERR_CONNECT_FLD_ONE_EP

3.28.1 Message

A connection in a field may have only one of `SOURCE`, `TARGET`, or `INITIAL` endpoints

3.28.2 Description

Each connection within a field may have only one endpoint - a source, a target or an initial.

3.28.3 Resolution

On the identified UIM page, ensure that each `CONNECT` element within a `FIELD` has only one child element from `SOURCE`, `TARGET`, and `INITIAL`.

3.29 -120068 ERR_CONNECT_INVALID_PAGE_PARAM

3.29.1 Message

Invalid page parameter in source connection

3.29.2 Description

A connection endpoint references a page parameter that has not been defined.

3.29.3 Resolution

On the identified UIM page, ensure that any SOURCE element that has a NAME attribute of PAGE has a PROPERTY attribute that corresponds to the name of a PAGE_PARAMETER defined on that page.

3.30 -120069 ERR_CONNECT_INCOMPATIBLE_LIST

3.30.1 Message

A list contains elements that make connections to list properties from incompatible lists or that mix extended paths with list properties.

3.30.2 Description

A list is modelled as an aggregation of records (or *struct* instances), each with a number of fields. In UIM, a server interface property corresponding to one of these fields is called a *list property*. When data is retrieved at runtime, all of the list properties corresponding to the fields from the same aggregation will have the same number of values, as the number of values is equal to the number of records. The first value in each list property is the value of the corresponding field in the first record; the second value in each, the second record; and so on. However, list properties from different aggregations of records do not collate in this manner and it is not permitted to mix them in the same UIM LIST. In the `ServerAccessBeans.xml` file, the LIST attribute for each property indicates which list the property belongs to. If the value is zero, the property is not a list property.

When extended paths are used, no list properties may be referenced. The extended paths must be used to access lists of values represented within the values of non-list properties, such as when a value is an XML document.

3.30.3 Resolution

On the identified UIM page, ensure that elements within a single LIST only reference list properties from the same list.

3.31 -120070

ERR_CONNECT_PAGE_PARAM_AND_TARGET

3.31.1 Message

A field with an input mapping may not have a page parameter as its source

3.31.2 Description

A field has been defined as an input and uses a page parameter as a source.

3.31.3 Resolution

On the identified UIM page, ensure that any FIELD element containing a TARGET does not also contain a SOURCE element with NAME attribute set to PAGE.

3.32 -120071 ERR_CONNECT_MISSING_ENDPOINT

3.32.1 Message

A connection must have a source, target, or initial endpoint.

3.32.2 Description

A CONNECT element has been encountered with no SOURCE, TARGET or INITIAL child element.

3.32.3 Resolution

On the identified UIM page, ensure that all CONNECT elements contain at least one child element from: SOURCE, TARGET and INITIAL.

3.33 -120072 ERR_CONNECT_INVALID_CHILD

3.33.1 Message

Child of connection element must be source, target or initial endpoint.

3.33.2 Description

Only SOURCE, TARGET and INITIAL are allowed as child elements of CONNECT.

3.33.3 Resolution

On the identified UIM page, ensure that only SOURCE, TARGET and INITIAL elements are used as child elements within CONNECTs.

3.34 -120073 ERR_CONNECT_INVALID_EP

3.34.1 Message

ERROR: A connection endpoint is invalid: %1s.

Message placeholders:

%1s

The reason the endpoint is invalid.

3.34.2 Description

Different element support different combinations of CONNECT elements and their endpoints (SOURCE, TARGET, and INITIAL). In this case, an unsupported combination was specified.

3.34.3 Resolution

The detail following the message will explain the exact cause of the problem.

3.35 -120074 ERR_CONNECT_UNKNOWN_PROP

3.35.1 Message

The server interface property is unknown.

3.35.2 Description

Although the bean referenced in the UIM page exists in the server access beans definition file, the bean property cannot be found.

3.35.3 Resolution

On the identified UIM page, ensure that referenced bean properties exist in the server access beans definition file. Consider the PROPERTY attribute in SOURCE, TARGET and INITIAL elements and the AC-

TION_ID_PROPERTY attribute in SERVER_INTERFACE.

3.36 -120075 ERR_CONNECT_AMBIGUOUS_PROP

3.36.1 Message

ERROR: The short form of the server interface property name '*%1s*' is ambiguous, it matches both '*%2s*' and '*%3s*'.

Message placeholders:

%1s

The short form of the property name that was used.

%2s

The name of the first property that was found to match the short property name.

%3s

The name of the second property that was found to match the short property name.

3.36.2 Description

Although the bean referenced in the UIM page exists in the server access beans definition file, more than one bean property matches the connection endpoint.

3.36.3 Resolution

On the identified UIM page, make the referenced bean property (the PROPERTY attribute in the SOURCE, TARGET or INITIAL elements) unambiguous by using more of the fully-qualified property name from the server access beans definition file.

3.37 -120076

ERR_CONNECT_WIDGET_PARAM_NUM_CONNS

3.37.1 Message

Invalid number of connections for a widget parameter (must be 1, 2 or 3).

3.37.2 Description

A widget parameter has been defined on the page with an invalid number of connections.

3.37.3 Resolution

On the identified UIM page, ensure that each `WIDGET_PARAMETER` element has 1, 2 or 3 `CONNECT` sub-elements.

3.38 -120077

ERR_CONNECT_WIDGET_PARAM_ONE_EP

3.38.1 Message

A connection in a widget parameter may have only one of `SOURCE`, `TARGET`, or `INITIAL` endpoints.

3.38.2 Description

A widget parameter has been defined on the page with an invalid selection of connections.

3.38.3 Resolution

On the identified UIM page, ensure that each `WIDGET_PARAMETER` element has at most one of `SOURCE`, `TARGET` and `INITIAL` endpoints.

3.39 -120078 ERR_CONNECT_WIDGET_PARAM_NO_EP

3.39.1 Message

A connection in a widget parameter must have at least one `SOURCE`, `TARGET`, or `INITIAL` endpoint.

3.39.2 Description

A widget parameter has been defined on the page with an invalid selection of connections.

3.39.3 Resolution

On the identified UIM page, ensure that each `WIDGET_PARAMETER` element has at least one `SOURCE`, `TARGET` or `INITIAL` endpoint.

3.40 -120079

ERR_CONNECT_WIDGET_PARAM_INVALID_EP

3.40.1 Message

ERROR: A connection endpoint of type *%1s* is not valid for this widget parameter.

Message placeholders:

%1s

The type of the connection endpoint, SOURCE, TARGET, or INITIAL.

3.40.2 Description

A widget parameter has been defined with an invalid type of connection endpoint.

3.40.3 Resolution

On the identified UIM page, ensure that each WIDGET_PARAMETER element has the correct connection endpoints for that type of widget.

3.41 -120080

ERR_CONNECT_WIDGET_PARAM_NO_CONNS

3.41.1 Message

A widget parameter must have at least one connection.

3.41.2 Description

A widget parameter has been defined on the page with no connections.

3.41.3 Resolution

On the identified UIM page, ensure that each WIDGET_PARAMETER element has at least one CONNECT sub-element.

3.42 -120081 ERR_CONNECT_INVALID_PATH

3.42.1 Message

A connection contains an extended path value '*%1s*' that is not a valid path.

Message placeholders:

%1s

The invalid path value.

3.42.2 Description

An `EXTENDED_PATH` attribute is used on a connection endpoint, but the value of that attribute cannot be parsed as a path value.

3.42.3 Resolution

Ensure that the extended path value is a valid path. See any associated error message for more details.

3.43 -120090 ERR_DOMAIN_EXPANSION_FAILED

3.43.1 Message

The expansion of fields for the `%1s` domain failed. Error: `%2s`.

Message placeholders:

%1s

The domain for which field expansion failed.

%2s

The error message.

3.43.2 Description

There was an error converting a single field into multiple fields. The address widget is an example of a single field which expands into multiple fields.

3.43.3 Resolution

The specific error message associated with the expansion of the field should provide information to help resolve the issue.

3.44 -120100 ERR_DUPLICATE_PAGE_ID

3.44.1 Message

The page ID '`%1s`' appears more than once in the page hierarchy.

Message placeholders:

%1s

The duplicated page ID.

3.44.2 Description

More than one page has been defined with the same page ID.

3.44.3 Resolution

Ensure that the `PAGE_ID` attributes in the `PAGE` elements of UIM files are unique.

3.45 -120101 ERR_DUPLICATE_GROUP_ID

3.45.1 Message

The following page group ID appears more than once in the page hierarchy:
`%1s`.

Message placeholders:

%1s

The duplicated page group ID.

3.45.2 Description

More than one group has been defined with the same group ID.

3.45.3 Resolution

Check that the page groups defined in the group definition files have unique group IDs (`GROUP_ID` attribute of `PAGE_GROUP` element).

3.46 -120102 ERR_DUPLICATE_PARAM_NAME

3.46.1 Message

Duplicate page parameter name.

3.46.2 Description

The same name has been assigned to two different page parameters.

3.46.3 Resolution

On the identified UIM page, ensure that the `NAME` attributes of the `PAGE_PARAMETER` elements are unique.

3.47 -120103 ERR_DUPLICATE_BEAN_NAME

3.47.1 Message

The server interface name is not unique.

3.47.2 Description

The same name has been assigned to two server interface beans on one page.

3.47.3 Resolution

On the identified UIM page, ensure that unique names are assigned to each server interface bean (NAME attribute of the SERVER_INTERFACE element).

3.48 -120104 ERR_HIERARCHY_MISSING_PARAM

3.48.1 Message

The page parameter '*%1s*' is not defined for page '*%2s*', but is defined for its containing page group '*%3s*'.

Message placeholders:

%1s

The name of the page parameter.

%2s

The page ID of the page that does not define the parameter.

%3s

The group ID of the group that defines the page parameter.

3.48.2 Description

A page group defines a page parameter, but a page within that group does not define the same parameter. All pages in a group must define the same parameters that are defined for the group.

3.48.3 Resolution

Ensure that the specified page defines the required parameter or that the page group has not defined it unnecessarily.

3.49 -120110 ERR_ELEMENT_UNKNOWN

3.49.1 Message

Invalid element: *%1s*

Message placeholders:

%1s

The name of the element.

3.49.2 Description

An unexpected element has been encountered in the UIM file.

3.49.3 Resolution

On the identified UIM page, change or remove the invalid element. See the UIM Schema for allowed elements.

3.50 -120111 ERR_ELEMENT_NOT_EMPTY

3.50.1 Message

The element *%1s* must not contain child elements.

Message placeholders:

%1s

The name of the element.

3.50.2 Description

The named element must not contain any child elements.

3.50.3 Resolution

On the identified UIM page, remove any child elements from the named element.

3.51 -120112 ERR_ELEMENT_MISSING_CHILD

3.51.1 Message

The element *%1s* is missing a mandatory *%2s* child element.

Message placeholders:

%1s

The name of the element.

%2s

The name of the mandatory child element.

3.51.2 Description

The named element is missing a mandatory child element.

3.51.3 Resolution

On the identified UIM page, add the required child element.

3.52 -120113 ERR_ELEMENT_EMPTY

3.52.1 Message

The element *%1s* must not be empty.

Message placeholders:

%1s

The name of the element.

3.52.2 Description

An element has been encountered that requires child elements.

3.52.3 Resolution

On the identified UIM page, add child elements as appropriate to the named element.

3.53 -120114 ERR_ELEMENT_MISSING_ATTRIBUTE

3.53.1 Message

The element *%1s* is missing a mandatory *%2s* attribute.

Message placeholders:

%1s

The name of the element.

%2s

The name of the mandatory attribute.

3.53.2 Description

An element has been encountered which is missing a required attribute.

3.53.3 Resolution

On the identified UIM page, find the named element and add the named attribute.

3.54 -120115 ERR_ELEMENT_INVALID_ATT

3.54.1 Message

The element *%1s* contains an unknown attribute. Allowed attributes for this element are: *%2s*.

Message placeholders:

%1s

The name of the element.

%2s

The list of allowed attributes.

3.54.2 Description

An unrecognized attribute was encountered on an element.

3.54.3 Resolution

TBD

3.55 -120116 ERR_ELEMENT_UNEXPECTED_CHILD

3.55.1 Message

The element *%1s* contains an unexpected child element. The only allowed elements at this position are: *%2s*.

Message placeholders:

%1s

The name of the element with invalid content.

%2s

List of allowed elements.

3.55.2 Description

An element has been encountered which is not allowed in this context.

3.55.3 Resolution

On the identified UIM page, locate the name element and ensure that all of its child elements belong to the list of allowed elements at this position.

3.56 -120130 ERR_FIELD_HOME_INVALID_SOURCE

3.56.1 Message

CONNECT element within FIELD linked to user home can only source from a TEXT connection.

3.56.2 Description

A CONNECT element within a FIELD linked to the user's home page may only contain an endpoint that sources from a TEXT connection.

3.56.3 Resolution

On the identified UIM page, for each FIELD that contains both a LINK with HOME_PAGE equal to `true` and a CONNECT, ensure that the CONNECT contains only a SOURCE with NAME equal to TEXT.

3.57 -120131 ERR_FIELD_INVALID_LINK

3.57.1 Message

A field with a target connection may only use a link element to pass a parameter to a pop-up page.

3.57.2 Description

A field has been found that contains both a target connection and a LINK element on which one or more attributes have been set. A LINK which is used for the purpose of passing parameters to a pop-up page will have no attributes, only nested CONNECT elements.

3.57.3 Resolution

On the identified UIM page, where a `FIELD` is defined with both `CONNECT/TARGET` and `LINK` child elements, ensure that the `LINK` element has no attributes.

3.58 -120132 ERR_FIELD_MULTIPLE_LINKS

3.58.1 Message

Field may not contain multiple links.

3.58.2 Description

A `FIELD` element must not contain more than one child `LINK` element.

3.58.3 Resolution

On the identified UIM page, ensure that each `FIELD` element contains no more than one child `LINK` element.

3.59 -120133 ERR_FIELD_MULTIPLE_SOURCES

3.59.1 Message

Field may not contain multiple source connections.

3.59.2 Description

A `FIELD` element must not contain more than one `SOURCE` element.

3.59.3 Resolution

On the identified UIM page, ensure that each `FIELD` element contains no more than one `SOURCE` element.

3.60 -120134 ERR_FIELD_MULTIPLE_TARGETS

3.60.1 Message

Field may not contain multiple target connections.

3.60.2 Description

A `FIELD` element must not contain more than one `TARGET` element.

3.60.3 Resolution

On the identified UIM page, ensure that each `FIELD` element contains no more than one `TARGET` element.

3.61 -120135 ERR_FIELD_MULTIPLE_INITIALS

3.61.1 Message

Field may not contain multiple initial connections.

3.61.2 Description

A `FIELD` element must not contain more than one `INITIAL` element.

3.61.3 Resolution

On the identified UIM page, ensure that each `FIELD` element contains no more than one `INITIAL` element.

3.62 -120136 ERR_FIELD_SINGLE_AS_MULTIPLE

3.62.1 Message

Field in page '`%1s`' should not be rendered as transfer list, as the targeted property '`%2s`' expects a single value.

Message placeholders:

`%1s`

Id of page containing the incorrect field.

`%2s`

Server interface property targeted by the field.

3.62.2 Description

An `FIELD` element must not contain a `CONTROL` attribute with the value of `TRANSFER_LIST` as it is associated with a reported property expecting singular value (code table code).

3.62.3 Resolution

On the identified UIM page, ensure that reported `FIELD` element does not

contain `CONTROL` attribute with the value of `TRANSFER_LIST`, or, otherwise, correct that `FIELD` connection to associate it with proper initial and target properties.

3.63 -120140 ERR_INFORMATIONAL_INVALID_SOURCE

3.63.1 Message

The `INFORMATIONAL` element cannot have a `CONSTANT`, `TEXT` or `PAGE` parameter source connection.

3.63.2 Description

The connection endpoint associated with an `INFORMATIONAL` element must be to the field of a bean containing informational messages. Thus, source connections of types `CONSTANT`, `TEXT` and `PAGE` may not be used.

3.63.3 Resolution

On the identified UIM page, ensure that the `INFORMATIONAL` element does not contain a `SOURCE` connection of type `CONSTANT`, `TYPE` or `PAGE`.

3.64 -120151 ERR_INVALID_XML

3.64.1 Message

ERROR: The XML file '*%1s*' could not be parsed.

Message placeholders:

%1s

The name of the file containing invalid XML.

3.64.2 Description

The page generator could not parse an XML file because it was not well-formed or valid.

3.64.3 Resolution

Ensure the file in question is a well-formed and valid XML file.

3.65 -120152 ERR_GEN_INVALID_XSL

3.65.1 Message

ERROR: The XSL stylesheet file '*%1s*' could not be parsed.

Message placeholders:

%1s

The name of the file containing invalid XSL.

3.65.2 Description

The page generator could not parse an XSL stylesheet file because it was not well-formed or valid.

3.65.3 Resolution

Ensure the file in question is a well-formed and valid XSL file. If the file is not one that was customized, report the error.

3.66 -120153 ERR_GEN_INVALID_XSL_DETAILED

3.66.1 Message

ERROR: A transformation using the stylesheet '*%1s*' failed. There was an error on line '*%2s*' at column '*%3s*'.

Message placeholders:

%1s

The name of the XSL stylesheet file.

%2s

The line number of the error.

%3s

The column number of the error.

3.66.2 Description

The page generator could not parse an XSL stylesheet file, or when executing it, the stylesheet directed the termination of the processing. The file may not be well-formed or not valid, or the input may not be acceptable to the stylesheet. The location of the error is described.

3.66.3 Resolution

Ensure the file in question is a well-formed and valid XSL file. If the file is not one that was customized, report the error.

3.67 -120154 ERR_INVALID_NAME

3.67.1 Message

Invalid name, must be valid Java identifier

3.67.2 Description

The name assigned to a server interface bean on the UIM page is invalid.

3.67.3 Resolution

On the identified UIM page, ensure that all names assigned to server interface beans constitute valid Java identifiers.

3.68 -120155 ERR_GEN_INVALID_UIM

3.68.1 Message

ERROR: A UIM file contains invalid content.

3.68.2 Description

During the validation of a UIM file, invalid content was detected.

3.68.3 Resolution

See the specific error message that accompanies this one for more information.

3.69 -120156 ERR_GEN_INVALID_MESSAGE

3.69.1 Message

ERROR: A UIM validation message was not formatted correctly.

3.69.2 Description

During the validation of a UIM file, a validation error occurred, but the error message was not formatted correctly and could not be displayed.

3.69.3 Resolution

This is an internal error. Report the problem.

3.70 -120160 ERR_LINK_INVALID_ATT

3.70.1 Message

A link may specify `URI_SOURCE_NAME` and `URI_SOURCE_PROPERTY` or exactly one of `PAGE_ID`, `PAGE_ID_REF`, `URL`, `URI` and `URI_REF`.

3.70.2 Description

A link has been found which attempts to set an invalid combination of the attributes `PAGE_ID`, `PAGE_ID_REF`, `URL`, `URI`, `URI_REF`, `URI_SOURCE_NAME` and `URI_SOURCE_PROPERTY`. These attributes are mutually exclusive apart from `URI_SOURCE_NAME` and `URI_SOURCE_PROPERTY`, which must be used together.

3.70.3 Resolution

On the identified UIM page, ensure that each `LINK` element defines a valid combination of attributes.

3.71 -120161 ERR_LINK_INVALID_SOURCE

3.71.1 Message

The `LINK` element cannot have a `TEXT` source connection.

3.71.2 Description

A link has been found that attempts to set a parameter value from a text source connection.

3.71.3 Resolution

On the identified UIM page, ensure that no `LINK` element attempts to define a `SOURCE` connection with `NAME` equal to `TEXT`.

3.72 -120162 ERR_LINK_INVALID_CONNS

3.72.1 Message

A `LINK` with a `PAGE_ID` of "THIS" cannot contain connections.

3.72.2 Description

A `LINK` with a `PAGE_ID` set to `THIS` cannot contain any `CONNECT` child elements.

3.72.3 Resolution

On the identified UIM page, ensure that links with the `PAGE_ID` attribute set to `THIS` do not contain any `CONNECT` child elements.

3.73 -120163 ERR_LINK_NO_CONNS

3.73.1 Message

A link in an action control of type `DISMISS` or `FILE_DOWNLOAD` must contain connections.

3.73.2 Description

A `LINK` element with no child `CONNECT` elements has been found within an `ACTION_CONTROL` element of type `DISMISS` or `FILE_DOWNLOAD`.

3.73.3 Resolution

On the identified UIM page, ensure that each `LINK` element within an `ACTION_CONTROL` element of type `DISMISS` or `FILE_DOWNLOAD` contains at least one child `CONNECT` element.

3.74 -120164 ERR_LINK_NO_ATTRIBUTES

3.74.1 Message

A link in an action control of type `SUBMIT`, `ACTION` or `CLIPBOARD` must have attributes.

3.74.2 Description

A `LINK` element with no attributes has been found within an `ACTION_CONTROL` element of type `SUBMIT`, `ACTION` or `CLIPBOARD`.

3.74.3 Resolution

On the identified UIM page, ensure that each `LINK` element within an `ACTION_CONTROL` element of type `SUBMIT`, `ACTION` or `CLIPBOARD`

defines the appropriate attributes.

3.75 -120165 ERR_LINK_MISSING_SOURCE_ATT

3.75.1 Message

The `URI_SOURCE_NAME` and `URI_SOURCE_PROPERTY` attributes on `LINK` must be used together or not at all.

3.75.2 Description

A link has been found which defines only one of the attributes `URI_SOURCE_NAME` and `URI_SOURCE_PROPERTY`. If either of these attributes is used, the other must be used too.

3.75.3 Resolution

On the identified UIM page, ensure that each `LINK` element defines both `URI_SOURCE_NAME` and `URI_SOURCE_PROPERTY` attributes or neither of these attributes.

3.76 -120166 ERR_SUBMIT_LINK_WITH_URI

3.76.1 Message

A `LINK` in an `ACTION_CONTROL` of type `SUBMIT` is not allowed to have attributes which specify a URL or a URI.

3.76.2 Description

A `LINK` within an `ACTION_CONTROL` of type `SUBMIT` only supports linking to UIM pages by explicitly specifying a page ID. Pages cannot be submitted to an external location or to an internal location (i.e. a page ID) generated at runtime, for example using the `URI_SOURCE_NAME` and `URI_SOURCE_PROPERTY` of the `LINK` element.

3.76.3 Resolution

On the UIM page, ensure that the identified `LINK` explicitly specifies a page ID.

3.77 -120180 ERR_LIST_EMPTY

3.77.1 Message

A list must contain at least one list value connection.

3.77.2 Description

A list has been defined that contains no list-related content. A `LIST` element should contain at least one element (directly or within a `CONTAINER`) which should have a connection that references a valid list property. Not all elements need a source connection to a list property but at least one element that is reproduced on each row of the list must have such a connection. A list property can be a server interface property that is modelled as a list of values, or it can be a property that is combined with an extended path value that contains an empty predicate (“[]”) to represent an embedded list of values.

3.77.3 Resolution

On the identified UIM page, ensure that each `LIST` element contains at least one element that sources its value from a valid list property.

3.78 -120181 ERR_LIST_MULTIPLE_ACTSETS

3.78.1 Message

A list can have only one action set.

3.78.2 Description

More than one action set has been defined for a list. Only one action set per list is permitted.

3.78.3 Resolution

On the identified UIM page, ensure that each `LIST` element contains no more than one `ACTION_SET` child element.

3.79 -120182 ERR_LIST_INVALID_EDITABLE_FIELD

3.79.1 Message

An editable field in a list must have a source connection.

3.79.2 Description

A field has been defined in a list which has a target connection but no source connection. A field in a list can have a source connection or it can

have a source connection and a target connection but it cannot have a target connection on its own because lists cannot be used to create or store data.

3.79.3 Resolution

On the identified field in the identified UIM page, ensure that the identified `FIELD` element contains a `CONNECT` element with a nested `SOURCE` element

3.80 -120183

ERR_LIST_INVALID_EDITABLE_FIELD_DOMAIN

3.80.1 Message

An editable field in a list must have a connection with a supported underlying domain.

3.80.2 Description

A field has been defined in a list which has a target connection, whose underlying domain is not supported.

3.80.3 Resolution

Read the section on editable lists to find out the list of supported domains on an editable field in a list. Then update the model to change the underlying domain of the specified target connection to one of the supported domains. Then rebuild the server and client as normal.

3.81 -120184

ERR_LIST_INVALID_EDITABLE_FIELD_HEIGHT

3.81.1 Message

An editable field in a list cannot have its text area set.

3.81.2 Description

The `HEIGHT` attribute has been added to an editable field in a list, and this is not supported.

3.81.3 Resolution

Read the section on editable lists to find out the list of supported attributes

on an editable field in a list. Then remove the HEIGHT attribute from and FIELD elements on this list.

3.82 -120185

ERR_LIST_INVALID_EDITABLE_FIELD_CONNECTION

3.82.1 Message

Each editable field in a list must have a list value connection.

3.82.2 Description

Every editable field in a list must have a list value connection.

3.82.3 Resolution

A target connections has been defined on a list that doesn't contain list-related content. Each TARGET element nested within a CONNECT element on a LIST element should reference a valid list property. A list property can be a server interface property that is modelled as a list of values, or it can be a property that is combined with an extended path value that contains an empty predicate (“[]”) to represent an embedded list of values.

3.83 -120200 ERR_MENU_INVALID_CHILD

3.83.1 Message

A MENU element with static or navigation mode may only have ACTION_CONTROL child elements.

3.83.2 Description

A MENU element with mode set to DYNAMIC or INTEGRATED_CASE may only have CONNECT child elements.

3.83.3 Resolution

On the identified UIM page, ensure that menus with the MODE attribute set to DYNAMIC or INTEGRATED_CASE only have CONNECT child elements.

3.84 -120201 ERR_MENU_DYN_INVALID_CHILD

3.84.1 Message

A dynamic, integrated case or wizard progress bar MENU element may only have CONNECT child elements.

3.84.2 Description

A MENU element with mode set to DYNAMIC or INTEGRATED_CASE or WIZARD_PROGRESS_BAR may only have CONNECT child elements.

3.84.3 Resolution

On the identified UIM page, ensure that menus with the MODE attribute set to DYNAMIC or INTEGRATED_CASE or WIZARD_PROGRESS_BAR only have CONNECT child elements.

3.85 -120202 ERR_MENU_INVALID_SOURCE

3.85.1 Message

The MENU element cannot have a CONSTANT source connection.

3.85.2 Description

Dynamic and Integrated Case menus can not take a CONSTANT source connection.

3.85.3 Resolution

On the identified UIM page, ensure that MENU elements with the MODE attribute set to DYNAMIC or INTEGRATED_CASE do not contain a SOURCE element with NAME set to CONSTANT.

3.86 -120203 ERR_FIELD_ADDRESS_CLUSTER

3.86.1 Message

A FIELD element based on the domain ADDRESS_DATA must exist in a CLUSTER on its own.

3.86.2 Description

If a CLUSTER contains a FIELD based on the ADDRESS_DATA domain, no other fields may exist in that cluster.

3.86.3 Resolution

Create a separate `CLUSTER` for the address field.

3.87 -120204 ERR_FIELD_DUPLICATE_FOCUS

3.87.1 Message

More than one `FIELD` element has been selected to receive the initial input focus.

3.87.2 Description

The initial input focus has been requested for more than one `FIELD` on the page, but only one `FIELD` is allowed to receive the initial input focus.

3.87.3 Resolution

Ensure that only one `FIELD` on the page has set the `INITIAL_FOCUS` attribute.

3.88 -120220 ERR_PAGE_MISSING_SUBMIT

3.88.1 Message

A page containing an `ACTION` phase `SERVER_INTERFACE` element must also define an `ACTION_CONTROL` element of type "SUBMIT".

3.88.2 Description

An action phase server interface has been defined on a page with no submit action control.

3.88.3 Resolution

On the identified UIM page, ensure that if there is a `SERVER_INTERFACE` where `PHASE` is set to `ACTION` that there is also, somewhere on the page, an `ACTION_CONTROL` where `TYPE` is set to `SUBMIT`.

3.89 -120221 ERR_PAGE_INVALID_ACTSET

3.89.1 Message

A page can have only one action set.

3.89.2 Description

More than one action set has been defined at page level. A `PAGE` element may have no more than one `ACTION_SET` child elements.

3.89.3 Resolution

On the identified UIM page, ensure that there is no more than one action set defined at page level, i.e. that the `PAGE` element contains no more than one `ACTION_SET` child elements.

3.90 -120222 ERR_PAGE_INVALID_TITLE

3.90.1 Message

Page can have only one page title.

3.90.2 Description

More than one `PAGE_TITLE` element has been found. A page may have only one page title.

3.90.3 Resolution

On the identified UIM page, ensure there is no more than one `PAGE_TITLE` element.

3.91 -120223 ERR_PAGE_INVALID_SHORTCUT

3.91.1 Message

Page can have only one shortcut title.

3.91.2 Description

More than one `SHORTCUT_TITLE` element has been found. A page may have only one shortcut title.

3.91.3 Resolution

On the identified UIM page, ensure there is no more than one `SHORTCUT_TITLE` element.

3.92 -120224 ERR_PAGE_MISSING_PAGE_TITLE

3.92.1 Message

Page Title element is mandatory.

3.92.2 Description

The UIM page must contain a page title.

3.92.3 Resolution

To the identified UIM page, add a page title.

3.93 -120225 ERR_PAGE_MISSING_SCRIPT_FILE

3.93.1 Message

There is no `SCRIPT_FILE` defined on the `SCRIPT` or the `PAGE` element.

3.93.2 Description

A reference to a JavaScript file is missing. This must be provided by a `SCRIPT_FILE` attribute either on the `SCRIPT` element directly or on the `PAGE` element.

3.93.3 Resolution

On the identified UIM page, ensure that there is a `SCRIPT_FILE` attribute on the page element or on each `SCRIPT` element.

3.94 -120226 ERR_PAGE_MULTIPLE_INFORMATIONALS

3.94.1 Message

`PAGE` can only have one `INFORMATIONAL`.

3.94.2 Description

More than one `INFORMATIONAL` element has been included in the UIM page. This is not allowed.

3.94.3 Resolution

On the identified UIM page, ensure that there is no more than one `INFORMATIONAL` element defined on the page.

3.95 -120227 ERR_PAGE_ID_FILENAME

3.95.1 Message

The page ID and filename do not match.

3.95.2 Description

The filename and page ID of the UIM page do not match.

3.95.3 Resolution

On the identified UIM page, ensure that the `PAGE_ID` attribute of the `PAGE` element has the same value as the name of the UIM file (minus the `.uim` extension).

3.96 -120228 ERR_PAGE_ID_REQUIRED

3.96.1 Message

`PAGE_ID` attribute is required on `PAGE` element.

3.96.2 Description

The mandatory `PAGE_ID` attribute is not present on the `PAGE` element.

3.96.3 Resolution

Add the mandatory `PAGE_ID` attribute to the `PAGE` element.

3.97 -120240 ERR_PAGE_REF_MISSING_ATT

3.97.1 Message

Either `PAGE_ID` or `HOME_PAGE` attribute must be set.

3.97.2 Description

A `PAGE_REF` element has been defined without one of the attributes `PAGE_ID` or `HOME_PAGE`.

3.97.3 Resolution

On the identified page, ensure that each `PAGE_REF` element contains one of the attributes `PAGE_ID` or `HOME_PAGE`.

3.98 -120241 ERR_PAGE_REF_INVALID_VISIBLE

3.98.1 Message

When the `HIGHLIGHT_PAGE_ID` attribute is used, `VISIBLE` must be set to 'false'.

3.98.2 Description

The settings of the `HIGHLIGHT_PAGE_ID` and `VISIBLE` attributes on a `PAGE_REF` element are incompatible. The `HIGHLIGHT_PAGE_ID` refers to the page in the navigation menu that is highlighted when this menu item is selected. Therefore this page must be invisible in the navigation menu.

3.98.3 Resolution

On the identified UIM page, set `VISIBLE` to `false` on any `PAGE_REF` element that uses the `HIGHLIGHT_PAGE_ID` attribute.

3.99 -120250 ERR_PAGE_GROUP_INVALID_PARENT

3.99.1 Message

This group has no parent so the `PARENT_TARGET` attribute must not be used.

3.99.2 Description

A parent target page has been defined on the root page group.

3.99.3 Resolution

On the identified UIM page, remove the `PARENT_TARGET` attribute from the root page group in the `Pages.xml` file.

3.100 -120260 ERR_PAGE_TITLE_INVALID_CONN

3.100.1 Message

Connection to page title must not have target.

3.100.2 Description

A target connection has been defined within a page title.

3.100.3 Resolution

On the identified UIM page, ensure that the `PAGE_TITLE` element does not contain a target connection (i.e. `CONNECT/TARGET`).

3.101 -120261 ERR_PAGE_TITLE_MISSING_SOURCE

3.101.1 Message

Connection to page title must have source.

3.101.2 Description

A page title has been defined without a source connection.

3.101.3 Resolution

On the identified UIM page, ensure that the page title contains a source connection (i.e. `CONNECT/SOURCE`).

3.102 -120270 ERR_PROP_NOT_LIST

3.102.1 Message

A list property is required in this context.

3.102.2 Description

An initial connection endpoint defined as a hidden property references a bean property that is not a list property.

3.102.3 Resolution

On the identified UIM page, ensure that any `INITIAL` element with attribute `HIDDEN_PROPERTY` set to `true` references a server access bean property (attribute `PROPERTY`) of type list.

3.103 -120280 ERR_SCRIPT_MULTIPLE_EVENTS

3.103.1 Message

Only one instance of an event is allowed in a SCRIPT for PAGE, FIELD or ACTION_CONTROL elements.

3.103.2 Description

An attempt has been made to invoke more than one script for the same event.

3.103.3 Resolution

On the identified UIM page, ensure that in a particular script context (i.e. within a PAGE, FIELD or ACTION_CONTROL element) that there is no more than one SCRIPT element defined for each type of event.

3.104 -120290 ERR_SHORTCUT_HAS_TARGET

3.104.1 Message

Connection to shortcut title must not have target.

3.104.2 Description

A target connection has been defined for a shortcut title.

3.104.3 Resolution

On the identified UIM page, ensure that the SHORTCUT_TITLE element does not contain a TARGET connection element.

3.105 -120291 ERR_SHORTCUT_MISSING_SOURCE

3.105.1 Message

Connection to shortcut title must have source.

3.105.2 Description

A source connection must be defined for a shortcut title.

3.105.3 Resolution

On the identified UIM page, ensure that the `SHORTCUT_TITLE` element contains a `SOURCE` connection element.

3.106 -120300 ERR_SI_INVALID_NAME

3.106.1 Message

Invalid `NAME` attribute value '*%1s*'. A server interface cannot be named 'PAGE', 'TEXT' or 'CONSTANT'.

Message placeholders:

%1s

Invalid value of `NAME` attribute.

3.106.2 Description

A server interface has been defined with an invalid name. `PAGE`, `TEXT` and `CONSTANT` are reserved names.

3.106.3 Resolution

On the identified UIM page, ensure that server interfaces are allocated a valid name, i.e. the `NAME` attribute of the `SERVER_INTERFACE` element should not be set to any of `PAGE`, `TEXT` or `CONSTANT`.

3.107 -120310 ERR_TARGET_NOT_ALLOWED

3.107.1 Message

A field in a list may not have a target connection.

3.107.2 Description

A field defined in a list may not contain a target endpoint.

3.107.3 Resolution

On the identified UIM page, ensure that there are no `TARGET` elements within a `LIST`.

3.108 -120320 ERR_UIM_INVALID_ROOT

3.108.1 Message

The root element must be *%1s*.

Message placeholders:

%1s

The name of the root element.

3.108.2 Description

An invalid root element has been provided.

3.108.3 Resolution

Only PAGE, PAGE_GROUP or VIEW may be a root element.

3.109 -120330 ERR_BEAN_META_TAG

3.109.1 Message

Invalid bean metadata tag attribute: *%1s*

Message placeholders:

%1s

Attribute name that triggered the error.

3.109.2 Description

An attribute is misplaced or incorrect in the server access beans definition file.

3.109.3 Resolution

Change the name of, or remove, the specified attribute.

3.110 -120340 ERR_WIDGET_INVALID_PARAMETER

3.110.1 Message

The widget cannot have a parameter named '*%1s*'.

Message placeholders:

%1s

The invalid widget parameter name.

3.110.2 Description

An unknown widget parameter name has been encountered.

3.110.3 Resolution

On the identified UIM page, ensure that all `WIDGET_PARAMETER` elements refer to valid widget parameters in the `NAME` attribute.

3.111 -120341 ERR_WIDGET_MISSING_PARAMETER

3.111.1 Message

The widget must have a parameter named '*%1s*'.

Message placeholders:

%1s

The missing widget parameter name.

3.111.2 Description

A widget has been defined but a mandatory parameter is missing.

3.111.3 Resolution

On the identified UIM page, ensure that each required widget parameters is represented by a `WIDGET_PARAMETER` elements.

3.112 -120350 ERR_PAGE_DETAILS_INVALID_TAB_NAME_NUMBER

3.112.1 Message

Details page must have one, and only one, tab name element.

3.112.2 Description

a `TAB_NAME` element has not been found, or more than one has been found. A details page must have one, and only one, tab name.

3.112.3 Resolution

On the identified UIM page, ensure there is one and only one `TAB_NAME` element.

3.113 -120351 ERR_PAGE_INVALID_TAB_NAME

3.113.1 Message

Non-details page cannot have any tab name.

3.113.2 Description

At least one `TAB_NAME` element has been found. A non-detail page cannot have any tab name.

3.113.3 Resolution

On the identified UIM page, ensure there is no `TAB_NAME` element.

3.114 -120352 ERR_PAGE_DETAILS_INVALID_PAGE_TITLE_NUMBER

3.114.1 Message

Details page must have one, and only one, page title element.

3.114.2 Description

More than one `PAGE_TITLE` element has been found, or not instance been found. A details page must have one, and only one, page title.

3.114.3 Resolution

On the identified UIM page, ensure there is one `PAGE_TITLE` element.

3.115 -120353 ERR_TAB_NAME_HAS_TARGET

3.115.1 Message

Connection to tab name must not have target.

3.115.2 Description

A target connection has been defined for a tab name.

3.115.3 Resolution

On the identified UIM page, ensure that the `TAB_NAME` element does not contain a `TARGET` connection element.

3.116 -120354 ERR_TAB_NAME_MISSING_SOURCE

3.116.1 Message

Connection to tab name must have source.

3.116.2 Description

A source connection must be defined for a tab name.

3.116.3 Resolution

On the identified UIM page, ensure that the `TAB_NAME` element contains a `SOURCE` connection element.

3.117 -120355 ERR_SI_INVALID_PHASE

3.117.1 Message

Invalid `PHASE` attribute value, '`%1s`'. Server interface must have a "DISPLAY" phase on a details page.

Message placeholders:

`%1s`

Invalid value of `PHASE` attribute.

3.117.2 Description

A server interface has been defined with an invalid phase.

3.117.3 Resolution

On the identified UIM details page, ensure that server interfaces are allocated a valid phase, i.e. the `PHASE` attribute of the `SERVER_INTERFACE` element should only be set to `DISPLAY`.

3.118 -120356 ERR_ACTCTL_INVALID_TYPE

3.118.1 Message

Invalid TYPE attribute value, '*%1s*'. Action control must have an "ACTION" type on a details page.

Message placeholders:

%1s

Invalid value of TYPE attribute.

3.118.2 Description

An action control has been defined with an invalid type.

3.118.3 Resolution

On the identified UIM details page, ensure that action controls are allocated a valid type, i.e. the TYPE attribute of the ACTION_CONTROL element should only be set to ACTION.

3.119 -120357 ERR_PAGE_TITLE_INVALID_ELEMENTS

3.119.1 Message

Page title elements on a details page can only be connections.

3.119.2 Description

An element other than CONNECT has been defined within a page title on a details page.

3.119.3 Resolution

On the identified UIM details page, ensure that the PAGE_TITLE element only contains connections (i.e. CONNECT).

3.120 -120358 ERR_PAGE_TITLE_INVALID_ATTRIBUTES

3.120.1 Message

Page title on a details page can only have a style attribute.

3.120.2 Description

An attribute other than STYLE has been defined within a page title on a details page.

3.120.3 Resolution

On the identified UIM details page, ensure that the PAGE_TITLE element only has styling attributes(i.e. STYLE).

3.121 -120359 ERR_PAGE_INVALID_ELEMENT

3.121.1 Message

Page elements on a details page cannot be SHORTCUT_TITLE, MENU, JSP_SCRIPTLET, INFORMATIONAL, DESCRIPTION, SCRIPT or INCLUDE.

3.121.2 Description

An unexpected element has been defined on a details page.

3.121.3 Resolution

On the identified UIM details page, ensure that the PAGE element does not contain SHORTCUT_TITLE, MENU, JSP_SCRIPTLET, INFORMATIONAL, DESCRIPTION, SCRIPT or INCLUDE elements.

3.122 -120400 ERR_GEN_UNKNOWN

3.122.1 Message

ERROR: An unknown or unexpected error occurred.

3.122.2 Description

During generation, an exception occurred unexpectedly. The specific exception will be reported along with this exception.

3.122.3 Resolution

See the specific exception message for more information.

3.123 -120401 ERR_PROCESSING_FAILED

3.123.1 Message

ERROR: An unknown or unexpected error occurred when processing the file '*%1s*'.

Message placeholders:

%1s

The name of the file that could not be processed.

3.123.2 Description

The page generator encountered a problem during the processing of a particular file.

3.123.3 Resolution

If the file is a required configuration file or a UIM file, ensure that it is present and that its contents are valid. Clean up the generator output and run the generator again. See the associated error message for more information. Report the error if it persists.

3.124 -120402 ERR_FILE_NOT_FOUND

3.124.1 Message

ERROR: The file '*%1s*' could not be found.

Message placeholders:

%1s

The name of the file that could not be found.

3.124.2 Description

The page generator could not find a required file.

3.124.3 Resolution

If the file is a required configuration file, ensure that it is present. Clean up the generator output and run the generator again. Report the error if it persists.

3.125 -120403 ERR_FOLDER_NOT_FOUND

3.125.1 Message

ERROR: '*%1s*' is not a folder or could not be found.

Message placeholders:

%1s

The path that was expected to be a folder.

3.125.2 Description

During generation, a path was expected to be a folder but was either not found at all or was an ordinary file.

3.125.3 Resolution

Check that the folder exists. Clean the generator output and restart it if the problem persists.

3.126 -120404 ERR_PROPS_IMAGE_UNDEFINED

3.126.1 Message

ERROR: The image property '*%1s*' is not defined.

Message placeholders:

%1s

The name of the property identifying the image that is not defined in the expected properties file.

3.126.2 Description

The page generator could not find a definition for the named image property.

3.126.3 Resolution

Ensure that the properties file defines the named property or that the named property is correctly spelled.

3.127 -120405 ERR_PROPS_CONSTANT_UNDEFINED

3.127.1 Message

ERROR: The constant property '*%1s*' is not defined.

Message placeholders:

%1s

The name of the property identifying the constant that is not defined in the expected properties file.

3.127.2 Description

The page generator could not find a definition for the named constant property.

3.127.3 Resolution

Ensure that the properties file defines the named property or that the named property is correctly spelled.

3.128 -120406 ERR_PROPS_TEXT_NO_FILE

3.128.1 Message

ERROR: The text property '*%1s*' used in the file '*%2s*' at line *%3s* could not be resolved, as no properties file was found.

Message placeholders:

%1s

The name of the property identifying the text string.

%2s

The name of the file from which the property was referenced.

%3s

The line number in the file from which the property was referenced.

3.128.2 Description

The page generator could not find a definition for the named text property because the properties file was missing.

3.128.3 Resolution

Ensure that the properties file required for the UIM page is present and that both the UIM file and the properties file are correctly named using the page ID.

3.129 -120407 ERR_PROPS_TEXT_UNDEFINED

3.129.1 Message

ERROR: The text property '*%1s*' used in the file '*%2s*' at line *%3s* could not

be resolved as no such property exists in the properties file '*%4s*'.

Message placeholders:

%1s

The name of the property identifying the text string.

%2s

The name of the file from which the property was referenced.

%3s

The line number in the file from which the property was referenced.

%4s

The name of the properties file that was expected to contain the property.

3.129.2 Description

The page generator could not find a definition for the named text property within the expected properties file.

3.129.3 Resolution

Ensure that the properties file required for the UIM page contains the named property or that the named property is correctly spelled.

3.130 -120408 ERR_PROPS_PAGE_ID_REF_UNDEFINED

3.130.1 Message

ERROR: The page ID reference property '*%1s*' was not found in the CuramLinks.properties file.

Message placeholders:

%1s

The name of the page ID reference property.

3.130.2 Description

The page generator could not find a definition for the specified page ID reference in the CuramLinks.properties file.

3.130.3 Resolution

Ensure that the CuramLinks.properties file defines the page ID reference used or that the reference is correctly spelled.

3.131 -120409 ERR_PROPS_URI_REF_UNDEFINED

3.131.1 Message

ERROR: The URI reference property '*%1s*' was not found in the CuramLinks.properties file.

Message placeholders:

%1s

The name of the URI reference property.

3.131.2 Description

The page generator could not find a definition for the specified URI reference in the CuramLinks.properties file.

3.131.3 Resolution

Ensure that the CuramLinks.properties file defines the URI reference used or that the reference is correctly spelled.

3.132 -120410 ERR_PROPS_HIERARCHY_NO_FILE

3.132.1 Message

ERROR: The page hierarchy file '*%1s*' does not exist or has no corresponding properties file.

Message placeholders:

%1s

The name of the page hierarchy file.

3.132.2 Description

The page hierarchy file named either does not exist or it has no corresponding properties file. Given the file name for a page group reference, the generator first checks if a properties file exists for that file. If the properties file does not exist, this error is reported. However, if the page hierarchy file itself does not exist (perhaps the name is specified incorrectly), then it is also unlikely that the properties file will exist, so a missing page hierarchy file could be the real cause of the error.

3.132.3 Resolution

Check that the relevant page hierarchy and properties files exist.

3.133 -120411 ERR_PROPS_HIERARCHY_TITLE_UNDEFINED

3.133.1 Message

ERROR: The page group title property '*%1s*' could not be found.

Message placeholders:

%1s

The name of the title property.

3.133.2 Description

The property referenced for the title of a page group within the page hierarchy does not exist.

3.133.3 Resolution

Check the relevant properties file exists and contains a definition for the named property.

3.134 -120412 ERR_PROPS_FILE_NOT_LOADED

3.134.1 Message

ERROR: The properties file '*%1s*' could not be loaded.

Message placeholders:

%1s

The name of the properties file.

3.134.2 Description

The properties file referenced could not be loaded.

3.134.3 Resolution

Check the relevant properties file exists.

3.135 -120413 ERR_PROPS_WIDGET_PROP_NAME

3.135.1 Message

ERROR: The file name '*%1s*' used is similar to the widget properties file name and it is a reserved name. It cannot be used for a uim or vim file. Please use a different file name for the uim or vim file and its corresponding properties file.

Message placeholders:

%1s

The name of the uim file which is a reserved name.

3.135.2 Description

The file name used is a reserved file name.

3.135.3 Resolution

Use a different file name for the uim or vim file and its corresponding properties file.

3.136 -120500 ERR_STAGING_ATTR_MISSING

3.136.1 Message

ERROR: A required attribute of the stage task is missing.

3.136.2 Description

The stage task that executes prior to page generation was not provided with a required attribute. These attributes are set in the Ant build scripts.

3.136.3 Resolution

Ensure that the build scripts have not been modified incorrectly. Report the problem if it persists.

3.137 -120501 ERR_STAGING_DUPLICATE

3.137.1 Message

ERROR: The file '*%1s*' appears twice in the folder '*%2s*'.

Message placeholders:

%1s

The name of the file.

%2s

The folder contains two copies of the file.

3.137.2 Description

During the staging phase of generation, two file with the same name were found in the same folder. This can indicate a problem with the case of the file name that can occur on *Unix*® systems.

3.137.3 Resolution

Check that the folder does not contain two files with the same name but in a different case. The page ID values used may need to be changed.

3.138 -120502 ERR_MULTIPLE_CONDITIONS

3.138.1 Message

ERROR: An element may only have one child CONDITION element.

3.138.2 Description

An element may only have one child CONDITION element. Only ACTION_SET and CLUSTER can have a child CONDITION element.

3.138.3 Resolution

Ensure that all ACTION_SET and CLUSTER elements have zero or one CONDITION elements.

3.139 -120503 ERR_INVALID_FOOTER_ROW

3.139.1 Message

ERROR: A FOOTER_ROW must contain the same number of fields as the parent LIST.

3.139.2 Description

A FOOTER_ROW element exists in a LIST element with a different number of FIELD elements to the LIST. A FOOTER_ROW must contain the same number of fields as the parent LIST.

3.139.3 Resolution

Ensure that all `FOOTER_ROW` elements have the same number of `FIELD` elements as the parent `LIST`.

3.140 -120504 ERR_INVALID_VIM_REFERENCE

3.140.1 Message

The `.vim` file '`%1s`' referenced in '`%2s`' does not exist.

Message placeholders:

%1s

The name of the `.vim` file being referenced.

%2s

The name of the `.uim` file containing the `.vim` file reference.

3.140.2 Description

A `.vim` file referenced within a `.uim` file does not exist.

3.140.3 Resolution

Ensure the existence of the `.vim` file.

3.141 -120505 ERR_INVALID_WINDOW_OPTION_NAME

3.141.1 Message

A '`%3s`' element contains an invalid option name '`%1s`'.

Message placeholders:

%1s

The erroneous option name used.

%2s

The option value used.

%3s

The element that contains invalid attribute value.

3.141.2 Description

A `WINDOW_OPTIONS` attribute contains an invalid character.

3.141.3 Resolution

On the identified UIM page, where an element is defined with a `WINDOW_OPTIONS` attribute, ensure that all entries in the attribute are of the format `name=value`, and that the format of the value is correct. No single or double quotes should be used in the `WINDOW_OPTIONS` attribute.

Current supported options are

width

The width of the dialog window in pixels. Type is NUMERIC.

height

The height of the dialog window in pixels. Type is NUMERIC.

An example of a correct `WINDOW_OPTIONS` value is `width=500,height=600`

3.142 -120506 ERR_INVALID_WINDOW_OPTION_VALUE

3.142.1 Message

A '`%1s`' element contains an invalid option value '`%3s`' for the option '`%2s`'.

Message placeholders:

%1s

The element that contains invalid attribute value.

%2s

The option name used.

%3s

The erroneous option value.

3.142.2 Description

A `WINDOW_OPTIONS` attribute contains a supported entry name with an invalid value.

3.142.3 Resolution

On the identified UIM page, where an element is defined with a `WINDOW_OPTIONS` attribute, ensure that all entries in the attribute are of the format `name=value`, and that the format of the value is correct.

Current supported options are

width

The width of the dialog window in pixels. Type is NUMERIC.

height

The height of the dialog window in pixels. Type is NUMERIC.

An example of a correct WINDOW_OPTIONS value is width=500,height=600

3.143 -120507 ERR_INVALID_WINDOW_OPTION_CHARACTER

3.143.1 Message

A WINDOW_OPTIONS attribute value on a '*%1s*' element contains an invalid character '*%2s*'

Message placeholders:

%1s

The element that contains invalid attribute value.

%2s

The erroneous character used.

3.143.2 Description

A WINDOW_OPTIONS attribute value contains an invalid character.

3.143.3 Resolution

On the identified UIM page, where an element is defined with a WINDOW_OPTIONS attribute, ensure that all entries in the attribute are of the format name=value, and that the format of the value is correct. No single or double quotes should be used in the WINDOW_OPTIONS attribute.

An example of a correct WINDOW_OPTIONS value is width=500,height=600

3.144 -120508 ERR_PROPERTY_NAME_TOO_LONG

3.144.1 Message

The length of a UIM property name is *%1s* characters while the maximum allowed length is *%2s*. The offending property name is '*%3s*'.

Message placeholders:

%1s

The actual length of the property name in characters.

%2s

The maximum allowed length of the property name in characters.

%3s

Name of the offending property.

3.144.2 Description

The UIM property name length must not exceed the allowed limit.

3.144.3 Resolution

Reduce the length of the identified UIM property name and rebuild.

3.145 -120509

ERR_SI_ACTID_PROP_ONLY_ON_ACTION

3.145.1 Message

Wrong server type for the ACTION_ID_PROPERTY attribute.

3.145.2 Description

The ACTION_ID_PROPERTY attribute is only valid on server interfaces of PHASE=ACTION.

3.145.3 Resolution

Make sure that only server interfaces of PHASE=ACTION have the ACTION_ID_PROPERTY attribute.

3.146 -120510

ERR_SI_NOT_ALL_ACTID_PROPS_SPECIFIED

3.146.1 Message

Missing ACTION_ID_PROPERTY attribute on some server interfaces within the page.

3.146.2 Description

The ACTION_ID_PROPERTY attribute must be either specified on all server interfaces within the page or not specified on any of them.

3.146.3 Resolution

Specify the ACTION_ID_PROPERTY attribute on all server interfaces of PHASE=ACTION within the page.

3.147 -120511 ERR_ACTCTL_NOT_ALL_IDS_SPECIFIED

3.147.1 Message

Missing ACTION_ID attribute on some action controls within the page.

3.147.2 Description

The ACTION_ID attribute must be either specified on all action controls within the page or not specified on any of them.

3.147.3 Resolution

Specify the ACTION_ID attribute on all action controls of TYPE=SUBMIT within the page.

3.148 -120512 ERR_SI_ACTCTL_IDS_NOT_SPECIFIED

3.148.1 Message

Missing ACTION_ID attribute on action controls within the page.

3.148.2 Description

If the ACTION_ID_PROPERTY attribute is specified, then ACTION_ID must be specified for all action controls within the page.

3.148.3 Resolution

Add the ACTION_ID attribute to all action controls of TYPE=SUBMIT within the page.

3.149 -120513 ERR_ACTCTL_SI_ACTID_PROPS_NOT_SPECIFIED

3.149.1 Message

Missing ACTION_ID_PROPERTY attribute on server interfaces within the page.

3.149.2 Description

If the `ACTION_ID` attribute is specified on `ACTION_CONTROL` then the `ACTION_ID_PROPERTY` attribute on `SERVER_INTERFACE` must also be specified.

3.149.3 Resolution

Specify the `ACTION_ID_PROPERTY` attribute on `SERVER_INTERFACE` elements in the page.

3.150 -120514 ERR_ACTCTL_WRONG_TYPE_FOR_ACTID

3.150.1 Message

Wrong action control type for the `ACTION_ID` attribute.

3.150.2 Description

The `ACTION_ID` attribute is only valid on action controls of `TYPE=SUBMIT`.

3.150.3 Resolution

Make sure that only action controls of `TYPE=SUBMIT` have the `ACTION_ID` attribute.

3.151 -120515 ERR_ACTCTL_ACTID_NOT_UNIQUE

3.151.1 Message

Duplicate value of the `ACTION_ID` attribute.

3.151.2 Description

The value of the `ACTION_ID` attribute must be unique within the page.

3.151.3 Resolution

Change the values of the `ACTION_ID` attributes within the page so that there are no duplicates.

3.152 -120520 ERR_INVALID_CONFIRMED_WIDGET

3.152.1 Message

ERROR: Only WIDGET of type MULTISELECT is allowed to have HAS_CONFIRM_PAGE attribute set to "true".

3.152.2 Description

A WIDGET element exists on a a PAGE element with the attribute HAS_CONFIRM_PAGE set to true which means a confirmation page is required for this widget. Confirmation pages are only supported for WIDGET's of TYPE of MULTISELECT, so the WIDGET in question is of different TYPE.

3.152.3 Resolution

Ensure that only WIDGET elements of TYPE of MULTISELECT have HAS_CONFIRM_PAGE attribute set to true.

3.153 -120521 ERR_CONFIRMED_WIDGET_WRONG_CONTEXT

3.153.1 Message

ERROR: WIDGET of type MULTISELECT is only allowed to source its contents from action phase bean when in a search page.

3.153.2 Description

A WIDGET element of TYPE of MULTISELECT exists on a PAGE and has its MULTI_SELECT_SOURCE parameter connection SOURCE's bound to an action phase bean. This type of connection for a MULTISELECT widget is only allowed on search pages, so there should be a submitting ACTION_CONTROL on the page with it's LINK_PAGE_ID attribute set to THIS.

3.153.3 Resolution

Ensure that either MULTISELECT WIDGET sourced from action phase bean is on search page, or, alternatively, set SOURCE connections in its MULTI_SELECT_SOURCE parameter to use a display phase bean instead.

3.154 -120522 ERR_CONNECT_INCOMPATIBLE_PAGE

3.154.1 Message

A page connection to a server interface has incompatible list and single properties.

3.154.2 Description

A `CONNECT` element nested directly with a page has a nested `SOURCE` element which returns a list property and a nested `TARGET` element which returns a single property or the nested `SOURCE` element returns a single property but the `TARGET` element returns a list property.

3.154.3 Resolution

Update either the `SOURCE` element or the `TARGET` element so that they both return either a single property or list property.

3.155 -120523 ERR_AJAX_UNEXPECTED_ELEMENT

3.155.1 Message

For Ajax, a `PAGE` element can only contain `SERVER_INTERFACE`, `PAGE_PARAMETER`, `CONNECT` or `FIELD` child elements.

3.155.2 Description

An Ajax UIM has been created with invalid elements. Only `SERVER_INTERFACE`, `PAGE_PARAMETER`, `CONNECT` or `FIELD` elements are allowed to be children of the `PAGE` element.

3.155.3 Resolution

On the identified UIM page, ensure that the `PAGE` element has only the following child elements, `SERVER_INTERFACE`, `PAGE_PARAMETER`, `CONNECT`, `FIELD`.

3.156 -120524 ERR_AJAX_SERVER_INTF

3.156.1 Message

For Ajax, a UIM must contain one, and only one, `DISPLAY` phase `SERVER-`

ER_INTERFACE

3.156.2 Description

An Ajax UIM has been created with invalid elements. One, and only one, DISPLAY phase SERVER_INTERFACE must be present.

3.156.3 Resolution

On the identified UIM page, ensure that there is one, and only one, DISPLAY phase SERVER_INTERFACE element.

Notices

This information was developed for products and services offered in the U.S.A. IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service. IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing

IBM Corporation

North Castle Drive

Armonk, NY 10504-1785

U.S.A.

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

Intellectual Property Licensing

Legal and Intellectual Property Law.

IBM Japan Ltd.

1623-14, Shimotsuruma, Yamato-shi

Kanagawa 242-8502 Japan

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law: INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typograph-

ical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you. Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Corporation
Dept F6, Bldg 1
294 Route 100
Somers NY 10589-3216
U.S.A.

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources.

IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products

should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only

All IBM prices shown are IBM's suggested retail prices, are current and are subject to change without notice. Dealer prices may vary.

This information is for planning purposes only. The information herein is subject to change before the products described become available.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

Each copy or any portion of these sample programs or any derivative work, must include a copyright notice as follows:

© (your company name) (year). Portions of this code are derived from IBM Corp. Sample Programs.

© Copyright IBM Corp. _enter the year or years_. All rights reserved.

If you are viewing this information softcopy, the photographs and color illustrations may not appear.

Programming Interface Information

This publication documents intended programming interfaces that allow the customer to write programs to obtain the services of IBM Cúram Social Program Management.

Trademarks

IBM, the IBM logo, and [ibm.com](http://www.ibm.com) are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at <http://www.ibm.com/legal/us/en/copytrade.shtml>.

Microsoft, Word, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

UNIX is a registered trademark of the Open Group in the United States and other countries.

Java and all Java-based trademarks and logos are registered trademarks of Oracle and/or its affiliates.

Red Hat Enterprise Linux is a registered trademark of Red Hat, Inc. in the United States and other countries.

Other names may be trademarks of their respective owners. Other company, product, and service names may be trademarks or service marks of others.