

IBM Tivoli Composite Application Manager for WebSphere V6.0

Readme for the update installer V6.0.0.2

February 27, 2006

CONTENTS

1	ABSTRACT	2
2	CHANGE HISTORY	2
3	INSTALLING UPDATES	3
3.1	UNPACKING UPDATE	3
3.2	UNPACKING THE UPDATE INSTALLER	3
3.3	PREPARING ENVIRONMENT	3
3.4	UPDATING THE RESPONSE FILE	4
3.5	PREPARING INSTALLATION	4
3.6	CLEANING PREPARED INSTALLATION	5
3.7	INSTALLING	6
3.8	ROLLING BACK FAILED INSTALLATION	6
4	UNINSTALLING UPDATES	7
4.1	UNPACKING THE UPDATE INSTALLER	7
4.2	PREPARING ENVIRONMENT	8
4.3	UPDATING THE RESPONSE FILE	8
4.4	PREPARING UNINSTALLATION.....	8
4.5	CLEANING PREPARED UNINSTALLATION	9
4.6	UNINSTALLING	10
4.7	ROLLING BACK FAILED UNINSTALLATION.....	11
5	DISPLAYING INSTALLED UPDATES	11
5.1	UNPACKING THE UPDATE INSTALLER	12
5.2	PREPARING ENVIRONMENT	12
5.3	UPDATING THE RESPONSE FILE	12
5.4	DISPLAYING INSTALLED UPDATES	12

1 Abstract

The Update Installer for IBM Tivoli Composite Application Manager for WebSphere V6.0 provides the following functionality:

- A silent command-line update installer.
- Installation and removal of individual or multiple updates (Fix Packs and interim fixes).
- Logging, tracking and prerequisites handling.

This readme describes how to use the update installer.

2 Change History

6.0.0.2 February 27, 2006

- Added new command-line options: -displayInstalledUpdates, -cleanPrepared, -rollback.
- Bug fixes

6.0.0.1 December 14, 2005

- First release.

3 Installing Updates

This section describes how to install Fix Packs and interim fixes.

3.1 Unpacking Update

The Fix Packs and interim fixes are distributed as tar files. Create a temporary directory, put the update package there and un-tar.

After un-taring the update package you should get the updates directory that contains the file with the *.update extension. For example:

```
>tar xvf 6.0.0.1-TIV-ITCAMfWAS_MP-IF0002.tar  
  
6.0.0.1-TIV-ITCAMfWAS_MP-IF0002.README  
updates/  
updates/6.0.0.1-TIV-ITCAMfWAS_MP-IF0002.update
```

3.2 Unpacking the Update Installer

Copy the update installer tar to the same directory were you un-tared the update package. This directory will typically contain the **updates** subdirectory. Un-tar the update installer package using the tar command, for example:

```
>tar xvf ITCAMfWAS_V6_UpdateInstaller.tar  
  
silentUpdate.bat  
silentUpdate.properties  
silentUpdate.sh  
update.jar
```

The resulting directory structure will contain both, the update installer and the update file. For example:

```
silentUpdate.bat  
silentUpdate.properties  
silentUpdate.sh  
update.jar  
6.0.0.1-TIV-ITCAMfWAS_MP-IF0002.README  
updates/6.0.0.1-TIV-ITCAMfWAS_MP-IF0002.update
```

3.3 Preparing Environment

Before running the update installer you should login as root (Administrator) or owner of the product directory. Then update the environment as below.

The update installer requires the Java Runtime Environment version 1.3.1 or higher. Either include the java command into PATH or define the JAVA_HOME environment variable to point to the Java Runtime Environment home directory.

For example, on UNIX or Linux, run:

```
JAVA_HOME=/opt/WebSphere/AppServer/java  
export JAVA_HOME
```

3.4 Updating the Response File

The update installer is a non-interactive silent installer that works based on the response file. The default name of the response file is silentUpdate.properties and it is supplied with the update installer. Update the response file as follows:

- Set the **product.location** property with the correct product location directory
- Optionally, if the *.update files are not in default ./updates directory, then set the **updates.loction** property with the directory that contains the *.update files.
- If the Visual Engine was not installed to the Managing Server runtime to be updated then set the **updateVe** property to false. Otherwise uncomment and set the **updateVe.wasHome** property with WAS_HOME of the Visual Engine application server.

Note: the response file is Java Properties file. Any backward-slashes should be doubled, for example:

```
product.location=C:\\Program Files\\IBM\\WSAM
```

3.5 Preparing Installation

To reduce the application server or Managing Server down-time the update installer allows to prepare installation while the product is running. This steps is optional but is recommended.

In order to prepare installation change to the directory where the update installer scripts are stored and run the following command:

Windows:

```
silentUpdate.bat -prepareInstall
```

UNIX or Linux:

```
./silentUpdate.sh -prepareInstall
```

If your response file is named differently then the default silentUpdate.properties then specify it as a parameter:

Windows:

```
silentUpdate.bat -prepareInstall my.properties
```

UNIX or Linux:

```
./silentUpdate.sh -prepareInstall my.properties
```

A typical output of the -prepareInstall command is:

```
>/silentUpdate.sh -prepareInstall  
Update installer version 6.0.0.2  
Logging details into  
/opt/IBM/itcam/WebSphere/MS/logs/update/update_20050916213723.log  
Action: prepare install  
Finished successfully
```

3.6 Cleaning Prepared Installation

If you decide to not install the update after you already run -prepareInstall then you can clean results of the '-prepareInstall' command. In order to do that change to the directory where the update installer scripts are stored and run the following command:

Windows:

```
silentUpdate.bat –cleanPrepared
```

UNIX or Linux:

```
./silentUpdate.sh –cleanPrepared
```

If your response file is named differently then the default silentUpdate.properties then specify it as a parameter:

Windows:

```
silentUpdate.bat -cleanPrepared my.properties
```

UNIX or Linux:

```
./silentUpdate.sh -cleanPrepared my.properties
```

A typical output of the -cleanPrepared command is:

```
>/silentUpdate.sh -cleanPrepared  
Update installer version 6.0.0.2  
Logging details into  
/opt/IBM/itcam/WebSphere/MS/logs/update/update_20050916213723.log
```

```
Action: clean prepared  
Finished successfully
```

3.7 Installing

It is recommended that you run the -prepareInstall command before installing the update, see the previous section for details.

Before installing the update you should stop the product that you will update, i.e. the application server being monitored or the Managing Server components.

After you stopped the product change to the directory where the update installer scripts are stored and run the following command.

Windows:

```
silentUpdate.bat –install
```

UNIX or Linux:

```
./silentUpdate.sh -install
```

If your response file is named differently then the default silentUpdate.properties then specify it as a parameter:

Windows:

```
silentUpdate.bat -install my.properties
```

UNIX or Linux:

```
./silentUpdate.sh -install my.properties
```

A typical output of the -install command is:

```
>/silentUpdate.sh -install  
Update installer version 6.0.0.2  
Logging details into /opt/IBM/itcam/WebSphere/logs/update/update_20050916213723.log  
Action: install  
Finished successfully
```

3.8 Rolling Back Failed Installation

If the -install command fails and the automatic rollback fails also then the runtime will be locked for the updates until the rollback is completed successfully. In order to complete the rollback successfully do the following:

- Review the update installer log and resolve the cause of the rollback failure.

- Change to the directory where the update installer scripts are stored and run the following command:

Windows:

```
silentUpdate.bat –rollback
```

UNIX or Linux:

```
./silentUpdate.sh –rollback
```

If your response file is named differently then the default silentUpdate.properties then specify it as a parameter:

Windows:

```
silentUpdate.bat -rollback my.properties
```

UNIX or Linux:

```
./silentUpdate.sh -rollback my.properties
```

A typical output of the -rollback command is:

```
>./silentUpdate.sh -rollback
Update installer version 6.0.0.2
Logging details into
/opt/IBM/itcam/WebSphere/MS/logs/update/update_20050916213723.log
Action: rollback
Finished successfully
```

4 Uninstalling Updates

This section describes how to uninstall Fix Packs and interim fixes.

4.1 *Unpacking the Update Installer*

The all necessary uninstall information is stored to the product directory under the **update** sub-directory. You don't need the original update package in order to uninstall it. So download the latest update installer and un-tar it:

```
>tar xvf ITCAMfWAS_V6_UpdateInstaller.tar
```

```
silentUpdate.bat
silentUpdate.properties
silentUpdate.sh
update.jar
```

4.2 Preparing Environment

Before running the update installer you should login as root (Administrator) or owner of the product directory. Then update the environment as below.

The update installer requires the Java Runtime Environment version 1.3.1 or higher. Either include the java command into PATH or define the JAVA_HOME environment variable to point to the Java Runtime Environment home directory.

For example, on UNIX or Linux, run:

```
JAVA_HOME=/opt/WebSphere/AppServer/java  
export JAVA_HOME
```

4.3 Updating the Response File

The update installer is non-interactive silent installer that works based on the response file. The default name of the response file is silentUpdate.properties and it is supplied with the update installer. Update the response file as follows:

- Set the **product.location** property with the correct product location directory.
- Optionally, if the *.update files are not in default ./updates directory, then set the **updates.location** property with the directory that contains the *.update files.
- If the Visual Engine was not installed to the Managing Server runtime to be updated then set the **updateVe** property to false. Otherwise uncomment and set the **updateVe.wasHome** property with WAS_HOME of the Visual Engine application server.
- Set the **uninstall.updates** property with the one of possible values:
 - **all** – uninstall all updates
 - **last** – uninstall the updates installed by the last -install command
 - **<comma separated list of updates>** -- uninstall the specified updates. The updates are specified by their identifiers as displayed by the –listInstalledUpdates command. (f.e. 6.0.0.1, 6.0.0.1.1)

Note: the response file is Java Properties file. Any backward-slashes should be doubled, for example:

```
product.location=C:\\Program Files\\IBM\\WSAM
```

4.4 Preparing Uninstallation

To reduce the application server or Managing Server down-time the update installer allows to prepare uninstallation while the product is running. This steps is optional but is recommended.

In order to prepare uninstallation change to the directory where the update installer scripts are stored and run the following command:

Windows:

```
silentUpdate.bat –prepareUninstall
```

UNIX or Linux:

```
./silentUpdate.sh -prepareUninstall
```

If your response file is named differently then the default silentUpdate.properties then specify it as a parameter:

Windows:

```
silentUpdate.bat -prepareUninstall my.properties
```

UNIX or Linux:

```
./silentUpdate.sh -prepareUninstall my.properties
```

A typical output of the -prepareUninstall command is:

```
>./silentUpdate.sh -prepareUninstall  
Update installer version 6.0.0.2  
Logging details into  
/opt/IBM/itcam/WebSphere/MS/logs/update/update_20050916213723.log  
Action: prepare uninstall  
Finished successfully
```

4.5 Cleaning Prepared Uninstallation

If you decide to not uninstall after you already run -prepareUninstall then you can clean results of the ‘-prepareUninstall’ command. In order to do that change to the directory where the update installer scripts are stored and run the following command:

Windows:

```
silentUpdate.bat –cleanPrepared
```

UNIX or Linux:

```
./silentUpdate.sh –cleanPrepared
```

If your response file is named differently then the default silentUpdate.properties then specify it as a parameter:

Windows:

```
silentUpdate.bat -cleanPrepared my.properties
```

UNIX or Linux:

```
./silentUpdate.sh -cleanPrepared my.properties
```

A typical output of the -cleanPrepared command is:

```
>/silentUpdate.sh -cleanPrepared  
Update installer version 6.0.0.2  
Logging details into  
/opt/IBM/itcam/WebSphere/MS/logs/update/update_20050916213723.log  
Action: clean prepared  
Finished successfully
```

4.6 Uninstalling

It is recommended that you run the -prepareUninstall command before uninstalling the update, see the previous section for details.

Before uninstalling the update you should stop the product that you will update, i.e. the application server being monitored or the Managing Server components.

After you stopped the product change to the directory where the update installer scripts are stored and run the following command:

Windows:

```
silentUpdate.bat –uninstall
```

UNIX or Linux:

```
./silentUpdate.sh -uninstall
```

If your response file is named differently then the default silentUpdate.properties then specify it as a parameter:

Windows:

```
silentUpdate.bat -uninstall my.properties
```

UNIX or Linux:

```
./silentUpdate.sh -uninstall my.properties
```

A typical output of the -uninstall command is:

```
>/silentUpdate.sh -uninstall  
Update installer version 6.0.0.2  
Logging details into  
/opt/IBM/itcam/WebSphere/MS/logs/update/update_20050916213723.log  
Action: uninstall  
Finished successfully
```

4.7 Rolling Back Failed Uninstallation

If the -uninstall command fails and the automatic rollback fails also then the runtime will be locked for the updates until the rollback is completed successfully. In order to complete the rollback successfully do the following:

- Review the update installer log and resolve the cause of the rollback failure.
- Change to the directory where the update installer scripts are stored and run the following command:

Windows:

```
silentUpdate.bat –rollback
```

UNIX or Linux:

```
./silentUpdate.sh –rollback
```

If your response file is named differently then the default silentUpdate.properties then specify it as a parameter:

Windows:

```
silentUpdate.bat -rollback my.properties
```

UNIX or Linux:

```
./silentUpdate.sh -rollback my.properties
```

A typical output of the -rollback command is:

```
>/silentUpdate.sh -rollback  
Update installer version 6.0.0.2  
Logging details into  
/opt/IBM/itcam/WebSphere/MS/logs/update/update_20050916213723.log  
Action: rollback  
Finished successfully
```

5 Displaying Installed Updates

This section describes how to display a list of the installed Fix Packs and interim fixes.

5.1 Unpacking the Update Installer

Download the latest update installer and un-tar it:

```
>tar xvf ITCAMfWAS_V6_UpdateInstaller.tar
```

```
silentUpdate.bat  
silentUpdate.properties  
silentUpdate.sh  
update.jar
```

5.2 Preparing Environment

Before running the update installer you should login as root (Administrator) or owner of the product directory. Then update the environment as below.

The update installer requires the Java Runtime Environment version 1.3.1 or higher. Either include the java command into PATH or define the JAVA_HOME environment variable to point to the Java Runtime Environment home directory.

For example, on UNIX or Linux, run:

```
JAVA_HOME=/opt/WebSphere/AppServer/java  
export JAVA_HOME
```

5.3 Updating the Response File

The update installer is non-interactive silent installer that works based on the response file. The default name of the response file is silentUpdate.properties and it is supplied with the update installer. Update the response file as follows:

- Set the **product.location** property with the correct product location directory

Note: the response file is Java Properties file. Any backward-slashes should be doubled, for example:

```
product.location=C:\\Program Files\\IBM\\WSAM
```

5.4 Displaying Installed Updates

To display a list of the installed Fix Packs and interim fixes change to the directory where the update installer scripts are stored and run the following command:

Windows:

```
silentUpdate.bat –displayInstalledUpdates
```

UNIX or Linux:

```
./silentUpdate.sh -displayInstalledUpdates
```

If your response file is named differently then the default silentUpdate.properties then specify it as a parameter:

Windows:

```
silentUpdate.bat -displayInstalledUpdates my.properties
```

UNIX or Linux:

```
./silentUpdate.sh -displayInstalledUpdates my.properties
```

A typical output of the - displayInstalledUpdates command is:

```
>./silentUpdate.sh - displayInstalledUpdates
Update installer version 6.0.0.2
Logging details into
/opt/IBM/itcam/WebSphere/DC/logs/update/update_20060121163339.log
Action: display installed updates
Updates installed 21.02.06 16:43
    6.0.0.1
Finished successfully
```