



**Installation Guide
for i5/OS**



**Installation Guide
for i5/OS**

Note:

Before using this information and the product it supports, be sure to read the general information under “Notices” on page 33.

Edition Notice

This edition of this book applies to version 6.0.0.2 of the following editions of WebSphere Commerce and to all subsequent releases and modifications until otherwise indicated in new editions:

- IBM WebSphere Commerce Enterprise (5724-i38)
- IBM WebSphere Commerce Professional (5724-i40)
- IBM WebSphere Commerce - Express (5724-i36)

Make sure you are using the correct edition for the level of the product.

Order publications through your IBM representative or the IBM branch office serving your locality.

IBM welcomes your comments. You can send your comments by using the online WebSphere Commerce reader comment form.

When you send information to IBM, you grant IBM a nonexclusive right to use or distribute the information in any way it believes appropriate without incurring any obligation to you.

© Copyright International Business Machines Corporation 1996, 2007. All rights reserved.

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

Preface	v	Troubleshooting general WebSphere Commerce fix pack issues	17
About this book	v	Two extra columns in the WebSphere Commerce 6.0 database are migrated from previous releases	17
Update history	v	Error message when accessing WebSphere Commerce tools	17
Conventions used in this book	v	Error message when applying a fix pack using the WebSphere Commerce Update Installer version 6.1.0.4	17
Path variables	v	Unable to find the fix pack log file	18
Other variables used in this book	vi	WebSphere Commerce pages are not accessible after applying the fix pack	18
		Accessing backup files.	18
Product editions	1	Troubleshooting the install and uninstall of the WebSphere Commerce fix pack on your installation directory	18
WebSphere Commerce editions supported by this fix pack	1	Error encountered when completing a silent installation	18
		The installer is unable to update a .jar file on the system	19
		Error encountered when attempting silent uninstall of fix pack	19
		Errors encountered when uninstalling the WebSphere Commerce fix pack.	20
Prerequisites	3	Troubleshooting the install and uninstall of the WebSphere Commerce fix pack on your instance	20
Master technote	3	Error encountered when applying the fix pack on a machine that has WebSphere Application Server 6.0.2.5 or higher installed	20
Apply the required maintenance.	3	The fix pack failed to update the WebSphere Commerce instance during install or uninstall	20
Additional maintenance required when using dynamic caching	3	The updatedb script fails during the application of the fix pack	22
iSeries Program Temporary Fixes (PTFs)	3	Error encountered when completing a silent installation	22
		The installer is unable to update a .jar file on the system	23
		Error encountered when attempting silent uninstall of fix pack	23
		Exceptions are logged in the createInstanceANT.err.log and createInstanceANT.log files	23
Installing the fix pack	5		
Before applying the fix pack	5	Appendix B. WebSphere Commerce updates	25
Fix pack installation overview	5		
Backing up the profile file	7	Notices	33
Installing new components	7	Trademarks	34
Preparing the system to run the fix pack installer	7		
Next step	7		
Silent installation	7		
Updating the WebSphere Commerce installation directory.	8		
Updating the WebSphere Commerce or WebSphere Commerce Payments instance	9		
Post installation steps	10		
Updating the WebSphere Commerce database manually	10		
Remote Web server tasks	11		
Determining the APARs that are installed on your machine.	11		
Precompiling JSP files	11		
Uninstalling the fix pack	13		
Next step	13		
Silent uninstallation	13		
Removing the fix pack from the WebSphere Commerce or WebSphere Commerce Payments instance	14		
Removing the fix pack from the WebSphere Commerce installation directory	14		
Appendix A. Troubleshooting	17		

Preface

About this book

This document describes the steps required to apply the IBM® WebSphere® Commerce 6.0.0.2 fix pack to version 6.0 of the following editions of WebSphere Commerce:

- IBM WebSphere Commerce Enterprise
- IBM WebSphere Commerce Professional
- IBM WebSphere Commerce - Express

Note: The IBM WebSphere Commerce 6.0.0.2 fix pack cannot be applied to IBM WebSphere Commerce Developer.

Update history

This section provides an outline of the history of changes to this book:


Edition	Updates
First edition	• Original publication of this document

Conventions used in this book

This book uses the following highlighting conventions:

- **Boldface type** indicates commands or graphical user interface (GUI) controls such as names of fields, icons, or menu choices.
- Monospace type indicates examples of text you type exactly as shown, file names, and directory paths and names.
- *Italic type* is used to emphasize words. Italics also indicate names for which you must substitute the appropriate values for your system.

 Enterprise Indicates information that is specific to WebSphere Commerce Enterprise

 Professional Indicates information that is specific to WebSphere Commerce Professional.

 Express Indicates information that is specific to WebSphere Commerce – Express.

 i5 Indicates information that is specific to WebSphere Commerce for i5/OS® for iSeries®.

Path variables

HTTPServer_installdir

The installation path for the IBM HTTP Server. The default installation directory is:

WAS_installdir

The installation path for WebSphere Application Server version. The default installation directory is:

`/QIBM/ProdData/WebSphere/AppServer/V6/edition/`

WAS_userdir

The directory for all the data that is used by WebSphere Application Server that can be modified or needs to be configured by the user:

`/QIBM/UserData/WebSphere/AppServer/V6/edition/`

WC_installdir

The installation path for WebSphere Commerce. The default installation directory is:

`/QIBM/ProdData/CommerceServer60`

WC_userdir

The directory for all the data that is used by WebSphere Commerce which can be modified or needs to be configured by the user:

`/QIBM/UserData/CommerceServer60`

WC_profiledir

The directory for the WebSphere Application Server profile that is used by a WebSphere Commerce instance. For example:

`WAS_userdir/profiles/profile_name/`

UPDI_installdir

The installation path for the WebSphere Commerce Update Installer. For example:

`/QIBM/ProdData/WebSphere/UpdateInstaller/V61/UPDI`

Other variables used in this book

cell_name

This variable represents the name of the WebSphere Application Server cell.

host_name

This variable represents the fully qualified host name of your WebSphere Commerce server (for example, server.mydomain.ibm.com is fully qualified).

instance_name

This variable represents the name of the WebSphere Commerce instance with which you are working (for example, demo).

payments_instance_name

This variable represents the name of the WebSphere Commerce Payments instance with which you are working.

profile_name

This variable represents the name of the WebSphere Application Server profile that is created for your WebSphere Commerce instance. This variable has the same name as your WebSphere Commerce instance.

Product editions

WebSphere Commerce editions supported by this fix pack

This fix pack supports WebSphere Commerce Enterprise, Version 6.0 on the following operating systems:

- AIX®
- i5/OS
- Linux® for iSeries
- Linux for pSeries®
- Linux for xSeries®
- Linux for zSeries®
- Solaris
- Windows® 2000 and Windows 2003

This fix pack supports WebSphere Commerce Professional, Version 6.0 on the following operating systems:

- AIX
- i5/OS
- Linux for xSeries
- Solaris
- Windows 2000 and Windows 2003

This fix pack supports WebSphere Commerce Express, Version 6.0 on the following operating systems:

- i5/OS
- Linux for xSeries
- Windows 2000 and Windows 2003

For the specific requirements on each of the supported operating systems, refer to the WebSphere Commerce detailed system requirements technote #1224147 page.

Prerequisites

Review this chapter and complete any of the following sections that are applicable to your WebSphere Commerce installation.

Master technote

The master technote summarizes the known fix pack issues, and which version of the fix packs they apply to. It provides information on how to sign up for automatic notification of new fix packs and flashes. Refer to the WebSphere Commerce V6.0 fix pack master installation technote for more information.

Apply the required maintenance

Complete the following steps:

- You must apply the latest WC-file-permission iFix as listed on the WC-file-permission iFix page.
- (optional) Apply the PK13460: Disk Cache Enhancements fix.

Additional maintenance required when using dynamic caching

If you are using WebSphere Application Server Version 6.0.2.9 or higher, and have dynamic caching enabled, you must complete the steps found in the NotSerializableException thrown when using dynacache with WebSphere Commerce technote.

iSeries Program Temporary Fixes (PTFs)

Ensure the required Program Temporary Fixes (PTFs) have been applied to the WebSphere Commerce system. Refer to PTF Tables by version for WebSphere Commerce technote #1239904.

Before applying any PTFs, view the PTF cover letters for any additional instructions.

Installing the fix pack

Before applying the fix pack

Important:

- If you are operating a clustered environment, apply all of the fix pack changes from the machine where you have created your WebSphere Commerce instances.
- Stop the WebSphere Commerce Information Center before applying the fix pack.
- Backup the WebSphere Commerce instance application and database before you apply the fix pack. The database updates included in this fix pack can not be undone. If you want to undo the database update after applying the WebSphere Commerce fix pack, you must restore your database backup. Refer to your database documentation for information on backing up your database. To backup the Commerce application, refer to the WebSphere Application Server Information Center documentation on backing up applications.

- Check the `WC_profiledir/logs/server1/SystemOut.log` to ensure that the database version is at the same level as the EAR version. Fix packs always update the database version number. If the versions are not the same errors can occur. For example, search for a message similar to:

```
0000000a SystemOut 0 WC.SERVER: Enterprise 6.0.0.0 / Database: ENT 6.0.0.0
```

The “Enterprise 6.0.0.0” is the EAR version, the “Database: ENT 6.0.0.0” is the Database version. The EAR version is retrieved from the `WC_profiledir/installedApps/cell_name/WC_instance_name.ear/properties/version/COMMERCE.product`. The Database version is retrieved from the SITE table.

- Make sure that the WebSphere Commerce Configuration Manager server is stopped before applying the fix pack.
- Disable your firewall, or allow access to the WebSphere Application Server administrative server. If you have installed a firewall on your machine, it can interfere with the application of the fix pack.
- Ensure that WebSphere Commerce and WebSphere Commerce Developer are at the same fix pack level.

Fix pack installation overview

The WebSphere Commerce fix pack is installed using the WebSphere Commerce Update Installer. The Update Installer is a tool that is used to apply maintenance to WebSphere Commerce and WebSphere Commerce Payments instances.

Notes:

1. During the application of maintenance to the WebSphere Commerce instance, the Update Installer stops the WebSphere Commerce application automatically.
2. If WebSphere Commerce is configured in a clustered environment, the WebSphere Commerce Update Installer stops the WebSphere Commerce enterprise application for the selected WebSphere Commerce instance on all servers that are running that application.

3. Updating the WebSphere Commerce instance can take 40 minutes or more depending on the size of your application and the speed of your system.

To minimize downtime, you should apply the fix pack to your configuration at a time that will least impact the operation of your business. If you have customized your WebSphere Commerce instance, ensure that you have followed the documented deployment procedure in the WebSphere Commerce Information Center, otherwise your customizations are removed when the fix pack is installed. For more information on customized code, refer to Customized code deployment.

Additionally, you should apply the fix pack to your non-production environment first, to ensure that you do not negatively impact your production environment. Here is an overview of the application process:

1. Install the Update Installer software on your machine.
2. Download the appropriate fix pack.
3. Use the Update Installer to apply the fix pack to your WebSphere Commerce installation directory. New WebSphere Commerce and WebSphere Commerce Payments instances are created at this new fix pack level. Existing WebSphere Commerce and WebSphere Commerce Payments instances are not updated automatically.
4. For each WebSphere Commerce or WebSphere Commerce Payments instance that you have created before applying the fix pack, you must complete the following steps:
 - a. Start your database server.
 - b. Start your management server:
 - If WebSphere Commerce is managed by WebSphere Application Server Deployment Manager (dmgr), start the dmgr server.
 - If WebSphere Commerce is not managed by WebSphere Application Server Deployment Manager (dmgr), start your WebSphere Application Server server1.
 - c. Using the Update Installer, update the WebSphere Commerce or WebSphere Commerce Payments instance. To update the instance you must know the following information:
 - The WebSphere Commerce or WebSphere Commerce Payments instance name
 - If the associated database should be updated
 - d. If you have WebSphere Application Server security enabled for your WebSphere Commerce Payments instance you must know the following information:
 - The global security user ID
 - The global security password
 - e. During the WebSphere Commerce or WebSphere Commerce Payments instance update, the Update Installer stops the WebSphere Commerce application. If the instance is part of a clustered environment, the WebSphere Application Server deployment manager ensures that all nodes in that cluster are updated with the fix pack changes. For the Deployment Manager to distribute the application to all nodes, you must ensure that you have not disabled application distribution. Distribution requires that your node agents are running.
 - f. After the Update Installer has updated the instance, you must restart the WebSphere Commerce application.

- g. To ensure that all of your instances are updated, repeat these steps for each instance that exists on your machine.

If you have installed the WebSphere Commerce remote management utilities on a separate node from your WebSphere Commerce server, ensure that you also install the fix pack on that machine. If you do not install the fix pack on that machine, you are not able to use the WebSphere Commerce Configuration Manager client.

Backing up the profile file

Before applying the fix pack to your machine, you should backup your profile. Refer to Backing up and recovering the application serving environment.

This fix pack overwrites certain JSP files related to the WebSphere Commerce tools pages. Refer to the text file `tools_jsps_changed.txt` available on the WebSphere Commerce Version 6.0.0.2 Download Page technote #4015395 for a list of the JSP files that are overwritten.

If you have customized any of these files then you must reapply your customizations after the fix pack is applied. Before you apply the fix pack, back up any files that you have customized.

Installing new components

If any new components are installed from the WebSphere Commerce base (6.0) CD images the you must reinstall the fix pack in order to upgrade that component to the 6.0.0.2 level. For example, if the Configuration Manager client is loaded on a node using the base CD images the fix pack must be reinstalled to the Configuration Manager client node.

Preparing the system to run the fix pack installer

1. Download and install the WebSphere Commerce Update Installer.
2. Open the WebSphere Commerce Version 6.0.0.2 Download Page technote #4013056.
3. Download the fix pack file `6.0.0-WS-WCServer-FP002.pak` and save it to the *UPDI/maintenance* directory.

Notes:

- a. Ensure that the fix pack maintains the proper file extension. The file must be named `6.0.0-WS-WCServer-FP002.pak`.
- b. It is recommended that no other maintenance files reside in the *UPDI/maintenance* directory.

Next step

Install the fix pack by completing the following section:

- “Silent installation”

Silent installation

Complete this section to silently install the WebSphere Commerce fix pack. If you have already created a WebSphere Commerce or WebSphere Commerce Payments instance, you must apply the fix pack to the WebSphere Commerce product first. After the fix pack is applied to the product, you must then apply it to your instances.

Refer to the following sections:

- “Updating the WebSphere Commerce installation directory.”
- “Updating the WebSphere Commerce or WebSphere Commerce Payments instance” on page 9.

Updating the WebSphere Commerce installation directory

This section updates the WebSphere Commerce product.

1. Ensure that your user has *SECOFR authority.
2. Download the appropriate maintenance from the following Web site to the *UPDI_installdir/maintenance* directory:

WebSphere Commerce 6.0.0.2 Download Page technote #4013056

3. Navigate to the *UPDI_installdir/responsefiles* directory and open the *install.txt* file in a text editor.
4. Edit the *install.txt* file, ensuring the following sections are edited appropriately and are not commented out:

Note: To uncomment a line, remove the “#” character from the beginning of the appropriate entry.

- The `-W maintenance.package` contains the directory name for the fix pack. For example:

```
-W maintenance.package="/QIBM/ProdData/WebSphere/UpdateInstaller/  
V61/UPDI/maintenance"
```

- The `-W product.location` contains the full path name of the WebSphere Commerce installation directory. For example:

```
-W product.location="/QIBM/ProdData/CommerceServer60"
```

Verify that the `-W update.instancename` and `-W update.db` entries do not exist or are commented out. Save the file and exit.

Note: If you have a WebSphere Commerce instance created, you must first update your WebSphere Commerce product. After you have updated the product, you must re-edit the response file, and run the Update installer again.

5. Open the QShell by typing QSH at the i5/OS command prompt.
6. Run the following command from the *UPDI_installdir*:
`update -devkit14 -options UPDI_installdir/responsefiles/install.txt`
7. Refer to the log files in the following directory to verify that your install was successful:

```
WC_installdir/logs/update
```

If problems are encountered during the update process, refer to Appendix A, “Troubleshooting,” on page 17.

If you do not have an existing WebSphere Commerce or WebSphere Commerce Payments instance then the installation of the fix pack is complete.

Updating the WebSphere Commerce or WebSphere Commerce Payments instance

Important:

If you are applying the fix pack to a WebSphere Commerce Payments instance that has WebSphere Application Server global security enabled, you must install interim fix IY90010 before continuing.

Refer to the WebSphere Commerce V6.0 fix pack master installation technote for more information.

This section updates a WebSphere Commerce or WebSphere Commerce Payments instance:

1. Ensure that your user has *SECOFR authority.
2. Ensure your database server is started.
3. Ensure that your WebSphere Commerce administrative server is started. For example:
 - If WebSphere Commerce is managed by WebSphere Application Server Deployment Manager (dmgr), start the server.
 - If WebSphere Commerce is not managed by WebSphere Application Server Deployment Manager (dmgr), start the WebSphere Application Server server1.

Note: During the application of maintenance to the WebSphere Commerce instance, the Update Installer stops the WebSphere Commerce application automatically.

4. Navigate to the *UPDI_installdir/responsefiles* directory and open the *install.txt* file in a text editor.
5. To update a WebSphere Commerce or WebSphere Commerce Payments instance:

Note: If you have an instance created, you must first update your WebSphere Commerce product. After you have update the product, you must re-edit the response file, and run the Update installer again.

- a. Update the `-W maintenance.package` entry with the directory name that contains the maintenance package.
- b. Update the `-W product.location` with the location of the WebSphere Commerce install.
- c. Complete one of the following steps if you are updating an instance:
 - If you are updating a WebSphere Commerce instance, add the following lines to the end of the *install.txt* file:

```
-W update.instancename="instance_name"  
-W update.db="true"
```

Note: If you set `-W update.db="false"` you must update the database manually. Refer to "Updating the WebSphere Commerce database manually" on page 10.

- If you do not have WebSphere Application Server security enabled with your WebSphere Commerce Payments instance, add the following lines to the end of the *install.txt* file:

```
-W update.instancename="payments_instance_name"  
-W update.db="true"
```

Note: If you set `-W update.db="false"` you must update the database manually. Refer to “Updating the WebSphere Commerce database manually.”

- If you have WebSphere Application Server security enabled with your WebSphere Commerce Payments instance, add the following lines to the end of the `install.txt` file:

```
-W update.instancename="payments_instance_name"  
-W update.db="true"  
-W update.wassecurityenable="true"  
-W update.wasuserid="WAS_user"  
-W update.wasuserpassword="WAS_password"
```

Note: If you set `-W update.db="false"` you must update the database manually. Refer to “Updating the WebSphere Commerce database manually.”

6. Open the QShell by typing `QSH` at the `i5/OS` command prompt.
7. Run the following command from the `UPDI_installdir`:

```
update -devkit14 -options UPDI_installdir/responsefiles/install.txt
```
8. Refer to the log files in the following directory to verify that your install was successful:

```
WC_installdir/logs/update
```
9. Complete the following steps based on the type of instances you have configured on your machine:
 - If you have a WebSphere Commerce instance created, restart the WebSphere Commerce application from within the administrative console.
 - If you have a WebSphere Commerce Payments instance created, restart the WebSphere Commerce Payments application from within the administrative console. If your WebSphere Commerce Payments instance has security enabled:
 - a. Navigate to the `WC_installdir/payments/bin` directory.
 - b. Run the following command:

```
IBMPayServer payments_instance_name payment_password
```

- Note:** If you have additional instances created, you can update them by updating the response file, and repeating the following section:
- “Updating the WebSphere Commerce or WebSphere Commerce Payments instance” on page 9.

Post installation steps

Important:

Refer to Appendix B, “WebSphere Commerce updates,” on page 25 for information on the APARs that are included in this fix pack. If you have installed APARs that are not included in this fix pack you must reinstall them after the fix pack is installed.

Updating the WebSphere Commerce database manually

If you did not choose to update your database automatically during the application of the WebSphere Commerce fix pack, you must manually update your database.

On the machine where you have applied the fix pack, complete the steps in this section to manually update your database:

Note: Ensure that you have backed up your database.

1. From a command prompt launch the following command:

```
WC_installdir/bin/updatedb.sh instance_name
```

Where *instance_name* is the name of the instance to be updated.

2. When the update is complete, review the output displayed in the console window and ensure that you have successfully updated the database to the correct fix pack level. For example:

```
UpdateSiteTable:
[EchoNL] Updating database fixpack level ...
[eCDatabaseVersionInfo] UPDATE SITE SET EDITION='ENT', VERSION=6,
RELEASE=0, MOD=0, FIXPACK=2 WHERE COMPNAME='BASE'
[eCDatabaseVersionInfo] SELECT COUNT(*) FROM SITE
[eCDatabaseVersionInfo] SELECT * FROM SITE
[eCDatabaseVersionInfo] Columns in SITE table:
[eCDatabaseVersionInfo] COMPNAME=BASE
[eCDatabaseVersionInfo] EDITION=ENT
[eCDatabaseVersionInfo] VERSION=6
[eCDatabaseVersionInfo] RELEASE=0
[eCDatabaseVersionInfo] MOD=0
[eCDatabaseVersionInfo] FIXPACK=2
[eCDatabaseVersionInfo] Updated SITE table successfully.
[EchoNL] Completed database fixpack update.
```

```
BUILD SUCCESSFUL
```

Remote Web server tasks

You must update the Web server machine with a new Stores.war file every time that you update the static Web content inside the application. Store Publishing and Upload Logo actions are examples of when you should update the Web server machine.

The Stores.war is located in the following directory: *WC_profiledir/installedApps/cell_name/WC_instance_name.ear/Stores.war*

Ensure that the path to this file is the same on the Web server node and the WebSphere Commerce node.

Note: Remove any JSP and JAR files from the *WC_instance_name.ear* directory on the Web server. Only static-content files should be in this directory on the Web server.

Determining the APARs that are installed on your machine

To determine the APARs that are installed on your WebSphere Commerce machine, refer to the Determining what APARs are installed on WebSphere Commerce Version 6.0 technote.

Precompiling JSP files

Precompile your JSP files before launching your store. Refer to: Compiling JavaServer Page files

Uninstalling the fix pack

Uninstalling the fix pack restores the WebSphere Commerce product files to the previous level. These instructions also remove the fix pack code from those WebSphere Commerce or WebSphere Commerce Payments instances that were updated at the same time the fix pack was applied to your system. After you apply the fix pack to your system, you cannot return your database configurations to their previous states.

WebSphere Commerce instances or WebSphere Commerce Payments instances that were created after the installation of the fix pack, will remain at the current fix pack level. Following these instructions will not restore these instances to the previous level. If these instances are required to be at the previous level, contact IBM Support for further assistance.

1. Ensure that you are logged in with a user profile that has *SECOFR authority.
2. Complete one of the following steps:
 - To remove the fix pack from the WebSphere Commerce product, stop the following servers:
 - WebSphere Commerce Help server.
 - WebSphere Commerce Configuration Manager server.
 - To remove the fix pack from the WebSphere Commerce instance or the WebSphere Commerce Payments instance only, start the following servers:
 - WebSphere Commerce database server.
 - WebSphere Commerce Application Server. For example, *server1*.
 - If you have a federated environment:
 - The WebSphere Application Server nodeagents are started.
 - The WebSphere Application Server deployment manager is started.

Next step

Uninstall the fix pack by completing the following section:

- “Silent uninstallation”

Silent uninstallation

Complete this section to silently uninstall the WebSphere Commerce fix pack. If you have applied the fix pack to your WebSphere Commerce or WebSphere Commerce Payments instance, you must uninstall the fix pack from that instance before uninstalling the fix pack from the WebSphere Commerce product.

Refer to the following sections:

- “Removing the fix pack from the WebSphere Commerce or WebSphere Commerce Payments instance” on page 14.
- “Removing the fix pack from the WebSphere Commerce installation directory” on page 14.

Removing the fix pack from the WebSphere Commerce or WebSphere Commerce Payments instance

Note: If you have created your instance **after** applying the fix pack, you cannot uninstall the fix pack from that instance.

1. Ensure that you are logged in with a user profile that has *SECOFR authority.
2. Navigate to the *UPDI_installdir*/responsefiles directory and open the *uninstall.txt* file in a text editor.
3. Complete the following steps:
 - To remove the fix pack from a WebSphere Commerce instance:
 - a. Update the **-W backup.package** entry with the name of the maintenance package that you want to uninstall.

Note: If the **-W backup.package** is not specified, the most recently installed fix pack is uninstalled.

- b. Update the **-W product.location** with the location of the WebSphere Commerce install.
- c. Add the following lines to the end of the *uninstall.txt* file:
`-W update.instancename="instance_name"`

Where *instance_name* is the name of your WebSphere Commerce instance or WebSphere Commerce Payments instance.

- To remove the fix pack from a WebSphere Commerce Payments instance when WebSphere Application Server security is enabled:
 - a. Update the **-W backup.package** entry with the name of the maintenance package that you want to uninstall.

Note: If the **-W backup.package** is not specified, the most recently installed fix pack is uninstalled.

- b. Update the **-W product.location** with the location of the WebSphere Commerce install.
- c. Add the following lines to the end of the *uninstall.txt* file:
`-W update.instancename="payments_instance_name"`
`-W update.was.security.enable="true"`
`-W update.wasuserid="was_user_ID"`
`-W update.wasuserpassword="was_user_password"`

4. Open the QShell by typing QSH at the i5/OS command prompt.

5. Run the following command:

```
update -devkit14 -options UPDI_installdir/responsefiles/uninstall.txt
```

6. Refer to the log files in the following directory to verify that your uninstall was successful:

```
WC_installdir/logs/update
```

Removing the fix pack from the WebSphere Commerce installation directory

Note: If you have applied the fix pack to a WebSphere Commerce or WebSphere Commerce Payments instance, you must refer to “Removing the fix pack from the WebSphere Commerce or WebSphere Commerce Payments instance” before uninstalling the fix pack from your WebSphere Commerce product.

1. Ensure that you are logged in with a user profile that has *SECOFR authority.
2. Open the QShell by typing QSH at the i5/OS command prompt.
3. Navigate to the *UPDI_installdir/responsefiles* directory and open the *uninstall.txt* file in a text editor.
4. To remove the fix pack from the WebSphere Commerce product:
 - a. Update the **-W backup.package** entry with the name of the maintenance package that you want to uninstall.

Note: If the **-W backup.package** is not specified, the most recently installed fix pack is uninstalled.

- b. Update the **-W product.location** with the location of the WebSphere Commerce install.
- c. Ensure that the following line does not exist or is commented out of the *uninstall.txt* file:

```
-W update.instancename="instance_name"
```

Where *instance_name* is the name of your WebSphere Commerce instance or WebSphere Commerce Payments instance.

5. Run the following command:

```
update -devkit14 -options UPDI_installdir/responsefiles/uninstall.txt
```
6. Refer to the log files in the following directory to verify that your uninstall was successful:

```
WC_installdir/logs/update
```
7. Restart your WebSphere Commerce or WebSphere Commerce Payments instance.

Appendix A. Troubleshooting

Troubleshooting general WebSphere Commerce fix pack issues

Two extra columns in the WebSphere Commerce 6.0 database are migrated from previous releases

When you install WebSphere Commerce 6.0, WebSphere Commerce 6.0.0.1 and WebSphere Commerce 6.0.0.2 and then migrate the WebSphere Commerce database from a previous version, additional columns and indices can appear. These two extra columns exist in the migrated database but do not exist in a newly created WebSphere Commerce 6.0 instance.

The two extra columns are:

- Column version of table orders
- Column complexorders of table store

If this problem occurs, copying data from the migrated production database to staging database will fail. You have the following options available if these columns are present:

- You can remove the indices and columns manually.
- You can apply the WebSphere Commerce 6.0.0.3 fix pack. This fix pack will remove the extra indices automatically. The extra columns must be removed manually.

For more information on removing the indices and columns, refer to the Two extra columns exist in the WebSphere Commerce 6.0 database that was migrated from previous releases Technote#1265056.

Error message when accessing WebSphere Commerce tools

When accessing the WebSphere Commerce tools such as WebSphere Commerce Accelerator, the following message is displayed:

```
You are not authorized to view this page
HTTP Error 403 - Forbidden
```

In the Web server's error log, you see a message similar to:

```
[Fri Jun 16 08:38:24 2006] [error] [client ip] (3401)Permission denied.:
ZSRV_MSG064B: access to /adminconsole denied
```

This error is caused by incorrect file permissions in the WebSphere Commerce Enterprise Application EAR file. See the Page is forbidden when accessing WebSphere Commerce tools (HTTP Error 403) technote for more information.

Error message when applying a fix pack using the WebSphere Commerce Update Installer version 6.1.0.4

You receive the following error message when using the WebSphere Commerce Update Installer to apply the maintenance:

The following APARs are installed or selected already for the current maintenance package.

This message means that the fixes or APARs that you have selected to install is included in, or superseded by, the fix pack. All of the APARS that are listed can be left unchecked when installing the fix pack.

Unable to find the fix pack log file

If the fix pack application failed, and you are unable to find the WebSphere Commerce log file in the *WC_installdir/logs/update* directory, refer to the following location:

UPDI_installdir/logs/tmp

WebSphere Commerce pages are not accessible after applying the fix pack

After applying the WebSphere Commerce Fix Pack and restarting WebSphere Commerce, some WebSphere Commerce pages will not be accessible.

The following error is displayed in the *SystemErr.log* file:

```
java.io.InvalidClassException
```

This error can be caused by a mismatch between a class file in the WebSphere Commerce EAR file and a class file stored in the Dynacache. To resolve the problem, restart the application server (for example. *server1*) that is associated with WebSphere Commerce .

Accessing backup files

The WebSphere Commerce fix pack update installer makes a backup of all the files modified during the fix pack installation.

- The backups made while installing the fix pack on the WebSphere Commerce product directory can be found in a *.pak* file at the following directory
- The backups made while installing the fix pack on your WebSphere Commerce instance can be found in a *.pak* file at the following location:

WC_installdir/properties/version/update/backup

*WC_userdir/instances/instance_name/properties/version/
update/backup*

Troubleshooting the install and uninstall of the WebSphere Commerce fix pack on your installation directory

Error encountered when completing a silent installation

Error encountered when referring to an incorrect .pak file location

When completing a silent installation, you encounter an error message similar to:

```
(Sep 21, 2006 2:21:27 PM), Install, com.ibm.ws.install.ni.ismp.actions.  
UPDIMaintenanceInformationAction,  
err, No such path or directory. /QIBM/ProdData/WebSphere/UpdateInstaller/  
V61/UPDI/maintenance/maintenance.xml
```

```
(Sep 21, 2006 2:21:27 PM), Install, com.ibm.ws.install.ni.ismp.actions.  
UPDIMaintenanceInformationAction,  
err, No such path or directory. /QIBM/ProdData/WebSphere/UpdateInstaller/  
V61/UPDI/maintenance/maintenance.xml
```

```
(Sep 21, 2006 2:21:27 PM), Install, com.ibm.ws.install.ni.ismp.actions.  
UPDIMaintenanceInformationAction,  
err, java.io.FileNotFoundException: No such path or directory.
```

```

/QIBM/ProdData/WebSphere/UpdateInstaller/V61/UPDI/maintenance/maintenance.xml
at java.lang.Throwable.<init>(Throwable.java:195)
at java.lang.Exception.<init>(Exception.java:41)
at java.io.IOException.<init>(IOException.java:40)
at java.io.FileNotFoundException.<init>(FileNotFoundException.java:46)
at java.io.FileInputStream.open(Native Method)
at java.io.FileInputStream.<init>(FileInputStream.java:106)
at com.ibm.ws.install.ni.framework.io.DiskFileSystem.readEntry
(DiskFileSystem.java:87)
at com.ibm.ws.install.ni.framework.io.FileSystemEntry.getInputStream
(FileSystemEntry.java:231)
at com.ibm.ws.install.ni.framework.xml.XMLUtils.
getSimpleXMLParserFromFileSystemEntry(XMLUtils.java:91)
at com.ibm.ws.install.ni.ismp.actions.UPDIMaintenanceInformationAction.execute
(UPDIMaintenanceInformationAction.java:60)
at com.installshield.wizard.StandardWizardListener.execute
(StandardWizardListener.java:123)
at com.installshield.wizard.StandardWizardListener.currentBeanChanged
(StandardWizardListener.java:106)

```

If you encounter this error edit your response file and ensure that you have the correct location for the WebSphere Commerce fix pack .pak file.

The installer is unable to update a .jar file on the system

If you receive an error message indicating that the installer is unable to update a .jar file on the system, refer to the *WC_installdir/logs/update/maintenance_name/*updatetrace.log file. Search this log file for an error message similar to:

```

Installer has pro2006.09.25 12:04:30.328 EDT java.lang.NullPointerException
at com.ibm.ws.install.ni.framework.io.ZIPFileSystem.copyZipEntry
(ZIPFileSystem.java:2010)
at com.ibm.ws.install.ni.framework.io.ZIPFileSystem.copyZipEntry
(ZIPFileSystem.java:1995)
at com.ibm.ws.install.ni.framework.io.ZIPFileSystem.copyThisEntryInThisSource
ToThisZipFileWithThisName(ZIPFileSystem.java:989)
at com.ibm.ws.install.ni.framework.io.ZIPFileSystem.applyZIPFileOperationsTo
ZIPFile(ZIPFileSystem.java:2112)
at com.ibm.ws.install.ni.framework.io.ZIPFileSystem.performAllZIPOperationsFor
ThisTargetFile(ZIPFileSystem.java:88)
at com.ibm.ws.install.ni.framework.fileactions.ZIPFileOperationController.
performAllZIPOperations(ZIPFileOperationController.java:108)
at com.ibm.commerce.install.updi.product.wc.WCUpdateComponent.execute
(WCUpdateComponent.java:119)

```

If you receive this error message, check if the path to the .pak file contains spaces. If there are spaces in the path, move the fix pack file to a path that does not contain spaces and complete the following steps:

1. Rerun the Update Installer to uninstall the fix pack from the system.
2. Reapply the fix pack to the system.

Error encountered when attempting silent uninstall of fix pack

The uninstall fails with the following message:

```

CWUPI0024E: The update operation is not permitted on FP002.pak. Either
this maintenance package is corrupted, or it has dependencies that prevent
this maintenance package from being updated.

```

If you encounter this error, edit your response file and ensure that you have the full name of the fix pack listed.

For example:

Errors encountered when uninstalling the WebSphere Commerce fix pack.

When the uninstall of the WebSphere Commerce fix pack fails and you encounter the following error message:

CWUPI0010E: Cannot uninstall an installed maintenance package. No corresponding maintenance backup package is available in the product maintenance backup directory.

Ensure that you have removed all dependent software, such as the WebSphere Commerce Feature Packs, from the machine and attempt to uninstall the fix pack again.

Troubleshooting the install and uninstall of the WebSphere Commerce fix pack on your instance

Error encountered when applying the fix pack on a machine that has WebSphere Application Server 6.0.2.5 or higher installed

If you have WebSphere Application Server Version 6.0.2.5 or higher installed on your machine and you are using a WebSphere Commerce Payments instance, refer to:

Applying WebSphere Commerce V6.0.0.2 Fix Pack to WebSphere Commerce Payments instance on i5/OS (IY91513) Technote #1250430

The fix pack failed to update the WebSphere Commerce instance during install or uninstall

Prerequisite checking fails during the application of the fix pack

Check the log files: If the prerequisite checking failed during the application of the fix pack, the following message is produced:

Failed to export the WebSphere Commerce instance to *user_temp_dir/wcupdate* directory. For more information, see the log file: "*WC_installdir/logs/update/actions/install/exporttear_instance_name.log*".

If the prerequisite checking failed during uninstall, the following message is produced:

Failed to export the WebSphere Commerce instance to *user_temp_dir/wcupdate* directory. For more information, see the log file: "*WC_installdir/logs/update/actions/uninstall/exporttear_instance_name.log*".

Ensure that the WebSphere Application Server Administrative server is started, and attempt the install or uninstall again.

Search for specific error codes in the log files: Search for the WASX7023E error code in the *exporttear_instance_name.log* file under the *stopWCApplications* or *stopPMAApplications* target. For example:

```
stopPMAApplications:
[wsadmin] WASX7023E: Error creating "SOAP" connection to host "localhost";
exception information: com.ibm.websphere.management.exception.
ConnectorNotAvailableException: com.ibm.websphere.management.exception.
ConnectorNotAvailableException: Failed to get a connection with IP
```

```

| address associated with hostname localhost
| [wsadmin] WASX7213I: This scripting client is not connected to a server
| process; please refer to the log file C:\Program Files\IBM\WebSphere\AppServer\
| profiles\wpm\logs\wsadmin.traceout for additional information.
| [wsadmin] WASX8011W: AdminTask object is not available.
| [wsadmin] WASX7303I: The following options are passed to the scripting
| environment and are available as argument that is stored in the argv variable:
| "[wpm_Commerce_Payments_App]"
| [wsadmin] WASX7017E: Exception received while running file "C:/Program Files/
| IBM/WebSphere/CommerceServer60/config/deployment/scripts/stopApps.jacl";
| exception information: com.ibm.ws.scripting.ScriptingException: AdminControl
| service not available

```

Ensure that the WebSphere Application Server Administrative server is started, and attempt the install or uninstall again.

Incomplete log files: If the last message in the `exportear_instance_name.log` is `stopWCApplications` or `stopPMAApplications`, check the following log file for a `WSProfileException` error:

`UPDI_installdir/logs/tmp/updatetrace.log`

For example:

```

| 2006.09.25 17:04:45.984 EDT Failed to export the WebSphere
| Commerce instance to C:\DOCUME~1\user\LOCALS~1\Temp\wcupdate
| directory.
| 2006.09.25 17:04:46.015 EDT C:\WebSphere\CommerceServer60\config\
| deployment\xml\exportEar.xml:55: The following error occurred while
| executing this line:
| C:\WebSphere\CommerceServer60\config\deployment\xml\exportEar.xml:145:
| WSProfileException profileName=wpm

```

If you experience this error message, run the following command to ensure that your profile is registered:

- `WAS_installdir/bin/wasprofile -listProfiles`

If the profile is not listed in the output of this command, contact WebSphere Commerce Support.

Problem deploying WebSphere Commerce

If installer failed to deploy WebSphere Commerce instance back to your WebSphere Application Server configuration, refer to the following log file:

- Install:

`WC_installdir/logs/update/actions/install/deployear_instance_name.log`

- Uninstall:

`WC_installdir/logs/update/actions/uninstall/deployear_instance_name.log`

If a problem with the `deployear_instance_name` task is indicated in these log files, check the following trace file for details:

`WC_profiledir/logs/wsadmin.traceout.log`

To reapply the fix pack update:

1. You must remove the fix pack backup information. Delete the following location:

`WC_userdir/instances/instance_name/properties/version/update/backup`

2. Delete the following location:

`WC_userdir/instances/instance_name/properties/version/update/confighistory`

3. If the following directory exists:

WC_userdir/instances/instance_name/properties/version/update/backup.save

Rename the directory to:

WC_userdir/instances/instance_name/properties/version/update/backup

4. If the following directory exists:

*WC_userdir/instances/instance_name/properties/version/update/
confighistory.save*

Rename the directory to:

WC_userdir/instances/instance_name/properties/version/update/confighistory

5. Restart the update installer, and reapply the fix pack to your instance.

The updatedb script fails during the application of the fix pack

If updatedb process fails during fix pack update, complete the following steps:

1. Review the log files in the following locations:

- *WC_userdir/instance/instance_name/logs/trace.txt*
- *WC_userdir/instance/instance_name/logs/messages.txt*

Review these error messages with your database administrator to ensure there are no data errors.

2. Navigate to the *WC_installdir/bin* directory.

3. Perform one of the following steps:

- Run the updatedb command again. Refer to “Updating the WebSphere Commerce database manually” on page 10 for more information.
- Restore the original database and run the updatedb command. Refer to “Updating the WebSphere Commerce database manually” on page 10 for more information.

4. If this problem cannot be resolved, contact IBM WebSphere Commerce Support.

Error encountered when completing a silent installation

Error encountered when referring to an incorrect .pak file location

When completing a silent installation, you encounter an error message similar to:

```
(Sep 21, 2006 2:21:27 PM), Install, com.ibm.ws.install.ni.ismp.actions.  
UPDIMaintenanceInformationAction,  
err, No such path or directory. /QIBM/ProdData/WebSphere/UpdateInstaller/  
V61/UPDI/maintenance/maintenance.xml  
(Sep 21, 2006 2:21:27 PM), Install, com.ibm.ws.install.ni.ismp.actions.  
UPDIMaintenanceInformationAction,  
err, No such path or directory. /QIBM/ProdData/WebSphere/UpdateInstaller/  
V61/UPDI/maintenance/maintenance.xml  
(Sep 21, 2006 2:21:27 PM), Install, com.ibm.ws.install.ni.ismp.actions.  
UPDIMaintenanceInformationAction,  
err, java.io.FileNotFoundException: No such path or directory.  
  
/QIBM/ProdData/WebSphere/UpdateInstaller/V61/UPDI/maintenance/maintenance.xml  
at java.lang.Throwable.<init>(Throwable.java:195)  
at java.lang.Exception.<init>(Exception.java:41)  
at java.io.IOException.<init>(IOException.java:40)  
at java.io.FileNotFoundException.<init>(FileNotFoundException.java:46)  
at java.io.FileInputStream.open(Native Method)  
at java.io.FileInputStream.<init>(FileInputStream.java:106)  
at com.ibm.ws.install.ni.framework.io.DiskFileSystem.readEntry  
(DiskFileSystem.java:87)  
at com.ibm.ws.install.ni.framework.io.FileSystemEntry.getInputStream
```

```

| (FileSystemEntry.java:231)
| at com.ibm.ws.install.ni.framework.xml.XMLUtils.
| getSimpleXMLParserFromFileSystemEntry(XMLUtils.java:91)
| at com.ibm.ws.install.ni.ismp.actions.UPDIMaintenanceInformationAction.execute
| (UPDIMaintenanceInformationAction.java:60)
| at com.installshield.wizard.StandardWizardListener.execute
| (StandardWizardListener.java:123)
| at com.installshield.wizard.StandardWizardListener.currentBeanChanged
| (StandardWizardListener.java:106)

```

If you encounter this error edit your response file and ensure that you are referring to the correct location for the WebSphere Commerce fix pack .pak file.

The installer is unable to update a .jar file on the system

If you receive an error message indicating that the installer is unable to update a .jar file on the system, refer to the *WC_installdir/logs/update/maintenance_name/* *updatetrace.log* file. Search this log file for an error message similar to:

```

| Installer has pro2006.09.25 12:04:30.328 EDT java.lang.NullPointerException
| at com.ibm.ws.install.ni.framework.io.ZIPFileSystem.copyZipEntry
| (ZIPFileSystem.java:2010)
| at com.ibm.ws.install.ni.framework.io.ZIPFileSystem.copyZipEntry
| (ZIPFileSystem.java:1995)
| at com.ibm.ws.install.ni.framework.io.ZIPFileSystem.copyThisEntryInThisSource
| ToThisZipFileWithThisName(ZIPFileSystem.java:989)
| at com.ibm.ws.install.ni.framework.io.ZIPFileSystem.applyZIPFileOperationsTo
| ZIPFile(ZIPFileSystem.java:2112)
| at com.ibm.ws.install.ni.framework.io.ZIPFileSystem.performAllZIPOperationsFor
| ThisTargetFile(ZIPFileSystem.java:88)
| at com.ibm.ws.install.ni.framework.fileactions.ZIPFileOperationController.
| performAllZIPOperations(ZIPFileOperationController.java:108)
| at com.ibm.commerce.install.updi.product.wc.WCUpdateComponent.execute
| (WCUpdateComponent.java:119)

```

If you receive this error message, check if the path to the fix pack (maintenance) pak file contains spaces. If there are spaces in the path, move the fix pack file to a path that does not contain spaces and complete the following steps:

1. Rerun the Update Installer to uninstall the fix pack from the system.
2. Reapply the fix pack to the system.

Error encountered when attempting silent uninstall of fix pack

The uninstall fails with the following message:

```

| CWUPI0024E: The update operation is not permitted on FP001.pak. Either
| this maintenance package is corrupted, or it has dependencies that prevent
| this maintenance package from being updated.

```

If you encounter this error, edit your response file and ensure that you have the full name of the fix pack listed.

For example:

```
6.0.0-WS-WCServer-FP002.pak
```

Exceptions are logged in the createInstanceANT.err.log and createInstanceANT.log files

When creating an authoring instance, errors similar to the following are logged in the *createInstanceANT.err.log* and *createInstanceANT.log* files

- *createInstanceANT.err.log*:

```
| [2006.09.21 08:07:26] [sql] Failed to execute: DROP TRIGGER STAG0082
| [2006.09.21 08:07:26] [sql] COM.ibm.db2.jdbc.DB2Exception: [IBM][CLI Driver]
| [DB2/NT] SQL0204N "BUILD.STAG0082" is an undefined name. SQLSTATE=42704
```

- createInstanceANT.log:

```
| [2006.09.21 08:07:25] RunSQLFileOnErrorContinue:
| [2006.09.21 08:07:26] [sql] Executing file: D:\WebSphere\CommerceServer60\
| schema\db2\fixpack2\wcs.d146740_trigger.sql
| [2006.09.21 08:07:26] [sql] Failed to execute: DROP TRIGGER STAG0082
| [2006.09.21 08:07:26] [sql] COM.ibm.db2.jdbc.DB2Exception: [IBM]
| [CLI Driver][DB2/NT] SQL0204N "BUILD.STAG0082" is an undefined name.
| SQLSTATE=42704
| [2006.09.21 08:07:26] [sql] 0 of 1 SQL statements executed successfully
```

These errors are caused by the following scenarios:

- You are creating a new instance with a staging database. The staging trigger is not created and the updatedb command catches an exception in the log file.
- You have an existing instance with a staging database. The staging trigger is created and the updatedb command catches an exception in the log file.

These error messages can safely be ignored.

Appendix B. WebSphere Commerce updates

If you have installed other APARs that are not listed in this section, you will need to reinstall them after applying this fix pack.

This fix pack contains the interim fixes (APARs) for the WebSphere Commerce Sales Center client:

Interim fix #	Description
APAR#IY85624	Corrected MANIFEST_ID field not updated in ORDITEMCONF table issue.
APAR#IY85624	Corrected SalesContainerItemsPageManager customization issue.
APAR#IY86085	Corrected an issue where, after cloning order GUI is not receiving model change events.
APAR#IY86085	Corrected customer not cleared from stores view when closed issue.
APAR#IY86085	Corrected an issue where editors do not scroll when tab through fields.
APAR#IY86085	Corrected FindDialog stops search when=0, but resultSetSize not reached issue.
APAR#IY86085	Corrected inconsistency and UI issues of the Contact history view.
APAR#IY86085	Corrected prodcompeditor does not close window when clear store clicked issue.
APAR#JR22550	Corrected customer editor update button enablement.
APAR#IY91991	The uninstallation of the IBM Sales Center client through WEDM failed.
APAR#JR25581	IBM Sales Center treats milliseconds as absolute values instead of percentages.
APAR#JR24891	Corrected an issue where you cannot deselect hip as complete for single order item.

This fix pack contains the interim fixes (APARs):

Interim fix #	Description
APAR#IY79965	Corrected an error returned due to serialization problems in data misleading issue.
APAR#IY83748	Corrected an unable to delete template that is assigned to a category in WebSphere Commerce Accelerator issue.
APAR#IY83823	Corrected PricingDataBean using commitCopyHelper() issue.
APAR#IY83995	Corrected an issue where the DN should be able to handle \,.
APAR#IY84162	Performance improvement for Manage Files page of WebSphere Commerce Accelerator
APAR#IY84389	PCI enablement.
APAR#IY84484	Addressed findApplicableByOrgEntity SQL performance.
APAR#IY84567	Corrected an available languages for a store contains a "selected" entry issue.
APAR#IY85030	Corrected an issue where WebSphere Commerce Accelerator access continues to work after Sales Center logoff.
APAR#IY85033	Corrected a content sensitive help of Blocked Order report page issue.

APAR#IY85037	Corrected a contract export/import using WebSphere Commerce Accelerator issue.
APAR#IY85624	Corrected a MANIFEST_ID field not updated in ORDITEMCONF table issue.
APAR#IY85624	DataBean for partial shipment.
APAR#IY85624	Corrected a NullPointerException if setup TAXJCRULE with no FFMCenter issue.
APAR#IY85929	Corrected an issue where the promotion engine gets protected context attribute and add protected context attribute.
APAR#IY86088	Corrected an extra space in org field of custTerritoryGroup page issue.
APAR#IY86468	Corrected JavaScript™ error on Criteria page.
APAR#IY86472	Corrected a find store (store name) ignoreCaseBegin is case sensitive issue.
APAR#IY86715	Corrected a blank page issue when using search with double quotes.
APAR#IY86766	Corrected a payment methods issue in SupplyMarketplace for auction.
APAR#IY86766	Corrected a Submit a AutoBid issue.
APAR#IY86769	Corrected a duplicate category issue when browsing catalog during promotion creation.
APAR#IY87038	Corrected a valid offer does not get picked up for a pending order issue.
APAR#IY88549	Provided Web Service invocation update for OpenWebServicesComponent.
APAR#IY89093	Corrected a parameter value in log file issue.
APAR#IY89489	Enhanced security.
APAR#JR22709	Corrected an issue where the optimizer statistics are destroyed and regenerated with estimate option.
APAR#JR23657	Corrected a catalog search tool not support nonbuyable items/products issue.
APAR#JR23680	Corrected a date range message persistence in Contract Activity issue.
APAR#JR23688	Corrected an issue of not assigning shipping codes to products, only items.
APAR#JR23695	Corrected a Daily Sales issue.
APAR#JR23771	Corrected an issue where the Find Quote finds Orders as well.
APAR#JR23844	Corrected an AddressDataBean does not populate for address of status 'T' issue.
APAR#JR24147	Corrected a Requisition List requires User's Organization issue.
APAR#JR24205	Corrected a Null Pointer Exception when enabling persistent sessions issue.
APAR#JR24243	Corrected an issue where the guest shopping cart does not merge with registered user's cart.
APAR#JR24312	Corrected an issue where the session code didn't extract the storeId from the body of a post request.
APAR#JR24336	Corrected a List of Files displayed should be sorted by alphabetical order issue.
APAR#JR24385	Corrected limitation with pricing component call.
APAR#JR24681	Corrected a SSL accelerator fails when using default port # issue.

APAR#LI71252	Corrected an issue where two order cancellation emails are sent to shoppers.
APAR#LI71288	Corrected a deadlock in INVENTORY in repeated scheduled orders.
APAR#LI71315	Corrected an issue displaying sales catalog instead of the master catalog.
APAR#LI71375	Corrected a WebSphere Commerce XHTML issue.
APAR#SI23474	Store DN as uppercase to avoid multiple toUpper calls.
APAR#IY88656	Corrected an issue to allow future invalidation through the cacheivl table.
APAR#JR25039	Corrected an issue where the promotion engine was not applying the promotion offering.
APAR#IY90973	Corrected an issue where the promotion name should allow numeric characters.
APAR#JR25364	Corrected an issue where no warnings are logged when WebSphere Commerce Analyzer fails to save long promotion descriptions.
APAR#JR25363	Corrected an issue where you are unable to specify the category for the product promotion when category is too long.
APAR#IY87190	Corrected an issue where a custom contract does not display discounts correctly from the base contract.
APAR#JR24752	Corrected an issue where the campaign panel fails to load if the number of activities is large.
APAR#IY90976	Corrected an issue with the ShopcartDrivenAgendaBuilder when modifying the shopcart item to be quantity 0.
APAR#JR24465	Corrected an issue where the RememberMe functionality fails due to Null LangId.
APAR#IY86836	Corrected an issue where the ProductDisplay command is slow with 13 million rows in PRESETCEREL.
APAR#LI72077	Corrected an issue where the user experiences slow performance with GetContractUnitPrice.
APAR#JR24733	Corrected an issue where the user's member group list should be sorted.
APAR#JR24790	Corrected an issue where the length of address fields are cut short.
APAR#JR25163	Corrected an issue where Oracle does not accept "" as empty string.
APAR#JR24970	Corrected an issue where the user cannot complete a promotion for the dynamic kit.
APAR#IY90774	Corrected an issue where the Marketing > Promotions > Segment summary is not working.
APAR#JR23846	Corrected an issue where the Quotes to Order Conversion Rate report was not displaying the correct results.
APAR#IY93118	Corrected an issue where logging into the Administration Console fails after configuring the WebSphere Commerce to LDAP server.
APAR#LI72077	Improved the performance of GetContractUnitPriceCmdImpl.
APAR#JR24757	Corrected an issue where the getEntitledSubCatalogGroupsByStore throws NullPointerExceptions.
APAR#JR24537	Corrected an issue where the stardate and endate in the offer table are not updated in database.
APAR#IY90803	Corrected an issue where searching for orders using customer name does not work.
APAR#JR24495	Corrected an issue to allow DBUpdateTool to re-encrypt data custom tables.

APAR#JR25013	Corrected an issue where the user cannot find the wcsadmin user for MQ on startup after enabling LDAP.
APAR#JR24848	Corrected an issue where the price adjustment does not refresh after applying IY87190.
APAR#JR25025	Corrected an issue where the user is unable to approve a second order since the previous order is cached.
APAR#IY86843	Corrected an issue where the Account Representative drop-down lists are truncated in MSC.
APAR#JR24748	Corrected an issue where the GiftRegistryItemUpdate and GiftRegistryItemDelete do not work properly.
APAR#LI71582	Corrected an issue where the setdbenv scripts are using old loader classes.
APAR#IY91134	Corrected an issue where the Auction Notify messages do not compile due to nullpointer exceptions.
APAR#LI71714	Corrected an issue where the Add to Shopping Cart action fails for the Content click action.
APAR#JR25336	Corrected an issue where the FileTreeDataBean uses hard coded EAR path.
APAR#LI71608	Corrected an issue where the user cannot delete the Task Group from the workspace upon failed quick publish.
APAR#JR24498	Corrected an issue where specific products are not showing after assigning the Shipping Code.
APAR#JR24621	Corrected an issue that occurred when displaying the information for an Ad Copy in WebSphere Commerce Accelerator, the Category Name does not display if it includes the '&' character.
APAR#JR25378	Corrected an issue where products that are created in a hosted store do not show up when added to a web activity for an emarketing spot.
APAR#LI71594	Corrected an issue where adding an item to the wish-list fails.
APAR#LI71607	Corrected an issue with the shopping flow.
APAR#IY90929	Corrected an issue where addresses were limited 10 for shipping and billing.
APAR#JR25085	Corrected an issue where x-data/xact-error is wrongly treated as unsupported.
APAR#IY89101	Corrected an issue with performance problems with shipping/tax calculations.
APAR#JR24969	Corrected an issue with the search filter.
APAR#JR25049	Corrected an issue where the shopper cannot login to the store if a CSR is editing their order.
APAR#IY91513	Corrected an issue where fixpack 6001 install fails on a WebSphere Payments instance.
APAR#JR24814	Corrected an issue where the promotions bucket, order checkout fails with a null pointer exception.
APAR#JR24888	createPaymentsVirtualHost.sh error corrected.
APAR#IY90010	Corrected an issue where the user cannot apply the fixpack to a WebSphere Payments instance when global security is enabled.
APAR#IY91476	E-mail Activity Performance improved.
APAR#JR24552	Corrected an issue that occurs if the user has two or more web activities, only one web activity shows up.

APAR#JR24721	Corrected an issue where the DuplicateKeyException passed over in SetOrderPaymentInfoCmdImpl.
APAR#IY88772	Corrected an issue where the create scheduler command will clear trash can order.
APAR#JR25024	Corrected an issue where the discount price of item is not reflected in the database during order flow.
APAR#JR25189	Corrected an issue where the user cannot add an item to the cart if the item is added to more than one product.
APAR#JR25015	Corrected an issue where values are not deleted for automatic deposit payments.
APAR#LI71708	Corrected an issue where the feature is enabled and the required files do not get copied.
APAR#SE27271	Corrected an issue where URLUTF8Encoder.decode throws an exception while handling "%%%"
APAR#IY91990	Synchronization issue with Order block corrected.
APAR#JR24876	Corrected an issue where a non-plugin folder that is placed under the plugins directory throws an exception.
APAR#JR25009	Corrected an issue where a WebSphere Payments instance is not set as INVALID when the plugin throws an InvalidPay exception.
APAR#JR24462	Corrected an issue where a StackOverflow exception is encountered during WebSphere Payment plug-in initialization.
APAR#JR25504	Corrected an issue where a user is remembered in a not remember case.
APAR#JR24546	Corrected an issue where a JspBatchCompiler error is logged with the SimpleCreditLine.jsp.
APAR#JR25335	Corrected an issue where a ProductSetID SAXException is logged.
APAR#JR25504	Corrected an issue with the AbstractMethodError.
APAR#JR25504	Corrected an issue where you do not need to setOwner on the AccManager..
APAR#JR25504	Added a cloudscape version of updatedbforldap*.sql script.
APAR#JR25504	Integrated changes required for UI Runtime support.
APAR#JR25504	Added ContextService interface and IdentityManager.
APAR#JR25504	Fixed the SOI example to match the most recent version.
APAR#LI71970	Corrected an issue where the ContentURLTag output is incorrect.
APAR#IY94004	WebSphere Commerce Analyzer find result customer segment page now list the search fields.
APAR#JR25504	Added a clean option to Windows start help script.
APAR#JR25504	Store publish and model changes.
APAR#JR25504	Corrected an issue where a NullPointerException is logged after a successful AjaxComponentService call.
APAR#JR25504	Corrected an issue where you cannot deploy an EJB on the Feature Pack 2 enablement script.
APAR#JR25038	Corrected an issue where you cannot handle an e-mail address with "1" or "3".
APAR#JR25517	Updated Migration documentation.
APAR#IY93384	Added "Select Distinct" in DynaCacheInvalidation to improve performance.
APAR#IY93347	Provided the ability to disable the Junk Order feature.

APAR#JR24734	Hardcoded role Ids make OAC uncustomizable.
APAR#JR25504	Added an iFeature version checker.
APAR#JR25504	Corrected an issue where the wmm.jar does not support a clustered environment.
APAR#JR25568	Fixed an error where an exception during a financial transaction does not roll back the transaction.
APAR#IY90328	Corrected an issue where a customer search for a segment needs to check for search criteria.
APAR#JR25504	Corrected an issue where the fixpack 2 database update fails on cloudscape.
APAR#LI71832	Corrected an issue where the store flow reset after a collapsed EAR is expanded.
APAR#LI72077	Corrected an issue where contracts cannot be displayed for Exclude/Include.
APAR#IY89289	Trace improvement in GetContractUnitPrice and RetrievePrice.
APAR#JR24749	A method has been added to make customization possible.
APAR#JR25931	Hide the 'Default' sales tax code and enable the "set as default" button.
APAR#JR25931	Support multiple fulfillment centers for the tax configuration user interface.
APAR#JR25548	Corrected an issue where phantom files were included in looseconfig.xml.
APAR#JR25518	Corrected an issue where the _API_BAD_INV error locks the shopping cart making it inaccessible.
APAR#JR25931	Corrected an issue where the UpdateTax01CmdImpl gives a Finder Exception.
APAR#JR25562	Corrected an issue where a script fails when it is running in a clustered environment.
APAR#IY94012	Corrected an issue where you cannot uninstall the fixpack after you have enabled LDAP.
APAR#JR26106	Corrected an issue where payment rules fail to resolve according to CorePaymentAction.
APAR#IY96015	Error page is display when updating the registry.
APAR#SE27480	Corrected an issue where creating a tickler at the transaction failed.
APAR#IY94647	Corrected an issue where the PluginAdapter does not set the expiry date..
APAR#JR25504	Add a trace component for Paymentech Plugin.
APAR#JR26117	In the memory the merchant configuration information should be plain text.
APAR#JR25504	Introduced a new WebSphere Payments plugin interface.
APAR#IY92177	Corrected an issue where you experience a bad or missing parameter: DynamicKitPricingTCId error.
APAR#LI71771	Corrected an issue where you empty the payments summary once a return is created for the order.
APAR#JR25553	Corrected an issue where large CatalogIDs prevents WebSphere Commerce Accelerator from modifying the price.
APAR#JR26161	Corrected an issue where Stageprop should report an error when 0 rows changed by I/U/D SQL.

APAR#IY92792	Corrected an issue where the KLF is not initiated when third-party code calls PaymentsConfigurator.
APAR#IY94694	Disable Multiclick when an https request is redirected to http.
APAR#IY93066	Unable to edit pending order in the WebSphere Commerce Accelerator
APAR#JR25513	Added a fix that corrects an error in the messaging composer on WebSphere Application Server 6.0.2.13 or later.
APAR#LI71819	Corrected an issue where you cannot add comments to orders in WebSphere Commerce Accelerator.
APAR#IY93739	Currency formats are appending, not refreshing.
APAR#JR26161	Do not fail on propagating a row delete, because the row is already deleted.
APAR#JR25413	Corrected an issue where the reserve payment fails on the second deposit.
APAR#JR25504	Corrected an issue where the enableFeatureForToolkit.xml fails.
APAR#IY93633	The content managed operation needs to be transaction aware.
APAR#JR25362	Corrected an issue where the Gift registry stops working after applying an APAR.
APAR#JR25318	Corrected an issue where you login as a registered customer and best price not updated.
APAR#JR25507	Fixed an issue where there was an incorrectly hardcoded a reason code in the WebSphere Payment AVS code.
APAR#JR24885	Corrected an issue where WebSphere Commerce 6.0 payments does not block an order as expected.
APAR#LI71827	Corrected an issue where there is no check operation performed during shopping flow.
APAR#JR25504	Corrected an issue to clear the identity token before the end of the web request.
APAR#LI71687	Updated OrderShippingModeListDataBean Javadoc.

Notices

This information was developed for products and services offered in the U.S.A.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

Any reference to an IBM licensed program in this publication is not intended to state or imply that only IBM's licensed program may be used. Any functionally equivalent product, program, or service that does not infringe any of IBM's intellectual property rights may be used instead of the IBM product, program, or service. Evaluation and verification of operation in conjunction with other products, except those expressly designated by IBM, is the user's responsibility.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk, NY 10504-1785
U.S.A.

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

IBM World Trade Asia Corporation
Licensing
2-31 Roppongi 3-chome, Minato-ku
Tokyo 106, Japan

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law:

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be

incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Canada Ltd.
Office of the Lab Director
8200 Warden Avenue
Markham, Ontario
L6G 1C7
Canada

Such information may be available, subject to appropriate terms and conditions, including in some cases payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurement may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

Trademarks

IBM, the IBM logo and the following terms are trademarks or registered trademarks of International Business Machines Corporation in the United States or other countries or both:

- AIX

- i5/OS
- iSeries
- pSeries
- xSeries
- zSeries
- WebSphere

Windows is a trademark of Microsoft Corporation in the United States, other countries, or both.

Linux is a trademark of Linus Torvalds in the United States, other countries, or both.

Other company, product or service names may be the trademarks or service marks of others.



Printed in USA