

IBM Application Performance Analyzer for z/OS



User's Guide

Version 10 Release 1

IBM Application Performance Analyzer for z/OS



User's Guide

Version 10 Release 1

Fourth Edition (August 2010)

Note: Before using this information and the product it supports, be sure to read the general information under Appendix E, "Notices," on page 805.

This edition applies to IBM Application Performance Analyzer for z/OS Version 10 Release 1 (5697-P36) as modified by PTFs listed in "About this document" on page xv and to any subsequent releases until otherwise indicated in new editions. Make sure you are using the correct edition for the level of Application Performance Analyzer.

You can order publications online at www.ibm.com/shop/publications/order, or order phone by phone or fax. IBM Software Manufacturing Solutions takes publication orders between 8:30 a.m. and 7:00 p.m. EST (Eastern Standard Time). The phone number is (800) 879-2755. The fax number is (800) 445-9269.

You can find out more about IBM Application Performance Analyzer for z/OS by visiting the IBM Web site for Application Performance Analyzer at: www.ibm.com/software/awdtools/apa/

Copyright © 2009, 2010 BankNet. All rights reserved.

© Copyright IBM Corporation 2009, 2010.

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

About this document xv

Documentation conventions xv

Summary of changes xvii

Changes introduced with IBM Application

Performance Analyzer V10.1 xvii

Chapter 1. Using Application

Performance Analyzer/ISPF 1

ISPF reports: navigation and control 1

Scrolling 1

Report headings 1

Action (menu) bar 1

Retaining open reports 2

Displaying HELP 2

Primary commands for report navigation 2

Line commands for report navigation 4

R02 - Observation session list 8

Input fields 9

Description of detail lines 9

Detail window 11

R01 - Application Performance Analyzer

performance reports menu 12

Chapter 2. Entering observation

requests 15

Entering an observation request 15

Using the NEW command 15

Using the MOD line command 16

Schedule New Measurement panels 16

Panel 1 – Job Information 17

Panel 2 – Options 22

Panel 3 – Multi-steps 26

Panel 4 – Active Jobs 28

Panel 5 – Subsystems 29

Panel 6 – Sysplex 32

Panel 7 – Schedule 32

Panel 8 – Sched Options 36

Entering a Threshold Monitor request 39

Using the TNEW command 39

Setting Threshold Requirements panels 39

Panel 3 - Criteria 39

Entering a Trigger request 40

Overview 40

Using the TR line command 41

Chapter 3. Performance analysis

reports. 43

Performance analysis basics 44

Sampling and system states 44

Types of system states 44

System objects 45

Quantities expressed as percentages 45

Margin of error 46

Color coding of graphs 46

Report categories and codes 47

S01 - Measurement profile 50

Usage 50

Performance graphs 50

Overall CPU activity 50

CPU usage distribution 51

Most CPU active modules 51

Most CPU active CSECTs 52

CPU modes 52

Most active IMS PSBs 52

Most active DLI calls 53

Most active DB2 plans 53

Most active packages/DBRMs 53

Most active SQL statements 54

Measurement values 54

Request parameters 54

Measurement environment 55

Measurement statistics 56

CPU consumption 56

DDF CPU consumption 57

Client enclave consumption 58

Sample reports 58

S02 - Load module attributes 60

SETUP options 61

S03 - Load module summary 62

Detail line descriptions 62

Line commands 63

Detail window 63

S04 - TCB summary 64

Overview 64

Detail line descriptions 64

Line commands 65

Detail window 65

S05 - Memory usage timeline 66

Overview 66

Detail line descriptions 66

Line commands 67

SETUP options 67

S06 - Data space usage timeline 68

Overview 68

Detail line descriptions 68

Line commands 68

SETUP options 69

S07 - TCB execution summary 69

Overview 69

Detail line descriptions 70

Line commands 71

S08 - Processor utilization summary 71

Usage 71

Quantification 71

Sample reports 73

S09 - Measurement analysis 73

Usage 73

Sample reports 74

C01 - CPU usage by category 74

| | | | |
|--|-----|--|-----|
| Overview | 74 | Detail window | 113 |
| Detail line descriptions | 75 | W01 - WAIT time by task/category | 113 |
| Subset reports | 79 | Overview | 113 |
| Line commands | 79 | Detail line descriptions | 114 |
| SETUP options | 80 | Line commands | 117 |
| Detail window | 81 | SETUP options | 117 |
| C02 - CPU usage by module. | 82 | Detail window | 118 |
| Overview | 82 | W02 - WAIT time by task/module | 118 |
| Detail line descriptions | 82 | Overview | 118 |
| Line commands | 83 | Detail line descriptions | 118 |
| Detail window | 84 | Line commands | 120 |
| SETUP options | 85 | SETUP options | 121 |
| C03 - CPU usage by code slice | 85 | Detail window | 121 |
| Overview | 85 | W03 - WAIT time referred attribution | 122 |
| Detail line descriptions | 87 | Usage | 122 |
| Line commands | 87 | Quantification | 122 |
| SETUP options | 87 | Detail line hierarchy | 122 |
| Detail window | 88 | Detail line descriptions | 122 |
| C04 - CPU usage timeline | 88 | Sample reports | 124 |
| Overview | 88 | Line commands | 124 |
| Detail line descriptions | 89 | SETUP options | 125 |
| Subset reports | 89 | W04 - WAIT time by task ENQ/RESERVE. | 125 |
| Line commands | 89 | Usage | 125 |
| SETUP options | 90 | Quantification | 125 |
| Detail window | 90 | Detail line hierarchy | 126 |
| C05 - CPU usage by task/category | 91 | Detail line descriptions | 126 |
| Overview | 91 | Sample reports | 127 |
| Detail line descriptions | 92 | Line commands | 127 |
| Line commands | 96 | Detail window | 128 |
| SETUP options | 97 | W05 - WAIT time by tape DDNAME | 128 |
| Detail window | 97 | Usage | 128 |
| C06 - CPU usage by task/module | 98 | Quantification | 128 |
| Overview | 98 | Detail line descriptions | 128 |
| Detail line descriptions | 98 | Sample reports | 129 |
| Sample reports | 99 | Line commands | 129 |
| Line commands | 100 | Detail window | 129 |
| SETUP options | 101 | D01 - DASD usage by device | 130 |
| Detail window | 101 | Overview | 130 |
| C07 - CPU usage by procedure | 102 | Detail line descriptions | 131 |
| Usage | 102 | Line commands | 131 |
| Quantification | 102 | Detail window | 132 |
| Detail line hierarchy | 102 | SETUP options | 132 |
| Detail line descriptions | 103 | D02 - DASD usage by DDNAME. | 132 |
| Sample reports | 103 | Overview | 132 |
| Line commands | 104 | Detail line descriptions | 133 |
| SETUP options | 104 | Line commands | 133 |
| Detail window | 104 | Detail window | 134 |
| C08 - CPU usage referred attribution | 105 | SETUP options | 135 |
| Usage | 105 | D03 - DASD usage by data set | 135 |
| Quantification | 105 | Overview | 135 |
| Detail line hierarchy | 105 | Detail line descriptions | 136 |
| Detail line descriptions | 106 | Line commands | 136 |
| Sample reports | 107 | Detail window | 136 |
| Line commands | 108 | SETUP options | 137 |
| Detail window | 109 | D04 - Data set attributes. | 137 |
| C09 - CPU usage by PSW/object code | 111 | D05 - DASD EXCP summary | 139 |
| Quantification | 111 | Usage | 139 |
| Detail line hierarchy | 111 | Quantification | 139 |
| Detail line descriptions | 111 | Detail line hierarchy | 139 |
| Sample reports | 112 | Detail line descriptions | 140 |
| Line commands | 112 | Sample reports | 140 |

| | | | |
|---|-----|--|-----|
| Line commands | 140 | E01 - CICS session statistics | 163 |
| SETUP options | 141 | Usage | 163 |
| Detail window | 141 | Detail line descriptions | 163 |
| D06 - DASD VSAM statistics | 142 | Sample reports | 165 |
| Usage | 142 | E02 - CICS CPU and use count by program | 166 |
| Quantification | 142 | Usage | 166 |
| Detail line hierarchy | 142 | Quantification | 166 |
| Detail line descriptions | 142 | Detail line hierarchy | 166 |
| Sample reports | 143 | Sample reports | 167 |
| Line commands | 143 | Detail line descriptions | 167 |
| SETUP options | 143 | Line commands | 167 |
| Detail window | 144 | Detail window | 168 |
| D07 - DASD activity timeline | 144 | E03 - CICS CPU usage by transaction | 168 |
| Usage | 145 | Usage | 168 |
| Quantification | 145 | Quantification | 168 |
| Detail line descriptions | 145 | Detail line hierarchy | 169 |
| Sample reports | 146 | Sample reports | 169 |
| Line commands | 146 | Detail line descriptions | 170 |
| SETUP options | 146 | Line commands | 172 |
| Detail window | 147 | Detail window | 173 |
| D08 - DASD I/O wait time | 147 | SETUP options | 175 |
| Usage | 147 | E04 - CICS mean service time by transaction | 175 |
| Quantification | 147 | Usage | 175 |
| Detail line hierarchy | 148 | Quantification | 175 |
| Detail line descriptions | 148 | Detail line hierarchy | 175 |
| Sample reports | 149 | Sample reports | 176 |
| Line commands | 150 | Detail line descriptions | 177 |
| Detail window | 151 | Line commands | 183 |
| D09 - VSAM buffer pool usage | 152 | Detail window | 184 |
| Usage | 152 | E05 - CICS total service time by Txn. | 186 |
| Quantification | 152 | Usage | 186 |
| Sample reports | 153 | Quantification | 186 |
| G01 - Coupling facility summary | 153 | Detail line hierarchy | 186 |
| Usage | 153 | Detail line descriptions | 187 |
| Facility summary | 154 | Sample reports | 193 |
| Sample reports | 154 | Line commands | 195 |
| G02 - Coupling facility mean times | 155 | Detail window | 195 |
| Usage | 155 | E06 - CICS service time by task ID | 197 |
| Quantification | 155 | Usage | 197 |
| Detail line hierarchy | 155 | Quantification | 197 |
| Detail line descriptions | 155 | Detail line hierarchy | 197 |
| Sample reports | 156 | Detail line descriptions | 198 |
| G03 - Coupling facility total times | 156 | Sample reports | 205 |
| Usage | 156 | Line commands | 206 |
| Quantification | 156 | Detail window | 207 |
| Detail line hierarchy | 156 | E07 - CICS wait by Txn | 207 |
| Detail line descriptions | 156 | Usage | 207 |
| Sample reports | 157 | Quantification | 207 |
| V01 - Measurement variance summary | 157 | Detail line hierarchy | 208 |
| Usage | 157 | Detail line descriptions | 208 |
| Measurements analyzed | 157 | Sample reports | 208 |
| Variances | 157 | Line commands | 209 |
| Sample reports | 159 | E08 - CICS mean service time by terminal ID. | 209 |
| | | Usage | 209 |
| | | Quantification | 209 |
| | | Detail line hierarchy | 210 |
| | | Detail line descriptions | 210 |
| | | Sample reports | 215 |
| | | Line commands | 216 |
| | | Detail window | 216 |
| | | E09 - CICS total service time by terminal ID | 218 |

Chapter 4. CICS performance analysis reports 161

| | |
|---|-----|
| Overview of CICS data extractor | 161 |
| Session statistics | 162 |
| Transaction measurement data. | 162 |
| CICS+ Extractor | 162 |
| Overview of CICS Multiple Address Space Support | 162 |

| | |
|--|-----|
| Usage | 218 |
| Quantification | 218 |
| Detail line hierarchy | 218 |
| Detail line descriptions | 219 |
| Sample reports | 224 |
| Line commands | 224 |
| Detail window | 225 |
| E10 - CICS mean service time by user ID | 227 |
| Usage | 227 |
| Quantification | 227 |
| Detail line hierarchy | 227 |
| Detail line descriptions | 228 |
| Sample reports | 233 |
| Line commands | 233 |
| Detail window | 234 |
| E11 - CICS total service time by user ID | 235 |
| Usage | 235 |
| Quantification | 235 |
| Detail line hierarchy | 235 |
| Detail line descriptions | 236 |
| Sample reports | 240 |
| Line commands | 241 |
| Detail window | 242 |
| E12 - CICS CPU/service time by transaction | 242 |
| Usage | 242 |
| Quantification | 243 |
| Detail line hierarchy | 243 |
| Detail line descriptions | 243 |
| Sample reports | 244 |
| Line commands | 244 |
| Detail window | 245 |
| X01 - CICS mean service time by transaction | 245 |
| Usage | 245 |
| Quantification | 245 |
| Detail line hierarchy | 246 |
| Detail line descriptions | 246 |
| Sample reports | 251 |
| Line commands | 251 |
| Detail window | 252 |
| X02 - CICS total service time by txn | 253 |
| Usage | 253 |
| Quantification | 253 |
| Detail line hierarchy | 253 |
| Detail line descriptions | 254 |
| Sample reports | 259 |
| Line commands | 259 |
| Detail window | 260 |
| X03 - CICS mean service time by terminal ID | 261 |
| Usage | 261 |
| Quantification | 261 |
| Detail line hierarchy | 261 |
| Detail line descriptions | 262 |
| Sample reports | 268 |
| Line commands | 268 |
| Detail window | 269 |
| X04 - CICS total service time by terminal ID | 269 |
| Usage | 269 |
| Quantification | 270 |
| Detail line hierarchy | 270 |
| Detail line descriptions | 270 |
| Sample reports | 276 |

| | |
|-------------------------|-----|
| Line commands | 276 |
| Detail window | 277 |

Chapter 5. IMS performance analysis reports 279

| | |
|--|-----|
| Overview of IMS data extractor | 280 |
| IMS+ extractor | 280 |
| Overview of IMS Multiple Address Space Support | 280 |
| I01 - IMS measurement profile. | 281 |
| Usage | 281 |
| IMS environment | 281 |
| Performance graphs | 281 |
| Transaction statistics | 283 |
| Sample reports | 284 |
| I02 - IMS DL/I call timeline | 284 |
| Usage | 284 |
| Quantification | 285 |
| Detail line hierarchy | 285 |
| Detail line descriptions | 285 |
| Sample reports | 285 |
| Line commands | 286 |
| I03 - IMS transaction timeline | 286 |
| Usage | 286 |
| Quantification | 286 |
| Detail line hierarchy | 286 |
| Detail line descriptions | 286 |
| Sample reports | 287 |
| Line commands | 288 |
| I04 - IMS transaction activity timeline | 288 |
| Usage | 288 |
| Quantification | 288 |
| Detail line descriptions | 288 |
| Sample reports | 289 |
| Line commands | 289 |
| Detail lines for reports I05 through I13 | 289 |
| Detail lines reported for PSW sampling. | 290 |
| I05 - IMS DL/I CPU usage by PSB | 293 |
| Usage | 293 |
| Quantification | 294 |
| Detail line hierarchy | 294 |
| Detail line descriptions | 294 |
| Sample reports | 295 |
| Line commands | 295 |
| Detail window | 296 |
| I06 - IMS DL/I CPU usage by transaction | 297 |
| Usage | 297 |
| Quantification | 297 |
| Detail line hierarchy | 298 |
| Detail line descriptions | 298 |
| Sample reports | 299 |
| Line commands | 299 |
| Detail window | 300 |
| I07 - IMS DL/I CPU usage by DL/I call | 301 |
| Usage | 301 |
| Quantification | 301 |
| Detail line hierarchy | 301 |
| Detail line descriptions | 301 |
| Sample reports | 302 |
| Line commands | 302 |
| Detail window | 303 |
| I08 - IMS DL/I WAIT time by PSB | 304 |

| | | | |
|---|-----|--|-----|
| Usage | 304 | Line commands | 326 |
| Quantification | 304 | Detail window | 327 |
| Detail line hierarchy | 304 | I17 - IMS transaction DL/I call counts | 327 |
| Detail line descriptions | 305 | Usage | 327 |
| Sample reports | 305 | Quantification | 327 |
| Line commands | 305 | Detail line hierarchy | 327 |
| Detail window | 306 | Detail line descriptions | 327 |
| I09 - IMS DL/I WAIT time by transaction | 307 | Sample reports | 328 |
| Usage | 307 | Line commands | 328 |
| Quantification | 307 | Detail window | 329 |
| Detail line hierarchy | 308 | I18 - IMS CPU/Svc time by DL/I calls | 329 |
| Detail line descriptions | 308 | Usage | 329 |
| Sample reports | 309 | Quantification | 329 |
| Line commands | 309 | Detail line hierarchy | 329 |
| Detail window | 310 | Detail line descriptions | 329 |
| I10 - IMS DL/I WAIT time by DL/I call | 310 | Sample reports | 330 |
| Usage | 310 | Line commands | 330 |
| Quantification | 310 | Detail window | 331 |
| Detail line hierarchy | 311 | I19 - IMS CPU/Svc time by PSB | 331 |
| Detail line descriptions | 311 | Usage | 331 |
| Sample reports | 311 | Quantification | 331 |
| Line commands | 311 | Detail line hierarchy | 331 |
| Detail window | 312 | Detail line descriptions | 331 |
| I11 - IMS DL/I activity by PSB | 313 | Sample reports | 332 |
| Usage | 313 | Line commands | 332 |
| Quantification | 313 | Detail window | 332 |
| Detail line hierarchy | 313 | I20 - IMS CPU/Svc time by transaction. | 333 |
| Detail line descriptions | 314 | Usage | 333 |
| Sample reports | 314 | Quantification | 333 |
| Line commands | 314 | Detail line hierarchy | 333 |
| Detail window | 316 | Detail line descriptions | 333 |
| I12 - IMS DL/I activity by transaction | 316 | Sample reports | 334 |
| Usage | 316 | Line commands | 334 |
| Quantification | 316 | Detail window | 334 |
| Detail line hierarchy | 316 | I21 - IMS CPU/Svc time by PCB | 335 |
| Detail line descriptions | 317 | Usage | 335 |
| Sample reports | 318 | Quantification | 335 |
| Line commands | 318 | Detail line hierarchy | 335 |
| Detail window | 319 | Detail line descriptions | 335 |
| I13 - IMS DL/I activity by DL/I call. | 320 | Sample reports | 336 |
| Usage | 320 | Line commands | 336 |
| Quantification | 320 | Detail window | 336 |
| Detail line hierarchy | 320 | | |
| Detail line descriptions | 320 | | |
| Sample reports | 321 | | |
| Line commands | 321 | | |
| Detail window | 322 | | |
| I14 - IMS PSB/PCB attributes | 323 | | |
| Usage | 323 | | |
| Detail line descriptions | 323 | | |
| Sample reports | 324 | | |
| I15 - IMS DL/I call attributes | 324 | | |
| Usage | 324 | | |
| Detail line descriptions | 324 | | |
| Sample reports | 325 | | |
| I16 - IMS transaction service times | 325 | | |
| Usage | 325 | | |
| Quantification | 326 | | |
| Detail line hierarchy | 326 | | |
| Detail line descriptions | 326 | | |
| Sample reports | 326 | | |

| | |
|--|------------|
| Chapter 6. DB2 performance analysis reports | 339 |
| Overview of DB2 data extractor | 340 |
| The DB2+ data extractor. | 340 |
| Measuring DDF activity | 340 |
| Displaying SQL Statement Text | 341 |
| SQL statement sequence numbers | 342 |
| Overview of DB2 Multiple Address Space Support | 342 |
| F01 - DB2 measurement | 343 |
| Usage | 343 |
| Performance graphs | 343 |
| Most Active DB2 Plans | 343 |
| Most active package/DBRMs | 343 |
| Most active SQL statements | 343 |
| Most CPU consumptive SQL | 344 |
| Most frequent SQL statements. | 344 |
| Single SQL call service time | 344 |
| DB2 measurement statistics. | 344 |

| | | | |
|--|-----|--|-----|
| Sample reports | 345 | Line commands | 370 |
| F02 - DB2 SQL activity timeline | 347 | SETUP options | 371 |
| Usage | 347 | F10 - DB2 SQL CPU/Svc time by DBRM | 371 |
| Quantification | 347 | Usage | 371 |
| Detail line hierarchy | 347 | Quantification | 371 |
| Detail line descriptions | 347 | Detail line descriptions | 372 |
| Sample reports | 348 | Sample reports | 373 |
| Line commands | 349 | Line commands | 373 |
| Detail window | 349 | SETUP options | 374 |
| F03 - DB2 SQL activity by DBRM. | 350 | F11 - DB2 SQL CPU/Svc time by stmt | 374 |
| Usage | 350 | Usage | 374 |
| Quantification | 350 | Quantification | 374 |
| Detail line hierarchy | 351 | Detail line hierarchy | 375 |
| Detail line descriptions | 351 | Detail line descriptions | 375 |
| Sample reports | 352 | Sample reports | 376 |
| Line commands | 352 | Line commands | 376 |
| Detail window | 353 | SETUP options | 377 |
| SETUP options | 353 | F12 - DB2 SQL CPU/Svc time by plan | 377 |
| F04 - DB2 SQL activity by statement. | 354 | Usage | 377 |
| Usage | 354 | Quantification | 378 |
| Quantification | 354 | Detail line hierarchy | 378 |
| Detail line hierarchy | 354 | Detail line descriptions | 378 |
| Detail line descriptions | 354 | Sample reports | 379 |
| Sample reports | 355 | Line commands | 380 |
| Line commands | 355 | SETUP options | 381 |
| Detail window | 356 | F13 - DB2 SQL threads analysis | 381 |
| SETUP options | 357 | Usage | 381 |
| F05 - DB2 SQL activity by plan | 357 | Quantification | 381 |
| Usage | 357 | Detail line hierarchy | 381 |
| Quantification | 357 | Detail line descriptions | 381 |
| Detail line hierarchy | 358 | Sample reports | 382 |
| Detail line descriptions | 358 | F14 - DB2 CPU by plan/stored proc. | 382 |
| Sample reports | 358 | Usage | 382 |
| Line commands | 359 | Quantification | 382 |
| Detail window | 360 | Detail line hierarchy | 382 |
| SETUP options | 360 | Detail line descriptions | 383 |
| F06 - DB2 SQL statement attributes | 360 | Sample reports | 384 |
| Usage | 360 | Line commands | 384 |
| Sample reports | 362 | SETUP options | 385 |
| F07 - DB2 SQL wait time by DBRM | 363 | F15 - DB2 SQL CPU/Svc Time by Rq Loc | 386 |
| Usage | 363 | Usage | 386 |
| Quantification | 363 | Quantification | 386 |
| Detail line hierarchy | 363 | Detail line hierarchy | 386 |
| Detail line descriptions | 363 | Detail line descriptions | 386 |
| Sample reports | 364 | Sample reports | 387 |
| Line commands | 365 | Line commands | 388 |
| SETUP options | 365 | SETUP options | 389 |
| F08 - DB2 SQL wait time by statement | 366 | F16 - DB2 SQL CPU/Svc Time by Enclave. | 389 |
| Usage | 366 | Usage | 389 |
| Quantification | 366 | Quantification | 389 |
| Detail line hierarchy | 366 | Detail line hierarchy | 389 |
| Detail line descriptions | 367 | Detail line descriptions | 390 |
| Sample reports | 367 | Sample reports | 391 |
| Line commands | 367 | Line commands | 391 |
| SETUP options | 368 | SETUP options | 392 |
| F09 - DB2 SQL wait time by plan. | 368 | F17 - DB2 SQL CPU/Svc Time by Corrid | 392 |
| Usage | 368 | Usage | 392 |
| Quantification | 369 | Quantification | 393 |
| Detail line hierarchy | 369 | Detail line hierarchy | 393 |
| Detail line descriptions | 369 | Detail line descriptions | 393 |
| Sample reports | 370 | Sample reports | 394 |

| | |
|--|-----|
| Line commands | 395 |
| SETUP options | 396 |
| F18 - DB2 SQL CPU/Svc Time by Wkstn | 396 |
| Usage | 396 |
| Quantification | 396 |
| Detail line hierarchy | 397 |
| Detail line descriptions | 397 |
| Sample reports | 398 |
| Line commands | 399 |
| SETUP options | 399 |
| F19 - DB2 SQL CPU/Svc Time by EndUsr | 400 |
| Usage | 400 |
| Quantification | 400 |
| Detail line hierarchy | 400 |
| Detail line descriptions | 400 |
| Sample reports | 401 |
| Line commands | 402 |
| SETUP options | 403 |
| DB2 EXPLAIN report | 403 |
| Usage | 403 |
| Field descriptions | 404 |
| Sample reports | 404 |
| Line commands | 405 |
| Detail window | 405 |
| DB2SQL category in C01 report | 406 |

Chapter 7. MQSeries performance analysis reports 409

| | |
|--|-----|
| Overview of MQSeries data extractor | 409 |
| Q01 - MQSeries activity summary | 410 |
| Usage | 410 |
| Detail line descriptions | 410 |
| Sample reports | 412 |
| Q02 - MQSeries CPU usage by queue | 412 |
| Usage | 412 |
| Quantification | 412 |
| Detail line hierarchy | 412 |
| Detail line descriptions | 412 |
| Sample reports | 413 |
| Line commands | 413 |
| Detail window | 414 |
| Q03 - MQSeries CPU usage by request | 415 |
| Usage | 415 |
| Quantification | 415 |
| Detail line descriptions | 415 |
| Sample reports | 416 |
| Line commands | 416 |
| Detail window | 416 |
| Q04 - MQSeries CPU usage by Txn | 417 |
| Usage | 417 |
| Quantification | 417 |
| Detail line hierarchy | 417 |
| Detail line descriptions | 417 |
| Sample reports | 418 |
| Line commands | 419 |
| Detail window | 420 |
| Q05 - MQSeries service time by queue | 420 |
| Usage | 420 |
| Quantification | 420 |
| Detail line hierarchy | 420 |
| Detail line descriptions | 420 |

| | |
|--|-----|
| Sample reports | 421 |
| Line commands | 421 |
| Detail window | 422 |
| Q06 - MQSeries service time by request | 423 |
| Usage | 423 |
| Quantification | 423 |
| Detail line hierarchy | 423 |
| Detail line descriptions | 423 |
| Sample reports | 424 |
| Line commands | 424 |
| Detail window | 425 |
| Q07 - MQSeries service time by Txn | 425 |
| Usage | 425 |
| Quantification | 425 |
| Detail line hierarchy | 425 |
| Detail line descriptions | 426 |
| Sample reports | 427 |
| Line commands | 427 |
| Detail window | 428 |
| Q08 - MQSeries wait time by queue | 428 |
| Usage | 428 |
| Quantification | 428 |
| Detail line hierarchy | 428 |
| Detail line descriptions | 429 |
| Sample reports | 429 |
| Line commands | 430 |
| Detail window | 430 |
| Q09 - MQSeries wait time by request | 431 |
| Usage | 431 |
| Quantification | 431 |
| Detail line hierarchy | 431 |
| Detail line descriptions | 431 |
| Sample reports | 432 |
| Line commands | 432 |
| Detail window | 433 |
| Q10 - MQSeries wait time by Txn | 433 |
| Usage | 433 |
| Quantification | 434 |
| Detail line hierarchy | 434 |
| Detail line descriptions | 434 |
| Sample reports | 435 |
| Line commands | 435 |
| Detail window | 436 |

Chapter 8. Java/USS/HFS performance analysis reports 437

| | |
|---|-----|
| Overview of Java data extractor | 438 |
| Java Version Support | 438 |
| Considerations for Java V5 and V6 | 438 |
| USS multiple address space measurements | 439 |
| J01 - Java summary and attributes | 439 |
| Usage | 439 |
| Sample reports | 441 |
| J04 - Java CPU usage by package | 441 |
| Usage | 441 |
| Quantification | 441 |
| Detail line hierarchy | 442 |
| Detail line descriptions | 442 |
| Sample reports | 443 |
| Line commands | 443 |
| Detail window | 444 |

| | | | |
|--|-----|---|-----|
| J05 - Java CPU usage by class | 444 | Sample reports | 467 |
| Usage | 444 | Line commands | 467 |
| Quantification | 444 | Detail window | 468 |
| Detail line hierarchy | 444 | J15 - Java wait time by class | 468 |
| Detail line descriptions | 445 | Usage | 468 |
| Sample reports | 446 | Quantification | 468 |
| Line commands | 446 | Detail line hierarchy | 468 |
| Detail window | 447 | Detail line descriptions | 469 |
| J06 - Java CPU usage by method | 447 | Sample reports | 470 |
| Usage | 447 | Line commands | 470 |
| Quantification | 447 | Detail window | 471 |
| Detail line hierarchy | 448 | J16 - Java wait time by method | 471 |
| Detail line descriptions | 448 | Usage | 471 |
| Sample reports | 448 | Quantification | 471 |
| Line commands | 449 | Detail line hierarchy | 472 |
| Detail window | 449 | Detail line descriptions | 472 |
| J07 - Java CPU usage by call path | 450 | Sample reports | 472 |
| Usage | 450 | Line commands | 473 |
| Quantification | 450 | Detail window | 473 |
| Detail line hierarchy | 450 | J17 - Java wait time by call path | 474 |
| Detail line descriptions | 451 | Usage | 474 |
| Sample reports | 451 | Quantification | 474 |
| Line commands | 451 | Detail line hierarchy | 474 |
| Detail window | 452 | Detail line descriptions | 475 |
| J09 - Java service time by package | 453 | Sample reports | 475 |
| Usage | 453 | Line commands | 475 |
| Quantification | 453 | Detail window | 476 |
| Detail line hierarchy | 453 | H01 - HFS Service Time by Path Name | 477 |
| Detail line descriptions | 454 | Usage | 477 |
| Sample reports | 455 | Quantification | 477 |
| Line commands | 455 | Detail line descriptions | 477 |
| Detail window | 456 | Sample reports | 478 |
| J10 - Java service time by class | 456 | Line commands | 478 |
| Usage | 456 | Detail window | 478 |
| Quantification | 456 | SETUP options | 479 |
| Detail line hierarchy | 457 | H02 - HFS Service Time by Device | 479 |
| Detail line descriptions | 457 | Usage | 479 |
| Sample reports | 458 | Quantification | 479 |
| Line commands | 458 | Detail line hierarchy | 480 |
| Detail window | 459 | Detail line descriptions | 480 |
| J11 - Java service time by method | 459 | Sample reports | 480 |
| Usage | 459 | Line commands | 481 |
| Quantification | 459 | Detail window | 481 |
| Detail line hierarchy | 460 | SETUP options | 482 |
| Detail line descriptions | 460 | H03 - HFS File Activity | 482 |
| Sample reports | 461 | Usage | 482 |
| Line commands | 461 | Quantification | 482 |
| Detail window | 462 | Detail line descriptions | 482 |
| J12 - Java service time by call path | 462 | Sample reports | 483 |
| Usage | 462 | Line commands | 483 |
| Quantification | 462 | Detail window | 483 |
| Detail line hierarchy | 463 | SETUP options | 484 |
| Detail line descriptions | 463 | H04 - HFS File Attributes | 484 |
| Sample reports | 464 | Usage | 484 |
| Line commands | 464 | Detail line descriptions | 484 |
| Detail window | 465 | Sample reports | 485 |
| J14 - Java wait time by package | 465 | H05 - HFS Device Activity | 485 |
| Usage | 465 | Usage | 485 |
| Quantification | 465 | Quantification | 485 |
| Detail line hierarchy | 465 | Detail line descriptions | 486 |
| Detail line descriptions | 466 | Sample reports | 486 |

| | |
|--|-----|
| Line commands | 486 |
| Detail window | 486 |
| SETUP options | 487 |
| H06 - HFS Device Attributes | 487 |
| Usage | 487 |
| Detail line descriptions | 487 |
| Sample reports | 488 |
| H07 - HFS Activity Timeline | 488 |
| Usage | 488 |
| Quantification | 488 |
| Detail line descriptions | 488 |
| Sample reports | 489 |
| Line commands | 489 |
| Detail window | 489 |
| SETUP options | 490 |
| H08 - HFS Wait Time by Path Name | 490 |
| Usage | 490 |
| Quantification | 490 |
| Detail line descriptions | 490 |
| Sample reports | 491 |
| Line commands | 491 |
| Detail window | 491 |
| SETUP options | 492 |
| H09- HFS Wait Time by Device | 492 |
| Usage | 492 |
| Quantification | 492 |
| Detail line hierarchy | 492 |
| Detail line descriptions | 493 |
| Sample reports | 493 |
| Line commands | 493 |
| Detail window | 494 |
| SETUP options | 494 |
| H10- HFS Service Time by Request | 495 |
| Usage | 495 |
| Quantification | 495 |
| Detail line hierarchy | 495 |
| Detail line descriptions | 495 |
| Sample reports | 496 |
| Line commands | 496 |
| Detail window | 497 |
| SETUP options | 497 |
| H11- HFS Wait Time by Request | 497 |
| Usage | 497 |
| Quantification | 497 |
| Detail line hierarchy | 498 |
| Detail line descriptions | 498 |
| Sample reports | 498 |
| Line commands | 499 |
| Detail window | 499 |
| SETUP options | 500 |

Chapter 9. Quick start guide for compiling and assembling programs for use with IBM Problem

| | |
|---|------------|
| Determination Tools products | 501 |
| Updating your build process | 502 |
| Updating your promotion process | 503 |
| Preparing your programs | 503 |
| Enterprise COBOL for z/OS Version 4 programs | 504 |

| | |
|--|-----|
| Enterprise COBOL for z/OS Version 3 and COBOL for OS/390 and VM programs | 507 |
| COBOL for MVS and VM programs | 510 |
| VS COBOL II programs, when the module is linked with Language Environment runtime services | 513 |
| VS COBOL II programs, when the module is not linked with Language Environment runtime services | 516 |
| OS/VS COBOL programs | 517 |
| Enterprise PL/I Version 3.5 and later programs | 520 |
| Enterprise PL/I Version 3.4 and earlier programs | 525 |
| PL/I for MVS and VM and OS PL/I programs | 529 |
| z/OS XL C and C++ programs | 532 |
| Assembler programs | 539 |

Chapter 10. Source program mapping 543

| | |
|--|-----|
| Introduction to source program mapping | 543 |
| A01 - Source program mapping panel | 545 |
| Overview | 545 |
| File specification input area | 546 |
| List of existing SPM file associations | 547 |
| Line commands | 547 |
| A011 - Source program mapping pick list | 548 |
| Overview | 548 |
| Field descriptions | 548 |
| Pick list description | 549 |
| A04 - Source mapping dataset list | 549 |
| Overview | 549 |
| Match on Compile Date & Time description | 550 |
| Dataset list description | 550 |
| Commands to save and edit | 551 |
| A03 - Java source program mapping panel | 551 |
| Overview | 551 |
| File prefix specification input area | 552 |
| Detail lines | 552 |
| Line commands | 552 |
| Java report detail window | 553 |
| P01 - Source program attribution | 553 |
| Overview | 553 |
| Code segments | 555 |
| Detail line descriptions | 555 |
| SETUP options | 556 |
| Detail window | 557 |
| P03 - USS Source Program Attribution | 557 |
| Overview | 557 |
| Detail line descriptions | 558 |
| SETUP options | 559 |
| P04 - USS Source Lines | 560 |
| Overview | 560 |
| Detail line descriptions | 560 |
| Line commands | 561 |
| Detail window | 561 |

Chapter 11. Printing reports and creating XML documents 563

| | |
|--|-----|
| About Application Performance Analyzer's report printing and XML document feature. | 563 |
| Line printer format | 563 |

| | |
|--|-----|
| PDF format | 564 |
| XML document format | 564 |
| Report sections | 564 |
| Using the ISPF report request facility | 564 |
| Specifying formatting options | 565 |
| The JCL submission/EDIT dialog. | 566 |
| Source program mapping | 568 |
| Preparing JCL to print reports or create XML documents | 568 |
| The input measurement file | 570 |
| The CAZLOG log file | 570 |
| The report output file | 570 |
| The PDF output file | 570 |
| The XML document file | 570 |
| Specifying control statements | 571 |
| General syntax rules | 571 |
| The PROFILE statement | 571 |
| The MAP statement | 572 |
| The SECTION statement. | 572 |
| The PRINT statement. | 573 |
| The CONVERT statement | 573 |
| Reports in PDF format | 574 |
| Reports in XML document format | 574 |
| Report SECTION descriptions | 575 |
| SECTION statement parameter summary | 575 |
| SECTION parameter descriptions. | 582 |

Chapter 12. Batch interface commands 587

| | |
|---|-----|
| Command syntax | 587 |
| Example of NEW command | 587 |
| Example of TNEW command | 588 |
| Example of DELETE command | 588 |
| Example of KEEP command | 588 |
| Example of CANCEL command | 588 |
| Command summary diagram | 588 |
| Sample JCL | 590 |
| Using the API to submit a command | 590 |
| Environment | 591 |
| Input registers | 591 |
| Output registers | 591 |
| Syntax. | 592 |
| Parameters | 592 |
| Return codes | 592 |
| Reason codes | 593 |
| Abend code | 594 |
| Command descriptions | 595 |
| NEW | 595 |
| TNEW. | 602 |
| DELETE | 603 |
| KEEP | 603 |
| CANCEL. | 603 |
| Batch import | 603 |

Chapter 13. Realtime Monitor 605

| | |
|--|-----|
| Auto-refresh mode | 605 |
| Monitor views | 605 |
| ACCUM and CURRENT modes | 605 |
| SETUP command | 605 |
| View 1. Measurement overview | 606 |

| | |
|---|-----|
| Measurement progress | 606 |
| System resource usage | 607 |
| DB2 activity | 607 |
| CICS transactions | 608 |
| View 2. CPU utilization | 608 |
| CPU activity. | 609 |
| CPU usage distribution | 610 |
| CPU modes | 611 |
| View 3. Measurement environment | 614 |
| Request parameters | 614 |
| Measurement environment | 615 |
| View 4. CPU active modules | 616 |
| Overall CPU activity | 616 |
| Current | 616 |
| Module attribution | 617 |
| View 5. Data mgmt service time | 617 |

Chapter 14. Application Performance Analyzer Graphical User Interface (GUI). 619

| | |
|---|-----|
| Getting started with the Application Performance Analyzer GUI | 619 |
| System requirements | 620 |
| Communications | 620 |
| Logon dialog | 621 |
| Select STC dialog | 622 |
| Main menu bar. | 623 |
| Main toolbar | 626 |
| Preferences | 626 |
| General preferences | 626 |
| Workspace preferences | 628 |
| Help preferences | 629 |
| Logging/debug preferences | 630 |
| Network connections preferences. | 632 |
| Report download options preferences | 633 |
| Status line | 634 |
| List navigation | 635 |
| Expand all | 635 |
| Collapse all | 635 |
| Home | 635 |
| Backward | 635 |
| Forward | 636 |
| View navigation | 636 |
| STC list view | 636 |
| Context menu | 637 |
| STC Properties view | 637 |
| Observations List view | 638 |
| Toolbar | 639 |
| Refresh observations | 640 |
| Filter observations. | 640 |
| Search observations | 640 |
| New observation | 641 |
| New threshold observation. | 654 |
| Context menu | 656 |
| Observation Detail view. | 661 |
| Observation Reports List view. | 662 |
| Toolbar | 664 |
| Context menu | 664 |
| Report Options view | 664 |
| Context menu | 666 |

| | |
|---|-----|
| Report views | 666 |
| Accelerator keys | 668 |
| Toolbar | 668 |
| Print | 669 |
| Save As | 669 |
| Find | 670 |
| Copy | 671 |
| Close report | 672 |
| Close all reports | 672 |
| Context menu | 672 |
| Search Results view | 674 |
| Help Search view | 675 |
| Adjustments for large reports | 676 |

Appendix A. Support resources and problem solving information 679

| | |
|--|-----|
| Searching knowledge bases | 679 |
| Searching the information center | 679 |
| Searching product support documents | 679 |
| Getting fixes | 681 |
| Subscribing to support updates | 681 |
| RSS feeds and social media subscriptions | 681 |
| My Notifications | 681 |
| Contacting IBM Support | 682 |
| Define the problem and determine the severity of the problem | 683 |
| Gather diagnostic information | 684 |
| Submit the problem to IBM Support | 684 |

Appendix B. Creating side files using CAZLANGX 687

| | |
|--|-----|
| CAZLANGX parameters | 689 |
| Parameters | 690 |
| Side file compatibility with Debug Tool for z/OS | 690 |
| Including a CAZLANGX step in your SCLM translator | 690 |
| High Level Assembler SCLM example | 690 |
| COBOL SCLM example | 691 |
| COBOL Report Writer Precompiler | 692 |
| Required compiler options for creating listings or CAZLANGX side files | 692 |
| TEST option considerations | 694 |
| Naming compiler listings or side files | 694 |
| Naming CSECTs for Application Performance Analyzer | 694 |
| Compiler listings and side file attributes | 695 |

Appendix C. XML document layout 697

| | |
|---|-----|
| XML declaration | 697 |
| Root tag | 697 |
| Layout standards | 697 |
| Measurement information | 697 |
| Performance analysis reports | 698 |
| S01 Measurement Profile | 698 |
| S02 Load Module Attributes | 704 |
| S03 Load Module Summary | 705 |
| S04 TCB Summary | 705 |
| S05 Memory Usage Timeline | 706 |
| S06 Data Space Usage Timeline | 706 |
| S07 TCB Execution Summary | 706 |

| | |
|---|-----|
| S08 Processor Utilization Summary | 707 |
| S09 Measurement Analysis | 707 |
| C01 CPU Usage by Category | 707 |
| C02 CPU Usage by Module | 709 |
| C03 CPU Usage by Code Slice | 710 |
| C04 CPU Usage Timeline | 710 |
| C05 CPU Usage by Task/Category | 711 |
| C06 CPU Usage by Task/Module | 713 |
| C07 CPU Usage by Procedure | 714 |
| C08 CPU Usage Referred Attribution | 714 |
| C09 CPU Usage by PSW/Object Code | 715 |
| W01 WAIT Time by Task/Category | 716 |
| W02 WAIT Time by Task/Module | 718 |
| W03 WAIT Referred Attribution by Task | 719 |
| W04 WAIT Time by Task ENQ/RESERVE | 720 |
| W05 WAIT Time by Tape DDNAME | 720 |
| D01 DASD Usage Time by Device | 720 |
| D02 DASD Usage Time by DDNAME | 721 |
| D03 DASD Usage Time by Dataset | 721 |
| D04 Dataset Attributes | 722 |
| D05 DASD EXCP Summary | 725 |
| D06 DASD VSAM Statistics | 725 |
| D07 DASD Activity Timeline | 726 |
| D08 DASD I/O Wait Time | 726 |
| D09 VSAM Buffer Pool Usage | 727 |
| G01 Coupling Facility Statistics | 728 |
| G02 Coupling Facility Mean Service Times | 728 |
| G03 Coupling Facility Total Service Times | 729 |
| V01 Measurement Variance Summary | 729 |
| CICS Performance analysis reports | 731 |
| E01 CICS Session Statistics | 731 |
| E02 CICS CPU and Use Counts by Pgm | 732 |
| E03 CICS CPU Usage by Transaction | 732 |
| E04 CICS Mean Service Time by Txn | 734 |
| E05 CICS Total Service Time by Txn | 736 |
| E06 CICS Total Service Time by Task ID | 738 |
| E07 CICS Wait by Txn | 740 |
| E08 CICS Mean Service Time by Termid | 740 |
| E09 CICS Total Service Time by Termid | 742 |
| E10 CICS Mean Service Time by User ID | 744 |
| E11 CICS Total Service Time by User ID | 747 |
| E12 CICS CPU/Service Time by Transaction | 749 |
| X01 CICS Mean Service Time by Txn | 749 |
| X02 CICS Total Service Time by Txn | 751 |
| X03 CICS Mean Service Time by Term | 753 |
| X04 CICS Total Service Time by Term | 756 |
| IMS Performance analysis reports | 758 |
| I01 IMS Measurement Profile | 758 |
| I02 IMS DL/I Call Timeline | 760 |
| I03 IMS Transaction Timeline | 761 |
| I04 IMS Transaction Activity Timeline | 761 |
| I05 to I13 | 762 |
| I14 IMS PSB/PCB Attributes | 764 |
| I15 IMS DL/I Call Attributes | 765 |
| I16 IMS Transaction Service Times | 765 |
| I17 IMS Transaction DL/I Call Counts | 766 |
| I18 IMS CPU/Service Time by DL/I Call | 766 |
| I19 IMS CPU/Service Time by PSB | 767 |
| I20 IMS CPU/Service Time by Transaction | 767 |
| I21 IMS CPU/Service Time by PCB | 767 |
| DB2 Performance analysis reports | 768 |

| | | | |
|--|-----|---|------------|
| F01 DB2 Measurement profile | 768 | H06 HFS Device Attributes | 793 |
| F02 DB2 SQL Activity Timeline | 770 | H07 HFS Activity Timeline | 794 |
| F03 SQL Activity by DBRM. | 770 | H08 HFS Wait Time by Path Name | 794 |
| F04 SQL Activity by Statement | 771 | H09 HFS Wait Time by Device | 794 |
| F05 SQL Activity by Plan | 771 | H10 HFS Service Time by Request | 795 |
| F06 DB2 SQL Statement Attributes | 772 | H11 HFS Wait Time by Request | 795 |
| F07 SQL WAIT Time by DBRM | 773 | MQSeries Performance analysis reports. | 796 |
| F08 SQL WAIT Time by Statement | 773 | Q01 MQSeries Activity Summary. | 796 |
| F09 SQL WAIT Time by Plan | 774 | Q02 MQSeries CPU Usage by Queue | 796 |
| F10 SQL CPU/Service Time by DBRM | 775 | Q03 MQSeries CPU Usage by Request | 797 |
| F11 SQL CPU/Service Time by Statement | 775 | Q04 MQSeries CPU Usage by Txn/Queue. | 797 |
| F12 SQL CPU/Service Time by Plan. | 776 | Q05 MQSeries Service Time by Queue | 798 |
| F13 DB2 Threads Analysis | 777 | Q06 MQSeries Service Time by Request | 798 |
| F14 DB2 CPU by Plan/Stored Proc | 777 | Q07 MQSeries Service Time by Txn/Queue | 799 |
| F15 DB2 SQL CPU/Svc Time by Rq Loc | 779 | Q08 MQSeries Wait Time by Queue | 799 |
| F16 DB2 SQL CPU/Svc Time by Enclave | 780 | Q09 MQSeries Wait Time by Request | 800 |
| F17 DB2 SQL CPU/Svc Time by Corrid | 781 | Q10 MQSeries Wait Time by Txn/Queue | 800 |
| F18 DB2 SQL CPU/Svc Time by Wkstn | 782 | Source Program Attribution | 801 |
| F19 DB2 SQL CPU/Svc Time by EndUsr | 783 | P01 Source Program Attribution | 801 |
| Java/USS/HFS Performance analysis reports. | 783 | Appendix D. Accessibility | 803 |
| J01 Java Summary/Attributes | 783 | Using assistive technologies | 803 |
| J04 Java CPU Usage by Package | 784 | Keyboard navigation of the user interface | 803 |
| J05 Java CPU Usage by Class | 785 | Accessibility of this document. | 803 |
| J06 Java CPU Usage by Method | 786 | Appendix E. Notices | 805 |
| J07 Java CPU Usage by Call Path. | 786 | Trademarks | 805 |
| J09 Java Service Time by Package. | 786 | Glossary | 807 |
| J10 Java Service Time by Class. | 787 | Bibliography. | 809 |
| J11 Java Service Time by Method | 788 | IBM Application Performance Analyzer for z/OS | |
| J12 Java Service Time by Call Path | 788 | documents | 809 |
| J14 Java Wait Time by Package | 788 | Documents for related products | 809 |
| J15 Java Wait Time by Class | 789 | Index | 811 |
| J16 Java Wait Time by Method. | 790 | | |
| J17 Java Wait Time by Call Path | 790 | | |
| H01 HFS Service Time by Path Name | 791 | | |
| H02 HFS Service Time by Device. | 791 | | |
| H03 HFS File Activity | 791 | | |
| H04 HFS File Attributes | 792 | | |
| H05 HFS Device Activity | 793 | | |

About this document

This document describes IBM Application Performance Analyzer for z/OS, Version 10 Release 1 plus the following PTFs:

| PTF (English) | for APAR | Date |
|---------------|----------|--------------|
| UK53837 | PM03857 | January 2010 |
| UK56111 | PM05497 | April 2010 |
| UK58288 | PM15384 | August 2010 |

| PTF (Japanese) | for APAR | Date |
|----------------|----------|--------------|
| UK53838 | PM03857 | January 2010 |
| UK56112 | PM05497 | April 2010 |
| UK58289 | PM15384 | August 2010 |

| PTF (Korean) | for APAR | Date |
|--------------|----------|--------------|
| UK53839 | PM03857 | January 2010 |
| UK56113 | PM05497 | April 2010 |
| UK58290 | PM15384 | August 2010 |

For the latest Application Performance Analyzer PTF information, see <http://www.ibm.com/software/awdtools/apa/support/>.

Appendix A contains information about IBM Web sites that can help you answer questions and solve problems.

IBM® Application Performance Analyzer is an application program performance measurement tool for use on z/OS® systems. This document describes how to use Application Performance Analyzer to measure the performance of z/OS applications.

If you need to install Application Performance Analyzer, refer to the *Application Performance Analyzer Program Directory* for installation instructions.

Documentation conventions

The following table describes typographical conventions used throughout this document:

| Convention | Explanation |
|-----------------|--|
| boldface | Indicates a command or keyword that you should type exactly as shown. |
| <i>italics</i> | Indicates a variable for which you should substitute an appropriate value. |
| monotype | Indicates literal input and output. |

| Convention | Explanation |
|-------------------|---|
| Ctrl + D | Indicates two or more keys pressed simultaneously. |
| [] | Brackets surround an optional value. |
| | Vertical bars separate alternative values from which you must make a selection. |
| ... | Ellipsis indicates that the preceding element can be repeated. |

Summary of changes

Changes introduced with IBM Application Performance Analyzer V10.1

- A Windows GUI is included that provides a workstation interface to create sample requests and view reports like those available via the host ISPF interface.
- Support is provided for multiple DB2 address spaces. Specific stored procedures and user-defined functions can be measured without knowing the WLM region in which they will execute. Additionally, a new data extractor will measure collateral DB2 activity in stored procedures and user-defined functions that are invoked from another measured job.
- Support is provided for measuring multiple IMS MPP regions. A specific IMS transaction in a single IMS subsystem can be measured when it is eligible to execute in multiple MPP regions.
- Support is provided for multiple CICS address spaces. Multiple CICS regions can be measured simultaneously, and transaction data from these regions merged to produce a set of CICS reports showing multi-region activity.
- The Application Performance Analyzer sample file size is reduced through compression.
- The user import of sample files is externalized so that sample files can be moved from one instance of Application Performance Analyzer to another.
- A new setup option is added to the S02 Load Module Attributes report, to eliminate repeating program attributes.
- Additional System z Integrated Information Processor (zIIP) and System z Application Assist Processor (zAAP) reporting is provided, to permit users to determine the utilization of these processors for the sampled applications.
- The dataspace sizes used during sampling and reporting are provided in the S01 Measurement Profile report.
- Additional DASD information is provided in the D04 Dataset Attributes report and DASD pop-up detail windows to display average times, total I/Os, cache and write statistics.
- An installation option is provided to make the sampling request description a mandatory field.
- An installation option is provided to display the default number of samples and the default sample duration on NEW observation requests.
- New installation options are provided to limit the amount of data collected by the DB2 and IMS intercepts. This provides a means of controlling the volume of data reported in the DB2 and IMS timeline reports, while continuing to collect the data required for other reports.
- Support for Java virtual machine V5 is provided.
- Currency support for IBM IMS V11 and IBM CICS Transaction Server (CICS TS) V4.1 is provided.

Chapter 1. Using Application Performance Analyzer/ISPF

Application Performance Analyzer/ISPF is the main interface to Application Performance Analyzer. It is used for submitting new observation requests, and for navigating the Performance Analysis Reports generated from observation requests. This chapter describes the Application Performance Analyzer/ISPF environment in general, how to submit observation requests, and how to navigate the reports.

Almost all panels in Application Performance Analyzer/ISPF are implemented as interactive reports. The first screen displayed when entering Application Performance Analyzer, "Observation Session List" follows the same rules and conventions as the Performance Analysis Reports.

| For information about ... | See ... |
|--|--|
| Commands used to navigate ISPF reports. | "ISPF reports: navigation and control" |
| Application Performance Analyzer's main entry panel: the observation session list. | "R02 - Observation session list" on page 8 |
| Accessing and using the performance reports menu. | "R01 - Application Performance Analyzer performance reports menu" on page 12 |

ISPF reports: navigation and control

You navigate and control Application Performance Analyzer/ISPF reports using two types of commands:

- Primary commands - commands that you type on the command line
- Line commands - commands that you type directly in input fields in the body of the report

Scrolling

The vertical and horizontal scrolling commands you are familiar with from using most ISPF applications are applicable when viewing Application Performance Analyzer reports. Use UP and DOWN (PF7 and PF8) to scroll towards the top and the bottom of the report. You can scroll Maximum, Half, a specific number of lines and by cursor position.

Similarly, use LEFT and RIGHT (PF10 and PF11) to scroll the report horizontally.

Report headings

Many reports present information in a tabular format in rows and columns. The table begins with one or more heading lines, which contain title fields for each of the columns. These heading lines will "lock" to the top of the report viewing area and the vertical scrolling commands will affect only the data lines.

Action (menu) bar

Report navigation primary commands can be displayed by selecting "Navigate" on the action bar menu or can be typed directly on the command line. The action bar menu can be removed from the display by entering the PREF command, and de-selecting the "Action Bar Visible" option.

Retaining open reports

Once you have opened and viewed reports, they can be retained for later viewing. Application Performance Analyzer provides this feature so that multiple reports (from multiple observation requests, if desired) can be readily available for viewing without re-generating the reports. You can navigate through all the open reports using the WIN and JUMP (PF4) commands. Reports are retained when you exit them using the CANCEL (PF12) command.

Displaying HELP

For information about the report currently being displayed, position the cursor in the body of the report (not on an input field), and press PF1. Pressing PF1 on an input field will display specific information about that field.

Primary commands for report navigation

The following is a list of the commands used to navigate reports and explanations for using them:

WIN You can use the WIN (WINdow) command to display a selection list of open reports in a pop-up panel. From that panel, you can make a selection to jump to the selected report. The main Observation Session List panel will be the report listed at the top of the selection list, so you can use WIN to quickly get back to this panel rather than navigating through all your open reports.

JUMP (PF4)

You can use the JUMP command, or the PF4 key, to jump to another open report. Each time you issue a JUMP request, Application Performance Analyzer will skip to the next open report, on a rotating basis.

END (PF3)

Use the END command, or the PF3 key, to return to the display of the previous report — the one from which the current report was launched. The END command will close (delete) the current report. Entering END from the Report Selection Menu will exit the Application Performance Analyzer Performance Reporting Facility.

CANCEL (PF12)

Use the CANCEL command, or the PF12 key, to return to the display of the previous report — the one from which the current report was launched. The CANCEL command will leave the current report open. You can return to it any time using the JUMP or WIN command. Entering CANCEL from the Report Selection Menu will exit the Application Performance Analyzer Performance Reporting Facility.

REPORT CODE

Once you have selected an observation session, you can enter a three character report code, even if you are not in the report menu. You can be viewing one report, and can immediately open an additional report by typing its code.

UP (PF7)

Use the UP command, or press PF7, to scroll vertically towards the top of the report.

DOWN (PF8)

Use the DOWN command, or press PF8, to scroll vertically towards the bottom of the report.

LEFT (PF10)

Use the LEFT command, or press PF10, to scroll the report horizontally to the left.

RIGHT (PF11)

Use the RIGHT command, or press PF11, to scroll the report horizontally to the right.

FIND The FIND command (abbreviation "F" can be used) finds all occurrences of a text string. It is similar to an ISPF FIND command, but does not have all the features. All occurrences of the target text string will be highlighted. To remove the highlights, enter the RESET command.

RESET

The RESET command removes the highlights set by the FIND command.

PREF Use this to set preferences for General Display Settings. Put a slash "/" beside an option to select it. The available options are:

1. Action bar visible on panels
2. Use 3270 graphic characters
3. Show long descriptions on multiple lines
4. Suppress use of special +/- character

CONNECT

Only available on the R02 Observation Session List screen. If your installation has multiple Application Performance Analyzer instances running, you can change which one your ISPF session is connected to by typing CONNECT followed by the Application Performance Analyzer identifier. You can use the VER command to view which Application Performance Analyzer instances are currently running on the same z/OS image that you are logged in to.

VERSION

Only available on the R02 Observation Session List screen. Type VERSION or VER and a list of the Application Performance Analyzer started tasks will be displayed, along with their version numbers, and when they were started.

SETUP

Use the SETUP command to filter information and select options for reports. This command is useful for reducing the size of reports by removing information that is not critical. The options available using the SETUP command vary by report. You can get more details from the report descriptions.

HIDE Only available on the R02 Observation Session List screen. Type HIDE to remove the list of commonly used Application Performance Analyzer primary commands from view.

SHOW

Only available on the R02 Observation Session List screen. Type SHOW to redisplay the list of commonly used Application Performance Analyzer primary commands at the top of the screen.

IMPORT

Only available in the R02 Observation Session List screen. Use the IMPORT

command to load a sample file. This can be a native Application Performance Analyzer sample file or one that has been previously exported using the EXP command and in TSO XMIT format. The IMPORT command displays a pop-up window to enter the fully qualified data set name of the native sample file or TSO XMIT file, and to indicate if that original file is to be deleted after import. A new request description can be optionally entered.

During IMPORT, Application Performance Analyzer creates a new observation, assigns a new request number and if provided on the IMPORT pop-up window, adds the description to the imported observation. If indicated, Application Performance Analyzer will delete the original file. The date and time of the imported request is set to the current date and time and the expiry date is recalculated based on the rules of the importing system.

Line commands for report navigation

You enter a line command directly in an input field in the body of a report. The line commands are usually typed directly over the text of the field, such as a column heading, or a data field in the report. Input fields where you can enter line commands are always underlined.

Many of Application Performance Analyzer's performance analysis reports contain input fields on which you can enter various line commands. Generally, you can enter line commands on quantified detail lines on the field under the "Name" heading.

The allowable line commands vary depending on the type of detail line. But, in all cases by entering "/" you can request the display of a Context Menu, which will present a list of the allowable line commands for that input field. The generally available line commands are summarized here, followed by details about each command.

- / Display context menu
- ? Display context help information
- + Expand
- ++ Show additional details (or just press the Enter key as a shortcut)
- – Collapse
- SV Sort by value
- SN Sort by name

"/" Context menu

Enter a slash "/" to display a context menu in a pop-up panel. The context menu lists the line commands that are available for that field. In addition, you are able to select the line command function directly from the context menu.

A sample context menu is shown below:

Enter S to select a function from this menu. The line command (Yellow) can also be entered on the main panel.

| <u>Sel</u> | <u>To Perform the Following</u> | <u>LineCmd</u> |
|------------|---|----------------|
| _ | display context help information | ? |
| _ | show additional details about this line | ++ |
| _ | expand to reveal next level entries | + |
| _ | collapse to hide next level entries | - |
| _ | sort next level entries by value | SV |
| _ | sort next level entries by name | SN |

“?” HELP

For context help information about the field, or report line, enter a question mark “?”. Alternatively, you can press the PF1 key with the cursor positioned on the input field.

“+” Expand

Enter a plus sign “+” on a report detail line to expand the report to reveal additional detail lines which are at the next hierarchical level under the selected line. This offers a means of breaking down one quantified item into greater detail.

For example, consider the following line item which quantifies CPU time in System/OS Services:

| | | | |
|---------------|--------------------|-------|-------|
| <u>SYSTEM</u> | System/OS Services | 44.30 | ===== |
|---------------|--------------------|-------|-------|

Type a plus sign in the name field – SYSTEM:

| | | | |
|----------------|--------------------|-------|-------|
| <u>±SYSTEM</u> | System/OS Services | 44.30 | ===== |
|----------------|--------------------|-------|-------|

Press the ENTER key and the item will be expanded as illustrated here:

| | | | |
|------------------|--------------------|-------|-------|
| <u>SYSTEM</u> | System/OS Services | 44.30 | ===== |
| → <u>SVC</u> | SVC Routines | 42.14 | ===== |
| → <u>MVS</u> | MVS System | 2.06 | == |
| → <u>NUCLEUS</u> | Nucleus Modules | 0.06 | |
| → <u>IMS</u> | IMS Subsystem | 0.03 | |

The plus sign (+) entered on the Name heading field will fully expand the entire report to show the full hierarchy of detail.

The plus sign (+) entered on the Description heading will expand the width of the description field. The plus sign (+) entered on the heading for the scale (histogram) will 'zoom in' the scale.

You can also use this line command in the “+n” format, where “n” is the number of levels to expand. On the Description heading, this allows you to expand the width of the description field by a specific number of characters, for example “+12” will widen the field by 12 characters.

“++” Additional details

Enter “++” on a report detail line to display detailed information about the selected item. A pop-up panel will appear in which this information is displayed. The nature of the information displayed in these pop-up panels varies widely depending on the type of item selected.

Note: As a shortcut, you can also simply press the Enter key on an item, it will be treated as if you had entered “++”.

As an example, consider the I/O Analysis by DDNAME report:

```
File View Navigate Help
-----
D02: DASD Usage Time by DDNAME (0723/TSTJOB01) Row 00001 of 00003
Command ==> _____ Scroll ==> CSR

DDName>Cyl Volume>Unit Percent of Time * 10.00% ±1.6%
*...1...2...3...4...5...6...7...8..
VSAM1-02 BKNSM2 31.16 =====
OUTFILE BKNSM2 1.16 ==
INFILE BKNSM1 0.05
```

Additional detail about the DDNAME VASM1-02, for example, can be displayed by typing ++ (or just pressing Enter) in that field:

```
File View Navigate Help
-----
D02: DASD Usage Time by DDNAME (0723/TSTJOB01) Row 00001 of 00003
Command ==> _____ Scroll ==> CSR

DDName>Cyl Volume>Unit Percent of Time * 10.00% ±1.6%
*...1...2...3...4...5...6...7...8..
++AM1-02 BKNSM2 31.16 =====
OUTFILE BKNSM2 1.16 ==
INFILE BKNSM1 0.05
```

A pop-up panel with detailed information will appear. (This pop-up panel is scrollable, more information is available by scrolling down with PF8):

```

File View Navigate Help
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| VSAM1-02      BKNSM2      31.16 ===== |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+

Calculation Details
The 31.16% quantification represents 1,174 measurements
of DASD I/O unit activity for the DDNAME VSAM1-02 from
a total of 3767 overall measurements. This is the
percentage of the measured run time I/O
was observed for this dataset.

VSAM file VSAM1(2) OPENed at 9:36:17.72 Wednesday Mar 24 2004

DDNAME          VSAM1
Open Intent     KEY,DIR,OUT
Dataset Name    USER1.DATA.TESTPF.DAT
Storage Class   BKNSMS
Device Type     3390
% Free Bytes in CI  10%
Volume Serial   BKNSM2  CI Splits      0      0
CI Size        8,192  CA Splits      0      0
Record Size (LRECL) 80    Logical Records 1    3,641
Number of Extents  1    Deleted Records 0    1
SHAREOPTIONS    (1 3)  Insrted Records 0    0
Organization    KSDS   Retrved Records 0    1
CIs per CA     78    Updated Records 0    0
Free CIs per CA  11    Byter Free Space 1,908,736  1,622,016
Free Bytes per CI 819    Number of EXCPs  Z    Z,ZZZ
% Free CIs in CA  15%
Strings        1
DATA Buffers   0
INDEX Buffers  0

Index Component of VSAM1(2)

```

“-” Collapse

Enter a minus sign “-” on a report detail line to collapse (hide) all items under the selected line which are at the next hierarchical level of detail.

The minus sign entered on the Name heading field will collapse the entire report so that only items in the first level of the hierarchy are visible.

The minus sign entered on the Description heading will reduce the width of the description field.

The minus sign entered on the heading for the scale (histogram) will “zoom out” the scale.

“SV” Sort by Value

Enter “SV” to sort detail lines by value. When this is entered on a detail line, detail lines under the selected line – at the next hierarchical level – will be sorted by value. Entering the “SV” command repeatedly will toggle between sorting in descending and ascending values.

Enter “SV” on the 'Name' heading field to sort the first level items by value.

“SN” Sort by Name

Enter “SN” to sort detail lines by name. When this is entered on a detail line, detail lines under the selected line — at the next hierarchical level — will be sorted by name.

Entering the "SN" command repeatedly will toggle between sorting in descending and ascending names. Enter "SN" on the "Name" heading field to sort the first level items by name.

Note: The line commands listed above are not a comprehensive list of all that are available in the various reports. See the documentation for each report, or enter a "/" to get a context menu in any input field in any report.

R02 - Observation session list

When you start Application Performance Analyzer/ISPF, the Observation Session List panel is displayed. A list of commonly used primary commands is displayed at the top of the screen to assist those users new to Application Performance Analyzer. Once you become familiar with the Observation Session List, these commands can be hidden from view by entering the HIDE primary command. They can be redisplayed by entering the SHOW primary command.

This panel displays a scrollable list of all the observation session requests, whether they are complete, active, or pending. The list is usually filtered by the owner ID, so each user would only see their own requests. The list can also be filtered by Job Name. The SETUP command is used to specify how the list is to be filtered.

Note: Although it is not started from the Report Selection Menu, the Observation Session List panel is implemented as a report, and, therefore, follows the same conventions as the Performance Analysis Reports panels.

A sample Observation Session List panel is shown here:

```

File View Navigate Help
-----
R02: Observation Session List (CAZ0)                               Row 00078 of 00810
Command ==>>> _____ Scroll ==>>> CSR

NEW      To define a new measurement
TNEW     To define a threshold measurement
CONNECT  To connect to another instance of the measurement task
VERSION  To display version information for all instances
IMPORT   To IMPORT a previously Exported sample file
HIDE     To remove these commands from the display (recommended)
/        On top of any ReqNum to get a list of the line commands

Reqnum  Owned By  Description          Job Name  Date/Time          Samples  Status
-----  -
1871    USER1      CICS22A             CICS22A   Jan-3 18:12         100     Ended
1870    USER1      CICS22A             CICS22A   Jan-3 18:11         100     Ended
1869    USER1      USER2               USER2     Jan-3 18:11        3,450   Cancel
1868    USER2      USER1               USER1     Jan-3 18:10        10,000  Ended
1867 +  USER1      repeat m-step a     CICS22A   Jan-3 18:07         100     STEPS
1866    USER1      USER1               USER1     Jan-3 18:08        10,000  Ended
1865 +  USER1      repeat m-step a     PFTEST11  Jan-3 17:55         100     STEPS
1864    USER1      USER1               USER1     Jan-3 17:56        10,000  Ended
1863 +  USER1      repeat m-step a     PFTEST11  Jan-3 17:54         100     STEPS
1862    USER1      USER1               USER1     Jan-3 17:54        10,000  Ended
1842    USER1      USER1               USER1     Jan-3 17:52        10,000  Ended
1803 +  USER1      repeat m-step a     PFTEST11  Jan-3 17:51         100     STEPS
1802    USER1      batch interface     USER1     Jan-3 17:46         5,000   Ended
1801    USER1      CICS22A             CICS22A   Jan-3 17:45         100     Cancel
1800    USER1      RT#2 (open/clos    PFTEST02  Jan-3 17:46        17,070  Cancel
1799    USER1      CICS22A             CICS22A   Jan-3 17:30         100     Ended
1798    USER1      CICS22A             CICS22A   Jan-3 17:30          1       Stoppd

```

This panel is used to initiate a new observation request, by using the “NEW” primary command, or the “NEW” line command (described in the next section). The “NEW” primary command and the “NEW” line command both cause the Schedule New Measurement panels to be displayed. For Threshold Monitor requests, use the “TNEW” primary command. For more information about Threshold Monitor requests, see “Using the TNEW command” on page 39.

This panel is also used to access the Reports menu, by entering the “R” line command on the request number for which you want to generate Performance Reports. The “NEW” and “R” commands are the most commonly used commands on this panel, and provide access to the primary functions of Application Performance Analyzer: submitting Observation Requests, and generating Performance Reports for a completed Observation Request.

Input fields

The inputs fields on this report are the ReqNum title field, and all the request number detail lines under it. The request number detail line input is described below in the section “Description of detail lines.”

You can type the following line commands directly on to the ReqNum title field:

- “?” Display context help information
- “SR” Sort report detail lines by Request Number
- “SJ” Sort report detail lines by Job Name
- “SD” Sort report detail lines by date/time

Description of detail lines

Each detail line shows the following information about the observation session:

Request Number

This is the unique four digit request number assigned to identify the observation session. This is also an input field which accepts line commands. Type the line command directly on top of the request number. If the request number has a “+” beside it, this indicates that there are subsequent entries underneath this one. The line commands accepted in the Request Number field are as follows:

- “/” Display context menu.
- “?” Display context help information.
- “++” Show additional details about this request in a pop-up window. As with all reports, you can also press the Enter key instead.
- “+” Expand to reveal next level entries. This is used for multi-step, repeat schedule, USS, threshold and collateral DB2 requests. When there is next level entries available, a “+” will appear beside the request number.
- “-” Collapse to hide next level entries.
- “D” Delete the request.
- “R” Display performance analysis reports menu for this request, or start Realtime Monitor if request is currently active. When entered for parent observations of multi-step, repeat schedule, USS and threshold measurements, this will expand to reveal next level entries.
- “S” Select Reports or Realtime Monitor. When entered for parent observations of multi-step, repeat schedule, USS and threshold measurements, this will expand to reveal next level entries.

"T" Tag up to 20 measurements at one time. Tagged measurements are used for variance reporting and CICS multiple address space reporting. For variance reporting, use the "T" line command together with the "V" line command, which you use to indicate the base measurement and launch variance reporting. For CICS multiple address space reporting, use the "T" line command together with the "R" line command, which you use to launch reporting for one of the CICS regions. In addition to the standard CICS reports, the specific CICS multiple address space reports are generated.

Note: Tagged measurements remain tagged only for the duration of the session.

"TR" Create a new request to be Triggered when this request starts. This can only be used on a request that is in SCHED status.

"V" Launch performance analysis reporting in a mode that enables access to variance reports. Use the "V" line command to compare a measurement previously tagged with a "T" line command. The measurement selected by the "V" line command is the base measurement in variance reports.

Note:

The report menu will be displayed in response to the "V" line command.

CAN Cancel the request (request must be active).

KEEP Keep this request until it is manually deleted. This overrides the auto delete feature.

MOD Modify the request (request must not have started yet).

NEW Create new observation request with the same attributes as this request.

The NEW line command will display the Schedule New Measurement panel with the input fields pre-filled with entries from the request on which "NEW" was typed. If you want an empty Schedule New Measurement panel, use the "NEW" primary command.

SUB Create a new observation request with the same attributes as this request and submit it immediately. You use "SUB" instead of the "NEW" line command when you do not need to view or change any of the fields in the original request.

EXP Export the sample file for this request to a file in XMIT format.

Owned By

This is the User ID of the "owner" of the request (the TSO ID of the user who created the request).

Description

This is the descriptive name of the observation session that was entered (optionally) when the request was made.

Job Name

This is the name of the job (or Started Task or TSO ID) that was measured.

Date/Time

This indicates the date and time of the completion of the measurement. If the measurement is not yet complete, the date and time when the request was made is shown.

Samples

If the session has a status of Ended or Active this is the number of observation samples done. If the observation session has not yet started (a status of "Sched" or "Future") then this shows the number of observation samples requested. This field changes color depending on the status.

Status

This shows the status of the observation session:

- **Active** means the session is currently taking place.
- **Cancel** means the request was cancelled using the "CAN" line command.
- **Ended** means the session has completed.
- **Ended+** means the session has completed, but this request will repeat if the target job runs again. This happens when the "Times to repeat measurement" field is specified, and the specified interval has not yet passed. Once the specified interval passes, the status will change to "Ended."
- **Failed** means the request failed to complete normally, and did not create a valid sample file.
- **REPEAT** means that this is a repeating schedule request. The requests under this entry can be displayed by using the "+" line command to expand to the next level.
- **Sched** means the session has been scheduled but measurement has not yet been started.
- **STEPS** means that this is a multi-step request. The requests under this entry can be displayed by using the "+" line command to expand to the next level.
- **Stoppd** means the request was stopped for some reason, usually a CPU Usage control issue, look at report S01 and check for the CPU Usage Status field. It will be present if the request was stopped due to CPU Usage controls. You can also use the "++" (or Enter key) line command directly on the request number field, and a reason will be shown in the detail window.
- **Tagged** means that this measurement has been tagged (with the "T" line command) for use in variance reports or CICS multiple address space reports.
- **Thresh** means that this is a Threshold Monitor request. The request under this entry can be displayed by using the "+" line command to expand to the next level.
- **Trig** means this request will be triggered when the corresponding scheduled request starts.
- **USS** means that this is a USS environment measurement. A separate measurement file is created for each spawned address space. Enter the "+" line command to expand this item to see each completed measurement.
- **MultJb** means that this is a multiple job request, created by entering a jobname with wildcards specified. The measurements under this entry can be displayed by using the "+" line command to expand to the next level.

Detail window

You can enter "++" (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window is shown here:

```

File View Navigate Help
-----+-----
General
Request Number      1946
Request Description No Description entered
Request Status      Ended
Owner Id            USER1
Time of Request     Wednesday Jan 26 2005 11:01:57.13
Session Start Time Wednesday Jan 26 2005 11:01:57.29
Session End Time   Wednesday Jan 26 2005 11:02:57.50
Session Duration   1 minutes, 0.21 seconds
Session Delete Date Do not Delete

Measurement Criteria
Select by Job Name  CICS22A
Select by Sys Name X235
Sample Interval    6000 microseconds
Duration           60 seconds

Measurement Information
Sample File DSN    0.USER1.R1946.CICS22A.SF
Samples Requested  10,000
Samples Done       10,000
ASID               005A

Data Extractors
CICS                Selected
IMS                 Not Selected
IMS+                Not Selected
DB2                 Selected
DB2+                Selected
MQSeries            Not Selected
-----+-----

```

R01 - Application Performance Analyzer performance reports menu

This panel is displayed as a result of entering the “R” line command to a line in the Observation Session List panel. It enables you to display Performance Analysis Reports for the selection observation session.

There are two distinct areas on this screen. The first, at the top of the screen, shows you a list of report categories. One of these categories is always highlighted (selected). The area at the lower half of the panel lists the available reports belonging to the highlighted (selected) category.

You can change the report category and hence change the list of available reports, by selecting a category by entering “S” beside the category, or by simply entering the single character code on the command line. You can then select a report from the lower portion of the screen.

As a shortcut, you can select a report directly by entering its three-character code on the command line. Note that if you are selecting by report code, it is not necessary to select the category to which the report belongs first, you can enter any three-character report code regardless of which category is currently highlighted. As a shortcut, you can also enter a report code on the command line while viewing a report, and that report will be opened, so it is not necessary to return to the report menu.

The most recently selected category persists from one session to the next.

This example shows the screen with DB2® Measurement as the currently selected category, note that if reports do not apply to the selected measurement, they category will be displayed in red, and will not be selectable.

```

File View Navigate Help
-----
R01: Performance Reports (1910/TSTJOB01)                               Row 00001 of 00008
Command ==>> _____ Scroll ==>> CSR

Select a category from the list of the right to view the available reports in the selection list below.
      _ A Admin/Miscellaneous      _ I IMS Measurement
      _ S Statistics/Storage       _ E CICS Measurement
      _ C CPU Usage/Analysis       _ F DB2 Measurement
      _ D DASD I/O Analysis        _ Q MQ Measurement
      _ W CPU WAIT Analysis        _ G Coupling Facility
      _ H HFS Analysis             _ J Java Measurement
      _ V Variance Reports         _ X Multi Address Space

-----
Enter S to make a selection or enter the report code on the command line

_ F01 DB2 Measurement Profile      _ F11 DB2 SQL CPU/Svc Time by Stmt
_ F02 DB2 SQL Activity Timeline    _ F12 DB2 SQL CPU/Svc Time by Plan
_ F03 DB2 SQL Activity by DBRM     _ F13 DB2 SQL Threads Analysis
_ F04 DB2 SQL Activity by Statement _ F14 DB2 CPU by Plan/Stored Proc
_ F05 DB2 SQL Activity by Plan     _ F15 DB2 SQL CPU/Svc Time by Rq Loc
_ F06 DB2 SQL Statement Attributes _ F16 DB2 SQL CPU/Svc Time by Enclav
_ F07 DB2 SQL Wait Time by DBRM    _ F17 DB2 SQL CPU/Svc Time by Corrid
_ F08 DB2 SQL Wait Time by Statement _ F18 DB2 SQL CPU/Svc Time by Wkstn
_ F09 DB2 SQL Wait Time by Plan    _ F19 DB2 SQL CPU/Svc Time by EndUsr
_ F10 DB2 SQL CPU/Svc Time by DBRM

```

The individual reports are described in the chapter Chapter 3, “Performance analysis reports,” on page 43.

Chapter 2. Entering observation requests

This section describes how to enter Observation Requests (measurements).

| For information about ... | See ... |
|--|--|
| Initiating a new observation request | "Using the NEW command" |
| Entering job information | "Panel 1 – Job Information" on page 17 |
| Specifying data extractors (CICS®, DB2, IMS™, MQSeries®, Java) or entering additional load libraries to search | "Panel 2 – Options" on page 22 |
| Entering multi-step measurements | "Panel 3 – Multi-steps" on page 26 |
| Selecting active jobs from a list | "Panel 4 – Active Jobs" on page 28 |
| Specifying CICS or IMS transactions or DB2 stored procedures or user-defined functions | "Panel 5 – Subsystems" on page 29 |
| Specifying Sysplex systems | "Panel 6 – Sysplex" on page 32 |
| Entering a recurring future scheduled measurement | "Panel 7 – Schedule" on page 32 |
| Additional options related to how the measurement is to be handled | "Panel 8 – Sched Options" on page 36 |

Entering an observation request

Using the NEW command

New observation requests are initiated from the Application Performance Analyzer Observation Session List panel (this is the panel where Application Performance Analyzer starts). You can use either the "NEW" primary command by entering it on the command line, or use the "NEW" line command by entering it on the request number field of an existing request. The "NEW" primary command will display the Schedule New Measurement panels with blank input fields. The "NEW" line command will display the Schedule New Measurement panels with the input fields pre-filled based on the existing request on which you typed the "NEW" command.

A sample Observation Session List panel with the "NEW" line command entered on the third request in the list is shown below.

```

File View Navigate Help
-----
R02: Observation Session List (0)
Command ==>> _____ Scroll ==>> CSR

```

| Reqnum | Owned By | Description | Job Name | Date/Time | Samples | Status |
|--------|----------|------------------|----------|--------------|---------|--------|
| 0200 | USER1 | CICS test 2 | CICS22A | May-30 14:15 | 5,000 | Ended |
| 0199 | USER1 | VSAM TEST | PFTEST03 | May-29 18:11 | 3,000 | Ended |
| NEW8 | USER1 | VSAM TEST | PFTEST03 | May-29 18:11 | 2,998 | Ended |
| 0197 | USER1 | | PFTEST03 | May-29 18:10 | 4,349 | Ended |
| 0196 | USER1 | | PFTEST03 | May-29 18:07 | 3,801 | Ended |
| 0195 | USER1 | Loop with open/c | PFTEST02 | May-28 18:08 | 20,000 | Ended |
| 0194 | USER1 | Loop with open/c | PFTEST02 | May-24 17:55 | 20,000 | Ended |
| 0193 | USER1 | Loop with open/c | PFTEST02 | May-24 17:56 | 5,000 | Ended |
| 0192 | USER1 | | USER1PF1 | May-22 17:54 | 3,019 | Ended |
| 0191 | USER1 | | USER1PF1 | May-22 17:54 | 10,000 | Ended |
| 0190 | USER1 | Loop with open/c | PFTEST02 | May-22 17:52 | 20,000 | Ended |
| 0189 | USER1 | Loop with open/c | PFTEST02 | May-20 17:51 | 20,000 | Ended |
| 0188 | USER1 | Loop with open/c | PFTEST02 | May-9 17:46 | 20,000 | Ended |
| 0187 | USER1 | PF05 | CICS22A | May-6 17:45 | 10,000 | Ended |
| 0186 | USER1 | | CICS22B | May-5 17:46 | 10,000 | Ended |
| 0183 | USER1 | 1000/60 | ARAOSHOW | Apr-30 17:30 | 1,000 | Ended |

Using the MOD line command

If you need to modify an existing measurement request, you can use the “MOD” line command. This only applies to measurements that are still pending, you cannot modify a request that is in progress or Ended. The “MOD” process uses exactly the same panels as the NEW process, so all the information in this chapter applies to “MOD” as well as “NEW”.

The “MOD” command can be used to modify future schedule requests, even if some of the generated future requests have run already.

Schedule New Measurement panels

After you have entered the “NEW” line command or “NEW” primary command, the Schedule New Measurement panel group is displayed.

The screens in the Schedule New Measurement dialog are divided into two sections. The top section is fixed and lists the available input panels. The current panel is highlighted. Each panel name is preceded by a symbol indicating if data has been entered to the panel. The symbol appears in green (green light) if data has been entered and is error free. A yellow or red light appears if there are warnings or errors in the data. The lower section of the screen is the input panel. It begins with an identifying heading.

Panel navigation

There are two methods you can use to JUMP from panel to panel:

- Type the panel number on the command line and press ENTER.
- Type a slash, immediately followed by the panel number in the first two positions of any input field.

These can be done in a single operation in combination with entry of input to the current panel. For example, you can enter input to Panel 1, place the cursor on the command line, type 2 and press ENTER. The entry to the Panel 1 input fields will be accepted and Panel 2 will appear. The same applies in this example if you type /2 in one of the data input fields. You must, of course, enter this on a field to which you are not specifying other input.

In some cases, automatic panel navigation occurs, for example, entering a jobname pattern will automatically take you to panel 4 to select from a list of active jobs based on that pattern.

Submitting the request

If you have entered enough data for a complete request to be submitted, “Input more data or ENTER to submit” will be displayed in the panel heading line. Pressing the ENTER key again will submit the request, unless you navigate to another panel to continue entering data.

There is a final confirmation prompt displayed before the request actually gets submitted. If you want to turn off this final confirmation prompt, use the SETUP command while you are in the R03 Schedule New Measurement dialog.

Primary commands

panel number

Enter a single-digit panel number to jump to that panel.

SUBMIT

Use SUBMIT to submit the request immediately and return control to the R02 panel.

JCL Use JCL to display the JCL and control statements that could be used to request the equivalent measurement request as a batch job using CAZBATCH.

SETUP options

Use the SETUP command to specify various options affecting this dialog:

Prompt for confirmation before submitting ...

By default, this option is selected. Indicate if the final confirmation prompt is to appear or is to be suppressed.

Prompt for confirmation before returning ...

By default, this option is selected. Normally a warning message will appear when the END command (or PF3) is issued after data has been input. This is to warn that the input data will be discarded. Unselect this option to suppress the warning.

Translate CICS trancode ...

By default, this option is selected. CICS transaction codes entered to Panel 5 will be translated to uppercase. Deselect this option to suppress this translation of lowercase characters.

Suppress warning flags ...

By default, this option is not selected. Select to suppress display of the yellow warning symbols that appear to the left of input fields indicating a warning condition.

Panel 1 – Job Information

The R03 Schedule New Measurement dialog always starts with panel 1 (Job Information) selected, it is shown here:

```

File View Navigate Help
-----
R03: Schedule New Measurement                               Row 00001 of 00019
Command ==> _____ Scroll ==> CSR

1. Job Information    3. Multi Steps    5. Subsystems    7. Schedule
2. Options           4. Active Jobs   6. Sysplex      8. Sched Options
-----
Panel 1. Job Information

Job Name/Pattern . . _____
                    (Inactive)

Step Specification
Step No. . . . . ____ Specify step number, program name,
Program Name . . . _____ step name or step name + Proc step
Step Name . . . . _____ name. Use panel 3 to specify more
ProcStepName . . . _____ than one step.

Description . . . . _____
Number of Samples . _____ Measure to step end . . . N
Duration (min:sec) . _____ Delay by (secs) . . . . ____
Notify TSO User . . _____ Retain file for (days) . 20
USS observations . . . . _____ Max. 20

```

The panel shown above was invoked with a NEW primary command, so input fields are mostly blank.

Panel 1 – input fields

Job Name/Pattern

This field is mandatory. It cannot be blank. Specify the name of the job, started task, or TSO region to be measured.

Searching for active jobs (*)

You can specify a job name pattern; for example, a job name prefix followed by an asterisk (*), a job name suffix preceded by an asterisk, or an asterisk by itself. The asterisk indicates that the region to be measured is currently active. A list of active jobs whose names match the wildcard pattern will be displayed in panel 4, where one or more can be selected for measurement.

Creating multi-job measurements (%)

You can specify wildcards in order to generate measurements for multiple jobs in one request. To sample multiple jobs in one request, use a percent (%) as a wild card character anywhere in the job name. Multiple percent characters may be used in the job name, such as %A%B% to sample any jobs with A and B in the job name separated by 0 to many characters. Panel 4 can be used to display the currently active jobs that will be sampled.

A job name pattern is only permitted in NEW or MOD requests. It is not valid for Threshold or Trigger requests. You can not specify a jobname pattern of "%". If a pattern is present in the jobname, then the request will automatically be set to only select active jobs.

The multiple job feature only works with jobs that are active. It does not wait for jobs to start. You can schedule a multiple job request to start at a future date and time by using panel 7 Schedule, but only one future event is permitted. The jobs that are active at the scheduled date and time (and matching the wildcard criteria) will be measured.

The maximum number of jobs that can be measured from a multi-job request is defined during the installation of Application Performance Analyzer. When this limit is exceeded, Application Performance Analyzer stops creating measurements for this request and the status of the request is displayed as 'Stoppd'. The measurements that executed (within the limit) are accessible for report viewing under the request. To increase the limit, contact your system programmer.

Obtaining DB2 DDF Data

To obtain DDF data, you must measure the DB2 DDF address space (xxxxDIST) with the DB2+ extractor turned on. For more information on measuring DDF activity, refer to "Measuring DDF activity" on page 340.

Measuring a specific DB2 stored procedure or user-defined function (-)

To measure a specific DB2 stored procedure or user-defined function, use a dash (-) as the first and only character in the Jobname/Pattern field. The information identifying the DB2 stored procedure or user-defined function must be entered on Panel 5. Subsystems. This feature is only available when the WLM Intercept is activated during Application Performance Analyzer installation, and you are given appropriate security access to it. Contact your system programmer for access if necessary. When measuring a specific DB2 stored procedure or user-defined function, the following measurement options are not applicable and will result in an error if used: Step specification/Multi Steps, Measure to step end, Delay by, Active Jobs, CICS and IMS selection criteria, Schedule and Schedule Options.

Measuring a specific IMS transaction across multiple MPP regions

To measure a specific IMS transaction that executes in multiple MPP regions, you must enter a dash (-) as the first and only character in the Jobname/Pattern field. The IMS subsystem name and IMS transaction name must be entered on Panel 5. Subsystems. You must also select the MPP regions you want to monitor in Panel 4. Active Jobs. When measuring a specific IMS transaction across multiple MPP regions, the following measurement options are not applicable and are ignored if used: Step specification/Multi Steps, Measure to step end, Delay by, Schedule and Schedule Options.

Active/Inactive indicator

When a NEW command is entered, Application Performance Analyzer checks for and displays the current status of the job, started task, or TSO region immediately below the jobname. When it is detected as active, 'Active' is displayed, otherwise, 'Inactive' is displayed. It is only necessary to use Panel 8 Sched Options if you wish to change the observation status from that detected by Application Performance Analyzer.

When more than one active job is selected for measurement in Panel 4, the phrase '(Active - Multiple Jobs Selected)' is displayed below the Jobname. In this case, the name listed is the first job selected in Panel 4. You must use Panel 4 to view or change the jobs that are selected for measurement.

System name

This field appears only if the Application Performance Analyzer you are

connected to is configured as a member in a SYSPLEX group. Specify the name of the system on which the measured job is to run (or is currently running). Specify an asterisk (*) in this field to indicate that the job could run on any of the systems in the group.

You can also select panel 6 to display a full list of available system names from which you can make a selection.

Step Specification Field Group

Step specification is not applicable when measuring specific DB2 stored procedures or user-defined functions.

The job step to be measured is specified by a group of four fields (Step Number, Step Program, Step Name, ProcStepName). To identify the step, you can specify one of the following:

- Step Number by itself
- Step Program by itself
- Step Name by itself
- Step Name and ProcStepName

If you leave all of these fields blank, the first job step is assumed. You cannot specify any of these fields when you are specifying measurement of a job that is currently active.

To schedule the measurement of multiple steps in the same job, select panel 3.

Step No.

If Step No. is specified, the other three step fields (Step Program, Step Name, and ProcStepName) must be left blank.

Step No. specifies the numeric step number.

Step Program

If Step Program is specified, the other three step fields (Step No., Step Name, and ProcStepName) must be left blank. Program Step specifies the name of the program coded in the PGM= parameter of the EXEC statement for the step you want to measure.

Step Name

If Step Name is specified, then Step Number, and Step Program must be left blank. You can specify Step Name by itself or in combination with ProcStepName.

Step Name specifies the symbol coded in the name field of an EXEC PGM = statement or an EXEC PROC = statement. In the event that the ProcStep name field is also supplied, this field always identifies the symbol coded in an EXEC PROC = statement.

In the event that the ProcStep name field is left blank, and Step Name matches an EXEC PROC = statement, the first step within that proc will be measured.

If the step to be measured is not within a proc, then Step Name specifies the symbol coded in the name field of an EXEC PGM = statement, and ProcStepName must not be specified.

ProcStepName

If ProcStepName is specified, then input must also be supplied in the Step Name field.

ProcStepName specifies the symbol coded in the name field of an EXEC PGM = statement that is part of a PROC.

Description

Enter a description for this observation request. This field is optional unless the option has been set during installation requiring a minimum description of 8 characters.

Number of Samples

Specify the number of times execution of the measured jobstep is to be sampled. Samples are taken in equal intervals. The sampling frequency is determined by dividing the number of samples by the specified measurement duration. If configured during installation, a default value will be displayed in this field for NEW and TNEW requests. An installation default value is used if you do not supply input in this field.

Note: This field is not used when sampling a DB2 DDF address space with the DB2+ extractor turned on, it will be ignored. In the case of DDF measurement, each SQL call is intercepted for the requested duration, no sampling takes place. The number of samples will always be converted to approximately one per second.

Measure to step end

This field is not applicable when measuring specific DB2 stored procedures or user-defined functions.

Specify 'Y' in this field to indicate that the measurement is to continue to the end of the step even if the specified number of samples has been recorded. Measurement will continue at the sampling rate calculated based on the specified duration and number of samples.

Duration (min:sec)

Specify the duration of the measurement. You can specify the value in seconds or in minutes and seconds. To specify the duration in minutes and seconds, separate the minutes value from the seconds value using a colon. If configured during installation, a default value will be displayed in this field for NEW and TNEW requests. An installation default value is used if you do not supply input in this field. Examples:

- 135 specifies 135 seconds
- 2:15 specifies 2 minutes and 15 seconds
- 2: specifies 2 minutes

The measurement will proceed for the specified time and the sampling rate will be established at a frequency that would perform the full number of samples for the specified duration.

The measurement will terminate before the duration ends if the job step ends first.

Delay by (secs)

This field is not applicable when measuring specific DB2 stored procedures or user-defined functions.

Specify a delay time, in seconds, to occur before initiation of the measurement. The delay will occur starting at the time execution of the job step begins. This cannot be specified for measurement of a job that is currently active.

Notify TSO User

Specify a TSO user ID to be notified upon completion of the measurement. Enter blanks in this field for no completion notification.

Retain file for (days)

Specify the number of days after completion of the measurement for which the measurement file is to be retained. The file and all information about the measurement will be deleted after this period. Enter blanks or zero in this field for no automatic deletion of the measurement data.

USS observations

Specify the maximum number of spawned address spaces or substeps to measure for a USS observation, up to the maximum defined in the system configuration. The same sampling frequency will be used for each spawned address space or substep. Sampling overhead can be high if several spawned address spaces are running simultaneously.

When this field is specified, the collection of measurements will be grouped under a USS master record on the Observation List panel.

Note: When you are deciding what values to enter in the Number of Samples and Duration fields, consider that Application Performance Analyzer does not have unlimited resources to store and report measurement data. Data spaces are used for collecting and reporting data. Extremely large amounts of measurement data can cause Application Performance Analyzer to fail in either the data collection or reporting process. Data space requirements for measurement data vary widely depending on the type of job or region being measured, data extractors selected, etc.

Panel 2 – Options

Panel 2 is used to enter extended measurement options (“Data Extractors”), and also to specify additional load libraries or HFS directories to be searched for external symbol information.

Enter a slash “/” beside each of the data extractors required for the measurement. The data extractors are used to measure additional information about CICS, DB2, IMS, Java™, MQSERIES and Adabas. When the CICS or IMS data extractor is specified, further transaction information can be specified in panel 5.

Panel 2 is show here:

```

File View Navigate Help
-----
R03: Schedule New Measurement                               Row 00001 of 00027
Command ==> _____ Scroll ==> CSR

o 1. Job Information    3. Multi Steps    5. Subsystems    7. Schedule
  2. Options            4. Active Jobs    6. Sysplex      8. Sched Options

Panel 2. Measurement Options

Data Extractors. /' to select extended measurement options:
CICS  CICS information          CICS+ CICS service/CPU time
DB2   SQL call information      DB2+  SQL service/CPU time/counts
CDB2  Collateral DB2 activity   DB2V  SQL Variables
IMS   DLI call information      IMS+  DLI service/CPU time/counts
Java  Java information          MQ    MQSeries call information
Ada   Adabas call information

Specify up to 10 load libraries, or up to 440 bytes of HFS directories, to
search for external symbol information. The load libraries apply only to
sampled modules that are fetched from dynamically allocated load libraries.
The directories apply only to sampled HFS programs that do not have absolute
path names. Enter multiple directories separated by at least one space.

_ Specify L for load libraries, D for directories

1  _____
2  _____
3  _____
4  _____
5  _____
6  _____
7  _____
8  _____

```

If your installation has configured Application Performance Analyzer to display the maximum number of trace entries for DB2+ and IMS+, two additional input fields are displayed in Panel 2 as shown here:

```

File View Navigate Help
-----
R03: Schedule New Measurement                               Row 00001 of 00027
Command ==> _____ Scroll ==> CSR

o 1. Job Information    3. Multi Steps    5. Subsystems    7. Schedule
  2. Options            4. Active Jobs    6. Sysplex      8. Sched Options

Panel 2. Measurement Options                               Input more data or ENTER to submit

Data Extractors. '/'to select extended measurement options:
- CICS CICS information      - CICS+ CICS service/CPU time
/ DB2 SQL call information   / DB2+ SQL service/CPU time/counts
- CDB2 Collateral DB2 activity - DB2V SQL Variables
/ IMS DLI call information   / IMS+ DLI service/CPU time/counts
- Java Java information      - MQ MQSeries call information
- Ada Adabas call information

50_ DB2+ Maximum number of trace entries in thousands
60_ IMS+ Maximum number of trace entries in thousands

Specify up to 10 load libraries, or up to 440 bytes of HFS directories, to
search for external symbol information. The load libraries apply only to
sampled modules that are fetched from dynamically allocated load libraries.
The directories apply only to sampled HFS programs that do not have absolute
path names. Enter multiple directories separated by at least one space.

_ Specify L for load libraries, D for directories

1  _____
2  _____
3  _____
4  _____
5  _____
6  _____
7  _____
8  _____
9  _____
10 _____

```

Panel 2 input fields

Data Extractors

Using a slash, select any of CICS, CICS+, CDB2, DB2, DB2+, DB2V, IMS, IMS+, MQ, Java or Adabas. This tells Application Performance Analyzer to measure additional data about CICS, DB2, IMS, MQSeries, Java, Adabas. When DB2+ is selected, DB2 is also included automatically. When IMS+ is selected, IMS is also included automatically. When either CDB2 or DB2V is selected, DB2 and DB2+ are also included automatically.

DB2+ and IMS+ are used to collect additional data about DB2 and IMS respectively, allowing exact call counts, service times, and CPU times to be measured and reported. DB2+ also ensures that SQL text reported is accurate, without DB2+ turned on, it is possible for the SQL text to be incorrect.

Note: Running Application Performance Analyzer measurements with the DB2+ or IMS+ data extractor turned on causes each DB2 or IMS call to be intercepted to collect additional data. This might have a small impact on the performance of the target address space. You should be careful when using these features with other products that also

intercept DB2 or IMS calls because unpredictable results might occur. Your installer might have chosen to limit access to this feature.

DB2V is used to turn on the DB2 variable extractor during the measurement. DB2V is a DB2 measurement option that will extract SQL variable names for sampled SQL calls. The variable names will then be substituted in place of the :H place holders when the SQL text is displayed.

CDB2 is used to turn on the collateral DB2 extractor during measurement. When the CDB2 data extractor is selected, Application Performance Analyzer measures DB2 activity in stored procedures and user-defined functions that are invoked as a result of this observation request. In the R02 Observation List, the collateral DB2 measurements are created separately and are grouped under this observation request. When CDB2 is specified, the DB2 and DB2+ options are automatically included.

Note: Running Application Performance Analyzer measurements with the CDB2 data extractor turned on causes each DB2 call and WLM call to be intercepted to collect additional data. This can have a small impact on the performance of the target address space. Your installer may have chosen to limit access to this feature. This feature is only available when the WLM Intercept is activated during Application Performance Analyzer installation, and you are given appropriate security access to it. Contact your system programmer for access if necessary.

The MQ data extractor provides the ability to observe/sample and report on MQSeries interface calls (both dynamic and static) in Batch, IMS and CICS application programs. This extractor is not used to measure the MQ address space itself. For more information on measuring MQ calls, refer to "Overview of MQSeries data extractor" on page 409.

CICS+ is used to collect additional data about CICS transactions, allowing exact transaction counts, service times and CPU times to be measured and reported. Your installer might have chosen to limit access to this data extractor.

If your installation has enabled Adabas in Application Performance Analyzer, you will see the Adabas extractor. If you select the Adabas extractor, data about Adabas calls is collected. There are no special Adabas reports. Adabas calls are reported under the ADABAS category in several reports. The C08 CPU Usage Referred Attribution report can also be used to see the Attribution offset for Adabas calls and to source map the program.

Maximum number of trace entries (DB2+ and IMS+)

These fields are displayed only when your installation has configured Application Performance Analyzer to display them. Otherwise, your installation default is used.

For DB2+, enter the value (in thousands) to limit the number of DB2+ SQL call interceptions for which full details will be written to the sample file. Collecting full details on every interception allows the F02 Timeline report to report exact times for all SQL calls. The F02 report will be truncated at the number of calls specified in this field. The DB2+ data extractor continues to collect the data it requires for the other reports for the duration of the measurement. The value is entered in thousands of calls to be recorded and cannot exceed the default value specified for

DB2IMaxTraceSize during Application Performance Analyzer installation. The default value is displayed in this field for NEW observation requests.

For IMS+, enter the value (in thousands) to limit the number of IMS+ DLI call interceptions for which full details will be written to the sample file. Collecting full details on every interception allows the I02 and I03 Timeline reports to report exact times for all DLI calls and IMS transactions. The I02 and I03 reports will be truncated at the number of calls specified in this field. The IMS+ data extractor continues to collect the data it requires for the other reports for the duration of the measurement. The value is entered in thousands of calls to be recorded and cannot exceed the default value specified for IMSIMaxTraceSize during Application Performance Analyzer installation. The default value is displayed in this field for NEW observation requests.

Specify L for load libraries, D for directories

Specify either L or D to indicate whether Application Performance Analyzer is to search load libraries or directories.

Libraries

Specify up to 10 load libraries to be searched by Application Performance Analyzer for external symbol information. These are applicable only when sampled modules are fetched from dynamically allocated load libraries. See “Specifying additional libraries” for more information.

Directories

Specify up to 440 bytes of HFS directory path names to be searched by Application Performance Analyzer, each separated by one or more spaces. These are applicable only when sampled HFS programs have relative path names.

Specifying additional libraries

It is sometimes necessary to specify additional libraries for Application Performance Analyzer to use to resolve sampled addresses to CSECT plus offset, instead of load module plus offset.

When one program issues a LOAD or LINK macro to fetch other load modules, they are typically loaded from STEPLIB or JOBLIB or a LINKLIST library. In this case Application Performance Analyzer will find them automatically during sampling.

However, the LOAD macro can be coded to reference a DCB for which a load library was OPENed. The library might have been allocated to a temporary DDNAME and after the LOAD is done, the DCB is closed and the DDNAME released. In this situation, Application Performance Analyzer has no way of determining what load library the module came from. Hence, it is unable to get CSECT (EBE) information. This would prevent such modules from being source mapped.

Panel 3 – Multi-steps

This panel is not applicable when measuring specific DB2 stored procedures or user-defined functions.

Panel 3 is used to specify that multiple job steps are to be measured. You can specify up to 20 steps, using the same specification rules described for single step measurements entered on panel 1. For more information, see “Panel 3 input fields” on page 27.

Panel 3 is shown here. In this example, three steps have been selected by StepName.

```
File View Navigate Help
-----
R03: Schedule New Measurement                      Row 00001 of 00021
Command ==>>> _____ Scroll ==>>> CSR

o 1. Job Information    3. Multi Steps    5. Subsystems    7. Schedule
o 2. Options           4. Active Jobs    6. Sysplex      8. Sched Options

-----
Panel 3. Measure Multiple Steps

Enter data here to measure multiple steps. Separate measurement files will
be produced for each step. '*' in the first StepNo selects all steps.

StepNo Program  StepName ProcStep    StepNo Program  StepName ProcStep
-----
  _____  _____  _____  _____  _____  _____  _____  _____
  _____  _____  IDC01      _____  _____  _____  _____  _____
  _____  _____  PGM0005   _____  _____  _____  _____  _____
  _____  _____  _____  _____  _____  _____  _____  _____
  _____  _____  _____  _____  _____  _____  _____  _____
  _____  _____  _____  _____  _____  _____  _____  _____
  _____  _____  _____  _____  _____  _____  _____  _____
  _____  _____  _____  _____  _____  _____  _____  _____
  _____  _____  _____  _____  _____  _____  _____  _____
```

Panel 3 input fields

Each step specification has a group of four fields. These four fields follow exactly the same rules as the step fields in panel 1.

Step Specification Field Group

The job step to be measured is specified by a group of four fields (Step Number, Step Program, Step Name, ProcStepName). To identify the step, you can specify one of the following:

- Step Number by itself
- Step Program by itself
- Step Name by itself
- Step Name and ProcStepName

Step No.

If Step No. is specified, the other three step fields (Step Program, Step Name, and ProcStepName) must be left blank.

Step No. specifies the numeric step number. Specify an asterisk (*) in the first Step No. field to indicate that all steps in the job are to be measured.

Step Program

If Step Program is specified, the other three step fields (Step No., Step Name, and ProcStepName) must be left blank.

Program Step specifies the name of the program coded in the PGM = parameter of the EXEC statement for the step you want to measure.

Step Name

If Step Name is specified, then Step Number, and Step Program must be left blank. You can specify Step Name by itself or in combination with ProcStepName.

Step Name specifies the symbol coded in the name field of an EXEC PGM = statement or an EXEC PROC = statement. In the event that the ProcStep name field is also supplied, this field always identifies the symbol coded in an EXEC PROC = statement.

In the event that the ProcStep name field is left blank, and Step Name matches an EXEC PROC = statement, the first step within that proc will be measured.

If the step to be measured is not within a PROC, then Step Name specifies the symbol coded in the name field of an EXEC PGM = statement, and ProcStepName must not be specified.

ProcStepName

If ProcStepName is specified, then input must also be supplied in the Step Name field.

ProcStepName specifies the symbol coded in the name field of an EXEC PGM = statement that is part of a PROC.

Panel 4 – Active Jobs

Panel 4 is used to select active jobs from a list. You can enter a Prefix to limit the jobs listed. If you enter a Pattern in the Job name/Pattern field in panel 1, this will be entered as the Prefix in panel 4. This is an input field, you can change the prefix while in panel 4.

Panel 4 is shown here. In this example the prefix entered is "C*".

```

File View Navigate Help
-----
R03: Schedule New Measurement                               Row 00001 of 00019
Command ==>> _____ Scroll ==>> CSR

o 1. Job Information  o 3. Multi Steps    5. Subsystems    7. Schedule
o 2. Options          4. Active Jobs      6. Sysplex      8. Sched Options

Panel 4. Active Jobs

Enter S to select an active job step to be measured.  Prefix . . C*_____

JobName  Type  JobId    StepName  ASIDX  System  CPU%  SIO
CATALOG  STC   N/A      CATALOG   0020   X235    0.00  0.00
CICS22A  STC   STC01159 CICS22A   00AB   X235    2.18  0.00
CICS22C  STC   STC03379 CICS22C   0190   X235    1.98  0.00
CICS31A  STC   STC03246 CICS31A   00B5   X235    2.58  0.00
CICS32A  STC   STC02104 CICS32A   0115   X235    2.58  0.00
CONSOLE  STC   N/A      CONSOLE   0009   X235    0.00  0.00
CSQ6MSTR STC   STC00454 CSQ6MSTR  0032   X235    5.95  0.00

```

Enter "S" beside the active job(s) you want to measure. You can select multiple active jobs to be measured simultaneously. The maximum number of jobs that can be selected is defined during the installation of Application Performance Analyzer. This feature is used to measure multiple active jobs at the same time, and is typically used for CICS and IMS multiple address space support.

When multiple jobs are selected, the selected jobs are listed in the lower half of the panel in Selected Jobs List. You add jobs to the Selected Jobs List by entering 'S' beside the active jobs in the upper half of the panel. Enter 'D' beside the active job in the lower half of the panel to remove jobs from the Selected Jobs List. When you return to Panel 1, the first job selected is displayed in the Jobname//Pattern field, and '(Active - Multiple Jobs Selected)' is displayed below the Jobname to indicate

that multiple jobs are selected. Multiple jobs can be selected only in NEW requests, and are not valid for Threshold or Trigger requests.

Panel 4 is shown here with multiple CICS regions selected for measurement simultaneously.

```

File View Navigate Help
-----
R03: Schedule New Measurement                               Row 00001 of 00011
Command ==> _____ Scroll ==> CSR

o 1. Job Information      3. Multi Steps      5. Subsystems      7. Schedule
  2. Options              o 4. Active Jobs    6. Sysplex        8. Sched Options

Panel 4. Active Jobs                                     Input more data or ENTER to submit

Enter S to select an active job step to be measured.  Prefix . . CICS* _____

   JobName  Type  JobId  StepName  Procstep  ASIDX  System  CPU%  SIO
-  CICS31A  STC  STC02977  CICS31A  CICS   01AC  X235    1.08  0.00
-  CICS32A  STC  STC02278  CICS32A  CICS   0167  X235    1.08  0.00
-  CICS32B  STC  STC02122  CICS32B  CICS   0151  X235    0.72  0.00
-  CICS41A  STC  STC02300  CICS41A  CICS   016E  X235    1.44  0.00

Selected Jobs List
Enter D to remove an active job from the list.

   JobName  System
-  CICS32A  X235
-  CICS32B  X235

```

Panel 5 – Subsystems

Use this panel to specify information about the measurement of a CICS region, IMS selection parameters, or specific DB2 stored procedures or user-defined functions. CICS, IMS and DB2 information are all mutually exclusive. The available fields on panel 5 differ when a dash (-) is entered in the Jobname field in panel 1. In this case, Application Performance Analyzer displays fields on this panel that are specific to either DB2 stored procedures and user-defined functions and IMS transactions that execute across multiple IMS MPP regions.

Specify the CICS tran codes for which CICS measurement information is to be recorded. Limiting this to the CICS transactions you are interested in can have a significant impact on the resources consumed by the measurement process.

For IMS, when you are measuring one MPP region, you can specify a transaction, program name, and user ID to limit the measurement information. When you are measuring an IMS transaction that executes across multiple MPP regions, you specify the IMS subsystem name and the IMS transaction name.

For specific DB2 stored procedures or user-defined functions, you specify the DB2 subsystem name, either a P or F, the schema name and the stored procedure or user-defined function name.

A sample panel 5 for CICS and one IMS region is shown here, with an asterisk (*) to indicate all CICS transactions are to be measured, and an asterisk (*) to indicate all CICS terminals are to be measured.

```

File View Navigate Help
-----
R03: Schedule New Measurement                               Row 00001 of 00019
Command ==>>> _____ Scroll ==>>> CSR

o 1. Job Information    3. Multi Steps    5. Subsystems    7. Schedule
  2. Options            4. Active Jobs    6. Sysplex      8. Sched Options
-----
Panel 5. Subsystems Measurement Criteria

Specify up to 16 CICS trancodes for which measurement data is to be
recorded.

  01 *__ 02 __ 03 __ 04 __ 05 __ 06 __ 07 __ 08 __
  09 __ 10 __ 11 __ 12 __ 13 __ 14 __ 15 __ 16 __

Include CICS system transaction in measurement(Y/N): N

Wildcard character '*' can be specified at the end of a partial name.
*' by itself specifies all transactions of terminals.

Specify up to 8 CICS terminal IDs for which measurement data is to be recorded.

  01 *__ 02 __ 03 __ 04 __ 05 __ 06 __ 07 __ 08 __

Include CICS non-terminal transactions in measurement(Y/N): Y

Enter IMS/TM selection parameters:

Transaction _____ Program Name _____ User ID _____

```

A sample panel 5 where you can enter information about a specific DB2 stored procedure or an IMS subsystem and transaction is shown here. This panel is displayed only when a dash (-) is entered in the Job Name/Pattern field in Panel 1.

```

File View Navigate Help
-----
R03: Schedule New Measurement                               Row 00001 of 00010
Command ==>>> _____ Scroll ==>>> CSR

o 1. Job Information    3. Multi Steps    5. Subsystems    7. Schedule
  2. Options            4. Active Jobs    6. Sysplex      8. Sched Options
-----
Panel 5. Subsystems Measurement Criteria

Enter DB2 stored procedure or user-defined function parameters:

DB2 Subsystem _____ Specify P for procedure or F for function _
Schema _____
Name _____

Enter IMS/TM selection parameters:
IMS Subsystem Id ____ Transaction _____

```

Panel 5 input fields

CICS Trancode

Specify a CICS transaction name or pattern. This identifies CICS transactions to be included in the measurement. You can also specify a partial name terminated by an asterisk (*) to indicate a wildcard pattern. You can specify up to 16 names/patterns. Specify an asterisk (*) by itself to measure all transactions.

Include CICS System Txns

Specify Y or N to indicate if the measurement is to include data on CICS system transactions. (Normally set to No).

CICS Terminal ID

Specify a CICS terminal ID name or pattern. This identifies CICS terminals to be included in the measurement. You can also specify a partial name terminated by an asterisk (*) to indicate a wildcard pattern. You can specify up to eight names/patterns. Specify an asterisk (*) by itself to measure all terminals.

Include CICS non-terminal transaction

Specify Y or N to indicate if the measurement is to include data on CICS non-terminal transactions.

IMS Transaction

Specify an IMS transaction id or pattern. This identifies IMS transactions to be included in the measurement when measuring an IMS/MPP region. You can also specify a partial name terminated by an asterisk (*) to indicate a wildcard pattern.

Any values in Transaction Id, Program Name and User ID are ANDed together to determine if a transaction should be included in the measurement.

IMS Program

Specify an IMS program name or pattern. This identifies IMS programs to be included in the measurement when measuring an IMS/MPP region. You can also specify a partial name terminated by an asterisk (*) to indicate a wildcard pattern.

Any values in Transaction Id, Program Name and User ID are ANDed together to determine if a transaction should be included in the measurement.

IMS User ID

Specify a userid or pattern. This identifies that transactions initiated by the userid are to be included in the measurement when measuring an IMS/MPP region. You can also specify a partial name terminated by an asterisk (*) to indicate a wildcard pattern. Any values in Transaction Id, Program Name and User ID are ANDed together to determine if a transaction should be included in the measurement.

Note: When limiting the observation to specific IMS transactions, programs or users in an MPP region, Application Performance Analyzer samples only when the transactions are running. The observation continues to run for the requested duration.

DB2 Subsystem

This field is displayed only when a dash (-) is entered in the Job Name/Pattern field in Panel 1. Specify a DB2 subsystem. This identifies the DB2 subsystem that will be used to run the stored procedure or user-defined function.

Specify procedure or function

This field is displayed only when a dash (-) is entered in the Job Name/Pattern field in Panel 1. Identify this request as a stored procedure or user-defined function. Enter P for stored procedure or F for a user-defined function.

Schema

This field is displayed only when a dash (-) is entered in the Job Name/Pattern field in Panel 1. Specify the schema name for this stored procedure or user-defined function. You can specify a schema name

pattern; for example, a schema name prefix followed by an asterisk (*) or an asterisk by itself. Application Performance Analyzer will measure the first DB2 stored procedure or user-defined function executed by the DB2 subsystem that matches that schema name pattern and name concatenation. If a single asterisk is coded in both schema and name, Application Performance Analyzer will measure the first stored procedure or user-defined function executed by the DB2 subsystem.

Name This field is displayed only when a dash (-) is entered in the Job Name/Pattern field in panel 1. Specify the name of the stored procedure or user-defined function. You can specify a name pattern; for example, a name prefix followed by an asterisk (*) or an asterisk by itself. Application Performance Analyzer will measure the first DB2 stored procedure or user-defined function executed by the DB2 subsystem that matches that schema name and name pattern concatenation. If a single asterisk is coded in both schema and name, Application Performance Analyzer will measure the first stored procedure or user-defined function executed by the DB2 subsystem.

IMS Subsystem Id

Specify an IMS subsystem. This identifies the IMS subsystem in which the IMS transaction you are measuring runs.

Transaction

Specify an IMS transaction code. This identifies the IMS transaction to be included in the measurement. All active MPP regions that are eligible to process the transaction code on the specified IMS subsystem are returned on panel 4.

Panel 6 – Sysplex

This panel is used to select a target Sysplex system from a list. You can also choose ALL systems, in which case the target job will be measured on the first system to run it. You cannot select ALL for active jobs. Selecting ALL is the same as entering an asterisk (*) in the System Name field on panel 1.

A sample panel 6 is shown here.

```

File View Navigate Help
-----
R03: Schedule New Measurement                               Row 00001 of 00010
Command ==> _____ Scroll ==> CSR

o 1. Job Information    3. Multi Steps    5. Subsystems    7. Schedule
  2. Options            4. Active Jobs   6. Sysplex      8. Sched Options
-----
Panel 6. Sysplex

Target System. 'S' to select one option from the list (scrollable):
- ALL All Sysplex members eligible
- SYSA
- SYSB
- SYSE
- XS02
- XS03
- XS05

```

Panel 7 – Schedule

This panel is not applicable when measuring specific DB2 stored procedures or user-defined functions.

This panel is used to generate a schedule for repetitions of future measurements. A maximum of 105 future scheduled measurement entries is allowed.

The panel is shown here before any future schedule data has been entered:

```

File View Navigate Help
-----
R03: Schedule New Measurement                               Row 00001 of 00015
Command ==> _____ Scroll ==> CSR

o 1. Job Information  o 3. Multi Steps  o 5. Subsystems  7. Schedule
o 2. Options          o 4. Active Jobs  o 6. Sysplex    8. Sched Options

Panel 7. Schedule
Date/time of first in sequence      Measurement repetitions
Date (yy mm dd) .  _ _ _ _         Repeat . . _ _ times
Time (hh mm) . . _ _ _             After . . . _ _ days _ _ minutes

Use this panel to specify a schedule for repetitions of the measurement.
Input the above fields and press ENTER to generate dates and times for
each of the measurements. These dates/times will be shown below in a
scrollable table which you can add to by repeating this input process.

```

Using this panel to create a future schedule is explained in the example below. Note that there are also important fields on panel 8 related to future schedules.

Example of creating a Future Schedule

If a user wanted to measure a job every Wednesday night at 8:00 pm, and every Friday night at 11:00 pm, for 10 weeks, starting on Wednesday Dec. 8, 2004, it would be set up like this:

1. Enter the first Wednesday date in the Date (yy mm dd) field: 04 12 08.
2. Enter 10 in the Repeat __ times field.
3. Enter 20:00 in the Time (hh mm) field.
4. Enter 7 in the After __ days field. (To indicate that it repeats each 7 days).

The screen would look like this:

```

File View Navigate Help
-----
R03: Schedule New Measurement                               Row 00001 of 00015
Command ==> _____ Scroll ==> CSR

o 1. Job Information  o 3. Multi Steps  o 5. Subsystems  7. Schedule
o 2. Options          o 4. Active Jobs  o 6. Sysplex    8. Sched Options

Panel 7. Schedule
Date/time of first in sequence      Measurement repetitions
Date (yy mm dd) . 04 12 08         Repeat . . 10 times
Time (hh mm) . . 20 00             After . . . 7 days _ _ minutes

Use this panel to specify a schedule for repetitions of the measurement.
Input the above fields and press ENTER to generate dates and times for
each of the measurements. These dates/times will be shown below in a
scrollable table which you can add to by repeating this input process.

```

Then press Enter to generate the schedule, it will appear at the bottom of the panel like this:

```

File View Navigate Help
-----
R03: Schedule New Measurement                               Row 00001 of 00015
Command ==> _____ Scroll ==> CSR

o 1. Job Information  o 3. Multi Steps  o 5. Subsystems  o 7. Schedule
o 2. Options          o 4. Active Jobs  o 6. Sysplex     o 8. Sched Options

Panel 7. Schedule
Date/time of first in sequence      Measurement repetitions
Date (yy mm dd) . __ __ __         Repeat . . __ times
Time (hh mm) . . __ __             After . . . __ days __ minutes

Measurement Schedule (/ for line command list, UP/DOWN to scroll)
SeqN  Date/Time      Status
0001  Wed Dec-08-04 20:00  Pending ADD
0002  Wed Dec-15-04 20:00  Pending ADD
0003  Wed Dec-22-04 20:00  Pending ADD
0004  Wed Dec-29-04 20:00  Pending ADD
0005  Wed Jan-05-05 20:00  Pending ADD
0006  Wed Jan-12-05 20:00  Pending ADD
0007  Wed Jan-19-05 20:00  Pending ADD
0008  Wed Jan-26-05 20:00  Pending ADD
0009  Wed Feb-02-05 20:00  Pending ADD
0010  Wed Feb-09-05 20:00  Pending ADD
***** End of Schedule *****

```

Now enter similar data for the Friday night schedule like this:

5. Enter the first Friday date in the Date (yy mm dd) field: 04 12 10.
6. Enter 10 in the Repeat __ times field.
7. Enter 23:00 in the Time (hh mm) field.
8. Enter 7 in the After __ days field. (To indicate that it repeats each 7 days).

Press Enter and your Friday dates will appear with the Wednesday dates already generated like this:

```

File View Navigate Help
-----
R03: Schedule New Measurement                               Row 00001 of 00015
Command ==> _____ Scroll ==> CSR

o 1. Job Information  o 3. Multi Steps  o 5. Subsystems  o 7. Schedule
o 2. Options          o 4. Active Jobs  o 6. Sysplex    o 8. Sched Options

Panel 7. Schedule
Date/time of first in sequence      Measurement repetitions
Date (yy mm dd) . __ __ __         Repeat . . __ times
Time (hh mm) . . __ __             After . . . __ days __ minutes

Measurement Schedule (/ for line command list, UP/DOWN to scroll)
SeqN  Date/Time      Status
0001  Wed Dec-08-04 20:00  Pending ADD
0002  Fri Dec-10-04 23:00  Pending ADD
0003  Wed Dec-15-04 20:00  Pending ADD
0004  Fri Dec-17-04 23:00  Pending ADD
0005  Wed Dec-22-04 20:00  Pending ADD
0006  Fri Dec-24-04 23:00  Pending ADD
0007  Wed Dec-29-04 20:00  Pending ADD
0008  Fri Dec-31-04 23:00  Pending ADD
0009  Wed Jan-05-05 20:00  Pending ADD
0010  Fri Jan-07-05 23:00  Pending ADD
0011  Wed Jan-12-05 20:00  Pending ADD
0012  Fri Jan-14-05 23:00  Pending ADD
0013  Wed Jan-19-05 20:00  Pending ADD
0014  Fri Jan-21-05 23:00  Pending ADD
0015  Wed Jan-26-05 20:00  Pending ADD
0016  Fri Jan-28-05 23:00  Pending ADD
0017  Wed Feb-02-05 20:00  Pending ADD
0018  Fri Feb-04-05 23:00  Pending ADD
0019  Wed Feb-09-05 20:00  Pending ADD
0020  Fri Feb-11-05 23:00  Pending ADD
***** End of Schedule *****

```

Your schedule dates have now all been generated. Also see panel 8 below for additional data regarding future schedules.

Note: If you are entering a multiple job request (using the % wildcard in the job name field), then you can only set one date and time. No repetitions are allowed.

Panel 7 input fields

First Schedule Date

Specify a starting date for a new sequence of recurring schedule date/time entries.

Schedule Repeat Count

Specify a repeat count. This is the number of measurement recurrences to be generated and added to the schedule. The maximum value that can be entered in this field is 99. Application Performance Analyzer will accept a schedule with up to 105 repeats.

To generate a schedule with more than 99 repeats, you must generate two schedules for the same request. After generating the repeats for the first schedule, remain in Panel 7 and generate another schedule for the remaining repeats.

First Schedule Time

Specify a starting time for a new sequence of recurring schedule date/time entries.

Interval in Days

Specify the interval, in days, between each measurement recurrence to be added to the schedule.

Interval in Minutes

Specify the interval, in minutes, between each measurement recurrence to be added to the schedule.

Panel 8 – Sched Options

This panel is not applicable when measuring specific DB2 stored procedures or user-defined functions.

The available fields on panel 8 vary depending on whether “Y” or “N” is entered in the Measure active job (Y/N) field, and whether or not a future schedule has been entered on panel 7.

No Future Schedule and Active YES

When there is no future schedule, and “Y” is entered in the Measure active job (Y/N) field, then no additional fields will appear on panel 8. In this case, specifying “Y” here is an alternative to selecting an active job from a list in panel 4. If you use this method to specify that a job is active, then the jobname entered in panel 1 must be currently active, otherwise the request will fail.

An example of panel 8 for a single occurrence of an active job (i.e., with no future schedule) is shown here:

```
File View Navigate Help
-----
R03: Schedule New Measurement          Row 00001 of 00004
Command ==> _____ Scroll ==> PAGE

o 1. Job Information    3. Multi Steps    5. Subsystems    7. Schedule
  2. Options           4. Active Jobs   6. Sysplex      8. Sched Options

-----
Panel 8. Schedule Options

Specify if the job is active and is to be measured immediately (Y) or if
IBM APA for z/OS is to wait for the job to be submitted (N):

Measure active job (Y/N) . . . . Y
```

No Future Schedule and Active NO

When there is no future schedule, and “N” is entered in the Measure active job (Y/N) field, then the field Times to Repeat and Within interval (minutes, days or weeks) will appear.

An example of panel 8 for a single occurrence of an inactive job (i.e., with no future schedule) is shown here:


```

File View Navigate Help
-----
R03: Schedule New Measurement                               Row 00001 of 00011
Command ==> _____ Scroll ==> CSR

o 1. Job Information    3. Multi Steps    5. Subsystems  7. Schedule
  2. Options            4. Active Jobs   6. Sysplex    8. Sched Options

Panel 8. Schedule Options

Specify if the job is active and is to be measured immediately (Y) or if
IBM APA for z/OS is to wait for the job to be submitted (N):

Measure active job (Y/N) . . . . N

Times to repeat measurement . __    If the job runs more than once
                                      within the specified interval.

Within interval (minutes) . . __    Maximum 999 minutes.
or within interval (days) . . __    Maximum 22 days.
or within interval (weeks) . . __    Maximum 3 weeks.

```

Future Schedule and Active YES

When entering a future schedule request, selecting “Y” for active means that the job is expected to be active when the measurement takes place. The fields Number of times to retry and Retry interval (minutes) will appear.

An example of panel 8 for an active job with a future schedule is shown here:

```

File View Navigate Help
-----
R03: Schedule New Measurement                               Row 00001 of 00007
Command ==> _____ Scroll ==> PAGE

o 1. Job Information    3. Multi Steps    5. Subsystems  o7. Schedule
  2. Options            4. Active Jobs   6. Sysplex    o8. Sched Options

Panel 8. Schedule Options                                Input more data or ENTER to submit

Specify if the job to be measured will be active when the scheduling occurs
(e.g. a CICS region) or pending (a batch job).

Job will be active (Y/N) . . . . Y

Number of times to retry . . . __    Indicate retry action if job is not
Retry interval (minutes) . . . __    active at the time of scheduling.

```

Future Schedule and Active NO

When entering a future schedule request, selecting “N” for not active means that the request will wait for the job to start. In this case three additional fields will appear: Expire after (minutes), Times to repeat measurement, and Within interval (minutes).

An example of panel 8 for an inactive job with a future schedule is shown here:

```

File View Navigate Help
-----
R03: Schedule New Measurement                               Row 00001 of 00010
Command ==>>> _____ Scroll ==>> CSR
o 1. Job Information   3. Multi Steps   5. Subsystems o 7. Schedule
  2. Options           4. Active Jobs   6. Sysplex    8. Sched Options

Panel 8. Schedule Options

Specify if the job to be measured will be active when the scheduling occurs
(e.g. a CICS region) or pending (a batch job).

Job will be active (Y/N) . . . . N

Expire after (minutes) . . . ____ Number of minutes from schedule time
to wait for job to be submitted.

Times to repeat measurement . ____ If the job runs more than once
Within interval (minutes) . . ____ within the specified interval.

```

Panel 8 input fields

Job Active (Y/N)

Specify Y to indicate the job is active and the measurement is to begin immediately. Specify N to indicate that the job is pending (a batch job) and Application Performance Analyzer is to wait for its execution.

If you have specified a recurring schedule for the measurement, then this field indicates the expected status of the job at the time the measurement is scheduled.

Times to Repeat

This applies to measurement of a job that is not active (pending). Specify the number of times the measurement is to be repeated if the job is rerun during the specified interval. Use this to ensure that a good measurement is captured in the event the job is cancelled or abends and is then rerun.

Within Interval

This applies to measurement of a job that is not active (pending). Specify the interval the Application Performance Analyzer started task is to check for reruns of the job. Use this to ensure that a good measurement is captured in the event the job is cancelled or abends and is then rerun.

In the case of a single occurrence of a batch job, use this when the exact time the job will be executed is unknown or varies. Measurements that have a future schedule associated with the job will accommodate an interval of up to 999 minutes only. Measurements for a single occurrence of a job (i.e., no future schedule) will accommodate an interval of either 999 minutes, 22 days or 3 weeks.

Times to Retry

This applies to a schedule of recurring measurements for a job that is expected to be active at the time the measurement is scheduled. Indicate the number of times Application Performance Analyzer is to check again for the job in the event that it was not active. The 'Retry Interval' field specifies the interval between retries.

Retry Interval

This applies to a schedule of recurring measurements for a job that is expected to be active at the time the measurement is scheduled. It specifies an action to be taken if the job is not active at the schedule time. Indicate the interval between each check for the job being active. The 'Number of Times to Retry' field specifies how many times the retry is to occur.

Entering a Threshold Monitor request

Note: It is important that you are already familiar with the preceding information in this chapter before using the Threshold Monitor feature. The Threshold Monitor request process uses most of the panels described in the previous sections, and the information is not repeated here.

Threshold measurements cannot be created for measuring specific DB2 stored procedures or user-defined functions

Using the TNEW command

The TNEW primary command is used to enter a new Observation Request, which will start only when specified threshold criteria have been satisfied for the target job-step.

The criteria are:

- CPU Time
- Elapsed Time
- EXCP Count

Setting Threshold Requirements panels

The Set Threshold Requirements panel group is very similar to the standard Schedule New Measurement panel group. The differences are that Multi-Step and Schedule information is not used for Threshold Monitor requests, so these panels are not available. Panel 3 - Criteria is specific to Threshold Monitor request. After entering the standard data to describe the measurement request, you must enter the Threshold Criteria.

Panel 3 - Criteria

After entering the data to describe the measurement request, you use the Criteria panel to specify the Threshold Criteria which will trigger the measurement to run. The panel 3 Criteria panel is shown here.

In this example, when CPU time exceeds 30 seconds, and EXCP count exceeds 20000, the measurement will be triggered.

```
File View Navigate Help
-----
R03: Set Threshold Requirements                               Row 00001 of 00005
Command ==> _____ Scroll ==> CSR
o 1. Job Information  o 3. Criteria      o 5. Subsystems
  2. Options          4. Active Jobs    6. Sysplex
-----
Panel 3. Threshold Criteria

Enter Threshold Criteria

      CPU Time Exceeds (min:sec) . . . 30
      Elapsed Time Exceeds (min:sec) .
      EXCP Count Exceeds . . . . . 20000

If you enter more than one threshold criteria field, then all the
criteria must be met for the measurement to be triggered.
```

Panel 3 input fields

CPU Time Exceeds

Enter the threshold amount of CPU time, if the target job-step exceeds this amount of CPU time, the measurement will be triggered.

You can specify the value in seconds or in minutes and seconds. To specify the threshold CPU time in minutes and seconds, separate the minutes value from the seconds value using a colon.

Examples:

- 135 specifies 135 seconds
- 2:15 specifies 2 minutes and 15 seconds
- 2: specifies 2 minutes

Elapsed Time Exceeds

Enter the threshold amount of Elapsed time, if the target job-step exceeds this amount of Elapsed time, the measurement will be triggered.

You can specify the value in seconds or in minutes and seconds. To specify the threshold Elapsed time in minutes and seconds, separate the minutes value from the seconds value using a colon.

Examples:

- 135 specifies 135 seconds
- 2:15 specifies 2 minutes and 15 seconds
- 2: specifies 2 minutes

EXCP Count Exceeds

Enter the threshold EXCP count. If the target job-step exceeds this EXCP count, the measurement will be triggered.

Note: : If you enter more than one threshold criteria field, then all the criteria must be met for the measurement to be triggered.

Entering a Trigger request

Note: It is important to be familiar with the preceding information in this chapter before using the Trigger feature. The Trigger request process uses most of the panels described in the previous sections and the information is not repeated here.

Overview

The trigger request feature is used to allow the start of one scheduled measurement to trigger an additional measurement (called the Trigger measurement). For example, you might want to have the beginning of a batch job step measurement also initiate a measurement of a particular CICS region. The original scheduled measurement request must be entered first, then the trigger measurement can be entered.

The trigger measurement cannot measure a specific DB2 stored procedure or user-defined function.

Using the TR line command

The original scheduled measurement request is identified by entering the TR line command on it in the R02 Observation Session List panel. This displays the panels for entering the measurement request information for the trigger request.

The Set Trigger Requirements panel group is very similar to the standard Schedule New Measurement panel group. The differences are that Multi-Step and Schedule information is not used for Trigger requests, so these panels are not available. For information on panels used to specify Trigger requests, refer to the preceding sections in this chapter.

Chapter 3. Performance analysis reports

This section describes the Performance Analysis Reports. Some basic concepts are covered, and the base reports (those not pertaining to a data extractor) are described.

For Performance Analysis Reports pertaining to a specific data extractor (CICS, IMS, DB2, etc.), refer to the chapter for the specific data extractor.

| For information about ... | See ... |
|--|--|
| General concepts required for interpreting these reports | "Performance analysis basics" on page 44 |
| Report categories and codes | "Report categories and codes" on page 47 |
| S01 Measurement profile | "S01 - Measurement profile" on page 50 |
| S02 Load module attributes | "S02 - Load module attributes" on page 60 |
| S03 Load module summary | "S03 - Load module summary" on page 62 |
| S04 TCB summary | "S04 - TCB summary" on page 64 |
| S05 Memory usage timeline | "S05 - Memory usage timeline" on page 66 |
| S06 Data space usage timeline | "S06 - Data space usage timeline" on page 68 |
| S07 TCB execution summary | "S07 - TCB execution summary" on page 69 |
| S08 Processor utilization summary | "S08 - Processor utilization summary" on page 71 |
| S09 Measurement analysis | "S09 - Measurement analysis" on page 73 |
| C01 CPU usage by category | "C01 - CPU usage by category" on page 74 |
| C02 CPU usage by module | "C02 - CPU usage by module" on page 82 |
| C03 CPU usage by code slice | "C03 - CPU usage by code slice" on page 85 |
| C04 CPU usage timeline | "C04 - CPU usage timeline" on page 88 |
| C05 CPU Usage by task/category | "C05 - CPU usage by task/category" on page 91 |
| C06 CPU Usage by task/module | "C06 - CPU usage by task/module" on page 98 |
| C07 CPU usage by procedure | "C07 - CPU usage by procedure" on page 102 |
| C08 CPU usage referred attribution | "C08 - CPU usage referred attribution" on page 105 |
| C09 CPU Usage by PSW/object code | "C09 - CPU usage by PSW/object code" on page 111 |
| W01 WAIT time by task/category | "W01 - WAIT time by task/category" on page 113 |
| W02 WAIT time by module | "W02 - WAIT time by task/module" on page 118 |
| W03 WAIT time referred attribution | "W03 - WAIT time referred attribution" on page 122 |
| W04 WAIT time by task ENQ/RESERVE | "W04 - WAIT time by task ENQ/RESERVE" on page 125 |

| For information about ... | See ... |
|-----------------------------------|---|
| W05 WAIT time by tape DDNAME | "W05 - WAIT time by tape DDNAME" on page 128 |
| D01 DASD usage by device | "D01 - DASD usage by device" on page 130 |
| D02 DASD usage by DDNAME | "D02 - DASD usage by DDNAME" on page 132 |
| D03 DASD usage by data set | "D03 - DASD usage by data set" on page 135 |
| D04 data set attributes | "D04 - Data set attributes" on page 137 |
| D05 DASD EXCP summary | "D05 - DASD EXCP summary" on page 139 |
| D06 DASD VSAM statistics | "D06 - DASD VSAM statistics" on page 142 |
| D07 DASD activity timeline | "D07 - DASD activity timeline" on page 144 |
| D08 DASD I/O wait time | "D08 - DASD I/O wait time" on page 147 |
| D09 VSAM buffer pool usage | "D09 - VSAM buffer pool usage" on page 152 |
| G01 Coupling facility summary | "G01 - Coupling facility summary" on page 153 |
| G02 Coupling facility mean times | "G02 - Coupling facility mean times" on page 155 |
| G03 Coupling facility total times | "G03 - Coupling facility total times" on page 156 |
| V01 Measurement variance summary | "V01 - Measurement variance summary" on page 157 |

Performance analysis basics

Some of the concepts that you need to understand in order to effectively interpret the Application Performance Analyzer performance analysis reports are explained here.

Sampling and system states

During an Application Performance Analyzer observation session, activity in the target address space is sampled at the frequency and for the duration which was specified when the session was requested. Each observation results in data being recorded which describes an observed System State. The essence of the analysis reports is the aggregation of System States and attribution of these aggregates to various System Objects. For example, CPU Executing is a type of System State and a Load Module is a type of System Object; a report might quantify observations of CPU Executing and attribute these quantities to various Load Modules. By mapping observed system states to system objects, the analysis reports provide a meaningful picture of how resources are consumed.

Types of system states

Each observation, or "sample," interrupts and momentarily "freezes" system activity in the target address space. Information about the state of the interrupted process (or, often, in the case of a multi-CPU system, processes) is recorded. System states that can be observed are:

- CPU Executing
- CPU Waiting
- Queued

It is important to understand that an observation session measures activity in a single address space. When we refer to system states like “CPU Waiting” or “CPU Unavailable” these states are with respect to the target address space only.

CPU Executing

A CPU was executing machine instructions for the task when the observation was made. Information about where (in what program) execution was taking place is captured. Application Performance Analyzer also determines, and records, whether execution was in Linear or Parallel mode. Linear mode refers to a state in which one, and only one, task was executing instructions. Parallel mode refers to a state in which more than one task was executing concurrently. Parallel mode occurs when two or more CPUs were executing instructions for the target address space at the same time.

CPU Waiting

A task was in a wait state. The task was waiting for an event (such as completion of an I/O operation) to occur.

Queued

The “Queued” state refers to a task (TCB) that was observed as dispatchable but was not executing instructions because no CPU was available. A measurement showing a high percentage of queued observations could imply an overall shortage of CPU resources. This would also occur in an address space in which the number of dispatchable tasks exceeds the number of physical CPUs.

Unavailability of memory can also cause the Queued state.

System objects

System Objects are objects to which quantified observations of systems states can be attributed. The following are the basic system objects:

- Load Modules
- TCBs
- DD Names
- DASD Volumes
- SVCs
- MQSeries Queue Names

Quantities expressed as percentages

The performance analysis reports express most quantified data as percentages. In most cases, absolute values (for example, actual number of observations in which execution was in DB2 services) would not, by themselves, be particularly meaningful. This is because the total number of samples chosen for an observation session is somewhat arbitrary. The percentage of activity attributed to a system object, on the other hand, provides a much better measure of the impact of that system object on performance. Furthermore, when expressed as percentages, quantification is likely to remain roughly equal if the sampling frequency and duration parameters are varied.

In order to effectively interpret the performance analysis reports it is important that you understand how these percentages are computed. The formulae vary depending upon what type of system activity is reported.

CPU Time Percentage

The percentage expresses the ratio of attributed CPU to the total CPU time

observed. This is computed by dividing the number of attributed "CPU EXECUTING" observations by the total number of "CPU EXECUTING" observations and multiplying that number by 100.

Note that observations of CPU Waiting and CPU Unavailable are excluded from the calculation. The objective is to report the relative demand placed on CPU resources by system objects.

I/O Activity Percentage of Time

The percentage reported for I/O activity expresses the ratio of time attributed I/O operations were active to the total observation session elapsed time. Consider an example in which 10,000 observations were made during a 60 second interval. Suppose during 1,500 of these observations, I/O was found to be active for a file with DDNAME=SYSIN. 15 percent would be reported as the I/O activity percentage of time attributed to SYSIN.

Parallel Activity

Application Performance Analyzer will report information about parallel activity. Examples of parallel activity are:

I/O activity concurrent CPU execution is observed.

Concurrent I/O activity is observed for multiple devices.

Concurrent CPU execution is observed. This is only possible on a system with multiple CPUs (a multiprocessor).

Margin of error

A margin of error value is displayed in various reports. The value is expressed as a percentage and represents a 95 percent confidence interval. What this means is that in 95 percent of cases (19 out of 20 times) a repetition of the same measurement will produce results within +/- the indicated number of percentage points. This value is based entirely on the size of a sample population and reflects only the statistical error that can be expected from the sample size. It does not take into account any effects caused by biased sample collection.

Color coding of graphs

Application Performance Analyzer makes extensive use of bar graphs to illustrate resource usage. The graphs are color coded as follows:

Table 1. Color coding of graphs

| Graph Color | Purpose |
|--------------------|-------------------------------|
| Green | CPU active |
| Yellow | CPU wait |
| White | Resources (memory, dataspace) |
| Red | DASD I/O |
| Blue | Service time |

Note: Report titles indicate each report's purpose. Color coding is included for emphasis, but color is not required to interpret information.

Report categories and codes

Application Performance Analyzer reports are each assigned a three-character code consisting of a one-letter prefix followed by a two-digit number. The prefix indicates which category the report belongs to, and the number is a sequence number within that category.

When you are viewing a report, you can enter another report's three-character code on the command line and that report will also open.

The categories and reports are listed here:

Table 2. Report categories and prefixes

| Prefix | Category | Reports |
|--------|---------------------|--|
| A | Admin/Miscellaneous | A01 Source Program Mapping A02 Request Printed Reports A03 Java Source Mapping A04 Source Mapping Dataset List |
| S | Statistics/Storage | S01 Measurement Profile S02 Load Module Attributes S03 Load Module Summary S04 TCB Summary S05 Memory Usage Timeline S06 Data Space Usage Timeline S07 TCB Execution Summary S08 Processor Utilization Summary S09 Measurement Analysis |
| C | CPU usage analysis | C01 CPU Usage by Category C02 CPU Usage by Module C03 CPU Usage by Code Slice C04 CPU Usage by Timeline C05 CPU Usage Task/Category C06 CPU Usage Task/Module C07 CPU Usage by Procedure C08 CPU Usage Referred Attribution C09 CPU Usage by PSW/Object Code |
| D | DASD I/O analysis | D01 DASD Usage by Device D02 DASD Usage by DDName D03 DASD Usage by data set D04 data set Attributes D05 DASD EXCP Summary D06 DASD VSAM Statistics D07 DASD Activity Timeline D08 DASD I/O Wait Time D09 VSAM Buffer Pool Usage |
| G | Coupling facility | G01 Coupling Facility Summary G02 Coupling Facility Mean Times G03 Coupling Facility Total Times |
| W | CPU WAIT analysis | W01 Wait Time by Category W02 Wait Time by Module W03 Wait Time Referred Attribution W04 Wait Time by task ENQ/RESERVE W05 Wait Time by Tape DDNAME |

Table 2. Report categories and prefixes (continued)

| Prefix | Category | Reports |
|--------|---|---|
| I | IMS measurement | I01 IMS Measurement Profile I02 IMS DL/I DL/I Call Timeline I03 IMS Transaction Timeline I04 IMS Txn Activity Timeline I05 IMS CPU Usage by PSB I06 IMS CPU Usage by Transaction I07 IMS CPU Usage by DL/I Call I08 IMS WAIT Time by PSB I09 IMS WAIT Time by Transaction I10 IMS WAIT Time by DL/I Call I11 IMS DL/I Activity by PSB I12 IMS DL/I Activity by Txn I13 IMS DL/I Activity by DL/I Call I14 IMS PSB/PCB Attributes I15 IMS DL/I Call Attributes I16 IMS Transaction Service Times I17 IMS Transaction DL/I Counts I18 IMS CPU/Svc Time by DL/I Call I19 IMS CPU/Svc Time by PSB I20 IMS CPU/Svc Time by Txn I21 IMS CPU/Svc Time by PCB |
| E | CICS measurement | E01 CICS Session Statistics E02 CICS CPU and Use Counts by Pgm E03 CICS CPU Usage by Txn E04 CICS Mean Service Time by Txn E05 CICS Total Service Time by Txn E06 CICS Service Time by Task ID E07 CICS Wait by Txn E08 CICS mean service time by terminal ID E09 CICS total service time by terminal ID E10 CICS Mean Service Time by user ID E11 CICS Total Service Time by user ID E12 CICS CPU/Service Time by Txn |
| X | CICS multiple address space measurement | X01 CICS Mean Service Time by Txn X02 CICS Total Service Time by Txn X03 CICS Mean Service Time by Term X04 CICS Total Service Time by Term |

Table 2. Report categories and prefixes (continued)

| Prefix | Category | Reports |
|--------|----------------------|--|
| F | DB2 measurement | <p>F01 DB2 Measurement Profile</p> <p>F02 DB2 SQL Activity Timeline</p> <p>F03 DB2 SQL Activity by DBRM</p> <p>F04 DB2 SQL Activity by Statement</p> <p>F05 DB2 SQL Activity by Plan</p> <p>F06 DB2 SQL Statement Attributes</p> <p>F07 DB2 SQL Wait Time by DBRM</p> <p>F08 DB2 SQL Wait Time by Statement</p> <p>F09 DB2 SQL Wait Time by Plan</p> <p>F10 DB2 SQL CPU/Svc Time by DBRM</p> <p>F11 DB2 SQL CPU/Svc Time by Stmt</p> <p>F12 DB2 SQL CPU/Svc Time by Plan</p> <p>F13 DB2 SQL Threads Analysis</p> <p>F14 DB2 CPU Usage by Plan/Proc</p> <p>F15 DB2 SQL CPU/Svc Time by Rq Loc</p> <p>F16 DB2 SQL CPU/Svc Time by Enclave</p> <p>F17 DB2 SQL CPU/Svc Time by Corrid</p> <p>F18 DB2 SQL CPU/Svc Time by Wkstn</p> <p>F19 DB2 SQL CPU/Svc Time by EndUsr</p> |
| Q | MQSeries measurement | <p>Q01 MQSeries Activity Summary</p> <p>Q02 MQSeries CPU Usage by Queue</p> <p>Q03 MQSeries CPU Usage by Request</p> <p>Q04 MQSeries CPU Usage by Txn</p> <p>Q05 MQSeries Serv Time by Queue</p> <p>Q06 MQSeries Serv Time by Request</p> <p>Q07 MQSeries Serv Time by Txn</p> <p>Q08 MQSeries Wait Time by Queue</p> <p>Q09 MQSeries Wait Time by Request</p> <p>Q10 MQSeries Wait Time by Txn</p> |
| J | Java Measurement | <p>J01 Java summary and attributes</p> <p>J04 Java CPU usage by package</p> <p>J05 Java CPU usage by class</p> <p>J06 Java CPU usage by method</p> <p>J07 Java CPU usage by call path</p> <p>J09 Java service time by package</p> <p>J10 Java service time by class</p> <p>J11 Java service time by method</p> <p>J12 Java service time by call path</p> <p>J14 Java wait time by package</p> <p>J15 Java wait time by class</p> <p>J16 Java wait time by method</p> <p>J17 Java wait time by call path</p> |

Table 2. Report categories and prefixes (continued)

| Prefix | Category | Reports |
|--------|------------------|--|
| V | Variance reports | V01 Measurement Variance Summary |
| H | HFS Analysis | H01 HFS Service Time by Path Name H02 HFS Service Time by Device H03 HFS File Activity H04 HFS File Attributes H05 HFS Device Activity H06 HFS Device Attributes H07 HFS Activity Timeline H08 HFS Wait Time by Path Name H09 HFS Wait Time by Device H10 HFS Service Time by Request H11 HFS Wait Time by Request |

S01 - Measurement profile

Usage

Use this report to see a general overview of the measurement. This is a good report to examine first when analyzing a measurement. It provides an at-a-glance summary of various aspects of the measurement data and helps you choose which other reports to concentrate on. The first section of this report consists of a series of mini performance graphs illustrating various types of activity that was measured. This is followed by a section that reports measurement values.

Performance graphs

These are histograms quantifying measurement data. To the right of each graph, report codes of reports that show related and more detailed information are displayed. You can display the report by skipping the cursor to one of these fields and by pressing the ENTER key.

Overall CPU activity

This graph is omitted for DDF measurements.

| Under heading | This is displayed |
|---------------|---|
| Samples | The number of samples done during the measurement upon which this graph is based. This number represents 100 percent of the data upon which the graph is based and is used as the divisor to compute the percentages shown in other lines in the graph. This number is sometimes slightly smaller than the total number of samples. Only those samples in which any TCBs existed are included in this count. Non-TCB samples can occur very early in a job step when the system is still initializing the step. |
| CPU Active | The number of samples the CPU was actively processing one or more TCBs. This value represents the percentage of time CPU activity was occurring in the address space. |
| WAIT | The number of samples all TCBs were in a WAIT. |

| Under heading | This is displayed |
|---------------|---|
| Queued | The number of samples no CPU activity was taking place because no resources (CPU or memory) were available to service the address space. At least one TCB was dispatchable and not in a WAIT. |

CPU usage distribution

This graph is omitted for DDF measurements.

| Under Heading | This is Displayed |
|---------------|--|
| CPU Active | The number of observations of CPU active TCBs. This number represents 100 percent of the data upon which the graph is based and is used as the divisor to compute the percentages shown in other lines in the graph. This value is different from the "samples" value reported in the "Overall CPU Activity" graph because multiple concurrent CPU active TCBs (multiple CPUs executing concurrently) are counted separately here. This quantification represents the overall consumption of CPU time. |
| Application | The number of observations of CPU active TCBs while executing in application modules. |
| System | The number of observations of CPU active TCBs while executing in system modules. |
| DB2 SQL | The number of observations of CPU active TCBs while servicing SQL requests. |
| Data Mgmt | The number of observations of CPU active TCBs while servicing data management requests. |
| Unresolved | The number of observations of CPU active TCBs while executing in addresses that could not be resolved to module names. |
| IMS DLI Call | The number of observations of CPU active TCBs while servicing IMS DLI requests. |

Most CPU active modules

This graph is omitted for DDF measurements.

| Under Heading | This is Displayed |
|---------------|---|
| CPU Active | The number of observations of CPU active TCBs. This number represents 100% of the data upon which the graph is based and is used as the divisor to compute the percentages shown in other lines in the graph. This value is different from the 'samples' value reported in the 'Overall CPU Activity' graph because multiple concurrent CPU active TCBs (multiple CPUs executing concurrently) are counted separately here. This quantification represents the overall consumption of CPU time. |
| Module | Five lines appear showing the five most CPU active load modules. The number of CPU active observations for each of these modules and its percentage of the total number of CPU active observations is shown. |

Most CPU active CSECTs

This graph is omitted for DDF measurements.

| Under Heading | This is Displayed |
|---------------|---|
| CPU Active | The number of observations of CPU active TCBs. This number represents 100% of the data upon which the graph is based and is used as the divisor to compute the percentages shown in other lines in the graph. This value is different from the 'samples' value reported in the 'Overall CPU Activity' graph because multiple concurrent CPU active TCBs (multiple CPUs executing concurrently) are counted separately here. This quantification represents the overall consumption of CPU time. |
| CSECT | Five lines appear showing the five most CPU active CSECTs (control sections) and their corresponding module names. The number of CPU active observations for each of these CSECTs and its percentage of the total number of CPU active observations is shown. |

CPU modes

This graph is omitted for DDF measurements.

| Under Heading | This is Displayed |
|---------------|--|
| CPU Active | The number of observations of CPU active TCBs. This number represents 100 percent of the data upon which the graph is based and is used as the divisor to compute the percentages shown in other lines in the graph. This value is different from the "samples" value reported in the "Overall CPU Activity" graph because multiple concurrent CPU active TCBs (multiple CPUs executing concurrently) are counted separately here. This quantification represents the overall consumption of CPU time. |
| Supv Mode | The number of observations of CPU active TCBs while the system was in supervisor (privileged) mode (usually system routines). |
| Prob Mode | The number of observations of CPU active TCBs while the system was in problem state. Applications normally execute in problem state. |
| In SVC | The number of observations of CPU active TCBs while the system was executing in an SVC (supervisor call) routine. |
| AMODE 24 | The number of observations of CPU active TCBs while the system was in 24 bit addressing mode. |
| AMODE 31 | The number of observations of CPU active TCBs while the system was in 31 bit addressing mode. |
| AMODE 64 | The number of observations of CPU active TCBs while the system was in 64 bit addressing mode. |
| User Key | The number of observations of CPU active TCBs while the system was in user storage key (key 8). |
| System Key | The number of observations of CPU active TCBs while the system was in a system storage protection key. |

Most active IMS PSBs

This graph is shown only if IMS measurement data was recorded. It shows the most active IMS PSBs. Up to five IMS PSBs are reported.

| Under Heading | This is Displayed |
|-----------------------|---|
| Samples | The number of samples done during the measurement upon which this graph is based. This number represents 100 percent of the data upon which the graph is based and is used as the divisor to compute the percentages shown in other lines in the graph. |
| IMS PSB Name | An IMS PSB name is shown and the number of samples in which processing of DLI calls under this PSB was observed. The percentage and the graph represent the proportion of the overall measurement time during which DLI calls were being serviced under this PSB. |
| Most Active DLI Calls | This graph is shown only if IMS measurement data was recorded. It shows the most active IMS DLI calls. Up to five DLI calls are reported. |

Most active DLI calls

This graph is shown only if IMS measurement data was recorded. It shows the most active IMS DLI calls. Up to five DLI calls are reported.

| Under Heading | This is Displayed |
|---------------|--|
| Samples | The number of samples done during the measurement upon which this graph is based. This number represents 100 percent of the data upon which the graph is based and is used as the divisor to compute the percentages shown in other lines in the graph. |
| DLI Call | A DLI call identified by three fields: a unique sequence number assigned to the DLI call; its DLI function code; and its PCB name. The percentage and the graph represent the proportion of samples in which processing of this DLI call was observed. The percentage and the graph represent the proportion of the overall measurement time during which all executions of this DLI call were being serviced. |

Most active DB2 plans

This graph is shown only if DB2 measurement data was recorded. It shows the most active DB2 plan names. Up to five DB2 plans are reported.

| Under Heading | This is Displayed |
|--------------------------|--|
| Samples | The number of samples done during the measurement upon which this graph is based. This number represents 100 percent of the data and is used as the divisor to compute the percentages shown for each Package or DBRM. |
| DB2 Package or DBRM Name | The number of samples SQL servicing was occurring against SQL statements defined in the indicated Package or DBRM. |

Most active packages/DBRMs

This graph is shown only if DB2 measurement data was recorded. It shows the most active DB2 Packages/DBRMs. Up to 5 DB2 Package names or DBRM names are reported. A DBRM name is shown instead of a Package name in the event the DBRM was bound directly to the Plan instead of to a Package.

| Under Heading | This is Displayed |
|--------------------------|--|
| Samples | The number of samples done during the measurement upon which this graph is based. This number represents 100 percent of the data and is used as the divisor to compute the percentages shown for each Package or DBRM. |
| DB2 Package or DBRM Name | The number of samples SQL servicing was occurring against SQL statements defined in the indicated Package or DBRM. |

Most active SQL statements

This graph is shown only if DB2 measurement data was recorded. It shows the most active DB2 SQL statements. Up to five SQL statements are reported.

| Under Heading | This is Displayed |
|------------------------------|--|
| Samples | The number of samples done during the measurement upon which this graph is based. This number represents 100 percent of the data and is used as the divisor to compute the percentages shown for each SQL statement. |
| DBRM: Statement SQL Function | The number of samples SQL servicing was occurring for the indicated SQL statement. The DBRM name, the statement number and the type of SQL statement are shown. |

Measurement values

This section of the report shows various values relating to the measurement. These appear under the following categories:

- Request parameters
- Measurement environment
- Measurement statistics
- CPU consumption

Request parameters

These values were established when the measurement was requested.

| Under Heading | This is Displayed |
|------------------|--|
| Request number | The unique four-digit identifier assigned to the measurement. |
| Description | A description specified when the measurement was requested. |
| Sample File DSN | The data set name of the measurement file. |
| Retention | The date upon which the measurement file is to be deleted by Application Performance Analyzer. |
| Data extractors | The specified data extractors (DB2, CICS, etc.) |
| Requesting user | The TSO user ID of the user that requested the measurement. |
| Time of request | The time of day the request was made. |
| Date of request | The date upon which the request was made. |
| Job name | The name of the job that was specified to be measured. |
| Step name/number | The step name or step number that was specified to be measured, if applicable. |
| Step program | The name of the step program that was specified to be measured, if applicable. |

| Under Heading | This is Displayed |
|----------------------|---|
| Number of samples | The number of samples specified. |
| Duration | The specified measurement duration. |
| Data extractors | The specified data extractors (DB2, CICS, etc.) |
| Active/pending | Indicates whether the measurement request specified an active job (an immediate measurement) or one that was to run later when execution of the job step is detected. |
| Proc step name | The procedure step name, if specified. |
| Delay time | The number of seconds specified for which the start of the measurement was to be delayed from the start of the job step. |

Measurement environment

Values relating to the environment in which the measurement took place are reported here.

| Under Heading | This is Displayed |
|----------------------|---|
| Job name | The name of the measured job. |
| Job number | The job number of the measured job assigned by JES. |
| Step name | The name of the measured step. |
| ASID | The ASID (address space ID) of the measured job. |
| DB2 attach type | The type of DB2 attachment, if DB2 data recorded. |
| Region size <16MB | The region size in the 24 bit address range. |
| Region size >16mb | The region size above the 24 bit address range. |
| Step program | The name of the measurement step program (specified in the EXEC JCL statement). |
| Region type | The type of region (Batch, TSO, IMS, CICS, etc.) measured. |
| System ID | The system identifier of the system on which the measurement took place. |
| SMFID | The SMF ID assigned to the system on which the measurement took place. |
| O/S Level | The operating system and level. |
| APA vers. | The version of Application Performance Analyzer that performed the measurement. |
| Nbr of CPUs | The number of CPUs in the system on which the measurement took place. |
| CPU rate factor | The factor used to determine CPU performance. |
| MIPS per CPU | The speed, in machine instructions per second, of one CPU. This is derived using the CPU rate factor. |
| CPU model | The CPU model number. |
| CPU version | The CPU version. |
| SUs per second | The number of service units per CPU second. |

Measurement statistics

| Under Heading | This is Displayed |
|--------------------|--|
| Start time | The time at which the measurement was initiated. |
| End time | The time at which the measurement ended. |
| Start date | The date upon which the measurement was initiated. |
| End date | The date upon which the measurement ended. |
| Total samples | The total number of samples taken during the measurement. |
| Sampling rate | The overall sampling rate expressed in samples per second. |
| CPU/WAIT samples | The number of samples in which CPU activity was observed or all TCBs were in wait state. Excluded from this count are samples in which no CPU activity was observed and one or more TCBs were dispatchable. |
| TCB samples | The number of samples in which TCBs existed. This number might be slightly smaller than the total number of samples. This occurs when some samples were taken at the beginning of a job step before the step initialization had completed. |
| Overall CPU | The average system CPU utilization percentage during the measurement period. It is obtained from the field CCVUTILP, which is the system CPU utilization as viewed by the System Resource Manager (SRM). Thus, it is the CPU utilization for the entire system, not for any individual LPAR. |
| Duration | The duration of the measurement in minutes and seconds. |
| Report dataspace | The size of the dataspace used to load the sample file and create indexes for reporting. This field is reported in megabytes. |
| Sample dataspace | The size of the dataspace used to record measurement data while sampling. This is the total uncompressed size reported in megabytes. |
| Meas significance | The ratio of the number of CPU/WAIT samples to the number of TCB samples. This is a measure of the quality of the measurement data. A low value indicates that CPU resources were unavailable to service the job step. |
| CPU queued samples | The number of samples in which no activity was occurring in the address space due to the unavailability of CPU resources. |
| Pages in | The number of page-in operations that occurred during the measurement interval. |
| Pages out | The number of page-out operations that occurred during the measurement interval. |
| EXCPs | The number of EXCPs processed during the measurement interval. |

CPU consumption

This section is omitted for DDF measurements.

| Under Heading | This is Displayed |
|--------------------|--|
| CPU active samples | The number of samples in which CPU activity (one or more CPUs) was observed. |
| CPU active time | The percentage of the measurement interval CPU activity was observed. |

| Under Heading | This is Displayed |
|----------------------|--|
| CPU wait samples | The number of samples in which all TCBs were in wait state. |
| CPU wait time | The percentage of the measurement interval all TCBs were in wait state. |
| CPU time TCB | The number of CPU seconds consumed in TCB mode during the measurement interval. |
| CPU time SRB | The number of CPU seconds consumed in SRB mode during the measurement interval. This does not include any SRB time consumed by the Application Performance Analyzer measurement task. |
| Service units | The number of service units based on the CPU TCB and CPU SRB consumption. |
| Measurement SRB | The number of CPU seconds in SRB mode consumed by the Application Performance Analyzer measurement task in the measured address space. |
| zAAP CPU time | This field is displayed only when zAAP time has been recorded. The number of CPU seconds consumed on zAAP processors during the measurement interval. |
| Task Time on CP | This field is displayed only when zAAP time has been recorded. The number of CPU seconds consumed on a standard processor for non-zAAP eligible work. |
| Normalized Time | This field is displayed only when zAAP time has been recorded. The zAAP CPU time displayed as a normalized CPU time. |
| zAAP Time on CP | This field is displayed only when zAAP time has been recorded. The number of CPU seconds consumed on a standard processor for zAAP eligible work. |
| Norm. Factor | This field is displayed only when zAAP time has been recorded. The normalization factor is used to express zAAP CPU time in the time a regular CP would have used for the same work. Multiply the zAAP CPU time by this number, then divide by 256. |

DDF CPU consumption

This section is shown for DDF measurements only.

| Under Heading | This is Displayed |
|----------------------|--|
| Task CPU time | The number of seconds of CPU time used by the enclave SRB dispatchable unit for all measured DDF SQL calls. |
| Enclave CPU time | The number of seconds of CPU time used by all dispatchable units in an enclave for all measured DDF SQL calls. |
| zIIP time | The number of seconds of zIIP time used by all measured DDF SQL calls. |
| zIIP on CP time | The number of seconds of CPU time on a standard processor for zIIP-eligible work used by all measured DDF SQL calls. |


```

File View Navigate Help
-----
S01: Measurement Profile (9263/DSN1WLM)                               Row 00037 of 00119
Command ==> _____ Scroll ==> CSR
+CPU Modes -----+Reports: -----+
| Active CPU      432 100.0% ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' | S08 |
| Supv Mode      429 99.3% ===== |   |
| Prob Mode       3  0.6% = |   |
| In SVC         14  3.2% = |   |
| AMODE 24        0  0.0% |   |
| AMODE 31       166 38.4% ===== |   |
| AMODE 64       266 61.5% ===== |   |
| User Key       11  2.5% = |   |
| System Key     421 97.4% ===== |   |
+-----+-----+

+Most Active DB2 Plans -----+Reports: ---+
| Samples          379 100.0% ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' | F05 |
| VICPLAN8        335 88.3% ===== |   |
+-----+-----+

+Most Active Packages/DBRMs -----+Reports: ---+
| Samples          379 100.0% ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' | F03 |
| DB2PGM81        335 88.3% ===== |   |
| DB2PGM81         1  0.2% = |   |
+-----+-----+

+Most Active SQL Statements -----+Reports: ---+
| Samples          379 100.0% ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' | F04 |
| DB2PGM81:00203 SELECT 309 81.5% ===== |   |
| DB2PGM81:00185 SELECT  89 23.4% ===== |   |
| DB2PGM81:00194 SELECT  81 21.3% ===== |   |
| DB2PGM81:00176 SELECT  75 19.7% ===== |   |
| DB2PGM81:00217 SELECT   1  0.2% = |   |
+-----+-----+

```

Scrolling down, sample report S01 continued:

```

File View Navigate Help
-----
S01: Measurement Profile (9263/DSN1WLM)                               Row 00069 of 00119
Command ==>>> _____ Scroll ==>>> CSR
+Request parameters-----+
| Request number      9263
| Description         v8 db2+
| Sample file DSN    BPNF.SST.AVP03.R9263.RUNPGM81.SF
| Retention          Mon Jan-14-2008
| Data Extractors    DB2,DB2+
|-----|-----|
| Requesting user    AVP03
| Time of request    14:25:50
| Date of request    Wed Jul-18-2007
| Job name           DSN1WLM
| Step name/number   n/a
| Step program       n/a
| Nbr of samples     100
| Duration           1 sec
| Active/pending     Pending
| Proc step name     n/a
| Delay time         none
|-----+-----+
+Measurement environment-----+
| Job name           DSN1WLM
| Job number         JOB02411
| Step name          DB21
| Proc step name     Region size <16MB 6,208K
| ASID              36
|                   Region size >16MB 32,768K
|                   Step program DB2PGM8
|                   Region type Batch
|                   DB2 Attach type RRSAF
|-----|-----|
| System ID          X235
| SMFID              X235
| O/S level          z/OS 01.08.00
| IBM APA Version    2.400A
|-----|-----|
| Nbr of CPUs        3
| CPU rate factor    7,321
| MIPS per CPU       45
| CPU model          2096
| CPU version        00
| SUs per second     2185.4
|-----+-----+

```

Scrolling down, sample report S01 continued:

```

File View Navigate Help
-----
S01: Measurement Profile (9263/DSN1WLM)                               Row 00100 of 00119
Command ==>>> _____ Scroll ==>>> CSR
+Measurement statistics-----+
| Start time         14:26:01
| End time           14:26:05
| Start date         Wed Jul-18-2007
| End date           Wed Jul-18-2007
|-----|-----|
| Total samples      381
| Sampling rate      98.44 per sec
| CPU/WAIT samples   345
| TCB samples        379
| Overall CPU        64.49%
| Duration           3.87 sec
| Report dataspace   0.16MB
| Sample dataspace   1.63MB
| Meas significance  91.02%
| CPU queued samples 34
|-----|-----|
| Pages in           0
| Pages out          0
| EXCPs              34
|-----+-----+
+CPU consumption-----+
| CPU active samples 341
| CPU active time    89.97%
| CPU WAIT samples   4
| CPU WAIT time      1.05%
| CPU time TCB       4.98 sec
| CPU time SRB       0.02 sec
| Service Units      10,927
| Measurement SRB    0.35 sec
|-----+-----+

```

S02 - Load module attributes

This report lists information about each of the load modules for which activity was measured during the observation session. Various attributes of each of the modules are reported.

You can specify SETUP options (use the SETUP command) to exclude the following information from the report:

- ESD (External Symbol Dictionary) information.
- Modules loaded in PLPA.
- Modules loaded in the NUCLEUS.

A sample screen is shown here:

```

File View Navigate Help
-----
S02: Load Module Attributes - 0327/TSTJOB1      Row 00001 of 01699
Command ==>> _____ Scroll ==>> CSR

SORT by name enter: SN, by load address: SA, by size: SS, by loadlib: SL
Information reported for 153 load modules. (SETUP has excluded 105 modules).

Module Information for ISFMAIN
Load Address      08B74D90 to 08B75FFF
Module Size       4,720
Attributes        REUS,RENT,APFLIB
Module Location   JPA
Loadlib DDNAME    -LNKLST-
Load Library      ISF.SISFLOAD

ESD Information for ISFMAIN
External  Offset  Length  Start Addr  End Addr
ISFMAIN  000000    4714   08B74D90   08B75FF9

Module Information for ISFVTBL
Load Address      08D6E480 to 08EDDFFF
Module Size       1,506,176
Attributes        REUS,RENT,APFLIB
Module Location   JPA

```

You can place your cursor on the SORT field and enter any of the following four sort codes to re-sort the report:

- SN By Name
- SA By Load Address
- SS By Size
- SL By Loadlib

SETUP options

Enter the SETUP primary command to select options for this report. The following pop-up window will be displayed:

```

File View Navigate Help
-----
S | Options for Load Module Attributes | 001 of 00957
C |                                     | 11 ==>> CSR
  | Enter "/" to select an option
S |   _ Omit display of ESD information |
I |   _ Omit Nucleus modules from report |
  |   _ Omit PLPA modules from report
M |   _ Omit repeating modules from report |
  |                                     |
E |                                     |
-----

```

Use these options to trim down your report by omitting information that you are not interested in. You can omit ESD information, Nucleus modules, PLPA Modules, or modules that have been reloaded at a new address but have the same name and size.

S03 - Load module summary

This report lists the load modules for which activity was measured during the observation session. For further details about a particular module, enter the “++” line command.

A sample report is shown here:

| File View Navigate Help | | | | | | | |
|---|------|----------|-------|-------------|------------|------------|--------------------|
| S03: Load Module Summary (2133/TSTJOB1) | | | | | | | Row 00001 of 00124 |
| Command ==> | | | | | | Scroll ==> | PAGE |
| Module | Locn | Address | Count | Size(bytes) | Attributes | DDName | Load Library |
| CEEBINIT | JPA | 0000B088 | 1 | 61,304 | RU RN | -VLF- | |
| CEEPLPKA | PLPA | 043C3000 | 1 | 1,967,824 | | | CEE.SCEELPA |
| COFMMTGR | NUC | 012D2D10 | 1 | 752 | | | |
| COFMSCHK | PLPA | 03D0B3D8 | 1 | 3,112 | | | SYS1.LPALIB |
| CSVEXPR | PLPA | 0296C000 | 1 | 31,448 | | | SYS1.LPALIB |
| CSVGETMD | NUC | 010FF180 | 1 | 17,544 | | | |
| CSVLLSCH | NUC | 010DAE40 | 1 | 1,848 | | | |
| CSVLLTCH | NUC | 010D82E0 | 1 | 8,232 | | | |
| CSVSYNCH | NUC | 012F8CA0 | 1 | 1,936 | | | |
| CSVXLOAD | NUC | 012FD0C0 | 1 | 2,448 | | | |
| CTXRSMGR | NUC | 0130BF68 | 1 | 9,024 | | | |
| IAXGT | NUC | 016B7370 | 1 | 7,512 | | | |
| IAXPI | NUC | 017378D8 | 1 | 2,976 | | | |
| IAXPN | NUC | 0173E958 | 1 | 3,752 | | | |
| IAXPQ | NUC | 01744310 | 1 | 7,168 | | | |
| IAXPS | NUC | 00FFE3F0 | 1 | 6,224 | | | |
| IAXVF | NUC | 017C4AD0 | 1 | 14,320 | | | |

Detail line descriptions

Each line reports values under the following headings:

- Module
- Locn
- Address
- Count
- Size(bytes)
- Attributes
- DDName
- Load Library

Module

This is the module name.

Location

This is the location where the module was loaded — JPA, PLPA, or NUCLEUS. JPA is displayed in green. All other locations are displayed in red.

Address

This is the address where the module was loaded. If it is below the line, it is displayed in yellow, above the line addresses are displayed in green.

Count

The number of unique instances of the load module observed at the indicated address. This value exceeds 1 if the module was loaded, deleted and then loaded again. A high value could indicate the module was loaded (and deleted) excessively and could be causing a performance problem.

Size This is the size of the module in bytes.

Attributes

This is the attributes of the module – RU=reusable, RN=reentrant, APF=APF-authorized.

DDName

This is the DDName of the load library from which the module was loaded.

Load Library

This is the data set name of the load library from which the module was loaded.

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized here:

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Load Module | Display context help information. |
| ++ | Load Module | Show additional details. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|-------------------------------------|
| ? | Load Module | Display context help information. |
| SN | Module | Sort report by module name. |
| SS | Module | Sort report by module size. |
| SA | Module | Sort report by module load address. |
| SL | Module | Sort report by module load library |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
-----
Module Information for IGG0191A
Load Address      00D89000 to 00D8CE7F
Module Size       16,000
Attributes        NOREUS,NORENT
Module Location   PLPA
Program Group     MVS System
Subgroup          MVS Services
Function          Data Management services

ESD Information for IGG0191A
External  Offset  Length  Start Addr  End Addr
IGG0191A 000000   2292   00D89000   00D898F3
IGG0196I 0008F8    932   00D898F8   00D89C9B
IGG0196A 000CA0   1186   00D89CA0   00D8A141
IGG0196Q 001148   1984   00D8A148   00D8A907
IGG0191N 001908   2700   00D8A908   00D8B393
IGG0191Y 002398    668   00D8B398   00D8B633
IGG0191B 002638   3254   00D8B638   00D8C2ED
IGG0196B 0032F0   1040   00D8C2F0   00D8C6FF
IGG0191I 003700   1352   00D8C700   00D8CC47
IGG0193I 003C58    564   00D8CC48   00D8CE7B

```

S04 - TCB summary

Overview

A list of all TCBs (Tasks) which were active at any time during the observation session is reported. The list is arranged in hierarchical sequence with ATTACHED subtasks indented relative to the parent tasks that performed the ATTACH functions.

A sample TCB Summary report is shown here:

```

File View Navigate Help
-----
S04: TCB Summary (0756/TSTJOB1)                               Row 00001 of 00005
Command ==> _____ Scroll ==> CSR
TCB_Name                Address  Samples  CPU Active  CPU WAIT  Queued
IEAVAR00-002            8FE0A8      0
> IEAVTSDT-003          8FFE88      0
> IEESB605-004          8FFBF8      0
  > IEFIIC-005           8FB7F0      0
    > LPRAYV4-001        8FB330    3996    75.75%    8.23%   16.01%

```

Detail line descriptions

Each line reports values under the following headings.

- TCB Name
- Address
- Samples
- CPU Active
- CPU WAIT
- Queued

TCB Name

This is the name of the program associated with the task; the one specified to the ATTACH function. An index value is also appended to the name. This is a sequence number that Application Performance Analyzer assigned to each unique TCB that it observed. The value is useful for distinguishing between more than one TCB with the same name (same program ATTACHed).

For CICS measurements that have the CICS data extractor selected, the TCB mode will be displayed for CICS TCBs. This will immediately follow the TCB name.

Address

This is the address of the TCB. Only 6 hexadecimal digits are shown as TCBs always reside below the 16MB line.

Samples

This is the number of samples in which the TCB was observed.

CPU Active

This is the number of samples in which the CPU was active (instruction execution was in progress) in this TCB.

CPU WAIT

This is the number of samples in which the Task was waiting.

Queued

This is the number of samples in which the TCB was observed in Queued status; it was ready to execute but no CPU was available.

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | TCB Name | Display context help information. |
| ++ | TCB Name | Show additional details. |
| C01 | TCB Name | Display C01 report subset. |
| C02 | TCB Name | Display C02 report subset. |
| C03 | TCB Name | Display C03 report subset. |

This report does not have any line commands on headings.

Detail window

You can enter "++" (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| > LPFRAYV4-001          8FB330    3996    75.75%    8.23% 1 |
+-----+

TCB Information for LPFRAYV4-001

Nbr of Samples          3996
Active CPU Samples      3027  =====
WAIT Samples            329   ==
Queued CPU Samples      640   =====

Session CPU Time        17.778 seconds
Accumulated CPU Time    17.778 seconds
Task ATTACHED by       IEFIIIC-005
Time to ATTACH          *UNKNOWN*

```

S05 - Memory usage timeline

Overview

This timeline analysis breaks the observation session duration into a number of (approximately) fixed-length, chronological time intervals. Each line represents one of these intervals. By default, 15 intervals are reported, each representing approximately the same number of samples. This illustrates any progressive resource usage trends. The value under the heading Storage quantify the number of Page Frames, which were allocated to the address space during the interval.

A sample Memory Usage Timeline report is shown here:

```

File View Navigate Help
-----
S05: Memory Usage Timeline (0644/TSTJOB1)                      Row 00001 of 00015
Command ==> _____ Scroll ==> CSR
SEQN  Seconds  Storage <----1380K-----2530K-->
*.....+.....+.....+.....+.....+.....+.....+.....+.....+.....*
0001   0.069   1548K  =====
0002   0.205   1660K  =====
0003   0.256   2040K  =====
0004   0.180   2040K  =====
0005   0.184   2040K  =====
0006   0.209   2104K  =====
0007   0.201   2144K  =====
0008   0.205   2188K  =====
0009   0.205   2280K  =====
0010   0.209   2380K  =====
0011   0.227   2404K  =====
0012   0.201   2432K  =====
0013   0.193   2408K  =====
0014   0.214   2176K  =====
0015   0.111   1556K  =====

```

Detail line descriptions

Each line reports values under the following headings:

- SEQN
- Seconds
- Storage

SEQN This is the sequence number of the interval. Intervals are numbered 0001, 0002, etc.

Seconds

This is the duration of the interval in seconds.

Storage

This is the amount of central storage allocated to the address space. In other words, Real Storage (or “Page Frames”). This is an effective measurement of the address space’s demand on central storage. The value is expressed in units of kilobytes (1024 bytes). Each line shows the maximum value observed during the particular interval. These page frames include paged-in storage for conventional allocations (for example, obtained by GETMAIN) as well as Dataspaces and Hiperspaces.

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|--------------------------|-----------------------------------|
| ? | SEQN (sampling interval) | Display context help information. |
| ++ | SEQN (sampling interval) | Show additional details. |
| C01 | SEQN (sampling interval) | Display C01 report subset. |
| C02 | SEQN (sampling interval) | Display C02 report subset. |
| C03 | SEQN (sampling interval) | Display C03 report subset. |

This report does not have any line commands on headings.

SETUP options

Enter the SETUP primary command to select options for this report. The following pop-up window will be displayed:

```

File View Navigate Help
-----+-----
S | Options for Memory Usage Timeline | 001 of 00015
C |                                     |    ==> CSR
S | Number of Intervals . . . . . 15 |
S | This is the number of equal time intervals within |
0 | the duration of the measurement that are to be |
0 | reported. Each report line will show measurement |
0 | information for one interval. |
0 |                                     |
+-----+-----

```

Number of Intervals

Use this option to change the number of equal time intervals that are reported.

S06 - Data space usage timeline

Overview

This timeline analysis breaks the observation session duration into a number of (approximately) fixed-length, chronological time intervals. Each line represents one of these intervals. By default, 15 intervals are reported, each representing approximately the same number of samples. This illustrates any progressive resource allocation trends. The values under the heading Storage quantify the amount of virtual storage allocated to the address space for private data spaces during the interval.

A sample of the Data Space Usage Timeline report is shown here:

```
File View Navigate Help
-----
S06: Data Space Usage Timeline (0656/TSTJOB1) Row 00001 of 00015
Command ==> Scroll ==> CSR

SEQN  Seconds  Storage <-----0K-----345520K-->
*...+...+...+...+...+...+...+...+...+...+...+...+...+...+...+...*
0001   10.314  245572K  =====
0002    9.106  343232K  =====
0003    8.657  245572K  =====
0004    9.146  343444K  =====
0005    9.140  245572K  =====
0006    9.083  245572K  =====
0007    8.806  245572K  =====
0008    7.417  245572K  =====
0009    6.975  245572K  =====
0010    6.743  245572K  =====
0011    6.465  245572K  =====
0012    6.447  245572K  =====
0013    6.462  245572K  =====
0014    6.418  245572K  =====
0015    6.514  245572K  =====
```

Detail line descriptions

Each line represents reports values under the following headings.

- SEQN
- Seconds
- Storage

SEQN This is the sequence number of the interval. Intervals are numbered 0001, 0002, etc.

Seconds

This is the duration of the interval in seconds.

Storage

This is the amount of virtual storage allocated to the address space for user-key Data Spaces. The value is expressed in units of kilobytes (1024 bytes). Each line shows the maximum value observed during the particular interval.

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|--------------------------|-----------------------------------|
| ? | SEQN (sampling interval) | Display context help information. |
| ++ | SEQN (sampling interval) | Show additional details. |
| C01 | SEQN (sampling interval) | Display C01 report subset. |
| C02 | SEQN (sampling interval) | Display C02 report subset. |
| C03 | SEQN (sampling interval) | Display C03 report subset. |

This report does not have any line commands on headings.

SETUP options

Enter the SETUP primary command to select options for this report. The following pop-up window will be displayed:

```
File View Navigate Help
-----+=====
S Options for Data Space Usage Timeline          001 of 00015
C                                                    ==> CSR
S Number of Intervals . . . . . 15
S This is the number of equal time intervals within
0 the duration of the measurement that are to be
0 reported. Each report line will show measurement
0 information for one interval.
```

Number of Intervals

Use this option to change the number of equal time intervals that are reported.

S07 - TCB execution summary

Overview

A list of all TCBs (Tasks) which were active at any time during the observation session is reported. The list is arranged in hierarchical sequence with ATTACHED subtasks indented relative to the parent tasks that performed the ATTACH functions.

A sample screen is shown here:

```

File View Navigate Help
-----
S07: TCB Execution Summary (0656/TSTJOB1) Row 00001 of 00019
Command ==>> _____ Scroll ==>> CSR

TCB_Name                --- CPU Time ---
                        Measured TCBTotal <-- Measurement Interval --->
IEAVAR00-001            0.0 Sec 2.3 Sec System TCB - Not Measured
> IEAVTSDT-002          0.0 Sec 0.0 Sec System TCB - Not Measured
> IEESB605-003          0.0 Sec 1.2 Sec System TCB - Not Measured
  > IKJEFT01-004         0.0 Sec 0.3 Sec =====
    > IKJEFT02-005       0.0 Sec 0.4 Sec =====
      > IKJEFT09-006     0.0 Sec 0.0 Sec =====
        > ISPF-007       0.9 Sec 32.3 Sec =====
          > ISPTASK-008   0.0 Sec 8.5 Sec =====
            > ISPTASK-009 8.2 Sec 21.0 Sec =====
              > EX-010    0.1 Sec 0.3 Sec =====
                > ALTLIB-015 0.0 Sec 0.0 Sec =
                  > FREE-016 0.0 Sec 0.0 Sec =
                    > CALL-011 0.1 Sec 0.2 Sec =====
                      > PMSSEL-12 3.9 Sec 42.3 Sec =====
                        > EXEC-013 0.1 Sec 0.8 Sec =
                          > CALL-014 0.0 Sec 0.2 Sec =
                            > ALLOC-017 0.1 Sec 0.1 Sec =
                              > ALLOC-018 0.1 Sec 0.1 Sec =
                                > ALLOC-019 0.1 Sec 0.1 Sec =

```

Detail line descriptions

Each line represents reports values under the following headings:

- TCB Name
- CPU Time – Measured
- CPU Time – TCBTotal
- Measurement Interval

TCB Name

This is the name of the program associated with the task; the one specified to the ATTACH function. An index value is also appended to the name.

This is a sequence number that Application Performance Analyzer assigned to each unique TCB that it observed. The value is useful for distinguishing between more than one TCB with the same name (same program ATTACHed).

For CICS measurements that have the CICS data extractor selected, the TCB mode will be displayed for CICS TCBs. This will immediately follow the TCB name.

CPU Time – Measured

This reports the amount of CPU time used by the Task for the duration of the observation session. This is accurate to within the span of two sample intervals.

CPU Time – TCBTotal

This reports the amount of accumulated CPU time used by the Task since the Task was started up to the time of the end of the observation session. This is accurate to within one sample interval.

Measurement Interval

A graph is plotted here showing the span of time within the observation session interval the Task was active.

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | TCB Name | Display context help information. |
| ++ | TCB Name | Show additional details. |
| C01 | TCB Name | Display C01 report subset. |
| C02 | TCB Name | Display C02 report subset. |
| C03 | TCB Name | Display C03 report subset. |

S08 - Processor utilization summary

Usage

Use this report to see a breakdown of CPU states observed during the measurement.

Quantification

Each detail line reports the number of active CPU samples for an indicated CPU state. This is also expressed as a percentage of the total number of active CPU samples.

The CPU states are not all mutually exclusive. Overlaps in the counts reported in different detail lines will occur.

| Under Heading | This is Displayed |
|------------------------|--|
| Storage key n | The number of active CPU samples in the indicated storage protect key. A value of 8 indicates user (application) key. Other values usually indicate execution is in a system routine. |
| Problem state | The number of active CPU samples in problem state. This is the usual state for application programs. |
| Supervisor state | The number of active CPU samples in supervisor state. This mode allows execution of privileged instructions. This typically indicates execution in an operating system routine. |
| Execution in SVC | The number of active CPU samples while executing in SVC (Supervisor Call) modules. |
| Execution in real mode | The number of active CPU samples in real mode. There are no normal operating conditions under which this mode can occur. The value should always be zero indicating execution in virtual mode. |
| Primary-space mode | The number of active CPU samples in which the ASC (Address-Space Control) bits indicate execution in primary-space mode. |
| Access-register mode | The number of active CPU samples in which the ASC (Address-Space Control) bits indicate execution in Access-register (AR) mode. |

| Under Heading | This is Displayed |
|--------------------------|--|
| Secondary-space mode | The number of active CPU samples in which the ASC (Address-Space Control) bits indicate execution in secondary-space mode. |
| Home-space mode | The number of active CPU samples in which the ASC (Address-Space Control) bits indicate execution in home-space mode. |
| Execution on processor n | The number of active CPU samples in which instructions were being executed by the indicated processor. Processors in a multi-CPU system are numbered 0,1,2,3 ... etc. Specialty processors such as zAAP are identified to the right of the processor percentage. |
| In private storage ABOVE | The number of active CPU samples in which instructions were located in private storage above the 16MB boundary. |
| In private storage BELOW | The number of active CPU samples in which instructions were located in private storage below the 16MB boundary. |
| In common storage ABOVE | The number of active CPU samples in which instructions were located in common storage above the 16MB boundary. |
| In common storage BELOW | The number of active CPU samples in which instructions were located in common storage below the 16MB boundary. |
| Execution in AMODE 24 | The number of active CPU samples in which instructions were being executed in AMODE 24. |
| Execution in AMODE 31 | The number of active CPU samples in which instructions were being executed in AMODE 31. |
| Execution in AMODE 64 | The number of active CPU samples in which instructions were being executed in AMODE 64. |

Sample reports

A sample report is shown here.

```
File View Navigate Help
-----
S08: Processor Utilitization Summary (0652/TSTJOB1) Row 00001 of 00031
Command ==> _____ Scroll ==> CSR

Processor states for 6879 CPU usage measurements
```

| <u>Processor State</u> | <u>Nbr of Samples</u> | <u>Percentage</u> |
|--------------------------|-----------------------|-------------------|
| Storage key 0 | 2,884 | 41.92% |
| Storage key 1 | 347 | 5.04% |
| Storage key 5 | 193 | 2.80% |
| Storage key 7 | 4 | 0.05% |
| Storage key 8 | 3,451 | 50.16% |
| Problem state | 3,357 | 48.80% |
| Supervisor state | 3,522 | 51.19% |
| Execution in SVC | 3,501 | 50.89% |
| Execution in real-mode | 0 | 0.00% |
| Primary-space mode | 6,879 | 100.00% |
| Access-register mode | 0 | 0.00% |
| Secondary-sapce mode | 0 | 0.00% |
| Home-space mode | 0 | 0.00% |
| Execution on processor 0 | 3,660 | 53.20% |
| Execution on processor 1 | 3,219 | 46.79% |
| In private storage | 1,366 | 19.85% |
| In private storage BELOW | 120 | 1.74% |
| In common storage | 2,837 | 41.24% |
| In common storage BELOW | 2,556 | 37.15% |
| Execution in AMODE 24 | 0 | 0.00% |
| Execution in AMODE 31 | 1 | 100.00% |
| Execution in AMODE 64 | 0 | 0.00% |

S09 - Measurement analysis

Usage

This report presents various textual statements, each representing an observation made about some aspect of execution of the measured job. The purpose of each of these observations is to provide a synoptic analysis of an area of resource usage and, in some cases, suggest where some performance improvement opportunities might exist.

It is important that you analyze these observations in the context of how you would expect the measured job to perform. Some of the statements in this report might draw your attention to aspects of resource consumption that is perfectly normal for the job. For example, high CPU consumption might be noted in a certain module in a situation where you would actually expect high CPU usage in that module.

Sample reports

A sample report is shown here.

```
File View Navigate Help
-----
S09: Measurement Analysis (9458/TSTJOB1) Row 00001 of 00031
Command ==> _____ Scroll ==> CSR

This report presents various textual statements pertaining to specific
aspects of application performance observed during the measurement
session. Each statement identifies areas of activity and resource
consumption or causes of execution delay and suggests areas where
performance improvement opportunities might exist.

+-----+
| 1. Small CPU sample size |
| This measurement recorded a relatively small number of active CPU |
| observations. Some figures shown in CPU usage reports may have a high |
| margin of error. Keep this in mind when analyzing these reports. |
+-----+

+-----+
| 2. System CPU overhead |
| A high percentage of CPU activity was observed in system service |
| routines. This indicates high system overhead. The level of system |
| overhead might be normal for the type of job being measured or it might |
| be an indication of a performance problem. |
+-----+

See reports: C01 C02
+-----+
```

C01 - CPU usage by category

Overview

| This report analyzes measured CPU consumption. It attributes CPU consumption
| to the following general categories:
|
| • APPLCN – Application Code
| • SYSTEM – System/OS Services
| • DB2SQL – SQL Processing
| • DATAMG – Data Management (DASD) Requests
| • IMSDLI – IMS DL/I call processing
| • ADABAS – Adabas requests

| In addition, any execution measured at locations for which no load module name
| could be determined is attributed to a category:
|
| • NOSYMB – No Module Name Found

A sample report is shown below. When the report is first displayed, only the top level of the hierarchy is visible. To expand any of these categories to show the next hierarchical level, you can type the “+” line command on the detail line. You can also enter the “+” line command on the Name heading to expand the entire report to show all detail lines in all hierarchical levels.

```

File View Navigate Help
-----
C01: CPU Usage by Category (0638/TSTJOB01) Row 00001 of 00004
Command ==> _____ Scroll ==> CSR

Name      Description      Percent of CPU time * 10.00% ±1.8%
          *...1...2...3...4...5...6...7...8
APPLCN    Application Code  54.36 =====
SYSTEM    System/OS Services 44.30 =====
DATAMG    Data Mgmt Processing 1.03 =
NOSYMB    No Module Name    0.29

```

Detail line descriptions

Each line represents a System Object – an object to which measured activity is attributed. These lines are arranged hierarchically. You can expand a line (using the “+” line command) to reveal a breakdown into subordinate objects. Each type of object shown in this report is described here:

Category

Category is the top level in the hierarchy. CPU consumption is categorized as APPLCN, SYSTEM, DB2SQL, DATAMG, IMSDLI, ADABAS or NOSYMB.

DPA Group

Within a category – usually the SYSTEM category – load modules can be further arranged into Descriptive Program Attribution (DPA) groups. These are functional groups like: IMS, DB2, MVS™, SVC, etc.

By entering a '+' on the SYSTEM category line:

```

File View Navigate Help
-----
C01: CPU Usage by Category (0638/TSTJOB01) Row 00001 of 00004
Command ==> _____ Scroll ==> CSR

Name      Description      Percent of CPU time * 10.00% ±1.8%
          *...1...2...3...4...5...6...7...8
APPLCN    Application Code  54.36 =====
+SYSTEM   System/OS Services 44.30 =====
  DATAMG   Data Mgmt Processing 1.03 =
  NOSYMB   No Module Name    0.29

```

The list of objects in this category is expanded to the next level of the hierarchy to include DPA groups:

```

File View Navigate Help
-----
C01: CPU Usage by Category (0638/TSTJOB01) Row 00001 of 00009
Command ==> _____ Scroll ==> CSR

Name      Description      Percent of CPU time * 10.00% ±1.8%
          *...1...2...3...4...5...6...7...8
APPLCN    Application Code  54.36 =====
SYSTEM    System/OS Services 44.30 =====
  → SVC    SVC Routines      42.14 =====
  → MVS    MVS System        2.06 ==
  → NUCLEUS Nucleus Modules  0.06
  → IMS    IMS Subsystem     0.03

DATAMG    Data Mgmt Processing 1.03 ==
NOSYMB    No Module Name    0.29

```

Note: Using the SETUP primary command, you can specify aggregation of modules into Group or Subgroup. Subgroup offers a more granular, less inclusive categorization than Group.

In this sample screen Subgroup has been selected in SETUP, note that the SVC group has now been replaced with SVC subgroups (a subgroup for each SVC type.)

```

File View Navigate Help
-----
C01: CPU Usage by Category (0638/TSTJOB01) Row 00001 of 00012
Command ==> _____ Scroll ==> CSR

```

| Name | Description | Percent of CPU time * 10.00% ±1.8% |
|------------|----------------------|------------------------------------|
| | | *...1...2...3...4...5...6...7...8 |
| APPLCN | Application Code | 54.36 ===== |
| SYSTEM | System/OS Services | 44.30 ===== |
| → SVCTYPE1 | Type 1 System SVC | 18.94 ===== |
| → SVCTYPE3 | Type 3 System SVC | 10.38 ===== |
| → SVCTYPE4 | Type 4 System SVC | 8.72 ===== |
| → SVCTYPE2 | Type 2 System SVC | 4.09 ===== |
| → MVS | MVS System | 2.06 = |
| → NUCLEUS | Nucleus Modules | 0.06 |
| → IMS | IMS Subsystem | 0.03 |
| DATAMG | Data Mgmt Processing | 1.03 = |
| NOSYMB | No Module Name | 0.29 |

Name Column

The symbolic name of the Group/Subgroup appears under this heading.

Description Column

A Group/Subgroup description appears under this heading.

CPU Percent Column

The aggregation of activity measured under the named Group/Subgroup appears under this heading as a percentage of CPU time.

Load Module

A load module line appears under a Group/Subgroup line, under a Category line, or under an SVC line.

For example, to see the load modules under the Group/Subgroup line CICS, enter + on the CICS object:


```

File View Navigate Help
-----
C01: CPU Usage by Category (0621/TSTJOB01) Row 00001 of 00014
Command ==> _____ Scroll ==> CSR

```

| Name | Description | Percent of CPU time * 10.00% | +3.8% |
|------------|----------------------|-----------------------------------|-------|
| | | *...1...2...3...4...5...6...7...8 | |
| SYSTEM | System/OS Services | 93.67 | ===== |
| → +ICS | CICS Services | 47.43 | ===== |
| → SVCTYPE1 | Type 1 System SVC | 22.43 | ===== |
| → MVS | MVS System | 5.42 | === |
| → NUCLEUS | Nucleus Modules | 5.27 | === |
| → SVCTYPE2 | Type 2 System SVC | 5.12 | === |
| → LEBASE | LE Base Modules | 3.61 | = |
| → USERSVC | User/Vendor SVC | 1.95 | = |
| → DB2 | DB2 Services | 1.95 | = |
| → SM | Storage Manager | 0.30 | |
| → LECOBOL | LE COBOL component M | 0.15 | |
| NOSYMB | No Module Name | 6.02 | === |
| APPLCN | Application Code | 0.30 | |

The CICS Group has now been expanded to show load modules in the next hierarchical level:

```

File View Navigate Help
-----
C01: CPU Usage by Category (0621/TSTJOB01) Row 00001 of 00014
Command ==> _____ Scroll ==> CSR

```

| Name | Description | Percent of CPU time * 10.00% | +1.8% |
|------------|--------------------|-----------------------------------|-------|
| | | *...1...2...3...4...5...6...7...8 | |
| SYSTEM | System/OS Services | 93.67 | ===== |
| → CICS | CICS Services | 47.43 | ===== |
| → DFHSIP | CICS Services | 22.89 | ===== |
| → DFHAPLI | CICS Services | 3.46 | == |
| → DFHPGDM | PG domain - intia | 3.46 | == |
| → DFHFCVS | File access VSAM r | 2.86 | = |
| → DFHZCB | VTAM working set m | 2.86 | = |
| → DFHAIP | CICS Services | 2.40 | = |
| → DFHMNDML | CICS Services | 1.35 | = |
| → DFHMCX | BMS fast path modu | 1.35 | = |
| → DFHZCP | Terminal managemen | 1.05 | = |
| → DFHF CFR | File control file | 0.90 | |
| → DFHAPSM | AP domain - transa | 0.75 | |

Name Column

The load module name appears under this heading.

Description Column

If a DPA functional description is found for the module name, it is reported under this heading. Otherwise "Application Program" is displayed.

CPU Percent Column

The measured CPU execution for this Load Module appears under this heading.

CSECT (Control Section)

These lines can appear as subordinate, breakdown items under a load module line. If Application Performance Analyzer was able to find ESD (External Symbol Dictionary) information, during the measurement process, for a load module, these items will appear under the load module and the measured activity will be attributed to them.

Name Column

The CSECT name appears under this heading.

Description Column

This will display "CSECT in xxxxxxxx" where xxxxxxxx is the name of the load module to which the CSECT belongs.

SVC (Supervisor Call)

This line shows attribution of measured activity during execution of an MVS Supervisor Call.

Name Column

"SVC" followed by a 3-digit decimal SVC number (000 to 255) appears under this heading. For example — 'SVC120'.

Description Column

A description of the SVC service, or the name of the macro which invokes the SVC appears under this heading. For example: "GETMAIN/FREEMAIN."

SQL Statement

This item attributes measured activity to a DB2 SQL statement.

Name Column

A sequence number is assigned by Application Performance Analyzer to each unique SQL statement observed during the measurement. This sequence number is shown in the name field. It is possible for some sequences numbers to be missing (sequence gaps) from the report. This will occur if a sequence number was assigned to SQL statements but no CPU activity was measured for these statements.

Description Column

The name of the program that issued the SQL request followed by the precompiler statement number (enclosed in parentheses) is shown here. This is followed by the SQL function (e.g. SELECT, INSERT, COMMIT).

DL/I Call

This item attributes measured activity to an IMS DL/I call.

Name Column

A sequence number is assigned to each unique DL/I call statement observed during the measurement. This sequence number is shown in the name field.

Description Column

The DL/I function code appears followed by the PCB name followed by the relative PCB number in parentheses. The location of the call, in *csect+offset* format, follows.

Adabas Call

This item attributes measured activity to an Adabas call.

Name Column

A sequence number is assigned to each unique Adabas call statement observed during the measurement. This sequence number is shown in the name field.

Description Column

The name of the program that issued the Adabas request and the

offset within the program, followed by the Adabas command code that was issued, is displayed in this field.

Unresolved Address

This item attributes measurement activity to a range of addresses for which a corresponding load module name could not be determined.

Name Column

Activity observed in a 4096 (4K) byte range of addresses is reported in an Unresolved Address line. This range is expressed in the format "HHHHHxxx" where HHHHH are the 5 high order hexadecimal digits of the address. For example: '08915xxx' means the range from 08915000 to 08915FFF.

Description Column

"Unresolved Address" appears under this heading.

Subset reports

This report can generate subset reports for any detail line. By entering a report code on a detail line, a pop-up subset report is displayed for this item. The item selected is scaled to 100 percent. The available subset reports are listed below in "Line commands, on objects."

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|--|-----------------------------------|
| ? | Category, Load Module, SVC, CSECT, SQL command, Unresolved Address, DLI call, Adabas call. | Display context help information. |
| ++ | Category, Load Module, SVC, CSECT, SQL command, Unresolved Address, DLI call, Adabas call. | Show additional details. |
| + | Category, Load Module, SVC, SQL command, DLI call, Adabas call. | Expand to reveal next level. |
| - | Category, Load Module, SVC, SQL command, DLI call, Adabas call. | Collapse to hide next level. |
| SV | SV Category, SVC, SQL command, DLI call, Adabas call. | Sort next level by value. |
| SN | Category, SVC, SQL command, DLI call, Adabas call. | Sort next level by name. |
| M | Load Module, CSECT. | Display load module information. |
| P | Load Module, CSECT, SQL command, DLI call, Adabas call. | Display source program mapping. |
| C01 | Category, Load Module, SVC, CSECT, SQL command, Unresolved Address, DLI call, Adabas call. | Display C01 report subset. |
| C02 | Category, Load Module, SVC, CSECT, SQL command, Unresolved Address, DLI call, Adabas call. | Display C02 report subset. |

| Cmd | When Applied To Object | Action |
|-----|--|----------------------------|
| C03 | Category, Load Module, SVC, CSECT, SQL command, Unresolved Address, DLI call, Adabas call. | Display C03 report subset. |
| C08 | Category, Load Module, SVC, CSECT, SQL command, Unresolved Address, DLI call, Adabas call. | Display C08 report subset. |
| C09 | Category, Load Module, SVC, CSECT, SQL command, Unresolved Address, DLI call, Adabas call. | Display C09 report subset. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size. |
| + | Percent CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent CPU | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

SETUP options

The following SETUP options can be selected with the SETUP primary command:

Reporting by Group / SubGroup

This option allows you to aggregate modules into Group or SubGroup. SubGroup offers a more granular, less inclusive categorization than Group. For example, when reporting by Group, all SVCs would be reported under the "SVC" Group. When reporting by SubGroup, SVCs would be reported under SubGroups such as SVCTYPE1, SVCTYPE2, etc.

Show the DB2SQL category

This shows activity attributed to DB2 SQL statements. If it is not selected, the activity will instead be included in the appropriate system modules in the SYSTEM category. This is not available for CICS measurements.

Show the DATAMG category

This shows activity attributed to data management functions, which include basic access functions such as READ and WRITE. Processing of OPEN and CLOSE functions is not included in this category. If it is not selected, the activity will instead be included in the appropriate system modules in the SYSTEM category.

Show the IMSDLI category

This shows activity attributed to IMS DLI calls. If it is not selected, the activity will instead be included in the appropriate system modules in the SYSTEM category.

Show the ADABAS category

When the Adabas extractor is on, this shows activity attributed to Adabas

|
|

requests. If it is not selected, the activity is included in the appropriate system modules in the SYSTEM category.

Minimum CPU percentage

You can set this option to eliminate modules where the CPU percentage is below a certain threshold.

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+
| > SVCTYPE1 Type 1 System SVC 4.78 00 |
+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+
Calculation Details
CPU measurements 139
Grouped under Type 1 System SVC
Total CPU measurements 2,906
Percent in category 4.78%
+-----+-----+-----+-----+-----+-----+
Processor states for the CPU usage measurements
+-----+-----+-----+-----+-----+-----+
Processor State Nbr of Samples Percentage
+-----+-----+-----+-----+-----+-----+
Storage key 0 111 79.85%
Storage key 6 5 3.59%
Storage key 8 23 16.54%
+-----+-----+-----+-----+-----+-----+
Problem state 1 0.71%
Supervisor state 138 99.28%
+-----+-----+-----+-----+-----+-----+
Execution in SVC 139 100.00%
+-----+-----+-----+-----+-----+-----+
Execution in real-mode 0 0.00%
+-----+-----+-----+-----+-----+-----+
Primary-space mode 139 100.00%
Access-register mode 0 0.00%
Secondary-space mode 0 0.00%
Home-space mode 0 0.00%
+-----+-----+-----+-----+-----+-----+
Execution on processor 0 80 57.55%
Execution on processor 1 59 42.44%
+-----+-----+-----+-----+-----+-----+
In private storage ABOVE 1 0.71%
In private storage BELOW 0 0.00%
In common storage ABOVE 82 58.99%
In common storage BELOW 56 40.28%
+-----+-----+-----+-----+-----+-----+
Execution in AMODE 24 0 0.00%
Execution in AMODE 31 139 100.00%
Execution in AMODE 64 0 0.00%
+-----+-----+-----+-----+-----+-----+

```

C02 - CPU usage by module

Overview

This report analyzes measured CPU consumption. It attributes CPU consumption to load modules.

In addition, any execution measured at locations for which no load module name could be determined is attributed to hexadecimal address ranges.

A sample report as it is initially displayed, with no expansion, is shown here:

```
File View Navigate Help
-----
C02: CPU Usage by Module (0656/TSTJOB01) Row 00001 of 00207
Command ==> Scroll ==> CSR

Name      Description      Percent of CPU time * 10.00% ±1.1%
          *....1....2....3....4....5....6....7....8
ISRSUPC   Application Progr 39.34 =====
C0020     Application Progr 14.57 =====
IGG0I93B  QSAM/BSAM Process 3.57 ==
IGDDCFSR  Storage Managemen 3.25 ==
ISPMAIN   Application Progr 2.66 =
C0325     Application Progr 2.47 =
ISPSUBS   Application Progr 2.44 =
C0200     Application Progr 2.16 =
IOSVSSCQ  Nucleus Routine   1.99 =
IAXPQ     Nucleus Routine   1.94 =
IAXVF     Nucleus Routine   1.83 =
IAXVP     Nucleus Routine   1.58 =
IEAVESVC  Supervisor Contro 1.56 =
IECVEXCP  Execute channel p 1.48 =
C0399     Application Progr 1.38 =
C0310     Application Progr 0.92
```

Detail line descriptions

Each line represents a System Object – an object to which measured activity is attributed. These lines are arranged hierarchically. You can expand a line (using the “+” line command) to reveal a breakdown into subordinate objects. Each type of object shown in this report is described here:

Load Module

Name Column the load module name appears under this heading.

Description Column

If a DPA functional description is found for the module name, it is reported under this heading. Otherwise “Application Program” is displayed.

CSECT (Control Section)

These lines can appear as subordinate, breakdown items under a load module line. If Application Performance Analyzer was able to find ESD (External Symbol Dictionary) information, during the measurement process, for a load module, these items will appear under the load module and the measured activity will be attributed to them.

A sample report with the second hierarchical level (CSECT) displayed is shown here:

```

File View Navigate Help
-----
C02: CPU Usage by Module (0656/TSTJOB01) Row 00005 of 00220
Command ==> _____ Scroll ==> CSR
Name      Description      Percent of CPU time * 2.50% ±1.1%
          *...1...2...3...4...5...6...7...8...9
ISPMAIN   Application Progr  2.66 =====
→ ISPMBP  CSECT in ISPMAI  1.26 ===
→ ISPMBX  CSECT in ISPMAI  0.52 =
→ ISPMOB  CSECT in ISPMAI  0.37 =
→ ISPMBW  CSECT in ISPMAI  0.32 =
→ ISPMUL  CSECT in ISPMAI  0.07
→ ISPMRO  CSECT in ISPMAI  0.05
→ ISPMCO  CSECT in ISPMAI  0.01
→ ISPMTB  CSECT in ISPMAI  0.01
→ ISPMUX  CSECT in ISPMAI  0.01
→ ISPMBY  CSECT in ISPMAI  0.01

C0325    Application Progr  2.47 =====
→ C0325  CSECT in C03      2.47 =====

ISPSUBS  Application Progr  2.44 =====
C0200    Application Progr  2.16 =====

```

Name Column

The CSECT name appears under this heading.

Description Column

This will display “CSECT in xxxxxxxx” where xxxxxxxx is the name of the load module to which the CSECT belongs.

Unresolved Address

This item attributes measurement activity to a range of addresses for which a corresponding load module name could not be determined.

Name Column

Activity observed in a 4096 (4K) byte range of addresses is reported in an Unresolved Address line. This range is expressed in the format “HHHHHxxx” where HHHHH are the 5 high order hexadecimal digits of the address. For example: '08915xxx' means the range from 08915000 to 08915FFF.

Description Column

“Unresolved Address” appears under this heading.

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|--|-----------------------------------|
| ? | Load Module, CSECT, Unresolved Address | Display context help information. |
| ++ | Load Module, CSECT, Unresolved Address | Show additional details. |
| + | Load Module | Expand to reveal next level. |
| - | Load Module | Collapse to hide next level. |
| M | Load Module, CSECT | Display load module information. |

| Cmd | When Applied To Object | Action |
|-----|--|---------------------------------|
| P | Load Module, CSECT | Display source program mapping. |
| C09 | Load Module, CSECT, Unresolved Address | Display C09 report subset. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries |
| + | Description | Expand field size. |
| + | Percent CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent CPU | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:


```

File View Navigate Help
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| IDA019L1 Virtual I/O (VIO) 16.53 00000000 |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+

Calculation Details
CPU measurements                215
In load module                  IDA019L1
Total CPU measurements          1,300
Percent in category             16.53%

Processor states for the CPU usage measurements

Processor State                Nbr of Samples Percentage
Storage key 8                   215      100.00%
Problem state                   215      100.00%
Supervisor state                0         0.00%
Execution in SVC                0         0.00%
Execution in real-mode          0         0.00%
Primary-space mode              215      100.00%
Access-register mode            0         0.00%
Secondary-space mode            0         0.00%
Home-space mode                 0         0.00%
Execution on processor 0        118      54.88%
Execution on processor 1        97       45.11%
In private storage ABOVE       0         0.00%
In private storage BELOW       0         0.00%
In common storage ABOVE        215      100.00%
In common storage BELOW        0         0.00%
Execution in AMODE 24          0         0.00%
Execution in AMODE 31          215      100.00%
Execution in AMODE 64          0         0.00%

```

SETUP options

The following SETUP option can be selected with the SETUP primary command:

Minimum CPU percentage

You can set this option to eliminate modules where the CPU percentage is below a certain threshold.

C03 - CPU usage by code slice

Overview

This report attributes CPU usage to Code Slices. A code slice is a range of storage addresses containing executable object code. You can use this report to pinpoint the exact locations of hot spots – segments of code where CPU consumption is particularly high. You can use SETUP to adjust the resolution of the report by varying the size of the code slice.

Two types of detail line are shown:

- Code Slice
- Code Address

Initially, only the Code slice lines are visible. You can expand a Code Slice line (using the “+” line command) to reveal its subordinate Code Address lines. Initially, report lines are arranged in descending sequence by CPU activity. The most active items appear at the top. You can also sort by address by entering the “SA” line command either on the Address title field or on one of the first level report line address fields.

A sample report, as it is initially displayed, is shown here:

```

File View Navigate Help
-----
C03: CPU Usage by Code Slice (0656/TSTJOB01) Row 00001 of 01127
Command ==> Scroll ==> CSR

Address Size Location Percent of CPU time * 10.00% ±1.1%
*...1....2....3....4....5....6....7....8..
00D0B1F0 64 ASMFPSRH+0A80 20.90 =====
08A45CC0 64 C0020+1CC0 3.50 ==
00D0D000 64 ASMFRDLN+0080 3.23 ==
00D0F480 64 ASMFRDLN+2500 3.09 ==
08A45300 64 C0020+1300 2.21 =

```

If you wanted to expand, for example, the third line, enter the “+” line command:

```

File View Navigate Help
-----
C03: CPU Usage by Code Slice (0656/TSTJOB01) Row 00001 of 01127
Command ==> Scroll ==> CSR

Address Size Location Percent of CPU time * 10.00% ±1.1%
*...1....2....3....4....5....6....7....8..
00D0B1F0 64 ASMFPSRH+0A80 20.90 =====
08A45CC0 64 C0020+1CC0 3.50 ==
+00D0D000 64 ASMFRDLN+0080 3.23 ==
00D0F480 64 ASMFRDLN+2500 3.09 ==
08A45300 64 C0020+1300 2.21 =

```

The subordinate Code Address lines would then be displayed:

```

File View Navigate Help
-----
C03: CPU Usage by Code Slice (0656/TSTJOB01) Row 00001 of 01131
Command ==> Scroll ==> CSR

Address Size Location Percent of CPU time * 10.00% ±1.1%
*...1....2....3....4....5....6....7....8..
00D0B1F0 64 ASMFPSRH+0A80 20.90 =====
08A45CC0 64 C0020+1CC0 3.50 ==
00D0D000 64 ASMFRDLN+0080 3.23 ==
→ 00D0D000 ASMFRDLN+0080 2.30 =
→ 00D0D026 ASMFRDLN+00A6 0.51
→ 00D0D036 ASMFRDLN+00B6 0.42
00D0F480 64 ASMFRDLN+2500 3.09 ==

```

Remember, you can also expand an entire report by typing “+” on the first heading, in this report it would be the Address heading.

Detail line descriptions

Code Slice

This line represents a block (or “slice”) of contiguous bytes of object code for which CPU execution is quantified. The number of times CPU execution was observed within this block is expressed as a percentage of the total number of CPU execution observations.

The hexadecimal address of the beginning of the slice is shown under the Address heading. The size of the slice, in bytes, is shown under the Size heading. If possible, the address of the beginning of the slice is expressed in the form CSECT+offset, or Module+offset, under the Location heading.

Source program mapping can be accessed from this line by entering a “p” line command.

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to view a pop-up menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|--------------------------|-----------------------------------|
| ? | Code Slice, Code Address | Display context help information. |
| ++ | Code Slice, Code Address | Show additional details. |
| + | Code Slice | Expand to reveal next level. |
| - | Code Slice | Collapse to hide next level. |
| SV | Code Slice | Sort next level by value. |
| SA | Code Slice | Sort next level by address. |
| M | Code Slice | Display load module information. |
| P | Code Slice, Code Address | Display source program mapping. |
| C09 | Code Slice, Code Address | Display C09 report subset. |

on headings

| Cmd | When Applied To Object | Action |
|-----|----------------------------|------------------------------------|
| ? | Address, Size, Percent CPU | Display context help information. |
| + | Address | Expand to reveal all entries. |
| + | Percent CPU | Zoom in scale. |
| - | Address | Collapse to show only first level. |
| - | Percent CPU | Zoom out scale. |
| SV | Address | Sort next level by value. |
| SA | Address | Sort next level by address. |

SETUP options

The following SETUP options can be selected with the SETUP primary command:

Code slice size

Use this to adjust the size of the Code Slice to be reported.

Minimum CPU percentage

You can set this option to eliminate Code Slice entries from the report, where the CPU percentage is below a certain threshold.

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```
File View Navigate Help
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| 00FF04A0  56  CPUREL          9.84 00000          |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
Calculation Details
CPU measurements                128
Address range                    00FF04A0 to 00FF04D7
Total CPU measurements          1,300
Percent in category              9.84%

Processor states for the CPU usage measurements

Processor State                Nbr of Samples  Percentage
Storage key 0                  128           100.00%
Problem state                   0             0.00%
Supervisor state               128           100.00%
Execution in SVC                128           100.00%
Execution in real-mode          0             0.00%
Primary-space mode              128           100.00%
Access-register mode            0             0.00%
Secondary-space mode            0             0.00%
Home-space mode                 0             0.00%
Execution on processor 0        74            57.81%
Execution on processor 1        54            42.18%
In private storage ABOVE       0             0.00%
In private storage BELOW       0             0.00%
In common storage ABOVE        0             0.00%
```

C04 - CPU usage timeline

Overview

This timeline analysis breaks the observation session duration into a number of (approximately) fixed-length, chronological time intervals. Each line represents one of these intervals. By default, 15 intervals are reported, each representing approximately the same number of samples. This illustrates any progressive CPU usage trends, such as blocks of intensive consumption or long periods of waits. The percentage value and the graph quantify CPU usage for an interval. The percentage is derived by dividing the number of samples CPU activity was observed by the number of samples in the interval. This, effectively, is the percentage of time the CPU was executing instructions.

A sample CPU Usage Timeline report is shown here:

```

File View Navigate Help
-----
C04: CPU Usage Timeline (0656/TSTJOB01) Row 00001 of 00015
Command ==> _____ Scroll ==> CSR

SEQN   Seconds  Sig   Percent of Interval * 10.00% ±1.1%
      *...1...2...3...4...5...6...7...8...9...*
0001   10.324  69%  19.08  =====
0002   9.114   64%  49.55  =====
0003   8.667   70%  70.82  =====
0004   9.153   83%  43.65  =====
0005   9.161   77%  39.36  =====
0006   9.094   70%  35.46  =====
0007   8.791   75%  41.95  =====
0008   7.424   89%  12.18  =====
0009   6.988   76%  63.63  =====
0010   6.741   71%  64.83  =====
0011   6.475   75%  70.12  =====
0012   6.467   73%  68.43  =====
0013   6.465   71%  67.03  =====
0014   6.422   75%  70.42  =====
0015   6.446   72%  64.60  =====

```

Detail line descriptions

Each line represents reports values under the following headings:

- SEQN
- Seconds
- Sig

SEQN This is the sequence number of the interval. Intervals are numbered 0001, 0002, etc. You can create a subset of report C01, C02, or C03 from this line by entering the report code as a line command. A pop-up window of the report will be displayed, and the subset of data used for the report will be the samples from this interval.

Seconds

This is the duration of the interval in seconds.

Sig This quantifies the significance of the measurement for the interval. This is the percentage of samples in the interval the address space was not Queued – either CPU consumption or WAIT state was observed.

Subset reports

This report can generate subset reports for any detail line. By entering a report code on a detail line, a pop-up subset report is displayed for this item. The item selected is scaled to 100 percent. The available subset reports are listed below in “Line commands, on objects.”

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|--------------------------|-----------------------------------|
| ? | SEQN (sampling interval) | Display context help information. |

| Cmd | When Applied To Object | Action |
|-----|--------------------------|----------------------------|
| ++ | SEQN (sampling interval) | Show additional details. |
| C01 | SEQN (sampling interval) | Display C01 report subset. |
| C02 | SEQN (sampling interval) | Display C02 report subset. |
| C03 | SEQN (sampling interval) | Display C03 report subset. |
| C09 | SEQN (sampling interval) | Display C09 report subset. |

This report does not have any line commands on headings.

SETUP options

Enter the SETUP primary command to select options for this report. The following pop-up window will be displayed:

```

File View Navigate Help
-----+-----
S | Options for CPU Usage Timeline | 001 of 00015
C |                               | ==> CSR
S | Number of Intervals . . . . . 15
0 | This is the number of equal time intervals within
0 | the duration of the measurement that are to be
0 | reported. Each report line will show measurement
0 | information for one interval.
+-----+-----

```

Number of Intervals

Use this option to change the number of equal time intervals that are reported.

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
-----+-----
+-----+----- The following report line was selected -----+
| 0001      8.269  52% 22.63  ==== |
+-----+-----
Information about sampled interval

Interval Number      1
Nbr of Samples       667
Duration             0 minutes, 8.26 seconds
Active CPU Samples   151 =====
WAIT Samples         200 =====
Queued CPU Samples   316 =====
+-----+-----

```

C05 - CPU usage by task/category

Overview

This report analyzes measured CPU consumption. It shows, for each Task (TCB), the percentage of the total CPU time measured in that Task. Under each task, this information is shown under the following general categories:

APPLCN

Application Code

SYSTEM

System/OS Services

DATAMG

Data Management (DASD) Requests

DB2SQL

SQL Processing

IMSDLI

IMS DL/I Calls

IMSDLI

IMS DL/I Calls

ADABAS

Adabas requests

In addition, any activity observed at locations for which no load module name could be determined is attributed to a category:

NOSYMB

No Module Name Found

A sample report is shown below. When the report is first displayed, only the top level of the hierarchy (Tasks) is visible. Often there will only be one task, however this example has many. To expand a task to show the next hierarchical level, you can type the "+" line command on the detail line. You can also enter the "+" line command on the Name heading to expand the entire report to show all detail lines in all hierarchical levels.

```

File View Navigate Help
-----
C05: CPU Usage by Task/Category (0711/TSTJOB01) Row 00001 of 00041
Command ==> _____ Scroll ==> CSR
Name Description Percent of CPU time * 10.00% ±3.8%
*....1....2....3....4....5....6....7....8.
DFHKETCB-007 TCB=008DAD90 52.19 =====
DFHKETCB-001 TCB=008DA6B8 32.07 =====
DFHKETCB-012 TCB=008C2068 13.16 =====
DFHKETCB-008 TCB=008DAA68 2.57 =
IEAVAR00-002 TCB=008FE0A8 0.00
IEAVTSDT-003 TCB=008FFE88 0.00
DFSPAT00-024 TCB=008BC210 0.00
DFSPAT00-025 TCB=008B9E88 0.00
DFHSIP-005 TCB=008F69F8 0.00
DFSPAT00-026 TCB=008B9CD8 0.00
DFHKETCB-009 TCB=008C2E88 0.00
DFSPAT00-027 TCB=008B9A30 0.00
DFHKETCB-011 TCB=008C2750 0.00
DFSPAT00-028 TCB=008B9788 0.00
CSQCSERV-014 TCB=008BDE88 0.00
DFSPAT00-029 TCB=008B94E0 0.00
CSQCSERV-016 TCB=008BDA60 0.00

```

Detail line descriptions

Each line represents a System Object – an object to which CPU time is attributed. These lines are arranged hierarchically. You can expand a line (using the “+” line command) to reveal a breakdown into subordinate objects. Each type of object shown in this report is described here:

Task This is the highest level object in the report. Each active Task is reported. The percentage of the total measured CPU time which was measured in this Task is reported. A SETUP option is available which specifies that all Tasks – including inactive tasks – are to be displayed.

Name Column

The name of the program specified in the ATTACH macro that started the task as well as the TCB index number is shown.

Description Column

The TCB address is shown. For CICS measurements that have the CICS data extractor selected, the TCB mode is displayed for CICS TCBs. This immediately follows the TCB address.

Category

Activity within a Task is categorized as APPLCN, SYSTEM, DATAMG, DB2SQL, IMSDLI, ADABAS or NOSYMB.

DPA Group

Within a category – usually the SYSTEM category – load modules can be further arranged into Descriptive Program Attribution (DPA) groups. These are functional groups like: IMS, DB2, MVS, SVC, etc. By entering a “+” on the SYSTEM category line:


```

File View Navigate Help
-----
C05: CPU Usage by Task/Category (0711/TSTJOB01) Row 00001 of 00045
Command ==> _____ Scroll ==> CSR

Name      Description      Percent of CPU time * 10.00% ±3.8%
          *....1....2....3....4....5....6....7....8.
DFHKETCB-007 TCB=008DAD90      52.19  =====
→ +SYSTEM      System/OS Servic 52.19  =====
→ APPLCN       Application Code  0.00
→ DATAMG       Data Mgmt Proces  0.00

```

The list of objects in this category is expanded to the next level of the hierarchy to include DPA groups:

```

File View Navigate Help
-----
C05: CPU Usage by Task/Category (0711/TSTJOB01) Row 00001 of 00048
Command ==> _____ Scroll ==> CSR

Name      Description      Percent of CPU time * 10.00% ±3.8%
          *....1....2....3....4....5....6....7....8.
DFHKETCB-007 TCB=008DAD90      52.19  =====
→ SYSTEM      System/OS Servic 52.19  =====
→ SVC         SVC Routines     51.13  =====
→ CICS        CICS Subsystem   0.60
→ MVS         MVS System       0.45
→ APPLCN       Application Code  0.00
→ DATAMG       Data Mgmt Proces  0.00

```

Note: Note Using the SETUP primary command, you can specify aggregation of modules into Group or Subgroup. Subgroup offers a more granular, less inclusive categorization than Group.

In this sample screen Subgroup has been selected in SETUP, note that the SVC group has now been replaced with SVC subgroups (a subgroup for each SVC type.)

```

File View Navigate Help
-----
C05: CPU Usage by Task/Category (0711/TSTJOB01) Row 00001 of 00014
Command ==> _____ Scroll ==> CSR

Name      Description      Percent of CPU time * 10.00% ±3.8%
          *....1....2....3....4....5....6....7....8.
DFHKETCB-007 TCB=008DAD90      52.19  =====
→ SYSTEM      System/OS Servic 52.19  =====
→ SVCTYPE1    Type 1 System    24.81  =====
→ SVCTYPE2    Type 2 System    14.22  =====
→ SVCTYPE4    Type 4 System     7.11  ===
→ SVCTYPE3    Type 3 System     4.99  ==
→ CICS        CICS Subsystem   0.60
→ MVS         MVS System       0.45
→ APPLCN       Application Code  0.00
→ DATAMG       Data Mgmt Proces  0.00

```

Name Column

The symbolic name of the Group/Subgroup appears under this heading.

Description Column

A Group/Subgroup description appears under this heading.

Load Module

A load module line appears under a Group/Subgroup line, under a Category line, or under an SVC line.

For example, to see the load modules under the Group/Subgroup line MVS, enter “+” on the MVS object:

```
File View Navigate Help
-----
C05: CPU Usage by Task/Category (0711/TSTJOB01) Row 00001 of 00014
Command ==> _____ Scroll ==> CSR

Name          Description          Percent of CPU time * 10.00% ±3.8%
*....1....2....3....4....5....6....7....8.
DFHKETCB-007  TCB=008DAD90         52.19  =====
→ SYSTEM      System/OS Servic       52.19  =====
  → SVCTYPE1   Type 1 System         24.81  =====
  → SVCTYPE2   Type 2 System         14.22  =====
  → SVCTYPE4   Type 4 System          7.11   ===
  → SVCTYPE3   Type 3 System          4.99   ==
  → CICS       CICS Services         0.60
  → +VS        MVS Services          0.45
→ APPLCN      Application Code       0.00
→ DATAMG      Data Mgmt Proces      0.00
```

The MVS Group has now been expanded to show load modules in the next hierarchical level:

```
File View Navigate Help
-----
C05: CPU Usage by Task/Category (0711/TSTJOB01) Row 00001 of 00016
Command ==> _____ Scroll ==> CSR

Name          Description          Percent of CPU time * 10.00% ±3.8%
*....1....2....3....4....5....6....7....8.
DFHKETCB-007  TCB=008DAD90         52.19  =====
→ SYSTEM      System/OS Servic       52.19  =====
  → SVCTYPE1   Type 1 System         24.81  =====
  → SVCTYPE2   Type 2 System         14.22  =====
  → SVCTYPE4   Type 4 System          7.11   ===
  → SVCTYPE3   Type 3 System          4.99   ==
  → CICS       CICS Services         0.60
  → +VS        MVS Services          0.45
  → IGGCLA0    Data Managem          0.30
  → IGVVSM3I   Virtual Stor          0.15
```

Name Column

The load module name appears under this heading.

Description Column

If a DPA functional description is found for the module name, it is reported under this heading. Otherwise “Application Program” is displayed.

CSECT (Control Section)

These lines can appear as subordinate, breakdown items under a load module line. If Application Performance Analyzer was able to find ESD (External Symbol Dictionary) information, during the measurement process, for a load module, these items will appear under the load module and the measured activity will be attributed to them.

Name Column

The CSECT name appears under this heading.

Description Column

This will display "CSECT in xxxxxxxx" where xxxxxxxx is the name of the load module to which the CSECT belongs.

Source program mapping can be accessed from this line by entering a "p" line command.

SVC (Supervisor Call)

This line shows attribution of measured activity during execution of an MVS Supervisor Call.

Name Column

"SVC" followed by a 3-digit decimal SVC number (000 to 255) appears under this heading. For example, "SVC120."

Description Column

A description of the SVC service, or the name of the macro which invokes the SVC appears under this heading. For example: "GETMAIN/FREEMAIN."

DDNAME

These lines appear under the DATAMG category and indicate the DDNAME of a file to which CPU usage is attributed. The quantification indicates CPU time consumed in data management routines.

Data Management Request

These lines appear under DDNAME lines and show a further breakdown of CPU usage for the DDNAME to the specific I/O request statements.

SQL Statement

This item attributes measured activity to a DB2 SQL statement.

Name Column

A sequence number is assigned to each unique SQL statement observed during the measurement. This sequence number is shown in the name field. It is possible for some sequence numbers to be missing (sequence gaps) from the report. This will occur if a sequence number was assigned to SQL statements but no CPU activity was measured for these statements.

Description Column

The name of the program that issued the SQL request followed by the precompiler statement number (enclosed in parentheses) is shown here. This is followed by the SQL function (e.g. SELECT, INSERT, COMMIT).

DL/I Call

This item attributes measured activity to an IMS DL/I call.

Name Column

A sequence number is assigned to each unique DL/I call statement observed during the measurement. This sequence number is shown in the name field.

Description Column

The DL/I function code appears followed by the PCB name followed by the relative PCB number in parentheses. The location of the call. in *csect+offset* format, follows.

Adabas Call

This item attributes measured activity to an Adabas call.

|
|

Name Column

A sequence number is assigned to each unique Adabas call statement observed during the measurement. This sequence number is shown in the name field.

Description Column

The name of the program that issued the Adabas request and the offset within the program, followed by the Adabas command code that was issued, is displayed in this field.

Unresolved Address

This item attributes measurement activity to a range of addresses for which a corresponding load module name could not be determined.

Name Column

Activity observed in a 4096 (4K) byte range of addresses is reported in an Unresolved Address line. This range is expressed in the format "HHHHHxxx" where HHHHH are the 5 high order hexadecimal digits of the address. For example: "08915xxx" means the range from 08915000 to 08915FFF.

Description Column

"Unresolved Address" appears under this heading.

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|---|-----------------------------------|
| ? | Task, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address, DLI call, Adabas call | Display context help information. |
| ++ | Task, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address, DLI call, Adabas call | Show additional details. |
| + | Task, Category, Load Module, SVC, SQL command, DLI call, Adabas call | Expand to reveal next level. |
| - | Task, Category, Load Module, SVC, SQL command, DLI call, Adabas call | Collapse to hide next level. |
| SV | Task, Category, SVC, SQL command, DLI call, Adabas call | Sort next level by value. |
| SN | Task, Category, SVC, SQL command, DLI call, Adabas call | Sort next level by name. |
| M | Load Module, CSECT | Display load module information. |
| P | Load Module, CSECT, SQL command, DLI call, Adabas call | Display source program mapping. |
| C09 | Category, Load Module, SVC, CSECT, SQL command, Unresolved Address, DLI call, Adabas call | Display C09 report subset. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size. |
| + | Percent CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent CPU | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

SETUP options

The following SETUP options can be selected with the SETUP primary command:

Reporting by Group / SubGroup

This option allows you to aggregate modules into Group or SubGroup. SubGroup offers a more granular, less inclusive categorization than Group. For example, when reporting by Group, all SVCs would be reported under the "SVC" Group. When reporting by SubGroup, SVCs would be reported under SubGroups such as SVCTYPE1, SVCTYPE2, etc.

Include inactive tasks

You can choose to include or eliminate inactive tasks from the report. An inactive task is one for which there were no observations of CPU consumption.

Show the DB2SQL category

You can choose to show the DB2SQL category in which CPU time attributed to SQL processing is shown.

Show the DATAMG category

This shows activity attributed to data management functions, which include basic access functions such as READ and WRITE. Processing of OPEN and CLOSE functions is not included in this category. If it is not selected, the activity will instead be included in the appropriate system modules in the SYSTEM category.

Show the IMSDLI category

This shows activity attributed to IMS DLI calls. If it is not selected, the activity will instead be included in the appropriate system modules in the SYSTEM category.

Show the ADABAS category

This shows activity attributed to Adabas requests. If it is not selected, the activity will instead be included in the appropriate system modules in the SYSTEM category.

Detail window

You can enter "++" (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| > CAZ00080   Application Pr 4.73 00 |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+

Calculation Details
CPU measurements                34
In load module                  CAZ00080
Total CPU measurements          718
Percent in category             4.73%

Processor states for the CPU usage measurements

Processor State                Nbr of Samples Percentage
Storage key 0                   34      100.00%
Problem state                   0         0.00%
Supervisor state                34      100.00%
Execution in SVC                 0         0.00%
Execution in real-mode           0         0.00%
Primary-space mode              34      100.00%
Access-register mode            0         0.00%
Secondary-space mode            0         0.00%
Home-space mode                 0         0.00%
Execution on processor 0        10       29.41%
Execution on processor 1       24       70.58%
In private storage ABOVE       34      100.00%
In private storage BELOW       0         0.00%
In common storage ABOVE        0         0.00%
In common storage BELOW        0         0.00%
Execution in AMODE 24           0         0.00%
Execution in AMODE 31          34      100.00%
Execution in AMODE 64           0         0.00%

```

C06 - CPU usage by task/module

Overview

This report analyzes measured CPU consumption. It shows, for each Task (TCB), the percentage of the total CPU time measured in that Task. Under each task, a further breakdown of CPU consumption is shown by load modules.

In addition, any execution measured at locations for which no load module name could be determined is attributed to hexadecimal address ranges.

Detail line descriptions

Each line represents a System Object, an object to which measured activity is attributed. These lines are arranged hierarchically. You can expand a line (using the "+" line command) to reveal a breakdown into subordinate objects. Each type of object shown in this report is described here:

Task This is the highest level object in the report. Each active Task is reported.

The percentage of the total measured CPU time which was measured in this Task is reported. A SETUP option is available which specifies that all Tasks - including inactive tasks - are to be displayed.

Name Column

The name of the program specified in the ATTACH macro that started the task as well as the TCB index number is shown.

Description Column

The TCB address is shown. For CICS measurements that have the CICS data extractor selected, the TCB mode is displayed for CICS TCBs. This immediately follows the TCB address.

Load Module

Name Column

The load module name appears under this heading.

Description Column

If a DPA functional description is found for the module name, it is reported under this heading. Otherwise "Application Program" is displayed.

CSECT (Control Section)

These lines can appear as subordinate, breakdown items under a load module line. If Application Performance Analyzer was able to find ESD (External Symbol Dictionary) information, during the measurement process, for a load module, these items will appear under the load module and the measured activity will be attributed to them.

Name Column

The CSECT name appears under this heading.

Description Column

This will display "CSECT in xxxxxxxx" where xxxxxxxx is the name of the load module to which the CSECT belongs.

Unresolved Address

This item attributes measurement activity to a range of addresses for which a corresponding load module name could not be determined.

Name Column

Activity observed in a 4096 (4K) byte range of addresses is reported in an Unresolved Address line. This range is expressed in the format "HHHHHxxx" where HHHHH are the 5 high order hexadecimal digits of the address. For example: "08915xxx" means the range from 08915000 to 08915FFF.

Description Column

"Unresolved Address" appears under this heading.

Sample reports

A sample report is shown below. When the report is first displayed, only the top level of the hierarchy (Tasks) is visible. Often there will only be one task, however this example has many. To expand a task to show the next hierarchical level, you can type the "+" line command on the detail line. You can also enter the "+" line command on the Name heading to expand the entire report to show all detail lines in all hierarchical levels.

```

File View Navigate Help
-----
C06: CPU Usage by Task/Module (0711/TSTJOB01) Row 00001 of 00021
Command ==> _____ Scroll ==> CSR

Name      Description      Percent of CPU time * 10.00% ±2.3%
          *....1....2....3....4....5....6....7....8.
PMSEL-012 TCB=008B8318      46.65 =====
TSPTASK-008 TCB=008B8D90      11.87 =====
PMSEL-021 TCB=008B8318      11.18 =====
TSPF-007 TCB=008E1190      10.70 =====
EXEC-017 TCB=008B8A50       5.13 ===
EX-018 TCB=008B8A50       3.21 ==
CALL-014 TCB=008A0B50       2.51 =
CALL-011 TCB=008A0130       1.92 =
CALL-020 TCB=008A0130       1.76 =
EX-010 TCB=008B8B48       1.28 =
EXEC-013 TCB=008A0E68       1.07 =
ALLTLIB-019 TCB=008A00F0       0.96
ALLTLIB-015 TCB=008A00F0       0.90
FREE-016 TCB=008A00F0       0.80
TEAVAR00-001 TCB=008FE0A8       0.00
TEAVTSDT-002 TCB=008FFE88       0.00
TEESB05-003 TCB=008FFBF8       0.00

```

Here is a sample with the first task fully expanded: Line commands:

```

File View Navigate Help
-----
C06: CPU Usage by Task/Module (0694/TSTJOB01) Row 00001 of 01111
Command ==> _____ Scroll ==> CSR

Name      Description      Percent of CPU time * 10.00% ±2.3%
          *....1....2....3....4....5....6....7....8.
PMSEL-012 TCB=008B8318      46.65 =====
→ C0200 Application Prog      9.84 ====
→ C0200 CSECT in C0        9.84 ====
→ C0020 Application Prog      7.86 ==
→ C0020 CSECT in C0        7.86 ==
→ BKNCESUP Application Prog      2.88 =
→ BKNCESUP CSECT in BKNCE      2.35 =
→ BKNSTFMT CSECT in BKNCE      0.53
→ IGDDCFSR Storage manageme      2.30 =
→ IAXVF Nucleus Routrine      2.08 =
→ IARVFRMN Real storage m      2.08 =
→ C0010 Application Prog      1.65 =
→ C0010 CSECT in C0        1.65 =
→ IAXVP Nucleus Routine      1.33 =
→ IARVPGTI Real storage m      1.33 =
→ IGWLHLS DFSMS              0.96
→ IGWLHRLS DFSMS              0.32
→ IGWLHAJB DFSMS              0.16

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|---|-----------------------------------|
| ? | Task, Load Module, CSECT, Unresolved Address | Display context help information. |
| ++ | Task, Load Module, CSECT, Unresolved Address | Show additional details. |

| Cmd | When Applied To Object | Action |
|-----|--|----------------------------------|
| + | Task, Load Module | Expand to reveal next level. |
| - | Task, Load Module | Collapse to hide next level. |
| SV | Task | Sort next level by value. |
| SN | Task, Category | Sort next level by name. |
| M | Load Module, CSECT | Display load module information. |
| P | Load Module, CSECT | Display source program mapping. |
| C09 | Load Module, CSECT, Unresolved Address | Display C09 report subset. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size. |
| + | Percent CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent CPU | Zoom out scale. |
| SV | Name, Description, Percent CPU | Sort next level by value. |
| SN | Name, Description, Percent CPU | Sort next level by name. |

SETUP options

The following SETUP option can be selected with the SETUP primary command:

Include inactive tasks

You can choose to include or eliminate inactive tasks from the report. An inactive task is one for which there were no observations of CPU consumption.

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+
| > CAZ00080   Application Pr 4.73 00 |
+-----+-----+-----+-----+-----+-----+
Calculation Details
CPU measurements                34
In load module                   CAZ00080
Total CPU measurements           718
Percent in category              4.73%

Processor states for the CPU usage measurements

Processor State                Nbr of Samples Percentage
Storage key 0                   34      100.00%
Problem state                   0         0.00%
Supervisor state                34      100.00%
Execution in SVC                 0         0.00%
Execution in real-mode           0         0.00%
Primary-space mode              34      100.00%
Access-register mode            0         0.00%
Secondary-space mode            0         0.00%
Home-space mode                 0         0.00%
Execution on processor 0        10      29.41%
Execution on processor 1        24      70.58%
In private storage ABOVE        34      100.00%
In private storage BELOW        0         0.00%
In common storage ABOVE         0         0.00%
In common storage BELOW         0         0.00%
Execution in AMODE 24           0         0.00%
Execution in AMODE 31           34      100.00%
Execution in AMODE 64           0         0.00%

```

C07 - CPU usage by procedure

Usage

Use this report to see quantification of CPU usage at the source program procedure level.

Quantification

Each report line quantifies CPU usage as a percentage. Each percentage represents the ratio of CPU consumption observed for the reported item to the total CPU consumption measured in the address space.

Detail line hierarchy

C07 displays detail lines at a single level. Up to four types of detail lines are reported.

- Level 1 Source Procedure
- Level 1 Source Procedure
- Level 1 Source Procedure

...
Level 1 APPLCN Category
Level 1 SYSTEM Category
Level 1 NOSYMB Category

Detail line descriptions

Source procedure detail line

This identifies a source program procedure and quantifies CPU usage attributed to the procedure. The source procedure detail lines are displayed only when the source program(s) are mapped and loaded. See Chapter 10, "Source program mapping," on page 543 for more details.

| Under Heading | This is Displayed |
|---------------------|---|
| Program | The name of the CSECT in the module containing the source procedure. |
| Procedure Name | The name of the source procedure. |
| Percent of CPU Time | The percentage of CPU time consumed during execution in the source procedure. |

APPLCN Category detail line

Any execution measured in application programs that could not be associated with a source program procedure is quantified in this detail line. No further breakdown of this category is reported. Use report C01 to see further details.

SYSTEM Category detail line

Any execution measured in system programs that could not be associated with a source program procedure is quantified in this detail line. No further breakdown of this category is reported. Use report C01 to see further details.

NOSYMB Category detail line

Any execution measured at addresses that could not be associated with a load module is quantified in this detail line. No further breakdown of this category is reported. Use report C01 to see further details.

Sample reports

A sample report is shown here:

| Program | Procedure Name | Percent of CPU time * 10.00% ±2.5% |
|----------|---------------------|------------------------------------|
| LPFRAYV4 | B300-PROCESS-ACCTS | 32.86 ===== |
| LPFRAYV4 | A200-CALCULATE-RTE | 16.60 ===== |
| LPFRAYV4 | A100-CALCULATE-MTX | 11.22 ===== |
| LPFRAYV4 | B300-EXIT | 0.53 |
| LPFRAYV4 | A200-EXIT | 0.46 |
| LPFRAYV4 | A100-EXIT | 0.06 |
| SYSTEM | System/OS Services | 37.45 ===== |
| APPLCN | No Procedure Mapped | 0.79 |

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Program, Category | Display context help information. |
| ++ | Program, Category | Show additional details. |
| M | Program | Display load module information. |
| P | Program | Display source program mapping. |
| C09 | Program, Category | Display C09 report subset. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------------|-----------------------------------|
| ? | Program, Procedure Name, Percent CPU | Display context help information. |
| + | Procedure name | Expand field size. |
| + | Percent CPU | Zoom in scale. |
| - | Procedure name | Reduce field size. |
| - | Percent CPU | Zoom out scale. |
| SV | Program, Procedure Name, Percent CPU | Sort next level by value. |
| SN | Program, Procedure Name, Percent CPU | Sort next level by name. |

SETUP options

Enter the SETUP primary command to select options for this report. The following pop-up window will be displayed:

```
+-----+
| Options for CPU Analysis by Procedure |
|                                     |
| Enter "/" to select an option      |
| /  Omit procedures for which no CPU activity was |
|    measured. Unselect to report all procedure |
|    names.                               |
|                                     |
+-----+
```

By default, only those procedures for which CPU activity was measured are displayed. Deselect this option to display all procedure names.

Detail window

You can enter "++" (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

- Level 3 Source statement
- Level 4 System module
- Level 5 CSECT in System module
- Level 4 Unresolved address

Detail line descriptions

Application module

This identifies an application module to which attribution of CPU usage in system routines has been referred. During the measurement, Application Performance Analyzer determined that execution in system modules was initiated by a system request statement (such as a CALL) with an invocation point in the identified application module.

| Under Heading | This is Displayed |
|---------------------|--|
| Name | Name of application load module in which CPU usage measured in system modules was attributed. |
| Description | Functional description of the load module if one is available. Otherwise, "Application Program" is shown here. |
| Percent of CPU Time | The percentage of attributed system module CPU usage referred back to this application module. |

CSECT in application module

These lines appear under the application module detail line. Each one reports an external name (CSECT) within the application module in which invocation points for attributed CPU execution reside.

| Under Heading | This is Displayed |
|---------------------|---|
| Name | Name of CSECT in which CPU usage measured in system modules was attributed. |
| Description | CSECT in loadmodname appears here. |
| Percent of CPU Time | The percentage of attributed system module CPU usage referred back to this CSECT. |

Offset in CSECT

These lines appear under the CSECT detail line. Each one reports a return address offset – the point in the CSECT at which control is returned from the attributed system services CPU usage. This identifies the address of the application statement.

| Under Heading | This is Displayed |
|---------------------|---|
| Name | The hexadecimal offset of the return point in the CSECT of the system execution invocation request. |
| Description | "Offset in csectname" appears here. |
| Percent of CPU Time | The percentage of CPU time measured in this system routine for the indicated invocation/return address. |

Source statement

One or more lines showing the source statement appear at the same level as the Offset in CSECT detail line. This appears only when the source program has been mapped and loaded. For more information, see Chapter 10, "Source program mapping," on page 543.

System Module

This line identifies a system module in which CPU usage was measured and attributed to the reported application module.

| Under Heading | This is Displayed |
|---------------------|--|
| Name | The name of a system module in which CPU usage was measured and referred back to the application module under which this line appears. |
| Description | Functional description of the system module. |
| Percent of CPU Time | The percentage of CPU time measured in this system routine for the invocation/return address under which this line appears. |

CSECT in System Module

This line identifies a CSECT within a system module in which CPU usage was measured and attributed to the reported application module.

| Under Heading | This is Displayed |
|---------------------|--|
| Name | The name of the CSECT in which CPU usage was measured and referred back to the application module under which this line appears. |
| Description | Functional description of the CSECT. |
| Percent of CPU Time | The percentage of CPU time measured in this system CSECT for the invocation/return address under which this line appears. |

Unresolved address

This line identifies an unresolved address in which CPU usage was measured and attributed to the reported application module.

| Under Heading | This is Displayed |
|---------------------|--|
| Name | An unresolved address range in which CPU usage was measured and referred back to the application module under which this line appears. |
| Description | "Unresolved Address" |
| Percent of CPU Time | The percentage of CPU time measured in this address range. |

Sample reports

A sample report is shown here. This has been expanded to the third level, and the source has been mapped and loaded. (It can be expanded further to show details of the modules.)

```

File View Navigate Help
-----
C08: CPU Usage Referred Attribution (3598/TSTJOB01) Row 00001 of 00027
Command ==> _____ Scroll ==> CSR
Name      Description          Percent of CPU time * 10.00% ±1.0%
          *....1....2....3....4....5....6....7....8.
SAMPLE1  Application Program      88.37 =====
→ SAMPLE1 CSECT in SAMPLE1      88.37 =====
  → 000854 Attribution Offset 35.06 =====
    > Source statement in: Sample1Mainline
    > Open Input SalesActivityFile
  → 00088A Attribution Offset 24.23 =====
    > Source statement in: Sample1Mainline
    > Open OUTPUT SalesReportFile
  → 000918 Attribution Offset 14.22 =====
    > Source statement in: Sample1Mainline
    > Close SalesActivityFile
  → 000936 Attribution Offset 13.89 =====
    > Source statement in: Sample1Mainline
    > Close SalesReportFile
  → 000814 Attribution Offset 0.73
    > Source statement in: Sample1Mainline
    > Inspect B tallying C for all '**'replacing all**'
  → 000A72 Attribution Offset 0.20
    > Source statement in: ProcessSalesRecord
    > Read SalesActivityFile

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|--|-----------------------------------|
| ? | Application Module, CSECT, Attribution Offset, System Module, Unresolved Address | Display context help information. |
| ++ | Application Module, CSECT, Attribution Offset, System Module, Unresolved Address | Show additional details. |
| + | Application Module, CSECT, Attribution Offset | Expand to reveal next level. |
| - | Application Module, CSECT, Attribution Offset, System Module, Unresolved Address | Collapse to hide next level . |
| M | Application Module, CSECT, System Module, Unresolved Address | Display load module information. |
| P | CSECT, Attribution Offset | Display source program mapping. |
| C09 | Application Module, CSECT, Attribution Offset, System Module, Unresolved Address | Display C09 report subset. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size. |
| + | Percent CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent CPU | Zoom out scale . |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

More: +

```

+----- The following report line was selected -----+
| > 0005BE  Attribution Offset 7.23 0000                |
+-----+

```

Calculation Details

```

CPU measurements attributed to services 582
In the csect                             LPFRAYV4
Return offset                             0005BE
Total CPU measurements                    8,040
Percent in category                       7.23%

```

```

Source Statement in: PROCEDURE-DIVISION
                    write VSAM-record

```

Processor states for the CPU usage measurements

| Processor State | Nbr of Samples | Percentage |
|--------------------------|----------------|------------|
| Storage key 0 | 303 | 52.06% |
| Storage key 8 | 279 | 47.93% |
| Problem state | 257 | 44.15% |
| Supervisor state | 325 | 55.84% |
| Execution in SVC | 325 | 55.84% |
| Execution in real-mode | 0 | 0.00% |
| Primary-space mode | 582 | 100.00% |
| Access-register mode | 0 | 0.00% |
| Secondary-space mode | 0 | 0.00% |
| Home-space mode | 0 | 0.00% |
| Execution on processor 0 | 302 | 51.89% |
| Execution on processor 1 | 280 | 48.10% |
| In private storage ABOVE | 0 | 0.00% |
| In private storage BELOW | 0 | 0.00% |
| In common storage ABOVE | 420 | 72.16% |
| In common storage BELOW | 162 | 27.83% |
| Execution in AMODE 24 | 0 | 0.00% |
| Execution in AMODE 31 | 582 | 100.00% |
| Execution in AMODE 64 | 0 | 0.00% |

More: -

```

In private storage ABOVE          1      0.02%
In private storage BELOW         31      0.92%
In common storage ABOVE          2,222  66.48%
In common storage BELOW          1,088  32.55%

Execution in AMODE 24             192     5.74%
Execution in AMODE 31            3,150  94.25%
Execution in AMODE 64              0      0.00%

```

C09 - CPU usage by PSW/object code

Use this report to see information about sampled CPU execution at the machine-instruction level. This report is most useful when used in Subset Analysis mode to provide more detailed analysis for a particular quantification. You can display this report by entering the “C09” line command on an eligible CPU usage report detail line. The C09 report will show you information about the executed machine instructions.

Quantification

Each report line quantifies CPU usage as a percentage. Each percentage represents the ratio of CPU consumption observed for the reported item to the total CPU consumption measured in the address space.

Detail line hierarchy

The first level detail line shows a PSW (program status word) address value that Application Performance Analyzer recorded when it made an active CPU observation. Each repeated CPU usage observation at the same PSW address is accumulated and reported as a single detail line.

In addition to the PSW address value, Application Performance Analyzer creates a separate first-level detail line if any of the following values are different:

- Execution in problem or supervisor mode
- Address mode (AMODE) 24, 31 or 64
- Address-space control: primary-space, AR mode, secondary-space or homespace
- PSW key
- SVC number if execution was in a supervisor call
- Object code at the PSW address

You can expand the first level detail line to show the object code at the PSW address. Object code is reported in the form of disassembled machine instructions. Application Performance Analyzer displays a line for each machine instruction from 12 bytes of object code captured during the measurement. The PSW address points to the sixth byte of the 12 bytes, so the first instructions reported are the ones that preceded the sampled instruction.

Detail line descriptions

PSW address line

One line appears for each unique PSW address. By default, these are sorted in descending sequence by CPU activity.

| Under Heading | This is Displayed |
|---------------|---|
| Address | The PSW address of the sampled instruction. |
| Module | The load module name at the sampled address, or 'Unknown' if Application Performance Analyzer was unable to determine the module name. |
| AM | The address mode (AMODE): 24, 31 or 64. |
| S/P | The SVC number if execution was in a supervisor call or S or P followed by the storage key. “S” indicates supervisor mode and “P” indicates problem mode. For example, “P8” indicates execution in problem mode in storage key 8. |

| Under Heading | This is Displayed |
|---------------------|--|
| AS | The address space control mode. AR indicates access-register mode, SS indicates secondary-space mode and HS indicates home-space mode. Blanks are shown for primary-space mode. |
| ASID | The ASID (address space ID) in hexadecimal of the address space that acquired the storage at the PSW address. This is shown only if the storage was acquired by an address space other than the measured one – a foreign address space. One example of this is the processing of an SQL request. Execution often occurs in load modules fetched into storage by one of the DB2 address spaces. |
| Percent of CPU Time | The percentage of CPU time observed at the indicated address. |

Machine instruction line

Each line shows one machine instruction in disassembled format. These lines pertain to the PSW address line shown above.

Sample reports

A sample report is shown here. The first entry has been expanded with the “+” line command.

```

File View Navigate Help
+-----+
C09: CPU Usage by PSW/Object Code (2133/TSTJOB01)      Row 00001 of 00018
Command ==> _____ Scroll ==> CSR

Address  Module  AM  S/P AS  ASID  Percent of CPU Time * 10.00% ±1.6%
*....1....2....3....4....5....6...
17801392 - LPFRAYVS 31  P8          98.2 =====
→ LPFRAYVS+05D6  47F0 B240    BC 15,576(,R11)
→ LPFRAYVS+05DA  FA20 9820  A06C AP 2080(3,R9),108(1,R10)76(,R11)

178012E4 + LPFRAYVS 31  P8          0.48
17801360 + LPFRAYVS 31  P8          0.25
17801416 + LPFRAYVS 31  P8          0.23
17801302 + LPFRAYVS 31  P8          0.15
17801312 + LPFRAYVS 31  P8          0.15
178012C4 + LPFRAYVS 31  P8          0.12
17801342 + LPFRAYVS 31  P8          0.10
178012F0 + LPFRAYVS 31  P8          0.07
17801362 + LPFRAYVS 31  P8          0.05
178012C6 + LPFRAYVS 31  P8          0.05
1780129A + LPFRAYVS 31  P8          0.02
1780137A + LPFRAYVS 31  P8          0.02
178012C0 + LPFRAYVS 31  P8          0.02

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Address | Display context help information. |
| ++ | Address | Show additional details. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|----------------------------------|
| + | Address | Expand to reveal next level. |
| - | Address | Collapse to hide next level . |
| M | Address | Display load module information. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Address, Percent CPU | Display context help information. |
| + | Address | Expand to reveal all entries. |
| + | Percent CPU | Zoom in scale. |
| - | Address | Collapse to show only first level. |
| - | Percent CPU | Zoom out scale. |
| SV | Address | Sort next level by value. |
| SA | Address | Sort next level by address. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| 18802338 + LPFRAYV4 31 P8          50.44 000000000000000000000000 |
+-----+

Calculation Details
CPU measurements          4,056
PSW address                18802338
Total CPU measurements    8,040
Percent in category       50.44%

PSW Information
PSW Address                18802338
Module Name                LPFRAYV4
CSECT Name                 LPFRAYV4
Module+Offset              LPFRAYV4+1748
CSECT+Offset               LPFRAYV4+1748
Addressing Mode (AMODE)    31 bit
Address Space Control      Primary Space
Problem/Supervisor Mode    Problem Mode

Machine Instructions
LPFRAYV4+1744  47F0 B0C2      BC   15,194(,R11)
LPFRAYV4+1748  FA20 A830 9075  AP   2096(3,R10),117(1,R9) <- PSW add
+-----+

```

W01 - WAIT time by task/category

Overview

This report analyzes measured CPU WAIT time. It shows, for each Task (TCB), the percentage of elapsed time the Task was observed to be in a WAIT. Under each task, this information is shown under the following general categories:

- APPLCN**
Application Code
- SYSTEM**
System/OS Services
- DATAMG**
Data Management (DASD) Requests
- DB2SQL**
SQL Processing
- IMSDLI**
IMS DL/I calls
- ADABAS**
Adabas requests

In addition, any WAIT time observed at locations for which no load module name could be determined is attributed to a category:

- NOSYMB**
No Module Name Found

The Task (TCB) name is the object at the top level of the hierarchy for this report, and is the only object visible when the report is first displayed.

A sample report is shown here, as it would appear when it is first displayed:

```

File View Navigate Help
-----
W01: WAIT Time by Category (0651/TSTJOB01) Row 00001 of 00009
Command ==>> _____ Scroll ==>> CSR
Name      Description      Percent of CPU time * 10.00% ±2.3%
          *....1....2....3....4....5....6....7....8.
ISPTASK-008 TCB=008B8D90      99.65 =====
PMSEL-012   TCB=00893528      99.58 =====
ISPF-007    TCB=008E1190      99.18 =====
ISPTASK-009 TCB=008B8738      16.54 =====
EXEC-013    TCB=008A67C0       1.01 =
ALLOC-017   TCB=008A67C0       0.06
ALLOC-015   TCB=008A67C0       0.05
ALLOC-016   TCB=008A67C0       0.04
CALL-014    TCB=008A6390       0.00

```

You can expand the entire report to show all detail lines at all hierarchical levels by entering the “+” line command on the Name heading.

Detail line descriptions

Each line represents a System Object – an object to which WAIT time is attributed. These lines are arranged hierarchically. You can expand a line (using the “+” line command) to reveal a breakdown into subordinate objects. Each type of object shown in this report is described here:

Task This is the highest level object in the report. Each active Task is reported. The percentage of the measurement time interval the task was observed to be WAITing is reported.

Note: A SETUP option is available which specifies that all Tasks – including inactive tasks – are to be displayed.

Name Column

The name of the program specified in the ATTACH macro that started the task as well as the TCB index number is shown.

Description Column

The TCB address is shown. For CICS measurements that have the CICS data extractor selected, the TCB mode is displayed for CICS TCBs. This immediately follows the TCB address.

Category

WAIT time within a Task is categorized as APPLCN, SYSTEM, DATAMG, IMSDLI, DB2SQL, ADABAS or NOSYMB.

DPA Group

Within a category – usually the SYSTEM category – load modules can be further arranged into Descriptive Program Attribution (DPA) groups. These are functional groups like: IMS, DB2, VSAM.

Note: A SETUP option is available from which you can specify aggregation of modules into Group or Subgroup. Subgroup offers a more granular, less inclusive categorization than Group. Application Performance Analyzer uses the module name to locate descriptive information in its DPA tables.

Name Column

The symbolic name of the Group/Subgroup appears under this heading.

Description Column

A Group/Subgroup description appears under this heading.

Load Module

A load module line appears under a Group/Subgroup line, under a Category line, or under an SVC line.

Name Column

The load module name appears under this heading.

Description Column

If a DPA functional description is found for the module name, it is reported under this heading. Otherwise “Application Program” is displayed.

CSECT (Control Section)

These lines can appear as subordinate, breakdown items under a load module line. If Application Performance Analyzer were able to find ESD (External Symbol Dictionary) information, during the measurement process, for a load module, these items will appear under the load module and the measured WAIT time will be attributed to them.

Name Column

The CSECT name appears under this heading.

Description Column This will display “CSECT in xxxxxxxx” where xxxxxxxx is the name of the load module to which the CSECT belongs.

SVC (Supervisor Call)

This line shows attribution of measured WAIT time during execution of an MVS Supervisor Call.

Name Column

“SVC” followed by a 3-digit decimal SVC number (000 to 255) appears under this heading. For example, “SVC120.”

Description Column

A description of the SVC service, or the name of the macro which invokes the SVC appears under this heading. For example, “GETMAIN/FREEMAIN.”

SQL Statement

This item attributes WAIT activity to a DB2 SQL statement.

Name Column

A sequence number is assigned to each unique SQL statement observed during the measurement. This sequence number is shown in the name field. It is possible for some sequences numbers to be missing (sequence gaps) from the report. This will occur if a sequence number was assigned to SQL statements but no WAIT activity was measured for these statements.

Description Column

The name of the program that issued the SQL request followed by the precompiler statement number (enclosed in parentheses) is shown here. This is followed by the SQL function (for example, SELECT, INSERT, COMMIT).

DL/I Call

This item attributes WAIT activity to an IMS DL/I call.

Name Column

A sequence number is assigned to each unique DL/I call statement observed during the measurement. This sequence number is shown in the name field.

Description Column

The DL/I function code appears followed by the PCB name followed by the relative PCB number in parentheses. The location of the call, in *csect+offset* format, follows.

Adabas Call

This item attributes WAIT activity to an Adabas call.

Name Column

A sequence number is assigned to each unique Adabas call statement observed during the measurement. This sequence number is shown in the name field.

Description Column

The name of the program that issued the Adabas request and the offset within the program, followed by the Adabas command code that was issued, is displayed in the field.

Unresolved Address

This item attributes measurement WAIT time to a range of addresses for which a corresponding load module name could not be determined.

Name Column

WAIT time observed in a 4096 (4K) byte range of addresses is reported in an Unresolved Address line. This range is expressed in the format “HHHHHxxx” where HHHHH are the 5 high order hexadecimal digits of the address. For example, “08915xxx” means the range from 08915000 to 08915FFF.

Description Column

“Unresolved Address” appears under this heading.

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|---|-----------------------------------|
| ? | Task, Category, Load Module, SVC, CSECT, Unresolved Address | Display context help information. |
| ++ | Task, Category, Load Module, SVC, CSECT, Unresolved Address | Show additional details. |
| + | Task, Category, Load Module, SVC | Expand to reveal next level. |
| - | Task, Category, Load Module, SVC | Collapse to hide next level. |
| SV | Task, Category, SVC | Sort next level by value. |
| SN | Task, Category, SVC | Sort next level by name. |
| M | Load Module, CSECT | Display load module information. |
| P | Load Module, CSECT | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|---------------------------------|------------------------------------|
| ? | Name, Description, Percent WAIT | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size. |
| + | Percent CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduces field size |
| - | Percent CPU | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

SETUP options

The following SETUP options can be selected with the SETUP primary command:

Reporting by Group / SubGroup

This option allows you to aggregate modules into Group or SubGroup. SubGroup offers a more granular, less inclusive categorization than Group. For example, when reporting by Group, all SVCs would be reported under the “SVC” Group. When reporting by SubGroup, SVCs would be reported under SubGroups such as SVCTYPE1, SVCTYPE2, etc.

Include inactive tasks

You can choose to include or eliminate inactive tasks from the report. An inactive task is one for which there were no observations of CPU consumption.

| **Show the DB2SQL category**

| This shows activity attributed to DB2 SQL statements. If it is not selected,
| the activity is included in the appropriate system modules in the SYSTEM
| category. This category is not applicable for CICS measurements.

| **Show the DATAMG category**

| This shows activity attributed to data management functions, which
| include basic access functions such as READ and WRITE. Processing of
| OPEN and CLOSE functions is not included in this category. If it is not
| selected, the activity will instead be included in the appropriate system
| modules in the SYSTEM category.

| **Show the IMSDLI category**

| This shows activity attributed to IMS DLI calls. If it is not selected, the
| activity will instead be included in the appropriate system modules in the
| SYSTEM category.

| **Show the ADABAS category**

| This shows activity attributed to Adabas requests. If it is not selected, the
| activity is included in the appropriate system modules in the SYSTEM
| category.

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```
File View Navigate Help
+-----+
+----- The following report line was selected -----+
| ISPF-007      TCB=008DFA10      98.66 0000000000000000000000000000000000|
+-----+

Calculation Details
Wait measurements          9,866
Task                       ISPF-007
Total measurements        10,000
Percent of total          98.66%
```

W02 - WAIT time by task/module

Overview

This report analyzes measured CPU WAIT time. It shows, for each Task (TCB), the percentage of elapsed time the Task was observed to be in a WAIT. Under each task, a further breakdown of wait time is shown by load modules.

In addition, any wait time measured at locations for which no load module name could be determined is attributed to hexadecimal address ranges.

Detail line descriptions

Each line represents a System Object - an object to which measured activity is attributed. These lines are arranged hierarchically. You can expand a line (using the “+” line command) to reveal a breakdown into subordinate objects. Each type of object shown in this report is described here:

Task This is the highest level object in the report. Each active Task is reported. The percentage of the total measured CPU time which was measured in this Task is reported. A SETUP option is available that specifies that all Tasks, including inactive tasks, are to be displayed.

Name Column

The name of the program specified in the ATTACH macro that started the task as well as the TCB index number is shown.

Description Column

The TCB address is shown. For CICS measurements that have the CICS data extractor selected, the TCB mode is displayed for CICS TCBs. This immediately follows the TCB address.

Load Module

Name Column

The load module name appears under this heading.

Description Column

If a DPA functional description is found for the module name, it is reported under this heading. Otherwise "Application Program" is displayed.

CSECT (Control Section)

These lines can appear as subordinate, breakdown items under a load module line. If Application Performance Analyzer was able to find ESD (External Symbol Dictionary) information, during the measurement process, for a load module, these items will appear under the load module and the measured wait time will be attributed to them.

Name Column

The CSECT name appears under this heading.

Description Column

This will display "CSECT in xxxxxxxx" where xxxxxxxx is the name of the load module to which the CSECT belongs.

Unresolved Address

This item attributes wait time to a range of addresses for which a corresponding load module name could not be determined.

Name Column

Activity observed in a 4096 (4K) byte range of addresses is reported in an Unresolved Address line. This range is expressed in the format "HHHHHxxx" where HHHHH are the 5 high order hexadecimal digits of the address. For example: "08915xxx" means the range from 08915000 to 08915FFF.

Description Column

"Unresolved Address" appears under this heading. A sample report is shown here. File

A sample report is shown here.

```

File View Navigate Help
-----
W02: WAIT Time by Module (0651/TSTJOB01) Row 00001 of 00017
Command ==> _____ Scroll ==> CSR

Name          Description          Percent of Time in WAIT * 10.00% ±0.8%
*...1...2...3...4...5...6...7...8.
IKJEFT01-004  TCB=008FF6E0          100.00 =====
IKJEFT02-005  TCB=008E1640          100.00 =====
IKJEFT09-006  TCB=008E1328          100.00 =====
EX-010        TCB=008B84DB          100.00 =====
CALL-011      TCB=008B8248          100.00 =====
ISPTASK-008   TCB=008B8D90          99.65 =====
PMSEL-012    TCB=00893528          99.58 =====
ISPF-007     TCB=008E1190          99.18 =====
ISPTASK-009   TCB=008B8738          16.54 =====
EXEC-013     TCB=008A67C0           1.01 =
ALLOC-017    TCB=008A67C0           0.06
ALLOC-015    TCB=008A67C0           0.05
ALLOC-016    TCB=008A67C0           0.04
IEAVAR00-001 TCB=008FE0A8           0.00
IEAVTSDT-002 TCB=008FFE88           0.00
IEESB605-003 TCB=008FFBF8           0.00
CALL-014     TCB=008A6390           0.00

```

A sample report with a task fully expanded is shown here.

```

File View Navigate Help
-----
W02: WAIT Time by Module (0651/TSTJOB01) Row 00001 of 00086
Command ==> _____ Scroll ==> CSR

Name          Description          Percent of Time in WAIT * 10.00% ±0.8%
*...1...2...3...4...5...6...7...8.
ISPTASK-009   TCB=008B8738          16.54 =====
  ↳ ISPSUBS      Application Prog 11.21 =====
    ↳ ISPCDI      CSECT in ISPSU  8.86 =====
    ↳ ISPCAT      CSECT in ISPSU  2.21 =
    ↳ ISPCCI      CSECT in ISPSU  0.09
    ↳ ISPPDP      CSECT in ISPSU  0.04
  ↳ IGG019BB     Data Management  4.57 ===
    ↳ IGG019BB     CSECT in IGG01  4.57 ===
  ↳ IGG0CLHA     Data Management  0.25
    ↳ IGG0CLXA     CSECT in IGG0C  0.25
  ↳ IEAVEWAT     Task management  0.18
    ↳ IGC001      CSECT in IEAVE  0.18
  ↳ IGC018      Supervisor Contr 0.17
    ↳ SVC018      CSECT in IGC01  0.17
  ↳ IGC0013I     Supervisor Contr 0.12
    ↳ ICVDS03     CSECT in IGC00  0.07
    ↳ ICVCM103    CSECT in IGC00  0.04

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|--|-----------------------------------|
| ? | Task, Load Module, CSECT, Unresolved Address | Display context help information. |
| ++ | Task, Load Module, CSECT, Unresolved Address | Show additional details. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|----------------------------------|
| + | Task, Load Module | Expand to reveal next level. |
| - | Task, Load Module | Collapse to hide next level. |
| SV | Task | Sort next level by value. |
| SN | Task | Sort next level by name. |
| M | Load Module, CSECT | Display load module information. |
| P | Load Module, CSECT | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|---------------------------------|------------------------------------|
| ? | Name, Description, Percent WAIT | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size. |
| + | Percent CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent CPU | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

SETUP options

The following SETUP option can be selected with the SETUP primary command:

Include inactive tasks

You can choose to include or eliminate inactive tasks from the report. An inactive task is one for which there were no observations of CPU consumption.

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+
+-----+ The following report line was selected -----+
| ISPF-007   TCB=008DFA10   98.66 00000000000000000000000000000000|
+-----+
Calculation Details
Wait measurements          9,866
Task                       ISPF-007
Total measurements        10,000
Percent of total           98.66%
+-----+

```

W03 - WAIT time referred attribution

Usage

Use this report to see attribution of WAIT time. WAITs issued in system modules are referred back to the points of invocation in application modules.

Quantification

Each report line quantifies WAIT time as a percentage. Each percentage represents the ratio of time in WAIT to the elapsed time of the measurement.

Detail line hierarchy

The first level detail line shows a task (TCB). For CICS measurements that have the CICS data extractor selected, the TCB mode is displayed for CICS TCBs. This immediately follows the TCB address. The second level detail line shows an application module to which WAIT time in system modules has been attributed. You can expand each line to reveal additional hierarchical levels of detail (using the "+" line command).

The hierarchy is illustrated here:

- Level 1 Task
- Level 2 Application Module
- Level 3 CSECT in application module
- Level 4 Offset in CSECT
- Level 4 Source statement
- Level 5 System module
- Level 6 CSECT in System module
- Level 5 Unresolved address

Detail line descriptions

Application module

This identifies an application module to which attribution of WAIT time in system routines has been referred. During the measurement, Application Performance Analyzer determined that WAIT in system modules was initiated by a system request statement (such as a CALL) with an invocation point in the identified application module.

| Under Heading | This is Displayed |
|-------------------------|--|
| Name | Name of application load module in which WAIT time observed in system modules was attributed. |
| Description | Functional description of the load module if one is available. Otherwise, "Application Program" is shown here. |
| Percent of Time in WAIT | The percentage of attributed system module WAIT time referred back to this application module. |

CSECT in application module

These lines appear under the application module detail line. Each one reports an external name (CSECT) within the application module in which invocation points for attributed WAIT reside.

| Under Heading | This is Displayed |
|---------------|---|
| Name | Name of CSECT in which WAIT time observed in system modules was attributed. |

| Under Heading | This is Displayed |
|-------------------------|---|
| Description | CSECT in loadmodname appears here. |
| Percent of Time in WAIT | The percentage of attributed system module WAIT time referred back to this CSECT. |

Offset in CSECT

These lines appear under the CSECT detail line. Each one reports a return address offset – the point in the CSECT at which control is returned from the attributed system services WAIT. This identifies the address of the application statement.

| Under Heading | This is Displayed |
|-------------------------|--|
| Name | The hexadecimal offset of the return point in the CSECT of the system execution invocation request. |
| Description | “Offset in csectname” appears here. |
| Percent of Time in WAIT | The percentage of WAIT time observed in this system routine for the indicated invocation/return address. |

Source statement

One or more lines showing the source statement appear at the same level as the Offset in CSECT detail line. This appears only when the source program has been mapped and loaded. See Chapter 10, “Source program mapping,” on page 543 for more information.

System module

This line identifies a system module in which WAIT was observed and attributed to the reported application module.

| Under Heading | This is Displayed |
|-------------------------|--|
| Name | The name of a system module in which WAIT time was measured and referred back to the application module under which this line appears. |
| Description | Functional description of the system module. |
| Percent of Time in WAIT | The percentage of WAIT time observed in this system routine for the invocation/return address under which this line appears. |

CSECT in System module

This line identifies a CSECT within a system module in which wait time was measured and attributed to the reported application module.

| Under Heading | This is Displayed |
|-------------------------|--|
| Name | The name of the CSECT in which wait time was measured and referred back to the application module under which this line appears. |
| Description | Functional description of the CSECT. |
| Percent of Time in WAIT | The percentage of WAIT time measured in this system CSECT for the invocation/return address under which this line appears. |

Unresolved address

This line identifies an unresolved address in which WAIT time was observed and attributed to the reported application module.

| Under Heading | This is Displayed |
|-------------------------|--|
| Name | An unresolved address range in which WAIT time was measured and referred back to the application module under which this line appears. |
| Description | "Unresolved Address" |
| Percent of Time in WAIT | The percentage of WAIT time observed in this address range. |

Sample reports

A sample report is show here, it has been expanded four levels.

```

File View Navigate Help
-----
W03: WAIT Referred Attribution by Task (1917/TSTJOB01)      Row 00001 of 00053
Command ==>> _____ Scroll ==>> CSR

Name      Description      Percent of CPU time * 10.00% ±0.9%
          *....1....2....3....4....5....6....7....8.
LPFRAYVS-001 TCB=008EA1C0      39.68 =====
→ LPFRAYVS      Regression test3 39.11 =====
  → LPFRAYVS      CSECT in LPFRA 39.11 =====
    → 0005AA      Attribution 35.76 =====
      > Source statement in: PROCEDURE-DIVISION
      > write VSAM-record

      → IDA019L1      Virtual I/ 35.76 =====
    → 0004C0      Attribution 2.72 =
      > Source statement in: PROCEDURE-DIVISION
      > OPEN OUTPUT VSAM1-FILE

      → IGG0CLHA      Data Manag 2.48 =
      → IDA019L1      Virtual I/ 0.23
      → IGC0013I      Supervisor 0.00
    → 00065A      Attribution 0.34
      > Source statement in: PROCEDURE-DIVISION
      > close VSAM1-FILE

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|---|-----------------------------------|
| ? | Task, Load Module, CSECT, Offset, System Module, Unresolved Address | Display context help information. |
| ++ | Task, Load Module, CSECT, Offset, System Module, Unresolved Address | Show additional details. |
| + | Task, Load Module, Offset | Expand to reveal next level. |
| - | Task, Load Module, Offset | Collapse to hide next level. |
| SV | Task | Sort next level by value. |
| SN | Task | Sort next level by name. |
| M | Load Module, CSECT, System Module | Display load module information. |
| P | CSECT, Offset | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|---------------------------------|------------------------------------|
| ? | Name, Description, Percent WAIT | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size. |
| + | Percent WAIT | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent WAIT | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

SETUP options

Enter the SETUP primary command to select options for this report. The following pop-up window will be displayed:

```
+-----+
| Options for WAIT Referred Attribution by Task |
|                                             |
| Enter "/" to select an option             |
| / Include "inactive" tasks in the report.  |
|   Inactive task is one for which there   |
|   were no observations of CPU consumption. |
|                                             |
+-----+
```

Include Inactive Tasks

You can include or eliminate inactive tasks from the report. An inactive task is one for which there were no observation of CPU consumption.

W04 - WAIT time by task ENQ/RESERVE

Usage

Use this report to view the wait time, QNAME and RNAME resulting from ENQueue or RESERVE requests.

Level 1 shows the MVS TCB (Task Control Block). The Name field identifies the attached subtask load module as well as a sequence number (Task Index). The Task/TCB address is shown in the Description field.

When expanded, level 2 shows a line for each unique ENQueue or RESERVE request. The Name column shows the QNAME and the description column shows the RNAME of the request. The RNAME can be up to 255 bytes. The full RNAME is shown in the detail window.

Quantification

Each report line quantifies wait time measured as a percentage of total time. The percentage represents the ratio of the number of samples in which an ENQueue/RESERVE request was in a wait state to the total number of samples.

Detail line hierarchy

An unexpanded report shows a line for each MVS task for which ENQueue or RESERVE activity was sampled. You can expand each line to reveal an additional hierarchical level of detail.

The hierarchy is illustrated here:

Level 1 TCB Task
Level 2 ENQueue/RESERVE

Detail line descriptions

TCB Task detail line

This is the first-level detail line.

| Under Heading | This is Displayed |
|-------------------------|--|
| Name | The name of the program specified in the ATTACH macro that started the task as well as the TCB index number. |
| Description | The TCB address is shown. For CICS measurements that have the CICS data extractor selected, the TCB mode is displayed for CICS TCBs. This immediately follows the TCB address. |
| Percent of Time in WAIT | The percentage of the measurement interval time during which the task was waiting on an ENQueue/RESERVE. |

ENQueue/ RESERVE detail line

This is the second-level detail line.

| Under Heading | This is Displayed |
|-------------------------|---|
| Name | The QNAME is shown. |
| Description | The RNAME is shown. Only 40 characters are shown. If the RNAME is longer, the full name can always be found in the Detail window. |
| Percent of Time in WAIT | The percentage of the measurement interval time during which the indicated ENQueue/RESERVE was waiting. |

Sample reports

A sample report is show here, it has been expanded to the second level.

| File View Navigate Help | | |
|--|------------------------|---------------------------------------|
| W04: Wait Time by Task ENQ/RESERVE (5331/TSTJOB01) | | Row 00001 of 00013 |
| Command ==> | | Scroll ==> CSR |
| Name | Description | Percent of Time in WAIT * 5.00% ±0.5% |
| *...1...2...3...4...5...6...7 | | |
| ISPF-007 | TCB=008DF5E8 | 6.95 ===== |
| → ISPFEDIT | ADS04.ISPF.ISPPROF | 2.78 === |
| → SYSZRACF | SYS1.RACFDS | 2.78 == |
| → SPFEDIT | USR01.SIMPLIST.TABLES | 1.39 = |
| ISPTASK-008 | TCB=008DF2D0 | 4.17 ===== |
| → SYSVTOC | BKNSM2 | 1.39 = |
| → SPFEDIT | USR01.SIMPLIST.L200708 | 1.39 = |
| | .LOG | |
| → SYSZRACF | SYS1.RACFDS | 1.39 = |
| EXEC-016 | TCB=008AAE88 | 2.78 === |
| → SYSZRACF | SYS1.RACFDS | 2.78 === |

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Task, ENQ/RESERVE | Display context help information. |
| ++ | Task, ENQ/RESERVE | Show additional details. |
| + | Task | Expand to reveal next level. |
| - | Task | Collapse to hide next level. |
| SV | Task | Sort next level by value. |
| SN | Task | Sort next level by name. |

on headings

| Cmd | When Applied To Object | Action |
|-----|---------------------------------|------------------------------------|
| ? | Name, Description, Percent WAIT | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size. |
| + | Percent WAIT | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent WAIT | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```
File View Navigate Help
+-----+
+----- The following report line was selected -----+
| SYSZRACF   SYS1.RACFDS       2.78 = |
+-----+

Calculation Details
Wait measurements           834
Total measurements         30,000
Percent of total           2.78%

QNAME   SYSZRACF
RNAME   SYS1.RACFDS
```

W05 - WAIT time by tape DDNAME

Usage

Use this report to view the wait time resulting from requests for tape mounts.

This report displays one line for each unique DDNAME for which tape mount waits occurred. The DDNAME column specifies the DDNAME for the tape and the device column specifies the device number for the tape unit.

Quantification

Each report line quantifies wait time measured as a percentage of total time. The percentage represents the ratio of the number of samples for which a wait for a tape mount was observed and the total number of samples.

Detail line descriptions

DDNAME detail line

| Under Heading | This is Displayed |
|-------------------------|---|
| DDNAME | The DDNAME name. |
| Device | The device number for the tape unit. |
| Percent of Time in WAIT | The percentage of the measurement interval time during which the indicated DDNAME was waiting for a tape mount. |

Sample reports

A sample report is show here.

```
File View Navigate Help
-----
W05: Wait Time by Tape DDNAME (5508/TSTJOB01) Row 00001 of 00011
Command ==> _____ Scroll ==> PAGE

DDNAME Device Percent of Time in WAIT * 10.00% ±58.8%
*...1...2...3...4...5...6...7...8...9...*
SYSUT2 590 66.66 =====
```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | DDNAME | Display context help information. |
| ++ | DDNAME | Show additional details. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------------|-----------------------------------|
| ? | DDNAME, Device, Percent WAIT | Display context help information. |
| SV | DDNAME, Device, Percent WAIT | Sort next level by value. |
| SN | DDNAME, Device, Percent WAIT | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+
| SYSUT2   590         66.66 |
+-----+-----+-----+-----+-----+-----+
Calculation Details
Wait measurements           2
Total measurements         3
Percent of total           66.66%

```

D01 - DASD usage by device

Note: This report also covers TAPE I/O.

Overview

This report shows how much I/O time was used by each DASD (direct access storage device) or tape device for which activity was measured during the observation session. The quantification is based on the number of samples activity on the device was observed. This is expressed as a percentage of the total number of samples.

Two types of detail lines are shown:

- Volume
- Cylinder Address (for DASD)

Initially, only the Volume lines are visible. You can expand a Volume line (using the “+” line command) to reveal its subordinate Cylinder Address lines.

A sample report is shown here, it has been fully expanded:

```

File View Navigate Help
-----
D01: DASD Usage Time by Device (0618/TSTJOB01) Row 00001 of 00006
Command ==>> Scroll ==>> CSR

Volume>Cyl Unit-Dev>DD Percent of Time * 10.00% ±2.2%
*...1...2...3...4...5...6...7...8..
BKNSM2 0A93-3390 8.90 ====
→ Cyl_00BA VSAM1 8.85 ====
→ Cyl_0007 VSAM1 0.05

BKNSM1 0A92-3390 1.25 ==
→ Cyl_0086 INFILE 1.25 ==

```

Detail line descriptions

Volume

This shows the VOLSER value for a DASD or TAPE device for which I/O activity was measured.

Cylinder Address

These lines appear when the “+” line command is used to expand a Volume line. Each line shows a particular DASD cylinder and further breaks down the measurement by file into quantification by specific cylinders.

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|--------------------------|-----------------------------------|
| ? | Volume, Cylinder Address | Display context help information. |
| ++ | Volume, Cylinder Address | Show additional details. |
| + | Volume | Expand to reveal next level. |
| - | Volume | Collapse to hide next level. |
| SV | Volume | Sort next level by value. |
| SN | Volume | Sort next level by name. |

on headings

| Cmd | When Applied To Object | Action |
|-----|---------------------------------------|------------------------------------|
| ? | Volume>Cyl, Unit-Dev>DD, Percent Time | Display context help information. |
| + | Volume>Cyl | Expand to reveal all entries. |
| + | Unit-Dev>DD | Expand field size. |
| + | Percent Time | Zoom in scale. |
| - | Volume>Cyl | Collapse to show only first level. |
| - | Unit-Dev>DD | Reduce field size. |
| - | Percent Time | Zoom out scale. |
| SV | Volume>Cyl | Sort next level by value. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|--------------------------|
| SN | Volume>Cyl | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+
+-----+ The following report line was selected +-----+
| BKNSM2      0A99-3390      45.09 000000000000000000000000 |
+-----+
Calculation Details
Data management CPU measurements      138
Device address                          0A99
Volume serial number                    BKNSM2
I/O unit type                           DASD
Device                                  3390
Total CPU measurements                  306
Percent of total                         45.09%

```

SETUP options

The following SETUP option can be selected with the SETUP primary command:

Minimum percentage of time

You can set this option to eliminate reporting of I/O where the percentage of time is below a certain threshold.

D02 - DASD usage by DDNAME

Note: This report also covers TAPE I/O.

Overview

This report shows how much DASD or TAPE I/O time was measured for each file that was open during the observation session. The quantification is based on the number of samples activity on the file was observed. This is expressed as a percentage of the total number of samples.

Two types of detail line are shown:

- DDNAME
- Cylinder Address (for DASD)

Initially, only the DDNAME lines are visible. You can expand a DDNAME line (using the “+” line command) to reveal its subordinate Cylinder Address lines.

A sample report is shown here, it has been fully expanded:


```

File View Navigate Help
-----
D02: DASD Usage Time by DDNAME (0618/TSTJOB01) Row 00001 of 00006
Command ==> _____ Scroll ==> CSR

DDNAME>Cyl Volume>Unit Percent of Time * 10.00% ±2.2%
*...1...2...3...4...5...6...7...8..
VSAM1-02 BKNSM2 8.90 =====
→ Cyl_00BA 0A93-3390 8.85 =====
→ Cyl_0007 0A93-3390 0.05
INFILE BKNSM1 1.25 ==
→ Cyl_0086 0A92-3390 1.25 ==

```

Detail line descriptions

DDNAME

This represents a file which was open during the observation session. If the same DDNAME is open (and closed) multiple times during the session, it is suffixed with an instance number to indicate this.

Cylinder Address

These lines appear when the “+” line command is used to expand a DDNAME line. Each line shows a particular DASD cylinder and further breaks down the measurement by file into quantification by specific cylinders.

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|--------------------------|-----------------------------------|
| ? | DDName, Cylinder Address | Display context help information. |
| ++ | DDName, Cylinder Address | Show additional details. |
| + | DDName | Expand to reveal next level. |
| - | DDName | Collapse to hide next level. |
| SV | DDName | Sort next level by value. |
| SN | DDName | Sort next level by name. |

on headings

| Cmd | When Applied To Object | Action |
|-----|---------------------------------------|------------------------------------|
| ? | DDName>Cyl, Unit-Dev>DD, Percent Time | Display context help information. |
| + | DDName>Cyl | Expand to reveal all entries. |
| + | Volume>Unit | Expand field size. |
| + | Percent Time | Zoom in scale. |
| - | DDName>Cyl | Collapse to show only first level. |
| - | Volume>Unit | Reduce field size. |
| - | Percent Time | Zoom out scale. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|---------------------------|
| SV | DDName>Cyl | Sort next level by value. |
| SN | DDName>Cyl | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+-----+
+-----+-----+
| VSAM1      BKNSM2      45.09 000000000000000000000000 |
+-----+-----+
+-----+-----+
Calculation Details
Data management CPU measurements      138
I/O unit type                          DASD
Servicing I/O requests for DD Name    VSAM1
Total CPU measurements                 306
Percent of total                       45.09%

VSAM file VSAM1 OPENed at 7:27:14.84 Friday Oct 7 2005

DDNAME        VSAM1
Open Intent   KEY,DIR,OUT
Dataset Name  USER1.DATA.TESTPF.DAT
Storage Class BKNSMS
Device Type   3390
% Free Bytes in CI  10%
Volume Serial  BKNSM2  CI Splits  0      Initial  Last
CI Size       8,192  CA Splits  0      0
Record Size (LRECL) 80    Logical Records 8      7,282
Number of Extents  1      Deleted Records 1      1
SHAREOPTIONS  (1 3)  Insrted Records 0      0
Organization    KSDS   Retrved Records 1      1
CIs per CA     78    Updated Records 0      0
Free CIs per CA  11    Bytes Free Space 1,908,736 1,327,104
Free Bytes per CI  819   Number of EXCPs 13     7,287
% Free CIs in CA  15%
Strings        1
DATA Buffers   2
INDEX Buffers  1

```

```

File View Navigate Help
-----+-----
Index Component of VSAM1
                                         More:  -
Dataset Name      USER1.DATA.TESTPF.IDX
Storage Class     BKNSMS
Device Type       3390
% Free Bytes in CI 0%
Volume Serial     BKNSM2  CI Splits      0      0
CI Size           1,024  CA Splits      0      0
Record Size (LRECL) 1,017  Logical Records 1      1
Number of Extents 1      Deleted Records 0      0
SHAREOPTIONS      (1 3)  Insrted Records 0      0
Organization      KSDS   Retrved Records 0      0
CIs per CA        33    Updated Records 0      71
Free CIs per CA   0     Bytes Free Space 32,768 32,768
Free Bytes per CI 0     Number of EXCPs 4      75
% Free CIs in CA  0%
-----+-----

```

SETUP options

The following SETUP option can be selected with the SETUP primary command:

Minimum percentage of time

You can set this option to eliminate reporting of I/O where the percentage of time is below a certain threshold.

D03 - DASD usage by data set

Note: This report also covers TAPE I/O.

Overview

This report shows how much DASD or TAPE I/O time was used by each data set for which activity was measured during the observation session. The quantification is based on the number of samples activity on the device was observed. This is expressed as a percentage of the total number of samples.

Two types of detail line are shown:

- Data set
- DDNAME

Initially, only the data set lines are visible. You can expand a data set line (using the "+" line command) to reveal its subordinate DDNAME lines.

A sample report is shown here, it has been fully expanded:

```

File View Navigate Help
-----+-----
D03: DASD Usage Time by Dataset (0618/TSTJOB01)      Row 00001 of 00005
Command ==>>> _____ Scroll ==>>> CSR
Dataset_Name>DDName  Percent of Time * 10.00% ±2.2%
                    *....1....2....3....4....5....6....7....8..
USER1.DATA.TESTPF    8.90 ====
→ VSAM1-02 BKNSM2    8.90 ====
USER1.TESTPF2.INFILE 1.25 ==
→ INFILE BKNSM1     1.25 ==
-----+-----

```

Detail line descriptions

Data set

This shows the name of a data set that was open at some point during the observation session.

DDNAME

This line shows a DDNAME corresponding to the data set name. There could be multiple entries under a data set if the data set was open more than once (concurrently or serially) with different DDNAMEs. If the same DDNAME is open (and closed) multiple times for the data set, it is suffixed with an instance number to indicate this.

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Data set Name, DDName | Display context help information. |
| ++ | Data set Name, DDName | Show additional details. |
| + | Data set Name | Expand to reveal next level. |
| - | Data set Name | Collapse to hide next level. |
| SV | Data set Name | Sort next level by value. |
| SN | Data set Name | Sort next level by name. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------------------|------------------------------------|
| ? | Data set Name>DDName, Percent Time | Display context help information. |
| + | Data set Name>DDName | Expand to reveal all entries. |
| + | Percent Time | Zoom in scale. |
| - | Data set Name>DDName | Collapse to show only first level. |
| - | Percent Time | Zoom out scale. |
| SV | Data set Name>DDName | Sort next level by value. |
| SN | Data set Name>DDName | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| ARA01.DATA.TESTPF          45.09 000000000000000000000000 |
+-----+

Calculation Details
Data management CPU measurements      138
I/O unit type                          DASD
Data set name                          ARA01.DATA.TESTPF
Total CPU measurements                 306
Percent of total                       45.09%

```

SETUP options

The following SETUP option can be selected with the SETUP primary command:

Minimum percentage of time

You can set this option to eliminate reporting of I/O where the percentage of time is below a certain threshold.

D04 - Data set attributes

This report lists information about each of the data sets (DASD and TAPE) which were open at some point during the observation session. Various attributes of each of the data sets are reported.

A sample report is shown here:

```

File View Navigate Help
-----
D04: Dataset Attributes (0618/TSTJOB01)          Row 00001 of 00105
Command ==> _____ Scroll ==> CSR

SORT by: DDname enter SF, by Dataset Name enter SD.
Dataset information reported for 4 Files.

Non-VSAM file OUTFILE OPENed at 6:45:30.18 Monday Jan 26 2004

DDNAME          OUTFILE
Open Intent      OUTPUT
Dataset Name     USER1.TESTPF2.OUTFILE
Device Type      3390      Number of Extent 3
Volume Serial    BKNSM1   Dataset Organiza PS
Block Size (BLKSIZE) 27,930 RECFM          FIXED BLOCKED
Record Size (LRECL) 133      Data Buffers    0

Non-VSAM file INFILE OPENed at 6:45:30.53 Monday Jan 26 2004

DDNAME          INFILE
Open Intent      INPUT
Dataset Name     USER1.TESTPF2.INFILE
Device Type      3390      Number of Extent 1
Volume Serial    BKNSM1   Dataset Organiza PS
Block Size (BLKSIZE) 13,300 RECFM          FIXED BLOCKED
Record Size (LRECL) 133

```

Scrolling down in this example shows some VSAM file information.

```

File View Navigate Help
-----
D04: Dataset Attributes (0618/TSTJOB01) Row 00026 of 00105
Command ==> Scroll ==> CSR

VSAM file VSAM1(1) OPENed at 6:45:33.66 Monday Jan 26 2004

DDNAME          VSAM1
Open Intent     KEY,DIR,OUT,RST
Dataset Name    USER1.DATA.TESTPF.DAT
Storage Class   BKNSMS
Device Type     3390
% Free Bytes in CI 10%          Initial      Last
Volume Serial  BKNSM2   CI Splits    0           0
CI Size        8,192   CA Splits    0           0
Record Size (LRECL) 80   Logical Records 0           0
Number of Extents 1     Deleted Records 0           0
SHAREOPTIONS    (1 3) Insrted Records 0           0
Organization    KSDS   Retrved Records 0           0
CIs per CA      78     Updated Records 0           0
Free CIs per CA 11     Bytes Free Space 1,916,928 1,916,928
Free Bytes per CI 819    Number of EXCPs 2           2
% Free CIs in CA 15%
Strings         0
DATA Buffers    0
INDEX Buffers   0

```

This example shows the index component:

```

File View Navigate Help
-----
D04: Dataset Attributes (2133/TSTJOB01) Row 00060 of 00116
Command ==> Scroll ==> CSR

Index Component of VSAM1(1)

Dataset Name    USER1.DATA.TESTPF.IDX
Storage Class   BKNSMS
Device Type     3390
% Free Bytes in CI 0%          Initial      Last
Volume Serial  BKNSM2   CI Splits    0           0
CI Size        1,024   CA Splits    0           0
Record Size (LRECL) 1,017   Logical Records 0           0
Number of Extents 1     Deleted Records 0           0
SHAREOPTIONS    (1 3) Insrted Records 0           0
Organization    KSDS   Retrved Records 0           0
CIs per CA      33     Updated Records 0           0
Free CIs per CA 0     Bytes Free Space 33,792    33,792
Free Bytes per CI 0     Number of EXCPs 1           1
% Free CIs in CA 0%

```

When available to Application Performance Analyzer, the following additional DASD statistics are displayed in D04, and in the detail windows of other DASD reports:

- Average Response Time
- Average Pending Time
- Average Disconnect Time
- Average Connect Time
- Average Queued Time
- Total I/Os
- Cache Candidates
- Cache Hits
- Write Candidates

- Write Hits

This example shows some of the additional DASD statistics:

```

File View Navigate Help
-----
D04: Dataset Attributes (4167/AGM01G)                               Row 00005 of 00125
Command ==>                                                       Scroll ==> CSR
VSAM file BNCSTFL OPENed at 16:19:58.25 Tuesday Aug 25 2009

DDNAME          BNCSTFL
Open Intent     KEY,DIR,SEQ,OUT
Dataset Name    BNET.CICS22C.BNCSTFL.DATA
Storage Class   BKNDATA
Device Type     3390
% Free Bytes in CI 0%
Volume Serial   BKNA91+  CI Splits      0          0
                BKNA93
CI Size         8,192    CA Splits      0          0
Record Size (LRECL) 516    Logical Records 14         14
Number of Extents  1      Deleted Records 0          0
SHAREOPTIONS     (4 3)  Insrted Records 0          0
Organization     KSDS   Retrved Records 15,858,330 15,918,231
CIs per CA       12     Updated Records 1          1
Free CIs per CA  0      Bytes Free Space 90,112     90,112
Free Bytes per CI 0      Number of EXCPs 7,991,951 8,051,851
% Free CIs in CA 0%
Strings          1      String Waits    0
DATA Buffers     2      String Waits HWM 0
INDEX Buffers    1
Avg Response Time 0.0256  Avg Pending Time 0.0000
Avg Disconnect Time 0.0000  Avg Connect Time 0.0128
Avg Queued Time   0.0000  Total I/Os      59,900
Cache Candidates 59,900  Cache Hits      59,900

```

You can place your cursor on the SORT field and enter any of the following sort codes to re-sort the report:

- SF By DDName
- SD By Data set name

D05 - DASD EXCP summary

Note: This report also covers TAPE I/O.

Usage

Use this report to see a summary of the number of EXCPs for each open data set.

Quantification

Each report line shows EXCP counts for a DDNAME. The EXCP count at the time the file was first observed to be open and the count at the time the file was last observed to be open are reported. The difference between these two values is also reported; this is the number of EXCPs occurring during the measurement interval.

Detail line hierarchy

There is only one detail line level in this report.

Detail line descriptions

EXCP counts

Each detail line shows the following information.

| Under Heading | This is Displayed |
|--------------------|--|
| DDNAME | The DDNAME of the file. If multiple OPENS occurred for the DDNAME, a separate line is reported for each "instance." A sequence number is appended to the DDNAME indicating the instance. |
| Type | The type of file (VSAM, Non-VSAM, Tape, etc.) |
| Concat | The concatenation number. A value (+0, +1, +2 ...) appears here to indicate the data set position in a concatenation. |
| At Start | The EXCP count for the data set when first observed. For VSAM data sets, the system maintains this count for the life of the file. For non-VSAM, this only reflects EXCPs during the step. |
| At End | The EXCP count for the data set when last observed. For VSAM data sets, the system maintains this count for the life of the file. For non-VSAM, this only reflects EXCPs during the step. |
| During Measurement | The number of EXCPs for the measurement duration. This is computed as the difference between the "At Start" count and the "At End" count. Note: The system maintains EXCP counts at the data set level. If a data set had more than one file open concurrently under different DDNAMEs, then overlapping EXCP counts will be reported. |

Sample reports

A sample report is shown here:

```

File View Navigate Help
-----
D05: DASD EXCP Summary (0647/TSTJOB01) Row 00001 of 00082
Command ==> Scroll ==> CSR
-----
DDNAME      Type      Concat  At Start  At End  During Measurement
SAMPIN      Non-VSAM          0         30         30
ISPMLIB     Non-VSAM      +2         22         26         4
ISP07053    Non-VSAM          19         21         2
SYS00117    VSAM-DATA     3648       3649         1
             VSAM_INDEX     41         42         1
SYS00116    VSAM-DATA     2          3          1
             VSAM_INDEX     1          2          1
ISP07078-3  Non-VSAM          35         37         2
ISP07073    Non-VSAM          4          5          1
ISP07074    Non-VSAM          20         21         1
ISP07078-1  Non-VSAM          34         35         1
ISP07078-2  Non-VSAM          34         35         1
ISPPROF     Non-VSAM          50         50         0
ISPPLIB     Non-VSAM      +0         0          0
ISPTLIB     Non-VSAM      +2         0          0
ISPPLIB     Non-VSAM      +2         6          6
  
```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | DDName | Display context help information. |
| ++ | DDName | Show additional details. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | DDName | Display context help information. |
| SV | DDName | Sort next level by value. |
| SN | DDName | Sort next level by name. |

SETUP options

Enter the SETUP primary command to select options for this report. The following pop-up window will be displayed:

```

File View Navigate Help
-----+-----
D | Options for DASD EXCP Summary | 001 of 00107
C |                               | 11 ==> CSR
  | Enter "/" to select an option |
  |   - Omit files for which no EXCPs were counted |
D |   during the measurement interval. Unselect to | asurement
  |   include all files. |
S |                               | 82
I |-----+-----| 0
  
```

Select this option to omit files from the report for which no I/O activity was observed. Deselect this option to display all files.

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
-----+-----
+-----+-----+-----+-----+-----+-----+
| INFILE      Non-VSAM          0      14      14 |
+-----+-----+-----+-----+-----+-----+
Non-VSAM file INFILE OPENed at 6:45:30.53 Monday Jan 26 2004

DDNAME          INFILE
Open Intent      INPUT
Dataset Name     USER1.TESTPF2.INFILE
Device Type      3390      Nbr of Extents  1
Volume Serial    BKNSM1    Dataset Org   PS
Block Size (BLKSIZE) 13,300  RECFM         FIXED BLOCKED
Record Size (LRECL) 133      Data Buffers  0
  
```

D06 - DASD VSAM statistics

Usage

Use this report to see file access statistics for each open VSAM data set.

Quantification

Each report line shows a VSAM DDNAME and its associated file access statistics.

Detail line hierarchy

There is only one detail line level in this report.

Detail line descriptions

VSAM statistics

Each detail line shows the following information.

| Under Heading | This is Displayed |
|---------------|--|
| DDNAME | The DDNAME of the file. If multiple OPENS occurred for the DDNAME, a separate line is reported for each "instance." A sequence number is appended to the DDNAME indicating the instance. |
| Retrvd | The number of records retrieved from the file during the measurement interval. |
| Added | The number of new records added to the file during the measurement interval. |
| Insrtd | The number of records inserted during the measurement interval. This count is also included in the 'added' record count. |
| Deletd | The number of records deleted from the file during the measurement interval. |
| Updatd | The number of updates to existing records during the measurement interval. |
| EXCPs | The number of EXCPs during the measurement interval. |
| FreeSpc | The change, in bytes, to the amount of free space during the measurement interval. This is shown as a plus or minus value to indicate if the free space increased or decreased. |
| CISplts | The change in the number of CI splits during the measurement interval. This is shown as a plus or minus value to indicate if the number of CI splits increased or decreased. |
| CASplts | The change in the number of CA splits during the measurement interval. This is shown as a plus or minus value to indicate if the number of CA splits increased or decreased. |

Sample reports

A sample report is shown here:

```

File View Navigate Help
-----
D06: DASD VSAM Statistics (0650/TSTJOB01)          Row 00001 of 00006
Command ==>> _____ Scroll ==>> CSR

      Logical Records During Interval
DDNAME  Retrvd  Added  Insrtd  Deletd  Updatd  EXCPs  +/- During Inte
-----  -----  -----  -----  -----  -----  -----  -----
FILEA   749    +0     0       0       0       0       +0    +0
DFHLCD   0     +0     0       0       0       0       +0    +0
DFHGCD   0     +0     0       0       0       0       +0    +0
DFHTEMP  0     +0     0       0       0       0       +0    +0
DFHINTRA 0     +0     0       0       0       0       +0    +0
DFHLRq   0     +0     0       0       0       0       +0    +0
  
```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | DDName | Display context help information. |
| ++ | DDName | Show additional details. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | DDName | Display context help information. |
| SV | DDName | Sort next level by value. |
| SN | DDName | Sort next level by name. |

SETUP options

Enter the SETUP primary command to select options for this report. The following pop-up window will be displayed:

```

File View Navigate Help
-----+-----
D | Options for DASD VSAM Statistics          | 001 of 00006
C |                                           | 11 ==>> CSR
  | Enter "/" to select an option
  |   - Omit files for which no EXCPs were counted
  |     during the measurement interval. Unselect to
  |     include all files.                    | - During Inte
  |                                           | Spc CISplts C
-----+-----
  
```

Select this option to omit from the report files for which no activity took place.
Deselect this option to display all files.

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| VSAM1-02      BKNSM2      8.90 === |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+

VSAM file FILEA OPENed at 13:04:47.81 Tuesday Mar 2 2004

DDNAME          FILEA
Open Intent     KEY,DSN,DIR,SEQ,SKP,OUT,NLW,LSR SHRPOOL=1
Dataset Name    BNET.CICS22A.FILEA.DATA
Storage Class   BKNDATA
Device Type     3390
% Free Bytes in CI 0%
Volume Serial   BKNA91
CI Size         18,432
Record Size (LRECL) 80
Number of Extents 1
SHAREOPTIONS    (1 3)
Organization    KSDS
CIs per CA     3
Free CIs per CA 0
Free Bytes per CI 0
% Free CIs in CA 0%
Strings        1
DATA Buffers   1
INDEX Buffers  1

Index Component of FILEA

Dataset Name     BNET.CICS22A.FILEA.INDEX
Storage Class    BKNSMS
Device Type      3390
% Free Bytes in CI 0%
Volume Serial    BKNA91
CI Size          512
Record Size (LRECL) 505
Number of Extents 1
SHAREOPTIONS     (2 3)
Organization     KSDS
CIs per CA      49
Free CIs per CA 0
Free Bytes per CI 0
% Free CIs in CA 0%
SHAREOPTIONS     (2 3)
Organization     KSDS
CIs per CA      49
Free CIs per CA 0
Free Bytes per CI 0
% Free CIs in CA 0%
Initial          Last
Logical Records 44      44
Deleted Records 0       1
Insrted Records 0       0
Retrvd Records 117,704 118,453
Updated Records 0       0
Byter Free Space 36,864 36,864
Number of EXCPs 29      29

Initial          Last
CI Splits        0       0
CA Splits        0       0
Logical Records  1       1
Deleted Records  0       0
Insrted Records  0       0
Retrvd Records   0       0
Updated Records  0       0
Byter Free Space 24,576 24,576
Number of EXCPs 35      35

Shared Resource Pool Information for LSR Pool 1
Type (Data/Index) DATA
Buffer Size       512
Buffers           8
Hiperspace Buffers 0
Reads             1
Reads Avoided    0
User Writes       0
Non-user Writes  0
Initial          Last
Reads            1       1
Reads Avoided   0       228
User Writes      0       0
Non-user Writes 0       0

```

D07 - DASD activity timeline

Note: This report also covers TAPE I/O.

Usage

Use this report to see, for each file, how I/O activity was distributed over the measurement interval.

Quantification

A graph, in bar chart format, is displayed for each DDNAME. The horizontal axis represents the measurement interval which spans 50 columns. Each column represents an equal 1/50th sub-interval of time. A scale is shown at the bottom of the graph indicating the percentage of time progression in the overall interval.

In each column, a vertical graph shows (roughly) how much I/O activity took place during the sub-interval. If any I/O activity did take place, a vertical bar of 1, 2, 3, 4 or 5 characters, extending upward from the scale, is displayed indicating the percentage of time in the sub-interval I/O was observed.

Detail line descriptions


File I/O activity distribution

A group of lines is shown for each reported file. Some information about the file appears to the left and a bar chart to the right.

| Under Heading | This is Displayed |
|-------------------------------|---|
| File Information | File Information The following information is shown for each file. <ul style="list-style-type: none">• The DDNAME• Type of file (VSAM, non-VSAM, Tape, etc.)• Volser• Unit (device type) |
| nnnn Samples: Duration ... | A graph showing the distribution of I/O activity over the measurement interval. |

Sample reports

A sample of the report is shown here:



Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | DDName | Display context help information. |
| ++ | DDName | Show additional details. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | DDName | Display context help information. |
| SV | DDName | Sort next level by value. |
| SN | DDName | Sort next level by name. |

SETUP options

Enter the SETUP primary command to select options for this report. The following pop-up window will be displayed:

```

File View Navigate Help
-----+-----
D | Options for DASD Activity Timeline | 001 of 00000
C |                                     | 11 ==> CSR
  | Enter "/" to select an option
  | / Omit files for which no I/O was observed
  |   during the measurement interval. Unselect
  |   to include all files.
  |                                     |
+-----+-----+

```

Select this option to omit from the report files for which no activity took place. This is the default option. Deselect this option to display all files, which will typically result in the display of numerous empty graphs.

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
-----+-----
+-----+-----+
+-----+-----+ The following report line was selected -----+
| INFILE          Non-VSAM                0          14          14|
+-----+-----+
Non-VSAM file INFILE OPENed at 6:45:30.53 Monday Jan 26 2004

DDNAME          INFILE
Open Intent     INPUT
Dataset Name    USER1.TESTPF2.INFILE
Device Type     3390          Nbr of Extents  1
Volume Serial   BKNSM1         Dataset Org    PS
Block Size (BLKSIZE) 13,300    RECFM          FIXED BLOCKED
Record Size (LRECL) 133          Data Buffers   5
+-----+-----+

```

D08 - DASD I/O wait time

Usage

Use this report to examine delays resulting from waits during DASD I/O operations. Note: This report is not applicable to CICS.

Quantification

Samples are counted in which the following conditions were observed:

- All TCBs (tasks) are in WAIT state
- One (or more) TCB is waiting for completion of a DASD I/O request

The number of samples satisfying these conditions divided by the total number of samples represents the percentage of time the step was waiting for completion of DASD I/O. These percentages are computed and reported by DDNAME.

Detail line hierarchy

An unexpanded D08 report shows a line for each DDNAME causing a delay in execution while waiting for DASD I/O activity to complete. You can expand each line to reveal additional hierarchical levels of detail (using the "+" line command).

The hierarchy is illustrated here:

```
Level 1 DDNAME
  Level 2 File I/O Request
    Level 3 Supervisor Call (SVC)
      Level 4 Module
        Level 5 CSECT

Level 2 File I/O Request
  Level 3 Module
    Level 4 CSECT

Level 2 Supervisor Call (SVC)
  Level 3 Module
    Level 4 CSECT
```

Detail line descriptions

DDNAME

This line identifies the DDNAME of a file for which delays due to wait for I/O completion were observed.

| Under Heading | This is Displayed |
|-----------------|--|
| Description | The volume ID (VOLSER) for the DDNAME. For a multivolume data set, the first volume is displayed. |
| Percent of Time | The percentage of the measurement interval time the step was waiting for completion of I/O for the indicated DDNAME. |

File I/O request

This line identifies the file request macro that caused a wait for I/O completion.

| Under Heading | This is Displayed |
|-----------------|---|
| Name | The DASD I/O macro function (GET, PUT, CHECK, etc.) that caused the wait. |
| Description | The address of the macro (return address) in CSECT+offset format. |
| Percent of Time | The percentage of the measurement interval time the step was waiting for completion of I/O for the indicated macro. |

Load module

This line identifies the data management load module in which the wait occurred.

| Under Heading | This is Displayed |
|-----------------|---|
| Name | Name of load module in which WAIT request was issued. |
| Description | Functional description of the load module if one is available. |
| Percent of Time | The percentage of the measurement interval time the step was waiting for completion of I/O. |

CSECT

This line identifies the CSECT in the data management load module in which the wait occurred.

| Under Heading | This is Displayed |
|-----------------|---|
| Name | Name of CSECT in which WAIT request was issued. |
| Description | Functional description of the CSECT if one is available. |
| Percent of Time | The percentage of the measurement interval time the step was waiting for completion of I/O. |

Supervisor Call (SVC)

This line identifies an SVC (Supervisor Call) that issued the wait.

| Under Heading | This is Displayed |
|-----------------|---|
| Name | Name of SVC (Supervisor Call) in which WAIT request was issued. |
| Description | Functional description of the SVC. |
| Percent of Time | The percentage of the measurement interval time the step was waiting for completion of I/O. |

Sample reports

A sample of the report as it is first displayed is shown here:

```
File View Navigate Help
-----
D08: DASD I/O Wait Time (0099/TSTJOB01) Row 00001 of 00006
Command ==> Scroll ==> CSR
Name      Description      Percent of CPU time * 10.00% ±3.5%
          *....1....2....3....4....5....6....7....8.
VSOUT1    BKNSM1            7.07 ====
VSOUT2    BKNSM1            5.05 ===
VSOUT3    BKNSM1            3.03 ==
VSINP4    BKNSM1            1.26 =
QSOUT5    BKNSM1            0.25
QSINP6    BKNSM1            0.12
```

Here is a sample of the report which has been fully expanded by entering the “+” line command on the Name heading:

```

File View Navigate Help
-----
D08: DASD I/O Wait Time (0099/TSTJOB01) Row 00001 of 00030
Command ==> Scroll ==> CSR

Name          Description          Percent of CPU time * 10.00% ±3.5%
*....1....2....3....4....5....6....7....8.
VSOUT1        BKNSM1                7.07 =====
→ PUT         U0053+C8              7.07 =====
  → IDA019L1   Virtual I/O (VI      7.07 =====
    → IDA019R3   CSECT in IDA0      7.07 =====

VSOUT2        BKNSM1                5.05 ===
→ PUT         U0053+194             5.05 ===
  → IDA019L1   Virtual I/O (VI      5.05 ===
    → IDA019R3   CSECT in IDA0      4.80 ==
      → IDA019RZ   CSECT in IDA0      0.25

VSOUT3        BKNSM1                3.03 =
→ PUT         U0053+266             3.03 =
  → IDA019L1   Virtual I/O (VI      3.03 =
    → IDA019R3   CSECT in IDA0      3.03 =

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|---|-----------------------------------|
| ? | DDName, File I/O Request, Load Module, CSECT, SVC | Display context help information. |
| ++ | DDName, File I/O Request, Load Module, CSECT, SVC | Show additional details. |
| + | DDName, File I/O Request, Load Module, SVC | Expand to reveal next level. |
| - | DDName, File I/O Request, Load Module, SVC | Collapse to hide next level. |
| SV | DDName, File I/O Request | Sort next level by value. |
| SN | DDName, File I/O Request | Sort next level by name. |
| M | Load Module, CSECT | Display load module information. |
| P | CSECT | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | DDName | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size. |
| + | Percent CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent of Time | Zoom out scale. |

| Cmd | When Applied To Object | Action |
|-----|------------------------------------|---------------------------|
| SV | Name, Description, Percent of Time | Sort next level by value. |
| SN | Name, Description, Percent of Time | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| VSAM1      BKNSM2      4.04 00      |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
Calculation Details
Data management CPU measurements      124
I/O unit type                          DASD
Servicing I/O requests for DD Name     VSAM1
Total measurements                     3,063
Percent of total                       4.04%

VSAM file VSAM1 OPENed at 7:27:14.84 Friday Oct 7 2005

DDNAME          VSAM1
Open Intent     KEY,DIR,OUT
Dataset Name    USER1.DATA.TESTPF.DAT
Storage Class   BKNSMS
Device Type     3390
% Free Bytes in CI  10%
Volume Serial   BKNSM2  CI Splits    0          0
CI Size        8,192  CA Splits    0          0
Record Size (LRECL) 80    Logical Records 8          7,282
Number of Extents  1    Deleted Records 1          1
SHAREOPTIONS      (1 3)  Insrted Records 0          0
Organization      KSDS   Retrved Records 1          1
CIs per CA        78    Updated Records 0          0
Free CIs per CA   11    Bytes Free Space 1,908,736  1,327,104
Free Bytes per CI  819   Number of EXCPs 13         7,287
% Free CIs in CA  15%
Strings          1
DATA Buffers     2
INDEX Buffers    1

Index Component of VSAM1

```

| File View Navigate Help | | | | |
|-------------------------|-----------------------|------------------|---------|---------|
| | | | | More: - |
| Dataset Name | USER1.DATA.TESTPF.IDX | | | |
| Storage Class | BKNSMS | | | |
| Device Type | 3390 | | | |
| % Free Bytes in CI | 0% | | Initial | Last |
| Volume Serial | BKNSM2 | CI Splits | 0 | 0 |
| CI Size | 1,024 | CA Splits | 0 | 0 |
| Record Size (LRECL) | 1,017 | Logical Records | 1 | 1 |
| Number of Extents | 1 | Deleted Records | 0 | 0 |
| SHAREOPTIONS | (1 3) | Insrted Records | 0 | 0 |
| Organization | KSDS | Retrvd Records | 0 | 0 |
| CI's per CA | 33 | Updated Records | 0 | 71 |
| Free CIs per CA | 0 | Bytes Free Space | 32,768 | 32,768 |
| Free Bytes per CI | 0 | Number of EXCPs | 4 | 75 |
| % Free CIs in CA | 0% | | | |

D09 - VSAM buffer pool usage

Usage

Use this report to see information about activity in VSAM LSR buffer pools.

A buffer pool number can be associated with a VSAM file. This is indicated in the Open Intent field in any reports that show detailed file information. For example, report D04 might show the following:

```
KEY,DSN,DIR,SEQ,SKP,OUT,NLW,LSR SHRPOOL=1
```

This indicates the file uses shared buffer pool number 1. Refer to report D09 to examine how effectively the buffer pool was able to reduce the I/O activity for the associated file(s).

For each buffer pool, activity is quantified for each buffer size and type (DATA or INDEX component). The buffer size corresponds to the CI size for the associated file component. VSAM will choose buffers which are at least as large as and closest in size to the CI size.

Quantification

The following values are reported.

| Under Heading | This is Displayed |
|---------------------|--|
| Type | DATA or INDEX. This indicates if the buffers are for VSAM DATA or INDEX components |
| Buffer Size | The buffer size, in bytes. |
| Buffers | The number of buffers in virtual storage. |
| Hiperspace™ Buffers | The number of buffers in Hiperspace. |
| Reads | The number of physical reads to the file. This is the number of reads that could not be avoided because no buffer contained a copy of the CI. Three values are shown: "Initial," which is the value at the start of the measurement interval; "Last," which is the value at the end; and "Difference," which is the difference between the other two values. The difference between the two values represents the activity for the duration of the interval. |

| Under Heading | This is Displayed |
|-----------------|---|
| Reads Avoided | The number of avoided reads (look-asides). This is the number of reads avoided because copies of the referenced CIs were found in the buffer pool. Three values are shown: "Initial," which is the value at the start of the measurement interval; "Last," which is the value at the end; and "Difference," which is the difference between the other two values. The difference between the two values represents the activity for the duration of the interval. High values indicate the buffer pool was effective in causing I/O operations to be avoided. |
| User Writes | The number of physical writes performed to the file at the request of the user program. Three values are shown: "Initial," which is the value at the start of the measurement interval; "Last," which is the value at the end; and "Difference," which is the difference between the other two values. The difference between the two values represents the activity for the duration of the interval. |
| Non-user Writes | The number of forced physical writes performed to the file. Three values are shown: "Initial," which is the value at the start of the measurement interval; "Last," which is the value at the end; and "Difference," which is the difference between the other two values. The difference between the two values represents the activity for the duration of the interval. |

Sample reports

A sample of the report is shown here:

```

File View Navigate Help
-----
D09: VSAM Buffer Pool Usage (5096/TSTJOB01) Row 00001 of 00022
Command ==>> _____ Scroll ==>> CSR

Shared Resource Pool Information for LSR Pool 1

Type (Data/Index)  INDEX  Reads      Initial    Last      Difference
Buffer Size        512    Reads Avoided 260279    270299    10020
Buffers            5      User Writes    0         0         0
Hiperspace Buffers 0      Non-user Writes 0         0         0

Type (Data/Index)  DATA  Reads      576       609       33
Buffer Size        8192  Reads Avoided 259704    269691    9987
Buffers            5      User Writes    0         0         0
Hiperspace Buffers 0      Non-user Writes 0         0         0

Type (Data/Index)  INDEX  Reads      0         0         0
Buffer Size        8192  Reads Avoided 0         0         0
Buffers            5      User Writes    0         0         0
Hiperspace Buffers 0      Non-user Writes 0         0         0

Type (Data/Index)  DATA  Reads      0         0         0
Buffer Size        20480 Reads Avoided 0         0         0
Buffers            5      User Writes    0         0         0
Hiperspace Buffers 0      Non-user Writes 0         0         0

```

G01 - Coupling facility summary

Usage

Use this report to see a summary of the coupling facility data collected during the observation session.

Facility summary

Fields under this heading summarize the storage and usage of the coupling facility by facility name. The facility name is listed in the heading.

| Under Heading | This is Displayed |
|---------------------------------|--|
| CF Storage | Total coupling facility storage |
| CF Storage Used | Total used coupling facility storage. |
| CF Dump Storage | Total coupling facility storage dump space. |
| CF Storage for Structures | Total coupling facility storage used by structures. |
| Subchannel Contention Count | Count of times a free subchannel was not available for synchronous immediate operations. |
| Subchannel Contention Time uSec | Amount of time in microseconds waiting for a free subchannel for synchronous immediate operations (u-sec). |
| Failed Request Count | Count of the number of summed times – for unsuccessful operations. |
| Failed Request Time uSec | Summed service time of unsuccessful operations (u-sec). |
| Number of Processors | Number of processors used by the coupling facility. |
| Processor Utilization | Processor utilization of coupling facility processors expressed as a percentage of the sampling time. |

Sample reports

A sample report is shown here:

```

File View Navigate Help
-----
G01: Coupling Facility Statistics (0003/TSTJOB01)          Row 00001 of 00023
Command ==> _____ Scroll ==> CSR

Facility Summary - CFCC1
CF Storage                      74,496K
CF Storage Used                  9,216K
CF Dump Storage                  2,048K
CF Storage for Structures        7,168K
Subchannel Contention Count      0
Subchannel Contention Time uSec  0
Failed Request Count             0
Failed Request Time uSec         0
Number of Processors              1
Processor Utilization             0%

Facility Summary - CFCCC2
CF Storage                      74,496K
CF Storage Used                  2,048K
CF Dump Storage                  2,048K
CF Storage for Structures        0K
Subchannel Contention Count      0
Subchannel Contention Time uSec  0
Failed Request Count             0
Failed Request Time uSec         0
Number of Processors              1
Processor Utilization             51%

```

G02 - Coupling facility mean times

Usage

Use this report to see an analysis of how time was spent by the Coupling Facility during the observation session. Expand a Coupling Facility report line to see a further breakdown by structure name within the facility name.

Quantification

Each report line quantifies time as arithmetic means for each measured facility. The means are calculated by dividing the total of all time spent servicing the facility by its number of requests. The means are expressed in units of micro-seconds.

Detail line hierarchy

An unexpanded G02 report shows a line for each facility name in the Coupling Facility. You can expand each line to reveal an additional hierarchical level of detail (using the “+” line command).

The hierarchy is illustrated here:

Level 1 Facility Name
Level 2 Structure Name

Detail line descriptions

Facility detail line

This is the first-level detail line. Each line shows information about a facility name in the coupling facility.

| Under Heading | This is Displayed |
|-------------------|---|
| Name | The facility name. |
| Requests - Sync | The number of synchronous operations to the coupling facility. |
| Requests - Async | The number of asynchronous operations to the coupling facility. |
| Requests - Queued | The number of queued operations to the coupling facility. |
| Requests - Delay | The number of operations to the coupling facility that were delayed for dump serialization. |
| uSeconds - Sync | Mean micro-seconds service time per synchronous operation to the coupling facility. |
| uSeconds - Async | Mean micro-seconds service time per asynchronous operation to the coupling facility. |
| uSeconds - Queued | Mean micro-seconds service time for operations queued for the coupling facility. |
| uSeconds - Delay | Mean micro-seconds service time for operation delays for dump serialization. |

Sample reports

A sample report is shown here:

```
File View Navigate Help
-----
G02: Coupling Facility Mean Service Times (0003/TSTJOB01) Row 00001 of 00002
Command ==> _____ Scroll ==> CSR

----- Number of Requests -----
Name      Sync  Asynch  Queued  Delay
CFCC1     4112    0       0       0
CFCC2      0       0       0       0

----- Mean uSeconds -----
Name      Sync  Asynch  Queued  Delay
CFCC1      1     0       0       0
CFCC2      0     0       0       0
```

G03 - Coupling facility total times

Usage

Use this report to see an analysis of how time was spent by the Coupling Facility during the observation session. Expand a Coupling Facility report line to see a further breakdown by structure name within the facility name.

Quantification

Each report line quantifies total time for each measured facility. The totals are the sum of all structures within the facility name. The totals are expressed in units of microseconds.

Detail line hierarchy

An unexpanded G03 report shows a line for each facility name in the Coupling Facility. You can expand each line to reveal an additional hierarchical level of detail (using the "+" line command). The hierarchy is illustrated here:

Level 1 Facility Name
Level 2 Structure Name

Detail line descriptions

Facility detail line

This is the first-level detail line. Each line shows information about a facility name in the coupling facility.

| Under Heading | This is Displayed |
|-------------------|---|
| Name | The facility name. |
| Requests - Sync | The number of synchronous operations to the coupling facility. |
| Requests - Asynch | The number of asynchronous operations to the coupling facility. |
| Requests - Queued | The number of queued operations to the coupling facility. |
| Requests - Delay | The number of operations to the coupling facility that were delayed for dump serialization. |
| uSeconds - Sync | Total micro-seconds service time per synchronous operation to the coupling facility. |
| uSeconds - Asynch | Total micro-seconds service time per asynchronous operation to the coupling facility. |
| uSeconds - Queued | Total micro-seconds service time for operations queued for the coupling facility. |

| | |
|----------------------|---|
| Under Heading | This is Displayed |
| uSeconds - Delay | Total micro-seconds service time for operation delays for dump serialization. |

Sample reports

A sample report is shown here:

```

File View Navigate Help
-----
G03: Coupling Facility Total Service Times (0003/TSTJOB01) Row 00001 of 00002
Command ==>> _____ Scroll ==>> CSR

----- Number of Requests -----
Name      Sync  Async  Queued  Delay      Sync  Async  Queued  Delay
CFCC1     4112    0      0       0         4352    0      0       0
CFCC2      0       0      0       0          0      0      0       0

```

V01 - Measurement variance summary

Usage

Use this report to analyze variances between multiple separate measurements. To gain access to variance reporting, issue the "V" line command from the Observation Session List. The "V" line command selects the base measurement for comparison. Prior to entering the line command you must previously tag at least one measurement by entering the "T" line command in the Observation Session List. Up to 20 measurements can be tagged at one time. This report quantifies variances between tagged measurements and the base measurement.

Measurements analyzed

The first segment of the V01 report lists the measurements analyzed in the report. Each measurement is assigned a two-digit sequential reference number. This segment of the report identifies each of the measurements and their reference number.

The measurement identified by reference number 01 is the "base" measurement, the measurement to which the other measurements are compared. Throughout this report, measurements are identified by their reference numbers.

Variances

A percentage value is displayed under the heading "Variance" in various segments of this report. Its value quantifies the variance between a particular performance figure for the compared measurement and the corresponding value for the base measurement. A plus (+) value indicates a higher value than the base measurement and a minus (-) value indicates a lower value. The value is the percentage by which the compared measurement figure exceeds (+) or is less than (-) the corresponding base measurement value. Any value exceeding 999 percent is reported as "999%." The magnitude of the value is also represented graphically by a string of greater-than or less-than symbols.

CPU time TCB

This report segment compares the TCB CPU times that were recorded by the operating system during the measurement sessions.

CPU time SRB

This report segment compares the SRB CPU times that were recorded by the operating system during the measurement sessions.

EXCP requests

This report segment compares the number of EXCPs that were processed during the measurement sessions.

Service units

This report segment compares the number of service units recorded by the operating system during the measurement sessions.

Percentage of CPU active samples

This report segment compares the percentage of samples during which one or more TCBs was executing CPU instructions.

Percentage of WAIT samples

This report segment compares the percentage of samples during which all TCBs were in WAIT state.

Percentage of queued samples

This report segment compares the percentage of samples during which no CPU activity was taking place but one or more TCBs was suspended and waiting to be dispatched.

Sample reports

A sample report is shown here:

| <u>File</u> | <u>View</u> | <u>Navigate</u> | <u>Help</u> | | |
|---|----------------------|-----------------|-----------------------|-------------|--------------------|
| ----- | | | | | |
| V01: Measurement Variance Summary (2312/TSTJOB01) | | | Row 00001 of 00059 | | |
| Command ==> | | | Scroll ==> <u>CSR</u> | | |
| The Following Measurements are Analyzed | | | | | |
| <u>Ref</u> | <u>ReqNum</u> | <u>Job Name</u> | <u>Date</u> | <u>Time</u> | <u>Description</u> |
| 01 | 2312 | TSTJOB01 | Mar-30-2007 | 10:54 | Test 2 |
| 02 | 2311 | TSTJOB01 | Mar-30-2007 | 10:52 | Test 1 |
| ----- | | | | | |
| CPU Time TCB | | | | | |
| <u>Ref</u> | <u>CPU Time TCB</u> | <u>Variance</u> | | | |
| 01 | 11.41 sec | | | | |
| 02 | 11.73 sec | + 2 % | | | |
| ----- | | | | | |
| CPU Time SRB | | | | | |
| <u>Ref</u> | <u>CPU Time SRB</u> | <u>Variance</u> | | | |
| 01 | 1.52 sec | | | | |
| 02 | 1.61 sec | + 5 % | | | |
| ----- | | | | | |
| EXCP Requests | | | | | |
| <u>Ref</u> | <u>EXCP Requests</u> | <u>Variance</u> | | | |
| 01 | 7,721 | | | | |
| 02 | 7,710 | - 0 % | | | |
| ----- | | | | | |
| Service Units | | | | | |
| <u>Ref</u> | <u>Service Units</u> | <u>Variance</u> | | | |
| 01 | 7,721 | | | | |
| 02 | 7,710 | + 3 % | | | |
| ----- | | | | | |

Percentage of CPU Active Samples

| Ref | --- Sample Count --- | | Percentage | Variance |
|-----|----------------------|-------|------------|----------|
| | CPU Active | Total | | |
| 01 | 2,171 | 4,136 | 52.51% | |
| 02 | 2,452 | 4,790 | 51.21% | - 2 % |

Percentage of WAIT Samples

| Ref | --- Sample Count --- | | Percentage | Variance |
|-----|----------------------|-------|------------|----------|
| | TCB WAIT | Total | | |
| 01 | 1,739 | 4,136 | 42.06% | |
| 02 | 1,979 | 4,790 | 41.33% | - 1 % |

Percentage of Queued Samples

| Ref | --- Sample Count --- | | Percentage | Variance |
|-----|----------------------|-------|------------|-----------|
| | Queued | Total | | |
| 01 | 224 | 4,136 | 5.41% | |
| 02 | 357 | 4,790 | 7.45% | + 37 % >> |

Chapter 4. CICS performance analysis reports

This section describes the CICS Performance Analysis Reports.

| For information about ... | See ... |
|---|--|
| The CICS data extractor | "Overview of CICS data extractor" |
| E01 CICS session statistics | "E01 - CICS session statistics" on page 163 |
| E02 CICS CPU and use count by program | "E02 - CICS CPU and use count by program" on page 166 |
| E03 CICS CPU usage by transaction | "E03 - CICS CPU usage by transaction" on page 168 |
| E04 CICS mean service time by transaction | "E04 - CICS mean service time by transaction" on page 175 |
| E05 CICS total service time by transaction | "E05 - CICS total service time by Txn" on page 186 |
| E06 CICS service time by task ID | "E06 - CICS service time by task ID" on page 197 |
| E07 CICS wait by transaction | "E07 - CICS wait by Txn" on page 207 |
| E08 CICS mean service time by terminal ID | "E08 - CICS mean service time by terminal ID" on page 209 |
| E09 CICS total service time by terminal ID | "E09 - CICS total service time by terminal ID" on page 218 |
| E10 CICS mean service time by user ID | "E10 - CICS mean service time by user ID" on page 227 |
| E11 CICS total service time by user ID | "E11 - CICS total service time by user ID" on page 235 |
| E12 CICS CPU/service time by transaction | "E12 - CICS CPU/service time by transaction" on page 242 |
| X01 CICS mean service time by transaction (for multiple CICS address spaces) | "X01 - CICS mean service time by transaction" on page 245 |
| X02 CICS total service time by transaction (for multiple CICS address spaces) | "X02 - CICS total service time by txn" on page 253 |
| X03 CICS mean service time by terminal ID (for multiple CICS address spaces) | "X03 - CICS mean service time by terminal ID" on page 261 |
| X04 CICS total service time by terminal ID (for multiple CICS address spaces) | "X04 - CICS total service time by terminal ID" on page 269 |

Overview of CICS data extractor

In order to use the CICS Performance Analysis Reports, the CICS data extractor must be turned on when the Observation Request is entered. You must select the CICS data extractor in the Schedule New Measurement panel, and enter the transaction name(s) or patterns you want to observe. For more information on entering an observation request for CICS, see "Panel 5 – Subsystems" on page 29.

There are two distinct types of data that Application Performance Analyzer gathers when the CICS extractor is active: Session statistics, and Transaction measurement data.

Session statistics

This data is a summary of how much CICS related activity occurred in the region during the Observation Session. The activity measured is directly related to services requested by in-flight transactions. The data provides an indication on the load (or stress level) that transactions are placing on the region. In a region that is idle, almost all these numbers would be zero. Data for the majority of these statistics are gathered once at the start of the session and once at the end of the session. The statistics are then calculated by taking the delta of each set of data values.

Transaction measurement data

There is one sample record created for each in-flight transaction during each sampling interval. A transaction is only sampled if it was specified when the Observation Request was created. For some reports the sample records are analyzed to produce CPU usage and Service Time by transaction. These reports describe the load that a transaction is placing on the CICS region.

The sample record consists of transaction state data captured during a sampling interval. This information is used to generate the Session Activity report. This report highlights the state of sampled transactions. State information includes:

1. Whether the transaction was running or suspended (active or not)
2. Module information where it was running
3. Module information where to be resumed if suspended
4. Information on the CICS service executing on behalf of the application (if applicable)

CICS+ Extractor

CICS+ is a CICS measurement option (data extractor) in which the precise number of CICS transactions are counted during the measurement interval. It records the exact service time and CPU time for each transaction. This data is displayed in the E12 report only, and has no effect on the other CICS reports.

Activating the CICS+ option automatically activates the CICS option. The extractor applies to CICS TS 3.1 and above. Your installer may have chosen to limit access to this data extractor.

Overview of CICS Multiple Address Space Support

CICS multiple address space (MASS) support allows you to measure and analyze multiple CICS regions simultaneously. Transaction data from multiple regions is merged to produce a set of 4 CICS reports showing multi-region activity. These reports are X01, X02, X03 and X04.

To enter CICS MASS observations:

1. Start a NEW request.
2. In Panel 1 – Job Information, enter either a Job name/Pattern with an asterisk (*) or a multi-job measurement with a percent (%) for the CICS regions you want to measure.
3. In Panel 4 – Active Jobs, if you entered an asterisk (*) in the Job Name/Pattern field, select the CICS regions from the list of active jobs presented. If you entered a percent (%) in the Job Name/Pattern field, the CICS regions that match the pattern are displayed. It is not necessary to select the CICS regions in

this case, unless you want to limit the measurement to specific CICS regions. The maximum number of regions you are permitted to select is determined during the installation of Application Performance Analyzer.

4. In Panel 2 – Options, select the CICS data extractor.
5. Complete any other relevant panels for your request. You can specify further CICS measurement criteria in Panel 5 – Subsystems.

Once the NEW request is complete and submitted, Application Performance Analyzer creates and starts separate observation requests for each CICS region selected for measurement.

When the separate observation requests are completed, you can view the CICS MASS reports by using the tag (T) and report (S or R) commands.

- Tag up to 20 CICS region measurements to be included in the CICS MASS reports.
- Select one of the CICS region measurements for reporting, using the S or R command. This measurement does not have to be tagged.

In addition to the standard reports for the selected observation, Application Performance Analyzer generates the specific CICS MASS reports that show multi-region activity for all selected CICS regions.

E01 - CICS session statistics

Usage

Use this report to see a summary of the CICS measurement data collected during the observation session.

Note: Be aware that a reset of CICS statistics, if done during the measurement interval, can invalidate some of the values reported here.

Detail line descriptions

Environmental Information

Fields under this heading describe characteristics of the CICS environment.

CICS Release

The CICS version and release.

Transaction Statistics

Some CICS processing statistical values are shown under this heading.

First Transaction TaskId

The value of the CICS TaskId at the beginning of the observation session.

Last Transaction TaskId

The value of the CICS TaskId at the end of the observation session.

Number of TaskId Increments

The difference between the first and last CICS TaskId.

Number of Observed Transactions

The number of transactions with unique CICS TaskId values observed. If this value does not correspond to the number of increments, it could be an indication that not all executed transactions were measured. Some transactions could have been excluded as specified in the measurement

request or transactions can be missed if a sampling rate is chosen that is slower than the transaction throughput rate.

Transaction Rate

The average number of transactions per second during the measurement interval.

Peak Active Transactions

The maximum number of concurrently active transactions observed during the measurement interval.

Peak Active Txns (Overall)

The maximum number of concurrently active transactions that occurred during the entire execution of the CICS region.

MaxTask

The maximum number of concurrent transactions CICS is configured for.

Mean Transaction Time

The average service time for the transactions observed during the measurement interval.

The service time consists of:

Execution Time

The time a CPU is processing the transaction.

Suspend Time

The time the transaction is suspended by CICS.

CICS Dispatch Delay Time

The time the transaction is delayed by CICS.

MVS Dispatch Delay Time

The time execution is delayed by the MVS dispatcher.

Service Time

The sum of the execution time, the suspend time, and the delay time.

Service Statistics

These are counts of service requests issued by CICS programs during the measurement interval:

- Program Requests
- Terminal Messages
- Storage Getmains
- Storage Freemains
- File I/O Requests
- Temporary Storage Requests
- Transient Data Requests
- Journal Write Requests

Exception or Critical Conditions

These are counts of certain exception or critical conditions that occurred during the measurement interval:

- System Dumps
- System Dumps Suppressed
- Transaction Dumps
- Transaction Dumps Suppressed

- Storage Violations
- Short on Storage occurrences
- Times at MaxTask
- Times at Class MaxTask

Transaction Counts

A list of each transaction code that was measured and the number of executions is shown here.

Sample reports

A sample report is shown here:

```

File View Navigate Help
-----
E01: CICS Session Statistics (0866/CICS23A) Row 00001 of 00045
Command ==> _____ Scroll ==> CSR

Environmental Information
  CICS Release                CICS/TS 2.3

Transaction Statistics
  First Transaction TaskId     0002089
  Last Transaction TaskId      0002242
  Number of TaskId Increments  153
  Number of Observed Transactions 153
  Transaction Rate (per sec)   2.18
  Peak Active Txns (Observed)  1
  Peak Active Txns (Overall)   2
  MaxTask                      5

Mean Transaction Time (Execution + Suspend + Delay = Service)
  Execution Time               0.0727747
  Suspend Time                  0.232708
  CICS Dispatch Delay Time     0.052427
  MVS Dispatch Delay Time      0.018062
  Service Time                  0.375944

Service Statistics
  Program Requests              536
  Terminal Messages             305
  Storage Getmains              3,295
  Storage Freemains             3,279
  File I/O Requests             0
  Temporary Storage Requests    0
  Transient Data Requests       0
  Journal Write Requests        0

Exception or Critical Conditions
  System Dumps                  0
  System Dumps Suppressed       0
  Transaction Dumps              0
  Transaction Dumps Suppressed   0
  Storage Violations             0
  Short on Storage occurrences    0
  Times at MaxTask               0

```

```

File View Navigate Help
-----
E01: CICS Session Statistics (0866/CICS23A) Row 00040 of 00047
Command ==> _____ Scroll ==> CSR

Transaction Counts

TranId  Count
DNC1    151
CESN     2
CQRY     1
CATA     1

```

E02 - CICS CPU and use count by program

Usage

Use this report to get CPU usage and call counts for CICS programs that were executing during the observation session.

Quantification

Each report line displays the number of times a program was called by CICS services. The report will not show any calls using a direct method such as a branch and link register (BALR). Each report line also quantifies CPU usage as a percentage. Each percentage represents the ratio of CPU consumption observed for the reported program to the total CPU consumption measured in the address space.

Note that the sum of all the percentages will normally be less than 100 percent because only those CICS transactions being measured are quantified in the report, but the percentage is the portion of the total CICS region CPU consumption. Similarly, any CICS region CPU overhead not attributable to CICS transactions will not be quantified in the report.

A program name of "CICS" is used to quantify CPU consumption not directly attributable to a CICS program. A CICS program in this report is a program that is defined in the CICS System Definition (CSD) dataset.

Note: The E02 report cannot be directly compared to the C02 CPU Usage report because C02 reports CPU usage by module, and E02 reports CPU directly used by or attributable to a CICS program. For example, CPU time used while processing an EXEC CICS command would be reported in a DFH program in the C02 report, but would be attributed to the CICS application program making the call in the E02 report.

Detail line hierarchy

The E02 shows one level, the detail lines cannot be expanded.

The hierarchy is illustrated here:

Sample reports

A sample is shown here:

| File View Navigate Help | | |
|--|-------|------------------------------------|
| E02: CICS CPU and Use Counts by Pgm (3090/CICS23A) | | Row 00001 of 00016 |
| Command ==> | | Scroll ==> CSR |
| Name | Calls | Percent of CPU Time * 10.00% ±1.5% |
| *....1....2....3....4....5....6....7....8....9.. | | |
| CICSDB2 | 300 | 36.82 ===== |
| SAMPREAD | 501 | 30.56 ===== |
| DSN5CA0 | 30 | 10.05 ===== |
| CSQCTRUE | 0 | 4.09 == |
| DFHD2EXI | 0 | 3.79 == |
| CICS | 0 | 3.74 == |
| DB2DRVR | 1 | 2.44 = |
| READDRVR | 1 | 2.29 = |
| MQSAMP1 | 100 | 2.12 = |
| MQDRVR | 1 | 1.54 = |
| SAMPBGN1 | 200 | 1.22 = |
| CSQ4CVK1 | 100 | 1.09 = |
| IMSDRVR | 1 | 0.19 |
| DFHEMTD | 1 | 0.00 |
| DFHEITMT | 1 | 0.00 |
| DFHEMTP | 1 | 0.00 |

Detail line descriptions

CICS program name detail line

This is the only level for the detail line. Each line shows information about a CICS program for which CPU consumption was measured.

| Under Heading | This is Displayed |
|---------------------|--|
| Name | The CICS program name. |
| Calls | The number of times this program was called by another CICS program. The call must be done by an EXEC CICS API call. |
| Percent of CPU Time | The percentage of CPU time consumed during execution of the program. |

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Load Module | Display context help information. |
| ++ | Load Module | Show additional details. |
| M | Load Module | Display load module information. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Name, Percent CPU | Display context help information. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|---------------------------|
| + | Percent CPU | Zoom in scale. |
| - | Percent CPU | Zoom out scale. |
| + | Percent CPU | Zoom in scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |
| SC | Name | Sort by call count. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| SAMPREAD      501      30.56 ===== |
+-----+

Call count at start:      3
Call count at end:       504
Difference:               501
Load count:               0
CPU active samples:      1,225
Total CPU active:        4,008
+-----+

```

E03 - CICS CPU usage by transaction

Usage

Use this report to see how CPU consumption was distributed across the CICS transactions that were executing during the observation session.

Expand a CICS transaction report line to see a further breakdown by program, CICS command and SQL Request.

Quantification

Each report line quantifies CPU usage as a percentage. Each percentage represents the ratio of CPU consumption observed for the reported item (transaction, program, CICS command or SQL request) to the total CPU consumption measured in the address space. The sum of all the percentages will normally be less than 100 percent because only those CICS transactions being measured are quantified in the report. But the percentage is the portion of the total CICS region CPU consumption.

Similarly, any CICS region CPU overhead not attributable to CICS transactions will not be quantified in the report.

Detail line hierarchy

An unexpanded E03 report shows a line for each CICS transaction for which CPU usage was measured. You can expand each line to reveal additional hierarchical levels of detail.

The hierarchy is illustrated here:

```

Level 1 CICS Transaction
Level 2 CICS Program
  Level 3 CICS Command
  Level 3 CICS Command

...
Level 2 CICS Program
Level 3 SQL Request
Level 3 SQL Request

...
Level 2 CICS Program
Level 3 DL/I Request
Level 3 DL/I Request

...
Level 2 CICS Program
Level 3 Module
Level 3 Module
Level 3 System Services

...
Level 2 CICS Program
Level 3 Adabas Request
Level 3 Adabas Request

...
Level 2 System Services
Level 3 Module
Level 3 Module
Level 3 System Services

...

```

Sample reports

When the report is first displayed, only the first level of the hierarchy is visible (transaction). A sample is shown here:

| File View Navigate Help | | | |
|---|-------------------|--------------------------------------|-------|
| E03: CICS CPU Usage by Transaction (0817/CICS23A) | | Row 00001 of 00004 | |
| Command ==> | | Scroll ==> CSR | |
| Name | NTxns/Description | Percent of CPU time * 10.00% | ±1.5% |
| | | *....1....2....3....4....5....6....7 | |
| DNC1 | 327 | 77.22 | ===== |
| FINQ | 295 | 8.35 | ==== |

You can enter the “+” line command on a transaction to expand to the next level. A sample of the report with a transaction expanded to the second level of the hierarchy (CICS program) is shown here:

```

File View Navigate Help
-----
E03: CICS CPU Usage by Transaction (0817/CICS23A)          Row 00001 of 00015
Command ==> _____ Scroll ==> CSR

Name  NTxns/Description          Percent of CPU time * 10.00% ±1.5%
      *...1...2...3...4...5...6...7
DNC1   327                    77.22 =====
→ PFSAMPC EXEC SQL          35.01 =====
→ DFHD2EX1 CICS Program     16.38 =====
→ PFSAMPB EXEC SQL           8.14 =====
→ PFSAMPA EXEC SQL           3.59 ==
→ PFSAMPA CICS Program       3.54 ==
→ CICS System Services      3.11 ==
→ PFSAMPB CICS Program       3.02 ==
→ PFSAMPA EXEC CICS         2.05 =
→ PFSAMPC CICS Program       1.89 =
→ CEECCICS EXEC CICS         0.34
→ PFSAMPB EXEC CICS         0.09
FINQ   295                    8.35 =====

```

You can enter the “+” line command on a program to expand to the next level. In the sample below, a line with description “EXEC SQL” has been expanded, showing the SQL commands:

```

File View Navigate Help
-----
E03: CICS CPU Usage by Transaction (0817/CICS23A)          Row 00001 of 00027
Command ==> _____ Scroll ==> CSR

Name  NTxns/Description          Percent of CPU time * 10.00% ±1.5%
      *...1...2...3...4...5...6...7
DNC1   327                    77.22 =====
→ PFSAMPC EXEC SQL          35.01 =====
  → +1BE2 FETCH             13.29 =====
  → +662A FETCH              6.56 ==
  → +0F52 SELECT             3.36 ==
  → +6E9C SELECT             2.72 =
  → +1164 SELECT             2.33 =
  → +6C4C SELECT             1.89 =
  → +6248 SELECT             1.85 =
  → +1588 OPEN               1.55 =
  → +64D0 OPEN               0.89
  → +6752 CLOSE             0.29
  → +2348 CLOSE             0.22

```

Detail line descriptions

CICS transaction detail line

This is the first-level detail line. Each line shows information about a CICS transaction for which CPU consumption was measured.

| Under Heading | This is Displayed |
|---------------------|--|
| Name | The CICS transaction code. |
| NTxns | The number of executions of the transaction. |
| Description | If this is a recognized CICS transaction, a functional description. |
| Percent of CPU Time | The percentage of CPU time consumed during execution of the transaction. |

CICS program or system services detail line

This is a second-level detail line shown directly under the CICS transaction detail line. This line represents a CICS program (usually an application) that was in control during execution of the transaction. The third-level lines shown under this item can be CICS command lines, SQL requests, DL/I requests or Module lines.

If no CICS application program was dispatched, "CICS" is shown under the Name heading and "System Services" under the Description heading.

| Under Heading | This is Displayed |
|---------------------|--|
| Name | The module name of the CICS program. If lines grouped under this line are CICS command lines, DB2 SQL, or IMS DLI calls, this field is displayed in red. For Module lines grouped under this line, the field is turquoise. "CICS" is displayed here if no application program was in control. |
| Description | If lines grouped under this line are CICS command lines, this displays "EXEC CICS." If lines grouped under this line are SQL request lines, this displays "EXEC SQL". If lines grouped under this line are DL/I request lines, this displays "EXEC DLI". Otherwise, if the program name is a recognized CICS module name (a DFH* name), a functional description is shown, and "CICS Program" is displayed if it is not recognized; indicating this is likely an application program. "System Services" is displayed if no application program was in control. |
| Percent of CPU Time | The percentage of CPU time consumed while executing in the identified program during execution of the transaction under which the line appears. |

CICS command detail line

These lines appear under a CICS Program detail line. Each one represents a CICS command issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC CICS command. This is in +xxxx format. If the CSECT containing the EXEC CICS is not the same name as the module identified in the CICS Program line above, this field contains the CSECT name. In this case, the offset is shown in the description field. This field is always displayed in red. |
| Description | The CICS command descriptor. If, as noted above, the CSECT name containing the EXEC CICS is different from the module name, the CICS command descriptor is preceded by the hexadecimal offset of the command from the start of the CSECT. |
| Percent of CPU Time | The percentage of CPU time consumed while executing the CICS command. |

SQL Request detail line

These lines appear under a CICS Program detail line. Each one represents an SQL request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------------|--|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC SQL call. This is in +xxxx format. This field is always displayed in red |
| Description | The SQL request function – SELECT, FETCH, UPDATE, etc. |
| Percent of CPU Time | The percentage of CPU time consumed while executing the SQL request. |

DL/I Request detail line

These lines appear under a CICS Program detail line. Each one represents an IMS DL/I request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------------|--|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC DL/I call. This is in +xxxx format. This field is always displayed in red. |
| Description | The DL/I function code followed by the PCB name. |
| Percent of CPU Time | The percentage of CPU time consumed while executing the DL/I request. |

Active module detail line

These lines appear under a CICS Program detail line. Each one represents a module that was executing under control of the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------------|--|
| Name | The name of the module that was executing. |
| Description | A functional description of the module if one is available. |
| Percent of CPU Time | The percentage of CPU time consumed while executing in the module within the grouping under which the detail line appears. |

Adabas request detail line

These lines appear under a CICS Program detail line. Each one represents an Adabas request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC ADABAS command. This is in +xxxx format. This field is always displayed in red. |
| Description | The Adabas request function -- OP, CL, L2, etc. |
| Percent of CPU Time | The percentage of CPU time consumed while executing the Adabas request. |

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|---|-----------------------------------|
| ? | Transaction, Load Module, CSECT, Command, Seqno, DL/I Request | Display context help information. |
| ++ | Transaction, Load Module, CSECT, Command, Seqno, DL/I Request | Show additional details. |
| + | Transaction, Load Module | Expand to reveal next level. |
| - | Transaction, Load Module | Collapse to hide next level. |
| SV | Transaction, Load Module | Sort next level by value. |
| SN | Transaction, Load Module | Sort next level by name. |
| M | Load Module | Display load module information. |
| P | CICS Active Module, Command, CSECT, Seqno, DL/I Request | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Sort next level by name. |
| + | Percent CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce description field size. |
| - | Percent CPU | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here, this one is for a CICS command:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| > +2C70   RETURN                   0.72             |
+-----+

Calculation Details
CICS Transaction                DNC1
CPU Measurements Servicing CICS Commands  21
Total Measurements              2906
Percent of total                 0.72%

Command Attributes
CICS Command                    EXEC CICS RETURN
Issued in Load Module           PFSAMPA
Return Offset in Module         +2C90
Name of CSECT                   PFSAMPA
Return Offset in CSECT         +2C70

The command execution measurement counts are
Executing (CPU active)          21
Suspended by CICS              0
Delayed
  CICS dispatch delay          0
  MVS delay (WAIT)             0
  MVS delay (Busy)             0

```

A sample detail window for an SQL command is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| → +84D6   SELECT                   1,84 =           |
+-----+

Calculation Details
CICS Transaction                DNC1
CPU Measurements Servicing DB2 SQL    168
Total Measurements              1980
Percent of total                 8.48%
These quantities represent measurements of CPU usage while
processing the indicated SQL requests.

SQL Statement Information
Subsystem name DSN1              Attach type  SASS
Plan name     PFSAMPA           Plan BIND time Nov-28-04 14:11:17

DBRM name     PSSAMPC          DBRM token   17859595 06957A24
DBRM date/time Nov-25-04 14:49:42

Package ID    PFSAMPC          Location     CABNETDB24
Collectn name PFSAMPX2        Pkg BIND time no data

SQL function  SELECT            Static/dynamic Static
Precmplr stmt# 3155          DBRM section# 20
CSECT/module   PFSAMPC in PFSAMPC  Offset of call 000084D6
Sample count   69              SQL req count 172
SQL CPU time   0.28          Service time   0.43

SQL Statement:  SELECT * INTO : H , : H , : H , : H , : H : H FROM
                DEPT WHERE XRATE = : H

```

SETUP options

The following SETUP option can be selected with the SETUP primary command:

Minimum CPU percentage

You can set this option to eliminate modules where the CPU percentage is below a certain threshold.

E04 - CICS mean service time by transaction

Usage

Use this report to see an analysis of how time was spent by the CICS transactions that were executing during the observation session. Expand a CICS transaction report line to see a further breakdown by program, CICS command, DL/I request and SQL request.

Quantification

Each report line quantifies time as arithmetic means for each measured transaction. The means are calculated by dividing the total of all time spent servicing all occurrences of a transaction by its number of occurrences. The means are expressed in units of seconds. The mean service time is shown and is further broken down into execution time, suspend time, and delay time.

Detail line hierarchy

An unexpanded E04 report shows a line for each measured CICS transaction. You can expand each line to reveal additional hierarchical levels of detail.

The hierarchy is illustrated here:

Level 1 CICS Transaction
Level 2 CICS Program
 Level 3 CICS Command
 Level 3 CICS Command

...

Level 2 CICS Program
Level 3 SQL Request
Level 3 SQL Request

...

Level 2 CICS Program
Level 3 DL/I Request
Level 3 DL/I Request

...

Level 2 CICS Program
Level 3 Module
Level 3 Module
Level 3 System Services

...

Level 2 CICS Program
Level 3 Adabas Request
Level 3 Adabas Request

...

Level 2 System Services
Level 3 Module

Level 3 Module
 Level 3 System Services

...

Sample reports

When the report is first displayed, only the first level of the hierarchy is visible (transaction). A sample is shown here:

```

File View Navigate Help
-----
E04: CICS Mean Service Time by Txn (0817/CICS23A)          Row 00001 of 00004
Command ==>>> _____ Scroll ==>>> CSR

Name      NTxns Description          Error Execution + Suspend + Delay = Service
-----
DNC1      327                          ± 5.5% 0.103 0.013 0.023 0.140
FINQ      295                          ± 5.8% 0.012 0.000 0.011 0.023
  
```

You can enter the “+” line command on a transaction to expand to the next level. A sample of the report with a transaction expanded to the second level of the hierarchy (CICS Program) is shown here:

```

File View Navigate Help
-----
E04: CICS Mean Service Time by Txn (0817/CICS23A)          Row 00001 of 00004
Command ==>>> _____ Scroll ==>>> CSR

Name      NTxns Description          Error Execution + Suspend + Delay = Service
-----
DNC1      327                          ± 5.5% 0.103 0.013 0.023 0.140
→ PFSAMPC EXEC SQL                  0.046 0.000 0.004 0.051
→ DFHD2EX1 CICS Program        0.021 0.011 0.002 0.035
→ PFSAMPB EXEC SQL                  0.010 0.000 0.002 0.013
→ CICS     System Services      0.004 0.000 0.008 0.012
→ PFSAMPA CICS Program        0.004 0.000 0.002 0.007
→ PFSAMPA EXEC SQL                  0.004 0.000 0.001 0.006
→ PFSAMPB CICS Program        0.004 0.000 0.000 0.004
→ PFSAMPC CICS Program        0.002 0.000 0.000 0.002
→ PFSAMPA EXEC CICS           0.002 0.000 0.000 0.002
→ CEECCICS EXEC CICS           0.000 0.000 0.000 0.000
→ PFSAMPB EXEC CICS           0.000 0.000 0.000 0.000
  
```

You can enter the “+” line command on a program to expand to the next level. In the sample below, a line with description “EXEC SQL” has been expanded, showing the SQL commands:

```

File View Navigate Help
-----
E04: CICS Mean Service Time by Txn (0817/CICS23A) Row 00001 of 00041
Command ==> _____ Scroll ==> CSR
-----
Name      NTxns Description      Error Execution + Suspend + Delay = Service
-----
DNC1      327                    ± 5.5%  0.103  0.013  0.023  0.140
→ PFSAMPC EXEC SQL              0.046  0.000  0.004  0.051
→ +1BE2   FETCH          0.017  0.000  0.001  0.019
→ +662A   FETCH          0.008  0.000  0.000  0.009
→ +0F52   SELECT          0.004  0.000  0.000  0.005
→ +6E9C   SELECT          0.003  0.000  0.000  0.004
→ +1164   SELECT          0.003  0.000  0.000  0.003
→ +6C4C   SELECT          0.002  0.000  0.000  0.002
→ +6248   SELECT          0.002  0.000  0.000  0.002
→ +1588   OPEN            0.002  0.000  0.000  0.002
→ +64D0   OPEN            0.001  0.000  0.000  0.001
→ +6752   CLOSE           0.000  0.000  0.000  0.000
→ +2348   CLOSE           0.000  0.000  0.000  0.000

```

Detail line descriptions

CICS transaction detail line

This is the first-level detail line. Each line shows information about a CICS transaction for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The CICS transaction code. |
| NTxns | The number of executions of the transaction. |
| Description | If this is a recognized CICS transaction, a functional description. |
| Error | The margin of error for the mean values calculated by using the number of executions of the transaction as the sample size. |
| Execution | The mean time, in seconds, a CPU was actively executing for the transaction. |
| Suspend | The mean time, in seconds, CICS had suspended execution of the transaction. |
| Delay | <p>The mean time, in seconds, execution of the transaction was delayed. This is a fourth-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i></p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |

| Under Heading | This is Displayed |
|---------------|---|
| Service | The mean service time for the transaction. This includes execution, suspend and delay time. |

CICS program or system services detail line

This is a second-level detail line shown directly under the CICS transaction detail line. This line represents a CICS program (usually an application) that was in control during execution of the transaction. The third-level lines shown under this item can be either CICS command lines, SQL Request lines, DL/I Request lines or Module lines.

If no CICS application program was dispatched, "CICS" is shown under the Name heading and "System Services" under the Description heading.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The module name of the CICS program. If lines grouped under this line are CICS command lines, DB2 SQL, or IMS DLI calls, this field is displayed in red. For Module lines grouped under this line, the field is turquoise. "CICS" is displayed here if no application program was in control. |
| NTxns | If lines grouped under this line are CICS command lines, this displays "EXEC CICS". If lines grouped under this line are SQL request lines, this displays "EXEC SQL". If lines grouped under this line are DL/I request lines, this displays "EXEC DLI". Otherwise, if the program name is a recognized CICS module name (a DFH* name), a functional description is shown, and "CICS Program" is displayed if it is not recognized; indicating this is likely an application program. "System Services" is displayed if no application program was in control. |
| Description | If this is a recognized CICS transaction, a functional description. |
| Execution | The mean time, in seconds, CPU execution was observed while transaction control was under the CICS program identified in the Name column. |
| Suspend | The mean time, in seconds, CICS had suspended execution of the transaction while transaction control was under the CICS program identified in the Name column. |

| Under Heading | This is Displayed |
|---------------|---|
| Delay | <p>The mean time, in seconds, execution of the transaction was delayed. This is a fourth-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i></p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |
| Service | The mean service time for the transaction control was under the CICS program identified in the Name column. This includes execution, suspend and delay time. |

CICS command detail line

These lines appear under a CICS Program detail line. Each one represents a CICS command issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC CICS command. This is in +xxxx format. If the CSECT containing the EXEC CICS is not the same name as the module identified in the CICS Program line above, this field contains the CSECT name. In this case, the offset is shown in the description field. This field is always displayed in red. |
| Description | The CICS command descriptor. If, as noted above, the CSECT name containing the EXEC CICS is different from the module name, the CICS command descriptor is preceded by the hexadecimal offset of the command from the start of the CSECT. |
| Execution | The mean time, in seconds, CPU execution was observed while the CICS command was being processed. |
| Suspend | The mean time, in seconds, CICS had suspended execution of the transaction while the CICS command was being processed. |

| Under Heading | This is Displayed |
|---------------|---|
| Delay | <p>The mean time, in seconds, execution of the transaction was delayed. This is a fourth-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i></p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |
| Service | The mean service time for the transaction the CICS command was being processed. This includes execution, suspend and delay time. |

SQL request detail line

These lines appear under a CICS Program detail line. Each one represents an SQL request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC SQL command. This is in +xxxx format. This field is always displayed in red. |
| Description | The SQL request function — SELECT, FETCH, UPDATE, etc. |
| Execution | The mean time, in seconds, CPU execution was observed while the SQL request was being processed. |
| Suspend | The mean time, in seconds, CICS had suspended execution of the transaction while the SQL request was being processed. |

| Under Heading | This is Displayed |
|---------------|---|
| Delay | <p>The mean time, in seconds, execution of the transaction was delayed. This is a fourth-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i></p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |
| Service | The mean service time for the transaction the SQL request was being processed. This includes execution, suspend and delay time. |

DL/I request detail line

These lines appear under a CICS Program detail line. Each one represents an IMS DL/I request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC DL/I command. This is in +xxxx format. This field is always displayed in red. |
| Description | The DL/I function code followed by the PCB name. |
| Execution | The mean time, in seconds, CPU execution was observed while the DL/I request was being processed. |
| Suspend | The mean time, in seconds, CICS had suspended execution of the transaction while the DL/I request was being processed. |

| Under Heading | This is Displayed |
|---------------|---|
| Delay | <p>The mean time, in seconds, execution of the transaction was delayed. This is a fourth-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i></p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |
| Service | The mean service time for the transaction the DL/I request was being processed. This includes execution, suspend and delay time. |

Module/system services detail line

These lines appear under a CICS Program detail line. Each one represents a module that was executing under control of the program identified in the name field of the CICS Program line under which these lines are grouped. If Application Performance Analyzer was unable to determine a module name, "CICS" is displayed in the name field and "System Services" in the description field.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The name of the module that was executing or "CICS" if a module name could not be determined. |
| Description | A functional description of the module if one is available. "System Services" is displayed if the module name could not be determined. |
| Execution | The mean time, in seconds, for execution of the module within the grouping under which the detail line appears. |
| Suspend | This field will contain a value of zero. |

| Under Heading | This is Displayed |
|---------------|---|
| Delay | <p>The mean time, in seconds, execution of the transaction was delayed. This is a fourth-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i></p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |
| Service | The mean service time for the transaction the identified module was executing or delayed. |

Adabas request detail line

These lines appear under a CICS Program detail line. Each one represents an Adabas request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC ADABAS command. This is in +xxxx format. This field is always displayed in red. |
| Description | The Adabas request function -- OP, CL, L2, etc. |
| Execution | The mean time, in seconds, during which CPU execution was observed while the Adabas request was being processed. |
| Suspend | The mean time, in seconds, during which CICS had suspended execution of the transaction while the Adabas request was being processed. |
| Delay | <p>The mean time, in seconds, during which execution of the transaction was delayed while the Adabas request was being processed for one of the following reasons:</p> <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The mean service time for the transaction during which the Adabas request was being processed. This includes execution, suspend and delay time. |

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|---|-----------------------------------|
| ? | Transaction, Load Module, CSECT, Command, Seqno, DL/I Request | Display context help information. |
| ++ | Transaction, Load Module, CSECT, Command, Seqno, DL/I Request | Show additional details. |
| + | Transaction, Load Module | Expand to reveal next level. |
| - | Transaction, Load Module | Collapse to hide next level. |
| SV | Transaction, Load Module | Sort next level by value. |
| SN | Transaction, Load Module | Sort next level by name. |
| M | Load Module | Display load module information. |
| P | CICS Active Module, Command, CSECT, Seqno, DL/I Request | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Name | Display context help information. |
| + | Name | Expand to reveal all entries. |
| - | Name | Collapse to show only first level. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here, this one is for a CICS command:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| > +2C70   RETURN           0.000   0.000   0.000   0.000|
+-----+

Calculation Details
CICS Transaction                DNC1
The quantities shown represent the service time for execution of the
indicated CICS command while processing this transaction. The
quantities are mean times for the command for all executions of the
transaction and are calculated as follows:

(1) Times command observed in txn/program      26
(2) Duration of one sample interval            0.006003
(3) (1) x (2) = total time for command         0.156078
(4) Number of executions of transaction        342
(5) (3) ÷ (4) = mean time for the command      0.000456

Command Attributes
CICS Command                      EXEC CICS RETURN
Issued in Load Module              PFSAMPA
Return Offset in Module            +2C90
Name of CSECT                      PFSAMPA
Return Offset in CSECT             +2C70

The command execution measurement counts are
Executing (CPU active)              21
Suspended by CICS                   5
Delayed
  CICS dispatch delay               0
  MVS delay (WAIT)                  0
  MVS delay (Busy)                  0

```

A sample detail window for an SQL command is shown here:

```

File View Navigate Help
+----- The following report line was selected -----+
|  → +85D8      SELECT                          0.001    0.000    0.000
+-----+

Calculation Details
CICS Transaction                                DNC1
The quantities shown represent the service time for execution of the
indicated DB2 SQL call while processing this transaction. The
quantities are mean times for the SQL call for all executions of the
transaction and are calculated as follows:

(1) Times SQL call observed in txn/program    93
(2) Duration of one sample interval          0.006003
(3) (1) x (2) = total time for SQL call      0.558279
(4) Number of execution of transaction       342
(5) (3) ÷ (4) = mean time for the SQL call   0.001632

SQL Statement Information
Subsystem name  DSN1                      Attach type  SASS
Plan name      PFSAMPA                    Plan BIND time  Nov-28-04 14:11:17

DBRM name      PSSAMPC                    DBRM token    17859595 06957A24
DBRM date/time Nov-25-04 14:49:42

Package ID     PFSAMPC                    Location      CABNETDB24
Collectn name  PFSAMPX2                       Pkg BIND time no data

SQL function   SELECT                          Static/dynamic Static
Precmplr stmt# 3179                          DBRM section#  21
CSECT/module   PFSAMPC in PFSAMPC                Offset of call 000085D8
Sample count   93                                SQL req count  172
SQL CPU time   0.28                           Service time   0.54

SQL Statement:  SELECT * INTO : H , : H , : H : H , : H FROM DEPT
                WHERE XRATE = : H

```

E05 - CICS total service time by Txn

Usage

Use this report to see an analysis of how time was spent by the CICS transactions that were measured during the observation session. Expand a CICS transaction report line to see a further breakdown by program and by CICS command.

Quantification

Each report line quantifies total times for each measured transaction. The total times are expressed in units of seconds. The total service time is shown and is further broken down into execution time, suspend time, and delay time.

Detail line hierarchy

An unexpanded E05 report shows a line for each measured CICS transaction. You can expand each line to reveal additional hierarchical levels of detail.

The hierarchy is illustrated here:

- | **Level 1** CICS Transaction
- | **Level 2** CICS Program
- | **Level 3** CICS Command
- | **Level 3** CICS Command

```

...
Level 2 CICS Program
Level 3 SQL Request
Level 3 SQL Request

...
Level 2 CICS Program
Level 3 DL/I Request
Level 3 DL/I Request

...
Level 2 CICS Program
Level 3 Module
Level 3 Module
Level 3 System Services

...
Level 2 CICS Program
Level 3 Adabas Request
Level 3 Adabas Request

...
Level 2 System Services
Level 3 Module
Level 3 Module
Level 3 System Services

...

```

Detail line descriptions

CICS transaction detail line

This is the first-level detail line. Each line shows information about a CICS transaction for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The CICS transaction code. |
| NTxns | The number of executions of the transaction. |
| Description | If this is a recognized CICS transaction, a functional description. |
| Error | The margin of error based on a sample population of the number of executions of the transaction. |
| Execution | The total time, in seconds, that a CPU was actively executing for the transaction. |
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction. |

| Under Heading | This is Displayed |
|---------------|--|
| Delay | <p>The mean time, in seconds, execution of the transaction was delayed. This is a fourth-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i>.</p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |
| Service | The total service time for the transaction. This includes execution, suspend and delay time. |

CICS program or system services detail line

This is a second-level detail line shown directly under the CICS transaction detail line. This line represents a CICS program (usually an application) that was in control during execution of the transaction. The third-level lines shown under this item can be either CICS command lines, SQL Request lines, DL/I Request lines or Module lines.

If no CICS application program was dispatched, "CICS" is shown under the Name heading and "System Services" under the Description heading.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The module name of the CICS program. If lines grouped under this line are CICS command lines, DB2 SQL, or IMS DLI calls, this field is displayed in red. For Module lines grouped under this line, the field is turquoise. "CICS" is displayed here if no application program was in control. |
| Description | If lines grouped under this line are CICS command lines, this displays "EXEC CICS". If lines grouped under this line are SQL request lines, this displays "EXEC SQL". If lines grouped under this line are DL/I request lines, this displays "EXEC DLI". Otherwise, if the program name is a recognized CICS module name (a DFH* name), a functional description is shown, and "CICS Program" is displayed if it is not recognized; indicating this is likely an application program. "System Services" is displayed if no application program was in control. |
| Execution | The total time, in seconds, CPU execution was observed while transaction control was under the CICS program identified in the Name column. |
| Suspend | The total time, in seconds, CICS had suspended execution of the transaction while transaction control was under the CICS program identified in the Name column. |

| Under Heading | This is Displayed |
|---------------|---|
| Delay | <p>The mean time, in seconds, execution of the transaction was delayed. This is a fourth-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i></p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |
| Service | The total service time for the transaction control was under the CICS program identified in the Name column. This includes execution, suspend and delay time. |

CICS command detail line

These lines appear under a CICS Program detail line. Each one represents a CICS command issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC CICS command. This is in +xxxx format. If the CSECT containing the EXEC CICS is not the same name as the module identified in the CICS Program line above, this field contains the CSECT name. In this case, the offset is shown in the description field. This field is always displayed in red. |
| Description | The CICS command descriptor. If, as noted above, the CSECT name containing the EXEC CICS is different from the module name, the CICS command descriptor is preceded by the hexadecimal offset of the command from the start of the CSECT. |
| Execution | The total time, in seconds, CPU execution was observed while the CICS command was being processed. |
| Suspend | The total time, in seconds, CICS had suspended execution of the transaction while the CICS command was being processed. |

| Under Heading | This is Displayed |
|---------------|---|
| Delay | <p>The mean time, in seconds, execution of the transaction was delayed. This is a fourth-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i></p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |
| Service | The total service time for the transaction the CICS command was being processed. This includes execution, suspend and delay time. |

SQL request detail line

These lines appear under a CICS Program detail line. Each one represents an SQL request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC SQL command. This is in +xxxx format. This field is always displayed in red. |
| Description | The SQL request function — SELECT, FETCH, UPDATE, etc. |
| Execution | The total time, in seconds, CPU execution was observed while the SQL request was being processed. |
| Suspend | The total time, in seconds, CICS had suspended execution of the transaction while the SQL request was being processed. |

| Under Heading | This is Displayed |
|---------------|---|
| Delay | <p>The mean time, in seconds, execution of the transaction was delayed. This is a fourth-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i></p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |
| Service | The total service time for the transaction the SQL request was being processed. This includes execution, suspend and delay time. |

DL/I request detail line

These lines appear under a CICS Program detail line. Each one represents an IMS DL/I request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC DL/I command. This is in +xxxx format. This field is always displayed in red. |
| Description | The DL/I function code followed by the PCB name. |
| Execution | The total time, in seconds, CPU execution was observed while the DL/I request was being processed. |
| Suspend | The total time, in seconds, CICS had suspended execution of the transaction while the DL/I request was being processed. |

| Under Heading | This is Displayed |
|---------------|---|
| Delay | <p>The mean time, in seconds, execution of the transaction was delayed. This is a fourth-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i></p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |
| Service | The total service time for the transaction the DL/I request was being processed. This includes execution, suspend and delay time. |

Module/system services detail line

These lines appear under a CICS Program detail line. Each one represents a module that was executing under control of the program identified in the name field of the CICS Program line under which these lines are grouped. If Application Performance Analyzer was unable to determine a module name, "CICS" is displayed in the name field and "System Services" in the description field.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The name of the module that was executing or "CICS" if a module name could not be determined. |
| Description | A functional description of the module if one is available. "System Services" is displayed if the module name could not be determined. |
| Execution | The total time, in seconds, for execution of the module within the grouping under which the detail line appears. |
| Suspend | This field will contain a value of zero. |

| Under Heading | This is Displayed |
|---------------|---|
| Delay | <p>The mean time, in seconds, execution of the transaction was delayed. This is a fourth-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i></p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |
| Service | The total service time for the transaction the identified module was executing or delayed. |

Adabas request detail line

These lines appear under a CICS Program detail line. Each one represents an Adabas request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC ADABAS command. This is in +xxxx format. This field is always displayed in red. |
| Description | The Adabas request function -- OP, CL, L2, etc. |
| Execution | The total time, in seconds, during which CPU execution was observed while the Adabas request was being processed. |
| Suspend | The total time, in seconds, during which CICS had suspended execution of the transaction while the Adabas request was being processed. |
| Delay | <p>The total time, in seconds, during which execution of the transaction was delayed while the Adabas request was being processed for one of the following reasons:</p> <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The total service time for the transaction during which the Adabas request was being processed. This includes execution, suspend and delay time. |

Sample reports

When the report is first displayed, only the first level of the hierarchy is visible (transaction). A sample is shown here:

```

File View Navigate Help
-----
E05: CICS Total Service Time by Txn (0817/CICS23A)          Row 00001 of 00004
Command ==>>> _____ Scroll ==>>> CSR

```

| Name | NTxns | Description | Error | ----- Mean Time in Seconds ----- | | | Service |
|------|-------|-------------|--------|----------------------------------|-----------|---------|---------|
| | | | | Execution | + Suspend | + Delay | |
| DNC1 | 327 | | ± 5.5% | 33.736 | 4.419 | 7.649 | 45.805 |
| FINQ | 295 | | ± 5.8% | 3.649 | 0.000 | 3.379 | 7.029 |

You can enter the “+” line command on a transaction to expand to the next level. A sample of the report with a transaction expanded to the second level of the hierarchy (CICS Program) is shown here:

```

File View Navigate Help
-----
E05: CICS Total Service Time by Txn (0817/CICS23A)          Row 00001 of 000015
Command ==>>> _____ Scroll ==>>> CSR

```

| Name | NTxns | Description | Error | ----- Total Time in Seconds ----- | | | Service |
|------------|-------|-----------------|--------|-----------------------------------|-----------|---------|---------|
| | | | | Execution | + Suspend | + Delay | |
| DNC1 | 327 | | ± 5.5% | 33.736 | 4.419 | 7.649 | 45.805 |
| → PFSAMPC | | EXEC SQL | | 15.298 | 0.000 | 1.569 | 16.868 |
| → DFHD2EX1 | | CICS Program | | 7.159 | 3.709 | 0.869 | 11.738 |
| → PFSAMPB | | EXEC SQL | | 3.559 | 0.000 | 0.949 | 4.509 |
| → CICS | | System Services | | 1.359 | 0.089 | 2.799 | 4.249 |
| → PFSAMPA | | CICS Program | | 1.549 | 0.259 | 0.769 | 2.579 |
| → PFSAMPA | | EXEC SQL | | 1.569 | 0.000 | 0.539 | 2.109 |
| → PFSAMPB | | CICS Program | | 1.319 | 0.179 | 0.079 | 1.579 |
| → PFSAMPC | | CICS Program | | 0.829 | 0.139 | 0.000 | 0.969 |
| → PFSAMPA | | EXEC CICS | | 0.899 | 0.009 | 0.039 | 0.949 |
| → CEECCICS | | EXEC CICS | | 0.149 | 0.019 | 0.029 | 0.199 |
| → PFSAMPB | | EXEC CICS | | 0.039 | 0.009 | 0.000 | 0.049 |

You can enter the “+” line command on a program to expand to the next level. In the sample below, a line with description “EXEC SQL” has been expanded, showing the SQL commands:

```

File View Navigate Help
-----
E05: CICS Total Service Time by Txn (0817/CICS23A)          Row 00001 of 00027
Command ==>>> _____ Scroll ==>>> CSR

```

| Name | NTxns | Description | Error | ----- Total Time in Seconds ----- | | | Service |
|-----------|-------|-------------|--------|-----------------------------------|-----------|---------|---------|
| | | | | Execution | + Suspend | + Delay | |
| DNC1 | 327 | | ± 5.5% | 33.736 | 4.419 | 7.649 | 45.805 |
| → PFSAMPC | | EXEC SQL | | 15.298 | 0.000 | 1.569 | 16.868 |
| → +1BE2 | | FETCH | | 5.809 | 0.000 | 0.579 | 6.389 |
| → +662A | | FETCH | | 2.869 | 0.000 | 0.109 | 2.979 |
| → +0F52 | | SELECT | | 1.469 | 0.000 | 0.239 | 1.709 |
| → +6E9C | | SELECT | | 1.189 | 0.000 | 0.129 | 1.319 |
| → +1164 | | SELECT | | 1.019 | 0.000 | 0.189 | 1.209 |
| → +6C4C | | SELECT | | 0.829 | 0.000 | 0.109 | 0.939 |
| → +6248 | | SELECT | | 0.809 | 0.000 | 0.079 | 0.889 |
| → +1588 | | OPEN | | 0.679 | 0.000 | 0.059 | 0.739 |
| → +64D0 | | OPEN | | 0.389 | 0.000 | 0.029 | 0.419 |
| → +6752 | | CLOSE | | 0.129 | 0.000 | 0.019 | 0.149 |
| → +2348 | | CLOSE | | 0.099 | 0.000 | 0.019 | 0.119 |

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|---|-----------------------------------|
| ? | Transaction, Load Module, CSECT, Command, Seqno, DL/I Request | Display context help information. |
| ++ | Transaction, Load Module, CSECT, Command, Seqno, DL/I Request | Show additional details. |
| + | Transaction, Load Module | Expand to reveal next level. |
| - | Transaction, Load Module | Collapse to hide next level. |
| SV | Transaction, Load Module | Sort next level by value. |
| SN | Transaction, Load Module | Sort next level by name. |
| M | Load Module | Display load module information. |
| P | CICS Active Module, Command, CSECT, Seqno, DL/I Request | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Name | Display context help information. |
| + | Name | Expand to reveal all entries. |
| - | Name | Collapse to show only first level. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here, this one is for a CICS command:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| > +2C70   RETURN           0.126   0.030   0.000   0.156|
+-----+

Calculation Details
CICS Transaction                DNC1
The quantities shown represent the service time for execution of the
indicated CICS command while processing this transaction. The
quantities are total times for all executions of the command within
the transaction and are calculated as follows:

(1) Times command observed in txn/program    26
(2) Duration of one sample interval          0.006003
(3) (1) x (2) = total time for command      0.156078

Command Attributes
CICS Command                     EXEC CICS RETURN
Issued in Load Module             PFSAMPA
Return Offset in Module           +2C90
Name of CSECT                     PFSAMPA
Return Offset in CSECT            +2C70

The command execution measurement counts are
Executing (CPU active)            21
Suspended by CICS                 5
Delayed
  CICS dispatch delay             0
  MVS delay (WAIT)                0
  MVS delay (Busy)                0

```

A sample detail window for an SQL command is shown here:


```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
|  -> +6E9C      SELECT                1.189      0.000      0.129  |
+-----+

Calculation Details
CICS Transaction                DNC1
The quantities shown represent the service time for execution of the
indicated CICS command while processing this transaction. The
quantities are total times for all executions of the command within
the transaction and are calculated as follows:

(1) Times SQL call observed in txn/program  132
(2) Duration of one sample interval         0.009999
(3) (1) x (2) = total time for SQL call    1.319868

SQL Statement Information
DBRM name           PSSAMPC
DBRM token          17652081 1C3E933C
Precmplr stmt#     3179
SQL Call Module    PFSAMPC
SQL Call CSECT     PFSAMPC
SQL Call Offset    00006E9C
SQL Function       SELECT
Subsystem name     DSN1
Connection Type    SASS
Package/Plan:
  Location          CABNETDB24
  Collectn name     PFSAMPC6
  Package ID        PFSAMPC
  Plan name         PFSAMPA

SQL Req Count      105

SQL Statement:     SELECT * INTO : H , : H , : H : H , : H FROM DEPT W
                   HERE XRATE = : H

```

E06 - CICS service time by task ID

Usage

Use this report to see a chronology of occurrences of CICS transactions. Expand a CICS transaction report line to see a separate line for each execution of the transaction. Expand a task number report line to see a further breakdown by program, CICS command, SQL request and DL/I request.

Quantification

Each report line quantifies total times for each measured transaction. The total times are expressed in units of seconds. The total service time is shown and is further broken down into execution time, suspend time, and delay time.

Detail line hierarchy

An unexpanded E06 report shows a line for each measured CICS transaction. You can expand each line to reveal a line for each occurrence of the transaction.

The hierarchy is illustrated here:

- Level 1 CICS Transaction
- Level 2 CICS Transaction Occurrence
- Level 3 CICS Program

```

Level 4 CICS Command
Level 4 CICS Command
...
Level 3 CICS Program
Level 4 SQL Request
Level 4 SQL Request
...
Level 3 CICS Program
Level 4 DLI Request
Level 4 DLI Request
...
Level 3 CICS Program
Level 4 Module
Level 4 Module
Level 4 System Services
...
Level 3 CICS Program
Level 4 Adabas Request
Level 4 Adabas Request
...
Level 3 System Services
Level 4 Module
Level 4 Module
Level 4 System Services
...
Level 2 CICS Transaction Occurrence
...

```

Detail line descriptions

CICS transaction detail line

This is the first-level detail line. Each line shows information about a CICS transaction for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The CICS transaction code. |
| NTxns | The number of executions of the transaction. |
| Description | If this is a recognized CICS transaction, a functional description. |
| Error | The margin of error based on a sample population of the number of executions of the transaction. |
| Execution | The total time, in seconds, that a CPU was actively executing for the transaction. |
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction. |

| Under Heading | This is Displayed |
|---------------|--|
| Delay | <p>The mean time, in seconds, execution of the transaction was delayed. This is a fifth-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i></p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |
| Service | The total service time for the transaction. This includes execution, suspend and delay time. |

CICS transaction number detail line

This detail line shows information about a single execution of the transaction.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The 'Task ID' of the transaction. This is a sequence number assigned to the transaction by CICS. CICS increments this value for each transaction execution. It serves as a unique transaction identifier. |
| Description | The time of day at which the transaction was executed. |
| Execution | The total time, in seconds, CPU execution was observed while the transaction was being processed. |
| Suspend | The total time, in seconds, CICS had suspended execution of the transaction. |

| Under Heading | This is Displayed |
|---------------|--|
| Delay | <p>The mean time, in seconds, execution of the transaction was delayed. This is a fifth-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i></p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |
| Service | The total service time for the transaction. This includes execution, suspend and delay time. |

CICS program or system services detail line

This is a third-level detail line shown directly under the CICS transaction detail line. This line represents a CICS program (usually an application) that was in control during execution of the transaction. The fourth-level lines shown under this item can be either CICS command lines, SQL request lines, DLI request lines or module lines.

If no CICS application program was dispatched, "CICS" is shown under the Name heading and "System Services" under the Description heading.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The module name of the CICS program. If lines grouped under this line are CICS command lines, this field is displayed in red. For Module lines grouped under this line, the field is turquoise. "CICS" is displayed here if no application program was in control. |
| Description | If lines grouped under this line are CICS command lines, this displays "EXEC CICS." If lines grouped under this line are SQL request lines, this displays "EXEC SQL." If lines grouped under this line are DLI request lines, this displays "EXEC DLI." Otherwise, if the program name is a recognized CICS module name (a DFH* name), a functional description is shown, and "CICS Program" is displayed if it is not recognized; indicating this is likely an application program. "System Services" is displayed if no application program was in control. |
| Execution | The total time, in seconds, CPU execution was observed while transaction control was under the CICS program identified in the Name column. |
| Suspend | The total time, in seconds, CICS had suspended execution of the transaction while transaction control was under the CICS program identified in the Name column. |

| Under Heading | This is Displayed |
|---------------|--|
| Delay | <p>The mean time, in seconds, execution of the transaction was delayed. This is a fifth-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i></p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |
| Service | The total service time for the transaction control was under the CICS program identified in the Name column. This includes execution, suspend and delay time. |

CICS command detail line

detail line These lines appear under a CICS Program detail line. Each one represents a CICS command issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC CICS command. This is in +xxxx format. If the CSECT containing the EXEC CICS is not the same name as the module identified in the CICS Program line above, this field contains the CSECT name. In this case, the offset is shown in the description field. This field is always displayed in red. |
| Description | The CICS command descriptor. If, as noted above, the CSECT name containing the EXEC CICS is different from the module name, the CICS command descriptor is preceded by the hexadecimal offset of the command from the start of the CSECT. |
| Execution | The total time, in seconds, CPU execution was observed while the CICS command was being processed. |
| Suspend | The total time, in seconds, CICS had suspended execution of the transaction while the CICS command was being processed. |

| Under Heading | This is Displayed |
|---------------|--|
| Delay | <p>The mean time, in seconds, execution of the transaction was delayed. This is a fifth-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i></p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |
| Service | The total service time for the transaction the CICS command was being processed. This includes execution, suspend and delay time. |

SQL request detail line

These lines appear under a CICS Program detail line. Each one represents an SQL request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC SQL command. This is in +xxxx format. This field is always displayed in red. |
| Description | The SQL request function – SELECT, FETCH, UPDATE, etc. |
| Execution | The total time, in seconds, CPU execution was observed while the SQL request was being processed. |
| Suspend | The total time, in seconds, CICS had suspended execution of the transaction while the SQL request was being processed. |

| Under Heading | This is Displayed |
|---------------|--|
| Delay | <p>The mean time, in seconds, execution of the transaction was delayed. This is a fifth-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i></p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |
| Service | The total service time for the transaction the SQL request was being processed. This includes execution, suspend and delay time. |

DLI request detail line

These lines appear under a CICS Program detail line. Each one represents an IMS DLI request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC DLI command. This is in +xxxx format. This field is always displayed in red. |
| Description | The DLI function code followed by the PCB name. |
| Execution | The total time, in seconds, CPU execution was observed while the DLI request was being processed. |
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction while the DLI request was being processed. |

| Under Heading | This is Displayed |
|---------------|---|
| Delay | <p>The mean time, in seconds, that execution of the transaction was delayed. This is a fifth-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i></p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |
| Service | The total service time for the transaction the DLI request was being processed. This includes execution, suspend and delay time. |

Module/system services detail line

These lines appear under a CICS Program detail line. Each one represents a module that was executing under control of the program identified in the name field of the CICS Program line under which these lines are grouped. If Application Performance Analyzer was unable to determine a module name, "CICS" is displayed in the name field and "System Services" in the description field.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The name of the module that was executing or "CICS" if a module name could not be determined. |
| Description | A functional description of the module if one is available. "System Services" is displayed if the module name could not be determined. |
| Execution | The total time, in seconds, for execution of the module within the grouping under which the detail line appears. |
| Suspend | This field will contain a value of zero. |

| Under Heading | This is Displayed |
|---------------|---|
| Delay | <p>The mean time, in seconds, that execution of the transaction was delayed. This is a fifth-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i></p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |
| Service | The total service time for the transaction the identified module was executing or delayed. |

Adabas request detail line

These lines appear under a CICS Program detail line. Each one represents an Adabas request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC ADABAS command. This is in +xxxx format. This field is always displayed in red. |
| Description | The Adabas request function -- OP, CL, L2, etc. |
| Execution | The total time, in seconds, during which CPU execution was observed while the Adabas request was being processed. |
| Suspend | The total time, in seconds, during which CICS had suspended execution of the transaction while the Adabas request was being processed. |
| Delay | <p>The total time, in seconds, during which execution of the transaction was delayed while the Adabas request was being processed for one of the following reasons:</p> <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The total service time for the transaction during which the Adabas request was being processed. This includes execution, suspend and delay time. |

Sample reports

When the report is first displayed, only the first level of the hierarchy is visible (transaction). A sample is shown here:

```

File View Navigate Help
-----
E06: CICS Service Time by Task Id (0712/CICS23A) Row 00001 of 00003
Command ==> _____ Scroll ==> CSR

Name Count Description Error Execution + Suspend + Delay = Service
-----
CKAM 1 ±99.9% 0.000 141.069 0.000 141.069
DNCI 72 ±11.9% 0.665 63.709 54.076 118.451
FINQ 174 ± 7.6% 1.576 0.035 73.506 75.118

```

By entering “+” on a transaction line, it is expanded into the CICS transaction occurrence detail line:

```

File View Navigate Help
-----
E06: CICS Service Time by Task Id (0712/CICS23A) Row 00001 of 00177
Command ==> _____ Scroll ==> CSR

Name Count Description Error Execution + Suspend + Delay = Service
-----
CKAM 1 ±99.9% 0.000 141.069 0.000 141.069
DNCI 72 ±11.9% 0.665 63.709 54.076 118.451
FINQ 174 ± 7.6% 1.576 0.035 73.506 75.118
→ 01531 16:34:50.97 0.000 0.000 0.361 0.361
→ 01533 16:34:51.87 0.000 0.000 0.513 0.513
→ 01534 16:34:53.55 0.000 0.000 0.303 0.303
→ 01536 16:34:53.99 0.000 0.000 0.490 0.490
→ 01537 16:34:54.92 0.000 0.000 0.256 0.256
→ 01539 16:34:55.30 0.035 0.000 0.490 0.525
→ 01540 16:34:56.39 0.000 0.000 0.482 0.482
→ 01541 16:34:58.06 0.000 0.000 0.397 0.397
→ 01542 16:34:58.60 0.000 0.000 0.408 0.408
→ 01544 16:34:59.08 0.000 0.000 0.432 0.432
→ 01545 16:34:59.99 0.023 0.000 0.280 0.303
→ 01547 16:34:00.48 0.011 0.000 0.361 0.373
→ 01548 16:34:00.92 0.000 0.000 0.443 0.443

```

Line commands

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------------------|-----------------------------------|
| ? | Transaction, Task ID, CICS Program | Display context help information. |
| ++ | Transaction, Task ID, CICS Program | Show additional details. |
| + | Transaction, Task ID, CICS Program | Expand to reveal next level. |
| - | Transaction, Task ID, CICS Program | Collapse to hide next level. |
| SV | Transaction, Task ID, CICS Program | Sort next level by value. |
| SN | Transaction, Task ID, CICS Program | Sort next level by name. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Name | Display context help information. |
| + | Name | Expand to reveal all entries. |
| - | Name | Collapse to show only first level. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|---------------------------|
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| DNC1      342          ± 5.4%  15.547    1.596    3.373    20.518|
+-----+

Calculation Details
CICS Transaction                               DNC1
The quantities shown represent the service time for executions of
this transaction. The service time is the sum of execution time,
suspend time and delay time. The quantities are total times for all
executions of the transaction and are calculated as follows:

(1) Number of times transaction observed      3418
(2) Duration of one sample interval          0.006003
(3) (1) × (2) = total time for transaction   20.518254

The transaction execution measurement counts are
Executing (CPU active)      2590
Suspended by CICS         266
Delayed
  CICS dispatch delay      125
  MVS delay (WAIT)         0
  MVS delay (Busy)         437

Measurement counts for service requests made by this transaction
Program requests           51
Terminal messages          0
Getmain requests          10
Freemain requests          11
File I/O requests          0
File suspends              0
Temporary storage requests 0
Transient data requests    0
Dump system requests       0
Dump transaction requests  0
Journal requests           0

```

E07 - CICS wait by Txn

Usage

Use this report to see where CICS transactions were waiting. Expand a CICS transaction report line to see a further breakdown by resource name.

Quantification

Each report line quantifies accumulated wait as a percentage. Each percentage represents the ratio of wait time observed for the reported item (transaction or

resource), to the total number of wait observations measured in the address space. There can be many wait observations recorded for the same CICS sample.

Detail line hierarchy

An unexpanded E07 report shows a line for each CICS transaction which was observed to be in a wait. You can expand each line to reveal additional hierarchical levels of detail (using the “+” line command).

The hierarchy is illustrated here:

```

Level 1 CICS Transaction
Level 2 Wait Resource
Level 2 CICS Dispatch Delay
Level 2 MVS Delay (Wait)
Level 2 MVS Delay (Busy)

```

...

Detail line descriptions

CICS transaction detail line

This is the first-level detail line. Each line shows information about a CICS transaction which was observed in a wait.

| Under Heading | This is Displayed |
|-------------------|--|
| Name | The CICS transaction code. |
| NTxns/Description | The number of executions of the transaction, and if this is a recognized CICS transaction, a functional description. |
| Percent wait time | The percentage of wait observations for this transaction of the total number of wait observations for the region. |
| Delay | <p>The mean time, in seconds, that execution of the transaction was delayed. This is a second-level detail line shown directly under the CICS transaction detail line. This line represents a CICS resource type or a wait type. The complete list of resource types is documented in the <i>CICS Transaction Server for z/OS Problem Determination Guide</i></p> <p>The most common wait types include:</p> <p>CICS The CICS region was busy processing other transactions and could not dispatch this transaction.</p> <p>MVSWait The entire region was in a wait for an MVS service.</p> <p>MVSBusy The MVS system was busy and did not dispatch the CICS region.</p> <p>CICSSusp The transaction has been suspended by CICS while waiting on a resource.</p> |

Sample reports

A sample report is shown here, the transaction has been expanded to the second level.

```

File View Navigate Help
-----
E07: CICS Wait by Txn (1623/CICS23A) Row 00001 of 00005
Command ==> _____ Scroll ==> CSR

Name  NTxns/Description          Percent of CPU time * 10.00% ±1.5%
      *....1....2....3....4....5....6....7
DNC1   342                    24.80 =====
→ MVSBusy  MVS Delay (Busy)          13.09 =====
→ CICSSusp Suspend                    7.51 ===
→ CICSDisp CICS Dispatch Delay      4.14 ==
→ MVSWait  MVS Delay (Wait)          0.04

```

Line commands

on objects

| Cmd | When Applied To Object | Action |
|-----|---------------------------------|-----------------------------------|
| ? | Transaction, Resource/Wait type | Display context help information. |
| ++ | Transaction, Resource/Wait type | Show additional details. |
| + | Transaction | Expand to reveal next level. |
| - | Transaction | Collapse to hide next level. |
| SV | Transaction | Sort next level by value. |
| SN | Transaction | Sort next level by name. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Name | Display context help information. |
| + | Name | Expand to reveal all entries. |
| - | Name | Collapse to show only first level. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

E08 - CICS mean service time by terminal ID

Usage

Use this report to see an analysis of how time was spent on CICS terminals that were executing during the observation session. Expand a CICS terminal report line to see a further breakdown by transaction, program, CICS command, DLI request and SQL request.

Quantification

Each report line quantifies time as arithmetic means for all measured transactions on the terminal. The means are calculated by dividing the total of all time spent servicing all occurrences of transactions on the terminal by the number of occurrences. The means are expressed in units of seconds. The mean service time is shown and is further broken down into execution time, suspend time, and delay time.

Detail line hierarchy

An unexpanded E08 report shows a line for each measured CICS terminal, and one line for all non-terminal-attached transactions. You can expand each line to reveal additional hierarchical levels of detail.

The hierarchy is illustrated here:

```

Level 1 CICS Terminal
  Level 2 CICS Transaction
    Level 3 CICS Program
      Level 4 CICS Command
      Level 4 CICS Command
    ...
    Level 3 CICS Program
      Level 4 SQL Request
      Level 4 SQL Request
    ...
    Level 3 CICS Program
      Level 4 DLI Request
      Level 4 DLI Request
    ...
    Level 3 CICS Program
      Level 4 Module
      Level 4 Module
      Level 4 System Services
    ...
    Level 3 CICS Program
      Level 4 Adabas Request
      Level 4 Adabas Request
    ...
    Level 3 System Services
      Level 4 Module
      Level 4 Module
      Level 4 System Services
  
```

Detail line descriptions

CICS terminal detail line

This is the first-level detail line. Each line shows information about a CICS terminal for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The CICS terminal ID. This will be the terminal ID or N/A if a terminal ID was not available during the sample. A terminal might not be available because the transaction was running while not attached to the terminal, or the transaction was not attached to the terminal during initialization or termination. |
| NTxns | The number of executions of transactions on this terminal. |
| Description | This will either be terminal transaction or nonterminal transaction. |
| Error | The margin of error for the mean values calculated by using the number of executions of transactions for this terminal as a sample size. |
| Execution | The mean time, in seconds, that a CPU was actively executing transactions on this terminal. |

| Under Heading | This is Displayed |
|---------------|--|
| Suspend | The mean time, in seconds, that CICS had suspended execution of transactions on this terminal. |
| Delay | The mean time, in seconds, execution of the transactions on this terminal was delayed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The mean service time for transactions on this terminal, including execution, suspend, and delay time. |

CICS transaction detail line

This is the second-level detail line. Each line shows information about a CICS transaction for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The CICS transaction code. |
| NTxns | The number of executions of the transaction. |
| Description | A functional description (if the transaction is a recognized CICS transaction). |
| Error | The margin of error for the mean values calculated by using the number of executions of the transaction as the sample size. |
| Execution | The mean time, in seconds, a CPU was actively executing for the transaction. |
| Suspend | The mean time, in seconds, that CICS had suspended execution of the transaction. |
| Delay | The mean time, in seconds, execution of the transaction was delayed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The mean service time for the transaction. This includes execution, suspend and delay time. |

CICS program or system services detail line

This is a third-level detail line shown directly under the CICS transaction detail line. This line represents a CICS program (usually an application) that was in control during execution of the transaction. The fourth-level lines shown under this item can be either CICS command lines, SQL Request lines, DLI Request lines, or Module lines.

If no CICS application program was dispatched, "CICS" is shown under the Name heading and "System Services" under the Description heading.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The module name of the CICS program. If lines grouped under this line are CICS command lines, this field is displayed in red. For Module lines grouped under this line, the field is turquoise. "CICS" is displayed here if no application program was in control. |
| NTxns | The number of executions of the transaction. |
| Description | If lines grouped under this line are CICS command lines, the description displays "EXEC CICS." If lines grouped under this line are SQL request lines, the description displays "EXEC SQL." If lines grouped under this line are DLI request lines, the description displays "EXEC DLI." Otherwise, if the program name is a recognized CICS module name (a DFH* name), a functional description is shown, and "CICS Program" is displayed if the CICS module name is not recognized; indicating this is likely an application program. "System Services" is displayed if no application program was in control. |
| Execution | The mean time, in seconds, that CPU execution was observed while transaction control was under the CICS program identified in the Name column. |
| Suspend | The mean time, in seconds, that CICS had suspended execution of the transaction while transaction control was under the CICS program identified in the Name column. |
| Delay | The mean time, in seconds, that execution of the transaction was delayed while transaction control was under the CICS program identified in the Name column. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The mean service time for the transaction during which control was under the CICS program identified in the Name column. Service time includes execution, suspend, and delay time. |

CICS command detail line

These lines appear under a CICS program detail line. Each one represents a CICS command issued by the program identified in the name field of the CICS program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC CICS command. This hexadecimal offset appears in +xxxx format. If the CSECT containing the EXEC CICS is not the same name as the module identified in the CICS Program line above, this field contains the CSECT name. In this case, the offset is shown in the description field. This field is always displayed in red. |
| Description | The CICS command descriptor. If, as noted above, the CSECT name containing the EXEC CICS is different from the module name, the CICS command descriptor is preceded by the hexadecimal offset of the command from the start of the CSECT. |

| Under Heading | This is Displayed |
|---------------|--|
| Execution | The mean time, in seconds, that CPU execution was observed while the CICS command was being processed. |
| Suspend | The mean time, in seconds, that CICS had suspended execution of the transaction while the CICS command was being processed. |
| Delay | The mean time, in seconds, that execution of the transaction was delayed while the CICS command was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The mean service time for the transaction the CICS command was being processed. This includes execution, suspend, and delay time. |

SQL request detail line

These lines appear under a CICS program detail line. Each line represents an SQL request issued by the program identified in the name field of the CICS program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC SQL command. This is in +xxxx format. This field is always displayed in red. |
| Description | The SQL request function – SELECT, FETCH, UPDATE, etc. |
| Execution | The mean time, in seconds, that CPU execution was observed while the SQL request was being processed. |
| Suspend | The mean time, in seconds, that CICS had suspended execution of the transaction while the SQL request was being processed. |
| Delay | The mean time, in seconds, that execution of the transaction was delayed while the SQL request was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The mean service time for the transaction the SQL request was being processed. This includes execution, suspend and delay time. |

DLI request detail line

These lines appear under a CICS Program detail line. Each line represents an IMS DLI request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC DLI command. This is in +xxxx format. This field is always displayed in red. |
| Description | The DLI function code followed by the PCB name. |

| Under Heading | This is Displayed |
|---------------|---|
| Execution | The mean time, in seconds, that CPU execution was observed while the DLI request was being processed. |
| Suspend | The mean time, in seconds, that CICS had suspended execution of the transaction while the DLI request was being processed. |
| Delay | The mean time, in seconds, that execution of the transaction was delayed while the DLI request was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The mean service time for the transaction the DLI request was being processed. This includes execution, suspend and delay time. |

Module/system services detail line

These lines appear under a CICS Program detail line. Each line represents a module that was executing under control of the program identified in the name field of the CICS Program line under which these lines are grouped. If Application Performance Analyzer was unable to determine a module name, "CICS" is displayed in the name field and "System Services" is displayed in the description field.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The name of the module that was executing or "CICS" if a module name could not be determined. |
| Description | A functional description of the module if one is available. "System Services" is displayed if the module name could not be determined. |
| Execution | The mean time, in seconds, for execution of the module within the grouping under which the detail line appears. |
| Suspend | This field will contain a value of zero. |
| Delay | The mean time, in seconds, that the identified module was preempted by MVS. |
| Service | The mean service time for the transaction the identified module was executing or delayed. |

Adabas request detail line

These lines appear under a CICS Program detail line. Each one represents an Adabas request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC ADABAS command. This is in +xxxx format. This field is always displayed in red. |
| Description | The Adabas request function -- OP, CL, L2, etc. |
| Execution | The mean time, in seconds, during which CPU execution was observed while the Adabas request was being processed. |

| Under Heading | This is Displayed |
|---------------|---|
| Suspend | The mean time, in seconds, during which CICS had suspended execution of the transaction while the Adabas request was being processed. |
| Delay | The mean time, in seconds, during which execution of the transaction was delayed while the Adabas request was being processed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The mean service time for the transaction during which the Adabas request was being processed. This includes execution, suspend and delay time. |

Sample reports

A sample report is shown here, the transaction has been expanded to the second level.

```

File View Navigate Help
-----
E08: CICS Mean Service Time by Termid (2669/CICS23A)          Row 00001 of 00005
Command ==>>> _____ Scroll ==>>> CSR

Name  NTxns  Description          Error  Execution  + Suspend  + Delay  = Service
-----
ET38   342    Terminal Attached   ± 5.4%  0.044      0.008      0.004      0.057
→ DNC1  342    ± 5.4%  0.044      0.008      0.004      0.057
  → DFHD2EX1  CICS Program      0.013      0.003      0.000      0.018
  → PFSAMPA   CICS Program      0.001      0.000      0.000      0.001
  → PFSAMPB   CICS Program      0.000      0.000      0.000      0.001
  → CICS      System Services    0.001      0.000      0.000      0.001
  → PFSAMPC   CICS Program      0.000      0.000      0.000      0.001
  → PFSAMPA   EXEC CICS          0.000      0.000      0.000      0.000
  → CEECCICS  EXEC CICS          0.000      0.000      0.000      0.000
  → PFSAMPB   EXEC CICS          0.000      0.000      0.000      0.000
  → PFSAMPC   EXEC CICS          0.000      0.000      0.000      0.000

ET40   325    Terminal Attached   ± 5.5%  0.042      0.007      0.005      0.056
→ DNC1  325    ± 5.5%  0.042      0.007      0.005      0.056
  → DFHD2EX1  CICS Program      0.012      0.003      0.001      0.016
  → PFSAMPA   CICS Program      0.001      0.000      0.000      0.001
  → PFSAMPB   CICS Program      0.000      0.000      0.000      0.001
  → PFSAMPC   CICS Program      0.000      0.000      0.000      0.001
  → CICS      System Services    0.000      0.000      0.000      0.001
  → PFSAMPA   EXEC CICS          0.000      0.000      0.000      0.000
  → PFSAMPB   EXEC CICS          0.000      0.000      0.000      0.000
  → CEECCICS  EXEC CICS          0.000      0.000      0.000      0.000
  → PFSAMPC   EXEC CICS          0.000      0.000      0.000      0.000

ET33   122    Terminal Attached   ± 9.0%  0.043      0.009      0.005      0.057
→ DNC1  122    ± 9.0%  0.043      0.009      0.005      0.057
  → DFHD2EX1  CICS Program      0.004      0.001      0.000      0.006
  → PFSAMPC   CICS Program      0.000      0.000      0.000      0.000
  → CICS      System Services    0.000      0.000      0.000      0.000
  → PFSAMPA   CICS Program      0.000      0.000      0.000      0.000
  → PFSAMPB   CICS Program      0.000      0.000      0.000      0.000
  → PFSAMPA   EXEC CICS          0.000      0.000      0.000      0.000
  → PFSAMPB   EXEC CICS          0.000      0.000      0.000      0.000
  → CEECCICS  EXEC CICS          0.000      0.000      0.000      0.000

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|--|-----------------------------------|
| ? | Terminal, Transaction, Load Module, CSECT, Command, SQL Request, DLI Request | Display context help information. |
| ++ | Terminal, Transaction, Load Module, CSECT, Command, SQL Request, DLI Request | Show additional details. |
| + | Terminal, Transaction, Load Module | Expand to reveal next level. |
| - | Terminal, Transaction, Load Module | Collapse to hide next level. |
| SV | Terminal, Transaction, Load Module | Sort next level by value. |
| SN | Terminal, Transaction, Load Module | Sort next level by name. |
| M | Load Module | Display load module information. |
| P | Command, CSECT, SQL Request, DLI Request, CICS Active Module | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Name | Display context help information. |
| + | Name | Expand to reveal all entries. |
| - | Name | Collapse to show only first level. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or press the enter key) on any line to open a window containing additional information.

A sample detail window for a CICS command report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
|  → +118E   RETURN TRANSID(DNC1)      0.000   0.000   0.000 |
+-----+

Calculation Details
CICS Transaction
The quantities shown represent the service time for execution
of the indicated CICS command while processing transaction DNC1.
The quantities are mean times for the command for all executions
of the transaction and are calculated as follows:

(1) Times command observed in txn/program      6
(2) Duration of one sample interval            0.009999
(3) (1) × (2) = total time for transaction    0.059994
(4) Number of executions of transaction        327
(5) (3) ÷ (4) = mean time for the command     0.000183

Command Attributes
CICS Command          EXEC CICS RETURN TRANSID(DNC1)
Issued in Load Module PFSAMPA
Return offset in Module +11AE
Name of CSECT         PFSAMPA
Return of Offset in CSECT +118E

The command execution measurement counts are
Executing (CPU active) 5
Suspended by CICS     0
Delayed
  CICS dispatch delay 0
  MVS delay (WAIT)    0
  MVS delay (Busy)    1

```

A sample detail window for an SQL command is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
|  → +85D8   SELECT                               0.001   0.000   0.000 |
+-----+

Calculation Details
The quantities shown represent the service time for execution
of the indicated DB2 SQL call while processing transaction DNC1.
The quantities are mean times for the SQL call for all executions
of the transaction and are calculated as follows:

(1) Times SQL call observed in txn/program      93
(2) Duration of one sample interval             0.006003
(3) (1) x (2) = total time for SQL call         0.558279
(4) Number of executions of transaction         342
(5) (3) ÷ (4) = mean time for the SQL call     0.001632

SQL Statement Information
Subsystem name DSN1          Attach type SASS
Plan name     PFSAMPA       Plan BIND time Nov-28-04 14:11:17

DBRM name     PFSAMPC       DBRM token    17859595 06957A24
DBRM date/time Nov-25-04 14:49:42

Package ID    PFSAMPC       Location      CABNETDB24
Collectn name PFSAMPX1      Pkg BIND time no data

SQL function  SELECT           Static/dynamic Static
Precmplr stmt# 3179          DBRM section# 21
CSECT/module  PFSAMPC in PFSAMPC Offset of call 000085D8
Sample count   93              SQL req count 172
SQL CPU time   0.28           Service time  0.54

SQL Statement  SELECT * INTO : H , : H , : H : H , : H FROM DEPT
              WHERE XRATE = : H

```

E09 - CICS total service time by terminal ID

Usage

Use this report to see an analysis of how time was spent on CICS terminals that were executing during the observation session. Expand a CICS terminal report line to see a further breakdown by transaction, program, CICS command, DLI request, and SQL request.

Quantification

Each report line quantifies total times for transactions measured on a terminal. The total times are expressed in units of seconds. The total service time is shown and is further broken down into execution time, suspend time, and delay time.

Detail line hierarchy

An unexpanded E09 report shows one line for each measured CICS terminal, and one line for all nonterminal attached transactions. You can expand each line to reveal additional hierarchical levels of detail.

The hierarchy is illustrated here:

```

Level 1 CICS Terminal
Level 2 CICS Transaction
Level 3 CICS Program
Level 4 CICS Command
Level 4 CICS Command

...

Level 3 CICS Program
Level 4 SQL Request
Level 4 SQL Request

...

Level 3 CICS Program
Level 4 DLI Request
Level 4 DLI Request

...

Level 3 CICS Program
Level 4 Module
Level 4 Module
Level 4 System Services

...

Level 3 CICS Program
Level 4 Adabas Request
Level 4 Adabas Request

...

Level 3 System Services
Level 4 Module
Level 4 Module
Level 4 System Services

```

Detail line descriptions

CICS terminal detail line

This is the first-level detail line. Each line shows information about a CICS terminal for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The CICS terminal ID. This will be the terminal ID or N/A if a terminal ID was not available during the sample. A terminal might not be available because the transaction was running while not attached to the terminal, or the transaction was not attached to the terminal during initialization or termination. |
| NTxns | The number of executions of transactions on this terminal. |
| Description | This will either be terminal transaction or nonterminal transaction. |
| Error | The margin of error for the mean values calculated by using the number of executions of transactions for this terminal as a sample size. |
| Execution | The total time, in seconds, a CPU was actively executing transactions on this terminal. |
| Suspend | The total time, in seconds, that CICS had suspended execution of transactions on this terminal. |

| Under Heading | This is Displayed |
|---------------|---|
| Delay | The total time, in seconds, execution of the transactions on this terminal was delayed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The mean service time for transactions on this terminal, including execution, suspend, and delay time. |

CICS transaction detail line

This is the first-level detail line. Each line shows information about a CICS transaction for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The CICS transaction code. |
| NTxns | The number of executions of the transaction. |
| Description | A functional description (if the transaction is a recognized CICS transaction). |
| Error | The margin of error based on a sample population of the number of executions of the transaction. |
| Execution | The total time, in seconds, that a CPU was actively executing for the transaction. |
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction. |
| Delay | The total time, in seconds, that execution of the transaction was delayed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The total service time for the transaction. This includes execution, suspend, and delay time. |

CICS program or system services detail line

This is a second-level detail line shown directly under the CICS transaction detail line. This line represents a CICS program (usually an application) that was in control during execution of the transaction. The third-level lines shown under this item can be either CICS command lines, SQL request lines, DLI request lines, or Module lines.

If no CICS application program was dispatched, "CICS" is shown under the Name heading and "System Services" under the Description heading.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The module name of the CICS program. If lines grouped under this line are CICS command lines, this field is displayed in red. For Module lines grouped under this line, the field is turquoise. "CICS" is displayed here if no application program was in control. |
| Description | If lines grouped under this line are CICS command lines, the description displays "EXEC CICS." If lines grouped under this line are SQL request lines, the description displays "EXEC SQL." If lines grouped under this line are DLI request lines, the description displays "EXEC DLI." Otherwise, if the program name is a recognized CICS module name (a DFH* name), a functional description is shown, and "CICS Program" is displayed if the CICS module name is not recognized; indicating this is likely an application program. "System Services" is displayed if no application program was in control. |
| Execution | The total time, in seconds, that CPU execution was observed while transaction control was under the CICS program identified in the Name column. |
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction while transaction control was under the CICS program identified in the Name column. |
| Delay | The total time, in seconds, that execution of the transaction was delayed while transaction control was under the CICS program identified in the Name column. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The total service time for the transaction during which control was under the CICS program identified in the Name column. Service time includes execution, suspend, and delay time. |

CICS command detail line

These lines appear under a CICS Program detail line. Each one represents a CICS command issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC CICS command. This hexadecimal offset appears in +xxxx format. If the CSECT containing the EXEC CICS is not the same name as the module identified in the CICS Program line above, this field contains the CSECT name. In this case, the offset is shown in the description field. This field is always displayed in red. |
| Description | The CICS command descriptor. If, as noted above, the CSECT name containing the EXEC CICS is different from the module name, the CICS command descriptor is preceded by the hexadecimal offset of the command from the start of the CSECT. |
| Execution | The total time, in seconds, that CPU execution was observed while the CICS command was being processed. |

| Under Heading | This is Displayed |
|---------------|---|
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction while the CICS command was being processed. |
| Delay | The total time, in seconds, that execution of the transaction was delayed while the CICS command was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The total service time for the transaction during which the CICS command was being processed. This includes execution, suspend, and delay time. |

SQL request detail line

These lines appear under a CICS program detail line. Each line represents an SQL request issued by the program identified in the name field of the CICS program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC SQL command. This is in +xxxx format. This field is always displayed in red. |
| Description | The SQL request function – SELECT, FETCH, UPDATE, etc. |
| Execution | The total time, in seconds, that CPU execution was observed while the SQL request was being processed. |
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction while the SQL request was being processed. |
| Delay | The total time, in seconds, that execution of the transaction was delayed while the SQL request was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The total service time for the transaction the SQL request was being processed. This includes execution, suspend and delay time. |

DLI request detail line

These lines appear under a CICS Program detail line. Each line represents an IMS DLI request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC DLI command. This is in +xxxx format. This field is always displayed in red. |
| Description | The DLI function code followed by the PCB name. |
| Execution | The total time, in seconds, that CPU execution was observed while the DLI request was being processed. |

| Under Heading | This is Displayed |
|---------------|--|
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction while the DLI request was being processed. |
| Delay | The total time, in seconds, that execution of the transaction was delayed while the DLI request was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The total service time for the transaction during which the DLI request was being processed. This includes execution, suspend, and delay time. |

Module/system services detail line

These lines appear under a CICS Program detail line. Each line represents a module that was executing under control of the program identified in the name field of the CICS Program line under which these lines are grouped. If Application Performance Analyzer was unable to determine a module name, "CICS" is displayed in the name field and "System Services" is displayed in the description field.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The name of the module that was executing or "CICS" if a module name could not be determined. |
| Description | A functional description of the module if one is available. "System Services" is displayed if the module name could not be determined. |
| Execution | The total time, in seconds, for execution of the module within the grouping under which the detail line appears. |
| Suspend | This field will contain a value of zero. |
| Delay | The total time, in seconds, that the identified module was preempted by MVS. |
| Service | The total service time for the transaction the during which the identified module was executing or delayed. |

Adabas request detail line

These lines appear under a CICS Program detail line. Each one represents an Adabas request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC ADABAS command. This is in +xxxx format. This field is always displayed in red. |
| Description | The Adabas request function -- OP, CL, L2, etc. |
| Execution | The total time, in seconds, during which CPU execution was observed while the Adabas request was being processed. |
| Suspend | The total time, in seconds, during which CICS had suspended execution of the transaction while the Adabas request was being processed. |

| Under Heading | This is Displayed |
|---------------|--|
| Delay | The total time, in seconds, during which execution of the transaction was delayed while the Adabas request was being processed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The total service time for the transaction during which the Adabas request was being processed. This includes execution, suspend and delay time. |

Sample reports

A sample report is shown here, the transaction has been expanded to the second level.

```

File View Navigate Help
-----
E09: CICS Total Service Time by Termid (2669/CICS23A)          Row 00001 of 00036
Command ==>>> _____ Scroll ==>>> CSR

Name  NTxns Description          Error  Execution  + Suspend  + Delay  = Service
-----
ET38   342 Terminal Attached  ± 5.4%  15.207    2.795    1.637    19.640
→ DNC1  342                ± 5.4%  15.207    2.795    1.637    19.640
  → DFHD2EX1 CICS Program          10.912    2.597    0.755    14.265
  → PFSAMPA  CICS Program          1.085     0.053    0.215    1.355
  → PFSAMPB  CICS Program          0.743     0.071    0.221    1.037
  → CICS     System Services       0.851     0.011    0.077    0.941
  → PFSAMPC  CICS Program          0.545     0.059    0.305    0.911
  → PFSAMPA  EXEC CICS             0.641     0.000    0.041    0.683
  → CEECCICS EXEC CICS             0.179     0.000    0.017    0.197
  → PFSAMPB  EXEC CICS             0.179     0.000    0.000    0.179
  → PFSAMPC  EXEC CICS             0.065     0.000    0.000    0.065

ET40   325 Terminal Attached  ± 5.5%  13.893    2.555    1.775    18.224
→ DNC1  325                ± 5.5%  13.893    2.555    1.775    18.224
  → DFHD2EX1 CICS Program          10.120    2.417    0.803    13.341
  → PFSAMPA  CICS Program          0.791     0.017    0.257    1.067
  → PFSAMPB  CICS Program          0.737     0.017    0.215    0.971
  → PFSAMPC  CICS Program          0.557     0.041    0.317    0.917
  → CICS     System Services       0.689     0.059    0.089    0.839
  → PFSAMPA  EXEC CICS             0.653     0.000    0.065    0.719
  → PFSAMPB  EXEC CICS             0.161     0.000    0.011    0.173
  → CEECCICS EXEC CICS             0.149     0.000    0.005    0.155
  → PFSAMPC  EXEC CICS             0.029     0.000    0.005    0.035

ET33   122 Terminal Attached  ± 9.0%   5.261    1.109    0.629    7.000
→ DNC1  122                ± 9.0%   5.261    1.109    0.629    7.000
  → DFHD2EX1 CICS Program          3.647    1.043    0.293    4.985
  → PFSAMPC  CICS Program          0.251    0.035    0.143    0.431
  → CICS     System Services       0.311    0.011    0.077    0.401
  → PFSAMPA  CICS Program          0.311    0.011    0.047    0.371
  → PFSAMPB  CICS Program          0.281    0.005    0.047    0.335
  → PFSAMPA  EXEC CICS             0.287    0.000    0.005    0.293
  → PFSAMPB  EXEC CICS             0.101    0.000    0.005    0.107
  → CEECCICS EXEC CICS             0.041    0.000    0.005    0.047

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|--|-----------------------------------|
| ? | Transaction, Load Module, CSECT, Command, SQL Request, DLI Request | Display context help information. |
| ++ | Transaction, Load Module, CSECT, Command, SQL Request, DLI Request | Show additional details. |
| + | Transaction, Load Module | Expand to reveal next level. |
| - | Transaction, Load Module | Collapse to hide next level. |
| SV | Transaction, Load Module | Sort next level by value. |
| SN | Transaction, Load Module | Sort next level by name. |
| M | Load Module | Display load module information. |
| P | Command, CSECT, SQL Request, DLI Request, CICS Active Module | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Name | Display context help information. |
| + | Name | Expand to reveal all entries. |
| - | Name | Collapse to show only first level. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or press the enter key) on any line to open a window containing additional information.

A sample detail window for a CICS command report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
|  → +118E   RETURN TRANSID(DNC1)      0.049   0.000   0.009 |
+-----+

Calculation Details
CICS Transaction          DNC1
The quantities shown represent the service time for execution of the
indicated CICS command while processing this transaction. The
quantities are total times for all executions of the command within
the transaction and are calculated as follows:

(1) Times command observed in txn/program      6
(2) Duration of one sample interval           0.009999
(3) (1) × (2) = total time for transaction     0.059994

Command Attributes
CICS Command          EXEC CICS RETURN TRANSID(DNC1)
Issued in Load Module PFSAMPA
Return offset in Module +11AE
Name of CSECT         PFSAMPA
Return of Offset in CSECT +118E

The command execution measurement counts are
Executing (CPU active) 5
Suspended by CICS     0
Delayed
  CICS dispatch delay 0
  MVS delay (WAIT)    0
  MVS delay (Busy)    1

```

A sample detail window for an SQL command is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
|  → +6E9c  SELECT                               1.189   0.000   0.129  |
+-----+

Calculation Details
CICS Transaction          DNC1
The quantities shown represent the service time for execution of the
indicated DB2 SQL call while processing this transaction. The
quantities are total times for all executions of the command within
the transaction and are calculated as follows:

(1) Times SQL call observed in txn/program    132
(2) Duration of one sample interval          0.009999
(3) (1) x (2) = total time for SQL call      1.319868

SQL Statement Information
DBRM name          PFSAMPC
DBRM Token         17652081 1C3E933C
Precmplr stmt#    3179
SQL Call Module   PFSAMPC
SQL Call CSECT    PFSAMPC
SQL Call Offset   00006E9C
SQL Function      SELECT
Subsystem name    DSN1
Connection Type   SASS
Package/Plan:
  Location        CABNETDB21
  Collectn Name   PFSAMPC6
  Package ID      PFSAMPC
  Plan Name       PFSAMPA

SQL Req Count:    105

SQL Statement:    SELECT * INTO : H , : H , : H : H , : H FROM DEPT
                  WHERE XRATE = : H

```

E10 - CICS mean service time by user ID

Usage

Use this report to see an analysis of how time was spent by CICS users that were executing during the observation session. Expand a CICS user ID report line to see a further breakdown by transaction, program, CICS command, DLI request and SQL request.

Quantification

Each report line quantifies time as arithmetic means for all measured transactions initiated by the user. The means are calculated by dividing the total of all time spent servicing all occurrences of transactions initiated by the user, by the number of occurrences. The means are expressed in units of seconds. The mean service time is shown and is further broken down into execution time, suspend time, and delay time.

Detail line hierarchy

An unexpanded E10 report shows one line for each measured CICS user. You can expand each line to reveal additional hierarchical levels of detail.

The hierarchy is illustrated here:

```

Level 1 CICS User ID
  Level 2 CICS Transaction
    Level 3 CICS Program
      Level 4 CICS Command
      Level 4 CICS Command

    ...
    Level 3 CICS Program
      Level 4 SQL Request
      Level 4 SQL Request

    ...
    Level 3 CICS Program
      Level 4 DLI Request
      Level 4 DLI Request

    ...
    Level 3 CICS Program
      Level 4 Module
      Level 4 Module
      Level 4 System Services

    ...
    Level 3 CICS Program
      Level 4 Adabas Request
      Level 4 Adabas Request

    ...
    Level 3 System Services
      Level 4 Module
      Level 4 Module
      Level 4 System Services
  
```

Detail line descriptions

CICS user detail line

This is the first-level detail line. Each line shows information about a CICS terminal for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The CICS user ID. |
| NTxns | The number of executions of transactions initiated by this user. |
| Description | |
| Error | The margin of error for the mean values calculated by using the number of executions of transactions by this user as a sample size. |
| Execution | The mean time, in seconds, during which a CPU was actively executing transactions initiated by this user. |
| Suspend | The mean time, in seconds, during which CICS had suspended execution of transactions initiated by this user. |
| Delay | <p>The mean time, in seconds, during which execution of the transactions initiated by this user was delayed.</p> <p>Transaction execution can be delayed for one of the following reasons:</p> <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |

| Under Heading | This is Displayed |
|---------------|---|
| Service | The mean service time for transactions initiated by this user. This includes execution, suspend and delay time. |

CICS transaction detail line

This is the second-level detail line. Each line shows information about a CICS transaction for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The CICS transaction code. |
| NTxns | The number of executions of the transaction. |
| Description | If this is a recognized CICS transaction, a functional description. |
| Error | The margin of error for the mean values calculated by using the number of executions of the transaction as the sample size. |
| Execution | The mean time, in seconds, during which a CPU was actively executing for the transaction. |
| Suspend | The mean time, in seconds, during which CICS had suspended execution of the transaction. |
| Delay | The mean time, in seconds, during which execution of the transaction was delayed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The mean service time for the transaction. This includes execution, suspend and delay time. |

CICS program or system services detail line

This is a third-level detail line shown directly under the CICS transaction detail line. This line represents a CICS program (usually an application) that was in control during execution of the transaction. The third-level lines shown under this item can be either CICS command lines, SQL request lines, DLI request lines, or Module lines.

If no CICS application program was dispatched, "CICS" is shown under the Name heading and "System Services" under the Description heading.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The module name of the CICS program. If lines grouped under this line are CICS command lines, this field is displayed in red. For Module lines grouped under this line, the field is turquoise. "CICS" is displayed here if no application program was in control. |

| Under Heading | This is Displayed |
|---------------|--|
| Description | If lines grouped under this line are CICS command lines, the description displays "EXEC CICS." If lines grouped under this line are SQL request lines, the description displays "EXEC SQL." If lines grouped under this line are DLI request lines, the description displays "EXEC DLI." Otherwise, if the program name is a recognized CICS module name (a DFH* name), a functional description is shown, and "CICS Program" is displayed if the CICS module name is not recognized; indicating this is likely an application program. "System Services" is displayed if no application program was in control. |
| Execution | The mean time, in seconds, during which CPU execution was observed while transaction control was under the CICS program identified in the Name column. |
| Suspend | The mean time, in seconds, during which CICS had suspended execution of the transaction while transaction control was under the CICS program identified in the Name column. |
| Delay | The mean time, in seconds, during which execution of the transaction was delayed while transaction control was under the CICS program identified in the Name column. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The mean service time for the transaction during which control was under the CICS program identified in the Name column. Service time includes execution, suspend and delay time. |

CICS command detail line

These lines appear under a CICS Program detail line. Each one represents a CICS command issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC CICS command. This hexadecimal offset appears in +xxxx format. If the CSECT containing the EXEC CICS is not the same name as the module identified in the CICS Program line above, this field contains the CSECT name. In this case, the offset is shown in the description field. This field is always displayed in red. |
| Description | The CICS command descriptor. If, as noted above, the CSECT name containing the EXEC CICS is different from the module name, the CICS command descriptor is preceded by the hexadecimal offset of the command from the start of the CSECT. |
| Execution | The mean time, in seconds, during which CPU execution was observed while the CICS command was being processed. |
| Suspend | The mean time, in seconds, during which CICS had suspended execution of the transaction while the CICS command was being processed. |

| Under Heading | This is Displayed |
|---------------|--|
| Delay | The mean time, in seconds, during which execution of the transaction was delayed while the CICS command was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The mean service time for the transaction during which the CICS command was being processed. This includes execution, suspend, and delay time. |

SQL request detail line

These lines appear under a CICS program detail line. Each line represents an SQL request issued by the program identified in the name field of the CICS program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC SQL command. This is in +xxxx format. This field is always displayed in red. |
| Description | The SQL request function – SELECT, FETCH, UPDATE, etc. |
| Execution | The mean time, in seconds, during which CPU execution was observed while the SQL request was being processed. |
| Suspend | The mean time, in seconds, during which CICS had suspended execution of the transaction while the SQL request was being processed. |
| Delay | The mean time, in seconds, during which execution of the transaction was delayed while the SQL request was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The mean service time for the transaction during which the SQL request was being processed. This includes execution, suspend and delay time. |

DLI request detail line

These lines appear under a CICS Program detail line. Each line represents an IMS DLI request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC DLI command. This is in +xxxx format. This field is always displayed in red. |
| Description | The DLI function code followed by the PCB name. |
| Execution | The mean time, in seconds, during which CPU execution was observed while the DLI request was being processed. |

| Under Heading | This is Displayed |
|---------------|---|
| Suspend | The mean time, in seconds, during which CICS had suspended execution of the transaction while the DLI request was being processed. |
| Delay | The mean time, in seconds, during which execution of the transaction was delayed while the DLI request was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The mean service time for the transaction during which the DLI request was being processed. This includes execution, suspend, and delay time. |

Module/system services detail line

These lines appear under a CICS Program detail line. Each line represents a module that was executing under control of the program identified in the name field of the CICS Program line under which these lines are grouped. If Application Performance Analyzer was unable to determine a module name, "CICS" is displayed in the name field and "System Services" is displayed in the description field.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The name of the module that was executing or "CICS" if a module name could not be determined. |
| Description | A functional description of the module if one is available. "System Services" is displayed if the module name could not be determined. |
| Execution | The mean time, in seconds, for execution of the module within the grouping under which the detail line appears. |
| Suspend | This field will contain a value of zero. |
| Delay | The mean time, in seconds, that the identified module was preempted by MVS. |
| Service | The mean service time for the transaction during which the identified module was executing or delayed. |

Adabas request detail line

These lines appear under a CICS Program detail line. Each one represents an Adabas request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC ADABAS command. This is in +xxxx format. This field is always displayed in red. |
| Description | The Adabas request function -- OP, CL, L2, etc. |
| Execution | The mean time, in seconds, during which CPU execution was observed while the Adabas request was being processed. |

| Under Heading | This is Displayed |
|---------------|---|
| Suspend | The mean time, in seconds, during which CICS had suspended execution of the transaction while the Adabas request was being processed. |
| Delay | The mean time, in seconds, during which execution of the transaction was delayed while the Adabas request was being processed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The mean service time for the transaction during which the Adabas request was being processed. This includes execution, suspend and delay time. |

Sample reports

A sample report is shown here, the transaction has been expanded to the second level.

```

File View Navigate Help
-----
E10: CICS Mean Service Time by Userid (1873/CICS32A)          Row 00001 of 00032
Command ==>>> _____ Scroll ==>>> CSR

Name  NTxns  Description          Error  Execution  + Suspend + Delay = Service
-----
AHM01    0
-> MQS1    0          ±99.9%  16.731    4.407  28.184  49.323
   -> MQSAMP1  CICS Program      12.848    0.089    0.944   13.882
   -> CEECCICS EXEC CICS          1.888    0.119    0.479    2.488
   -> CEEPLPKA EXEC CICS          0.000    0.000    0.659    0.659
   -> CICS      System Services   0.104    0.089    0.239    0.434
   -> DFHTFP   CICS Program      0.059    0.000    0.000    0.059
   -> MQSAMP1  EXEC CICS          0.014    0.000    0.014    0.029

-> MQDR    0          ±99.9%  0.359    0.404  15.966  16.731
   -> CSQ4CVK1 CICS Program      0.239    0.254  15.696  16.191
   -> MQDRVR   EXEC CICS          0.089    0.044    0.224    0.359
   -> MQDRVR   CICS Program      0.014    0.104    0.044    0.164
   -> CICS      System Services   0.014    0.000    0.000    0.014

-> TDB2    0          ±99.9%  1.379    3.463  8.305  13.147
   -> CICS      System Services   0.329    2.413  6.506  9.250
   -> CICSDB3  CICS Program      0.989    0.899    1.769    3.658
   -> CEECCICS EXEC CICS          0.014    0.149    0.014    0.179
   -> CICSDB3  EXEC CICS          0.044    0.000    0.014    0.059

-> DBDR    0          ±99.9%  0.074    0.239  1.574  1.888
   -> DB2DRVR  EXEC CICS          0.074    0.239  1.574  1.888

AGM02    0          ±99.9%  0.000    29.984  0.000  29.984
-> CKAM    0          ±99.9%  0.000    29.984  0.000  29.984
   -> DFHMOMON EXEC CICS          0.000    29.984  0.000  29.984

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|---|-----------------------------------|
| ? | User ID, Transaction, Load Module, CSECT, Command, SQL Request, DLI Request | Display context help information. |
| ++ | User ID, Transaction, Load Module, CSECT, Command, SQL Request, DLI Request | Show additional details. |
| + | User ID, Transaction, Load Module | Expand to reveal next level. |
| - | User ID, Transaction, Load Module | Collapse to hide next level. |
| SV | User ID, Transaction, Load Module | Sort next level by value. |
| SN | User ID, Transaction, Load Module | Sort next level by name. |
| M | Load Module | Display load module information. |
| P | Command, CSECT, SQL Request, DLI Request, CICS Active Module | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Name | Display context help information. |
| + | Name | Expand to reveal all entries. |
| - | Name | Collapse to show only first level. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or press the enter key) on any line to open a window containing additional information.

A sample detail window for a CICS command report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
|  → +06B8   PROGRAM(CSQ4CVK1)      0.014  0.044  0.104  0.164  |
+-----+

Calculation Details
CICS Transaction                MQDR
The quantities shown represent the service time for execution of the
indicated CICS command while processing this transaction. The
quantities are mean times for the command for all executions of the
transaction and are calculated as follows:

(1) Times command observed in txn/program      11
(2) Duration of one sample interval            0.014992
(3) (1) × (2) = total time for command         0.164912
(4) Number of executions of transaction        0
(5) (3) / (4) = mean time for the command     252.263688

Command Attributes
CICS Command                      EXEC CICS LINK PROGRAM(CSQ4CVK1)
Issued in Load Module              MQDRVR
Return offset in Module            +06D8
Name of CSECT                     MQDRVR
Return Offset in CSECT             +06B8

The command execution measurement counts are
Executing (CPU active)             1
Suspended by CICS                 3
Delayed
  CICS dispatch delay              0
  MVS delay (WAIT)                 0
  MVS delay (Busy)                 7

```

E11 - CICS total service time by user ID

Usage

Use this report to see an analysis of how time was spent by CICS users that were measured during the observation session. Expand a CICS user ID report line to see a further breakdown by transaction, program, CICS command, DLI request and SQL request.

Quantification

Each report line quantifies total times for transactions measured for a CICS user. The total times are expressed in units of seconds. The total service time is shown and is further broken down into execution time, suspend time, and delay time.

Detail line hierarchy

An unexpanded E11 report shows one line for each measured CICS user ID. You can expand each line to reveal additional hierarchical levels of detail.

The hierarchy is illustrated here:

- Level 1 CICS User ID
- Level 2 CICS Transaction
- Level 3 CICS Program
- Level 4 CICS Command
- Level 4 CICS Command

...

```

Level 3 CICS Program
Level 4 SQL Request
Level 4 SQL Request

...
Level 3 CICS Program
Level 4 DLI Request
Level 4 DLI Request

...
Level 3 CICS Program
Level 4 Module
Level 4 Module
Level 4 System Services

...
Level 3 CICS Program
Level 4 Adabas Request
Level 4 Adabas Request

...
Level 3 System Services
Level 4 Module
Level 4 Module
Level 4 System Services

```

Detail line descriptions

CICS terminal detail line

This is the first-level detail line. Each line shows information about a CICS user for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The CICS user ID. |
| NTxns | The number of executions of transactions initiated by this user. |
| Description | This is either Terminal Txn or Non-Terminal Txn. |
| Error | The margin of error for the mean values calculated by using the number of executions of transactions by this user as a sample size. |
| Execution | The total time, in seconds, during which a CPU was actively executing transactions initiated by this user. |
| Suspend | The total time, in seconds, during which CICS had suspended execution of transactions initiated by this user. |
| Delay | <p>The total time, in seconds, during which execution of the transactions initiated by this user was delayed.</p> <p>Transaction execution can be delayed for one of the following reasons:</p> <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The total service time for transactions initiated by this user. This includes execution, suspend and delay time. |

CICS transaction detail line

This is the second-level detail line. Each line shows information about a CICS transaction for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The CICS transaction code. |
| NTxns | The number of executions of the transaction. |
| Description | If this is a recognized CICS transaction, a functional description. |
| Error | The margin of error based on a sample population of the number of executions of the transaction. |
| Execution | The total time, in seconds, during which a CPU was actively executing for the transaction. |
| Suspend | The total time, in seconds, during which CICS had suspended execution of the transaction. |
| Delay | The total time, in seconds, during which execution of the transaction was delayed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The total service time for the transaction. This includes execution, suspend and delay time. |

CICS program or system services detail line

This is a second-level detail line shown directly under the CICS transaction detail line. This line represents a CICS program (usually an application) that was in control during execution of the transaction. The third-level lines shown under this item can be either CICS command lines, SQL request lines, DLI request lines, or Module lines.

If no CICS application program was dispatched, "CICS" is shown under the Name heading and "System Services" under the Description heading.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The module name of the CICS program. If lines grouped under this line are CICS command lines, this field is displayed in red. For Module lines grouped under this line, the field is turquoise. "CICS" is displayed here if no application program was in control. |
| Description | If lines grouped under this line are CICS command lines, the description displays "EXEC CICS." If lines grouped under this line are SQL request lines, the description displays "EXEC SQL." If lines grouped under this line are DLI request lines, the description displays "EXEC DLI." Otherwise, if the program name is a recognized CICS module name (a DFH* name), a functional description is shown, and "CICS Program" is displayed if the CICS module name is not recognized; indicating this is likely an application program. "System Services" is displayed if no application program was in control. |
| Execution | The total time, in seconds, during which CPU execution was observed while transaction control was under the CICS program identified in the Name column. |

| Under Heading | This is Displayed |
|---------------|--|
| Suspend | The total time, in seconds, during which CICS had suspended execution of the transaction while transaction control was under the CICS program identified in the Name column. |
| Delay | <p>The total time, in seconds, during which execution of the transaction was delayed while transaction control was under the CICS program identified in the Name column.</p> <p>Transaction execution can be delayed for one of the following reasons:</p> <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The total service time for the transaction during which control was under the CICS program identified in the Name column. Service time includes execution, suspend and delay time. |

CICS command detail line

These lines appear under a CICS Program detail line. Each one represents a CICS command issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC CICS command. This hexadecimal offset appears in +xxxx format. If the CSECT containing the EXEC CICS is not the same name as the module identified in the CICS Program line above, this field contains the CSECT name. In this case, the offset is shown in the description field. This field is always displayed in red. |
| Description | The CICS command descriptor. If, as noted above, the CSECT name containing the EXEC CICS is different from the module name, the CICS command description is preceded by the hexadecimal offset of the command from the start of the CSECT. |
| Execution | The total time, in seconds, during which CPU execution was observed while the CICS command was being processed. |
| Suspend | The total time, in seconds, during which CICS had suspended execution of the transaction while the CICS command was being processed. |
| Delay | <p>The total time, in seconds, during which execution of the transaction was delayed while the CICS command was being processed.</p> <p>Transaction execution can be delayed for one of the following reasons:</p> <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The total service time for the transaction during which the CICS command was being processed. This includes execution, suspend, and delay time. |

SQL request detail line

These lines appear under a CICS program detail line. Each line represents an SQL request issued by the program identified in the name field of the CICS program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC SQL command. This is in +xxxx format. This field is always displayed in red. |
| Description | The SQL request function – SELECT, FETCH, UPDATE, etc. |
| Execution | The total time, in seconds, during which CPU execution was observed while the SQL request was being processed. |
| Suspend | The total time, in seconds, during which CICS had suspended execution of the transaction while the SQL request was being processed. |
| Delay | The total time, in seconds, during which execution of the transaction was delayed while the SQL request was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none">• CICS dispatch delay• MVS dispatch delay |
| Service | The total service time for the transaction during which the SQL request was being processed. This includes execution, suspend and delay time. |

DLI request detail line

These lines appear under a CICS Program detail line. Each line represents an IMS DLI request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC DLI command. This is in +xxxx format. This field is always displayed in red. |
| Description | The DLI function code followed by the PCB name. |
| Execution | The total time, in seconds, during which CPU execution was observed while the DLI request was being processed. |
| Suspend | The total time, in seconds, during which CICS had suspended execution of the transaction while the DLI request was being processed. |
| Delay | The total time, in seconds, during which execution of the transaction was delayed while the DLI request was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none">• CICS dispatch delay• MVS dispatch delay |
| Service | The total service time for the transaction during which the DLI request was being processed. This includes execution, suspend, and delay time. |

Module/system services detail line

These lines appear under a CICS Program detail line. Each line represents a module that was executing under control of the program identified in the name field of the CICS Program line under which these lines are grouped. If Application Performance Analyzer was unable to determine a module name, "CICS" is displayed in the name field and "System Services" is displayed in the description field.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The name of the module that was executing or "CICS" if a module name could not be determined. |
| Description | A functional description of the module if one is available. "System Services" is displayed if the module name could not be determined. |
| Execution | The total time, in seconds, for execution of the module within the grouping under which the detail line appears. |
| Suspend | This field will contain a value of zero. |
| Delay | The total time, in seconds, that the identified module was preempted by MVS. |
| Service | The total service time for the transaction during which the identified module was executing or delayed. |

Adabas request detail line

These lines appear under a CICS Program detail line. Each one represents an Adabas request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC ADABAS command. This is in +xxxx format. This field is always displayed in red. |
| Description | The Adabas request function -- OP, CL, L2, etc. |
| Execution | The total time, in seconds, during which CPU execution was observed while the Adabas request was being processed. |
| Suspend | The total time, in seconds, during which CICS had suspended execution of the transaction while the Adabas request was being processed. |
| Delay | The total time, in seconds, during which execution of the transaction was delayed while the Adabas request was being processed for one of the following reasons: <ul style="list-style-type: none">• CICS dispatch delay• MVS dispatch delay |
| Service | The total service time for the transaction during which the Adabas request was being processed. This includes execution, suspend and delay time. |

Sample reports

A sample report is shown here. The transaction has been expanded to the second level.

```

File View Navigate Help
-----
E11: CICS Total Service Time by Userid (1873/CICS32A)          Row 00001 of 00032
Command ==>> _____ Scroll ==>> CSR
-----
Name  NTxns  Description          Error  Execution  + Suspend + Delay = Service
-----
AHM01    0          ±99.9%  16.731    4.407  28.184  49.323
→ MQS1    0          ±99.9%  14.917    0.299  2.338  17.555
  → MQSAMP1 CICS Program      12.848    0.089  0.944  13.882
  → CEECCICS EXEC CICS          1.888    0.119  0.479  2.488
  → CEEPLPKA EXEC CICS          0.000    0.000  0.659  0.659
  → CICS     System Services  0.104    0.089  0.239  0.434
  → DFHTFP  CICS Program      0.059    0.000  0.000  0.059
  → MQSAMP1 EXEC CICS          0.014    0.000  0.014  0.029

→ MQDR    0          ±99.9%  0.359    0.404  15.966  16.731
  → CSQ4CVK1 CICS Program      0.239    0.254  15.696  16.191
  → MQDRVR  EXEC CICS          0.089    0.044  0.224  0.359
  → MQDRVR  CICS Program      0.014    0.104  0.044  0.164
  → CICS     System Services  0.014    0.000  0.000  0.014

→ TDB2    0          ±99.9%  1.379    3.463  8.305  13.147
  → CICS     System Services  0.329    2.413  6.506  9.250
  → CICSDB3 CICS Program      0.989    0.899  1.769  3.658
  → CEECCICS EXEC CICS          0.014    0.149  0.014  0.179
  → CICSDB3 EXEC CICS          0.044    0.000  0.014  0.059

→ DBDR    0          ±99.9%  0.074    0.239  1.574  1.888
  → DB2DRVR EXEC CICS          0.074    0.239  1.574  1.888

AGM02    0          ±99.9%  0.000    29.984  0.000  29.984
→ CKAM    0          ±99.9%  0.000    29.984  0.000  29.984
  → DFHMOMON EXEC CICS          0.000    29.984  0.000  29.984

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|--|-----------------------------------|
| ? | User ID, Load Module, CSECT, Command, SQL Request, DLI Request | Display context help information. |
| ++ | User ID, Load Module, CSECT, Command, SQL Request, DLI Request | Show additional details. |
| + | User ID, Load Module | Expand to reveal next level. |
| - | User ID, Load Module | Collapse to hide next level. |
| SV | User ID, Load Module | Sort next level by value. |
| SN | User ID, Load Module | Sort next level by name. |
| M | Load Module | Display load module information. |
| P | Command, CSECT, SQL Request, DLI Request, CICS Active Module | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Name | Display context help information. |
| + | Name | Expand to reveal all entries. |
| - | Name | Collapse to show only first level. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or press the enter key) on any line to open a window containing additional information.

A sample detail window for a CICS command report is shown here:

```
File View Navigate Help
+-----+
+----- The following report line was selected -----+
|  → +0750  START TRANSID(MQS1)      0.014  0.000  0.000  0.014  |
+-----+

Calculation Details
CICS Transaction              MQDR
The quantities shown represent the service time for execution of the
indicated CICS command while processing this transaction. The
quantities are total times for all executions of the command within
the transaction and are calculated as follows:

(1) Times command observed in txn/program      1
(2) Duration of one sample interval            0.014992
(3) (1) × (2) = total time for command        0.014992

Command Attributes
CICS Command                  EXEC  CICS START TRANSID(MQS1)
Issued in Load Module         MQDRVR
Return offset in Module       +0770
Name of CSECT                 MQDRVR
Return Offset in CSECT        +0750

The command execution measurement counts are
Executing (CPU active)        1
Suspended by CICS            0
Delayed
  CICS dispatch delay        0
  MVS delay (WAIT)           0
  MVS delay (Busy)           0
```

E12 - CICS CPU/service time by transaction

Usage

Use this report to see an analysis of how much time was used by the CICS transactions that were measured during the observation session. A prerequisite for this report is activation of the CICS+ option during the measurement. This option records exact CPU and service times for CICS transactions. Expand a CICS transaction report line to see a further breakdown by task number.

Quantification

Each report line shows the following for each CICS transaction:

- Number of transactions executed
- Percentage of total CPU used for this transaction
- Total CPU used for this transaction
- Mean CPU used for this transaction
- Total service time for this transaction
- Mean service time for this transaction

Detail line hierarchy

An unexpanded E11 report shows one line for each measured CICS user ID. You can expand each line to reveal additional hierarchical levels of detail.

The hierarchy is illustrated here:

```
Level 1 CICS Transaction
Level 2 CICS Task Number
Level 2 CICS Task Number
...
```

Detail line descriptions

CICS transaction detail line

This is the first-level detail line. Each line shows information about a CICS transaction for which measurement data was recorded.

| Under Heading | This is Displayed |
|-----------------|---|
| Name | The CICS transaction code. |
| NTxns | The number of executions of the transaction. |
| Description | If this is a recognized CICS transaction, a functional description. |
| % of CPU | The percent CPU consumed by this transaction, out of the total recorded for this report. |
| CPU Time: Total | The total task CPU time for all tasks counted for this CICS transaction. Large numbers will be expressed in minutes with an M suffix. |
| CPU Time: Mean | The mean task CPU time per CICS transaction. Large numbers will be expressed in minutes with an M suffix. |
| Svc Time: Total | The total service time for all tasks for this CICS transaction. Large numbers will be expressed in minutes with an M suffix. |
| Svc Time: Mean | The mean service time per CICS transaction. Large numbers will be expressed in minutes with an M suffix. |

CICS task number detail line

This is the second-level detail line shown directly under the CICS transaction detail line. It quantifies the CPU and service time for each individual CICS task run under this transaction id.

| Under Heading | This is Displayed |
|-----------------|--|
| Name | The task number of the CICS transaction. |
| Description | The start time of the CICS transaction. |
| CPU Time: Total | The total task CPU time for this task. |

| Under Heading | This is Displayed |
|-----------------|---|
| CPU Time: Mean | The mean task CPU time for this task. This is the same as the total time since it applies to only 1 task. This shows the CPU time to 5 decimal positions. |
| Svc Time: Total | The total service time for this task. |
| Svc Time: Mean | The mean service time for this task. This is the same as the total time since it applies to only 1 task. This shows the CPU time to 5 decimal positions. |

Sample reports

A sample report is shown here. The CICS transaction has been expanded to the second level (task number).

```

File View Navigate Help
-----
E12: CICS CPU/Service Time by Transaction (1860/CICS32A)      Row 00001 of 00603
Command ==>>> _____ Scroll ==>>> CSR

Name      NTxns Description          % of CPU    --CPU Time--    --Svc Time--
          Total Mean          Total Mean      Total Mean
TDB2      600
-> 08879   16:05:08.21          64.5%    4.25  0.00709    83.55  0.13925
-> 09180   16:05:20.52          0.01  0.01550    0.09  0.09333
-> 08883   16:05:08.22          0.01  0.01099    0.05  0.05510
-> 08880   16:05:08.21          0.00  0.00977    0.15  0.15520
-> 08901   16:05:08.21          0.00  0.00965    0.09  0.09113
-> 09185   16:05:08.46          0.00  0.00925    0.13  0.13706
-> 09013   16:05:20.54          0.00  0.00910    0.16  0.16997
-> 09283   16:05:09.75          0.00  0.00844    0.13  0.13625
-> 09283   16:05:21.42          0.00  0.00842    0.21  0.21626

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Transaction, Task | Display context help information. |
| ++ | Transaction, Task | Show additional details. |
| + | Transaction | Expand to reveal next level. |
| - | Transaction | Collapse to hide next level. |
| SV | Transaction | Sort next level by value. |
| SN | Transaction | Sort next level by name. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Name | Display context help information. |
| + | Name | Expand to reveal all entries. |
| - | Name | Collapse to show only first level. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|---------------------------|
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or press the enter key) on any line to open a window containing additional information.

A sample detail window for a CICS command report is shown below. This example shows a CICS task ID:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
|  → 08879  16:05:08.21          0.01  0.01550  0.09  0.0933|
+-----+

CPU and Service Time for CICS Transaction
Transaction ID          TDB2
Start Time              16:05:08.21
Stop Time               16:05:08.30
Task Number             08879
Dispatch Time           0.04277
CPU Time                0.01550
Suspend Time            0.05055
Dispatch Wait Time      0.04030
File Control Requests   370064
DB2 Requests            3
IMS Requests             0
MQ Requests              0

```

X01 - CICS mean service time by transaction

Usage

Use this report to see an analysis of how time was spent by the CICS transactions that were measured during the observation session in multiple regions. CICS sample data from the selected regions is merged to produce a single report showing multi-region activity. Transaction data from the multiple regions is correlated using the network unit of work ID to relate the remote activity to the local transaction. Since this is based on sample data, there are samples from the remote region that do not match with a local transaction. These are reported under the remote transaction name, such as CSMI.

Expand a CICS transaction report line to see a further breakdown by region, program, CICS command, DLI request and SQL request.

Quantification

Each report line quantifies time as arithmetic means for each measured transaction. The means are calculated by dividing the total of all time spent servicing all occurrences of a transaction by its number of occurrences. The means are expressed in units of seconds. The mean service time is shown and is further broken down into execution time, suspend time, and delay time.

Detail line hierarchy

An unexpanded X01 report shows one line for each measured CICS transaction. You can expand each line to reveal additional hierarchical levels of detail.

The hierarchy is illustrated here:

```

Level 1 CICS Transaction
  Level 2 CICS Region Applid
    Level 3 CICS Program
      Level 4 CICS Command
        Level 4 CICS Command

...
  Level 2 CICS Region Applid
    Level 3 CICS Program
      Level 4 SQL Request
        Level 4 SQL Request

...
  Level 2 CICS Region Applid
    Level 3 CICS Program
      Level 4 DLI Request
        Level 4 DLI Request

...
  Level 2 CICS Region Applid
    Level 3 CICS Program
      Level 4 Module
        Level 4 Module
        Level 4 System Services

...
  Level 2 CICS Region Applid
    Level 3 CICS Program
      Level 4 Adabas Request
        Level 4 Adabas Request

...
  Level 2 CICS Region Applid
    Level 3 System Services
      Level 4 Module
        Level 4 Module
        Level 4 System Services
  
```

Detail line descriptions

CICS transaction detail line

This is the first-level detail line. Each line shows information about a CICS transaction for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The CICS transaction code. |
| NTxns | The number of executions of the transaction. |
| Description | A functional description (if the transaction is a recognized CICS transaction). |
| Error | The margin of error for the mean values calculated by using the number of executions of the transaction as the sample size. |
| Execution | The mean time, in seconds, that a CPU was actively executing for the transaction. |

| Under Heading | This is Displayed |
|---------------|---|
| Suspend | The mean time, in seconds, that CICS had suspended execution of the transaction. |
| Delay | The mean time, in seconds, that execution of the transaction was delayed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The mean service time for the transaction. This includes execution, suspend, and delay time. |

CICS region applid detail line

This is the second-level detail line shown directly under the CICS transaction detail line. This line represents the VTAM applid of the CICS region sampled. If a transaction shows more than 1 region applid, then activity was measured in multiple regions for that transaction.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The CICS region applid. This is the VTAM applid of the region where the samples were taken. |
| NTxns | The number of executions of the transaction. |
| Description | "Region Applid" |
| Execution | The mean time, in seconds, that a CPU was actively executing for the transaction in the region. |
| Suspend | The mean time, in seconds, that CICS had suspended execution of the transaction in the region. |
| Delay | The mean time, in seconds, that execution of the transaction was delayed in the region. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The mean service time for the transaction in the region. This includes execution, suspend, and delay time. |

CICS program or system services detail line

This is a third-level detail line shown directly under the CICS region applid detail line. This line represents a CICS program (usually an application) that was in control during execution of the transaction. The fourth-level lines shown under this item can be either CICS command lines, SQL Request lines, DLI Request lines or Module lines.

If no CICS application program was dispatched, "CICS" is shown under the Name heading and "System Services" under the Description heading.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The module name of the CICS program. If lines grouped under this line are CICS command lines, this field is displayed in red. For Module lines grouped under this line, the field is turquoise. "CICS" is displayed here if no application program was in control. |
| Description | If lines grouped under this line are CICS command lines, the description displays "EXEC CICS." If lines grouped under this line are SQL request lines, the description displays "EXEC SQL." If lines grouped under this line are DLI request lines, the description displays "EXEC DLI." Otherwise, if the program name is a recognized CICS module name (a DFH* name), a functional description is shown, and "CICS Program" is displayed if the CICS module name is not recognized; indicating this is likely an application program. "System Services" is displayed if no application program was in control. |
| Execution | The mean time, in seconds, that CPU execution was observed while transaction control was under the CICS program identified in the Name column. |
| Suspend | The mean time, in seconds, that CICS had suspended execution of the transaction while transaction control was under the CICS program identified in the Name column. |
| Delay | The mean time, in seconds, that execution of the transaction was delayed while transaction control was under the CICS program identified in the Name column. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The mean service time for the transaction during which control was under the CICS program identified in the Name column. Service time includes execution, suspend, and delay time. |

CICS command detail line

These lines are displayed under a CICS Program detail line. Each one represents a CICS command issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC CICS command. This hexadecimal offset appears in +xxxx format. If the CSECT containing the EXEC CICS is not the same name as the module identified in the CICS Program line above, this field contains the CSECT name. In this case, the offset is shown in the description field. This field is always displayed in red. |
| Description | The CICS command description. If, as noted above, the CSECT name containing the EXEC CICS is different from the module name, the CICS command description is preceded by the hexadecimal offset of the command from the start of the CSECT. |
| Execution | The mean time, in seconds, that CPU execution was observed while the CICS command was being processed. |

| Under Heading | This is Displayed |
|---------------|--|
| Suspend | The mean time, in seconds, that CICS had suspended execution of the transaction while the CICS command was being processed. |
| Delay | The mean time, in seconds, that execution of the transaction was delayed while the CICS command was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The mean service time for the transaction during which the CICS command was being processed. This includes execution, suspend, and delay time. |

SQL request detail line

These lines are displayed under a CICS program detail line. Each line represents an SQL request issued by the program identified in the name field of the CICS program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC SQL command. This is in +xxxx format. This field is always displayed in red. |
| Description | The SQL request function – SELECT, FETCH, UPDATE, etc. |
| Execution | The mean time, in seconds, that CPU execution was observed while the SQL request was being processed. |
| Suspend | The mean time, in seconds, that CICS had suspended execution of the transaction while the SQL request was being processed. |
| Delay | The mean time, in seconds, that execution of the transaction was delayed while the SQL request was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The mean service time for the transaction during which the SQL request was being processed. This includes execution, suspend and delay time. |

DLI request detail line

These lines are displayed under a CICS Program detail line. Each line represents an IMS DLI request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC DLI command. This is in +xxxx format. This field is always displayed in red. |
| Description | The DLI function code followed by the PCB name. |
| Execution | The mean time, in seconds, that CPU execution was observed while the DLI request was being processed. |

| Under Heading | This is Displayed |
|---------------|---|
| Suspend | The mean time, in seconds, that CICS had suspended execution of the transaction while the DLI request was being processed. |
| Delay | The mean time, in seconds, that execution of the transaction was delayed while the DLI request was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The mean service time for the transaction during which the DLI request was being processed. This includes execution, suspend, and delay time. |

Module/system services detail line

These lines are displayed under a CICS Program detail line. Each line represents a module that was executing under control of the program identified in the name field of the CICS Program line under which these lines are grouped. If Application Performance Analyzer was unable to determine a module name, "CICS" is displayed in the name field and "System Services" is displayed in the description field.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The name of the module that was executing or "CICS" if a module name could not be determined. |
| Description | A functional description of the module if one is available. "System Services" is displayed if the module name could not be determined. |
| Execution | The mean time, in seconds, for execution of the module within the grouping under which the detail line is displayed. |
| Suspend | This field will contain a value of zero. |
| Delay | The mean time, in seconds, that the identified module was preempted by MVS. |
| Service | The mean service time for the transaction during which the identified module was executing or delayed. |

Adabas request detail line

These lines appear under a CICS Program detail line. Each one represents an Adabas request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC ADABAS command. This is in +xxxx format. This field is always displayed in red. |
| Description | The Adabas request function -- OP, CL, L2, etc. |
| Execution | The mean time, in seconds, during which CPU execution was observed while the Adabas request was being processed. |
| Suspend | The mean time, in seconds, during which CICS had suspended execution of the transaction while the Adabas request was being processed. |

| Under Heading | This is Displayed |
|---------------|---|
| Delay | The mean time, in seconds, during which execution of the transaction was delayed while the Adabas request was being processed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The mean service time for the transaction during which the Adabas request was being processed. This includes execution, suspend and delay time. |

Sample reports

When the report is first displayed, only the first level of the hierarchy is visible (transaction). A sample is shown here:

```

File View Navigate Help
-----
X01: CICS Mean Service Time by Txn (1682/CICS32A)          Row 00001 of 00002
Command ==> _____ Scroll ==> CSR

Name  NTxns  Description          Error  Execution  + Suspend + Delay = Service
-----
RDDR      2                ±71.4%  0.359    16.333   0.809   17.502
READ     680                ± 3.8%  0.020    2.860   0.068   2.950

```

You can enter the + line command on a transaction to expand to the next level. A sample of the report with a transaction expanded to the third level of the hierarchy (CICS Region Applid and CICS Program) is shown here:

```

File View Navigate Help
-----
X01: CICS Mean Service Time by Txn (1682/CICS32A)          Row 00001 of 00010
Command ==> _____ Scroll ==> CSR

Name  NTxns  Description          Error  Execution  + Suspend + Delay = Service
-----
RDDR      2                ±71.4%  0.359    16.333   0.809   17.502
→ CICS32A  Region Applid      0.119    16.333   0.749   17.202
→ READDRV  EXEC CICS          0.119    16.333   0.749   17.202

→ CICS32B  Region Applid      0.031    0.000   0.007   0.039
→ DFHMIRS  EXEC CICS          0.021    0.000   0.001   0.023
→ DFHMIRS  CICS Program       0.005    0.000   0.003   0.009
→ CICS     System Services    0.003    0.000   0.001   0.005

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|---|-----------------------------------|
| ? | Transaction, Region Applid, Load Module, CSECT, Command, SQL Request, DLI Request | Display context help information. |

| Cmd | When Applied To Object | Action |
|-----|---|----------------------------------|
| ++ | Transaction, Region Applid, Load Module, CSECT, Command, SQL Request, DLI Request | Show additional details. |
| + | Transaction, Region Applid, Load Module | Expand to reveal next level. |
| - | Transaction, Region Applid, Load Module | Collapse to hide next level. |
| SV | Transaction, Region Applid, Load Module | Sort next level by value. |
| SN | Transaction, Region Applid, Load Module | Sort next level by name. |
| M | Load Module | Display load module information. |
| P | Command, CSECT, SQL Request, DLI Request, CICS Active Module | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Name | Display context help information. |
| + | Name | Expand to reveal all entries. |
| - | Name | Collapse to show only first level. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or press the enter key) on any line to open a window containing additional information.

A sample detail window for this report is shown below. This example shows a CICS region:


```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| CICS32A   Region Applid      0.089   17.172   0.929   18.191 |
+-----+

Calculation Details
CICS Transaction           RDDR
The quantities shown represent the service time for execution of the
indicated CICS command while processing this transaction. The
quantities are mean times for the command for all executions of the
transaction and are calculated as follows:

(1) Times command observed in txn/program      607
(2) Duration of one sample interval           0.029970
(3) (1) A (2) = total time for command        18.191790
(4) Number of executions of transaction       1
(5) (3) S (4) = mean time for the command    18.191790

The execution measurement counts are
Executing (CPU active)           3
Suspended by CICS               573
Delayed
  CICS dispatch delay           29
  MVS delay (WAIT)              0
  MVS delay (Busy) 2

```

X02 - CICS total service time by txn

Usage

Use this report to view an analysis of how time was spent by the CICS transactions that were measured during the observation session in multiple regions. CICS sample data from the selected regions is merged to produce a single report showing multi-region activity. Transaction data from the multiple regions is correlated using the network unit of work ID to relate the remote activity to the local transaction. Since this is based on sample data, there will be samples from the remote region that do not match with a local transaction. These are reported under the remote transaction name, such as CSMI.

Expand a CICS transaction report line to see a further breakdown by region, program, CICS command, DLI request and SQL request.

Quantification

Each report line quantifies total times for each measured transaction. The total times are expressed in units of seconds. The total service time is shown and is further broken down into execution time, suspend time, and delay time.

Detail line hierarchy

An unexpanded X02 report shows one line for each measured CICS transaction. You can expand each line to reveal additional hierarchical levels of detail.

The hierarchy is illustrated here:

```

Level 1 CICS Transaction
  Level 2 CICS Region Applid
    Level 3 CICS Program
      Level 4 CICS Command
      Level 4 CICS Command

...
  Level 2 CICS Region Applid
    Level 3 CICS Program
      Level 4 SQL Request
      Level 4 SQL Request

...
  Level 2 CICS Region Applid
    Level 3 CICS Program
      Level 4 DLI Request
      Level 4 DLI Request

...
  Level 2 CICS Region Applid
    Level 3 CICS Program
      Level 4 Module
      Level 4 Module
      Level 4 System Services

...
  Level 2 CICS Region Applid
    Level 3 CICS Program
      Level 4 Adabas Request
      Level 4 Adabas Request

...
  Level 2 CICS Region Applid
    Level 3 System Services
      Level 4 Module
      Level 4 Module
      Level 4 System Services

```

Detail line descriptions

CICS transaction detail line

This is the first-level detail line. Each line shows information about a CICS transaction for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The CICS transaction code. |
| NTxns | The number of executions of the transaction. |
| Description | A functional description (if the transaction is a recognized CICS transaction). |
| Error | The margin of error based on a sample population of the number of executions of the transaction. |
| Execution | The total time, in seconds, that a CPU was actively executing for the transaction. |
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction. |

| Under Heading | This is Displayed |
|---------------|--|
| Delay | The total time, in seconds, that execution of the transaction was delayed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The total service time for the transaction. This includes execution, suspend, and delay time. |

CICS region applid detail line

This is the second-level detail line shown directly under the CICS transaction detail line. This line represents the VTAM applid of the CICS region sampled. If a transaction shows more than 1 region applid, then activity was measured in multiple regions for that transaction.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The CICS region applid. This is the VTAM applid of the region where the samples were taken. |
| NTxns | The number of executions of the transaction. |
| Description | "Region Applid" |
| Execution | The total time, in seconds, that a CPU was actively executing for the transaction in the region. |
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction in the region. |
| Delay | The total time, in seconds, that execution of the transaction was delayed in the region. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The total service time for the transaction in the region. This includes execution, suspend, and delay time. |

CICS program or system services detail line

This is a third-level detail line shown directly under the CICS region applid detail line. This line represents a CICS program (usually an application) that was in control during execution of the transaction. The fourth-level lines shown under this item can be either CICS command lines, SQL Request lines, DLI Request lines or Module lines.

If no CICS application program was dispatched, "CICS" is shown under the Name heading and "System Services" under the Description heading.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The module name of the CICS program. If lines grouped under this line are CICS command lines, this field is displayed in red. For Module lines grouped under this line, the field is turquoise. "CICS" is displayed here if no application program was in control. |
| Description | If lines grouped under this line are CICS command lines, the description displays "EXEC CICS." If lines grouped under this line are SQL request lines, the description displays "EXEC SQL." If lines grouped under this line are DLI request lines, the description displays "EXEC DLI." Otherwise, if the program name is a recognized CICS module name (a DFH* name), a functional description is shown, and "CICS Program" is displayed if the CICS module name is not recognized; indicating this is likely an application program. "System Services" is displayed if no application program was in control. |
| Execution | The total time, in seconds, that CPU execution was observed while transaction control was under the CICS program identified in the Name column. |
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction while transaction control was under the CICS program identified in the Name column. |
| Delay | The total time, in seconds, that execution of the transaction was delayed while transaction control was under the CICS program identified in the Name column. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The total service time for the transaction during which control was under the CICS program identified in the Name column. Service time includes execution, suspend, and delay time. |

CICS command detail line

These lines are displayed under a CICS Program detail line. Each one represents a CICS command issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC CICS command. This hexadecimal offset appears in +xxxx format. If the CSECT containing the EXEC CICS is not the same name as the module identified in the CICS Program line above, this field contains the CSECT name. In this case, the offset is shown in the description field. This field is always displayed in red. |
| Description | The CICS command description. If, as noted above, the CSECT name containing the EXEC CICS is different from the module name, the CICS command description is preceded by the hexadecimal offset of the command from the start of the CSECT. |
| Execution | The total time, in seconds, that CPU execution was observed while the CICS command was being processed. |

| Under Heading | This is Displayed |
|---------------|---|
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction while the CICS command was being processed. |
| Delay | The total time, in seconds, that execution of the transaction was delayed while the CICS command was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The total service time for the transaction during which the CICS command was being processed. This includes execution, suspend, and delay time. |

SQL request detail line

These lines are displayed under a CICS program detail line. Each line represents an SQL request issued by the program identified in the name field of the CICS program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC SQL command. This is in +xxxx format. This field is always displayed in red. |
| Description | The SQL request function – SELECT, FETCH, UPDATE, etc. |
| Execution | The total time, in seconds, that CPU execution was observed while the SQL request was being processed. |
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction while the SQL request was being processed. |
| Delay | The total time, in seconds, that execution of the transaction was delayed while the SQL request was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The total service time for the transaction during which the SQL request was being processed. This includes execution, suspend and delay time. |

DLI request detail line

These lines are displayed under a CICS Program detail line. Each line represents an IMS DLI request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC DLI command. This is in +xxxx format. This field is always displayed in red. |
| Description | The DLI function code followed by the PCB name. |
| Execution | The total time, in seconds, that CPU execution was observed while the DLI request was being processed. |

| Under Heading | This is Displayed |
|---------------|--|
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction while the DLI request was being processed. |
| Delay | The total time, in seconds, that execution of the transaction was delayed while the DLI request was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The total service time for the transaction during which the DLI request was being processed. This includes execution, suspend, and delay time. |

Module/system services detail line

These lines are displayed under a CICS Program detail line. Each line represents a module that was executing under control of the program identified in the name field of the CICS Program line under which these lines are grouped. If Application Performance Analyzer was unable to determine a module name, "CICS" is displayed in the name field and "System Services" is displayed in the description field.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The name of the module that was executing or "CICS" if a module name could not be determined. |
| Description | A functional description of the module if one is available. "System Services" is displayed if the module name could not be determined. |
| Execution | The total time, in seconds, for execution of the module within the grouping under which the detail line is displayed. |
| Suspend | This field will contain a value of zero. |
| Delay | The total time, in seconds, that the identified module was preempted by MVS. |
| Service | The total service time for the transaction during which the identified module was executing or delayed. |

Adabas request detail line

These lines appear under a CICS Program detail line. Each one represents an Adabas request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC ADABAS command. This is in +xxxx format. This field is always displayed in red. |
| Description | The Adabas request function -- OP, CL, L2, etc. |
| Execution | The total time, in seconds, during which CPU execution was observed while the Adabas request was being processed. |
| Suspend | The total time, in seconds, during which CICS had suspended execution of the transaction while the Adabas request was being processed. |

| Under Heading | This is Displayed |
|---------------|--|
| Delay | The total time, in seconds, during which execution of the transaction was delayed while the Adabas request was being processed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The total service time for the transaction during which the Adabas request was being processed. This includes execution, suspend and delay time. |

Sample reports

When the report is first displayed, only the first level of the hierarchy is visible (transaction). A sample is shown here:

```

File View Navigate Help
-----
X02: CICS Total Service Time by Txn (1684/CICS32A)          Row 00001 of 00001
Command ==> _____ Scroll ==> CSR

Name  NTxns  Description          Error  Execution  + Suspend + Delay = Service
-----
READ   340    ± 5.4%  7.672  1028.360  27.422  1063.455
RDDR   1      ±99.9%  0.449   17.172   1.018   18.641

```

You can enter the + line command on a transaction to expand to the next level. A sample of the report with a transaction expanded to the third level of the hierarchy (CICS Region Applid and CICS Program) is shown here:

```

File View Navigate Help
-----
X02: CICS Total Service Time by Txn (1684/CICS32A)          Row 00001 of 00011
Command ==> _____ Scroll ==> CSR

Name  NTxns  Description          Error  Execution  + Suspend + Delay = Service
-----
READ   340    ± 5.4%  7.672  1028.360  27.422  10623.455
+ CICS32B  Region Applid      3.686   970.788   3.956   978.430
+ SAMPREAD EXEC CICS          3.416   970.788   3.926   978.130
+ SAMPREAD CICS Program  0.149    0.000    0.029    0.179
+ CICS     System Services    0.119    0.000    0.000    0.119

+ CICS32A  Region Applid      3.986    57.572   23.466    85.024
+ DFHMIRS  CICS Program       2.697    57.482   22.327    82.507
+ CICS     System Services    1.288    0.089    1.138    2.517

RDDR   1      ±99.9%  0.449   17.172   1.018   18.641

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|---|-----------------------------------|
| ? | Transaction, Region Applid, Load Module, CSECT, Command, SQL Request, DLI Request | Display context help information. |
| ++ | Transaction, Region Applid, Load Module, CSECT, Command, SQL Request, DLI Request | Show additional details. |
| + | Transaction, Region Applid, Load Module | Expand to reveal next level. |
| - | Transaction, Region Applid, Load Module | Collapse to hide next level. |
| SV | Transaction, Region Applid, Load Module | Sort next level by value. |
| SN | Transaction, Region Applid, Load Module | Sort next level by name. |
| M | Load Module | Display load module information. |
| P | Command, CSECT, SQL Request, DLI Request, CICS Active Module | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Name | Display context help information. |
| + | Name | Expand to reveal all entries. |
| - | Name | Collapse to show only first level. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or press the enter key) on any line to open a window containing additional information.

A sample detail window for this report is shown below. This example shows a CICS region:


```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| CICS32B   Region Applid      3.686  970.788  3.956  978.430 |
+-----+

Calculation Details
CICS Transaction          READ
The quantities shown represent the service time for execution of the
indicated CICS command while processing this transaction. The
quantities are total times for all executions of the command within
the transaction and are calculated as follows:

(1) Times command observed in txn/program      32647
(2) Duration of one sample interval            0.029970
(3) (1) A (2) = total time for command         978.430590

The execution measurement counts are
Executing (CPU active)      123
Suspended by CICS          32392
Delayed
  CICS dispatch delay      103
  MVS delay (WAIT)         0
  MVS delay (Busy)         29

```

X03 - CICS mean service time by terminal ID

Usage

Use this report to see an analysis of how time was spent on CICS terminals that were measured during the observation session in multiple regions. CICS sample data from the selected regions is merged to produce a single report showing multiregion activity. Transaction data from the multiple regions is correlated using the network unit of work id to relate the remote activity to the local transaction. Since this is based on sample data, there will be samples from the remote region that do not match with a local transaction. These will be reported under the remote transaction name, such as CSMI.

Expand a CICS terminal report line to see a further breakdown by transaction, region, program, CICS command, DLI request and SQL request.

Quantification

Each report line quantifies time as arithmetic means for all measured transactions on the terminal. The means are calculated by dividing the total of all time spent servicing all occurrences of transactions on the terminal by the number of occurrences. The means are expressed in units of seconds. The mean service time is shown and is further broken down into execution time, suspend time, and delay time.

Detail line hierarchy

An unexpanded X03 report shows one line for each measured CICS terminal and 1 line for all non-terminal attached transactions. You can expand each line to reveal additional hierarchical levels of detail.

The hierarchy is illustrated here:

```

Level 1 CICS Terminal
  Level 2 CICS Transaction
    Level 3 CICS Region Applid
      Level 4 CICS Program
        Level 5 CICS Command
        Level 5 CICS Command
      ...
    Level 3 CICS Region Applid
      Level 4 CICS Program
        Level 5 SQL Request
        Level 5 SQL Request
      ...
    Level 3 CICS Region Applid
      Level 4 CICS Program
        Level 5 DLI Request
        Level 5 DLI Request
      ...
    Level 3 CICS Region Applid
      Level 4 CICS Program
        Level 5 Module
        Level 5 Module
        Level 5 System Services
      ...
    Level 3 CICS Region Applid
      Level 4 CICS Program
        Level 5 Adabas Request
        Level 5 Adabas Request
      ...
    Level 3 CICS Region Applid
      Level 4 System Services
        Level 5 Module
        Level 5 Module
        Level 5 System Services
  
```

Detail line descriptions

CICS terminal detail line

This is the first-level detail line. Each line shows information about a CICS terminal for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The CICS terminal ID. This is the terminal ID or N/A if a terminal ID was not available during the sample. A terminal might not be available because the transaction was running non-terminal attached, or the transaction was not attached to the terminal during initialization or termination. |
| NTxns | The number of executions of transactions on this terminal. |
| Description | This is either Terminal Txn or Non-Terminal Txn. |
| Error | The margin of error for the mean values calculated by using the number of executions of transactions for this terminal as a sample size. |
| Execution | The mean time, in seconds, that a CPU was actively executing transactions on this terminal. |

| Under Heading | This is Displayed |
|---------------|---|
| Suspend | The mean time, in seconds, that CICS had suspended execution of transactions on this terminal. |
| Delay | The mean time, in seconds, that execution of transactions on this terminal was delayed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The mean service time for transactions on this terminal. This includes execution, suspend, and delay time. |

CICS transaction detail line

This is the second-level detail line. Each line shows information about a CICS transaction for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The CICS transaction code. |
| NTxns | The number of executions of the transaction. |
| Description | A functional description (if the transaction is a recognized CICS transaction). |
| Error | The margin of error for the mean values calculated by using the number of executions of the transaction as the sample size. |
| Execution | The mean time, in seconds, that a CPU was actively executing for the transaction. |
| Suspend | The mean time, in seconds, that CICS had suspended execution of the transaction. |
| Delay | The mean time, in seconds, that execution of the transaction was delayed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The mean service time for the transaction. This includes execution, suspend, and delay time. |

CICS region applid detail line

This is the third-level detail line shown directly under the CICS transaction detail line. This line represents the VTAM applid of the CICS region sampled. If a transaction shows more than 1 region applid, then activity was measured in multiple regions for that transaction.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The CICS region applid. This is the VTAM applid of the region where the samples were taken. |
| NTxns | The number of executions of the transaction. |

| Under Heading | This is Displayed |
|---------------|---|
| Description | "Region Applid" |
| Execution | The mean time, in seconds, that a CPU was actively executing for the transaction in the region. |
| Suspend | The mean time, in seconds, that CICS had suspended execution of the transaction in the region. |
| Delay | The mean time, in seconds, that execution of the transaction was delayed in the region. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The mean service time for the transaction in the region. This includes execution, suspend, and delay time. |

CICS program or system services detail line

This is a fourth-level detail line shown directly under the CICS region applid detail line. This line represents a CICS program (usually an application) that was in control during execution of the transaction. The fifth-level lines shown under this item can be either CICS command lines, SQL Request lines, DLI Request lines or Module lines.

If no CICS application program was dispatched, "CICS" is shown under the Name heading and "System Services" under the Description heading.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The module name of the CICS program. If lines grouped under this line are CICS command lines, this field is displayed in red. For Module lines grouped under this line, the field is turquoise. "CICS" is displayed here if no application program was in control. |
| Description | If lines grouped under this line are CICS command lines, the description displays "EXEC CICS." If lines grouped under this line are SQL request lines, the description displays "EXEC SQL." If lines grouped under this line are DLI request lines, the description displays "EXEC DLI." Otherwise, if the program name is a recognized CICS module name (a DFH* name), a functional description is shown, and "CICS Program" is displayed if the CICS module name is not recognized; indicating this is likely an application program. "System Services" is displayed if no application program was in control. |
| Execution | The mean time, in seconds, that CPU execution was observed while transaction control was under the CICS program identified in the Name column. |
| Suspend | The mean time, in seconds, that CICS had suspended execution of the transaction while transaction control was under the CICS program identified in the Name column. |

| Under Heading | This is Displayed |
|---------------|---|
| Delay | <p>The mean time, in seconds, that execution of the transaction was delayed while transaction control was under the CICS program identified in the Name column.</p> <p>Transaction execution can be delayed for one of the following reasons:</p> <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | <p>The mean service time for the transaction during which control was under the CICS program identified in the Name column. Service time includes execution, suspend, and delay time.</p> |

CICS command detail line

These lines are displayed under a CICS Program detail line. Each one represents a CICS command issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|--|
| Name | <p>The hexadecimal offset in the identified CICS program of the return address of the EXEC CICS command. This hexadecimal offset appears in +xxxx format. If the CSECT containing the EXEC CICS is not the same name as the module identified in the CICS Program line above, this field contains the CSECT name. In this case, the offset is shown in the description field. This field is always displayed in red.</p> |
| Description | <p>The CICS command description. If, as noted above, the CSECT name containing the EXEC CICS is different from the module name, the CICS command description is preceded by the hexadecimal offset of the command from the start of the CSECT.</p> |
| Execution | <p>The mean time, in seconds, that CPU execution was observed while the CICS command was being processed.</p> |
| Suspend | <p>The mean time, in seconds, that CICS had suspended execution of the transaction while the CICS command was being processed.</p> |
| Delay | <p>The mean time, in seconds, that execution of the transaction was delayed while the CICS command was being processed.</p> <p>Transaction execution can be delayed for one of the following reasons:</p> <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | <p>The mean service time for the transaction during which the CICS command was being processed. This includes execution, suspend, and delay time.</p> |

SQL request detail line

These lines are displayed under a CICS program detail line. Each line represents an SQL request issued by the program identified in the name field of the CICS program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC SQL command. This is in +xxxx format. This field is always displayed in red. |
| Description | The SQL request function – SELECT, FETCH, UPDATE, etc. |
| Execution | The mean time, in seconds, that CPU execution was observed while the SQL request was being processed. |
| Suspend | The mean time, in seconds, that CICS had suspended execution of the transaction while the SQL request was being processed. |
| Delay | The mean time, in seconds, that execution of the transaction was delayed while the SQL request was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The mean service time for the transaction during which the SQL request was being processed. This includes execution, suspend and delay time. |

DLI request detail line

These lines are displayed under a CICS Program detail line. Each line represents an IMS DLI request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC DLI command. This is in +xxxx format. This field is always displayed in red. |
| Description | The DLI function code followed by the PCB name. |
| Execution | The mean time, in seconds, that CPU execution was observed while the DLI request was being processed. |
| Suspend | The mean time, in seconds, that CICS had suspended execution of the transaction while the DLI request was being processed. |
| Delay | The mean time, in seconds, that execution of the transaction was delayed while the DLI request was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The mean service time for the transaction during which the DLI request was being processed. This includes execution, suspend, and delay time. |

Module/system services detail line

These lines are displayed under a CICS Program detail line. Each line represents a module that was executing under control of the program identified in the name field of the CICS Program line under which these lines are grouped. If Application Performance Analyzer was unable to determine a module name, "CICS" is displayed in the name field and "System Services" is displayed in the description field.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The name of the module that was executing or "CICS" if a module name could not be determined. |
| Description | A functional description of the module if one is available. "System Services" is displayed if the module name could not be determined. |
| Execution | The mean time, in seconds, for execution of the module within the grouping under which the detail line is displayed. |
| Suspend | This field will contain a value of zero. |
| Delay | The mean time, in seconds, that the identified module was preempted by MVS. |
| Service | The mean service time for the transaction during which the identified module was executing or delayed. |

Adabas request detail line

These lines appear under a CICS Program detail line. Each one represents an Adabas request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC ADABAS command. This is in +xxxx format. This field is always displayed in red. |
| Description | The Adabas request function -- OP, CL, L2, etc. |
| Execution | The mean time, in seconds, during which CPU execution was observed while the Adabas request was being processed. |
| Suspend | The mean time, in seconds, during which CICS had suspended execution of the transaction while the Adabas request was being processed. |
| Delay | The mean time, in seconds, during which execution of the transaction was delayed while the Adabas request was being processed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The mean service time for the transaction during which the Adabas request was being processed. This includes execution, suspend and delay time. |

Sample reports

A sample report that has been expanded four levels is shown below .

| File View Navigate Help | | | | | | | |
|--|-------|---------------------|--------|-----------|-----------|--------------------|-----------|
| X03: CICS Mean Service Time by Term (1684/CICS32A) | | | | | | Row 00001 of 00033 | |
| Command ==> | | | | | | Scroll ==> CSR | |
| Name | NTxns | Description | Error | Execution | + Suspend | + Delay | = Service |
| ET36 | 1 | Terminal Attached | ±99.9% | 0.449 | 17.172 | 1.018 | 18.641 |
| → RDDR | 1 | | ±99.9% | 0.449 | 17.172 | 1.018 | 18.641 |
| → CICS32A | | Region Applid | | 0.089 | 17.172 | 0.929 | 18.191 |
| → READDRVR | | EXEC CICS | | 0.089 | 17.172 | 0.929 | 18.191 |
| → +0700 | | START TRANSID(READ) | | 0.059 | 12.377 | 0.029 | 12.467 |
| → +0884 | | START TRANSID(READ) | | 0.000 | 0.719 | 0.149 | 0.869 |
| → +0B84 | | START TRANSID(READ) | | 0.000 | 0.749 | 0.059 | 0.809 |
| → +0984 | | START TRANSID(READ) | | 0.000 | 0.509 | 0.149 | 0.659 |
| → +0904 | | START TRANSID(READ) | | 0.000 | 0.539 | 0.089 | 0.629 |
| → +0A04 | | START TRANSID(READ) | | 0.000 | 0.539 | 0.059 | 0.599 |
| → +0784 | | START TRANSID(READ) | | 0.000 | 0.479 | 0.089 | 0.569 |
| → +0804 | | START TRANSID(READ) | | 0.000 | 0.389 | 0.119 | 0.509 |
| → +0A84 | | START TRANSID(READ) | | 0.000 | 0.329 | 0.089 | 0.419 |
| → +0B04 | | START TRANSID(READ) | | 0.000 | 0.359 | 0.029 | 0.389 |
| → +0BFC | | SEND TEXT | | 0.029 | 0.179 | 0.059 | 0.269 |

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|---|-----------------------------------|
| ? | Terminal, Transaction, Region Applid, Load Module, CSECT, Command, SQL Request, DLI Request | Display context help information. |
| ++ | Terminal, Transaction, Region Applid, Load Module, CSECT, Command, SQL Request, DLI Request | Show additional details. |
| + | Terminal, Transaction, Region Applid, Load Module | Expand to reveal next level. |
| - | Terminal, Transaction, Region Applid, Load Module | Collapse to hide next level. |
| SV | Terminal, Transaction, Region Applid, Load Module | Sort next level by value. |
| SN | Terminal, Transaction, Region Applid, Load Module | Sort next level by name. |
| M | Load Module | Display load module information. |
| P | Command, CSECT, SQL Request, DLI Request, CICS Active Module | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Name | Display context help information. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| + | Name | Expand to reveal all entries. |
| - | Name | Collapse to show only first level. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or press the enter key) on any line to open a window containing additional information.

A sample detail window for this report is shown below. This example shows a CICS region:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| CICS32A  Region Applid      0.089  17.172  0.929  18.191 |
+-----+

Calculation Details
CICS Transaction                      RDDR
The quantities shown represent the service time for execution of the
indicated CICS command while processing this transaction. The
quantities are mean times for the command for all executions of the
transaction and are calculated as follows:

(1) Times command observed in txn/program      607
(2) Duration of one sample interval            0.029970
(3) (1) A (2) = total time for command         18.191790
(4) Number of executions of transaction        1
(5) (3) S (4) = mean time for the command     18.191790

The execution measurement counts are
Executing (CPU active)                      3
Suspended by CICS                          573
Delayed
  CICS dispatch delay                       29
  MVS delay (WAIT)                          0
  MVS delay (Busy)                          2

```

X04 - CICS total service time by terminal ID

Usage

Use this report to view an analysis of how time was spent on CICS terminals that were measured during the observation session in multiple regions. CICS sample data from the selected regions is merged to produce a single report showing multiregion activity. Transaction data from the multiple regions is correlated using the network unit of work ID to relate the remote activity to the local transaction. Since this is based on sample data, there will be samples from the remote region that do not match with a local transaction. These are reported under the remote transaction name, such as CSMI.

Expand a CICS terminal report line to see a further breakdown by transaction, region, program, CICS command, DLI request and SQL request.

Quantification

Each report line quantifies total times for transactions measured on a terminal. The total times are expressed in units of seconds. The total service time is shown and is further broken down into execution time, suspend time, and delay time.

Detail line hierarchy

An unexpanded X03 report shows one line for each measured CICS terminal and 1 line for all non-terminal attached transactions. You can expand each line to reveal additional hierarchical levels of detail.

The hierarchy is illustrated here:

```
Level 1 CICS Terminal
  Level 2 CICS Transaction
    Level 3 CICS Region Applid
      Level 4 CICS Program
        Level 5 CICS Command
        Level 5 CICS Command

    ...
    Level 3 CICS Region Applid
      Level 4 CICS Program
        Level 5 SQL Request
        Level 5 SQL Request

    ...
    Level 3 CICS Region Applid
      Level 4 CICS Program
        Level 5 DLI Request
        Level 5 DLI Request

    ...
    Level 3 CICS Region Applid
      Level 4 CICS Program
        Level 5 Module
        Level 5 Module
        Level 5 System Services

    ...
    Level 3 CICS Region Applid
      Level 4 CICS Program
        Level 5 Adabas Request
        Level 5 Adabas Request

    ...
    Level 3 CICS Region Applid
      Level 4 System Services
        Level 5 Module
        Level 5 Module
        Level 5 System Services
```

Detail line descriptions

CICS terminal detail line

This is the first-level detail line. Each line shows information about a CICS terminal for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The CICS terminal ID. This is the terminal ID or N/A if a terminal ID was not available during the sample. A terminal might not be available because the transaction was running non-terminal attached, or the transaction was not attached to the terminal during initialization or termination. |
| NTxns | The number of executions of transactions on this terminal. |
| Description | This is either Terminal Txn or Non-Terminal Txn. |
| Error | The margin of error for the mean values calculated by using the number of executions of transactions for this terminal as a sample size. |
| Execution | The total time, in seconds, that a CPU was actively executing transactions on this terminal. |
| Suspend | The total time, in seconds, that CICS had suspended execution of transactions on this terminal. |
| Delay | The total time, in seconds, that execution of transactions on this terminal was delayed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The total service time for transactions on this terminal. This includes execution, suspend, and delay time. |

CICS transaction detail line

This is the second-level detail line. Each line shows information about a CICS transaction for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The CICS transaction code. |
| NTxns | The number of executions of the transaction. |
| Description | A functional description (if the transaction is a recognized CICS transaction). |
| Error | The margin of error based on a sample population of the number of executions of the transaction. |
| Execution | The total time, in seconds, that a CPU was actively executing for the transaction. |
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction. |
| Delay | The total time, in seconds, that execution of the transaction was delayed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The total service time for the transaction. This includes execution, suspend, and delay time. |

CICS region applid detail line

This is the third-level detail line shown directly under the CICS transaction detail line. This line represents the VTAM applid of the CICS region sampled. If a transaction shows more than 1 region applid, then activity was measured in multiple regions for that transaction.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The CICS region applid. This is the VTAM applid of the region where the samples were taken. |
| NTxns | The number of executions of the transaction. |
| Description | "Region Applid" |
| Execution | The total time, in seconds, that a CPU was actively executing for the transaction in the region. |
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction in the region. |
| Delay | The total time, in seconds, that execution of the transaction was delayed in the region. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The total service time for the transaction in the region. This includes execution, suspend, and delay time. |

CICS program or system services detail line

This is a fourth-level detail line shown directly under the CICS region applid detail line. This line represents a CICS program (usually an application) that was in control during execution of the transaction. The fifth-level lines shown under this item can be either CICS command lines, SQL Request lines, DLI Request lines or Module lines.

If no CICS application program was dispatched, "CICS" is shown under the Name heading and "System Services" under the Description heading.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The module name of the CICS program. If lines grouped under this line are CICS command lines, this field is displayed in red. For Module lines grouped under this line, the field is turquoise. "CICS" is displayed here if no application program was in control. |
| Description | If lines grouped under this line are CICS command lines, the description displays "EXEC CICS." If lines grouped under this line are SQL request lines, the description displays "EXEC SQL." If lines grouped under this line are DLI request lines, the description displays "EXEC DLI." Otherwise, if the program name is a recognized CICS module name (a DFH* name), a functional description is shown, and "CICS Program" is displayed if the CICS module name is not recognized; indicating this is likely an application program. "System Services" is displayed if no application program was in control. |

| Under Heading | This is Displayed |
|---------------|--|
| Execution | The total time, in seconds, that CPU execution was observed while transaction control was under the CICS program identified in the Name column. |
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction while transaction control was under the CICS program identified in the Name column. |
| Delay | <p>The total time, in seconds, that execution of the transaction was delayed while transaction control was under the CICS program identified in the Name column.</p> <p>Transaction execution can be delayed for one of the following reasons:</p> <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay • MVS WAIT |
| Service | The total service time for the transaction during which control was under the CICS program identified in the Name column. Service time includes execution, suspend, and delay time. |

CICS command detail line

These lines are displayed under a CICS Program detail line. Each one represents a CICS command issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC CICS command. This hexadecimal offset appears in +xxxx format. If the CSECT containing the EXEC CICS is not the same name as the module identified in the CICS Program line above, this field contains the CSECT name. In this case, the offset is shown in the description field. This field is always displayed in red. |
| Description | The CICS command description. If, as noted above, the CSECT name containing the EXEC CICS is different from the module name, the CICS command description is preceded by the hexadecimal offset of the command from the start of the CSECT. |
| Execution | The total time, in seconds, that CPU execution was observed while the CICS command was being processed. |
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction while the CICS command was being processed. |
| Delay | <p>The total time, in seconds, that execution of the transaction was delayed while the CICS command was being processed.</p> <p>Transaction execution can be delayed for one of the following reasons:</p> <ul style="list-style-type: none"> • CICS dispatch delay • MVS dispatch delay |
| Service | The total service time for the transaction during which the CICS command was being processed. This includes execution, suspend, and delay time. |

SQL request detail line

These lines are displayed under a CICS program detail line. Each line represents an SQL request issued by the program identified in the name field of the CICS program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC SQL command. This is in +xxxx format. This field is always displayed in red. |
| Description | The SQL request function – SELECT, FETCH, UPDATE, etc. |
| Execution | The total time, in seconds, that CPU execution was observed while the SQL request was being processed. |
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction while the SQL request was being processed. |
| Delay | The total time, in seconds, that execution of the transaction was delayed while the SQL request was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none">• CICS dispatch delay• MVS dispatch delay |
| Service | The total service time for the transaction during which the SQL request was being processed. This includes execution, suspend and delay time. |

DLI request detail line

These lines are displayed under a CICS Program detail line. Each line represents an IMS DLI request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC DLI command. This is in +xxxx format. This field is always displayed in red. |
| Description | The DLI function code followed by the PCB name. |
| Execution | The total time, in seconds, that CPU execution was observed while the DLI request was being processed. |
| Suspend | The total time, in seconds, that CICS had suspended execution of the transaction while the DLI request was being processed. |
| Delay | The total time, in seconds, that execution of the transaction was delayed while the DLI request was being processed. Transaction execution can be delayed for one of the following reasons: <ul style="list-style-type: none">• CICS dispatch delay• MVS dispatch delay |
| Service | The total service time for the transaction during which the DLI request was being processed. This includes execution, suspend, and delay time. |

Module/system services detail line

These lines are displayed under a CICS Program detail line. Each line represents a module that was executing under control of the program identified in the name field of the CICS Program line under which these lines are grouped. If Application Performance Analyzer was unable to determine a module name, "CICS" is displayed in the name field and "System Services" is displayed in the description field.

| Under Heading | This is Displayed |
|---------------|--|
| Name | The name of the module that was executing or "CICS" if a module name could not be determined. |
| Description | A functional description of the module if one is available. "System Services" is displayed if the module name could not be determined. |
| Execution | The total time, in seconds, for execution of the module within the grouping under which the detail line is displayed. |
| Suspend | This field will contain a value of zero. |
| Delay | The total time, in seconds, that the identified module was preempted by MVS. |
| Service | The total service time for the transaction during which the identified module was executing or delayed. |

Adabas request detail line

These lines appear under a CICS Program detail line. Each one represents an Adabas request issued by the program identified in the name field of the CICS Program line under which these lines are grouped.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The hexadecimal offset in the identified CICS program of the return address of the EXEC ADABAS command. This is in +xxxx format. This field is always displayed in red. |
| Description | The Adabas request function -- OP, CL, L2, etc. |
| Execution | The total time, in seconds, during which CPU execution was observed while the Adabas request was being processed. |
| Suspend | The total time, in seconds, during which CICS had suspended execution of the transaction while the Adabas request was being processed. |
| Delay | The total time, in seconds, during which execution of the transaction was delayed while the Adabas request was being processed for one of the following reasons: <ul style="list-style-type: none">• CICS dispatch delay• MVS dispatch delay |
| Service | The total service time for the transaction during which the Adabas request was being processed. This includes execution, suspend and delay time. |

Sample reports

A sample report that has been expanded five levels is shown below .

```

File View Navigate Help
-----
X04: CICS Total Service Time by Term (1684/CICS32A)          Row 00001 of 00098
Command ==>> _____ Scroll ==>> CSR

----- Total Time in Seconds -----
Name  NTxns  Description          Error  Execution  + Suspend + Delay = Service
-----
N/A    340    Non-Terminal Atta  ± 5.4%  7.672    1028.360  27.422  1063.455
→ READ  340    ± 5.4%  7.672    1028.360  27.422  1063.455
→ CICS32B Region Applid          3.686    970.788  3.956  978.430
→ SMPREAD EXEC CICS          3.416    970.788  3.926  978.130
→ +04C4 READ FILE(FILEA)    3.266    970.788  3.926  977.981
→ ALLOCATE Wait on Interregion 0.000    863.885  0.000  863.885
→ IRLINK Wait on InterRegion Li 0.000    106.873  0.000  106.873
→ CICSDisp CICS Dispatch Delay 0.000    0.000    3.086  3.086
→ MVSBusy MVS Delay (Busy)    0.000    0.000    0.839  0.839
→ CICS susp Suspend          0.000    0.029    0.000  0.029
→ +0468 RETURN              0.089    0.000    0.000  0.089
→ +03E0 RETRIEVE            0.059    0.000    0.000  0.059
→

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|---|-----------------------------------|
| ? | Terminal, Transaction, Region Applid, Load Module, CSECT, Command, SQL Request, DLI Request | Display context help information. |
| ++ | Terminal, Transaction, Region Applid, Load Module, CSECT, Command, SQL Request, DLI Request | Show additional details. |
| + | Terminal, Transaction, Region Applid, Load Module | Expand to reveal next level. |
| - | Terminal, Transaction, Region Applid, Load Module | Collapse to hide next level. |
| SV | Terminal, Transaction, Region Applid, Load Module | Sort next level by value. |
| SN | Terminal, Transaction, Region Applid, Load Module | Sort next level by name. |
| M | Load Module | Display load module information. |
| P | Command, CSECT, SQL Request, DLI Request, CICS Active Module | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Name | Display context help information. |
| + | Name | Expand to reveal all entries. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| - | Name | Collapse to show only first level. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or press the enter key) on any line to open a window containing additional information.

A sample detail window for this report is shown below. This example shows a CICS region:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| CICS32B      Region Applid      3.686  970.788  3.956  978.430 |
+-----+

Calculation Details
CICS Transaction          READ
The quantities shown represent the service time for execution of the
indicated CICS command while processing this transaction. The
quantities are total times for all executions of the command within
the transaction and are calculated as follows:

(1) Times command observed in txn/program      32647
(2) Duration of one sample interval            0.029970
(3) (1) A (2) = total time for command         978.430590

The execution measurement counts are
Executing (CPU active)          123
Suspended by CICS              32392
Delayed
  CICS dispatch delay          103
  MVS delay (WAIT)             0
  MVS delay (Busy)             29

```


Chapter 5. IMS performance analysis reports

This section describes the IMS Performance Analysis Reports.

| For information about ... | See ... |
|---|--|
| The IMS data extractor | "Overview of IMS data extractor" on page 280 |
| The IMS+ extractor | "IMS+ extractor" on page 280 |
| IMS Multiple Address Space Support (MASS) | "Overview of IMS Multiple Address Space Support" on page 280 |
| I01 IMS measurement profile | "I01 - IMS measurement profile" on page 281 |
| I02 IMS DL/I call timeline | "I02 - IMS DL/I call timeline" on page 284 |
| I03 IMS transaction timeline | "I03 - IMS transaction timeline" on page 286 |
| I04 IMS transaction activity timeline | "I04 - IMS transaction activity timeline" on page 288 |
| I05 IMS DL/I CPU usage by PSB | "I05 - IMS DL/I CPU usage by PSB" on page 293 |
| I06 IMS DL/I CPU usage by transaction | "I06 - IMS DL/I CPU usage by transaction" on page 297 |
| I07 IMS DL/I CPU usage by DL/I call | "I07 - IMS DL/I CPU usage by DL/I call" on page 301 |
| I08 IMS DL/I WAIT time by PSB | "I08 - IMS DL/I WAIT time by PSB" on page 304 |
| I09 IMS DL/I WAIT time by transaction | "I09 - IMS DL/I WAIT time by transaction" on page 307 |
| I10 IMS DL/I WAIT time by DL/I call | "I10 - IMS DL/I WAIT time by DL/I call" on page 310 |
| I11 IMS DL/I activity by PSB | "I11 - IMS DL/I activity by PSB" on page 313 |
| I12 IMS DL/I activity by transaction | "I12 - IMS DL/I activity by transaction" on page 316 |
| I13 IMS DL/I activity by DL/I call | "I13 - IMS DL/I activity by DL/I call" on page 320 |
| I14 IMS PSB/PCB attributes | "I14 - IMS PSB/PCB attributes" on page 323 |
| I15 IMS DL/I call attributes | "I15 - IMS DL/I call attributes" on page 324 |
| I16 IMS transaction service times | "I16 - IMS transaction service times" on page 325 |
| I17 IMS transaction DL/I call counts | "I17 - IMS transaction DL/I call counts" on page 327 |
| I18 IMS CPU/Svc time by DL/I calls | "I18 - IMS CPU/Svc time by DL/I calls" on page 329 |
| I19 IMS CPU/Svc time by PSB | "I19 - IMS CPU/Svc time by PSB" on page 331 |
| I20 IMS CPU/Svc time by transaction | "I20 - IMS CPU/Svc time by transaction" on page 333 |
| I21 IMS CPU/Svc time by PCB | "I21 - IMS CPU/Svc time by PCB" on page 335 |

Overview of IMS data extractor

When the IMS data extractor is active all DL/I calls in the target address space are recorded each time a sample is taken. For each DL/I call in flight, all of the call parameters, SSAs etc, are recorded, as well as the module and offset from which the call was made. In a CICS region there can be multiple IMS threads active and so multiple DL/I calls can be recorded each time an IMS sample is taken in a CICS region.

Additionally, several IMS environment parameters are recorded each time a sample is taken. These parameters include, the region type and its status, the PSB, transaction code, IMS version and release, message sequence number and time stamp from the IOPCB. In the case of a CICS region, the scheduling and termination of PSBs is also recorded.

IMS+ extractor

IMS+ is an IMS measurement option (data extractor) in which the precise number of DL/I calls is counted as well as the exact DL/I service time and CPU time by DL/I call. Activating the IMS+ option automatically activates the IMS option. Many of the IMS reports require that the IMS+ extractor be used.

Note: Running measurements with the IMS+ data extractor turned on causes each IMS call to be intercepted to collect additional data. This may have a small impact on the performance of the target address space. Care should be taken when using this feature with other products that also intercept IMS calls as unpredictable results may occur. Your installer may have chosen to limit access to this feature.

Overview of IMS Multiple Address Space Support

IMS multiple address space (MASS) support allows you to measure an IMS transaction that is eligible to run in multiple MPP regions within a single IMS subsystem. You specify the IMS subsystem and IMS transaction to measure. Application Performance Analyzer determines the MPP regions that are eligible to process the transaction and returns a list of active MPP regions in Panel 4. You select the regions you want to measure, and Application Performance Analyzer creates one observation request for each selected MPP region.

To enter IMS MASS observations:

1. Start a NEW request.
2. In Panel 1 – Job Information, enter a dash (-) in the Job name/Pattern field.
3. In Panel 5 – Subsystems, enter the IMS subsystem ID and IMS transaction code.
4. In Panel 4 – Active Jobs, Application Performance Analyzer returns a list of active MPP regions that are eligible to process the transaction. Select the MPP regions you want to measure. The maximum number of regions you are permitted to select is determined during the installation of Application Performance Analyzer.
5. In Panel 2 – Options, select the IMS+ data extractor.
6. Complete any other relevant fields for your observation request.

Once the NEW request is complete and submitted, Application Performance Analyzer creates and starts separate observation requests for each MPP region selected for measurement. You can view the IMS reports for each MPP region individually. When any of the selected MPP regions has not processed the IMS

transaction during the measurement interval, the measurement has a status of Ended, with 1 Sample and no IMS reports are generated.

I01 - IMS measurement profile

Usage

Use this report to see a general overview of the IMS measurement data. This is a good report to examine first when analyzing IMS information. It provides an at-a-glance summary of various aspects of the measurement data and helps you choose which other reports to concentrate on. Information about the IMS environment is shown at the top of this report. This is followed by a series of mini performance graphs illustrating various types of measured activity.

A sample report is shown here, expanded to show PSB, Transaction, and IMS calls:

IMS environment

This does not appear if the measurement was for a CICS region.

| Under Heading | This is Displayed |
|-----------------|---|
| DFSRRRC00 parms | The PARM data that was passed to DFSRRRC00 (the IMS region controller) in the EXEC statement. |
| IMS system ID | The system name of the IMS subsystem under which the measured activity took place. |
| IMS region name | The JOB name/STC name of the IMS dependent region. |
| IMS version | The IMS version. |
| IMS region type | The type of dependent region: BMP, MPP, etc. |

Performance graphs

These are histograms quantifying measurement data. To the right of some of the graphs, report codes of reports that show related and more detailed information are displayed. You can display the report by skipping the cursor to one of these fields and by pressing the ENTER key.

Most active IMS PSBs

| Under Heading | This is Displayed |
|---------------|---|
| Samples | The number of samples done during the measurement upon which this graph is based. This number represents 100 percent of the data upon which the graph is based and is used as the divisor to compute the percentages shown in other lines in the graph. |
| IMS PSB Name | An IMS PSB name is shown and the number of samples in which processing of DL/I calls under this PSB was observed. The percentage and the graph represent the proportion of the overall measurement time DL/I calls were being serviced under this PSB. |

Most active IMS transactions

| Under Heading | This is Displayed |
|----------------------|---|
| Samples | The number of samples done during the measurement upon which this graph is based. This number represents 100 percent of the data upon which the graph is based and is used as the divisor to compute the percentages shown in other lines in the graph. |
| IMS Transaction Code | An IMS transaction code is shown and the number of samples in which processing of DL/I calls under this transaction was observed. The percentage and the graph represent the proportion of the overall measurement time DL/I calls were being serviced in this transaction. |

Most active DL/I calls

| Under Heading | This is Displayed |
|---------------|---|
| Samples | The number of samples done during the measurement upon which this graph is based. This number represents 100 percent of the data upon which the graph is based and is used as the divisor to compute the percentages shown in other lines in the graph. |
| DL/I Call | A DL/I call identified by three fields: a unique sequence number assigned to the DL/I call, its DL/I function code and its PCB name. The percentage and the graph represent the proportion of samples in which processing this DL/I call was observed. The percentage and the graph represent the proportion the overall measurement time all executions of this DL/I call were being serviced. |

Most CPU consumptive DL/I

| Under Heading | This is Displayed |
|---------------------|--|
| Total DL/I CPU Time | The number of seconds of CPU time consumed by all executions of DL/I calls during the measurement. This number represents 100 percent of the data upon which the graph is based and is used as the divisor to compute the percentages shown in other lines in the graph. |
| DL/I Call | A DL/I call identified by three fields: a unique sequence number assigned to the DL/I call, its DL/I function code and its PCB name. The quantification and the graph show the number of CPU seconds of execution for this DL/I call. |

Most frequent transactions

This requires that the IMS+ measurement option is active and the execution of IMS transaction was observed. The graphic information is based on the number of transactions counted.

| Under Heading | This is Displayed |
|--------------------|--|
| Total txns counted | The total number of IMS transactions counted during the measurement. This number represents 100 percent of the data upon which the graph is based and is used as the divisor to compute the percentages shown in other lines in the graph. |

| Under Heading | This is Displayed |
|-----------------|--|
| IMS transaction | The IMS transaction code and the number of executions of this transaction. |

Most frequent DL/I calls

This requires that the IMS+ measurement option was active. The graphic information is based on the number of DL/I calls counted.

| Under Heading | This is Displayed |
|--------------------------|--|
| Total DL/I calls counted | The total number of DL/I calls counted during the measurement. This number represents 100 percent of the data upon which the graph is based and is used as the divisor to compute the percentages shown in other lines in the graph. |
| DL/I call | A DL/I call identified by three fields: a unique sequence number assigned to the call, its DL/I function code and its PCB name. The number of executions of this call is quantified. |

Transaction statistics

This requires that the IMS+ measurement option was active and the execution of IMS transaction was observed.

| Under Heading | This is Displayed |
|------------------|---|
| IMS Txns counted | The number of IMS transactions counted during the measurement interval. |
| Transaction rate | The average rate, in transactions per second, at which transactions were processed during the measurement interval. |
| Txn observations | The number of samples transaction execution was observed. |
| Txn throughput | The theoretical transaction throughput, in transactions per second, based on the number of counted transactions divided by the number of seconds transactions were executing. |
| IMS Txn svc time | The total service time for all observed transactions. |
| IMS Txn CPU time | The total CPU time consumed by all observed transactions. |
| IMS Txn max svc | The maximum service time observed for a single transaction execution. |
| IMS Txn max CPU | The maximum CPU time observed for a single transaction execution. |
| IMS Txn min svc | The minimum service time observed for a single transaction execution. |
| IMS Txn min CPU | The minimum CPU time observed for a single transaction execution. |

Sample reports

A sample report is shown here:

```

File View Navigate Help
-----
I01: IMS Measurement Profile (0954/ADSMPP)          Row 00001 of 00049
Command ==>>> _____ Scroll ==>>> CSR

IMS Environment -----
DFSRRRC00 parms  MSG,002002002000,N000000000,,,,,7,10,,,,,DSN1,,,N,,,
-----
IMS system id    IMSP                IMS region name  ADSMPP
IMS version      8.1.0                IMS region type  MPP
-----*-----*

Most Active IMS PSBs -----
Samples          3,000 100.0% ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '
XTEITS20         49   1.6% *
Reports:
I05 I08
I11

Most Active IMS Transactions -----
Samples          3,000 100.0% ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '
TMEITS20         49   1.6% *
Reports:
I04 I06
I09 I12

Most Active IMS DLI Calls -----
Samples          3,000 100.0% ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '
00001 GU IOPCB   32   1.0% *
00002 ISRT IOPCB 11   0.3% *
Reports:
I07 I10
I13

Most CPU consumptive DLI -----
Total DLI CPU time  0.25 100.0% ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '
00001 GU IOPCB   0.20 81.3% *****
00002 ISRT IOPCB 0.04 18.6% ***
Reports:
I18 I19
I20 I21

Most Frequent Transactions -----
Total txns counted  104 100.0% ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '
TMEITS20           104 100.0% *****
Reports:
I03 I04
I16 I17

```

Remainder of report after scrolling down is shown here:

```

File View Navigate Help
-----
I01: IMS Measurement Profile (0954/ADSMPP)          Row 00031 of 00049
Command ==>>> _____ Scroll ==>>> CSR

Most Frequent DL/I Calls -----
Total DLI calls counted  620 100.0% ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '
00001 GU IOPCB   206 33.2% *****
00002 ISRT IOPCB 104 16.7% ***
Reports:
I02 I17
I18

Transactions Statistics-----
IMS Txns counted  104                Transaction rate  3.47 per sec
Txn observations  612                Txn throughput   24.18 per sec
-----
IMS Txn svc time  4.3456 sec          IMS Txn CPU time  2.2794 sec
IMS Txn max svc   0.1496 sec          IMS Txn max CPU   0.0266 sec
IMS Txn min svc   0.0276 sec          IMS Txn min CPU   0.0206 sec
-----*-----*

```

I02 - IMS DL/I call timeline

Usage

Use this report to see the chronology of DL/I calls observed during the measurement interval. Each line shows information about one executed DL/I call. The IMS+ feature must have been enabled when the measurement was performed.

The number of DLI calls displayed in this report is limited by the value of the IMSIMaxTraceSize parameter specified during Application Performance Analyzer installation, or by the value on panel 2 of the measurement request (if your installation has configured this field). The report is truncated when the number of DLI calls issued reaches the value specified for IMSIMaxTraceSize.

Quantification

Each report line shows information pertaining to one IMS DL/I call.

Detail line hierarchy

The I02 report shows only one detail line level. It cannot be expanded.

Detail line descriptions

| Under Heading | This is Displayed |
|---------------|--|
| Call Seq | A sequence number assigned to the DL/I call execution. |
| Func | The DL/I function code. |
| PCB Name | The name of the PCB referenced by the DL/I call. |
| ID | An identifier assigned to each unique DL/I call. This is useful when examining printed reports. You can use this identifier to locate detailed information about the DL/I call in the I15 DL/I Call Attributes report. |
| Location | The location, in CSECT+offset format, of the return address of the DL/I call. |
| Stat | The PCB status code returned by IMS upon completion of the DL/I call. |
| Call Time | The time of day at which the DL/I call occurred. |
| Duration | The duration of the DL/I call in seconds. |

Sample reports

Below is an IMS DL/I call timeline sample report:

```

File View Navigate Help
-----
I02: IMS DL/I Call Timeline (0805/ADSMPP)                               Row 00001 of 01128
Command ==>>> _____ Scroll ==>>> CSR

CallSeq  Func  PCB Name  Id   Location          Stat  Call Time  Duration
-----
000001  GU   IOPCB    0001 BBSFIN00+038C    20:36:10.29  0.0001
000002  GHU  DBSCA001 0002 BBSAP012+0E0E    20:36:11.20  0.0556
000003  GHU  DBSCN001 0003 BBSAP012+0EE4    20:36:11.26  0.0133
000004  GHU  DBSCA002 0004 BBSAP012+1086    20:36:11.27  0.0003
000005  ISRT DBSCA002 0005 BBSAP012+1110    20:36:11.27  0.0003
000006  GHU  DBSTL001 0006 BBSAP012+11B0    20:36:11.27  0.0232
000007  ISRT DBSTL001 0007 BBSAP012+1252    20:36:11.30  0.0003
000008  REPL DBSCA001 0008 BBSAP012+131E    20:36:11.30  0.0001
000009  REPL DBSCN001 0009 BBSAP012+13A4    20:36:11.30  0.0023
000010  ISRT IOPCB    0010 BBSFIN00+0410    QH   20:36:11.46  0.0002

000011  GU   IOPCB    0001 BBSFIN00+038C    20:36:11.46  0.0087
000012  GHU  DBSCA001 0002 BBSAP012+0E0E    20:36:11.47  0.0396
000013  GHU  DBSCN001 0003 BBSAP012+0EE4    20:36:11.51  0.0257
000014  GHU  DBSCA002 0004 BBSAP012+1086    20:36:11.54  0.0002

```

Line commands

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | DL/I call | Display context help information. |
| ++ | DL/I call | Show additional details. |
| M | DL/I call | Display load module information. |
| P | DL/I call | Display source program mapping. |

I03 - IMS transaction timeline

Usage

Use this report to see the chronology of IMS transactions observed during the measurement interval. Each line shows information about one executed IMS transaction and can be expanded to show the sequence of DL/I calls executed by the transaction. The IMS+ feature must have been enabled when the measurement was performed.

The number of transactions and DLI calls displayed in this report is limited by the value of the IMSIMaxTraceSize parameter specified during Application Performance Analyzer installation, or by the value on panel 2 of the measurement request (if your installation has configured this field). The report is truncated when the number of DLI calls issued reaches the value specified for IMSIMaxTraceSize.

Quantification

Each report line shows information pertaining to one IMS transaction.

Detail line hierarchy

The unexpanded I03 report shows a line for each observed IMS transaction. You can expand each line to reveal one additional hierarchical level of detail. The hierarchy is illustrated here:

Level 1 IMS Transaction
Level 2 DL/I Call

Detail line descriptions

IMS transaction detail line

This is the first-level detail line. Each line shows information about an observed IMS transaction. These lines appear in transaction chronological sequence.

| Under Heading | This is Displayed |
|---------------|--|
| TranCode | The IMS transaction code. |
| PSB/PCB | The name of the PSB under which the IMS transaction was scheduled. |
| Location | The LTERM where the transaction originated. |
| Txn Time | The time of day at which the IMS transaction was initiated. This is the time at which the transaction program received control upon return from the GU-IOPCB call. |

| Under Heading | This is Displayed |
|---------------|---|
| Duration | The duration of the IMS transaction in seconds. The duration is measured from the time of return from the GU-IOPCB to the time of entry to the next GU-IOPCB. |

DL/I call detail line

Line This is the second-level detail line. Each line shows information about an observed IMS DL/I Call that was executed in the transaction. These lines appear in DL/I call chronological sequence.

| Under Heading | This is Displayed |
|---------------|--|
| TranCode | A sequence number assigned to the DL/I call execution. |
| PSB/PCB | The name of the PCB referred to by the DL/I call. |
| ID | An identifier assigned to each unique DL/I call. This is useful when examining printed reports. You can use this identifier to locate detailed information about the DL/I call in the I15 DL/I Call Attributes report. |
| Func | The DLI function code. |
| Location | The location, in CSECT+offset format, of the return address of the DL/I call. |
| Stat | The PCB status code returned by IMS upon completion of the DL/I call. |
| Txn Time | The time of day at which the DL/I call occurred. |
| Duration | The duration of the DL/I call in seconds. |

Sample reports

A sample report is shown below. The first TranCode has been expanded to the second level.

```

File View Navigate Help
-----
I03: IMS Transaction Timeline (0805/ADSMPP) Row 00001 of 00111
Command ==>>> _____ Scroll ==>>> CSR

```

| TranCode | PSB/PCB | Id | Func | Location | Stat | Txn Time | Duration |
|----------|----------|------|------|---------------|------|-------------|----------|
| BBSDR000 | BBSFIN00 | | | | | 20:36:10.29 | 1.1639 |
| ± 000001 | IOPCB | 0001 | GU | BBSFIN00+038C | | 20:36:10.29 | 0.0001 |
| → 000002 | DBSCA001 | 0002 | GHU | BBSAP012+0E0E | | 20:36:11.20 | 0.0556 |
| → 000003 | DBSCN001 | 0003 | GHU | BBSAP012+0EE4 | | 20:36:11.26 | 0.0133 |
| → 000004 | DBSCA002 | 0004 | GHU | BBSAP012+1086 | | 20:36:11.27 | 0.0003 |
| → 000005 | DBSCA002 | 0005 | ISRT | BBSAP012+1110 | | 20:36:11.27 | 0.0003 |
| → 000006 | DBSTL001 | 0006 | GHU | BBSAP012+11B0 | | 20:36:11.27 | 0.0232 |
| → 000007 | DBSTL001 | 0007 | ISRT | BBSAP012+1252 | | 20:36:11.30 | 0.0003 |
| → 000008 | DBSCA001 | 0008 | REPL | BBSAP012+131E | | 20:36:11.30 | 0.0001 |
| → 000009 | DBSCN001 | 0009 | REPL | BBSAP012+13A4 | | 20:36:11.30 | 0.0023 |
| → 000010 | IOPCB | 0010 | ISRT | BBSFIN00+0410 | QH | 20:36:11.46 | 0.0002 |
| BBSDR000 | BBSFIN00 | | | TERM09 | | 20:36:11.47 | 0.0760 |
| BBSDR000 | BBSFIN00 | | | | | 20:36:11.55 | 0.0273 |
| BBSDR000 | BBSFIN00 | | | | | 20:36:11.58 | 0.0467 |

Line commands

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Trancode, DL/I call | Display context help information. |
| ++ | Trancode, DL/I call | Show additional details. |
| + | Trancode | Expand to reveal next level. |
| - | Trancode | Collapse to hide next level. |
| M | Trancode, DL/I call | Display load module information. |
| P | Trancode, DL/I call | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Trancode | Display context help information. |
| + | Trancode | Expand to reveal all entries. |
| - | Trancode | Collapse to show only first level. |

I04 - IMS transaction activity timeline

Usage

Use this report to see, for each IMS transaction, how execution of that transaction was distributed over the measurement interval.

Quantification

A graph, in bar chart format, is displayed for each observed IMS transaction code. The horizontal axis represents the measurement interval which spans 50 columns. Each column represents an equal 1/50th subinterval of time. A scale is shown at the bottom of the graph indicating the percentage of time progression in the overall interval.

In each column, a vertical graph shows the approximate percentage of time during the subinterval that execution of the IMS transaction took place. A vertical bar of 1, 2, 3, 4 or 5 characters, extending upward from the scale, is displayed indicating the percentage of time in the subinterval execution of the indicated transaction was observed.

Detail line descriptions

IMS transaction activity distribution

A group of lines is shown for each reported transaction. Some information about the transaction appears to the left, and a bar chart appears to the right.

| Under Heading | This is Displayed |
|---------------|----------------------------------|
| Txn | The IMS transaction code. |
| PSB | The name of the PSB and program. |

| Under Heading | This is Displayed |
|---------------|---|
| Txns | The number of executions of the transaction that occurred during the measurement interval. This value is available only if the IMS+ measurement option was enabled. |

Sample reports

A sample report is shown below.

```

File View Navigate Help
-----
I04: IMS Transaction Activity Timeline (0805/ADSMPP)          Row 00001 of 00018
Command ==> _____ Scroll ==> CSR

IMS Transaction          <----- 2,000 Samples: Duration 59.8 Seconds ----->

Txn: BBSDR000          >80%      *      * * * * *
PSB: BBSFIN00          >60%     ** * * * * *
Txns: 50                >40%     ** * * * * *
                        >20%     * * * * *
                        > 0%     * * * * *
                        *.....1....2....3....4....5....6....7....8....9....*

Txn: BBSCR000          >80%      *      * *
PSB: BBSFIN00          >60%     * * * * *
Txns: 49                >40%     ** * * * * *
                        >20%     **** * * * * *
                        > 0%     * * * * *
                        *.....1....2....3....4....5....6....7....8....9....*

```

Line commands

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Trancode | Display context help information. |
| ++ | Trancode | Show additional details. |

on headings

| Cmd | When Applied To Object | Action |
|-----|-------------------------|-----------------------------------|
| ? | IMS Transaction Display | Display context help information. |
| SV | IMS Transaction | Sort next level entries by value. |
| SN | IMS Transaction | Sort next level entries by name. |

Detail lines for reports I05 through I13

This section describes the common format of detail lines shared by reports I05 through I13. These reports quantify activity based on the basis of the PSW (Program Status Word) address values observed at the time of the sample. This format is not exclusive to the IMS reports, it is also used in CPU reports such as C01, and Wait reports such as W01.

Detail lines reported for PSW sampling

Various report detail lines quantify activity on the basis of the PSW (Program Status Word) address values observed at the time of the sample. One PSW observation is recorded for each TCB. Depending on the report, the 'activity' might be: CPU usage, WAIT time, Queued time, or overall service time.

The analysis reports classify the PSW address values and aggregate them into 'objects'. The reports show each of these objects in one detail line arranged in a hierarchy. Each successive level in the hierarchy represents a more granular breakdown of the quantifications reported in the higher level items.

These objects are reported with a Name field, a Description, a quantification expressed as a percentage, and a histogram depicting the quantity. Descriptions of these detail lines are presented here.

APPLCN - Application code category

A group of lines is shown for each reported transaction. Some information about the transaction appears to the left, and a bar chart appears to the right.

| Under Heading | This is Displayed |
|-----------------|---|
| Name | "APPLCN" |
| Description | "Application Code" |
| Percent of Time | The percentage of activity measured in application code. The classification as application code is done on the basis of load module names and DPA (Descriptive Program Attribution) tables. |

SYSTEM - System/OS services category

| Under Heading | This is Displayed |
|-----------------|---|
| Name | "SYSTEM" |
| Description | "System/OS Services" |
| Percent of Time | The percentage of activity measured in system services. The classification as SYSTEM is done on the basis of load module names and DPA (Descriptive Program Attribution) tables. These include core operating system services as well as major system applications or subsystems: DB2, IMS, CICS, MQSeries, etc. SVC (Supervisor Call) routines and MVS Nucleus routines are included in this category. |

NOSYMB - No module name found

| Under Heading | This is Displayed |
|-----------------|--|
| Name | "NOSYMB" |
| Description | "No Module Name" |
| Percent of Time | The percentage of activity measured at addresses for which associated module names could not be determined. An example of this would be execution of instructions moved into an area of GETMAINed storage. |

DPA group

| Under Heading | This is Displayed |
|-----------------|---|
| Name | DPA Group name |
| Description | Description of the DPA group. For example: MVS, IMS, DB2, SVC, LERUNLIB, etc. |
| Percent of Time | The percentage of activity measured in modules in the indicated grouping. |

DPA subgroup

| Under Heading | This is Displayed |
|-----------------|---|
| Name | DPA Subgroup name. |
| Description | Description of the DPA subgroup. For example: MVS, IMS, SVCTYPE1, SVCTYPE2, LEBASE, LECOBOL, etc. |
| Percent of Time | The percentage of activity measured in modules in the indicated grouping. |

NOSYMB address range

| Under Heading | This is Displayed |
|-----------------|--|
| Name | Hexadecimal address range. |
| Description | "Unresolved Address." |
| Percent of Time | The percentage of activity measured at the indicated address range. These are addresses for which no corresponding module name could be determined. These measurements are aggregated under the NOSYMB category. Each report line represents a 4K (4096 bytes) range of addresses. The address range is displayed under the Name heading in the format HHHHHHxxx. HHHHHH displays the first five hexadecimal digits of the address and xxx represents the three lower order digits: a range from X'000' to X'FFF' (decimal 0 to 4095). |

SVC - Supervisor call

| Under Heading | This is Displayed |
|-----------------|---|
| Name | SVCnnn - where nnn is the supervisor call number in decimal. |
| Description | Description of the supervisor call function. |
| Percent of Time | The percentage of activity measured in the indicated supervisor call. |

CSECT - Control section

| Under Heading | This is Displayed |
|-----------------|---|
| Name | A CSECT (Control Section) name. |
| Description | Functional description of the CSECT if one is available. Otherwise "csectname in modulename" appears. |
| Percent of Time | The percentage of activity measured in the indicated CSECT. |

DB2SQL - DB2 SQL processing category

| Under Heading | This is Displayed |
|-----------------|--|
| Name | "DB2SQL" |
| Description | "SQL Processing." |
| Percent of Time | The percentage of activity measured while processing SQL requests. |

SQL statement

| Under Heading | This is Displayed |
|-----------------|---|
| Name | A unique reference number assigned to the SQL statement. |
| Description | The name of the program that issued the SQL request as well as the precompiler statement number of the SQL statement in PGMNAME(stmt#) format. This is followed by the SQL function name. For example: SELECT, INSERT, COMMIT, etc. |
| Percent of Time | The percentage of activity measured while processing the indicated SQL statement. |

DATAMG - Data management processing category

| Under Heading | This is Displayed |
|-----------------|---|
| Name | "DATAMG" |
| Description | "Data Mgmt Processing." |
| Percent of Time | The percentage of activity measured in routines that were servicing data management (DASD) requests. This includes basic access functions (such as READ and WRITE) to files. Processing of OPEN and CLOSE functions is not included in this category. |

DDNAME

| Under Heading | This is Displayed |
|-----------------|--|
| Name | DDNAME of a DASD file. |
| Description | Access method for the indicated file: VSAM, QSAM, etc. |
| Percent of Time | The percentage of activity measured in routines that were servicing data management (DASD) requests for the indicated DDNAME. This includes basic access functions (such as READ and WRITE) to files. Processing of OPEN and CLOSE functions is not included in this category. |

DASD I/O request

| Under Heading | This is Displayed |
|-----------------|--|
| Name | Type of I/O request. |
| Description | Program name and offset of the I/O request. |
| Percent of Time | The percentage of activity measured in routines that were servicing data management (DASD) requests for the indicated request. |

IMS PSB

| Under Heading | This is Displayed |
|-----------------|--|
| Name | IMS PSB Name. NONIMS to indicate IMS activity for which no PSB has been scheduled. |
| Description | The type of IMS dependent region: BMP, MPP, IFP, etc. |
| Percent of Time | The percentage of activity measured under the indicated IMS PSB. |

IMS transaction

| Under Heading | This is Displayed |
|-----------------|--|
| Name | IMS transaction code. |
| Description | The PSB to which the IMS transaction belongs. |
| Percent of Time | The percentage of activity measured while executing the indicated IMS transaction. |

IMS DL/I call

| Under Heading | This is Displayed |
|-----------------|---|
| Name | A unique reference number assigned to the DL/I call. |
| Description | The DL/I function code followed by the PCB name followed by the relative PCB number in parentheses. The location of the call in csect+offset format follows this. |
| Percent of Time | The percentage of activity measured while executing the indicated DL/I call. |

IMSDLI - IMS DL/I processing category

| Under Heading | This is Displayed |
|-----------------|--|
| Name | "IMSDLI" |
| Description | "IMS DL/I Calls." |
| Percent of Time | The percentage of activity measured in the processing of IMS DL/I calls. |

I05 - IMS DL/I CPU usage by PSB

Usage

Use this report to see the distribution of CPU usage in an IMS-dependent region. This report aggregates CPU usage by IMS PSB and is meaningful when measuring a region in which multiple IMS PSBs are scheduled (for example, an MPP region). Both IMS and non-IMS CPU usage is reported. IMS CPU usage measured during the execution of DL/I calls is reported under detail lines, which identify each of the DL/I calls. Non-DL/I call CPU usage is reported as application code or system routines.

This report is intended for measurements of IMS-dependent regions (MPP, BMP, FPP) as well as IMS batch DL/I regions.

Note:

You should not use this report to analyze CICS measurements.

Quantification

Each report line quantifies CPU usage as a percentage of the overall CPU usage observed for the measurement interval. Each quantity is expressed as a percentage representing the ratio of the number of CPU active observations for the object on the report detail line to the total number of CPU active observations in the measurement.

Detail line hierarchy

An unexpanded I05 report shows a line for each IMS PSB in which CPU usage was observed. The name field reports the PSB name. I05 reports CPU usage for which there was no IMS PSB on a separate line named NONIMS. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

```

Level 1 PSB Name or 'NONIMS'
Level 2 IMSDLI - DL/I call execution
  Level 3 DL/I call identification
    Level 4 Category
      Level 5 Load module
        Level 6 CSECT
          Level 4 SVC total
            Level 5 SVCnnn
              Level 6 Load module
                Level 7 CSECT
          Level 2 APPLCN - application code
            Level 3 Load module
              Level 4 CSECT
          Level 2 SYSTEM - system routines
            Level 3 Category
              Level 4 Load module
                Level 5 CSECT
          Level 3 SVC total
            Level 4 SVCnnn
              Level 5 Load module
                Level 6 CSECT

Level 2 NOSYMB - no load module name
Level 3 hexadecimal addresses

```

Detail line descriptions

PSB detail line

This is the first-level detail line. It aggregates activity by IMS PSB.

| Under Heading | This is Displayed |
|-----------------|--|
| Name | IMS PSB Name. NONIMS to indicate IMS activity for which no PSB has been scheduled. |
| Description | The type of IMS dependent region: BMP, MPP, IFP, etc. |
| Percent of Time | The percentage of activity measured under the indicated IMS PSB. |

Other detail lines

Other detail lines are subcategories and show objects based on observed PSW addresses. See “Detail lines for reports I05 through I13” on page 289.

Sample reports

A sample report is shown below. The report is expanded to the second level.

```

File View Navigate Help
-----
I05: IMS CPU Usage by PSB (0805/ADSMPP) Row 00001 of 00008
Command ==> _____ Scroll ==> CSR

Name      Description      Percent of CPU time * 10.00% ±10.1%
          *....1....2....3....4....5....6....7....8.
BBSFIN00  PSB in MPP region  98.98 =====
→ SYSTEM  System/OS Services  57.57 =====
→ IMSDLI  IMS DL/I Calls      30.30 =====
→ APPLCN  Application Code     10.10 =====
→ NOSYMB  No Module Name      1.01 =

NONIMS    Not IMS Execution   1.01 =
→ SYSTEM  System/OS Services  1.01 =

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|--|----------------------------------|
| ? | PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display context help information |
| ++ | PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Show additional details |
| + | PSB, DL/I call, Category, Load Module, SVC, SQL command | Expand to reveal next level |
| - | PSB, DL/I call, Category, Load Module, SVC, SQL command | Collapse to hide next level |
| SV | PSB, DL/I call, Category, SVC, SQL command | Sort next level by value |
| SN | PSB, DL/I call, Category, SVC, SQL command | Sort next level by name |
| M | Load Module, CSECT | Display load module information |
| P | Load Module, DL/I call, CSECT, SQL command | Display source program mapping |
| C01 | PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C01 report subset |
| C02 | PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C02 report subset |
| C03 | PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C03 report subset |

| Cmd | When Applied To Object | Action |
|-----|--|---------------------------|
| C08 | PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C08 report subset |
| C09 | PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C09 report subset |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|-----------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries |
| + | Description | Expand field size |
| + | Percent CPU | Zoom in scale |
| - | Name | Collapse to show only first level |
| - | Description | Reduce field size |
| - | Percent CPU | Zoom out scale |
| SV | Name | Sort next level by value |
| SN | Name | Sort next level by name |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here:

representing the ratio of the number of CPU active observations for the object on the report detail line to the total number of CPU active observations in the measurement.

Detail line hierarchy

An unexpanded I06 report shows a line for each IMS transaction in which CPU usage was observed. The name field reports the transaction code. I06 reports CPU usage for which no IMS transaction was active under a line identifying the PSB name. If no IMS PSB was active the CPU usage is reported under a line named "NONIMS." You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

```

Level 1 Trancode, PSB Name or 'NONIMS'
Level 2 IMSDLI - DL/I call execution
  Level 3 DL/I call identification
    Level 4 Category
      Level 5 Load module
        Level 6 CSECT
          Level 4 SVC total
            Level 5 SVCnnn
              Level 6 Load module
                Level 7 CSECT
Level 2 APPLCN - application code
  Level 3 Load module
    Level 4 CSECT
Level 2 SYSTEM - system routines
  Level 3 Category
    Level 4 Load module
      Level 5 CSECT
Level 3 SVC total
  Level 4 SVCnnn
    Level 5 Load module
      Level 6 CSECT

Level 2 NOSYMB - no load module name
Level 3 hexadecimal addresses
  
```

Detail line descriptions

Transaction detail line

This is the first-level detail line. It aggregates activity by IMS transaction. A PSB line is reported for any activity under IMS that is not under an IMS transaction.

| Under Heading | This is Displayed |
|-----------------|--|
| Name | IMS transaction code. |
| Description | The PSB to which the IMS transaction belongs. |
| Percent of Time | The percentage of activity measured while executing the indicated IMS transaction. |

Other detail lines

Other detail lines are subcategories and show objects based on observed PSW addresses. See "Detail lines for reports I05 through I13" on page 289.

Sample reports

A sample report is shown below. The report is expanded to the second level.

```

File View Navigate Help
-----
I06: IMS CPU Usage by Txn (0805/ADSMPP) Row 00001 of 00013
Command ==> _____ Scroll ==> CSR

Name      Description      Percent of CPU time * 10.00% ±10.1%
          *....1....2....3....4....5....6....7....8.
BBSDR000 Txn in PSB BBSFIN00 55.55 =====
→ SYSTEM System/OS Services 29.29 =====
→ IMSDLI IMS DL/I Calls 19.19 =====
→ APPLCN Application Code 6.06 ===
→ NOSYMB No Module Name 1.01 =

BBSR000 Txn in PSB BBSFIN00 43.43 =====
→ SYSTEM System/OS Services 28.28 =====
→ IMSDLI IMS DL/I Calls 11.11 =====
→ APPLCN Application Code 4.04 ==

NONIMS Not IMS Execution 1.01 =
→ SYSTEM System/OS Services 1.01 =

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|--|-----------------------------------|
| ? | TranCode, PSB, Category, DL/I call, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display context help information. |
| ++ | Trancode, PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Show additional details. |
| + | Trancode, PSB, DL/I call, Category, Load Module, SVC, SQL command | Expand to reveal next level. |
| - | Trancode, PSB, DL/I call, Category, Load Module, SVC, SQL command | Collapse to hide next level. |
| SV | Trancode, PSB, DL/I call, Category, SVC, SQL command | Sort next level by value. |
| SN | Trancode, PSB, DL/I call, Category, SVC, SQL command | Sort next level by name. |
| M | Load Module, CSECT | Display load module information. |
| P | Load Module, CSECT, DL/I call, SQL command | Display source program mapping. |
| C01 | Trancode, PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C01 report subset. |
| C02 | Trancode, PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C02 report subset. |

| Cmd | When Applied To Object | Action |
|-----|--|----------------------------|
| C03 | Trancode, PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C03 report subset |
| C08 | Category, DL/I call, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C08 report subset. |
| C09 | Trancode, PSB, Category, DL/I call, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C09 report subset. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size. |
| + | Percent CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent CPU | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| BBSDR000 Txn in PSB BBSFIN00 55.55 00000000000000000000000000000000 |
+-----+

Calculation Details
IMS DL/I call CPU measurements          55
IMS transaction                          BBSDR000
Total CPU measurements                   99
Percent of total                          55.55%

IMS Transaction Information
IMS Trancode   BBSDR000          IMS system   IMSP
PSB name       BBSFIN00         Txn count   50
Total time     10.1332          Total CPU time 0.4327

```

I07 - IMS DL/I CPU usage by DL/I call

Usage

Use this report to see the distribution of CPU usage across IMS DL/I calls. I07 reports only CPU activity that occurred during processing of DL/I calls.

This report is intended for measurements of IMS-dependent regions (MPP, BMP, FPP) as well as IMS batch DL/I regions.

Note:

You should not use this report to analyze CICS measurements.

Quantification

Each report line quantifies CPU usage as a percentage of the total CPU usage observed for all DL/I call processing. CPU usage observed outside of DL/I call processing is excluded from the calculation. Each quantity is expressed as a percentage representing the ratio of the number of CPU active observations for the object described by the report detail line to the total number of CPU active observations in DL/I call processing.

Detail line hierarchy

An unexpanded I07 report shows a line for each IMS DL/I call in which CPU usage was observed. The name field shows a sequence number assigned to each unique DL/I call. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

- Level 1** DL/I call identification
- Level 2** Category
 - Level 3** Load module
 - Level 4** CSECT
- Level 2** SVC total
 - Level 3** SVCnnn
 - Level 4** Load module
 - Level 5** CSECT

Detail line descriptions

See "Detail lines for reports I05 through I13" on page 289.

Sample reports

A sample report is shown below. The report is expanded to the second level.

```

File View Navigate Help
-----
I07: IMS CPU Usage by DL/I Call (0005/ADSMPP) Row 00001 of 00039
Command ==>> _____ Scroll ==>> CSR

Name      Description                Percent of DLI CPU time * 10.00% ±18.5%
          *....1....2....3....4....5....6....7....8.
00001     GU-IOPCB(1) BBSFIN00+0 46.66 =====
→ IMS     IMS Subsystem           33.33 =====
→ MVS     MVS System              10.00 =====
→ NOSYMB  No Module Name          3.33  ==

00006     GHU-DBSTL001(13) BBSAP  6.66  ===
→ IMS     IMS Subsystem           3.33  ==
→ SVC     SVC Routines            3.33  ==

00018     REPL-DBSCN001(4) BBSAP  6.66  ===
→ IMS     IMS Subsystem           6.66  ===

00002     DBSCA001(10) BBSAP      6.66  ===
→ SVC     SVC Routines            6.66  ===

00009     DBSCN001(4) BBSAP       6.66  ===
→ IMS     IMS Subsystem           6.66  ===

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|---|-----------------------------------|
| ? | DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display context help information. |
| ++ | DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Show additional details. |
| + | DL/I call, Category, Load Module, SVC, SQL command | Expand to reveal next level. |
| - | DL/I call, Category, Load Module, SVC, SQL command | Collapse to hide next level. |
| SV | DL/I call, Category, SVC, SQL command | Sort next level by value. |
| SN | DL/I call, Category, SVC, SQL command | Sort next level by name. |
| M | Load Module, CSECT | Display load module information. |
| P | CSECT, DL/I call, SQL command | Display source program mapping. |
| C01 | DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C01 report subset. |
| C02 | DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C02 report subset. |

| Cmd | When Applied To Object | Action |
|-----|---|----------------------------|
| C03 | DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C03 report subset |
| C08 | DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C08 report subset. |
| C09 | Category, DL/I call, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C09 report subset. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size. |
| + | Percent CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent CPU | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| 00001  GU-IOPCB(1) BBSFIN00+0 46.66 000000000000000000000000 |
+-----+

Calculation Details
IMS DL/I call CPU measurements          14
Total CPU measurements                   30
Percent of total                         46.66%

DL/I Call Information
Function code  GU                PSB Name      BBSFIN00
PCB Name      IOPCB              IMS Id-Region  IMSP-ADSMPP
PCB Number    1                  Call type     CBLTDLI
CSECT/module  BBSFIN00 in BBSFIN00  Offset of call 0000038C
Sample count  10                  Call count    60
DLI CPU time  0.14                 Service time   0.19

```

I08 - IMS DL/I WAIT time by PSB

Usage

Use this report to identify any delays caused by wait conditions in IMS regions. This report shows wait time by IMS PSB and is meaningful when measuring a region in which multiple IMS PSBs are scheduled (for example, a MPP region). Only wait time observed when an IMS PSB is active is reported. Wait time is identified both within the processing of DL/I calls and outside of DL/I call processing.

This report is intended for measurements of IMS-dependent regions (MPP, BMP, FPP) and IMS batch DL/I regions.

Note:

You should not use this report to analyze CICS measurements.

Quantification

Each report line quantifies wait time as a percentage of the overall time IMS PSBs were active. Each quantity is expressed as a percentage representing the ratio of the number of samples in which the active IMS program was waiting to the total number of samples IMS programs were active. Any time when no IMS programs were active is excluded. This ensures that quantifications are not distorted by inactive intervals such as those that occur between scheduled transactions.

Detail line hierarchy

An unexpanded I08 report shows a line for each IMS PSB that was observed. The name field reports the PSB name. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

- Level 1** PSB Name or 'NONIMS'
- Level 2** IMSDLI - DL/I call execution
 - Level 3** DL/I call identification
 - Level 4** Category
 - Level 5** Load module
 - Level 6** CSECT
 - Level 4** SVC total
 - Level 5** SVCnnn
 - Level 6** Load module
 - Level 7** CSECT
- Level 2** APPLCN - application code
 - Level 3** Load module
 - Level 4** CSECT
- Level 2** SYSTEM - system routines
 - Level 3** Category
 - Level 4** Load module
 - Level 5** CSECT
 - Level 3** SVC total
 - Level 4** SVCnnn
 - Level 5** Load module
 - Level 6** CSECT

- Level 2** NOSYMB - no load module name
- Level 3** hexadecimal addresses

Detail line descriptions

PSB detail line

This is the first-level detail line. It aggregates activity by IMS transaction.

| Under Heading | This is Displayed |
|-----------------|--|
| Name | IMS PSB Name. NONIMS to indicate IMS activity for which no PSB has been scheduled. |
| Description | The type of IMS dependent region: BMP, MPP, IFP, etc. |
| Percent of Time | The percentage of activity measured under the indicated IMS PSB. |

Other detail lines

Other detail lines are subcategories and show objects based on observed PSW addresses. See “Detail lines for reports I05 through I13” on page 289.

Sample reports

A sample report is shown below. The report is expanded to the third level.

```

File View Navigate Help
-----
I08: IMS WAIT Time by PSB (0805/ADSMPP) Row 00001 of 00020
Command ==>> Scroll ==>> CSR
Name Description Percent of Time * 10.00% #3.5
*...1...2...3...4...5...6...7...8
BBSFIN00 PSB in MPP region 82.42 =====
-> IMSDL1 IMS DL/I Calls 73.24 =====
-> 00012 GHU-DBSCN001(4) BB 35.15 =====
-> 00003 GHU-DBSCN001(4) BB 33.37 =====
-> 00011 GHU-DBSCA001(10) B 1.91 ==
-> 00002 GHU-DBSCA001(10) B 1.78 ==
-> 00015 GHU-DBSTL001(13) B 0.25
-> 00018 REPL-DBSCN001(4) B 0.25
-> 00001 GU-IOPCB(1) BBSFIN 0.25
-> 00006 GHU-DBSTL001(13) B 0.12
-> 00007 ISRT-DBSTL001(13) 0.12
-> SYSTEM System/OS Services 5.60 ====
-> SVC SVC Routines 5.35 ====
-> LERUNLIB Language Environme 0.25
-> APPLCN Application Code 3.56 ===
-> BKN00SUP Application Progra 1.65 =
-> BKN00102 Application Progra 1.14 =
-> BKN00101 Application Progra 0.38
-> BKN00103 Application Progra 0.25
-> BKN00111 Application Progra 1.12 =
  
```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|--|-----------------------------------|
| ? | PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display context help information. |

| Cmd | When Applied To Object | Action |
|-----|--|----------------------------------|
| ++ | PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Show additional details. |
| + | PSB, DL/I call, Category, Load Module, SVC, SQL command | Expand to reveal next level. |
| - | PSB, DL/I call, Category, Load Module, SVC, SQL command | Collapse to hide next level. |
| SV | PSB, DL/I call, Category, SVC, SQL command | Sort next level by value. |
| SN | PSB, DL/I call, Category, SVC, SQL command | Sort next level by name. |
| M | Load Module, CSECT | Display load module information. |
| P | Load Module, CSECT, DL/I call, SQL command | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size. |
| + | Percent CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent CPU | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here:

Detail line hierarchy

An unexpanded I09 report shows a line for each IMS transaction observed. The name field reports the transaction code. In the event that no IMS transaction was active but a PSB was active, the PSB will be identified in the report line. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

- Level 1** Trancode, PSB Name or 'NONIMS'
- Level 2** IMSDLI - DL/I call execution
 - Level 3** DL/I call identification
 - Level 4** Category
 - Level 5** Load module
 - Level 6** CSECT
 - Level 4** SVC total
 - Level 5** SVCnnn
 - Level 6** Load module
 - Level 7** CSECT
 - Level 2** APPLCN - application code
 - Level 3** Load module
 - Level 4** CSECT
 - Level 2** SYSTEM - system routines
 - Level 3** Category
 - Level 4** Load module
 - Level 5** CSECT
 - Level 3** SVC total
 - Level 4** SVCnnn
 - Level 5** Load module
 - Level 6** CSECT

- Level 2** NOSYMB - no load module name
 - Level 3** hexadecimal addresses

Detail line descriptions

Transaction detail line

This is the first-level detail line. It aggregates activity by IMS transaction. For any activity under IMS which is not under an IMS transaction a PSB line is reported.

| Under Heading | This is Displayed |
|-----------------|--|
| Name | IMS transaction code. |
| Description | The PSB to which the IMS transaction belongs. |
| Percent of Time | The percentage of activity measured while executing the indicated IMS transaction. |

Other detail lines

Other detail lines are subcategories and show objects based on observed PSW addresses. See "Detail lines for reports I05 through I13" on page 289.

Sample reports

A sample report is shown below. The report is expanded to the third level.

```

File View Navigate Help
-----
I09: IMS WAIT Time by TXn (0805/ADSMPP) Row 00001 of 00026
Command ==>> _____ Scroll ==>> CSR

Name      Description      Percent of Time * 10.00% ±3.5
*...1...2...3...4...5...6...7...8
BBSDR000  Txn in PSB BBSFIN00  42.80 =====
→ IMSDLI  IMS DL/I Calls      35.54 =====
→ 00003   GHU-DBSCN001(4) BB  33.37 =====
→ 00002   GHU-DBSCA001(10) B  1.78 ==
→ 00006   GHU-DBSTL001(13) B  0.12
→ 00001   GU-IOPCB(1) BBSFIN  0.25
→ 00007   ISRT-DBSTL001(13)  0.12
→ SYSTEM  System/OS Services  3.69 ===
→ SVC     SVC Routines        3.43 ===
→ LERUNLIB Language Environme  0.25
→ APPLCN  Application Code     3.56 ===
→ BKN00SUP Application Progra   1.65 =
→ BKN00102 Application Progra  1.14 =
→ BKN00101 Application Progra  0.38
→ BKN00103 Application Progra  0.25
→ BKN00111 Application Progra  1.12 =

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|--|-----------------------------------|
| ? | Trancode, PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display context help information. |
| ++ | Trancode, PSB, Category, DL/I call, Load Module, SVC, CSECT, SQL command, Unresolved Address | Show additional details. |
| + | Trancode, PSB, Category, DL/I call, Load Module, SVC, CSECT, SQL command | Expand to reveal next level. |
| - | Trancode, PSB, Category, DL/I call, Load Module, SVC, SQL command | Collapse to hide next level. |
| SV | Trancode, PSB, Category, DL/I call, Load Module, SVC, SQL command | Sort next level by value. |
| SN | Trancode, PSB, Category, DL/I call, Load Module, SVC, SQL command | Sort next level by name. |
| M | Load Module, CSECT | Display load module information. |
| P | Load Module, CSECT, DL/I call, SQL command | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size. |
| + | Percent CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent CPU | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| BBSDR000 Txn in PSB BBSFIN00  42.80 00000000000000000000 |
+-----+

Calculation Details
  IMS DL/I call wait time measurements      336
  IMS transaction                          BBSDR000
  Total measurements                        785
  Percent of total                          42.80%

IMS Transaction Information
  IMS Trancode   BBSDR000           IMS system   IMSP
  PSB name      BBSFIN00           Txn count   50
  Total time    10.1332           Total CPU time 0.4327
  
```

I10 - IMS DL/I WAIT time by DL/I call

Usage

Use this report to identify delays caused by wait conditions in specific DL/I calls. This report is intended for measurements of IMS-dependent regions (MPP, BMP, FPP) as well as IMS batch DL/I regions.

Note:

You should not use this report to analyze CICS measurements.

Quantification

Each report line quantifies wait time as a percentage of the total time observed for all DL/I call processing. Time observed outside of DL/I call processing is excluded from the calculation. Each quantity is expressed as a percentage representing the ratio of the number of wait samples for the object described by the report detail line to the total number of samples in DL/I call processing.

Detail line hierarchy

An unexpanded I10 report shows a line for each IMS DL/I call. The name field shows a sequence number assigned to each unique DL/I call. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

```

Level 1 DL/I call identification
Level 2 Category
Level 3 Load module
Level 4 CSECT
Level 2 SVC total
Level 3 SVCnnn
Level 4 Load Module
Level 5 CSECT
  
```

Detail line descriptions

See “Detail lines for reports I05 through I13” on page 289.

Sample reports

A sample report is shown below. The report is expanded to the third level.

```

File View Navigate Help
-----
I10: IMS WAIT Time by DL/I Call (0805/ADSMPP) Row 00001 of 00037
Command ==> _____ Scroll ==> CSR

Name      Description                               Percent of Time * 10.00% ±4.0
*...1...2...3...4...5...6...7...8
00012    GHU-DBSCN001(4) BBSAP0  45.17 =====
→ IMS    IMS Subsystem           45.17 =====
→ DFSREP00 IMS Dispatcher Int 45.17 =====

00003    GHU-DBSCN001(4) BBSAP0  42.88 =====
→ IMS    IMS Subsystem           42.88 =====
→ DFSREP00 IMS Dispatcher Int 42.71 =====
→ DBFDEDB0 IMS Module         0.16

00011    GHU-DBSCA001(10) BBSAP  2.45 ==
→ IMS    IMS Subsystem           2.45 ==
→ DBFDEDB0 IMS Module         2.45 ==

00002    GHU-DBSCA001(10) BBSAP  2.29 ==
→ IMS    IMS Subsystem           2.29 ==
→ DBFDEDB0 IMS Module         2.29 ==
  
```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|---|-----------------------------------|
| ? | DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display context help information. |
| ++ | DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Show additional details. |

| Cmd | When Applied To Object | Action |
|-----|--|----------------------------------|
| + | DL/I call, Category, Load Module, SVC, SQL command | Expand to reveal next level. |
| - | DL/I call, Category, Load Module, SVC, SQL command | Collapse to hide next level. |
| SV | DL/I call, Category, SVC, SQL command | Sort next level by value. |
| SN | DL/I call, Category, SVC, SQL command | Sort next level by name. |
| M | Load Module, CSECT | Display load module information. |
| P | DL/I call, CSECT, SQL command | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size. |
| + | Percent CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent CPU | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| 00012   GHU-DBSCN001(4) BBSAP0 45.17 000000000000000000000000 |
+-----+

Calculation Details
IMS DL/I call wait time measurements      276
Total measurements                        611
Percent of total                          45.17%

DL/I Call Information
Function code  GHU                PSB Name      BBSFIN00
PCB Name      DBSCN001            IMS Id-Region IMSP-ADSMPP
PCB Number    4                  Call type    CBLTDLI
CSECT/module  BBSAP011 in BBSAP011  Offset of call 00000E68
Sample count  277                 Call count    49
DLI CPU time  0.02                Service time   8.21

SSA/FSA      01 SBSCNTL (CNTLNUM =...)
+-----+

```

I11 - IMS DL/I activity by PSB

Usage

Use this report to see how time is consumed in IMS-dependent regions. All time is reported regardless of whether the time is CPU usage or wait. This report shows activity by IMS PSB and is meaningful when measuring a region in which multiple IMS PSBs are scheduled (for example, a MPP region). Only time observed while an IMS PSB was active is reported. Time is identified both within the processing of DL/I calls and outside of DL/I call processing but only when an IMS PSB is active.

This report is intended for measurements of IMS-dependent regions (MPP, BMP, FPP) as well as IMS batch DL/I regions.

Note:

You should not use this report to analyze CICS measurements.

Quantification

Each report line quantifies time as a percentage of the overall time IMS PSBs were active. Each quantity is expressed as a percentage representing the ratio of the number of samples in which the active IMS program was observed compared to the total number of samples IMS programs were active. Any time when no IMS programs were active is excluded. This ensures that quantifications are not distorted by inactive intervals such as those that occur between scheduled transaction.

Detail line hierarchy

An unexpanded I11 report shows a line for each IMS PSB in which activity was observed. The name field reports the PSB name. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

- Level 1** Trancode, PSB Name or 'NONIMS'
- Level 2** IMSDLI - DL/I call execution
 - Level 3** DL/I call identification
 - Level 4** Category
 - Level 5** Load module
 - Level 6** CSECT
 - Level 4** SVC total
 - Level 5** SVCnnn
 - Level 6** Load module
 - Level 7** CSECT
- Level 2** APPLCN - application code
 - Level 3** Load module
 - Level 4** CSECT
- Level 2** SYSTEM - system routines
 - Level 3** Category
 - Level 4** Load module
 - Level 5** CSECT
 - Level 3** SVC total
 - Level 4** SVCnnn
 - Level 5** Load module
 - Level 6** CSECT

- Level 2** NOSYMB - no load module name
- Level 3** hexadecimal addresses

Detail line descriptions

PSB detail line

This is the first-level detail line. It aggregates activity by IMS transaction.

| Under Heading | This is Displayed |
|-----------------|--|
| Name | IMS PSB Name. NONIMS to indicate IMS activity for which no PSB has been scheduled. |
| Description | The type of IMS dependent region: BMP, MPP, IFP, etc. |
| Percent of Time | The percentage of activity measured under the indicated IMS PSB. |

Other detail lines

Other detail lines are subcategories and show objects based on observed PSW addresses. See “Detail lines for reports I05 through I13” on page 289.

Sample reports

A sample report is shown below. The report is expanded to the third level.

```

File View Navigate Help
-----
I11: IMS DL/I Activity by PSB (0805/ADSMPP) Row 00001 of 00034
Command ==> _____ Scroll ==> CSR

Name      Description      Percent of Time * 10.00% ±3.5
*....1....2....3....4....5....6....7....8
-----
BBSFIN00  PSB in MPP region 100.00 =====
→ IMSDLI  IMS DL/I Calls    77.83 =====
  → 00012  GHU-DBSCN001(4) BB 35.28 =====
  → 00003  GHU-DBSCN001(4) BB 33.50 =====
  → 00001  GU-IOPCB(1) BBSFIN 2.29 ==
  → 00002  GHU-DBSCA001(10) B 2.16 ==
  → 00011  GHU-DBSCA001(10) B 1.91 ==
  → 00018  REPL-DBSCN001(4) B 0.50
  → 00006  GHU-DBSTL001(13) B 0.38
  → 00015  GHU-DBSTL001(13) B 0.38
  → 00009  REPL-DBSCN001(4) B 0.38
  → 00007  ISRT-DBSTL001(13) 0.38
  → 00004  GHU-DBSCA002(11) B 0.12
  → 00017  REPL-DBSCA001(10) 0.12
  → 00013  GHU-DBSCA002(11) B 0.12
  → 00008  REPL-DBSCA001(10) 0.12
  → 00010  ISRT-IOPCB(1) BBSF 0.12
→ SYSTEM  System/OS Services 16.94 =====
  → SVC    SVC Routines        15.28 =====
  → LERUNLIB Language Environme 1.14 ==
  → MVS    MVS System          0.50
→ APPLCN  Application Code     5.09 ===
  → BKN00SUP Application Progra 2.03 ==
  → BKNCSI02 Application Progra 1.27 ==
  → BKNCSI01 Application Progra 0.38
  
```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|--|-----------------------------------|
| ? | PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display context help information. |
| ++ | PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Show additional details. |
| + | PSB, DL/I call, Category, Load Module, SVC, SQL command | Expand to reveal next level. |
| - | PSB, DL/I call, Category, Load Module, SVC, SQL command | Collapse to hide next level. |
| SV | PSB, DL/I call, Category, SVC, SQL command | Sort next level by value. |
| SN | PSB, DL/I call, Category, SVC, SQL command | Sort next level by name. |
| M | Load Module, CSECT | Display load module information. |
| P | DL/I call, CSECT, SQL command | Display source program mapping. |
| C01 | PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C01 report subset. |
| C02 | PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C02 report subset. |
| C03 | PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C03 report subset |
| C08 | PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C08 report subset. |
| C09 | PSB, DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C09 report subset. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size. |
| + | Percent CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent CPU | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here:

```
File View Navigate Help
+-----+
+----- The following report line was selected -----+
| > 00012   GHU-DBSCN001(4) BB 35.28 000000000000000000 |
+-----+

Calculation Details
IMS DL/I call activity measurements      277
Total measurements                       785
Percent of total                         35.28%

DL/I Call Information
Function code   GHU                PSB Name      BBSFIN00
PCB Name       DBSCN001            IMS Id-Region IMSP-ADSMPP
PCB Number     4                   Call type     CBLTDLI
CSECT/module   BBSAP011 in BBSAP011 Offset of call 00000E68
Sample count   277                 Call count    49
DLI CPU time   0.02                Service time   8.21

SSA/FSA       01 SBSCNTL (CNTLNUM =...)
```

I12 - IMS DL/I activity by transaction

Usage

Use this report to see how time is consumed in IMS-dependent regions. All time is reported regardless of whether the time is CPU usage or wait. This report shows activity by IMS transaction and is meaningful when measuring a region in which multiple IMS transactions are scheduled (for example, a MPP region). Only time observed while an IMS PSB was active is reported. Time is identified both within the processing of DL/I calls and outside of DL/I call processing but only when an IMS PSB is active.

This report is intended for measurements of IMS-dependent regions (MPP, BMP, FPP) as well as IMS batch DL/I regions.

Note:

You should not use this report to analyze CICS measurements.

Quantification

Each report line quantifies time as a percentage of the overall time IMS PSBs were active. Each quantity is expressed as a percentage representing the ratio of the number of samples in which the active IMS program was observed compared to the total number of samples IMS programs were active. Any time when no IMS programs were active is excluded. This ensures that quantifications are not distorted by inactive intervals such as those that occur between scheduled transaction.

Detail line hierarchy

An unexpanded I12 report shows a line for each IMS transaction observed. The name field reports the transaction code. In the event that no IMS transaction was

active but a PSB was active, the PSB will be identified in the report line. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

```

Level 1 Trancode, PSB Name or 'NONIMS'
Level 2 IMSDLI - DL/I call execution
  Level 3 DL/I call identification
    Level 4 Category
      Level 5 Load module
        Level 6 CSECT
      Level 4 SVC total
        Level 5 SVCnnn
          Level 6 Load module
            Level 7 CSECT
    Level 2 APPLCN - application code
      Level 3 Load module
        Level 4 CSECT
    Level 2 SYSTEM - system routines
      Level 3 Category
        Level 4 Load module
          Level 5 CSECT
      Level 3 SVC total
        Level 4 SVCnnn
          Level 5 Load module
            Level 6 CSECT
  
```

```

Level 2 NOSYMB - no load module name
Level 3 hexadecimal addresses
  
```

Detail line descriptions

Transaction detail line

This is the first-level detail line. It aggregates activity by IMS transaction. A PSB line is reported for any activity under IMS that is not under an IMS transaction.

| Under Heading | This is Displayed |
|-----------------|--|
| Name | IMS transaction code |
| Description | The PSB to which the IMS transaction belongs. |
| Percent of Time | The percentage of activity measured while executing the indicated IMS transaction. |

Other detail lines

Other detail lines are subcategories and show objects based on observed PSW addresses. See “Detail lines for reports I05 through I13” on page 289.

Sample reports

A sample report is shown below. The report is expanded to the third level.

```

File View Navigate Help
-----
I12: IMS DL/I Activity by Txn (0805/ADSMPP) Row 00001 of 00046
Command ==> _____ Scroll ==> CSR

Name      Description      Percent of Time * 10.00% ±3.5
*....1....2....3....4....5....6....7....8
-----
BBSDR000  Txn in PSB BBSFIN00  52.48 =====
→ IMSDLI  IMS DL/I Calls      38.47 =====
→ 00003   GHU-DBSCN001(4) BB  33.50 =====
→ 00002   GHU-DBSCA001(10) B  2.16 ==
→ 00001   GU-IOPCB(1) BBSFIN  1.27 ==
→ 00006   GHU-DBSTL001(13) B  0.38
→ 00009   REPL-DBSCN001(4) B  0.38
→ 00007   ISRT-DBSTL001(13)  0.38
→ 00004   GHU-DBSCA002(11) B  0.12
→ 00008   REPL-DBSCA001(10)  0.12
→ 00010   ISRT-IOPCB(1) BBSF  0.12
→ SYSTEM  System/OS Services  9.29 =====
→ SVC     SVC Routines        8.53 =====
→ LERUNLIB Language Environme  0.50
→ MVS     MVS System          0.25
→ APPLCN  Application Code     4.58 ==
→ BKN00SUP Application Progra   2.03 ==
→ BKNCS102 Application Progra  1.14 ==

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|--|-----------------------------------|
| ? | Trancode, PSB, Category, DL/I call, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display context help information. |
| ++ | Trancode, PSB, Category, DL/I call, Load Module, SVC, CSECT, SQL command, Unresolved Address | Show additional details. |
| + | Trancode, PSB, Category, DL/I call, Load Module, SVC, SQL command | Expand to reveal next level. |
| - | Trancode, PSB, Category, DL/I call, Load Module, SVC, SQL command | Collapse to hide next level. |
| SV | Trancode, PSB, Category, DL/I call, Load Module, SVC, SQL command | Sort next level by value. |
| SN | Trancode, PSB, Category, DL/I call, Load Module, SVC, SQL command | Sort next level by name. |
| M | Load Module, CSECT | Display load module information. |
| P | Load Module, CSECT, DL/I call, SQL command | Display source program mapping. |
| C01 | Trancode, PSB, Category, DL/I call, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C01 report subset. |

| Cmd | When Applied To Object | Action |
|-----|--|----------------------------|
| C02 | Trancode, PSB, Category, DL/I call, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C02 report subset. |
| C03 | Trancode, PSB, Category, DL/I call, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C03 report subset |
| C08 | Category, DL/I call, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C08 report subset. |
| C09 | Trancode, PSB, Category, DL/I call, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C09 report subset. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size. |
| + | Percent CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent CPU | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| BBSDR000 Txn in PSB BBSFIN00  52.48 00000000000000000000000000000000 |
+-----+

Calculation Details
  IMS DL/I call activity measurements      412
  IMS transaction                          BBSDR000
  Total measurements                        785
  Percent of total                          52.48%

IMS Transaction Information
  IMS Trancode   BBSDR000           IMS system   IMSP
  PSB name       BBSFIN00           Txn count   50
  Total time     10.1332             Total CPU time 0.4327
+-----+

```

I13 - IMS DL/I activity by DL/I call

Usage

Use this report to see how time is consumed in IMS-dependent regions by specific DL/I calls. All time is reported regardless of whether the time is CPU usage or wait.

This report is intended for measurements of IMS-dependent regions (MPP, BMP, FPP) as well as IMS batch DL/I regions.

Note:

You should not use this report to analyze CICS measurements.

Quantification

Each report line quantifies time as a percentage of the total time observed for all DL/I call processing. Time observed outside of DL/I call processing is excluded from the calculation. Each quantity is expressed as a percentage representing the ratio of the number of samples for the object described by the report detail line to the total number of samples in DL/I call processing.

Detail line hierarchy

An unexpanded I13 report shows a line for each IMS DL/I call. The name field shows a sequence number assigned to each unique DL/I call. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

- Level 1** DL/I call identification
- Level 2** Category
 - Level 3** Load module
 - Level 4** CSECT
- Level 2** SVC total
 - Level 3** SCVnnn
 - Level 4** Load module
 - Level 5** CSECT

Detail line descriptions

See "Detail lines for reports I05 through I13" on page 289.

Sample reports

A sample report is shown below. The report is expanded to the third level.

```

File View Navigate Help
-----
I13: DL/I Activity by DL/I Call (0005/ADSMPP) Row 00001 of 00089
Command ==>> _____ Scroll ==>> CSR

Name      Description                Percent of DLI Time * 10.00% ±4.0
*....1....2....3....4....5....6....7....8
00012     GHU-DBSCN001(4) BBSAP0 45.33 =====
→ IMS     IMS Subsystem                45.33 =====
  → DFSREP00 IMS Dispatcher Int 45.17 =====
  → DFSLMGR0 IMS Global Lock Ma 0.16

00003     GHU-DBSCN001(4) BBSAP0 43.04 =====
→ IMS     IMS Subsystem                42.88 =====
  → DFSREP00 IMS Dispatcher Int 42.71 =====
  → DBFDEDB0 IMS Module                0.16
→ SVC     SVC Routines                 0.16
  → SVC138   PGSER                       0.16

00001     GU-IOPCB(1) BBSFIN00+0 2.94 ==
→ IMS     IMS Subsystem                2.29 ==
  → DFSREP00 IMS Dispatcher Int 0.65
  → DBFSYNC0 IMS Module                0.49
  → DFSQGU00 IMS Module                0.32

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|---|-----------------------------------|
| ? | DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display context help information. |
| ++ | DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Show additional details. |
| + | DL/I call, Category, Load Module, SVC, SQL command | Expand to reveal next level. |
| - | DL/I call, Category, Load Module, SVC, SQL command | Collapse to hide next level. |
| SV | DL/I call, Category, Load Module, SVC, SQL command | Sort next level by value. |
| SN | DL/I call, Category, Load Module, SVC, SQL command | Sort next level by name. |
| M | Load Module, CSECT | Display load module information. |
| P | DL/I call, CSECT, SQL command | Display source program mapping. |
| C01 | DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C01 report subset. |
| C02 | DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C02 report subset. |

| Cmd | When Applied To Object | Action |
|-----|---|----------------------------|
| C03 | DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C03 report subset |
| C08 | DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C08 report subset. |
| C09 | DL/I call, Category, Load Module, SVC, CSECT, SQL command, Unresolved Address | Display C09 report subset. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size. |
| + | Percent CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent CPU | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| 00012   GHU-DBSCN001(4) BBSAP0 45.33 00000000000000000000 |
+-----+

Calculation Details
IMS DL/I call activity measurements      277
Total measurements                       611
Percent of total                         45.33%

DL/I Call Information
Function code   GHU                PSB Name      BBSFIN00
PCB Name       DBSCN001            IMS Id-Region  IMSP-ADSMPP
PCB Number     4                  Call type     CBLTDLI
CSECT/module   BBSAP011 in BBSAP011  Offset of call 00000E68
Sample count   277                  Call count    49
DLI CPU time   0.02                Service time   8.21

SSA/FSA        01 SBSCNTL (CNTLNUM =...)

```

I14 - IMS PSB/PCB attributes

Usage

This report is intended primarily for use when analyzing measurements using printed reports. Use I14 to look up detailed information about PSBs (and their PCBs) referred to by detail lines in other reports. When analyzing data in interactive mode, you can look up this information by pressing the ENTER key (or entering the “++” line command) on any detail line that refers to the PSB.

Detail line descriptions

PSB information

The following information is reported for each PSB:

| Under Heading | This is Displayed |
|---------------|--|
| PSB Name | The name of the PSB. |
| IMS System | The system ID of the IMS subsystem. This information might not be available for a CICS measurement. |
| No. of PCBs | The number of PCBs in the PSB. This information is available only if the IMS+ measurement option was enabled. |
| LIST=NO PCBs | The number of PCBs in the PSB defined with the LIST=NO option. These PCBs are not visible to the application in the PSB list passed by IMS. They are accessed by symbolic name using the AIB interface. This information is available only if the IMS+ measurement option was enabled. |
| Txn Count | The number of IMS transactions under this PSB counted during the measurement. This information is available only if the IMS+ measurement option was enabled. |
| DL/I calls | The number of DL/I calls executed under this PSB during the measurement. This information is available only if the IMS+ measurement option was enabled. |
| Sample count | The number of times execution under this PSB was sampled. |

PCB information

The PCBs are listed if the IMS+ measurement option was enabled.

| Under Heading | This is Displayed |
|---------------|--|
| PSBNum | The relative PCB number. |
| Name | The symbolic name of the PCB defined in the label field of the PCB macro. |
| Type | TP or DB indicates a data communications or data base PCB. |
| DBD/LTRM | The data base name for a data base PCB. The PCB LTERM parameter value for a data communications PCB. |
| PROCOPT | The processing options for a data base PCB. |
| LIST | Indicates whether the PCB was defined as LIST=YES or LIST=NO. |

Sample reports

A sample report is shown below.

```

File View Navigate Help
-----
I14: IMS PSB/PCB Attributes (0805/ADSMPP) Row 00001 of 00036
Command ==>> _____ Scroll ==>> CSR

IMS PSB Information for PSBName BBSFIN00

PSB Name      BBSFIN00          IMS system      IMSP
No.of PCBs    27                 LIST=NO PCBs   12
Txn count     99                DL/I calls     1010
Sample count  611

PCBNum  Name   Type  DBD/LTRM  PROCOPT  LIST
-----  ---   ---   ---      ---      ---
1       IOPCB  TP    DBD/LTRM  A        YES
2       ALT1   TP    DBD/LTRM  A        YES
3       ALT2   TP    DBD/LTRM  A        YES
4       DBSCN001 DB    DBSCN000  A        YES
5       DBSCN002 DB    DBSCN000  A        YES
6       DBSCN003 DB    DBSCN000  A        YES
7       DBSCI001 DB    DBSCI000  A        YES
8       DBSCI002 DB    DBSCI000  A        YES
9       DBSCI003 DB    DBSCI000  A        YES
10      DBSCA001 DB    DBSCA000  A        YES
11      DBSCA002 DB    DBSCA000  A        YES
12      DBSCA003 DB    DBSCA000  A        YES
13      DBSTL001 DB    DBSTL000  A        YES
14      DBSTL002 DB    DBSTL000  A        YES
15      DBSTL003 DB    DBSTL000  A        YES
16      DBSCNA01 DB    DBSCN000  A        NO
17      DBSCNA02 DB    DBSCN000  A        NO
18      DBSCNA03 DB    DBSCN000  A        NO

```

I15 - IMS DL/I call attributes

Usage

This report is intended primarily for use when analyzing measurements using printed reports. Use I15 to look up detailed information about DL/I calls referred to by detail lines in other reports. When analyzing data in interactive mode, you can look up this information by pressing the ENTER key (or entering the “++” line command) on any detail line that refers to the DL/I call.

Detail line descriptions

DL/I call information

The following information is reported for each DL/I call:

| Under Heading | This is Displayed |
|---------------|---|
| DL/I Call ID | A unique reference number assigned to the call. |
| Function Code | The DL/I function code. |
| PSB Name | The name of the PSB under which all occurrences of this DL/I call executed. |
| PCB Name | The name of the PCB referenced by the DL/I call. |
| IMS ID-Region | The ID of the IMS subsystem and the name of the IMS-dependent region. |
| PCB Number | The relative PCB number in its PSB. |

| Under Heading | This is Displayed |
|----------------|--|
| Call Type | The language interface used by the call: <ASMTDLI, CBLTDLI, etc.> was sampled. |
| CSECT/Module | The CSECT name and load module of the DL/I call. |
| Offset of call | The offset in the CSECT of the call. |
| Sample count | The number of times activity in this DL/I call was sampled. |
| Call count | The number of occurrences of this DL/I call observed. This information is available only if the IMS+ measurement option was enabled. |
| DL/I CPU time | The number of seconds of CPU time consumed by all occurrences of the DL/I call. This information is available only if the IMS+ measurement option was enabled. |
| Service time | The number of seconds of service time for all occurrences of the DL/I call. This information is available only if the IMS+ measurement option was enabled. |

Sample reports

A sample report is shown below.

```

File View Navigate Help
-----
I15: IMS DL/I Call Attributes (0805/ADSMPP) Row 00001 of 0192
Command ==> _____ Scroll ==> CSR

DL/I Call Id 00001

Function code  GU          PSB Name      BBSFIN00
PCB Name      IOPCB        IMS Id-Region IMSP-ADSMPP
PCB Number    1              Call type     CBLTDLI
CSECT/module  BBSFIN00 in BBSFIN00 Offset of call 0000038C
Sample count  9              Call count    60
DL/I CPU time 0.14          Service time   0.19

DL/I Call Id 00002

Function code  GHU          PSB Name      BBSFIN00
PCB Name      DBSCA001     IMS Id-Region IMSP-ADSMPP
PCB Number    10           Call type     CBLTDLI
CSECT/module  BBSAP012 in BBSAP012 Offset of call 00000E0E
Sample count  16           Call count    50
DLI CPU time  0.04        Service time   0.66

SSA/FSA      01 SBSABAS (ACCTNUM =...)

```

I16 - IMS transaction service times

Usage

Use this report to see information about IMS transaction service times. This report is meaningful only when measuring an IMS-dependent region in which transactions are executed. The IMS+ feature must have been enabled when the measurement was performed.

Quantification

Use this report to see information about IMS transaction service times. This report is meaningful only when measuring an IMS-dependent region in which transactions are executed. The IMS+ feature must have been enabled when the measurement was performed.

Detail line hierarchy

The I16 report shows one detail line level. It cannot be expanded.

Detail line descriptions

The following information is reported for each DL/I call:

| Under Heading | This is Displayed |
|---------------|---|
| TranCode | The IMS transaction code. |
| PSB/PGM | The name of the PSB and program. |
| Counts: Txns | The number of executions of the transaction that occurred during the measurement interval. |
| Counts: Fetch | The number of times the program was fetched by IMS. In general, the program is fetched when the transaction is scheduled. The number of fetches of the program is also affected by the limit count value for the transaction. A high fetch count could mean that a performance improvement might be realized by raising the limit count or pre-loading the program. |
| Counts: Sched | The number of times the program was scheduled for successive executions of the transaction. This is the count of sets of consecutive transaction executions that occurred before QC status was returned to the GU-IOPCB call. |
| Total Time | The total execution time of the transaction during the measurement interval. |
| Avg/Txn | The average execution time for the transaction based on the measurement interval. |
| CPU Time | The total CPU time consumed by all executions of the transaction during the measurement interval. |

Sample reports

A sample report is shown below.

```

File View Navigate Help
-----
I16: IMS Transaction Service Times (0805/ADSMPP) Row 00001 of 0002
Command ==> _____ Scroll ==> CSR
-----
TranCode   PSB/PGM   Counts   Times (secs)
Txns  Fetch  Sched  Total Time  Avg/Txn  CPU Time
-----
BBSDR000  BBSFIN00  50    20    20    10.133    0.202    0.432
BBSCR000  BBSFIN00  49    20    20     9.438    0.192    0.407

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Trancode | Display context help information. |
| ++ | Trancode | Show additional details. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here:

```
File View Navigate Help
+-----+
+----- The following report line was selected -----+
| BBSDR000  BBSFIN00  50  20  20  10.133  0.202  0.432 |
+-----+

IMS Transaction Information
IMS Trancode  BBSDR000          IMS system  IMSP
PSB name     BBSFIN00          Txn count  50
Total time   10.1332          Total CPU time 0.4327
```

I17 - IMS transaction DL/I call counts

Usage

Use this report to see information about the number of DL/I calls issued by each of the measured IMS transactions. This report is meaningful only when measuring an IMS-dependent region in which transactions are executed. The IMS+ feature must have been enabled when the measurement was performed.

Quantification

Each report line shows information pertaining to one IMS transaction.

Detail line hierarchy

An unexpanded I17 report shows a line for each IMS transaction code for which transaction execution was observed. You can expand each line to reveal one additional hierarchical level of detail. The hierarchy is illustrated here:

```
Level 1 IMS Transaction
Level 2 DL/I Call
```

Detail line descriptions

IMS transaction detail line

This is the first-level detail line. Each line shows information about one IMS transaction code.

| Under Heading | This is Displayed |
|---------------|---|
| Tran/PCB | The IMS transaction code. |
| PSB/DBD | The name of the PSB and program. |
| PCBNum | No data is reported in the transaction detail line. |

| Under Heading | This is Displayed |
|--------------------------|---|
| Func | No data is reported in the transaction detail line. |
| DL/I Call Count: Total | The total number of DL/I calls counted for all executions of the transaction during the measurement interval. |
| DL/I Call Count: Minimum | The minimum number of DL/I calls observed in a single execution of the transaction during the measurement interval. |
| DL/I Call Count: Maximum | The maximum number of DL/I calls observed in a single execution of the transaction during the measurement interval. |
| DL/I Call Count: Average | The average number of DL/I calls per transaction for all executions of the transaction during the measurement interval. |

DL/I call detail line

This is the second-level detail line. Each line shows information about a DL/I call for which execution was observed under the transaction.

| Under Heading | This is Displayed |
|--------------------------|---|
| Tran/PCB | The name of the PCB referenced by the indicated DL/I call. |
| PSB/DBD | The DBD name for the DL/I call for database calls. |
| PCBNum | The relative PCB number of the PCB referenced by the DL/I call. |
| Func | The DL/I function code. |
| DL/I Call Count: Total | The total number of occurrences of the indicated DL/I call counted for all executions of the transaction during the measurement interval. |
| DL/I Call Count: Minimum | The minimum number of occurrences of the indicated DL/I call observed in a single execution of the transaction during the measurement interval. |
| DL/I Call Count: Maximum | The maximum number of occurrences of the indicated DL/I call observed in a single execution of the transaction during the measurement interval. |
| DL/I Call Count: Average | The average number of occurrences of the indicated DL/I call per transaction during the measurement interval. |

Sample reports

A sample report is shown below.

| File View Navigate Help | | | | | | | |
|---|----------|--------|------|------------------|---------|-------------------|---------|
| I17: IMS Transaction DL/I Call Counts (0805/ADSMPP) | | | | | | Row 00001 of 0002 | |
| Command ==> | | | | | | Scroll ==> CSR | |
| TranPCB | PSB/DBD | PCBNum | Func | DL/I Call Counts | | | |
| | | | | Total | Minimum | Maximum | Average |
| BBSR000 | BBSFIN00 | | | 490 | 10 | 10 | 10.00 |
| BBSR000 | BBSFIN00 | | | 500 | 10 | 10 | 10.00 |

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects


| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Trancode, PCB | Display context help information. |
| + | Trancode | Show additional details. |
| - | Trancode | Collapse to hide next level. |
| ++ | Trancode, PCB | Show additional details. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Tran/PCB | Display context help information. |
| + | Tran/PCB | Expand to reveal all entries. |
| - | Tran/PCB | Collapse to show only first level. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here:



```
File View Navigate Help
+-----+
+----- The following report line was selected -----+
| BBSR000   BBSFIN00           490      10      10      10.00 |
+-----+

IMS Transaction Information
  IMS Trancode   BBSR000           IMS system   IMSP
  PSB name       BBSFIN00           Txn count    49
  Total time     9.4387             Total CPU time 0.4074
```

I18 - IMS CPU/Svc time by DL/I calls

Usage

Use this report to see information about exact CPU times and service times for DL/I calls. The IMS+ feature must have been enabled when the measurement was performed.

Quantification

Each report line shows information pertaining to one DL/I call.

Detail line hierarchy

The I18 report shows one detail line level. It cannot be expanded.

Detail line descriptions

| Under Heading | This is Displayed |
|---------------|--|
| Call | A unique reference number assigned to the DL/I call. |

| Under Heading | This is Displayed |
|-----------------|---|
| Func | The DL/I function code. |
| PCB Name | The name of the PCB referenced by the DL/I call. |
| Location | The location of the DL/I call in CSECT+offset format. |
| Count | The number of executions of the DL/I call counted. |
| Svc time/Prcent | The total service time for all executions of this DL/I call and the percentage of the total DL/I call service time. |
| CPU time/Prcent | The total CPU time consumed by all executions of this DL/I call and the percentage of the total DL/I call CPU time. |

Sample reports

A sample report is shown below.

| File View Navigate Help | | | | | | | | |
|--|------|----------|---------------|-------|-----------------|-------------------|--|--|
| ----- | | | | | | | | |
| I18: IMS CPU/Service Time by DL/I Call (0805/ADSMPP) | | | | | | Row 00001 of 0018 | | |
| Command ==>> | | | | | | Scroll ==>> CSR | | |
| ----- | | | | | | | | |
| ---- DL/I Processing Time ---- | | | | | | | | |
| Call | Func | PCB Name | Location | Count | Svc Time/Prcent | CPU Time/Prcent | | |
| 0012 | GHU | DBSCN001 | BBSAP011+0E68 | 49 | 8.210 44.4% | 0.028 4.8% | | |
| 0003 | GHU | DBSCN001 | BBSAP012+0EE4 | 50 | 7.823 42.3% | 0.031 5.4% | | |
| 0002 | GHU | DBSCA001 | BBSAP012+0E0E | 50 | 0.664 3.5% | 0.048 8.3% | | |
| 0011 | GHU | DBSCA001 | BBSAP011+0D92 | 49 | 0.590 3.1% | 0.047 8.2% | | |
| 0001 | GU | IOPCB | BBSFIN00+038C | 119 | 0.557 3.0% | 0.148 25.8% | | |
| 0015 | GHU | DBSTL001 | BBSAP011+111E | 49 | 0.134 0.7% | 0.045 7.8% | | |
| 0006 | GHU | DBSTL001 | BBSAP012+11B0 | 50 | 0.114 0.6% | 0.043 7.5% | | |
| 0018 | REPL | DBSCN001 | BBSAP011+12EA | 49 | 0.107 0.5% | 0.036 6.2% | | |
| 0009 | REPL | DBSCN001 | BBSAP012+13A4 | 50 | 0.075 0.4% | 0.035 6.1% | | |
| 0007 | ISRT | DBSTL001 | BBSAP012+1252 | 50 | 0.072 0.3% | 0.027 4.7% | | |
| 0010 | ISRT | IOPCB | BBSFIN00+0410 | 99 | 0.034 0.1% | 0.010 1.7% | | |
| 0016 | ISRT | DBSTL001 | BBSAP011+11C0 | 49 | 0.016 0.0% | 0.015 2.6% | | |
| 0013 | GHU | DBSCA002 | BBSAP011+0FF4 | 49 | 0.015 0.0% | 0.011 1.9% | | |
| 0004 | GHU | DBSCA002 | BBSAP012+1086 | 50 | 0.014 0.0% | 0.010 1.7% | | |
| 0005 | ISRT | DBSCA002 | BBSAP012+1110 | 50 | 0.011 0.0% | 0.011 1.9% | | |
| 0014 | ISRT | DBSCA002 | BBSAP011+107E | 49 | 0.011 0.0% | 0.011 1.9% | | |

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | DL/I Call | Display context help information. |
| ++ | DL/I Call | Show additional details. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Call | Display context help information. |
| SV | Call | Sort next level by value. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|--------------------------|
| SN | Call | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+-----+-----+-----+-----+-----+-----+-----+
| 0012  GHU DBSCN001  BBSAP011+0E68  49  8.210  44.4%  0.028  4.8%|
+-----+-----+-----+-----+-----+-----+-----+-----+

DL/I Call Information
Function code  GHU                PSB Name      BBSFIN00
PCB Name      DBSCN001            IMS Id-Region IMSP-ADSMPP
PCB Number    4                          Call type     CBLTDLI
CSECT/module  BBSAP011 in BBSAP011      Offset of call 00000E68
Sample count  277                         Call count    49
DLI CPU time  0.02                       Service time  8.21

SSA/FSA      01 SBSCNTL (CNTLNUM =...)

```

I19 - IMS CPU/Svc time by PSB

Usage

Use this report to see information about exact CPU times and service times for DL/I calls by PSB. The IMS+ feature must have been enabled when the measurement was performed.

Quantification

Each report line shows information pertaining to one PSB.

Detail line hierarchy

The I19 report shows one detail line level. It cannot be expanded.

Detail line descriptions

| Under Heading | This is Displayed |
|----------------|---|
| PSB Name | The IMS PSB name. |
| Txn Count | The number of transaction executions counted under the indicated PSB. |
| DL/I Count | The number of DL/I calls counted under the indicated PSB. |
| Svc time/Prcnt | The total service time for all executions of DL/I calls under the indicated PSB and the percentage of the total DL/I call service time. |
| CPU time/Prcnt | The total CPU time consumed by all executions of DL/I calls under the indicated PSB and the percentage of the total DL/I call CPU time. |

Sample reports

A sample report is shown below.

```
File View Navigate Help
-----
I19: IMS CPU/Service Time by PSB (0805/ADSMPP) Row 00001 of 0001
Command ==> _____ Scroll ==> CSR

PSB Name Txn DL/I ----- DL/I Processing Time -----
          Count Count Svc Time/Prcnt CPU Time/Prcnt
BBSFIN00 101 1010 18.466 100.0% 0.573 100.0%
```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | PSB Name | Display context help information. |
| ++ | PSB Name | Show additional details. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | PSB Name | Display context help information. |
| SV | PSB Name | Sort next level by value. |
| SN | PSB Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here:


```

File View Navigate Help
+----- The following report line was selected -----+
| BBSFIN00      99      1010      18.466      100.0%      0.573      100.0% |
+-----+

IMS PSB Information
PSB Name      BBSFIN00      IMS system      IMSP
No.of PCBs    27      LIST=NO PCBs    12
Txn count     99      DL/I calls      1010
Sample count  611

PCBNum  Name      Type  DBD/LTRM  PROCOPT  LIST
1      IOPCB     TP           DBSCN000  A         YES
2      ALT1      TP           DBSCN000  A         YES
3      ALT2      TP           DBSCN000  A         YES
4      DBSCN001 DB      DBSCN000  A         YES
5      DBSCN002 DB      DBSCN000  A         YES
6      DBSCN003 DB      DBSCN000  A         YES
7      DBSCI001 DB      DBSCI000  A         YES
8      DBSCI002 DB      DBSCI000  A         YES
9      DBSCI003 DB      DBSCI000  A         YES
10     DBSCA001 DB      DBSCA000  A         YES
11     DBSCA002 DB      DBSCA000  A         YES
12     DBSCA003 DB      DBSCA000  A         YES
13     DBSTL001 DB      DBSTL000  A         YES
14     DBSTL002 DB      DBSTL000  A         YES
15     DBSTL003 DB      DBSTL000  A         YES
16     DBSCNA01 DB      DBSCN000  A         NO
17     DBSCNA02 DB      DBSCN000  A         NO
18     DBSCNA03 DB      DBSCN000  A         NO
19     DBSCIA01 DB      DBSCI000  A         NO
20     DBSCIA02 DB      DBSCI000  A         NO
21     DBSCIA03 DB      DBSCI000  A         NO
22     DBSCAA01 DB      DBSCA000  A         NO
23     DBSCAA02 DB      DBSCA000  A         NO
24     DBSCAA03 DB      DBSCA000  A         NO
25     DBSTLA01 DB      DBSTL000  A         NO

```

I20 - IMS CPU/Svc time by transaction

Usage

Use this report to see information about exact CPU times and service times for DL/I calls by IMS transaction. The IMS+ feature must have been enabled when the measurement was performed.

Quantification

Each report line shows information pertaining to one IMS transaction code.

Detail line hierarchy

The I20 report shows one detail line level. It cannot be expanded.

Detail line descriptions

| Under Heading | This is Displayed |
|---------------|--|
| TranCode | The IMS transaction code. |
| Txn Count | The number of executions of the transaction that occurred during the measurement interval. |

| Under Heading | This is Displayed |
|-------------------------|--|
| Txn Total Time: Service | The total service time for all execution in the indicated transaction. This includes DL/I call execution and all other program execution. |
| Txn Total Time: CPU | The total DL/I CPU time consumed by all execution in the indicated transaction. This includes DL/I call execution and all other program execution. |
| Svc time/% of Txn | The total service time for all executions of DL/I calls in the indicated transaction. The percentage indicates how much of the service time was in DL/I call processing. This total does not include GU-IOPCB wait times (not attributed to transaction service time) and may differ from other reports. |
| CPU time/% of Txn | The total CPU time for all executions of DL/I calls in the indicated transaction. The percentage indicates how much of the CPU time was in DL/I call processing. |

Sample reports

A sample report is shown below.

| File View Navigate Help | | | | | | | |
|--|-----------|----------------|---------------------|----------------------------------|-------|-------------------|------------------|
| I20: IMS CPU/Service Time by Transaction (0805/ADSMPP) | | | | | | Row 00001 of 0002 | |
| Command ==> | | | | | | Scroll ==> CSR | |
| TranCode | Txn Count | -- Txn Service | Total Time CPU Time | ----- DL/I Processing Time ----- | | Svc time %of Txn | CPU Time %of Txn |
| BBSDR000 | 50 | 10.133 | 0.432 | 8.995 | 88.7% | 0.372 | 86.1% |
| BBSR000 | 49 | 9.438 | 0.407 | 9.316 | 98.7% | 0.356 | 87.4% |

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | TranCode | Display context help information. |
| ++ | TranCode | Show additional details. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | TranCode | Display context help information. |
| SV | TranCode | Sort next level by value. |
| SN | TranCode | Sort next level by name. |

Detail window

You can enter "++" (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| BBSDR000   50   10.133   0.432   8.995   88.7%   0.372   86.1% |
+-----+

IMS Transaction Information
IMS Trancode   BBSDR000           IMS system   IMSP
PSB name       BBSFIN00           Txn count   50
Total time     10.1332              Total CPU time 0.4327

```

I21 - IMS CPU/Svc time by PCB

Usage

Use this report to see information about exact CPU times and service times for DL/I calls by individual PCB. The IMS+ feature must have been enabled when the measurement was performed.

Quantification

Each report line shows information pertaining to one DL/I call.

Detail line hierarchy

The I21 report shows one detail line level. It cannot be expanded.

Detail line descriptions

| Under Heading | This is Displayed |
|------------------|---|
| PSB Name | The PSB name. |
| PCB Name | The name of the PCB. |
| PCBNum | The relative PCB number. |
| Count | The total number of executions of DL/I calls that referenced the indicated PCB. |
| Svc time/Percent | The total service time for all executions of DL/I calls in the indicated PCB and the percentage of the total DL/I service time. |
| CPU time/Percent | The total CPU time consumed by all executions of DL/I calls in the indicated PCB and the percentage of the total DL/I CPU time. |

Sample reports

A sample report is shown below.

| File View Navigate Help | | | | | | | |
|--|----------|--------|-------|------------------------------|-------|-------------------|-------|
| I21: IMS CPU/Service Time by PCB (0805/ADSMPP) | | | | | | Row 00001 of 0002 | |
| Command ==> | | | | | | Scroll ==> CSR | |
| | | | | ----- DL/I Call Counts ----- | | | |
| PSB Name | PCB Name | PCBNum | Count | Svc time/Percent | | CPU Time/Percent | |
| BBSFIN00 | DBSCN001 | 4 | 198 | 16.216 | 87.8% | 0.131 | 22.8% |
| BBSFIN00 | DBSCA001 | 10 | 198 | 1.268 | 6.8% | 0.106 | 18.4% |
| BBSFIN00 | IOPCB | 1 | 218 | 0.591 | 3.2% | 0.158 | 27.5% |
| BBSFIN00 | DBSTL001 | 13 | 198 | 0.337 | 1.8% | 0.132 | 23.0% |
| BBSFIN00 | DBSCA002 | 11 | 198 | 0.053 | 0.2% | 0.044 | 7.6% |

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | PCB | Display context help information. |
| ++ | PCB | Show additional details. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | PSB Name | Display context help information. |
| SV | PSB Name | Sort next level by value. |
| SN | PSB Name | Sort next level by name. |

Detail window

You can enter "++" (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here:

```

+----- The following report line was selected -----+
| BBSFIN00  DBSCN001  4  198  16.216  87.8%  0.131  22.8% |
+-----+

```

IMS PSB Information

```

PSB Name      BBSFIN00          IMS system      IMSP
No.of PCBs    27                LIST=NO PCBs   12
Txn count     99                DL/I calls     1010
Sample count  611

```

| <u>PCBNum</u> | <u>Name</u> | <u>Type</u> | <u>DBD/LTRM</u> | <u>PROCOPT</u> | <u>LIST</u> |
|---------------|-------------|-------------|-----------------|----------------|-------------|
| 1 | IOPCB | TP | | | YES |
| 2 | ALT1 | TP | | | YES |
| 3 | ALT2 | TP | | | YES |
| 4 | DBSCN001 | DB | DBSCN000 | A | YES |
| 5 | DBSCN002 | DB | DBSCN000 | A | YES |
| 6 | DBSCN003 | DB | DBSCN000 | A | YES |
| 7 | DBSCI001 | DB | DBSCI000 | A | YES |
| 8 | DBSCI002 | DB | DBSCI000 | A | YES |
| 9 | DBSCI003 | DB | DBSCI000 | A | YES |
| 10 | DBSCA001 | DB | DBSCA000 | A | YES |
| 11 | DBSCA002 | DB | DBSCA000 | A | YES |
| 12 | DBSCA003 | DB | DBSCA000 | A | YES |
| 13 | DBSTL001 | DB | DBSTL000 | A | YES |
| 14 | DBSTL002 | DB | DBSTL000 | A | YES |
| 15 | DBSTL003 | DB | DBSTL000 | A | YES |
| 16 | DBSCNA01 | DB | DBSCN000 | A | NO |
| 17 | DBSCNA02 | DB | DBSCN000 | A | NO |
| 18 | DBSCNA03 | DB | DBSCN000 | A | NO |
| 19 | DBSCIA01 | DB | DBSCI000 | A | NO |
| 20 | DBSCIA02 | DB | DBSCI000 | A | NO |
| 21 | DBSCIA03 | DB | DBSCI000 | A | NO |
| 22 | DBSCAA01 | DB | DBSCA000 | A | NO |
| 23 | DBSCAA02 | DB | DBSCA000 | A | NO |
| 24 | DBSCAA03 | DB | DBSCA000 | A | NO |
| 25 | DBSTLA01 | DB | DBSTL000 | A | NO |

Chapter 6. DB2 performance analysis reports

This section describes the DB2 Performance Analysis Reports.

| For information about ... | See ... |
|---------------------------------------|--|
| The DB2 data extractor | "Overview of DB2 data extractor" on page 340 |
| The DB2+ data extractor | "The DB2+ data extractor" on page 340 |
| Displaying SQL Statement Text | "Displaying SQL Statement Text" on page 341 |
| SQL statement sequence numbers | "SQL statement sequence numbers" on page 342 |
| DB2 Multiple Address Space Support | "Overview of DB2 Multiple Address Space Support" on page 342 |
| F01 DB2 session statistics | "F01 - DB2 measurement" on page 343 |
| F02 DB2 SQL activity timeline | "F02 - DB2 SQL activity timeline" on page 347 |
| F03 DB2 SQL activity by DBRM | "F03 - DB2 SQL activity by DBRM" on page 350 |
| F04 SQL execution summary | "F04 - DB2 SQL activity by statement" on page 354 |
| F05 DB2 SQL activity by plan | "F05 - DB2 SQL activity by plan" on page 357 |
| F06 SQL statement attributes | "F06 - DB2 SQL statement attributes" on page 360 |
| F07 DB2 SQL wait time by DBRM | "F07 - DB2 SQL wait time by DBRM" on page 363 |
| F08 DB2 SQL wait time by statement | "F08 - DB2 SQL wait time by statement" on page 366 |
| F09 DB2 SQL wait time by plan | "F09 - DB2 SQL wait time by plan" on page 368 |
| F10 DB2 SQL CPU/Svc time by DBRM | "F10 - DB2 SQL CPU/Svc time by DBRM" on page 371 |
| F11 DB2 SQL CPU/Svc Time by Stmt | "F11 - DB2 SQL CPU/Svc time by stmt" on page 374 |
| F12 DB2 SQL CPU/Svc Time by Plan | "F12 - DB2 SQL CPU/Svc time by plan" on page 377 |
| F13 DB2 SQL threads analysis | "F13 - DB2 SQL threads analysis" on page 381 |
| F14 DB2 CPU by plan/stored proc | "F14 - DB2 CPU by plan/stored proc" on page 382 |
| F15 DB2 SQL CPU/Svc Time by Rq Loc | "F15 - DB2 SQL CPU/Svc Time by Rq Loc" on page 386 |
| F16 - DB2 SQL CPU/Svc Time by Enclave | "F16 - DB2 SQL CPU/Svc Time by Enclave" on page 389 |
| F17 - DB2 SQL CPU/Svc Time by Corrid | "F17 - DB2 SQL CPU/Svc Time by Corrid" on page 392 |

| For information about ... | See ... |
|--------------------------------------|--|
| F18 - DB2 SQL CPU/Svc Time by Wkstn | "F18 - DB2 SQL CPU/Svc Time by Wkstn" on page 396 |
| F19 - DB2 SQL CPU/Svc Time by EndUsr | "F19 - DB2 SQL CPU/Svc Time by EndUsr" on page 400 |
| DB2 EXPLAIN report | "DB2 EXPLAIN report" on page 403 |
| DB2SQL Category in report C01 | "DB2SQL category in C01 report" on page 406 |

Overview of DB2 data extractor

In order to use the DB2 Performance Analysis Reports, the DB2 data extractor must be turned on when the Observation Request is entered. You must select the DB2 data extractor in the Schedule New Measurement panel.

The DB2 extractor collects measurement data directly related to SQL activity. During each sampling interval, Application Performance Analyzer interrogates DB2 to determine if the application or transaction is currently performing a DB2 request. If it is, a DB2 measurement record is created that describes the request. If the request was to process an SQL statement then details of the SQL statement are also recorded. These DB2 records later are analyzed to produce the DB2 reports.

The DB2+ data extractor

There is a second DB2 data extractor called DB2+. You will see this if your installation has it enabled, and your TSO ID has authority to use it.

Turning on the DB2+ data extractor allows Application Performance Analyzer to collect the data required to report exact SQL request counts, SQL CPU time, and SQL Service Time. The DB2+ data extractor needs to be selected to produce report F10, F11, F12, F15, F16, F17, F18, and F19. Also some fields in the F01 report require DB2+.

Turning on DB2+ will insure that the SQL text reported on SQL statements is accurate. Without DB2+ turned on, it is possible for the SQL text to be incorrect. This is true for both static and dynamic SQL.

Note: Running Application Performance Analyzer measurements with the DB2+ data extractor turned on causes each DB2 call to be intercepted to collect additional data. This might have a small impact on the performance of the target address space. Care should be taken when using this feature with other products that also intercept DB2 calls as unpredictable results might occur. Your installer might have chosen to limit access to this feature.

Measuring DDF activity

If you measure a DB2 DDF address space with the DB2+ extractor turned on, Application Performance Analyzer captures the remote SQL activity detected in the address space. The data is reported in the following reports: F02, F10, F11, F12, F15, F16, F17, F18 and F19. The only other report available for a DDF measurement is S01 Measurement Profile.

For DDF measurements only, Application Performance Analyzer records the enclave CPU time, zIIP time, and zIIP on CP time for each observed SQL call.

There are some limitations when reporting on a DDF address space:

1. The SQL calls observed will not correlate one-for-one with those issued by the application at the requester site. Some calls will not be observed because they are not sent to the DIST address space.
2. Multiple SQL calls can be issued by DB2 when processing a particular SQL call. For example, an OPEN call could result in FETCH and CLOSE calls being issued by the DIST address space. These calls will have the same statement number as the OPEN call.
3. When a CALL statement results in invoking a stored procedure in the same DB2 subsystem, the stored procedure calls can also be observed in the DIST address space.
4. Some dynamic SQL statements can be shown as static. This is because the DIST address space is treating them as though they are static.
5. Some SQL calls have a statement type of Remote SQL instead of the expected SQL type. For example, INSERT and DELETE calls are observed as Remote SQL. As a consequence:
 - The SQL text might not be accurate.
 - Issuing an EXPLAIN request against a SQL statement with a type of Remote SQL can result in an error at the server rather than being caught in the TSO session of the user.
6. A CALL statement might not always have SQL text available.
7. A DESCRIBE statement does not have any SQL text available.

Notes:

1. If you want to select a DDF address space from a list when setting up the measurement, enter **DIST* in the Job Name pattern field.
2. The Number of Samples specified for a DDF measurement is not used because each DDF call is intercepted rather than sampled. The number of samples will always be converted to approximately one per second.

Displaying SQL Statement Text

When SQL statement text is displayed in a DB2 report, a limit of up to 4,000 characters, or up to 15,000 characters is displayed, depending on the circumstances. SQL statements exceeding the limit are truncated.

For non-DDF observations, the SQL text for dynamic SQL can be up to 15,000 characters long. If the DB2V option is selected, then static SQL text can also be up to 15,000 characters long. Otherwise, static SQL text is limited to 4,000 characters.

For DDF observations, the SQL text for dynamic SQL can be up to 15,000 characters long. Static SQL statements are limited to 4,000 characters.

When the execution of a SQL statement is unsuccessful, DB2 sets a negative SQLCODE. In this situation, Application Performance Analyzer displays the negative SQLCODE in the DB2 reports, rather than the SQL statement text. Report F11 SQL CPU/Service Time by Statement provides a SETUP option to limit the display of SQL statements to only those that ended successfully or to only those that ended unsuccessfully.

SQL statement sequence numbers

A sequence number is assigned by Application Performance Analyzer to each unique SQL statement observed during the measurement. In most DB2 reports, this sequence number is preceded by either “S” or “D” indicating if the SQL statement is static or dynamic. Application Performance Analyzer will stop sampling when 99,999 unique SQL statements are observed. When this maximum is reached the observation request is cancelled with the reason ‘Maximum SQL statements exceeded’.

Overview of DB2 Multiple Address Space Support

DB2 multiple address space (MASS) support allows you to create a request to measure a specific DB2 stored procedure or user-defined function, regardless of which WLM region it executes in.

You can also measure DB2 activity in stored procedures and user-defined functions that are invoked from any job you are measuring, by selecting the Collateral DB2 data extractor (CDB2). In this case, the measured job does not have to be a stored procedure or user-defined function.

To enter a DB2 MASS observation that measures a specific DB2 stored procedure or user-defined function:

1. Start a NEW request.
2. In Panel 1 – Job Information, enter a dash (-) in the Job name/Pattern field.
3. In Panel 5 – Subsystems, enter the DB2 subsystem name, the schema name, and the stored procedure name or the user-defined function name. You must also indicate whether you are measuring a stored procedure or a user-defined function.
4. In Panel 2 – Options, select the DB2 data extractor.
5. Complete any other relevant fields for your observation request.

Once the NEW request is complete and submitted, Application Performance Analyzer creates and starts an observation request for the DB2 stored procedure or user-defined function. It will execute for the duration specified on the NEW request.

To enter an observation that measures a DB2 batch job that invokes a DB2 stored procedure or user-defined function:

1. Start a NEW request.
2. In Panel 1 – Job Information, enter the batch job name in the Job name/Pattern field.
3. In Panel 2 – Options, select the DB2+ and CDB2 data extractors.
4. Complete any other relevant fields for your observation request.

Once the NEW request is complete and submitted, Application Performance Analyzer creates and starts an observation request for the DB2 batch job. Because the collateral DB2 extractor is on, when the DB2 batch job calls the stored procedure or user-defined function, Application Performance Analyzer generates a separate measurement. This measurement is displayed in the R02 Observation List as child observations under the parent.

F01 - DB2 measurement

Usage

Use this report to see a general overview of the DB2 measurement data. This is a good report to examine first when analyzing DB2 information. It provides an at-a-glance summary of various aspects of the measurement data and helps you choose which other reports to concentrate on. The first section of this report consists of a series of mini performance graphs illustrating various types of activity that was measured. This is followed by a section that reports measurement values.

Performance graphs

These are histograms quantifying measurement data. To the right of some of the graphs, report codes of reports that show related and more detailed information are displayed. You can display the report by skipping the cursor to one of these fields and by pressing the ENTER key.

Most Active DB2 Plans

| Under Heading | This is Displayed |
|---------------|--|
| Samples | The number of samples done during the measurement upon which this graph is based. This number represents 100 percent of the data upon which the graph is based and is used as the divisor to compute the percentages shown in other lines in the graph. |
| DB2 Plan Name | A DB2 plan name is shown and the number of samples in which processing of SQL requests under this plan was observed. The percentage and the graph represent the proportion of the overall measurement time SQL requests were being serviced under this DB2 plan. |

Most active package/DBRMs

| Under Heading | This is Displayed |
|----------------------|---|
| Samples | The number of samples done during the measurement upon which this graph is based. This number represents 100 percent of the data upon which the graph is based and is used as the divisor to compute the percentages shown in other lines in the graph. |
| Package or DBRM Name | A package or DBRM name is shown and the number of samples in which processing of SQL requests in this Package/DBRM was observed. The percentage and the graph represent the proportion of the overall measurement time SQL requests were being serviced in this Package/DBRM. |

Most active SQL statements

| Under Heading | This is Displayed |
|---------------|---|
| Samples | The number of samples done during the measurement upon which this graph is based. This number represents 100 percent of the data upon which the graph is based and is used as the divisor to compute the percentages shown in other lines in the graph. |

| Under Heading | This is Displayed |
|---------------|--|
| SQL Statement | The DBRM name, precompiler statement number, SQL function and the number of samples in which processing of this SQL request was observed. The percentage and the graph represent the proportion of the overall measurement time this SQL request was being serviced. |

Most CPU consumptive SQL

This requires that the DB2+ measurement option was active.

| Under Heading | This is Displayed |
|--------------------|--|
| Total SQL CPU Time | The number of seconds of CPU time consumed by all executions of SQL requests during the measurement. This number represents 100 percent of the data upon which the graph is based and is used as the divisor to compute the percentages shown in other lines in the graph. |
| SQL Statement | The DBRM name, precompiler statement number, SQL function and the number of CPU seconds of execution for this statement. |

Most frequent SQL statements

This requires that the DB2+ measurement option was active. The graphic information is based on the number of SQL requests counted.

| Under Heading | This is Displayed |
|-------------------------|--|
| Total SQL Calls Counted | The total number of SQL requests counted during the measurement. This number represents 100 percent of the data upon which the graph is based and is used as the divisor to compute the percentages shown in other lines in the graph. |
| SQL Statement | The DBRM name, precompiler statement number, SQL function and the number of SQL requests counted for this statement. |

Single SQL call service time

This requires that the DB2+ measurement option was active.

| Under Heading | This is Displayed |
|------------------------------|--|
| Total SQL Service Time | The number of seconds of service time for all executions of SQL requests during the measurement. This number represents 100 percent of the data upon which the graph is based and is used as the divisor to compute the percentages shown in other lines in the graph. |
| SQL statement identification | The DBRM name, precompiler statement number, SQL function and the number of seconds of service time for this statement. |

DB2 measurement statistics

A grid of values is shown for the overall DB2 measurement and then a separate grid for each DB2 subsystem. If only one subsystem was observed then only one grid appears.

| Under Heading | This is Displayed |
|--------------------|--|
| DB2 Subsystem Name | The name of the DB2 subsystem. |
| DB2 Version | The version of DB2 for the subsystem. |
| SQL Calls Sampled | The number of unique SQL requests in which samples were taken. |
| SQL observations | The number of samples in which SQL activity was observed. |
| SQL Calls Executed | The number of SQL requests executed determined on the basis of lower and upper REQCT values for each of the DB2 threads. |
| Avg SQL call rate | This is the average number of SQL calls per second for the measurement interval. This is based on the SQL calls counted value if it was measured (DB2+ option active). Otherwise it is based on the SQL calls executed value. |
| SQL Calls Counted | The number of SQL requests counted by the DB2+ measurement feature. This value is available only if the DB2+ measurement option was selected for the measurement. This is an exact SQL request count for the measurement interval. |
| SQL throughput | A theoretical SQL request throughput rate based on the number of SQL requests for the portion of the measurement interval SQL processing was occurring. (Time other non-SQL application activity was taking place is excluded.) This is based on the SQL calls counted value if it was measured (DB2+ option active). Otherwise it is based on the SQL calls executed value. |
| SQL service time | The total service time for SQL processing. This value is available only if the DB2+ measurement option was selected for the measurement. |
| SQL CPU time | The total CPU time in the measured region for SQL processing. This value is available only if the DB2+ measurement option was selected for the measurement. |
| SQL max time | The maximum service time for a single SQL call. This value is available only if the DB2+ measurement option was selected for the measurement. |
| SQL max CPU | The maximum CPU time for a single SQL call. This value is available only if the DB2+ measurement option was selected for the measurement. |
| SQL min time | The minimum service time for a single SQL call. This value is available only if the DB2+ measurement option was selected for the measurement. |
| SQL min CPU | The minimum CPU time for a single SQL call. This value is available only if the DB2+ measurement option was selected for the measurement. |

Sample reports

A sample report is shown here, it is a scrollable report, and is shown here split into two screen images.

F02 - DB2 SQL activity timeline

Usage

Use this report to see information about the chronology of SQL requests that were sampled over the duration of the measurement and to identify any calls with excessive service times. Each line shows information about one SQL call. By default, the detail lines are sorted chronologically by DB2 thread. You can also request that the data be sorted in descending sequence by SQL call duration. Enter the “SD” line command on the “Threads” heading field to sort in this sequence. This will bring to the top of the report any SQL calls that might have had excessive service times.

When the DB2+ feature is active for a measurement, the number of SQL calls displayed in this report is limited by the value of the DB2IMaxTraceSize parameter specified during Application Performance Analyzer installation, or by the value on panel 2 of the measurement request (if your installation has configured this field). The report is truncated when the number of SQL calls issued reaches the value specified for DB2IMaxTraceSize.

Quantification

When the DB2+ feature is not active, each report line shows the time at which the first sample for the identified SQL call took place. The duration of the interval execution of the SQL call was observed is also reported. This is derived from the number of samples and the sampling interval. This gives an indication of the service time for the particular SQL call.

When the DB2+ feature is active each report line shows the time at which the identified SQL call started. The service time or duration of execution of the SQL call is also reported. This is measured directly by the DB2+ feature.

Detail line hierarchy

An unexpanded F02 report shows a line for each SQL call that was measured by the DB2+ feature or that was sampled one or more times. You can expand each line to reveal one additional hierarchical level of detail (using the “+” line command).

The hierarchy is illustrated here:

Level 1 SQL Call
Level 2 SQL Statement Text

...

Detail line descriptions

SQL Call execution detail line

This is the first-level detail line. Each line shows information about one SQL call.

| Under Heading | This is Displayed |
|---------------|---|
| Thread | A sequence number identifying the DB2 thread. Application Performance Analyzer assigns a unique sequence number to each DB2 thread that was observed. |
| REQCT | The REQCT value for the SQL call. |
| Program | The name of the DBRM in which the SQL call was defined. |

| Under Heading | This is Displayed |
|---------------|--|
| Stmt# | The precompiler statement number of the SQL statement. |
| SQL Function | The SQL function performed by the reported statement: SELECT, INSERT, UPDATE, etc. |
| Samps | The number of samples recorded for the interval described by this report line. This can be zero if the identified SQL call was measured by the DB2+ feature but not sampled. |
| Call Time | When the DB2+ feature is not active this is the time at which the first sample in the sequence of samples reported by this line occurred. When the DB2+ feature is active each report line shows the time at which the identified SQL call started. The time is shown in minutes, seconds and hundredths of seconds. |
| Interval | When the DB2+ feature is not active, this is the duration of the interval, in seconds, during which samples were recorded for the indicated SQL call. This can provide a good indication of the service time for the SQL call. When the DB2+ feature is active, this is measured directly by the DB2+ feature. |
| CPU Time | The CPU time, in seconds, for the reported SQL call as measured by the DB2+ feature. If an SQL call was not measured by the DB2+ feature but was sampled, the CPU time will be reported as Not Available (N/A). This might occur at the beginning of a measurement before the DB2+ feature completes initialization, depending on the sampling rate and system activity. |

SQL statement text detail line

This is second-level detail line shown directly under the SQL statement detail line. It shows the SQL statement text. If necessary, more than one line is displayed in order to show the full SQL text.

Sample reports

When the report is first displayed, only the first level of the hierarchy is visible (Thread). A sample is shown here:

| Thread | REQCT | Program | Stmt# | SQL Function | Samps | Call Time | Interval | CPU Time |
|--------|-------|---------|-------|--------------|-------|-------------|----------|----------|
| 52577 | 08557 | PFSAMPA | 816 | SELECT | 1 | 08:24:45.96 | 0.00 | 0.002 |
| 52577 | 08564 | PFSAMPA | 816 | SELECT | 1 | 08:24:46.25 | 0.00 | 0.001 |
| 52577 | 08566 | PFSAMPB | 678 | SELECT | 1 | 08:24:46.27 | 0.00 | 0.002 |
| 52577 | 08567 | PFSAMPC | 1316 | SELECT | 2 | 08:24:46.27 | 0.01 | 0.001 |
| 52577 | 08569 | PFSAMPC | 1443 | OPEN | 1 | 08:24:46.28 | 0.00 | 0.002 |
| 52577 | 08570 | PFSAMPC | 1466 | FETCH | 2 | 08:24:46.29 | 0.01 | 0.003 |
| 52577 | 08571 | PFSAMPC | 1466 | FETCH | 2 | 08:24:46.30 | 0.01 | 0.002 |
| 52577 | 08586 | PFSAMPC | 3155 | SELECT | 3 | 08:24:46.32 | 0.01 | 0.006 |
| 52577 | 08587 | PFSAMPC | 3179 | SELECT | 1 | 08:24:46.33 | 0.00 | 0.005 |
| 52577 | 08588 | PFSAMPB | 816 | UPDATE | 1 | 08:24:46.34 | 0.00 | 0.002 |
| 52577 | 08592 | PFSAMPA | 816 | SELECT | 1 | 08:24:46.50 | 0.00 | 0.001 |
| 52577 | 08598 | PFSAMPA | 816 | SELECT | 1 | 08:24:46.68 | 0.00 | 0.001 |
| 52577 | 08599 | PFSAMPB | 408 | SET HOST VAR | 1 | 08:24:46.69 | 0.00 | 0.002 |
| 52577 | 08601 | PFSAMPC | 1316 | SELECT | 5 | 08:24:46.69 | 0.03 | 0.003 |
| 52577 | 08604 | PFSAMPC | 1466 | FETCH | 1 | 08:24:46.73 | 0.00 | 0.001 |
| 52577 | 08605 | PFSAMPC | 1466 | FETCH | 3 | 08:24:46.74 | 0.01 | 0.001 |
| 52577 | 08607 | PFSAMPC | 2989 | SELECT | 1 | 08:24:46.76 | 0.00 | 0.002 |

You can enter a “+” line command to expand to the next level, which is the SQL text. The report is shown here where a thread has been expanded:

| Thread | REQCT | Program | Stmt# | SQL Function | Samps | Call Time | Interval | CPU Time | |
|--------|-------|---------|-------|--|-------|-------------|----------|----------|--|
| 52577 | 08557 | PFSAMPA | 816 | SELECT | 1 | 08:24:45.96 | 0.00 | 0.002 | |
| 52577 | 08564 | PFSAMPA | 816 | SELECT | 1 | 08:24:46.25 | 0.00 | 0.001 | |
| 52577 | 08566 | PFSAMPB | 678 | SELECT | 1 | 08:24:46.27 | 0.00 | 0.002 | |
| 52577 | 08567 | PFSAMPC | 1316 | SELECT | 2 | 08:24:46.27 | 0.01 | 0.001 | |
| 52577 | 08569 | PFSAMPC | 1443 | OPEN | 1 | 08:24:46.28 | 0.00 | 0.002 | |
| 52577 | 08570 | PFSAMPC | 1466 | FETCH | 2 | 08:24:46.29 | 0.01 | 0.003 | |
| 52577 | 08571 | PFSAMPC | 1466 | FETCH | 2 | 08:24:46.30 | 0.01 | 0.002 | |
| 52577 | 08586 | PFSAMPC | 3155 | SELECT | 3 | 08:24:46.32 | 0.01 | 0.006 | |
| | | | | > SELECT * INTO : H , : H , : H , : H , : H : H FROM | | | | | |
| | | | | > DEPT WHERE XRATE = : H | | | | | |
| 52577 | 08587 | PFSAMPC | 3179 | SELECT | 1 | 08:24:46.33 | 0.00 | 0.005 | |
| 52577 | 08588 | PFSAMPB | 816 | UPDATE | 1 | 08:24:46.34 | 0.00 | 0.002 | |
| 52577 | 08592 | PFSAMPA | 816 | SELECT | 1 | 08:24:46.50 | 0.00 | 0.001 | |
| 52577 | 08598 | PFSAMPA | 816 | SELECT | 1 | 08:24:46.68 | 0.00 | 0.001 | |
| 52577 | 08599 | PFSAMPB | 408 | SET HOST VAR | 1 | 08:24:46.69 | 0.00 | 0.002 | |
| 52577 | 08601 | PFSAMPC | 1316 | SELECT | 5 | 08:24:46.69 | 0.03 | 0.003 | |

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Thread | Display context help information. |
| ++ | Thread | Show additional details. |
| + | Thread | Expand to reveal next level. |
| - | Thread | Collapse to hide next level. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|---------------------------------------|
| ? | Thread | Display context help information. |
| + | Thread | Expand to reveal all entries. |
| - | Thread | Collapse to hide next level. |
| ST | Thread | Sort chronologically by DB2 thread. |
| SD | Thread | Sort descending by SQL call duration. |
| SC | Thread | Sort descending by SQL CPU Time |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. For example, entering “++” on an SQL line will cause this detail window to appear:

| File View Navigate Help | | | |
|--|--------------------|----------------|-------------------|
| SQL Call Information | | | |
| Sample count | 1 | DB2 Authid | USER1 |
| SQL CPU time | 0.002 | Service time | 0.00 |
| SQL Statement Information | | | |
| Subsystem name | DSN1 | Attach type | SASS |
| Plan name | PFSAMPC | Plan bind time | no data |
| DBRM name | PFSAMPA | DBRM token | 17D8B8DF 05CC86F8 |
| DBRM date/time | May-08-06 15:48:14 | | |
| Package ID | PFSAMPA | Location | CABNETDB24 |
| Collectn name | PFSAMPX1 | Pkg BIND time | no data |
| SQL function | SELECT | Static/dynamic | Static |
| Precmplr stmt# | 678 | DBRM section# | 4 |
| CSECT/module | PFSAMPA in PFSAMPA | Offset of call | 00002764 |
| Sample count | 147 | SQL req count | 333 |
| SQL CPU time | 0.60 | Service time | 0.84 |
| SQL Statement: SELECT * INTO : H , : H , : H , : H , : H FROM DEP WHERE XRATE = : H | | | |
| DB2 Thread Information | | | |
| Thread sequence number | | 00001 | |
| Attachment type | | CICS | |
| First REQCT value observed | | 05256 | |
| Time of first REQCT | | 14:06:47.24 | |
| Last REQCT value observed | | 10613 | |
| Time of last REQCT | | 14:07:46.74 | |
| Total REQCT increments | | 5,358 | |
| Duration first to last | | 59.49 | |
| SQL rate for thread, per second | | 90.06 | |
| Number of samples for thread | | 1,417 | |
| Number of REQCT values sampled | | 1,292 | |

F03 - DB2 SQL activity by DBRM

Usage

Use this report to see how time was consumed by SQL request processing. The percentage of time is reported by each module that issued SQL requests. Expand a module line to see a further breakdown of time consumption by individual SQL request issued by the module.

Note: This report shows all SQL calls that were sampled, but when the DB2+ feature is active it will not show SQL calls that were measured by the DB2+ feature but not sampled.

Quantification

Each report line quantifies service time for all SQL requests issued by a module (DBRM). This is further broken down by SQL request. Each quantity is expressed as a percentage of the overall measurement interval.

Detail line hierarchy

An unexpanded F03 report shows a line for each module that issued SQL requests. You can expand each line to reveal two additional hierarchical levels of detail (using the “+” line command).

The hierarchy is illustrated here:

```
Level 1 Module (DBRM)
Level 2 SQL Request
Level 3 SQL Statement Text
Level 2 SQL Request
Level 3 SQL Statement Text
```

...

Detail line descriptions

SQL DBRM (Module) detail line

This is the first-level detail line. Each line shows information about a DBRM (Module) for which SQL request measurement data was recorded.

| Under Heading | This is Displayed |
|-----------------|--|
| Name | The DBRM name. The DBRM name is often the same name as the corresponding module in which SQL requests were issued. |
| Percent of Time | The percentage of the measurement interval duration SQL Requests for the indicated DBRM Name were being processed. |

SQL request detail line

This is the second-level detail line shown directly under the DBRM/Module detail line. It quantifies the aggregated service time for a specific SQL request.

| Under Heading | This is Displayed |
|-----------------|--|
| Name | A sequence number. This is assigned by Application Performance Analyzer to uniquely identify the SQL request. Either “S” or “D” precedes the sequence number indicating if the SQL statement is static or dynamic. |
| Stmt# | The precompiler statement number. This is the statement number assigned by the precompiler to the SQL request. |
| SQL Function | The SQL function. This is the name of the SQL function: SELECT, FETCH, UPDATE, etc. |
| Percent of Time | The percentage of the measurement interval duration the indicated SQL Request was being processed. |

Note: It is normal for the counts for the second-level items to add up to a higher value than the first level line. The reason for this is that the program level line shows the percentage of time DB2 processing is active. For a sample, DB2 is counted as being active only once, regardless of the number of SQL statements being processed (concurrently). So its percentage can be lower than the sum of the individual SQL request statement percentages because of overlaps.

SQL statement text detail line

This is third-level detail line shown directly under the SQL request detail line. It shows the SQL statement text. If necessary, more than one line is displayed in order to show the full SQL text.

Sample reports

When the report is first displayed, only the first level of the hierarchy is visible (DBRM Name). A sample is shown here:

```

File View Navigate Help
-----
F03: SQL Activity by Module (0659/CICS23A) Row 00001 of 00003
Command ==> _____ Scroll ==> CSR
Name Stmt# SQL Function Percent of Time * 10.00% ±1.1%
*....1....2....3....4....5....6....7.
PFSAMPC 17.22 =====
PFSAMPB 6.31 ===
PFSAMPA 2.00 =

```

You can enter the “+” line command on a DBRM Name to expand to the next level, which is SQL commands. Then you can expand the SQL commands to show the SQL. A sample is shown here with the first DBRM expanded, and then one of the SQL commands expanded:

```

File View Navigate Help
-----
F03: SQL Activity by Module (0659/CICS23A) Row 00001 of 00019
Command ==> _____ Scroll ==> CSR
Name Stmt# SQL Function Percent of Time * 10.00% ±1.1%
*....1....2....3....4....5....6....7.
PFSAMPC 17.22 =====
→ S00012 01466 FETCH 9.13 =====
→ S00008 01316 SELECT 1.82 =
→ S00017 03054 FETCH 1.81 =
→ S00010 01347 SELECT 1.48 =
→ S00011 01443 OPEN 0.80
→ S00018 03155 SELECT 0.66
> SELECT * INTO : H , : H , : H , : H , : H : H FROM DEP
> T WHERE XRATE = : H
→ S00015 02989 SELECT 0.48
→ S00019 03179 SELECT 0.43
→ S00014 01562 CLOSE 0.26
→ S00016 03046 OPEN 0.25
→ S00020 03065 CLOSE 0.05
→ S00009 01316 SELECT 0.01

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Module, Seqno | Display context help information. |
| ++ | Module, Seqno | Show additional details. |
| + | Module, Seqno | Expand to reveal next level. |
| - | Module, Seqno | Collapse to hide next level. |
| SV | Module | Sort next level by value. |
| M | Module, Seqno | Display load module information. |
| SS | Module | Sort next level by Seqno. |
| P | Seqno | Display source program mapping. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|---------------------------|
| EX | Seqno | Display DB2 EXPLAIN data. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Name, Percent Time | Display context help information. |
| + | Name, Percent Time | Expand to reveal all entries. |
| - | Name, Percent Time | Collapse to show only first level. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level entries by name |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. For example, entering “++” on an SQL line will cause this detail window to appear:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| > S00012   3179 SELECT                0.84          |
+-----+

Calculation Details
DB2 SQL activity measurements      84
SQL request                        SELECT
In program                         PFSAMPC
Precompiler statement number      3179
Total measurements                10,000
Percent of total                  0.84

SQL Statement Information
Subsystem name DSN1                Attach type  SASS
Plan name     PFSAMPA              Plan bind time May-11-05 13:57:39

DBRM name     PFSAMPC              DBRM token   179FD30A 1B977868
DBRM date/time May-11-05 13:56:56

Package ID    PFSAMPC              Location     CABNETDB24
Collectn name PFSAMPX1            Pkg BIND time May-11-05 13:57:36

SQL function  SELECT                Static/dynamic Static
Precmplr stmt# 3179                DBRM section# 21
CSECT/module  PFSAMPC in PFSAMPC      Offset of call 00008610
Sample count  84                    SQL req count 172
SQL CPU time  0.28                Service time  0.45

SQL Statement:  SELECT * INTO : H , : H , : H : H , : H FROM VDEPT
                WHERE DEPTNO = : H

```

SETUP options

The following SETUP option can be selected with the SETUP primary command:

Minimum percentage of time

You can set this option to eliminate reporting of SQL activity where the percentage of time is below a certain threshold.

F04 - DB2 SQL activity by statement

Usage

Use this report to see how time was consumed by SQL request processing. The percentage of time is reported by each SQL request.

Note: This report shows all SQL calls that were sampled, but when the DB2+ feature is active it will not show SQL calls that were measured by the DB2+ feature but not sampled.

Quantification

Each report line quantifies service time for all executions of an SQL request. Each quantity is expressed as a percentage of the overall measurement interval.

Detail line hierarchy

An unexpanded F04 report shows a line for each SQL request. You can expand each line to reveal one additional hierarchical level of detail (using the “+” line command).

The hierarchy is illustrated here:

Level 1 SQL Request
Level 2 SQL Statement Text

...

Detail line descriptions

SQL request detail line

This is the first-level detail line. It quantifies the aggregated service time for a specific SQL request.

| Under Heading | This is Displayed |
|-----------------|--|
| Seqno | A sequence number. This is assigned by Application Performance Analyzer to uniquely identify the SQL request. Either “S” or “D” precedes the sequence number indicating if the SQL statement is static or dynamic. |
| Program | The DBRM name for the program that issued the SQL request. |
| Stmt# | The precompiler statement number. This is the statement number assigned by the precompiler to the SQL request. |
| SQL Function | The SQL function. This is the name of the SQL function: SELECT, FETCH, UPDATE, etc. |
| Percent of Time | The percentage of the measurement interval duration the indicated SQL Request was being processed. |

SQL statement text detail line

This is second-level detail line shown directly under the SQL request detail line. It shows the SQL statement text. If necessary, more than one line is displayed in order to show the full SQL text.

Sample reports

A sample report is shown here:

```

File View Navigate Help
-----
F04: SQL Activity by Statement (0659/CICS23A) Row 00001 of 00020
Command ==> _____ Scroll ==> CSR

Seqno Program Stmt# SQL Function Percent of Total Time * 10.00% ±1.1%
*....1....2....3....4....5....6....7...
S00012 PFSAMPC 01466 FETCH 9.13 =====
S00013 PFSAMPB 00816 UPDATE 3.28 ==
S00001 PFSAMPA 00816 SELECT 2.00 =
S00008 PFSAMPC 01316 SELECT 1.82 =
S00017 PFSAMPC 03054 FETCH 1.81 =
S00004 PFSAMPB 00678 SELECT 1.67 =
S00010 PFSAMPC 01347 SELECT 1.48 =
S00002 PFSAMPB 00408 SET HOST VA 1.26 =
S00011 PFSAMPC 01433 OPEN 0.80
S00018 PFSAMPC 03155 SELECT 0.66
S00015 PFSAMPC 02989 SELECT 0.48
S00019 PFSAMPC 03179 SELECT 0.43
S00014 PFSAMPC 01562 CLOSE 0.26
S00016 PFSAMPC 03046 OPEN 0.25
S00020 PFSAMPC 03065 CLOSE 0.05
S00007 PFSAMPB 01385 SELECT 0.03
S00005 PFSAMPB 00947 SELECT 0.02
S00003 PFSAMPB 00408 SET HOST VA 0.01
S00006 PFSAMPB 01163 SELECT 0.01
S00009 PFSAMPC 01316 SELECT 0.01

```

Each line can be expanded to display the SQL statement by entering the “+” line command on the Sequence Number. For example, “+” was entered on the third line in this report to display the SQL.

```

File View Navigate Help
-----
F04: SQL Activity by Statement (0659/CICS23A) Row 00001 of 00022
Command ==> _____ Scroll ==> CSR

Seqno Program Stmt# SQL Function Percent of Total Time * 10.00% ±1.1%
*....1....2....3....4....5....6....7...
S00012 PFSAMPC 01466 FETCH 9.13 =====
S00013 PFSAMPB 00816 UPDATE 3.28 ==
S00001 PFSAMPA 00816 SELECT 2.00 =
      > SELECT * INTO : H FROM DEPTA WHERE XRATE = : H
S00008 PFSAMPC 01316 SELECT 1.82 =
S00017 PFSAMPC 03054 FETCH 1.81 =
S00004 PFSAMPB 00678 SELECT 1.67 =
S00010 PFSAMPC 01347 SELECT 1.48 =
S00002 PFSAMPB 00408 SET HOST VA 1.26 =
S00011 PFSAMPC 01433 OPEN 0.80
S00018 PFSAMPC 03155 SELECT 0.66
S00015 PFSAMPC 02989 SELECT 0.48
S00019 PFSAMPC 03179 SELECT 0.43
S00014 PFSAMPC 01562 CLOSE 0.26
S00016 PFSAMPC 03046 OPEN 0.25
S00020 PFSAMPC 03065 CLOSE 0.05
S00007 PFSAMPB 01385 SELECT 0.03

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Seqno | Display context help information. |
| ++ | Seqno | Show additional details. |
| + | Seqno | Expand to reveal next level. |
| - | Seqno | Collapse to hide next level. |
| M | Seqno | Display load module information. |
| P | Seqno | Display source program mapping. |
| EX | Seqno | Display DB2 EXPLAIN data |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Seqno, Percent of Time | Display context help information. |
| + | Seqno | Expand to reveal all entries. |
| + | Percent of Time | Zoom in scale. |
| - | Seqno | Collapse to show only first level. |
| - | Percent of Time | Zoom out scale |
| SV | Seqno | Sort next level by value. |
| SS | Seqno | Sort next level by Seqno. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on an SQL line will cause this detail window to pop up:


```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| > S00012   3179 SELECT                               0.84 |
+-----+

Calculation Details
DB2 SQL activity measurements      84
SQL request                        SELECT
In program                         PFSAMPC
Precompiler statement number       3179
Total measurements                 10,000
Percent of total                   0.84

SQL Statement Information
Subsystem name DSN1                Attach type SASS
Plan name     PFSAMPA              Plan bind time May-11-05 13:57:39

DBRM name     PFSAMPC              DBRM token    179FD30A 1B977868
DBRM date/time May-11-05 13:56:56

Package ID    PFSAMPC              Location     CABNETDB24
Collectn name PFSAMPX1            Pkg BIND time May-11-05 13:57:36

SQL function  SELECT                Static/dynamic Static
Precmplr stmt# 3179                DBRM section# 21
CSECT/module  PFSAMPC in PFSAMPC   Offset of call 00008610
Sample count  84                    SQL req count 172
SQL CPU time  0.28                  Service time  0.45

SQL Statement:  SELECT * INTO : H , : H , : H : H , : H FROM VDEPT
                WHERE DEPTNO = : H

```

SETUP options

The following SETUP option can be selected with the SETUP primary command:

Minimum percentage of time

You can set this option to eliminate reporting of SQL activity where the percentage of time is below a certain threshold.

F05 - DB2 SQL activity by plan

Usage

Use this report to see how time was consumed by SQL request processing. The percentage of time is reported by each DB2 plan under which measured SQL activity was recorded. Expand a plan line to see a further breakdown of time consumption by individual SQL request.

Note: This report shows all SQL calls that were sampled, but when the DB2+ feature is active it will not show SQL calls that were measured by the DB2+ feature but not sampled.

Quantification

Each report line quantifies service time for all SQL requests issued under a DB2 Plan. This is further broken down by SQL request. Each quantity is expressed as a percentage of the overall measurement interval.

Detail line hierarchy

An unexpanded F05 report shows a line for each module that issued SQL requests. You can expand each line to reveal two additional hierarchical levels of detail (using the “+” line command).

The hierarchy is illustrated here:

```
Level 1 DB2 Plan
  Level 2 SQL Request
    Level 3 SQL Statement Text
  Level 2 SQL Request
    Level 3 SQL Statement Text
```

...

Detail line descriptions

DB2 plan detail line

This is the first-level detail line. Each line shows information about a DB2 Plan for which SQL request measurement data was recorded.

| Under Heading | This is Displayed |
|-----------------|---|
| Seqno | A sequence number assigned to the DB2 plan. |
| Plan/Pgm | The DB2 plan name. |
| Percent of Time | The percentage of the measurement interval duration the indicated DB2 plan was being processed. |

SQL request detail line

This is the second-level detail line shown directly under the DB2 Plan detail line. It quantifies the aggregated service time for a specific SQL request.

| Under Heading | This is Displayed |
|-----------------|--|
| Seqno | A sequence number. This is assigned by Application Performance Analyzer to uniquely identify the SQL request. Either “S” or “D” precedes the sequence number indicating if the SQL statement is static or dynamic. |
| Plan/Pgm | The DBRM name for the program that issued the SQL request. |
| Stmnt# | The precompiler statement number. This is the statement number assigned by the precompiler to the SQL request. |
| SQL Function | SQL Function The SQL function. The is the name of the SQL function: SELECT, FETCH, UPDATE, etc. |
| Percent of Time | The percentage of the measurement interval duration the indicated SQL Request was being processed. |

SQL statement text detail line

This is third-level detail line shown directly under the SQL request detail line. It shows the SQL statement text. If necessary, more than one line is displayed in order to show the full SQL text.

Sample reports

A sample report is shown here with a plan expanded to the second level (statement) and a statement expanded to show the SQL text.

```

File View Navigate Help
-----
F05: SQL Activity by Plan (1336/CICS23A) Row 00001 of 00017
Command ==>> _____ Scroll ==>> CSR

Seqno      Plan/Pgm  Stmt#  SQL Function  Percent of Time * 10.00% ±1.1%
          *.....1.....2.....3.....4....5....6.....7.
P0001      PFSAMPA           20.60 =====
→ S00003   PFSAMPC    1466  FETCH        5.79 ===
→ S00001   PFSAMPA     816  SELECT        3.10 ==
      > SELECT NEXTLIM INTO : H FROM MRATE WHERE CURATE = : H

→ S00005   PFSAMPC    3054  FETCH        2.29 =
→ S00012   PFSAMPB     678  SELECT        1.94 =
→ S00011   PFSAMPC    1316  SELECT        1.47 =
→ S00010   PFSAMPB     816  UPDATE        1.40 =
→ S00007   PFSAMPC    3179  SELECT        1.09 =
→ S00002   PFSAMPC    1347  SELECT        0.89
→ S00009   PFSAMPC    3155  SELECT        0.79
→ S00008   PFSAMPC    2989  SELECT        0.68
→ S00013   PFSAMPC    1433  OPEN          0.60
→ S00004   PFSAMPC    3046  OPEN          0.30
→ S00014   PFSAMPC    1562  CLOSE         0.14
→ S00006   PFSAMPC    3065  CLOSE         0.12

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Plan Seqno, SQL Seqno | Display context help information. |
| ++ | Plan Seqno, SQL Seqno | Show additional details. |
| + | Plan Seqno, SQL Seqno | Expand to reveal next level. |
| - | Plan Seqno, SQL Seqno | Collapse to hide next level. |
| M | SQL Seqno | Display load module information. |
| P | SQL Seqno | Display source program mapping. |
| EX | SQL Seqno | Display DB2 EXPLAIN data |
| | | |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Seqno, Percent of Time | Display context help information. |
| + | Seqno | Expand to reveal all entries. |
| + | Percent of Time | Zoom in scale. |
| - | Seqno | Collapse to show only first level. |
| - | Percent of Time | Zoom out scale. |
| SV | Seqno | Sort next level by value. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. For example, entering “++” on an SQL line will cause this detail window to pop up:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| > S00012   3179 SELECT                               0.84 |
+-----+

Calculation Details
DB2 SQL activity measurements           84
SQL request                             SELECT
In program                              PFSAMPC
Precompiler statement number           3179
Total measurements                     10,000
Percent of total                       0.84

SQL Statement Information
Subsystem name DSN1                      Attach type  SASS
Plan name     PFSAMPA                    Plan bind time May-11-05 13:57:39

DBRM name     PFSAMPC                    DBRM token   179FD30A 1B977868
DBRM date/time May-11-05 13:56:56

Package ID    PFSAMPC                    Location     CABNETDB24
Collectn name PFSAMPX1                   Pkg BIND time May-11-05 13:57:36

SQL function  SELECT                      Static/dynamic Static
Precmplr stmt# 3179                      DBRM section# 21
CSECT/module  PFSAMPC in PFSAMPC         Offset of call 00008610
Sample count  84                          SQL req count 172
SQL CPU time  0.28                        Service time  0.45

SQL Statement:  SELECT * INTO : H , : H , : H : H , : H FROM VDEPT
                WHERE DEPTNO = : H
  
```

SETUP options

The following SETUP option can be selected with the SETUP primary command:

Minimum percentage of time

You can set this option to eliminate reporting of SQL activity where the percentage of time is below a certain threshold.

F06 - DB2 SQL statement attributes

Usage

Use this report to see detailed information about each of the measured SQL statements. This is useful as a reference report when working with printed copies of other DB2 reports that do not show full SQL statement details. (When browsing online, the pop-up detail windows show this information.) The following information is shown for each SQL statement for which activity was observed.

| Under Heading | This is Displayed |
|------------------|--|
| SQL Statement ID | A unique sequence number assigned by Application Performance Analyzer to the SQL statement. This is shown in other DB2 reports that display SQL statement information. |

| Under Heading | This is Displayed |
|----------------------|--|
| Subsystem name | The name of the DB2 subsystem under which the SQL statement was executed. |
| Attachment type | The type of DB2 attachment for the thread under which the SQL statement was executed. |
| Plan name | The name of the DB2 plan under which the SQL statement was executed. |
| Plan Bind Time | The date and time of the BIND of the plan. |
| DBRM Name | The name of the DBRM under which the SQL statement was executed. |
| DBRM Token | The DBRM consistency token. This is an 8 byte hexadecimal value that identifies the DBRM. |
| DBRM Date/Time | The date and time of the DBRM. This is the time at which the precompiler created the DBRM. |
| Package ID | The package ID. This is omitted if there was no package bound for the DBRM. |
| Location | The location name associated with the package. This is omitted if there was no package bound for the DBRM. |
| Collection Name | The collection name for the package. This is omitted if there was no package bound for the DBRM. |
| Package Bind Time | The date and time of the BIND of the package. This is omitted if there was no package bound for the DBRM. |
| SQL Function | The SQL function: SELECT, UPDATE, FETCH, etc. |
| Precmplr Stmt# | The statement number assigned by the precompiler to the SQL statement. |
| Static/Dynamic | This indicates if the SQL request was Static or Dynamic. |
| DBRM Section# | The section number assigned by the precompiler to the SQL statement. Groups of related statements (such as OPEN, FETCH, CLOSE) are correlated using the section number. |
| PREPARE Stmt# | The statement number of the corresponding PREPARE statement. This field only applies to dynamic SQL statement that operate on SQL text processed by a corresponding PREPARE statement. In order for this information to appear, it is required that execution of the corresponding PREPARE was sampled. |
| CSECT/Module | The name of the load module and CSECT in which the SQL call was issued. |
| Offset of Call | The offset of the SQL call return address in the CSECT or module. |
| SQL Req Count | The number of SQL calls counted for the indicated statement. This information is available only if the DB2+ measurement option was active. It indicates the number of calls counted at the indicated SQL statement number for the duration of the measurement. Counting begins when the first SQL call is sampled. |
| Sample Count | The number of Samples in which execution of the indicate statement was measured. |

| Under Heading | This is Displayed |
|--------------------|--|
| Total CPU Time | The total CPU time consumed by processing of the indicated statement in the measured region. This information is available only if the DB2+ measurement option was active. It indicates the accumulated CPU time used by the indicated SQL statement number for the duration of the measurement. Accumulation begins when the first SQL call is sampled. |
| Total Service Time | The total service time for processing of the indicated statement. This information is available only if the DB2+ measurement option was active. It indicates the accumulated service time used by the indicated SQL statement number for the duration of the measurement. Accumulation begins when the first SQL call is sampled. |
| SQL Statement | The SQL statement text. |

Sample reports

A sample report is shown here:

```

File View Navigate Help
-----
F06: DB2 SQL Statement Attributes (1623/CICS23A)          Row 00001 of 00324
Command ==> _____ Scroll ==> CSR

SQL Statement Id 00001

Subsystem name DSN1          Attach type SASS
Plan name     PFSAMPA        Plan BIND time Nov-28-04 14:11:17

DBRM name     PSSAMPA        DBRM token     17859595 050DCBBC
DBRM date/time Nov-25-04 14:50:15

Package ID    PFSAMPA          Location       CABNETDB24
Collectn name PFSAMPX1        Pkg BIND time no data

SQL function  SELECT                  Static/dynamic Static
Precmplr stmt# 816                    DBRM section# 1
CSECT/module  PFSAMPA in PFSAMPA     Offset of call 000007FA
Sample count  324                    SQL req count 342
SQL CPU time  0.91                   Service time  1.72

SQL Statement:  SELECT NEXTLIM INTO : H FROM MRATE WHERE CURATE = :
                H

SQL Statement Id 00002

Subsystem name DSN1          Attach type SASS
Plan name     PFSAMPA        Plan BIND time Nov-28-04 14:11:17

DBRM name     PFSAMPC          DBRM token     17859595 06957A24
DBRM date/time Nov-25-04 14:49:42

Package ID    PFSAMPC          Location       CABNETDB24
Collectn name PFSAMPX1        Pkg BIND time no data

SQL function  SELECT                  Static/dynamic Static
Precmplr stmt# 1316                    DBRM section# 6

```

F07 - DB2 SQL wait time by DBRM

Usage

Use this report to see information about WAIT time that occurred during the processing of SQL requests. The percentage of time is reported for each module (DBRM) that issued SQL requests and is expressed as the percentage of the total measurement interval.

In addition, a SETUP option lets you choose to see the WAIT time expressed as a percentage of SQL service time. The two quantification options help answer these questions about SQL processing wait time:

- For how much of the overall measurement interval was the address space in a WAIT during SQL processing?
- For how much of the SQL processing time was the address space in a WAIT?

You can further expand each module line to see a further breakdown and quantification by individual SQL statements.

Note: This report shows all SQL calls that were sampled, but when the DB2+ feature is active it will not show SQL calls that were measured by the DB2+ feature but not sampled.

Quantification

Each report line quantifies wait time for all SQL requests issued by a module (DBRM). This is further broken down by SQL request.

Depending on a report SETUP option, the quantities are expressed as a percentage of the overall measurement interval or as a percentage of the overall service time for the DBRM.

Keep in mind that quantification applies only to the region being measured. DB2 executes in multiple address spaces and a WAIT in the measured address space could indicate the region was suspended while part of the SQL processing was being serviced by another region.

Detail line hierarchy

An unexpanded F07 report shows a line for each module that issued SQL requests. You can expand each line to reveal two additional hierarchical levels of detail (using the "+" line command).

The hierarchy is illustrated here:

```
Level 1 Module (DBRM)
  Level 2 SQL Request
    Level 3 SQL Statement Text
  Level 2 SQL Request
    Level 3 SQL Statement Text
```

...

Detail line descriptions

SQL DBRM (Module) detail line

This is the first-level detail line. Each line shows information about a DBRM (Module) for which SQL request measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The DBRM name. |
| Percent | Either Percent of Total Time or Percent of DBRM SQL Time depending on SETUP option. This is the percentage of time that SQL processing for the indicated DBRM was observed to be in WAIT state. |

SQL request detail line

This is the second-level detail line shown directly under the DBRM/Module detail line. It quantifies the wait time for a specific SQL request.

| Under Heading | This is Displayed |
|---------------|--|
| Name | A sequence number. This is assigned by Application Performance Analyzer to uniquely identify the SQL request. Either "S" or "D" precedes the sequence number indicating if the SQL statement is static or dynamic. |
| Stmt# | The precompiler statement number of the SQL statement. |
| SQL Function | The SQL function. |
| Percent | The percentage of the total time or of the DBRM time (depending on SETUP option) for which SQL processing for the indicated statement was in WAIT state. |

SQL statement text detail line

This is third-level detail line shown directly under the SQL request detail line. It shows the SQL statement text. If necessary, more than one line is displayed in order to show the full SQL text.

Sample reports

This shows the report with one DBRM expanded to the second level (SQL statement):

```

File View Navigate Help
-----
F07: SQL WAIT Time by DBRM (0611/CICS23A) Row 00001 of 00009
Command ==> _____ Scroll ==> CSR

Name      Stmt#  SQL Function  Percent of Total Time * 10.00% ±2.5%
          *....1....2....3....4....5....6....7.
PFSAMPD           25.49 =====
→ S00001    435  FETCH        12.05 =====
→ S00003    541  UPDATE        7.50 ===
→ S00004    465  FETCH         3.95 ==
→ S00002    455  FETCH         1.91 =
→ S00005    485  FETCH         0.06
→ S00008    462  OPEN          0.00
→ S00006    481  CLOSE         0.00
→ S00007    451  CLOSE         0.00

```

You can use the + command to expand an SQL statement and show the SQL text as shown here:


```

File View Navigate Help
-----
F07: SQL WAIT Time by DBRM (0611/CICS23A) Row 00001 of 00009
Command ==> _____ Scroll ==> CSR

Name      Stmt#  SQL Function  Percent of Total Time * 10.00% ±2.5%
          *....1....2....3....4....5....6....7.
PFSAMPD           25.49 =====
→ S00001    435  FETCH           12.05 =====
→ S00003    541  UPDATE           7.50  ==
→ S00004    465  FETCH           3.95  ==
→ S00002    455  FETCH           1.91  =
  > DECLARE RATE2 CURSOR FOR SELECT * FROM CUSTAMTS
→ S00005    485  FETCH           0.06
→ S00008    462  OPEN            0.00
→ S00006    481  CLOSE           0.00
→ S00007    451  CLOSE           0.00

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field.)

on objects


| Cmd | When Applied To Object | Action |
|-----|------------------------|---|
| ? | DBRM, Seqno | Display context help information. |
| ++ | DBRM, Seqno | Show additional details. |
| + | DBRM, Seqno | Expand to reveal next level. |
| - | DBRM, Seqno | Collapse to hide next level. |
| M | DBRM, Seqno | Display load module information. |
| P | Seqno | Display source program mapping. |
| SV | DBRM | Sort next level by value. |
| SS | DBRM | Sort lines by program and statement number. |
| EX | Seqno | Display DB2 EXPLAIN data |

on headings

| Cmd | When Applied To Object | Action |
|-----|-----------------------------|------------------------------------|
| ? | Name, Percent of Total Time | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Percent of Total Time | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Percent of Total Time | Zoom out scale. |
| SV | Seqno | Sort next level by value. |
| SN | Name | Sort next level entries by name |

SETUP options

Enter the SETUP primary command to select options for this report. The following option is available:



F08 - DB2 SQL wait time by statement

Usage

Use this report to see information about WAIT time that occurred during the processing of SQL requests. The percentage of time is reported for each SQL statement sampled during the measurement.

In addition, a SETUP option lets you choose to see the WAIT time expressed as a percentage of SQL service time. The two quantification options help answer these questions about SQL processing wait time:

- For how much of the overall measurement interval was the address space in a WAIT during SQL processing?
- For how much of the SQL processing time was the address space in a WAIT?

Note: This report shows all SQL calls that were sampled, but when the DB2+ feature is active it will not show SQL calls that were measured by the DB2+ feature but not sampled.

Quantification

Each report line quantifies wait time for an SQL request observed during the measurement.

Depending on a report SETUP option, the quantities are expressed as a percentage of the overall measurement interval or as a percentage of the overall service time for the SQL statement.

Keep in mind that quantification applies only to the region being measured. DB2 executes in multiple address spaces and a WAIT in the measured address space could indicate the region was suspended while part of the SQL processing was being serviced by another region.

Detail line hierarchy

An unexpanded F08 report shows a line for each observed SQL statement. You can expand each line to reveal one additional hierarchical level of detail (using the "+" line command).

The hierarchy is illustrated here:

```
Level 1 SQL Request
  Level 2 SQL Statement Text
Level 1 SQL Request
  Level 2 SQL Statement Text
...
```

Detail line descriptions

SQL request detail line

This is the first-level detail line. It quantifies the wait time for a specific SQL request.

| Under Heading | This is Displayed |
|-----------------------|--|
| Seqno | A sequence number. This is assigned by Application Performance Analyzer to uniquely identify the SQL request. Either "S" or "D" precedes the sequence number indicating if the SQL statement is static or dynamic. |
| Program | The DBRM name for the program that issued the SQL request. |
| Stmt# | The precompiler statement number. This is the statement number assigned by the precompiler to the SQL request. |
| SQL Function | The SQL function. This is the name of the SQL function: SELECT, FETCH, UPDATE, etc. |
| Percent of Total Time | The percentage of the total time or of the SQL statement service time (depending on SETUP option) for which processing for the indicated statement was in WAIT state. |

SQL statement text detail line

This is second-level detail line shown directly under the SQL request detail line. It shows the SQL statement text. If necessary, more than one line is displayed in order to show the full SQL text.

Sample reports

This shows the report with one of the SQL statements expanded to show the next level, which is SQL text.

```

File View Navigate Help
-----
F08: SQL WAIT Time by Statement (0611/CICS23A)          Row 00001 of 00010
Command ==> _____ Scroll ==> CSR

Seqno  Program  Stmt#  SQL Function  Percent of Total Time * 10.00%  ±2.5%
      *...1...2...3...4...5...6...7...
S00001  PFTESTD   435    FETCH         12.05 =====
S00003  PFTESTD   541    UPDATE         7.50  ===
S00004  PFTESTD   465    FETCH         3.95  ==
S00002  PFTESTD   455    FETCH         1.91  =
      > DECLARE RATE2 CURSOR FOR SELECT * FROM CUSTAMTS

S00005  PFTESTD   485    FETCH         0.06
S00007  PFTESTD   451    CLOSE         0.00
S00008  PFTESTD   462    OPEN          0.00
S00006  PFTESTD   481    CLOSE         0.00

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Seqno | Display context help information. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|----------------------------------|
| ++ | Seqno | Show additional details. |
| + | Seqno | Expand to reveal next level. |
| - | Seqno | Collapse to hide next level. |
| M | Seqno | Display load module information. |
| P | Seqno | Display source program mapping. |
| EX | Seqno | Display DB2 EXPLAIN data |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------------|--|
| ? | Seqno, Percent of Total Time | Display context help information. |
| + | Seqno | Expand to reveal all entries. |
| + | Percent of Total Time | Zoom in scale. |
| - | Seqno | Collapse to show only first level. |
| - | Percent of Total Time | Zoom out scale. |
| SV | Seqno | Sort next level by value. |
| SS | Seqno | Sort next level by program and statement number. |

SETUP options

Enter the SETUP primary command to select options for this report. The following option is available:

```

File View Navigate Help
+-----+
| Options for DB2 SQL wait time by statement |
|                                           |
| Enter "/" to select an option           |
|   - Quantify wait time as a percentage of total |
|     measurement interval. Unselect to quantify |
|     as a percentage of the SQL service time for |
|     the SQL statement.                   |
+-----+

```

F09 - DB2 SQL wait time by plan

Usage

Use this report to see information about WAIT time that occurred during the processing of SQL requests. The percentage of time is reported for each observed DB2 Plan under which SQL requests were issued. It is expressed as the percentage of the total measurement interval.

In addition, a SETUP option lets you choose to see the WAIT time expressed as a percentage of SQL service time. The two quantification options help answer these questions about SQL processing wait time:

1. For how much of the overall measurement interval was the address space in a WAIT during SQL processing?

2. For how much of the SQL processing time was the address space in a WAIT?

You can further expand each DB2 Plan line to see a further breakdown and quantification by individual SQL statements. The SQL statements can be expanded to show the SQL text.

Note: This report shows all SQL calls that were sampled, but when the DB2+ feature is active it will not show SQL calls that were measured by the DB2+ feature but not sampled.

Quantification

Each report line quantifies wait time for all SQL requests issued under a DB2 Plan. This is further broken down by SQL request.

Depending on a report SETUP option, the quantities are expressed as a percentage of the overall measurement interval or as a percentage of the overall service time under the Plan.

Keep in mind that quantification applies only to the region being measured. DB2 executes in multiple address spaces and a WAIT in the measured address space could indicate the region was suspended while part of the SQL processing was being serviced by another region.

Detail line hierarchy

An unexpanded F09 report shows a line for each module that issued SQL requests. You can expand each line to reveal two additional hierarchical levels of detail (using the “+” line command).

The hierarchy is illustrated here:

```
Level 1 DB2 Plan
Level 2 SQL Request
  Level 3 SQL Statement Text
Level 2 SQL Request
  Level 3 SQL Statement Text
...
```

Detail line descriptions

DB2 plan detail line

This is the first-level detail line. Each line shows information about a DB2 Plan under whose execution SQL request measurement data was recorded.

| Under Heading | This is Displayed |
|-----------------------|--|
| Seqno | A sequence number assigned, by Application Performance Analyzer, to the DB2 plan. |
| Plan/Pgm | The name of a DB2 plan. |
| Percent of Total Time | The percentage of the total time or of the SQL processing time for the PLAN (depending on SETUP option) for which SQL processing under the plan was in WAIT state. |

SQL request detail line

This is the second-level detail line shown directly under the Plan detail line. It quantifies the wait time for a specific SQL request.

| Under Heading | This is Displayed |
|-----------------------|--|
| Seqno | A sequence number. This is assigned by Application Performance Analyzer to uniquely identify the SQL request. Either "S" or "D" precedes the sequence number indicating if the SQL statement is static or dynamic. |
| Plan/Pgm | The name of a DB2 plan. |
| Stmt# | The precompiler statement number. This is the statement number assigned by the precompiler to the SQL request. |
| SQL Function | The SQL function. The is the name of the SQL function: SELECT, FETCH, UPDATE, etc. |
| Percent of Total Time | The percentage of the total time or of the SQL processing time for the PLAN (depending on SETUP option) for which processing for the indicated statement was in WAIT state. |

SQL statement text detail line

This is third-level detail line shown directly under the SQL request detail line. It shows the SQL statement text. If necessary, more than one line is displayed in order to show the full SQL text.

Sample reports

In this sample, the P0001 plan line has been expanded to the second level (SQL statement), and one of the statements has been expanded to the third level to show the SQL text.

```

File View Navigate Help
-----
F09: SQL WAIT Time by Plan (0611/CICS23A) Row 00001 of 00010
Command ==> _____ Scroll ==> CSR

Seqno   Plan/Pgm  Stmt#  SQL Function  Percent of Total Time * 10.00% ±2.5%
          *....1....2....3....4....5....6....7...
P0001   PFPLN022          25.49 =====
-> S00001 PFTESTD   435  FETCH        12.05 =====
-> S00003 PFTESTD   541  UPDATE        7.50 =====
-> S00004 PFTESTD   465  FETCH         3.95 ==
-> S00002 PFTESTD   455  FETCH         1.91 =
      > DECLARE RATE2 CURSOR FOR SELECT * FROM CUSTAMTS
-> S00005 PFTESTD   485  FETCH         0.06

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Plan Seqno, Seqno | Display context help information. |
| ++ | Plan Seqno, Seqno | Show additional details. |
| + | Plan Seqno, Seqno | Expand to reveal next level. |
| - | Plan Seqno, Seqno | Collapse to hide next level. |
| M | Seqno | Display load module information. |
| P | Seqno | Display source program mapping. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|--------------------------|
| EX | Seqno | Display DB2 EXPLAIN data |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Seqno,Percent of Time | Display context help information. |
| + | Seqno | Expand to reveal all entries. |
| + | Percent of Time | Zoom in scale. |
| - | Seqno | Collapse to show only first level. |
| - | Percent of Time | Zoom out scale. |
| SV | Seqno | Sort next level by value. |

SETUP options

Enter the SETUP primary command to select options for this report. The following option is available:

```

File View Navigate Help
+-----+
| Options for DB2 SQL wait time by plan |
|                                       |
| Enter "/" to select an option       |
|   - Quantify wait time as a percentage of total |
|     measurement interval. Unselect to quantify |
|     as a percentage of the SQL service time for |
|     the plan.                         |
+-----+

```

F10 - DB2 SQL CPU/Svc time by DBRM

Usage

A prerequisite for this report is activation of the DB2+ option during the measurement. This option records exact SQL call counts, total SQL service time and total SQL processing CPU time by embedded SQL statement. When measuring a distributed data facility (DDF) address space, SQL Enclave and SQL zIIP CPU times are also recorded. This report shows quantification by DBRM. You can further expand each DBRM line to see a further breakdown and quantification by individual embedded SQL statement.

Quantification

Each report line shows the following for each DBRM and, when expanded, for each SQL statement observed in the DBRM.

- Number of SQL calls.
- Total CPU time for the SQL call processing.
- Mean SQL call CPU time, or percent of total used.
- Total service time for the SQL call processing.
- Mean SQL call service time, or percent of total used.

A setup option is available to display the percent used in place of the mean fields. Keep in mind that measured CPU time applies only to the region being measured. DB2 executes in multiple address spaces and CPU could also be consumed in other DB2 regions not reflected in this report. For DDF only, this is reflected in the enclave CPU times shown in the detail windows of this report.

Detail line descriptions

SQL DBRM (Module) detail line

This is the first-level detail line. Each line shows information about a DBRM (Module) for which SQL request measurement data was recorded.

| Under Heading | This is Displayed |
|-----------------|--|
| Name | The DBRM name. |
| Nbr of Calls | The number of SQL calls counted for this DBRM. |
| CPU Time: Total | The total CPU time for all SQL calls counted for this DBRM. Large numbers will be expressed in minutes with an M suffix. |
| CPU Time: Mean | The mean CPU time per SQL call. Large numbers will be expressed in minutes with an M suffix. |
| CPU time: Pct | The percent of total CPU time this DBRM used. |
| Svc Time: Total | The total service time for all SQL calls for this DBRM. Large numbers will be expressed in minutes with an M suffix. |
| Svc Time: Mean | The mean service time per SQL call. Large numbers will be expressed in minutes with an M suffix. |
| Svc time: Pct | The percent of total service time this DBRM used. |

SQL request detail line

This is the second-level detail line shown directly under the DBRM/Module detail line. It quantifies an individual SQL statement.

| Under Heading | This is Displayed |
|-----------------|--|
| Name | A sequence number. This is assigned by Application Performance Analyzer to uniquely identify the SQL request. Either "S" or "D" precedes the sequence number indicating if the SQL statement is static or dynamic. |
| Stmnt# | The precompiler statement number. This is the statement number assigned by the precompiler to the SQL request. When the statement number is zero, it indicates that the SQL statement was not produced by the DB2 precompiler or the SQL preprocessor, but was generated by some other means. For example, JDBC SQL statements have statement numbers that are zero. |
| SQL Function | The SQL function. This is the name of the SQL function: SELECT, FETCH, UPDATE, etc. |
| Nbr of Calls | The number of SQL calls counted for this SQL statement. |
| CPU Time: Total | The total CPU time for all SQL calls counted for this statement. Large numbers will be expressed in minutes with an M suffix. |
| CPU Time: Mean | The mean CPU time per SQL call. Large numbers will be expressed in minutes with an M suffix. |
| CPU Time: Pct | The percent of total CPU time this statement used. |

| Under Heading | This is Displayed |
|-----------------|---|
| Svc Time: Total | The total service time for all SQL calls for this statement. Large numbers will be expressed in minutes with an M suffix. |
| Svc Time: Mean | The mean service time per SQL call. Large numbers will be expressed in minutes with an M suffix. |
| Svc Time: Pct | The percent of total service time this statement used. |

SQL statement text detail line

This is third-level detail line shown directly under the SQL request detail line. It shows the SQL statement text. If necessary, more than one line is displayed in order to show the full SQL text.

Sample reports

This sample shows the report expanded to the second level (SQL statement), and one of the statements has been expanded to the third level to show the SQL text.

```

File View Navigate Help
-----
F10: SQL CPU/Service Time by DBRM (1286/CICS23A)          Row 00001 of 00014
Command ==>>> _____ Scroll ==>>> CSR

Name          Stmt#  SQL Function      Nbr of  --CPU Time--  --Svc Time--
                SQL Calls  Total    Mean         Total    Mean
PFSAMPC                1,204    3.08  0.00256    5.57  0.00462
± S00003          1466  FETCH              516    2.27  0.00441    3.86  0.00749
→ S00006          1316  SELECT              172    0.39  0.00227    1.01  0.00588
→ S00005          1347  SELECT              172    0.25  0.00150    0.40  0.00232
    > SELECT CUSACCT INTO : H FROM ACTINFO WHERE SPCRATE =
    > : H AND INDX01 = '01'

→ S00008          1443  OPEN                172    0.11  0.00064    0.21  0.00122
→ S00007          1562  CLOSE               172    0.04  0.00026    0.07  0.00045
PFSAMPB                514    1.04  0.00203    1.70  0.00331
→ S00002           672  SELECT              342    0.69  0.00204    1.13  0.00332
→ S00004           810  UPDATE              172    0.34  0.00201    0.56  0.00331
PFSAMPA                342    0.84  0.00246    1.74  0.00511
→ S00002           815  SELECT              342    0.84  0.00246    1.74  0.00511

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | DBRM, Seqno | Display context help information. |
| ++ | DBRM, Seqno | Show additional details. |
| + | DBRM, Seqno | Expand to reveal next level. |
| - | DBRM, Seqno | Collapse to hide next level. |
| M | DBRM, Seqno | Display load module information. |
| P | Seqno | Display source program mapping. |
| SV | DBRM | Sort next level entries by value. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|---|
| SS | DBRM | Sort lines by program and statement number. |
| EX | Seqno | Display DB2 EXPLAIN data |
| SD | DBRM | Sort next level entries by service time |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|---|
| ? | Name | Display context help information. |
| + | Name | Expand to reveal all entries. |
| - | Name | Collapse to show only first level. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level entries by name |
| SD | Name | Sort next level entries by service time |

SETUP options

Enter the SETUP primary command to select options for this report. The following window is displayed:

```

File View Navigate Help
+-----+
| Options for DB2 SQL CPU/Svc Time by DBRM |
| Enter "/" to select an option           |
|   _ Display Percent used in place of Mean fields |
+-----+

```

Display Percent used in place of Mean fields

When selected, this displays the percent of total CPU and total service time used by each DBRM (Module) and SQL statement, rather than the mean time.

F11 - DB2 SQL CPU/Svc time by stmt

Usage

A prerequisite for this report is activation of the DB2+ option during the measurement. This option records exact SQL call counts, total SQL service time and total SQL processing CPU time by embedded SQL statement. When measuring a distributed data facility (DDF) address space, SQL Enclave and SQL zIIP CPU times are also recorded.

Quantification

Each report line shows the following for each SQL statement:

- Number of SQL calls.
- Total CPU time for the SQL call processing.
- Mean SQL call CPU time, or percent of total used.
- Total service time for the SQL call processing.
- Mean service time per SQL call, or percent of total used.

A setup option is available to display the percent used in place of the mean fields. Keep in mind that measured CPU time applies only to the region being measured. DB2 executes in multiple address spaces and CPU could also be consumed in other DB2 regions not reflected in this report. For DDF only, this is reflected in the enclave CPU times shown in the detail windows of this report.

Detail line hierarchy

An unexpanded F11 report shows a line for each measured SQL request. You can expand each line to reveal one additional hierarchical level of detail (using the “+” line command).

The hierarchy is illustrated here:

```

Level 1 SQL Request
  Level 2 SQL Statement Text
Level 2 SQL Request
  Level 3 SQL Statement Text

```

...

Detail line descriptions

SQL request detail line

This is the first-level detail line. It quantifies an individual SQL statement.

| Under Heading | This is Displayed |
|-----------------|--|
| Seqno | A sequence number. This is assigned by Application Performance Analyzer to uniquely identify the SQL request. Either “S” or “D” precedes the sequence number indicating if the SQL statement is static or dynamic. |
| Name | The DBRM name. |
| Stmt# | The precompiler statement number. This is the statement number assigned by the precompiler to the SQL request. When the statement number is zero, it indicates that the SQL statement was not produced by the DB2 precompiler or the SQL preprocessor, but was generated by some other means. For example, JDBC SQL statements have statement numbers that are zero. |
| SQL Function | The SQL function. This is the name of the SQL function: SELECT, FETCH, UPDATE, etc. |
| Nbr of Calls | The number of SQL calls counted for this SQL statement. |
| CPU Time: Total | The total CPU time for all SQL calls counted for this statement. Large numbers will be expressed in minutes with an M suffix. |
| CPU Time: Mean | The mean CPU time per SQL call. Large numbers will be expressed in minutes with an M suffix. |
| CPU time: Pct | The percent of total CPU time this statement used. |
| Svc Time: Total | The total service time for all SQL calls for this statement. Large numbers will be expressed in minutes with an M suffix. |
| Svc Time: Mean | The mean service time per SQL call. Large numbers will be expressed in minutes with an M suffix. |
| Svc time: Pct | The percent of total service time this statement used. |

SQL statement text detail line

This is second-level detail line shown directly under the SQL request detail line. It shows the SQL statement text. If necessary, more than one line is displayed in order to show the full SQL text.

Sample reports

This sample shows the report with one of the lines expanded to the second level to show SQL text.

```

File View Navigate Help
-----
F11: SQL CPU/Service Time by Statement (1300/CICS23A)          Row 00001 of 00017
Command ==>>> _____ Scroll ==>>> CSR

Seqno  Name      Stmt#  SQL Function  Nbr of  --CPU Time--  --Svc Time--
      Name      SQL Calls  Total  Mean      Total  Mean
S00007 PFSAMPC   1466  FETCH          344   1.48   0.00432   2.35   0.00685
S00001 PFSAMPA   816   SELECT          342   0.88   0.00258   1.70   0.00497
      > SELECT NEXTLIM INTO : H FROM MRATE WHERE CURATE = : H

S00009 PFSAMPC   3054  FETCH          1,720 0.74   0.00043   1.15   0.00066
S00003 PFSAMPB   678   SELECT          342   0.47   0.00137   0.75   0.00221
S00004 PFSAMPC   1316  SELECT          172   0.42   0.00249   0.76   0.00446
S00010 PFSAMPB   816   UPDATE          172   0.39   0.00231   0.75   0.00441
S00002 PFSAMPB   408   SET HOST VAR    342   0.38   0.00112   0.72   0.00211
S00005 PFSAMPC   1347  SELECT          172   0.27   0.00161   0.48   0.00282
S00014 PFSAMPC   3155  SELECT          172   0.27   0.00160   0.41   0.00243
S00012 PFSAMPC   3179  SELECT          172   0.27   0.00158   0.47   0.00277
S00011 PFSAMPC   2989  SELECT          172   0.22   0.00130   0.38   0.00221
S00008 PFSAMPC   3046  OPEN            172   0.20   0.00121   0.29   0.00170
S00006 PFSAMPC   1443  OPEN            172   0.11   0.00067   0.31   0.00181
S00013 PFSAMPC   1562  CLOSE           172   0.04   0.00028   0.08   0.00048
S00015 PFSAMPC   3065  CLOSE           172   0.03   0.00021   0.05   0.00034

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Seqno | Display context help information. |
| ++ | Seqno | Show additional details. |
| + | Seqno | Expand to reveal next level. |
| - | Seqno | Collapse to hide next level. |
| M | Seqno | Display load module information. |
| P | Seqno | Display source program mapping. |
| EX | Seqno | Display DB2 EXPLAIN data |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Seqno | Display context help information. |
| + | Seqno | Expand to reveal all entries. |
| - | Seqno | Collapse to show only first level. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|---|
| SV | Seqno | Sort next level by value. |
| SS | Seqno | Sort lines by program and stmt number |
| SD | Seqno | Sort next level entries by service time |

SETUP options

Enter the SETUP primary command to select options for this report. The following window is displayed:

```

+-----+
| Options for DB2 SQL CPU/Svc Time by Stmt |
|                                           |
| Enter "/" to select an option           |
| / Show SQL statements with a positive  |
|   SQLCODE                               |
|   (these are successful calls).         |
|                                           |
| / Show SQL statements with a negative  |
|   SQLCODE                               |
|   (these are failed calls).            |
|                                           |
| / Show SQL statements by statement      |
|   number and ignore differences in     |
|   SQL text.                            |
|                                           |
| /Display Percent used in place of      |
|   Mean fields                           |
|                                           |
+-----+

```

Show SQL statements with positive SQLCODE

This shows SQL statements that end successfully with a zero or positive SQLCODE. When selected, successful SQL statements are included in the report.

Show SQL statements with negative SQLCODE

This shows SQL statements that are unsuccessful; that is, with a negative SQLCODE. When selected, unsuccessful SQL statements are included in the report.

Show SQL statements by statement number

This displays dynamic SQL statements consolidated by statement number and ignores differences in the SQL text. When selected, only one line is displayed per statement number regardless of the contents of the SQL text. The detail window for each statement number displays the SQL information for the first call from this statement.

Display Percent used in place of Mean fields

When selected, this displays the percent of total CPU and total service time used by each SQL statement, rather than the mean time.

F12 - DB2 SQL CPU/Svc time by plan

Usage

A prerequisite for this report is activation of the DB2+ option during the measurement. This option records exact SQL call counts, total SQL service time and total SQL processing CPU time by embedded SQL statement. When measuring a distributed data facility (DDF) address space, SQL Enclave and SQL zIIP CPU

times are also recorded. This report shows quantification by DB2 Plan. You can further expand each DB2 Plan line to see a further breakdown and quantification by individual embedded SQL statement.

Quantification

Each report line shows the following for each DB2 Plan and, when expanded, for each SQL statement observed under the Plan.

- Number of SQL calls.
- Total CPU time for the SQL call processing.
- Mean SQL call CPU time, or percent of total used.
- Total service time for the SQL call processing.
- Mean SQL call service time, or percent of total used.

A setup option is available to display the percent used in place of the mean fields. Keep in mind that measured CPU time applies only to the region being measured. DB2 executes in multiple address spaces and CPU could also be consumed in other DB2 regions not reflected in this report. For DDF only, this is reflected in the enclave CPU times shown in the detail windows of this report.

Detail line hierarchy

An unexpanded F12 report shows a line for each DB2 Plan under which SQL request were issued. You can expand each line to reveal two additional hierarchical levels of detail (using the “+” line command).

The hierarchy is illustrated here:

```

Level 1 DB2 Plan
Level 2 SQL Request
Level 3 SQL Statement Text
Level 2 SQL Request
Level 3 SQL Statement Text
...

```

Detail line descriptions

DB2 Plan detail line

This is the first-level detail line. Each line shows information about a DB2 Plan under which SQL request measurement data was recorded.

| Under Heading | This is Displayed |
|-----------------|---|
| Seqno | A sequence number assigned, by Application Performance Analyzer, to the DB2 plan. |
| Plan/Pgm | The DB2 Plan name. |
| Nbr of Calls | The number of SQL calls counted for this DB2 Plan. |
| CPU Time: Total | The total CPU time for all SQL calls counted for this statement. Large numbers will be expressed in minutes with an M suffix. |
| CPU Time: Mean | The mean CPU time per SQL call. Large numbers will be expressed in minutes with an M suffix. |
| CPU time: Pct | The percent of total CPU time this plan used. |
| Svc Time: Total | The total service time for all SQL calls for this statement. Large numbers will be expressed in minutes with an M suffix. |
| Svc Time: Mean | The mean service time per SQL call. Large numbers will be expressed in minutes with an M suffix. |

| Under Heading | This is Displayed |
|---------------|---|
| SVC time: Pct | The percent of total service time this plan used. |

SQL request detail line

This is the second-level detail line shown directly under the DB2 Plan detail line. It quantifies an individual SQL statement.

| Under Heading | This is Displayed |
|-----------------|--|
| Seqno | A sequence number. This is assigned by Application Performance Analyzer to uniquely identify the SQL request. Either "S" or "D" precedes the sequence number indicating if the SQL statement is static or dynamic. |
| Plan/Pgm | The DBRM name. |
| Stmnt# | The precompiler statement number of the SQL statement. When the statement number is zero, it indicates that the SQL statement was not produced by the DB2 precompiler or the SQL preprocessor, but was generated by some other means. For example, JDBC SQL statements have statement numbers that are zero. |
| SQL Function | The SQL function. |
| Nbr of Calls | The number of SQL calls counted for this statement. |
| CPU Time: Total | The total CPU time for all SQL calls counted for this statement. Large numbers will be expressed in minutes with an M suffix. |
| CPU Time: Mean | The mean CPU time per SQL call. Large numbers will be expressed in minutes with an M suffix. |
| CPU time: Pct | The percent of total CPU time this statement used. |
| Svc Time: Total | The total service time for all SQL calls for this statement. Large numbers will be expressed in minutes with an M suffix. |
| Svc Time: Mean | The mean service time per SQL call. Large numbers will be expressed in minutes with an M suffix. |
| SVC time: Pct | The percent of total service time this statement used. |

SQL statement text detail line

This is third-level detail line shown directly under the SQL request detail line. It shows the SQL statement text. If necessary, more than one line is displayed in order to show the full SQL text.

Sample reports

This sample shows the report with the plan expanded to the second level and one of the SQL statement lines expanded to the third level to show SQL text.

```

File View Navigate Help
-----
F12: SQL CPU/Service Time by Plan (1300/CICS23A) Row 00001 of 00018
Command ==> _____ Scroll ==> CSR

Seqno Plan/PGM Stmt# SQL Function Nbr of SQL Calls --CPU Time-- --Svc Time--
Total Mean Total Mean
P0001 PFSAMPA 4,810 6.25 0.00130 10.73 0.00223
-> S00007 PFSAMPC 1466 FETCH 344 1.48 0.00432 2.35 0.00685
-> S00001 PFSAMPA 816 SELECT 342 0.88 0.00258 1.70 0.00497
    > SELECT NEXTLIM INTO : H FROM MRATE WHERE CURATE = : H
-> S00009 PFSAMPC 3054 FETCH 1,720 0.74 0.00043 1.15 0.00066
-> S00003 PFSAMPB 678 SELECT 342 0.47 0.00137 0.75 0.00221
-> S00004 PFSAMPC 1316 SELECT 172 0.42 0.00249 0.76 0.00446
-> S00010 PFSAMPB 816 UPDATE 172 0.39 0.00231 0.75 0.00441
-> S00002 PFSAMPB 408 SET HOST V 342 0.38 0.00112 0.72 0.00211
-> S00005 PFSAMPC 1347 SELECT 172 0.27 0.00161 0.48 0.00282
-> S00014 PFSAMPC 3155 SELECT 172 0.27 0.00160 0.41 0.00243
-> S00012 PFSAMPC 3179 SELECT 172 0.27 0.00158 0.47 0.00277
-> S00011 PFSAMPC 2989 SELECT 172 0.22 0.00130 0.38 0.00221
-> S00008 PFSAMPC 3046 OPEN 172 0.20 0.00121 0.29 0.00170
-> S00006 PFSAMPC 1443 OPEN 172 0.11 0.00067 0.31 0.00181
-> S00013 PFSAMPC 1562 CLOSE 172 0.04 0.00028 0.08 0.00048
-> S00015 PFSAMPC 3065 CLOSE 172 0.03 0.00021 0.05 0.00034

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|---|
| ? | Plan Seqno, Seqno | Display context help information. |
| ++ | Plan Seqno, Seqno | Show additional details. |
| + | Plan Seqno, Seqno | Expand to reveal next level. |
| - | Plan Seqno, Seqno | Collapse to hide next level. |
| SV | Plan Seqno | Sort next level entries by value. |
| SS | Plan Seqno | Sort lines by program and statement number. |
| M | Seqno | Display load module information. |
| P | Seqno | Display source program mapping. |
| EX | Seqno | Display DB2 EXPLAIN data |
| SD | Plan Seqno | Sort next level entries by service time |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|---|
| ? | Seqno | Display context help information. |
| + | Seqno | Expand to reveal all entries. |
| - | Seqno | Collapse to show only first level. |
| SV | Seqno | Sort next level by value. |
| SD | Seqno | Sort next level entries by service time |

SETUP options

Enter the SETUP primary command to select options for this report. The following window is displayed:

```
File View Navigate Help
+-----+
| Options for DB2 SQL CPU/Svc Time by Plan |
|                                           |
| Enter "/" to select an option          |
|   _ Display Percent used in place of Mean fields |
+-----+
```

Display Percent used in place of Mean fields

When selected, this displays the percent of total CPU and total service time used by each DB2 plan and SQL statement, rather than the mean time.

F13 - DB2 SQL threads analysis

Usage

Use this report to see information about DB2 threads observed during the sampling of SQL call activity.

Quantification

Each report line represents a range of REQCT values for one DB2 thread. A new line is reported each time a reset of the REQCT value occurs for the thread (when the value reaches 32767 and is reset to 1).

Detail line hierarchy

Report F13 shows only one level. The detail lines cannot be expanded.

Detail line descriptions

Thread detail line

| Under Heading | This is Displayed |
|---------------|--|
| SeqNum | A unique sequence number assigned to the DB2 thread. |
| Thread Addr | An address of the DB2 'ACE' control block. |
| Attach | The type of attachment to DB2 for the thread. This can be: CAF, SSRF, CICS, IMS or CIB. |
| REQCT Range | This is the range of REQCT values observed. The lower value is the first REQCT value observed during any measurement sample. Lower values might have occurred during the measurement which were not sampled. The higher value is the last REQCT value observed during a measurement sample. Higher values might have occurred during the measurement which were not sampled. In the case where the range is a continuation after a REQCT reset, a lower value of 1 will be reported. In the case where the range is followed by another detail line after a REQCT reset, an upper value of 32768 will be reported. |

| Under Heading | This is Displayed |
|--------------------|---|
| SQL Calls Executed | The number of SQL calls executed. This number is derived from the REQCT values. |
| SQL Calls Sampled | This is the number of unique REQCT values within the reported range for which samples occurred. This number will often be significantly lower than the Calls Executed number because the rate of SQL call processing is typically much higher than the measurement sampling rate. Hence, not all SQL calls are sampled. |

Sample reports

A sample report is shown here:

```

File View Navigate Help
-----
F13: DB2 Threads Analysis (3398/CICS23A)                               Row 00001 of 00020
Command ==>>> _____ Scroll ==>>> CSR

SeqNum  Thread Addr  Attach  REQCT Range  --- SQL Calls ---
                Executed  Sampled
000035   167CCAD0    CAF     00003-04003    4,001    844
                Thread Totals    4,001    844

000036   167CCA8     CAF     00003-04002    4,000    866
                Thread Totals    4,000    866

000037   172B61F8    CAF     00003-04001    3,999    908
                Thread Totals    3,999    908

```

F14 - DB2 CPU by plan/stored proc

Usage

Use this report to see how CPU resource was consumed by each stored procedure measured during the sampling interval. The percentage of time is reported for each DB2 plan under which measured stored procedure activity was recorded. Expand a plan line to see a further breakdown of time consumption by category.

Quantification

Each report line quantifies CPU usage as a percentage. Each percentage represents the ratio of CPU consumption observed for the reported item to the total CPU consumption measured in the address space.

Detail line hierarchy

An unexpanded F14 report shows a line for each plan that was measured in the stored procedure address space. You can expand each line to reveal additional hierarchical levels of detail (using the "+" line command).

Only the DB2SQL Category hierarchy is shown here. Activity for the Stored Procedure which is not related to SQL processing will be shown in the SYSTEM,

APPLCN, or NOSYMB categories. For information about these other categories, see “C01 - CPU usage by category” on page 74. The hierarchy is illustrated here:

- Level 1 DB2 Plan
- Level 2 DB2SQL Category
- Level 3 DB2 DBRM
- Level 4 DB2 Load Module

Detail line descriptions

DB2 Plan detail line

This is the first-level detail line. Each line shows information about a DB2 Plan for which stored procedure measurement data was recorded.

| Under Heading | This is Displayed |
|-----------------|--|
| Seqno | A sequence number assigned to the DB2 plan. |
| Description | The plan name. |
| Percent of Time | The percentage of the measurement interval duration stored procedure requests under the indicated DB2 Plan were being processed. |

Category detail line

This is a second-level detail line. This line shows one of five categories to which CPU time has been attributed:

APPLCN

Application Code

SYSTEM

System/OS Services

DB2SQL

SQL Processing

DATAMG

Data Management (DASD) Requests

NOSYMB

No Module Name Found, any execution measured at locations for which no load module name could be determined is attributed to this category.

As F14 is used for analyzing CPU consumption in DB2 Store Procedures, the category DB2SQL is the one where you should see the majority of the activity. This category and the detail lines under it are described here. For detailed information on the other categories, see “C01 - CPU usage by category” on page 74.

| Under Heading | This is Displayed |
|-----------------|---|
| Seqno | The category name “DB2SQL.” |
| Description | The category description “SQL Processing.” |
| Percent of Time | The percentage of the measurement interval duration SQL requests under the indicated DB2 Plan were being processed. |

DB2 DBRM detail line

This is a third-level detail line shown directly under the DB2 Plan detail line. It quantifies the percentage CPU time for a specific SQL request.

| Under Heading | This is Displayed |
|-----------------|--|
| Seqno | A sequence number assigned, by Application Performance Analyzer, to the SQL statement. |
| Description | The DBRM name, DBRM statement number and SQL function. |
| Percent of Time | The percentage of the measurement interval duration the indicated SQL Request was being processed. |

DB2 load module detail line

This is a fourth-level detail line showing activity for DB2 load modules used in the SQL request processing.

| Under Heading | This is Displayed |
|-----------------|---|
| Seqno | The DB2 Load Module name. |
| Description | If a DPA functional description is found for the module name, it is reported under this heading. |
| Percent of Time | The percentage of the measurement interval duration the indicated SQL Request being processed was in this module. |

Sample reports

A sample report is shown here, it has been expanded to the second level.

```

File View Navigate Help
-----
F14: DB2 CPU by Plan/Stored Proc (0888/CICS23A) Row 00001 of 00019
Command ==>> _____ Scroll ==>> CSR

Seqno      Description                Percent of CPU time * 10.00% ±2.3%
          *...1...2...3...4...5...6...7...8.
P0001     DB2MAIN                    39.68 =====
  → DB2SQL  SQL Processing              38.41 =====
  → SYSTEM  System/OS Services          1.16 =
  → APPLCN  Application Code            0.05
  → NOSYMB  No Module Name              0.05
  → DATAMG  Data Mgmt Processin        0.00

P0002     TRSAMP                     35.29 =====
  → DB2SQL  SQL Processing              34.07 =====
  → SYSTEM  System/OS Services          1.11 =
  → NOSYMB  No Module Name              0.11
  → APPLCN  Application Code            0.00
  → DATAMG  Data Mgmt Processin        0.00

P0003     WLSAMP1M                   24.79 =====
  → DB2SQL  SQL Processing              24.45 =====
  → SYSTEM  System/OS Services          0.33
  → APPLCN  Application Code            0.00
  → DATAMG  Data Mgmt Processin        0.00

```

Line commands

on objects

| Cmd | When Applied To Object | Action |
|-----|--|-----------------------------------|
| ? | Plan Seqno, Category, Seqno, Load Module | Display context help information. |
| ++ | Plan Seqno, Category, Seqno, Load Module | Show additional details. |

| Cmd | When Applied To Object | Action |
|-----|--|-----------------------------------|
| + | Plan Seqno, Category, Seqno, Load Module | Expand to reveal next level. |
| - | Plan Seqno, Category, Seqno, Load Module | Collapse to hide next level. |
| SV | Plan Seqno, Category, Seqno | Sort next level entries by value. |
| SN | Plan Seqno, Category, Seqno | Sort next level entries by name. |
| M | Load Module | Display load module information. |
| P | Load Module, Seqno | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------------------|------------------------------------|
| ? | Seqno, Description, Percent of CPU | Display context help information. |
| + | Seqno | Expand to reveal all entries. |
| + | Description | Expand description field size |
| + | Percent of CPU | Zoom in scale. |
| - | Seqno | Collapse to show only first level. |
| - | Description | Reduce description field size. |
| - | Percent of CPU | Zoom out scale. |
| SV | Seqno | Sort next level by value. |
| SN | Seqno | Sort next level by name. |

SETUP options

Enter the SETUP primary command to select options for this report. The following pop-up window will be displayed:

```

File View Navigate Help
-----+=====
F | Options for DB2 CPU by Plan/Stored Proc | 001 of 00001
C |                                         | ==> CSR
S | Enter "/" to select an option
P | / Report modules by "Group". Unselect to report
  |   by "SubGroup". Group is a higher level (more
  |   inclusive) categorization than SubGroup.
  |
  | / Show the DB2SQL category in which CPU time
  |   attributed to SQL processing is shown.
-----+=====

```

Reporting by Group / SubGroup

This option allows you to aggregate modules into Group or SubGroup. SubGroup offers a more granular, less inclusive categorization than Group. For example, when reporting by Group, all SVCs would be reported under the "SVC" Group. When reporting by SubGroup, SVCs would be reported under SubGroups such as SVCTYPE1 and SVCTYPE2.

Show the DB2SQL category

This shows activity attributed to DB2 SQL statements. If it is not selected, the activity will instead be included in the appropriate system modules in the SYSTEM category. This is not available for CICS measurements.

F15 - DB2 SQL CPU/Svc Time by Rq Loc

Usage

A prerequisite for this report is activation of the DB2+ option during the measurement. Also this report is only created when measuring a Distributed Data Facility (DDF) address space. Exact SQL call counts, total SQL service time, total SQL processing CPU time, SQL Enclave, and SQL zIIP times by SQL statement are recorded. This report shows quantification by Requester Location. You can further expand each line to see a more detailed breakdown and quantification by individual SQL statement.

Note: This report is for DDF measurements only.

Quantification

Each report line shows the following for each Requester Location and, when expanded, for each SQL statement observed for the Requester Location.

- Number of SQL calls
- Total CPU time for the SQL call processing
- Mean SQL call CPU time, or percent of total used
- Total service time for the SQL call processing
- Mean SQL call service time, or percent of total used

A setup option is available to display the percent used in place of the mean fields. Remember that measured CPU time applies only to the region being measured. DB2 executes in multiple address spaces and CPU could also be consumed in other DB2 regions not reflected in this report. This is reflected in the enclave CPU times shown in the detail windows of this report.

Detail line hierarchy

An unexpanded F15 report shows a line for each module that issued SQL requests. You can expand each line to reveal two additional hierarchical levels of detail (using the "+" line command). The hierarchy is illustrated here:

```
Level 1 Requester Location
  Level 2 SQL Request
    Level 3 SQL Statement Text
  Level 2 SQL Request
    Level 3 SQL Statement Text
```

Detail line descriptions

Requester Location detail line

This is the first-level detail line. Each line shows information about a Requester Location for which SQL request measurement data was recorded.

| Under Heading | This is Displayed |
|-----------------|---|
| Name | The Requester Location name. |
| Nbr of Calls | The number of SQL calls counted for this Requester Location. |
| CPU Time: Total | The total CPU time for all SQL calls counted for this Requester Location. |
| CPU Time: Mean | The mean CPU time per SQL call. |
| CPU time: Pct | The percent of total CPU time this requestor location used. |

| Under Heading | This is Displayed |
|-----------------|---|
| Svc Time: Total | The total service time for all SQL calls for this Requester Location. |
| Svc Time: Mean | The mean service time per SQL call. |
| Svc time: Pct | The percent of total service time this requestor location used. |

SQL request detail line

This is the second-level detail line shown directly under the Requester Location detail line. It quantifies an individual SQL statement.

| Under Heading | This is Displayed |
|-----------------|--|
| Name | A sequence number. This is assigned by Application Performance Analyzer to uniquely identify the SQL request. Either "S" or "D" precedes the sequence number indicating if the SQL statement is static or dynamic. |
| Plan/Pgm | The DBRM name. |
| Stmnt# | The precompiler statement number. This is the statement number assigned by the precompiler to the SQL request. When the statement number is zero, it indicates that the SQL statement was not produced by the DB2 precompiler or the SQL preprocessor, but was generated by some other means. For example, JDBC SQL statements have statement numbers that are zero. |
| SQL Function | The SQL function. This is the name of the SQL function, SELECT, FETCH, UPDATE, etc. Nbr of Calls The number of SQL calls counted for this SQL statement. |
| Nbr of Calls | The number of SQL calls counted for this SQL statement. |
| CPU Time: Total | The total CPU time for all SQL calls counted for this statement. |
| CPU Time: Mean | The mean CPU time per SQL call. |
| CPU time: Pct | The percent of total CPU time this statement used. |
| Svc Time: Total | The total service time for all SQL calls for this statement. |
| Svc Time: Mean | The mean service time per SQL call. |
| Svc time: Pct | The percent of total service time this statement used. |

SQL statement text detail line

This is the third-level detail line shown directly under the SQL request detail line. It shows the SQL statement text. If necessary, more than one line is displayed in order to show the full SQL text.

Sample reports

This sample shows the report with one location expanded to the third level (SQL text).

```

File View Navigate Help
-----
F15: DB2 SQL CPU/Svc Time by Rq Loc (6783/CICS23A) Row 00001 of 01067
Command ==>> _____ Scroll ==>> CSR
Name Plan/Pgm Stmt# SQL Functn Nbr of SQL Calls --CPU Time-- --Svc Time--
Total Mean Total Mean
CABNETDB24 295 1.66 0.00562 4.11 0.01394
- D00156 DDF2425A 279 FETCH 1 0.73 0.73480 0.79 0.79001
> Select count(*) from SYSIBM.SYSPACKSTMT
> (PREPARE of SQL was done at Stmt# 269 Seqno D00154)
- D00258 DDF2425A 279 FETCH 1 0.12 0.12491 0.14 0.14127
> Select count(*) from SYSIBM.SYSVLTREE
> (PREPARE of SQL was done at Stmt# 269 Seqno D00256)
- S00282 DDF2425A 372 Remote SQL 1 0.07 0.07215 1.18 1.18355
> CREATE TABLE AIF04 . TT1 LIKE AIF04 . DEPI IN DATABASE
> IPLF
- S00286 DDF2425A 392 Remote SQL 1 0.06 0.06569 0.08 0.08638
> CREATE DISTINCT TYPE DT2 AS INTEGER

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|---|
| ? | Location, Seqno | Display context help information. |
| ++ | Location, Seqno | Show additional details. |
| + | Location, Seqno | Expand to reveal next level. |
| - | Location, Seqno | Collapse to hide next level. |
| P | Seqno | Display source program mapping. |
| SV | Location | Sort next level entries by value. |
| SS | Location | Sort lines by program and statement number. |
| EX | Seqno | Display DB2 EXPLAIN data. |
| SD | Location | Sort next level entries by service time |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|---|
| ? | Name | Display context help information. |
| + | Name | Expand to reveal all entries. |
| - | Name | Collapse to show only first level. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level entries by name |
| SD | Name | Sort next level entries by service time |

SETUP options

Enter the SETUP primary command to select options for this report. The following window is displayed:

```
File View Navigate Help
+-----+
| Options for DB2 SQL CPU/Svc Time by Rq Loc |
|                                           |
| Enter "/" to select an option          |
|   - Display Percent used in place of Mean fields |
+-----+
```

Display Percent used in place of Mean fields

When selected, this displays the percent of total CPU and total service time used by each Requestor Location and SQL statement, rather than the mean time.

F16 - DB2 SQL CPU/Svc Time by Enclave

Usage

A prerequisite for this report is activation of the DB2+ option during the measurement. Also, this report is only created when measuring a Distributed Data Facility (DDF) address space. Exact SQL call counts, total SQL service time, total SQL task CPU time, SQL Enclave, and SQL zIIP times by SQL statement are recorded. This report shows quantification by Enclave token. You can further expand each line to see a further breakdown and quantification by individual SQL statement.

Note: This report is for DDF measurements only.

Quantification

Each report line shows the following for each Enclave token and, when expanded, for each SQL statement observed for the Enclave token.

- Number of SQL calls
- Total task CPU time for the SQL call processing
- Mean SQL call task CPU time, or percent of total used
- Total service time for the SQL call processing
- Mean SQL call service time, or percent of total used

A setup option is available to display the percent used in place of the mean fields. Keep in mind that the task CPU time applies only to the region being measured. DB2 executes in multiple address spaces and CPU could also be consumed in other DB2 regions not reflected in this report. This is reflected in the enclave CPU times shown in the detail windows of this report.

Detail line hierarchy

An unexpanded F16 report shows a line for each Enclave token that issued SQL requests. You can expand each line to reveal two additional hierarchical levels of detail (using the + line command). The hierarchy is illustrated here:

Level 1 Enclave token
Level 2 SQL Request
Level 3 SQL Statement Text
Level 2 SQL Request
Level 3 SQL Statement Text

Detail line descriptions

Enclave token detail line

This is the first-level detail line. Each line shows information about an Enclave token for which SQL request measurement data was recorded.

| Under Heading | This is Displayed |
|------------------|---|
| Token | The Enclave token name. |
| Nbr of SQL Calls | The number of SQL calls counted for this Enclave token. |
| CPU Time: Total | The total task CPU time for all SQL calls counted for this Enclave token. |
| CPU Time: Mean | The mean CPU time per SQL call. |
| CPU time: Pct | The percent of total CPU time this Enclave token used. |
| Svc Time: Total | The total service time for all SQL calls for this Enclave token. |
| Svc Time: Mean | The mean service time per SQL call. |
| SVC time: Pct | The percent of total service time this Enclave token used. |

SQL request detail line

This is the second-level detail line shown directly under the Enclave token detail line. It quantifies an individual SQL statement.

| Under Heading | This is Displayed |
|-----------------|--|
| Token | A sequence number. This is assigned by Application Performance Analyzer to uniquely identify the SQL request. Either "S" or "D" precedes the sequence number indicating if the SQL statement is static or dynamic. |
| Stmnt# | The precompiler statement number. This is the statement number assigned by the precompiler to the SQL request. When the statement number is zero, it indicates that the SQL statement was not produced by the DB2 precompiler or the SQL preprocessor, but was generated by some other means. For example, JDBC SQL statements have statement numbers that are zero. |
| SQL Function | The SQL function. This is the name of the SQL function (SELECT, FETCH, UPDATE, etc.) |
| Nbr of Calls | The number of SQL calls counted for this SQL statement. |
| CPU Time: Total | The total task CPU time for all SQL calls counted for this statement. |
| CPU Time: Mean | The mean task CPU time per SQL call. |
| CPU Time: Pct | The percent of total CPU time this statement used. |
| Svc Time: Total | The total service time for all SQL calls for this statement. |
| Svc Time: Mean | The mean service time per SQL call. |
| Svc Time: Pct | The percent of total service time this statement used. |

SQL statement text detail line

This is the third-level detail line shown directly under the SQL request detail line. It shows the SQL statement text. If necessary, more than one line is displayed in order to show the full SQL text.

Sample reports

This sample shows the report with one Enclave token expanded to the third level (SQL text).

```

File View Navigate Help
-----
F16: DB2 SQL CPU/Svc Time by Enclave (1641/DB2ADIST)          Row 00001 of 01410
Command ==>>> _____ Scroll ==>> PAGE

Token      Stmt#  SQL Function          Nbr of  --CPU Time--      --Svc Time--
          SQL Calls  Total  Mean              Total  Mean
00000020-0000017E          1    0.04  0.04177          0.05  0.05652
± D00026      0 EXECUTE IMME          1    0.04  0.04177          0.05  0.05652
  > EXPLAIN PLAN SET QUERYNO=1 FOR SELECT
  > COALESCE(FIELD_ONE_KEY, DEP2_COL1_KEY) AS COL1_KEY
  > ,COALESCE(DEP2_COL2_KEY, DEP3_COL2_KEY) AS COL2_KEY
  > ,DEP3_COL3_KEY ,DEP3_COL4 ,DEP3_COL5 ,DEP2_COL3
  > ,DEP2_COL4 ,FIELD_TWO ,FIELD_THREE ,FIELD_FOUR
  > ,FIELD_FIVE ,FIELD_SIX ,FIELD_SEVEN
  > ,CHAR(FIELD_EIGHT,ISO) ,CHAR(FIELD_NINE,ISO)
  > ,FIELD_TEN ,TIMEZONE () FROM MAIN FULL OUTER JOIN DEP2
  > ON DEP2_COL1_KEY = FIELD_ONE_KEY LEFT JOIN DEP3 ON
  > DEP3_COL1_KEY = DEP2_COL1_KEY AND DEP3_COL2_KEY =
  > DEP2_COL2_KEY ORDER BY COL1_KEY ,COL2_KEY
  > ,DEP3_COL3_KEY

00000024-00000198          1    0.04  0.04154          0.04  0.04668
→ D00026      0 EXECUTE IMME          1    0.04  0.04154          0.04  0.04668
  > EXPLAIN PLAN SET QUERYNO=1 FOR SELECT
  > COALESCE(FIELD_ONE_KEY, DEP2_COL1_KEY) AS COL1_KEY
  > ,COALESCE(DEP2_COL2_KEY, DEP3_COL2_KEY) AS COL2_KEY
  > ,DEP3_COL3_KEY ,DEP3_COL4 ,DEP3_COL5 ,DEP2_COL3
  > ,DEP2_COL4 ,FIELD_TWO ,FIELD_THREE ,FIELD_FOUR
  > ,FIELD_FIVE ,FIELD_SIX ,FIELD_SEVEN
  > ,CHAR(FIELD_EIGHT,ISO) ,CHAR(FIELD_NINE,ISO)
  > ,FIELD_TEN ,TIMEZONE () FROM MAIN FULL OUTER JOIN DEP2
  > ON DEP2_COL1_KEY = FIELD_ONE_KEY LEFT JOIN DEP3 ON
  > DEP3_COL1_KEY = DEP2_COL1_KEY AND DEP3_COL2_KEY =
  > DEP2_COL2_KEY ORDER BY COL1_KEY ,COL2_KEY
  > ,DEP3_COL3_KEY

00000020-000001A8          1    0.04  0.04167          0.04  0.04925
→ D00026      0 EXECUTE IMME          1    0.04  0.04167          0.04  0.04925
  > EXPLAIN PLAN SET QUERYNO=1 FOR SELECT
  > COALESCE(FIELD_ONE_KEY, DEP2_COL1_KEY) AS COL1_KEY
  > ,COALESCE(DEP2_COL2_KEY, DEP3_COL2_KEY) AS COL2_KEY

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Token, Seqno | Display context help information. |
| ++ | Token, Seqno | Show additional details. |
| + | Token, Seqno | Expand to reveal next level. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|---|
| - | Token, Seqno | Collapse to hide next level. |
| SV | Token | Sort next level entries by value. |
| SS | Token | Sort lines by program and statement number. |
| SD | Token | Sort next level entries by service time |
| P | Seqno | Display source program mapping. |
| EX | Seqno | Display DB2 EXPLAIN data. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Token | Display context help information. |
| + | Token | Expand to reveal all entries. |
| - | Token | Collapse to show only first level. |
| SV | Token | Sort next level by value. |
| SN | Token | Sort next level by name. |
| SD | Token | Sort next level by service time. |

SETUP options

Enter the SETUP primary command to select options for this report. The following window is displayed:

```

File View Navigate Help
+-----+
| Options for DB2 SQL CPU/Svc Time by Enclave |
| Enter "/" to select an option                |
|   _ Display Percent used in place of Mean fields |
+-----+

```

Display Percent used in place of Mean fields

When selected, this displays the percent of total CPU and total service time used by each Enclave token and SQL statement, rather than the mean time.

F17 - DB2 SQL CPU/Svc Time by Corrid

Usage

A prerequisite for this report is activation of the DB2+ option during the measurement. Also this report is only created when measuring a Distributed Data Facility (DDF) address space. Exact SQL call counts, total SQL service time, total SQL task CPU time, SQL Enclave, and SQL zIIP times by SQL statement are recorded. This report shows quantification by Correlation ID. You can further expand each line to see a further breakdown and quantification by individual SQL statement.

Note: This report is for DDF measurements only.

Quantification

Each report line shows the following for each Correlation ID and, when expanded, for each SQL statement observed for the Correlation ID.

- Number of SQL calls
- Total task CPU time for the SQL call processing
- Mean SQL call task CPU time, or percent of total used
- Total service time for the SQL call processing
- Mean SQL call service time, or percent of total used

A setup option is available to display the percent used in place of the mean fields. Keep in mind that the task CPU time applies only to the region being measured. DB2 executes in multiple address spaces and CPU could also be consumed in other DB2 regions not reflected in this report. This is reflected in the enclave CPU times shown in the detail windows of this report.

Detail line hierarchy

An unexpanded F17 report shows a line for each Correlation ID that issued SQL requests. You can expand each line to reveal two additional hierarchical levels of detail (using the + line command). The hierarchy is illustrated here:

```
Level 1 Correlation ID
Level 2 SQL Request
Level 3 SQL Statement Text
Level 2 SQL Request
Level 3 SQL Statement Text
```

Detail line descriptions

Correlation ID detail line

This is the first-level detail line. Each line shows information about a Correlation ID for which SQL request measurement data was recorded.

| Under Heading | This is Displayed |
|------------------|--|
| Corrid | The Correlation ID name. |
| Nbr of SQL Calls | The number of SQL calls counted for this Correlation ID. |
| CPU Time: Total | The total task CPU time for all SQL calls counted for this Correlation ID. |
| CPU Time: Mean | The mean CPU time per SQL call. |
| CPU Time: Pct | The percent of total CPU time this Correlation ID used. |
| Svc Time: Total | The total service time for all SQL calls for this Correlation ID. |
| Svc Time: Mean | The mean service time per SQL call. |
| Svc Time: Pct | The percent of total service time this Correlation ID used. |

SQL request detail line

This is the second-level detail line shown directly under the Correlation ID detail line. It quantifies an individual SQL statement.

| Under Heading | This is Displayed |
|---------------|--|
| Corrid | A sequence number. This is assigned by Application Performance Analyzer to uniquely identify the SQL request. Either "S" or "D" precedes the sequence number indicating if the SQL statement is static or dynamic. |

| Under Heading | This is Displayed |
|----------------------|--|
| Stmt# | The precompiler statement number. This is the statement number assigned by the precompiler to the SQL request. When the statement number is zero, it indicates that the SQL statement was not produced by the DB2 precompiler or the SQL preprocessor, but was generated by some other means. For example, JDBC SQL statements have statement numbers that are zero. |
| SQL Function | The SQL function. This is the name of the SQL function (SELECT, FETCH, UPDATE, etc.) |
| Nbr of Calls | The number of SQL calls counted for this SQL statement. |
| CPU Time: Total | The total task CPU time for all SQL calls counted for this statement. |
| CPU Time: Mean | The mean task CPU time per SQL call. |
| CPU Time: Pct | The percent of total CPU time this statement used. |
| Svc Time: Total | The total service time for all SQL calls for this statement. |
| Svc Time: Mean | The mean service time per SQL call. |
| Svc Time: Pct | The percent of total service time this statement used. |

SQL statement text detail line

This is the third-level detail line shown directly under the SQL request detail line. It shows the SQL statement text. If necessary, more than one line is displayed in order to show the full SQL text.

Sample reports

This sample shows the report with one Correlation ID expanded to the third level (SQL text).

```

File View Navigate Help
-----
F17: DB2 SQL CPU/Svc Time by Corrid (1641/DB2ADIST)          Row 00001 of 00314
Command ==>>> _____ Scroll ==>>> PAGE

Corrid      Stmt#  SQL Function      Nbr of  --CPU Time--  --Svc Time--
              SQL Calls  Total  Mean          Total  Mean
db2bp.exe
± D00026      0 EXECUTE IMME          4      0.16  0.04137      0.20  0.05004
> EXPLAIN PLAN SET QUERYNO=1 FOR SELECT
> COALESCE(FIELD_ONE_KEY, DEP2_COL1_KEY) AS COL1_KEY
> ,COALESCE(DEP2_COL2_KEY, DEP3_COL2_KEY) AS COL2_KEY
> ,DEP3_COL3_KEY ,DEP3_COL4 ,DEP3_COL5 ,DEP2_COL3
> ,DEP2_COL4 ,FIELD_TWO ,FIELD_THREE ,FIELD_FOUR
> ,FIELD_FIVE ,FIELD_SIX ,FIELD_SEVEN
> ,CHAR(FIELD_EIGHT,ISO) ,CHAR(FIELD_NINE,ISO)
> ,FIELD_TEN ,TIMEZONE () FROM MAIN FULL OUTER JOIN DEP2
> ON DEP2_COL1_KEY = FIELD_ONE_KEY LEFT JOIN DEP3 ON
> DEP3_COL1_KEY = DEP2_COL1_KEY AND DEP3_COL2_KEY =
> DEP2_COL2_KEY ORDER BY COL1_KEY ,COL2_KEY
> ,DEP3_COL3_KEY
± D00007      0 FETCH              4      0.07  0.01895      0.07  0.01983
> ( SELECT T1.FIELD_ONE_KEY AS
> UNION_COLUMN_01 ,T1.FIELD_TWO AS
> UNION_COLUMN_02 FROM AIF04.MAIN T1 WHERE NOT EXISTS
> (SELECT * FROM AIF04.DEP1 T2 WHERE T1.FIELD_ONE_KEY =
> T2.DEP1_COL1_KEY1 ) UNION SELECT T3.FIELD_ONE_KEY
> AS UNION_COLUMN_01 ,T3.FIELD_TWO
> AS UNION_COLUMN_02 FROM AIF04.MAIN T3 WHERE NOT EXISTS
> (SELECT * FROM AIF04.DEP2 T4 WHERE T3.FIELD_ONE_KEY =
> T4.DEP2_COL1_KEY ) ) UNION ALL ( SELECT
> T2.FIELD_ONE_KEY AS UNION_COLUMN_01
> ,T2.FIELD_TWO AS UNION_COLUMN_02 FROM
> AIF04.MAIN T2 WHERE NOT EXISTS (SELECT * FROM
> AIF04.DEP1 T1 WHERE T2.FIELD_ONE_KEY =
> T1.DEP1_COL1_KEY1 ) UNION SELECT T4.FIELD_ONE_KEY
> AS UNION_COLUMN_01 ,T4.FIELD_TWO
> AS UNION_COLUMN_02 FROM AIF04.MAIN T4 WHERE NOT EXISTS
> (SELECT * FROM AIF04.DEP2 T3 WHERE T4.FIELD_ONE_KEY =
> T3.DEP2_COL1_KEY ) )
> (PREPARE of SQL was done at Stmt# 0 Seqno D0005)

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|---|
| ? | Corrid, Seqno | Display context help information. |
| ++ | Corrid, Seqno | Show additional details. |
| + | Corrid, Seqno | Expand to reveal next level. |
| - | Corrid, Seqno | Collapse to hide next level. |
| SV | Corrid | Sort next level entries by value. |
| SS | Corrid | Sort lines by program and statement number. |
| SD | Corrid | Sort next level entries by service time |
| P | Seqno | Display source program mapping. |
| EX | Seqno | Display DB2 EXPLAIN data. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Corrid | Display context help information. |
| + | Corrid | Expand to reveal all entries. |
| - | Corrid | Collapse to show only first level. |
| SV | Corrid | Sort next level by value. |
| SN | Corrid | Sort next level by name. |
| SD | Corrid | Sort next level by service time. |

SETUP options

Enter the SETUP primary command to select options for this report. The following window is displayed:

```
File View Navigate Help
+-----+
| Options for DB2 SQL CPU/Svc Time by Corrid |
|                                             |
| Enter "/" to select an option             |
|   _ Display Percent used in place of Mean |
|                                             |
+-----+
```

Display Percent used in place of Mean fields

When selected, this displays the percent of total CPU and total service time used by each Correlation ID and SQL statement, rather than the mean time.

F18 - DB2 SQL CPU/Svc Time by Wkstn

Usage

A prerequisite for this report is activation of the DB2+ option during the measurement. Also this report is only created when measuring a Distributed Data Facility (DDF) address space. Exact SQL call counts, total SQL service time, total SQL task CPU time, SQL Enclave, and SQL zIIP times by SQL statement are recorded. This report shows quantification by Workstation ID. You can further expand each line to see a further breakdown and quantification by individual SQL statement.

Note: This report is for DDF measurements only.

Quantification

Each report line shows the following for each Workstation ID and, when expanded, for each SQL statement observed for the Workstation ID.

- Number of SQL calls
- Total task CPU time for the SQL call processing
- Mean SQL call task CPU time, or percent of total used
- Total service time for the SQL call processing
- Mean SQL call service time, or percent of total used

A setup option is available to display the percent used in place of the mean fields. Keep in mind that the task CPU time applies only to the region being measured.

DB2 executes in multiple address spaces and CPU could also be consumed in other DB2 regions not reflected in this report. This is reflected in the enclave CPU times shown in the detail windows of this report.

Detail line hierarchy

An unexpanded F18 report shows a line for each Workstation ID that issued SQL requests. You can expand each line to reveal two additional hierarchical levels of detail (using the + line command). The hierarchy is illustrated here:

```

Level 1 Workstation ID
Level 2 SQL Request
Level 3 SQL Statement Text
Level 2 SQL Request
Level 3 SQL Statement Text
  
```

Detail line descriptions

Workstation ID detail line

This is the first-level detail line. Each line shows information about a Workstation ID for which SQL request measurement data was recorded.

| Under Heading | This is Displayed |
|------------------|--|
| Wkstn | The Workstation ID name. |
| Nbr of SQL Calls | The number of SQL calls counted for this Workstation ID. |
| CPU Time: Total | The total task CPU time for all SQL calls counted for this Workstation ID. |
| CPU Time: Mean | The mean CPU time per SQL call. |
| CPU Time: Pct | The percent of total CPU time this Workstation ID used. |
| Svc Time: Total | The total service time for all SQL calls for this Workstation ID. |
| Svc Time: Mean | The mean service time per SQL call. |
| Svc Time: Pct | The percent of total service time this Workstation ID used. |

SQL request detail line

This is the second-level detail line shown directly under the Workstation ID detail line. It quantifies an individual SQL statement.

| Under Heading | This is Displayed |
|-----------------|--|
| Wkstn | A sequence number. This is assigned by Application Performance Analyzer to uniquely identify the SQL request. Either "S" or "D" precedes the sequence number indicating if the SQL statement is static or dynamic. |
| Stmnt# | The precompiler statement number. This is the statement number assigned by the precompiler to the SQL request. When the statement number is zero, it indicates that the SQL statement was not produced by the DB2 precompiler or the SQL preprocessor, but was generated by some other means. For example, JDBC SQL statements have statement numbers that are zero. |
| SQL Function | The SQL function. This is the name of the SQL function (SELECT, FETCH, UPDATE, etc.) |
| Nbr of Calls | The number of SQL calls counted for this SQL statement. |
| CPU Time: Total | The total task CPU time for all SQL calls counted for this statement. |

| Under Heading | This is Displayed |
|-----------------|--|
| CPU Time: Mean | The mean task CPU time per SQL call. |
| CPU Time: Pct | The percent of total CPU time this statement used. |
| Svc Time: Total | The total service time for all SQL calls for this statement. |
| Svc Time: Mean | The mean service time per SQL call. |
| Svc Time: Pct | The percent of total service time this statement used. |

SQL statement text detail line

This is the third-level detail line shown directly under the SQL request detail line. It shows the SQL statement text. If necessary, more than one line is displayed in order to show the full SQL text.

Sample reports

This sample shows the report with one Workstation id expanded to the third level (SQL text)

```

File View Navigate Help
-----
F18: DB2 SQL CPU/Svc Time by Wkstn (1641/DB2ADIST)          Row 00001 of 00337
Command ==>>> _____ Scroll ==>>> CSR

Wkstn      Stmt#  SQL Function      Nbr of  --CPU Time--      --Svc Time--
           Stmts  SQL Calls  Total  Mean      Total  Mean
-----
D12A3H26           105    0.57  0.00548    0.61  0.00586
± D00016           3     0.11  0.03885    0.13  0.04345
> EXECUTE IMME
> EXPLAIN PLAN SET QUERYNO=1 FOR SELECT
> COALESCE(FIELD_ONE_KEY, DEP2_COL1_KEY) AS COL1_KEY
> ,COALESCE(DEP2_COL2_KEY, DEP3_COL2_KEY) AS COL2_KEY
> ,DEP3_COL3_KEY ,DEP3_COL4 ,DEP3_COL5 ,DEP2_COL3
> ,DEP2_COL4 ,FIELD_TWO ,FIELD_THREE ,FIELD_FOUR
> ,FIELD_FIVE ,FIELD_SIX ,FIELD_SEVEN
> ,CHAR(FIELD_EIGHT,ISO) ,CHAR(FIELD_NINE,ISO)
> ,FIELD_TEN ,TIMEZONE () FROM MAIN FULL OUTER JOIN DEP2
> ON DEP2_COL1_KEY = FIELD_ONE_KEY LEFT JOIN DEP3 ON
> DEP3_COL1_KEY = DEP2_COL1_KEY AND DEP3_COL2_KEY =
> DEP2_COL2_KEY ORDER BY COL1_KEY ,COL2_KEY
> ,DEP3_COL3_KEY

→ D00020           12     0.08  0.00744    0.09  0.00763
> FETCH
> SELECT * FROM PLAN_TABLE ORDER BY QUERYNO, QBLOCKNO,
> PLANNO
> (PREPARE of SQL was done at Stmt# 0 Seqno D00017)

→ D00019           3     0.08  0.02768    0.08  0.02891
> OPEN
> SELECT * FROM PLAN_TABLE ORDER BY QUERYNO, QBLOCKNO,
> PLANNO
> (PREPARE of SQL was done at Stmt# 0 Seqno D00017)

→ D00034           3     0.05  0.01741    0.05  0.01809
> FETCH
> ( SELECT T1.FIELD_ONE_KEY AS
> UNION_COLUMN_01 ,T1.FIELD_TWO AS
> UNION_COLUMN_02 FROM AIF04.MAIN T1 WHERE NOT EXISTS
> (SELECT * FROM AIF04.DEP1 T2 WHERE T1.FIELD_ONE_KEY =
> T2.DEP1_COL1_KEY1 ) UNION SELECT T3.FIELD_ONE_KEY
> AS UNION_COLUMN_01 ,T3.FIELD_TWO
> AS UNION_COLUMN_02 FROM AIF04.MAIN T3 WHERE NOT EXISTS
> (SELECT * FROM AIF04.DEP2 T4 WHERE T3.FIELD_ONE_KEY =
> T4.DEP2_COL1_KEY ) ) UNION ALL ( SELECT

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|---|
| ? | Wkstn, Seqno | Display context help information. |
| ++ | Wkstn, Seqno | Show additional details. |
| + | Wkstn, Seqno | Expand to reveal next level. |
| - | Wkstn, Seqno | Collapse to hide next level. |
| SV | Wkstn | Sort next level entries by value. |
| SS | Wkstn | Sort lines by program and statement number. |
| SD | Wkstn | Sort next level entries by service time. |
| P | Seqno | Display source program mapping. |
| EX | Seqno | Display DB2 EXPLAIN data. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | Wkstn | Display context help information. |
| + | Wkstn | Expand to reveal all entries. |
| - | Wkstn | Collapse to show only first level. |
| SV | Wkstn | Sort next level by value. |
| SN | Wkstn | Sort next level by name. |
| SD | Wkstn | Sort next level by service time. |

SETUP options

Enter the SETUP primary command to select options for this report. The following window is displayed:

```
File View Navigate Help
+-----+
| Options for DB2 SQL CPU/Svc Time by Wkstn |
| Enter "/" to select an option           |
|   _ Display Percent used in place of Mean fields |
+-----+
```

Display Percent used in place of Mean fields

When selected, this displays the percent of total CPU and total service time used by each Workstation ID and SQL statement, rather than the mean time.

F19 - DB2 SQL CPU/Svc Time by EndUsr

Usage

A prerequisite for this report is activation of the DB2+ option during the measurement. Also this report is only created when measuring a Distributed Data Facility (DDF) address space. Exact SQL call counts, total SQL service time, total SQL task CPU time, SQL Enclave, and SQL zIIP times by SQL statement are recorded. This report shows quantification by End User ID. You can further expand each line to see a further breakdown and quantification by individual SQL statement.

Note: This report is for DDF measurements only.

Quantification

Each report line shows the following for each End User ID and, when expanded, for each SQL statement observed for the End User ID.

- Number of SQL calls
- Total task CPU time for the SQL call processing
- Mean SQL call task CPU time, or percent of total used
- Total service time for the SQL call processing
- Mean SQL call service time, or percent of total used

A setup option is available to display the percent used in place of the mean fields. Keep in mind that the task CPU time applies only to the region being measured. DB2 executes in multiple address spaces and CPU could also be consumed in other DB2 regions not reflected in this report. This is reflected in the enclave CPU times shown in the detail windows of this report.

Detail line hierarchy

An unexpanded F19 report shows a line for each End User ID that issued SQL requests. You can expand each line to reveal two additional hierarchical levels of detail (using the + line command). The hierarchy is illustrated here:

```
Level 1 End User ID
  Level 2 SQL Request
    Level 3 SQL Statement Text
  Level 2 SQL Request
    Level 3 SQL Statement Text
```

Detail line descriptions

End User ID detail line

This is the first-level detail line. Each line shows information about an End User ID for which SQL request measurement data was recorded.

| Under Heading | This is Displayed |
|------------------|---|
| EndUsr | The End User ID name. |
| Nbr of SQL Calls | The number of SQL calls counted for this End User ID. |
| CPU Time: Total | The total task CPU time for all SQL calls counted for this End User ID. |
| CPU Time: Mean | The mean CPU time per SQL call. |
| CPU Time: Pct | The percent of total CPU time this End User ID used. |

| Under Heading | This is Displayed |
|-----------------|--|
| Svc Time: Total | The total service time for all SQL calls for this End User ID. |
| Svc Time: Mean | The mean service time per SQL call. |
| Svc Time: Pct | The percent of total service time this End User ID used. |

SQL request detail line

This is the second-level detail line shown directly under the End User ID detail line. It quantifies an individual SQL statement.

| Under Heading | This is Displayed |
|-----------------|--|
| EndUsr | A sequence number. This is assigned by Application Performance Analyzer to uniquely identify the SQL request. Either "S" or "D" precedes the sequence number indicating if the SQL statement is static or dynamic. |
| Stmnt# | The precompiler statement number. This is the statement number assigned by the precompiler to the SQL request. When the statement number is zero, it indicates that the SQL statement was not produced by the DB2 precompiler or the SQL preprocessor, but was generated by some other means. For example, JDBC SQL statements have statement numbers that are zero. |
| SQL Function | The SQL function. This is the name of the SQL function (SELECT, FETCH, UPDATE, etc.) |
| Nbr of Calls | The number of SQL calls counted for this SQL statement. |
| CPU Time: Total | The total task CPU time for all SQL calls counted for this statement. |
| CPU Time: Mean | The mean task CPU time per SQL call. |
| CPU Time: Pct | The percent of total CPU time this statement used. |
| Svc Time: Total | The total service time for all SQL calls for this statement. |
| Svc Time: Mean | The mean service time per SQL call. |
| Svc Time: Pct | The percent of total service time this statement used. |

SQL statement text detail line

This is the third-level detail line shown directly under the SQL request detail line. It shows the SQL statement text. If necessary, more than one line is displayed in order to show the full SQL text.

Sample reports

This sample shows the report with one End User ID expanded to the third level (SQL text).

```

File View Navigate Help
-----
F19: DB2 SQL CPU/Svc Time by EndUsr (1641/DB2ADIST) Row 00001 of 00336
Command ==> _____ Scroll ==> CSR
-----
EndUsr      Stmt#  SQL Function      Nbr of  --CPU Time--  --Svc Time--
              SQL Calls  Total  Mean          Total  Mean
-----
USR01              121    0.67  0.00555      16.74  0.13837
± D00016      0 EXECUTE IMME          3    0.11  0.03885       0.13  0.04345
> EXPLAIN PLAN SET QUERYNO=1 FOR SELECT
> COALESCE(FIELD_ONE_KEY, DEP2_COL1_KEY) AS COL1_KEY
> ,COALESCE(DEP2_COL2_KEY, DEP3_COL2_KEY) AS COL2_KEY
> ,DEP3_COL3_KEY ,DEP3_COL4 ,DEP3_COL5 ,DEP2_COL3
> ,DEP2_COL4 ,FIELD_TWO ,FIELD_THREE ,FIELD_FOUR
> ,FIELD_FIVE ,FIELD_SIX ,FIELD_SEVEN
> ,CHAR(FIELD_EIGHT,ISO) ,CHAR(FIELD_NINE,ISO)
> ,FIELD_TEN ,TIMEZONE () FROM MAIN FULL OUTER JOIN DEP2
> ON DEP2_COL1_KEY = FIELD_ONE_KEY LEFT JOIN DEP3 ON
> DEP3_COL1_KEY = DEP2_COL1_KEY AND DEP3_COL2_KEY =
> DEP2_COL2_KEY ORDER BY COL1_KEY ,COL2_KEY
> ,DEP3_COL3_KEY

→ D00020      0 FETCH              12    0.08  0.00744       0.09  0.00763
> SELECT * FROM PLAN_TABLE ORDER BY QUERYNO, QBLOCKNO,
> PLANNO
> (PREPARE of SQL was done at Stmt# 0 Seqno D00017)

→ D00019      0 OPEN                3    0.08  0.02768       0.08  0.02891
> SELECT * FROM PLAN_TABLE ORDER BY QUERYNO, QBLOCKNO,
> PLANNO
> (PREPARE of SQL was done at Stmt# 0 Seqno D00017)

→ D00034      0 FETCH                3    0.05  0.01741       0.05  0.01809
> ( SELECT T1.FIELD_ONE_KEY AS
> UNION_COLUMN_01 ,T1.FIELD_TWO AS
> UNION_COLUMN_02 FROM AIF04.MAIN T1 WHERE NOT EXISTS
> (SELECT * FROM AIF04.DEP1 T2 WHERE T1.FIELD_ONE_KEY =
> T2.DEP1_COL1_KEY1 ) UNION SELECT T3.FIELD_ONE_KEY
> AS UNION_COLUMN_01 ,T3.FIELD_TWO
> AS UNION_COLUMN_02 FROM AIF04.MAIN T3 WHERE NOT EXISTS
> (SELECT * FROM AIF04.DEP2 T4 WHERE T3.FIELD_ONE_KEY =
> T4.DEP2_COL1_KEY ) ) UNION ALL ( SELECT

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|---|
| ? | EndUsr, Seqno | Display context help information. |
| ++ | EndUsr, Seqno | Show additional details. |
| + | EndUsr, Seqno | Expand to reveal next level. |
| - | EndUsr, Seqno | Collapse to hide next level. |
| SV | EndUsr | Sort next level entries by value. |
| SS | EndUsr | Sort lines by program and statement number. |
| SD | EndUsr | Sort next level entries by service time |
| P | Seqno | Display source program mapping. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|---------------------------|
| EX | Seqno | Display DB2 EXPLAIN data. |

on headings

| Cmd | When Applied To Object | Action |
|-----|------------------------|------------------------------------|
| ? | EndUsr | Display context help information. |
| + | EndUsr | Expand to reveal all entries. |
| - | EndUsr | Collapse to show only first level. |
| SV | EndUsr | Sort next level by value. |
| SN | EndUsr | Sort next level by name. |
| SD | EndUsr | Sort next level by service time. |

SETUP options

Enter the SETUP primary command to select options for this report. The following window is displayed:

```

File View Navigate Help
+-----+
| Options for DB2 SQL CPU/Svc Time by Endusr |
|                                             |
| Enter "/" to select an option             |
|   _ Display Percent used in place of Mean fields |
+-----+

```

Display Percent used in place of Mean fields

When selected, this displays the percent of total CPU and total service time used by each End User ID and SQL statement, rather than the mean time.

DB2 EXPLAIN report

The DB2 EXPLAIN report is displayed by typing the command "EX" on an SQL statement, it is available in most DB2 reports.

Usage

Use this report to see information from PLAN_TABLE built by a DB2 EXPLAIN request for a particular SQL statement. Each report line represents a row in the result PLAN_TABLE. You obtain this report by issuing an "EX" line command against the SQL statement you want explained. Application Performance Analyzer will issue a dynamic EXPLAIN request on the SQL text of the statement you have selected.

Note:

Not all SQL statements can be the subject of a dynamic EXPLAIN request. Included among these are UPDATE or DELETE statements with a WHERE CURRENT OF clause.

A prerequisite for this report is activation of the DB2+ option during the measurement.

The EXPLAIN request is executed at the time you request it. It is not issued at the time of the measurement. Thus any changes made to the DB2 objects since the

measurement was requested will affect the EXPLAIN request. It is valid to select a DECLARE CURSOR or a SELECT INTO statement for EXPLAIN. Application Performance Analyzer will remove the DECLARE CURSOR clause or the INTO clause before issuing the dynamic EXPLAIN. Application Performance Analyzer will also substitute any :H host variable placeholders in static SQL statements with a question mark. Application Performance Analyzer can issue EXPLAIN on SQL statements up to 15000 bytes long.

Field descriptions

The values of certain columns from each row of PLAN_TABLE are displayed in each report line. To see more detailed information, including values of additional PLAN_TABLE columns, issue the “++” line command or press the ENTER key. For full descriptions of these columns, refer to *DB2 Universal Database™ for z/OS: Application Programming and SQL Guide*.

| Under Heading | This is Displayed |
|---------------|---|
| Blk Num | The value of the QBLOCKNO column. This is also an input field. Use the “++” line command or press the ENTER key to display more information about the PLAN_TABLE row. |
| Plan Num | The value of the PLANNO column. |
| Mix Op | The value of the MIXOPSEQ column. |
| Join Mthd | The value of the METHOD column. |
| Acc Type | The value of the ACCESTYPE column. |
| Match Cols | The value of the MATCHCOLS column. |
| Index Only | The value of the INDEXONLY column. |
| Sort New | U J O G The values of the SORTN_UNIQ, SORTN_JOIN, SORTN_ORDERBY and SORTN_GROUPBY columns. |
| Sort Comp | U J O G The values of the SORTC_UNIQ, SORTC_JOIN, SORTC_ORDERBY and SORTC_GROUPBY columns. |
| Table Name | The value of the TNAME column. |

Sample reports

A sample report is shown here:

```

File View Navigate Help
+-----+-----+
DB2 EXPLAIN (0167/CICS23A)                               Row 00001 of 00010
Command ==>>>                                           Scroll ==>> CSR
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
Blk   Plan   Mix   Join   Acc   Match   Index   Sort New   Sort Comp   Table
Num.  Num.    Op    Mthd   Type  Cols    Only   U J O G   U J O G   Name
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
0001   1      0     0      R     0       N     N N N N   N N N N   MAIN
0001   2      0     3      R     0       N     N N N N   Y N N N
0002   1      0     0      R     0       N     N N N N   N N N N   DEP1
0003   1      0     0      R     0       N     N N N N   N N N N   MAIN
0004   1      0     0      R     0       N     N N N N   N N N N   DEP2
0005   1      0     0      R     0       N     N N N N   N N N N   MAIN
0005   2      0     3      R     0       N     N N N N   Y N N N
0006   1      0     0      R     0       N     N N N N   N N N N   DEP1
0007   1      0     0      R     0       N     N N N N   N N N N   MAIN
0008   1      0     0      R     0       N     N N N N   N N N N   DEP2

```


Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field).

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Blk Num | Display context help information. |
| ++ | Blk Num | Show additional details. |

Note: There are no line commands on headings for this report.

Detail window

You can enter "++" (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown below (shown in three scrollable screen segments).

```
File View Navigate Help
+-----+
DB2 EXPLAIN Data for Selected Row                                     More:  +
Block number                0003
Plan number                 0001
Join method                 None
Table creator               USER4
Table name                  MAIN
Access type                 Table space scan
Matching columns            0
Index creator               n/a
Index name                  n/a
Index only                  No
Merge join columns         0
Correlation name           T3
Page range screening       n/a
Join type                   n/a
Query block type           SELECT
Direct row access          n/a

Sort      New      Composite
Unique    No      No
Join      No      No
Order by  No      No
Group by  No      No

Lock mode           Intent Share
Prefetch            Pure sequential
Function evaluation After data retrieval and sorting
Multiple index operation sequence no. 0

Parallelism Information:
Number of tasks      0
Group identifier     0
Join degree          0
Join group id        0
Sort composite group id 0
+-----+
```

| File View Navigate Help | |
|---|------------------------------|
| Sort new table group id | 0 |
| Parallelism mode | n/a |
| More: - + | |
| Descriptive Names Mapped to PLAN_TABLE Column Names | |
| Descriptive Name | Column Name |
| Block number | QBLOCKNO |
| Plan number | PLANNO |
| Join method | METHOD |
| Table creator | CREATOR |
| Table name | TNAME |
| Access type | ACCESSTYPE |
| Matching columns | MATCHCOLS |
| Index creator | ACCESSCREATOR |
| Index name | ACCESSNAME |
| Index only | INDEXONLY |
| Unique | SORTN_UNIQ, SORTC_UNIQ |
| Join | SORTN_JOIN, SORTC_JOIN |
| Order by | SORTN_ORDERBY, SORTC_ORDERBY |
| Group by | SORTN_GROUPBY, SORTC_GROUPBY |
| Lock mode | TSLOCKMODE |
| Prefetch | PREFETCH |
| Function evaluation | COLUMN_FN_EVAL |
| Multiple index operation sequence no. | MIXOPSEQ |
| Number of tasks | ACCESS_DEGREE |
| Group identifier | ACCESS_PGROUP_ID |
| Join degree | JOIN_DEGREE |
| Join group id | JOIN_PGROUP_ID |
| Sort composite group id | SORTC_PGROUP_ID |
| Sort new table group id | SORTN_PGROUP_ID |
| Parallelism mode | PARALLELISM_MODE |
| Merge join columns | MERGE_JOIN_COLS |
| Correlation name | CORRELATION_NAME |
| Page range screening | PAGE_RANGE |
| Join type | JOIN_TYPE |

| File View Navigate Help | |
|-------------------------|--------------------|
| Query block type | QBLOCK_TYPE |
| Direct row access | PRIMARY_ACCESSTYPE |
| More: - | |

DB2SQL category in C01 report

More DB2 measurement data is presented in the C01 CPU Usage by Category report, under the category DB2SQL. If you expand the DB2SQL with the "+" line command, SQL Statement items will be displayed.

A sample is shown here:

```

File View Navigate Help
-----
C01: CPU Usage by Category (0645/CICS23A) Row 00001 of 00014
Command ==> _____ Scroll ==> CSR

Name      Description      Percent of CPU time * 10.00% ±2.6%
          *....1....2....3....4....5....6....7....8.
SYSTEM    System/OS Services  76.39 =====
DB2SQL    SQL Processing      17.02 =====
→ 00008   PFSAMPC(1466) FETCH  8.00 ====
→ 00003   PFSAMPB(408) SET HOS  2.10 =
→ 00010   PFSAMPB(816) UPDATE  2.03 =
→ 00004   PFSAMPC(1316) SELECT  1.56 =
→ 00006   PFSAMPC(1347) SELECT  0.94
→ 00002   PFSAMPB(678) SELECT  0.67
→ 00001   PFSAMPA(816) SELECT  0.67
→ 00007   PFSAMPC(1443) OPEN   0.61
→ 00009   PFSAMPC(1562) CLOSE  0.40

APPLCN    Application Code    6.58 ==

```

You can enter the “+” command to further expand each SQL statement one more level to display a breakdown by load module.

SQL Statement

This item attributes measured activity to a DB2 SQL statement.

Name Column

A sequence number is assigned by Application Performance Analyzer to each unique SQL statement observed during the measurement. This sequence number is shown in the name field. It is possible for some sequences numbers to be missing (sequence gaps) from the report. This will occur if a sequence number was assigned to SQL statements but no CPU activity was measured for these statements.

Description Column

The name of the program that issued the SQL request followed by the precompiler statement number (enclosed in parentheses) is shown here. This is followed by the SQL function (e.g. SELECT, INSERT, COMMIT).

Chapter 7. MQSeries performance analysis reports

This section describes the MQSeries performance analysis reports.

| For information about ... | See ... |
|--|--|
| The MQSeries data extractor | "Overview of MQSeries data extractor" |
| Q01 MQSeries activity summary | "Q01 - MQSeries activity summary" on page 410 |
| Q02 MQSeries CPU usage by queue | "Q02 - MQSeries CPU usage by queue" on page 412 |
| Q03 MQSeries CPU usage by request | "Q03 - MQSeries CPU usage by request" on page 415 |
| Q04 MQSeries CPU usage by transaction | "Q04 - MQSeries CPU usage by Txn" on page 417 |
| Q05 MQSeries service time by queue | "Q05 - MQSeries service time by queue" on page 420 |
| Q06 MQSeries Serv Time by Request | "Q06 - MQSeries service time by request" on page 423 |
| Q07 MQSeries service time by transaction | "Q07 - MQSeries service time by Txn" on page 425 |
| Q08 MQSeries wait time by queue | "Q08 - MQSeries wait time by queue" on page 428 |
| Q09 MQSeries wait time by request | "Q09 - MQSeries wait time by request" on page 431 |
| Q10 MQSeries wait time by transaction | "Q10 - MQSeries wait time by Txn" on page 433 |

Overview of MQSeries data extractor

In order to use the MQSeries Performance Analysis Reports, the MQSeries data extractor must be turned on when the Observation Request is entered. You must select the MQS data extractor in the Enter an Observation Request panel.

This data extractor provides the ability to observe/sample and report on MQSeries interface calls (both dynamic and static) in Batch, IMS and CICS programs. More specifically, to show the CPU and wait time spent in MQSeries interface calls and to attribute the time spent to a particular MQSeries interface call.

When the MQSeries data extractor is selected, Application Performance Analyzer will record the following information in the sample file for each MQSeries call that it observes:

- Environment (Batch, IMS or CICS)
- Load module that issued the call
- Offset within the load module of the return address from the MQ call
- Type of MQI call (MQOPEN, MQGET, etc.)
- Queue Manager name
- Object name (for example, the queue name)

- Message size (actual length for MQPUT/MQPUT1, buffer length for MQGET)
- MQ Options (for MQOPEN, MQGET, MQPUT MQCLOSE)
- Message type, priority and persistence
- Transaction ID (CICS and IMS)

Note: In an IMS environment, Application Performance Analyzer might not be able to determine the default Queue Manager name for some samples if the Application Performance Analyzer task has not previously sampled any. This might result in the MQ object name being unknown for the first few calls. Subsequent sampling runs will obtain the MQ object name for each sample.

Q01 - MQSeries activity summary

Usage

Use this report to see a summary of the MQSeries requests (Calls) issued during the observation session and a list of the MQSeries objects referenced by these requests.

Detail line descriptions

Access to the following MQSeries objects observed

Each referenced object is described under this heading. For each object, the following information is reported:

| Under Heading | This is Displayed |
|---------------------|--|
| Object Seq. Nbr | A unique sequence number assigned by Application Performance Analyzer to each unique object. |
| Object Manager Name | The name of the MQSeries Queue Manager – usually four characters. This name is combined with the object name to fully qualify the name. |
| Object Name | A one to 48 character MQSeries object name. Some functions do not reference an object. In this case, Application Performance Analyzer shows an entry with 'n/a' in this field. |

| Under Heading | This is Displayed |
|---------------|--|
| Object Type | The type of object. One of the following is shown: <ul style="list-style-type: none"> • Queue • Namelist • Process • Storage Class • Queue Manager • Channel • Auth Info • CF Structure • Alias Queue • Model Queue • Local Queue • Remote Queue • Sender Channel • Server Channel • Reqstr Channel • Recvr Channel • Current Channel • Saved Channel • SVRCON Channel • CLNTCON Channel |

MQSeries calls observed

Each observed MQSeries request is listed under this heading. For each request, the following information is reported:

| Under Heading | This is Displayed |
|---------------|---|
| Module | The name of the load module that issued the MQSeries request. |
| CSECT | The name of the CSECT in the module containing the MQSeries CALL. |
| Offset | The hexadecimal offset in the CSECT of the return address to the CALL. |
| Function | The MQSeries function: <ul style="list-style-type: none"> • CONNECT • DISCONN • OPEN • CLOSE • GET • PUT • PUT1 • COMMIT • BACKOUT • INQUIRE • SET |
| Queue Mgr | The Queue Manager name. |
| Object Name | The object name. |

Sample reports

A sample report is shown here:

```
File View Navigate Help
-----
Q01: MQSeries Activity Summary (0643/MQTST01) Row 00001 of 00023
Command ==> _____ Scroll ==> CSR

Access to the Following MQSeries Objects Observed

Object Sequence Number 0001
Queue Manager Name CSQ1
Object Name n/a

Object Sequence Number 0002
Queue Manager Name CSQ1
Object Name SYSTEM.DEFAULT.ALIAS.QUEUE
Object Type Queue

MQSeries Calls Observed

Module CSECT Offset Function Queue Mgr Object Name
MQBCS01 MQBCS01 0030A4 CONNECT CSQ1
MQBCS01 MQBCS01 00313E OPEN CSQ1 SYSTEM.DEFAULT.ALIAS.Q
MQBCS01 MQBCS01 00334C PUT CSQ1 SYSTEM.DEFAULT.ALIAS.Q
MQBCS01 MQBCS01 0033DC CLOSE CSQ1 SYSTEM.DEFAULT.ALIAS.Q
MQBCS01 MQBCS01 0033DC CLOSE CSQ1
MQBCS01 MQBCS01 003452 COMMIT CSQ1
MQBCS01 MQBCS01 0034c8 DISCONN CSQ1
```

Q02 - MQSeries CPU usage by queue

Usage

Use this report to see how CPU resources were consumed by MQSeries Requests. The percentage of CPU usage is reported by MQSeries Queue Name. Expand the Queue Name detail lines to see a further breakdown by individual MQSeries Request.

Quantification

Each report line quantifies CPU usage for an MQSeries Queue Name. This is further broken down by MQSeries Request.

Detail line hierarchy

An unexpanded Q02 report shows a line for each MQSeries Queue. You can expand each line to reveal one additional hierarchical level of detail.

The hierarchy is illustrated here:

```
Level 1 MQSeries Queue
Level 2 MQSeries Request
Level 2 MQSeries Request
```

...

Detail line descriptions

MQSeries queue detail line

This is the first-level detail line. Each line shows information about an MQSeries Queue for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------------|---|
| Name | The MQSeries Queue Manager name. This name, in combination with the Queue Name, uniquely identifies the MQSeries Queue. |
| Description | The MQSeries Queue Name. This name, in combination with the Queue Manager Name, uniquely identifies the MQSeries Queue. |
| Percent of CPU Time | The percentage of CPU time consumed while executing MQSeries Requests for the indicated MQSeries Queue Name. |

MQSeries request detail line

This is a second-level detail line shown directly under the MQSeries Queue detail line. It quantifies CPU usage for a specific MQSeries Request.

| Under Heading | This is Displayed |
|---------------------|---|
| Name | The MQSeries Request function. This is the MQSeries function specified by the MQSeries Request. |
| Description | Program name and offset. This is the name of the program in which the MQSeries CALL was issued and the hexadecimal offset of the CALL return address. |
| Percent of CPU Time | The percentage of CPU time consumed while executing the indicated MQSeries Request. |

Sample reports

A sample report is shown here. It has been fully expanded by entering “+” on the Name field.

```

File View Navigate Help
-----
Q02: MQSeries CPU Usage by Queue (0643/MQTST01)          Row 00001 of 00010
Command ==>>> _____ Scroll ==>>> CSR

Name      Description      Percent of CPU time * 10.00% ±2.8%
          *...1...2...3...4...5...6...7.
CSQ1     SYSTEM.DEFAULT.ALIAS.QUEUE  75.90 =====
→ PUT    MQBCS01+334C             75.50 =====
→ OPEN   MQBCS01+313E             0.32
→ CLOSE  MQBCS01+33DC             0.08

CSQ1     No Object Name      8.83 ==
→ CONNECT MQBCS01+30A4        7.06 ==
→ DISCONN MQBCS01+34C8        1.60 =
→ CLOSE  MQBCS01+33DC        0.08
→ COMMIT MQBCS01+3452        0.08

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Queue, Request | Display context help information. |
| ++ | Queue, Request | Show additional details. |
| + | Queue | Expand to reveal next level. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|---------------------------------|
| - | Queue | Collapse to hide next level. |
| SV | Queue | Sort next level by value. |
| SN | Queue | Sort next level by name. |
| P | Request | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size |
| + | Percent of CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent of CPU | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| > PUT      MQBCS01+334C      78.70 000000000000000000000000 |
+-----+

Calculation Details
MQ Series CPU measurements           1,201
Total CPU measurements               1,526
Percent of total                     78.70%

MQSeries Request Details
Calling Module  MQBCS01
CSECT          MQBCS01
Offset         00334C
Request Type   PUT
Queue Manager  CSQ1
Object Name    SYSTEM.DEFAULT.LOCAL.QUEUE
Object Type    Queue

```

Q03 - MQSeries CPU usage by request

Usage

Use this report to see how CPU resources were consumed by MQSeries Requests. The percentage of CPU usage is reported by MQSeries Request. Expand the MQSeries Request lines to see a further breakdown by MQSeries Queue.

Quantification

Each report line quantifies CPU usage for an MQSeries Request. This is further broken down by MQSeries Queue Name.

Detail line descriptions

MQSeries request detail line

This is a first-level detail line shown directly under the MQSeries Queue detail line. It quantifies CPU usage for a specific MQSeries Request.

| Under Heading | This is Displayed |
|---------------------|---|
| Name | The MQSeries Request function. This is the MQSeries function specified by the MQSeries Request. |
| Description | Program name and offset. This is the name of the program in which the MQSeries CALL was issued and the hexadecimal offset of the CALL return address. |
| Percent of CPU Time | The percentage of CPU time consumed while executing the indicated MQSeries Request. |

MQSeries queue detail line

This is the second-level detail line. Each line shows information about an MQSeries Queue for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------------|---|
| Name | The MQSeries Queue Manager name. This name, in combination with the Queue Name, uniquely identifies the MQSeries Queue. |
| Description | The MQSeries Queue Name. This name, in combination with the Queue Manager Name, uniquely identifies the MQSeries Queue. |
| Percent of CPU Time | The percentage of CPU time consumed while executing MQSeries Requests for the indicated MQSeries Queue Name. |

Sample reports

A sample report is shown here:

| File View Navigate Help | | | |
|---|--------------|---------------------------------------|-------|
| Q03: MQSeries CPU Usage by Request (0643/MQTST01) | | Row 00001 of 00007 | |
| Command ==> | | Scroll ==> CSR | |
| Name | Description | Percent of CPU time * 10.00% | ±2.8% |
| | | *....1....2....3....4....5....6....7. | |
| PUT | MQBCS01+334C | 75.50 | ===== |
| CONNECT | MQBCS01+30A4 | 7.06 | === |
| DISCONN | MQBCS01+34C8 | 1.60 | = |
| OPEN | MQBCS01+313E | 0.32 | |
| CLOSE | MQBCS01+33DC | 0.08 | |
| CLOSE | MQBCS01+33DC | 0.08 | |
| COMMIT | MQBCS01+3452 | 0.08 | |

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Request, Queue | Display context help information. |
| ++ | Request, Queue | Show additional details. |
| + | Request | Expand to reveal next level. |
| - | Request | Collapse to hide next level. |
| P | Request | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size |
| + | Percent of CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent of CPU | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter "++" (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```
File View Navigate Help
+-----+
+----- The following report line was selected -----+
| > PUT      MQBCS01+334C      78.70 00000000000000000000000000000000 |
+-----+

Calculation Details
MQ Series CPU measurements          1,201
Total CPU measurements              1,526
Percent of total                    78.70%

MQSeries Request Details
Calling Module    MQBCS01
CSECT            MQBCS01
Offset           00334C
Request Type     PUT
Queue Manager    CSQ1
Object Name      SYSTEM.DEFAULT.LOCAL.QUEUE
Object Type      Queue
```

Q04 - MQSeries CPU usage by Txn

Usage

Use this report to see how CPU resources were consumed by MQSeries Requests. The percentage of CPU usage is reported by CICS or IMS transaction. Expand the transaction detail lines to see a further breakdown by MQSeries Queue and by individual MQSeries Request.

Quantification

Each report line quantifies CPU usage for a CICS or IMS transaction under which MQSeries Requests were serviced. This is further broken down by MQSeries Queue and by MQSeries Request.

Detail line hierarchy

An unexpanded Q04 report shows a line for each CICS or IMS transaction. You can expand each line to reveal one additional hierarchical level of detail.

The hierarchy is illustrated here:

- Level 1 CICS/IMS Transaction Level
- Level 2 MQSeries Queue
- Level 3 MQSeries Request
- Level 3 MQSeries Request

...

Detail line descriptions

CICS/IMS transaction detail line

This is the first-level detail line. Each line shows information about a CICS or IMS transaction under which MQSeries requests were issued.

| Under Heading | This is Displayed |
|---------------------|--|
| Name | A CICS or IMS transaction code. This is the transaction under which measured MQSeries Requests were issued. "Batch" is shown here for request not issued under control of a CICS or IMS transaction. |
| Description | "CICS Transaction" or "IMS Transaction". "Not in IMS/CICS Txn" is shown here if the request was not issued under control of a CICS or IMS transaction. |
| Percent of CPU Time | The percentage of CPU time consumed while executing MQSeries Requests under control of the indicated transaction. |

MQSeries queue detail line

This is the second-level detail line. Each line shows information about an MQSeries Queue for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------------|---|
| Name | The MQSeries Queue Manager name. This name, in combination with the Queue Name, uniquely identifies the MQSeries Queue. |
| Description | The MQSeries Queue Name. This name, in combination with the Queue Manager Name, uniquely identifies the MQSeries Queue. |
| Percent of CPU Time | The percentage of CPU time consumed while executing MQSeries Requests for the indicated MQSeries Queue Name. |

MQSeries request detail line

This is a third-level detail line shown directly under the MQSeries Queue detail line. It quantifies CPU usage for a specific MQSeries Request.

| Under Heading | This is Displayed |
|---------------------|---|
| Name | The MQSeries Request function. This is the MQSeries function specified by the MQSeries Request. |
| Description | Program name and offset. This is the name of the program in which the MQSeries CALL was issued and the hexadecimal offset of the CALL return address. |
| Percent of CPU Time | The percentage of CPU time consumed while executing the indicated MQSeries Request. |

Sample reports

A sample report is show here. It has been fully expanding by entering "+" on the Name heading.

```

File View Navigate Help
-----
Q04: MQSeries CPU Usage by Txn/Queue (0025/MQTST01)          Row 00001 of 00015
Command ==> _____ Scroll ==> CSR

Name      Description      Percent of CPU time * 10.00% ±2.8%
          *...1...2...3...4...5...6...7.
MQS1      CICS Transaction    13.71 =====
→ CSQ1    CSQ1.DEFXMIT.QUEUE 13.20 =====
→ GET     MQSAMP1+2DF2       10.92 =====
→ OPEN    MQSAMP1+2C2C       1.94 =
→ CLOSE   MQSAMP1+31A0       0.34
→ CSQ1    No Object Name     0.50
→ CLOSE   MQSAMP1+31A0       0.50

MQDR      CICS Transaction    8.03 =====
→ CSQ1    CSQ1.DEFXMIT.QUEUE 7.80 =====
→ PUT     CSQ4CVK1+284E      5.65 ===
→ OPEN    CSQ4CVK1+277E      1.86 =
→ CLOSE   CSQ4CVK1+29E2      0.28
→ CSQ1    No Object Name     0.23
→ CLOSE   CSQ4CVK1+29E2      0.12

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------------|-----------------------------------|
| ? | Transactions, Queue, Request | Display context help information. |
| ++ | Transactions, Queue, Request | Show additional details. |
| + | Transactions, Queue | Expand to reveal next level. |
| - | Transactions, Queue | Collapse to hide next level. |
| SV | Transactions, Queue | Sort next level by value. |
| SN | Transactions, Queue | Sort next level by name. |
| P | Request | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size |
| + | Percent of CPU | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent of CPU | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here:

```
File View Navigate Help
+-----+
+----- The following report line was selected -----+
| > PUT      MQBCS01+334C      78.70 000000000000000000000000|
+-----+

Calculation Details
MQ Series CPU measurements      1,201
Total CPU measurements          1,526
Percent of total                 78.70%

MQSeries Request Details
Calling Module  MQBCS01
CSECT          MQBCS01
Offset         00334C
Request Type   PUT
Queue Manager  CSQ1
Object Name    SYSTEM.DEFAULT.LOCAL.QUEUE
Object Type    Queue
```

Q05 - MQSeries service time by queue

Usage

Use this report to see how time was consumed by MQSeries Requests. The percentage of time is reported by MQSeries Queue Name. Expand the Queue Name detail lines to see a further breakdown by individual MQSeries Request.

Quantification

Each report line quantifies service time for an MQSeries Queue Name. The service time is the actual time measured MQSeries requests were being processed. This is further broken down by MQSeries Request.

Detail line hierarchy

An unexpanded Q05 report shows a line for each MQSeries Queue. You can expand each line to reveal one additional hierarchical level of detail.

The hierarchy is illustrated here:

```
Level 1 MQSeries Queue
Level 2 MQSeries Request
Level 2 MQSeries Request
```

...

Detail line descriptions

MQSeries queue detail line

This is the first-level detail line. Each line shows information about an MQSeries Queue for which measurement data was recorded.

| Under Heading | This is Displayed |
|-----------------|---|
| Name | The MQSeries Queue Manager name. This name, in combination with the Queue Name, uniquely identifies the MQSeries Queue. |
| Description | The MQSeries Queue Name. This name, in combination with the Queue Manager Name, uniquely identifies the MQSeries Queue. |
| Percent of Time | The percentage of the measurement interval duration MQSeries Requests for the indicated Queue Name were being processed. This represents the percentage of samples for MQSeries requests out of the total number of samples, except for CICS measurements, where it represents the percentage of samples for MQSeries requests out of the total number of CICS samples. |

MQSeries request detail line

This is a second-level detail line shown directly under the MQSeries Queue detail line. It quantifies time consumed during executions of a specific MQSeries Request.

| Under Heading | This is Displayed |
|-----------------|--|
| Name | The MQSeries Request function. This is the MQSeries function specified by the MQSeries Request. |
| Description | Program name and offset. This is the name of the program in which the MQSeries CALL was issued and the hexadecimal offset of the CALL return address. |
| Percent of Time | The percentage of the measurement interval duration the indicated MQSeries request was being processed. This represents the percentage of samples for MQSeries requests out of the total number of samples, except for CICS measurements, where it represents the percentage of samples for MQSeries requests out of the total number of CICS samples. |

Sample reports

A sample report is show here. It has been fully expanded by pressing “+” on the Name heading.

```

File View Navigate Help
-----
Q05: MQSeries Service Time by Queue (0025/MQTST01)          Row 00001 of 00010
Command ==>>> _____ Scroll ==>>> CSR

Name      Description      Percent of time * 10.00% ±0.9%
          *...1...2...3...4...5...6...7.
CSQ1     CSQ1.DEFXMIT.QUEUE  29.71 =====
→ GET    MQSAMP1+2DF2        14.79 =====
→ PUT    CSQ4CVK1+284E       8.56  ===
→ OPEN   CSQ4CVK1+277E       2.64  =
→ OPEN   MQSAMP1+2C2C        2.54  =
→ CLOSE  CSQ4CVK1+29E2       0.61
→ CLOSE  MQSAMP1+31A0        0.55

CSQ1     No Object Name      0.90
→ CLOSE  MQSAMP1+31A0        0.50
→ CLOSE  CSQ4CVK1+29E2       0.39

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Queue, Request | Display context help information. |
| ++ | Queue, Request | Show additional details. |
| + | Queue | Expand to reveal next level |
| - | Queue | Collapse to hide next level |
| SV | Queue | Sort next level by value. |
| SN | Queue | Sort next level by name. |
| P | Request | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size |
| + | Percent of Time | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent of Time | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| > PUT      MQBCS01+334C          72.46 000000000000000000000000 |
+-----+

Calculation Details
MQ Series activity measurements      1,645
Total measurements                   2,270
Percent of total                     72.46%

MQSeries Request Details
Calling Module  MQBCS01
CSECT          MQBCS01
Offset         00334C
Request Type   PUT
Queue Manager  CSQ1
Object Name    SYSTEM.DEFAULT.LOCAL.QUEUE
Object Type    Queue
  
```

Q06 - MQSeries service time by request

Usage

Use this report to see how time was consumed by MQSeries Requests. The percentage of time is reported by MQSeries Request. Expand the MQSeries Request lines to see a further breakdown by MQSeries Queue.

Quantification

Each report line quantifies service time for an MQSeries Request. This is further broken down by MQSeries Queue Name.

Detail line hierarchy

An unexpanded Q06 report shows a line for each MQSeries Request. You can expand each line to reveal one additional hierarchical level of detail.

The hierarchy is illustrated here:

Level 1 MQSeries Request
Level 2 MQSeries Queue
Level 2 MQSeries Queue

...

Detail line descriptions

MQSeries request detail line

This is a first-level detail line shown directly under the MQSeries Queue detail line. It quantifies consumption of time for a specific MQSeries Request.

| Under Heading | This is Displayed |
|-----------------|--|
| Name | The MQSeries Request function. This is the MQSeries function specified by the MQSeries Request. |
| Description | Program name and offset. This is the name of the program in which the MQSeries CALL was issued and the hexadecimal offset of the CALL return address. |
| Percent of Time | The percentage of the measurement interval duration the indicated MQSeries request was being processed. This represents the percentage of samples for MQSeries requests out of the total number of samples, except for CICS measurements, where it represents the percentage of samples for MQSeries requests out of the total number of CICS samples. |

MQSeries queue detail line

This is the second-level detail line. Each line shows information about an MQSeries Queue for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The MQSeries Queue Manager name. This name, in combination with the Queue Name, uniquely identifies the MQSeries Queue. |
| Description | The MQSeries Queue Name. This name, in combination with the Queue Manager Name, uniquely identifies the MQSeries Queue. |

| Under Heading | This is Displayed |
|-----------------|---|
| Percent of Time | The percentage of the measurement interval duration MQSeries Requests for the indicated Queue Name were being processed. This represents the percentage of samples for MQSeries requests out of the total number of samples, except for CICS measurements, where it represents the percentage of samples for MQSeries requests out of the total number of CICS samples. |

Sample reports

A sample report is shown here:

```

File View Navigate Help
-----
Q06: MQSeries Service Time by Request (0643/MQTST01)      Row 00001 of 00007
Command ==>> _____ Scroll ==>> CSR

Name      Description      Percent of time * 10.00% ±2.3%
          *...1...2...3...4...5...6...7.
PUT       MQBCS01+334C      60.38 =====
CONNECT  MQBCS01+30A4      10.84 =====
DISCONN  MQBCS01+34C8      1.42 =
COMMIT   MQBCS01+3452      1.09 =
OPEN     MQBCS01+313E      0.21
CLOSE    MQBCS01+33DC      0.05
CLOSE    MQBCS01+33DC      0.05

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Request, Queue | Display context help information. |
| ++ | Request, Queue | Show additional details. |
| + | Request | Expand to reveal next level |
| - | Request | Collapse to hide next level |
| P | Request | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size |
| + | Percent of Time | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent of Time | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```
File View Navigate Help
+-----+
+----- The following report line was selected -----+
| > PUT      MQBCS01+334C      72.46 00000000000000000000000000000000|
+-----+

Calculation Details
MQ Series activity measurements      1,645
Total measurements                    2,270
Percent of total                      72.46%

MQSeries Request Details
Calling Module      MQBCS01
CSECT               MQBCS01
Offset              00334C
Request Type        PUT
Queue Manager       CSQ1
Object Name         SYSTEM.DEFAULT.LOCAL.QUEUE
Object Type         Queue
```

Q07 - MQSeries service time by Txn

Usage

Use this report to see how time was consumed by MQSeries Requests. The percentage of time is reported by CICS or IMS transaction. Expand the transaction detail lines to see a further breakdown by MQSeries Queue and by individual MQSeries Request.

Quantification

Each report line quantifies time consumed by MQSeries requests in a CICS or IMS transaction. This is further broken down by MQSeries Queue and by MQSeries Request.

Detail line hierarchy

An unexpanded Q07 report shows a line for each CICS or IMS transaction. You can expand each line to reveal one additional hierarchical level of detail.

The hierarchy is illustrated here:

- Level 1** CICS/IMS Transaction
- Level 2** MQSeries Queue
- Level 3** MQSeries Request
- Level 3** MQSeries Request

...

Detail line descriptions

CICS/IMS transaction detail line

This is the first-level detail line. Each line shows information about a CICS or IMS transaction under which MQSeries requests were issued.

| Under Heading | This is Displayed |
|-----------------|---|
| Name | A CICS or IMS transaction code. This is the transaction under which measured MQSeries Requests were issued. "Batch" is shown here for request not issued under control of a CICS or IMS transaction. |
| Description | "CICS Transaction" or "IMS Transaction." "Not in IMS/CICS Txn" is shown here if the request was not issued under control of a CICS or IMS transaction. |
| Percent of Time | The percentage of the measurement interval duration MQSeries Requests under control of the indicated transaction were being processed. This represents the percentage of samples for MQSeries requests out of the total number of samples, except for CICS measurements, where it represents the percentage of samples for MQSeries requests out of the total number of CICS samples. |

MQSeries queue detail line

This is the second-level detail line. Each line shows information about an MQSeries Queue for which measurement data was recorded.

| Under Heading | This is Displayed |
|-----------------|---|
| Name | The MQSeries Queue Manager name. This name, in combination with the Queue Name, uniquely identifies the MQSeries Queue. |
| Description | The MQSeries Queue Name. This name, in combination with the Queue Manager Name, uniquely identifies the MQSeries Queue. |
| Percent of Time | The percentage of the measurement interval duration MQSeries Requests for the indicated Queue Name were being processed. This represents the percentage of samples for MQSeries requests out of the total number of samples, except for CICS measurements, where it represents the percentage of samples for MQSeries requests out of the total number of CICS samples. |

MQSeries request detail line

This is a third-level detail line shown directly under the MQSeries Queue detail line. It quantifies time consumption for a specific MQSeries Request.

| Under Heading | This is Displayed |
|-----------------|--|
| Name | The MQSeries Request function. This is the MQSeries function specified by the MQSeries Request. |
| Description | Program name and offset. This is the name of the program in which the MQSeries CALL was issued and the hexadecimal offset of the CALL return address. |
| Percent of Time | The percentage of the measurement interval duration the indicated MQSeries request was being processed. This represents the percentage of samples for MQSeries requests out of the total number of samples, except for CICS measurements, where it represents the percentage of samples for MQSeries requests out of the total number of CICS samples. |

Sample reports

A fully expanded report is shown here:

```

File View Navigate Help
-----
Q07: MQSeries Service Time by Txn/Queue (0025/MQTST01)      Row 00001 of 00015
Command ==>> _____ Scroll ==>> CSR

Name      Description      Percent of time * 10.00% ±0.9%
          *...1...2...3...4...5...6...7.
MQS1      CICS Transaction  18.40 =====
→ CSQ1    CSQ1.DEFXMIT.QUEUE 17.89 =====
  → GET    MQSAMP1+2DF2      14.79 =====
  → OPEN   MQSAMP1+2C2C      2.54 =
  → CLOSE  MQSAMP1+31A0      0.55
→ CSQ1    No Object Name    0.50
  → CLOSE  MQSAMP1+31A0      0.50

MQDR      CICS Transaction  12.21 ====
→ CSQ1    CSQ1.DEFXMIT.QUEUE 11.82 ====
  → PUT    CSQ4CVK1+284E     8.56 ===
  → OPEN   CSQ4CVK1+277E     2.64 =
  → CLOSE  CSQ4CVK1+29E2     0.61
→ CSQ1    No Object Name    0.39
  → CLOSE  CSQ4CVK1+29E2     0.39

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|-----------------------------|-----------------------------------|
| ? | Transaction, Queue, Request | Display context help information. |
| ++ | Transaction, Queue, Request | Show additional details. |
| + | Transaction, Queue | Expand to reveal next level. |
| - | Transaction, Queue | Collapse to hide next level. |
| SV | Transaction, Queue | Sort next level by value. |
| SN | Transaction, Queue | Sort next level by name. |
| P | Request | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size |
| + | Percent of Time | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent of Time | Zoom out scale. |

Detail line descriptions

MQSeries queue detail line

This is the first-level detail line. Each line shows information about an MQSeries Queue for which measurement data was recorded.

| Under Heading | This is Displayed |
|-----------------|---|
| Name | The MQSeries Queue Manager name. This name, in combination with the Queue Name, uniquely identifies the MQSeries Queue.. |
| Description | The MQSeries Queue Name. This name, in combination with the Queue Manager Name, uniquely identifies the MQSeries Queue. |
| Percent of Time | The percentage of the measurement interval duration MQSeries Requests for the indicated Queue Name were being processed. This represents the percentage of samples for MQSeries requests out of the total number of samples, except for CICS measurements, where it represents the percentage of samples for MQSeries requests out of the total number of CICS samples. |

MQSeries request detail line

This is a second-level detail line shown directly under the MQSeries Queue detail line. It quantifies wait time during executions of a specific MQSeries Request.

| Under Heading | This is Displayed |
|-----------------|--|
| Name | The MQSeries Request function. This is the MQSeries function specified by the MQSeries Request. |
| Description | Program name and offset. This is the name of the program in which the MQSeries CALL was issued and the hexadecimal offset of the CALL return address. |
| Percent of Time | The percentage of the measurement interval duration the indicated MQSeries request was being processed. This represents the percentage of samples for MQSeries requests out of the total number of samples, except for CICS measurements, where it represents the percentage of samples for MQSeries requests out of the total number of CICS samples. |

Sample reports

A fully expanded report is shown here:

```

File View Navigate Help
-----
Q08: MQSeries Wait Time by Queue (0025/MQTST01)          Row 00001 of 00011
Command ==>>> _____ Scroll ==>>> CSR

Name      Description      Percent of time * 10.00% ±0.9%
          *.....1.....2.....3.....4.....5.....6.....7.
CSQ1      CSQ1.DEFXMIT.QUEUE  5.80 ==
→ GET      MQSAMP1+2DF2        3.01 ==
→ PUT      CSQ4CVK1+284E       1.60 =
→ OPEN     CSQ4CVK1+277E       0.59
→ OPEN     MQSAMP1+2C2C        0.38
→ CLOSE    CSQ4CVK1+29E2       0.18
→ CLOSE    MQSAMP1+31A0        0.01

CSQ1      No Object Name      0.10
→ CLOSE    MQSAMP1+31A0        0.08
→ CLOSE    CSQ4CVK1+29E2       0.01

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Queue, Request | Display context help information. |
| ++ | Queue, Request | Show additional details. |
| + | Queue | Expand to reveal next level. |
| - | Queue | Collapse to hide next level. |
| SV | Queue | Sort next level by value. |
| SN | Queue | Sort next level by name. |
| P | Request | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size |
| + | Percent of Time | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent of Time | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| > PUT      MQBCS01+334C      19.55 0000000000      |
+-----+

Calculation Details
MQ Series wait measurements      444
Total measurements                2,270
Percent of total                  19.55%

MQSeries Request Details
Calling Module    MQBCS01
CSECT            MQBCS01
Offset           00334C
Request Type     PUT
Queue Manager    CSQ1
Object Name      SYSTEM.DEFAULT.LOCAL.QUEUE
Object Type      Queue

```

Q09 - MQSeries wait time by request

Usage

Use this report to see how much wait time occurred during processing of MQSeries Requests. The percentage of wait time is reported by MQSeries Request. Expand the MQSeries Request lines to see a further breakdown by MQSeries Queue.

Quantification

Each report line quantifies wait time for an MQSeries Request. This is further broken down by MQSeries Queue Name.

Detail line hierarchy

An unexpanded Q09 report shows a line for each MQSeries Request. You can expand each line to reveal one additional hierarchical level of detail.

The hierarchy is illustrated here:

- Level 1 MQSeries Request
- Level 2 MQSeries Queue
- Level 2 MQSeries Queue

...

Detail line descriptions

MQSeries request detail line

This is a first-level detail line shown directly under the MQSeries Queue detail line. It quantifies wait time for a specific MQSeries Request.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The MQSeries Request function. This is the MQSeries function specified by the MQSeries Request. |

| Under Heading | This is Displayed |
|-----------------|--|
| Description | Program name and offset. This is the name of the program in which the MQSeries CALL was issued and the hexadecimal offset of the CALL return address. |
| Percent of Time | The percentage of the measurement interval duration the indicated MQSeries request was being processed. This represents the percentage of samples for MQSeries requests out of the total number of samples, except for CICS measurements, where it represents the percentage of samples for MQSeries requests out of the total number of CICS samples. |

MQSeries queue detail line

This is the second-level detail line. Each line shows information about an MQSeries Queue for which measurement data was recorded.

| Under Heading | This is Displayed |
|-----------------|---|
| Name | The MQSeries Queue Manager name. This name, in combination with the Queue Name, uniquely identifies the MQSeries Queue. |
| Description | The MQSeries Queue Name. This name, in combination with the Queue Manager Name, uniquely identifies the MQSeries Queue. |
| Percent of Time | The percentage of the measurement interval duration MQSeries Requests for the indicated Queue Name were being processed. This represents the percentage of samples for MQSeries requests out of the total number of samples, except for CICS measurements, where it represents the percentage of samples for MQSeries requests out of the total number of CICS samples. |

Sample reports

A sample report is shown here:

| Name | Description | Percent of time * 10.00% ±2.3% |
|---------|--------------|--------------------------------|
| COMMIT | MQBCS01+3452 | 1.04 = |
| CONNECT | MQBCS01+30A4 | 0.38 |
| DISCONN | MQBCS01+34C8 | 0.21 |

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Request, Queue | Display context help information. |
| ++ | Request, Queue | Show additional details. |
| + | Request | Expand to reveal next level. |
| - | Request | Collapse to hide next level. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|---------------------------------|
| P | Request | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size |
| + | Percent of Time | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent of Time | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information. A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| > PUT      MQBCS01+334C      19.55 0000000000      |
+-----+

Calculation Details
MQ Series wait measurements          444
Total measurements                   2,270
Percent of total                     19.55%

MQSeries Request Details
Calling Module  MQBCS01
CSECT          MQBCS01
Offset         00334C
Request Type   PUT
Queue Manager  CSQ1
Object Name    SYSTEM.DEFAULT.LOCAL.QUEUE
Object Type    Queue
  
```

Q10 - MQSeries wait time by Txn

Usage

Use this report to see how much wait time occurred during processing of MQSeries Requests. The percentage of wait time is reported by CICS or IMS transaction. Expand the transaction detail lines to see a further breakdown by MQSeries Queue and by individual MQSeries Request.

Quantification

Each report line quantifies wait time in MQSeries requests in a CICS or IMS transaction. This is further broken down by MQSeries Queue and by MQSeries Request.

Detail line hierarchy

An unexpanded Q10 report shows a line for each CICS or IMS transaction. You can expand each line to reveal one additional hierarchical level of detail (using the “+” line command).

The hierarchy is illustrated here:

Level 1 CICS/IMS Transaction

Level 2 MQSeries Queue

Level 3 MQSeries Request

Level 3 MQSeries Request

...

Detail line descriptions

CICS/IMS transaction detail line

This is the first-level detail line. Each line shows information about a CICS or IMS transaction under which MQSeries requests were issued.

| Under Heading | This is Displayed |
|-----------------|--|
| Name | A CICS or IMS transaction code. This is the transaction under which measured MQSeries requests were issued. “Batch” is shown here for requests not issued under control of a CICS or IMS transaction. |
| Description | Either “CICS Transaction” or “IMS Transaction.” If the request was not issued under control of a CICS or IMS transaction, “Not in IMS/CICS Txn” will be displayed. |
| Percent of Time | The percentage of the measurement interval duration during which MQSeries requests under control of the indicated transaction were being processed. This represents the percentage of samples for MQSeries requests out of the total number of samples, except for CICS measurements, where it represents the percentage of samples for MQSeries requests out of the total number of CICS samples. |

MQSeries queue detail line

This is the second-level detail line. Each line shows information about an MQSeries Queue for which measurement data was recorded.

| Under Heading | This is Displayed |
|---------------|---|
| Name | The MQSeries Queue Manager name. This name, in combination with the Queue Name, uniquely identifies the MQSeries Queue. |
| Description | The MQSeries Queue Name. This name, in combination with the Queue Manager Name, uniquely identifies the MQSeries Queue. |

| Under Heading | This is Displayed |
|-----------------|---|
| Percent of Time | The percentage of the measurement interval duration MQSeries Requests for the indicated Queue Name were being processed. This represents the percentage of samples for MQSeries requests out of the total number of samples, except for CICS measurements, where it represents the percentage of samples for MQSeries requests out of the total number of CICS samples. |

MQSeries request detail line

This is a third-level detail line shown directly under the MQSeries Queue detail line. It quantifies wait time for a specific MQSeries Request.

| Under Heading | This is Displayed |
|-----------------|--|
| Name | The MQSeries Request function. This is the MQSeries function specified by the MQSeries Request. |
| Description | Program name and offset. This is the name of the program in which the MQSeries CALL was issued and the hexadecimal offset of the CALL return address. |
| Percent of Time | The percentage of the measurement interval duration the indicated MQSeries request was being processed. This represents the percentage of samples for MQSeries requests out of the total number of samples, except for CICS measurements, where it represents the percentage of samples for MQSeries requests out of the total number of CICS samples. |

Sample reports

A fully expanded report is shown here:

```

File View Navigate Help
-----
Q10: MQSeries Wait Time by Transaction (0025/MQTST01)      Row 00001 of 00015
Command ==>> _____ Scroll ==>> CSR

Name      Description      Percent of time * 2.5% ±0.9%
          *...1...2...3...4...5...6...7.
MQS1      CICS Transaction  3.64 =====
-> CSQ1    CSQ1.DEFXMIT.QUEUE  3.62 =====
  -> GET     MQSAMP1+2DF2        3.01 =====
  -> OPEN    MQSAMP1+2C2C        0.59 =
  -> CLOSE   MQSAMP1+31A0        0.01
-> CSQ1    No Object Name      0.01
  -> CLOSE   MQSAMP1+31A0        0.01

MQDR      CICS Transaction  2.25 ====
-> CSQ1    CSQ1.DEFXMIT.QUEUE  2.17 ====
  -> PUT     CSQ4CVK1+284E       1.60 ===
  -> OPEN    CSQ4CVK1+277E       0.38 =
  -> CLOSE   CSQ4CVK1+29E2       0.18
-> CSQ1    No Object Name      0.08
  -> CLOSE   CSQ4CVK1+29E2       0.08

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|-----------------------------|-----------------------------------|
| ? | Transaction, Queue, Request | Display context help information. |
| ++ | Transaction, Queue, Request | Show additional details. |
| + | Transaction, Queue | Expand to reveal next level. |
| - | Transaction, Queue | Collapse to hide next level. |
| SV | Transaction, Queue | Sort next level by value. |
| SN | Transaction, Queue | Sort next level by name. |
| P | Request | Display source program mapping. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | Name, Description, Percent CPU | Display context help information. |
| + | Name | Expand to reveal all entries. |
| + | Description | Expand field size |
| + | Percent of Time | Zoom in scale. |
| - | Name | Collapse to show only first level. |
| - | Description | Reduce field size. |
| - | Percent of Time | Zoom out scale. |
| SV | Name | Sort next level by value. |
| SN | Name | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| > PUT      MQBCS01+334C          19.55 0000000000    |
+-----+

Calculation Details
MQ Series wait measurements          444
Total measurements                   2,270
Percent of total                     19.55%

MQSeries Request Details
Calling Module  MQBCS01
CSECT          MQBCS01
Offset         00334C
Request Type   PUT
Queue Manager  CSQ1
Object Name    SYSTEM.DEFAULT.LOCAL.QUEUE
Object Type    Queue
  
```

Chapter 8. Java/USS/HFS performance analysis reports

This section describes the Java performance analysis reports.

| For information about ... | See ... |
|------------------------------------|--|
| The Java data extractor | "Overview of Java data extractor" on page 438 |
| J01 Java summary and attributes | "J01 - Java summary and attributes" on page 439 |
| J04 Java CPU usage by package | "J04 - Java CPU usage by package" on page 441 |
| J05 Java CPU usage by class | "J05 - Java CPU usage by class" on page 444 |
| J06 Java CPU usage by method | "J06 - Java CPU usage by method" on page 447 |
| J07 Java CPU usage by call path | "J07 - Java CPU usage by call path" on page 450 |
| J09 Java service time by package | "J09 - Java service time by package" on page 453 |
| J10 Java service time by class | "J10 - Java service time by class" on page 456 |
| J11 Java service time by method | "J11 - Java service time by method" on page 459 |
| J12 java service time by call path | "J12 - Java service time by call path" on page 462 |
| J14 Java wait time by package | "J14 - Java wait time by package" on page 465 |
| J15 Java wait time by class | "J15 - Java wait time by class" on page 468 |
| J16 Java wait time by method | "J16 - Java wait time by method" on page 471 |
| J17 Java wait time by call path | "J17 - Java wait time by call path" on page 474 |
| H01 HFS Service Time by Path Name | "H01 - HFS Service Time by Path Name" on page 477 |
| H02 HFS Service Time by Device | "H02 - HFS Service Time by Device" on page 479 |
| H03 HFS File Activity | "H03 - HFS File Activity" on page 482 |
| H04 HFS File Attributes | "H04 - HFS File Attributes" on page 484 |
| H05 HFS Device Activity | "H05 - HFS Device Activity" on page 485 |
| H06 HFS Device Attributes | "H06 - HFS Device Attributes" on page 487 |
| H07 HFS Activity Timeline | "H07 - HFS Activity Timeline" on page 488 |
| H08 HFS Wait Time by Path Name | "H08 - HFS Wait Time by Path Name" on page 490 |
| H09 HFS Wait Time by Device | "H09- HFS Wait Time by Device" on page 492 |
| H10 HFS Service Time by Request | "H10- HFS Service Time by Request" on page 495 |

| For information about ... | See ... |
|------------------------------|---|
| H11 HFS Wait Time by Request | "H11- HFS Wait Time by Request" on page 497 |

Overview of Java data extractor

In order to use the Java Performance Analysis Reports, the Java data extractor must be turned on when the Observation Request is entered. You must select the Java data extractor in the Schedule New Measurement panel.

The Java data extractor collects Java call stack information for each Java application thread. The call stack information identifies the methods in the call chain. Information about each method includes the package (if any), class, method and signature (parameter types and return type), and the source line number being executed (if available).

Java Version Support

Application Performance Analyzer supports 31-bit Java at the following levels:

- Java V1.4.2 SR13 and above
- Java V5 SR10 and above
- Java V6 SR11 and above

Considerations for Java V5 and V6

Before Java V5 and V6 programs can be sampled, the J9VM support in Application Performance Analyzer must be enabled. Contact your systems programmer to verify this support is enabled.

Only one observation at a time is supported for a specific Java V5 or V6 program.

CICS and IMS Java V5 and V6 programs are not supported.

Application Performance Analyzer will stop sampling Java V5 and V6 programs when the main thread ends, even if the specified number of samples has not been reached.

The Java Measurement reports for V5 and V6 are the same as V1.4.2. However, for V5 they are unrelated to the CPU Usage Analysis and CPU Wait Analysis reports.

Java calls that are observed with a native method at the top of the call stack are only included in the Service Time reports. This is because the J9VM does not know whether the native method is executing, waiting, or queued for execution.

Java V5 and V6 native methods are identified in the method detail pop-up window of Java Service Time reports.

If you are measuring applications running under Java V5 SR11 or Java V6 SR6, you must add the '-Dcom.ibm.tools.attach.enable=yes' run time parameter and run the job with UID=0.

USS multiple address space measurements

Spawned address spaces and substeps might be generated when measuring USS. Application Performance Analyzer will measure these additional address spaces if you specify a value in the USS observations field in the Schedule New Measurement panel.

When you use this feature, a USS master record will be displayed above all the associated measurements. The master record has a status of **USS**.

An example is shown here:

```
File View Navigate Help
-----
R02: IBM APA for z/OS Observation List (ZRAY) Row 00001 of 00221
Command ==> _____ Scroll ==> CSR

ReqNum Owned By Description Job Name Date/Time Samples Status
-----
+-----+
2385 + USER1 USS TEST#1 ARAUTEE Apr-18 19:56 2,500 USS
  -> 2386 BPXBATCH RUN Apr-18 19:56 10 Ended
  -> 2387 BPXPREFC *OMVSEX Apr-18 19:56 7 Ended
  -> 2388 BPXPREFC *OMVSEX *Java* Apr-18 19:57 2,500 Ended
  -> 2389 BPXPREFC STEP1 Apr-18 19:56 29 Ended
  -> 2390 BPXPREFC STEP1 Apr-18 19:57 2,500 Ended
  -> 2391 BPXPREFC STEP1 Apr-18 19:57 2,500 Ended
  -> 2392 BPXPREFC STEP1 *Java* Apr-18 19:57 2,500 Ended
  -> 2393 BPXPREFC STEP1 *Java* Apr-18 19:57 2,500 Ended
+-----+
```

You can expand the USS master record by entering a “+” on the sequence number. The additional measurements in the expanded record include the original measurement (the initiating step) and any spawned address spaces or substeps.

The description field in the subordinate measurements under the USS master record is populated with the program name and step name. For spawned address spaces, this would normally be BPXPREFC STEP1. For substeps, this would normally be BPXPREFC *OMVSEX.

If Java is detected in a step, then *Java* is placed in the description to the right of the program and step name.

If the step is run from the USS shell, and a Java command string is available, then the Java command string will be placed in the description instead of the information described above.

J01 - Java summary and attributes

Usage

This report displays general information about the observed Java environment. There are four sections:

- Java Virtual Machines
- Java Packages
- Java Classes
- Java Methods

Java Virtual Machines

This section identifies Java Virtual Machines (JVMs) observed during the measurement session.

Java packages

This section lists each of the Java packages in which activity was observed during the measurement session. Each package is assigned a unique sequence number, which is cross referenced in other reports.

Java classes

This section lists each of the Java classes in which activity was observed during the measurement session. Each class is assigned a unique sequence number, which is cross referenced in other reports.

Java methods

This section lists each of the Java methods in which activity was observed during the measurement session. Each method is assigned a unique sequence number, which is cross referenced in other reports.

Sample reports

A sample report is shown here.

```
File View Navigate Help
-----
J01: Java Summary/Attributes (8551/JVMTST01) Row 00001 of 00082
Command ==>> _____ Scroll ==>> CSR

Observed Java Virtual Machines (JVMs)

JVMIId Identifier Heap Max Description
00001 18754508 1M 67 J2RE 1.4.2 IBM z/OS Persistent Reusable VM
build cm142-20060824 (SR6)

Observed Java Packages

PkgId Package Name
00001 java/util/Zip
00002 java/lang
00003 java/util/jar
00004 sun/misc
00005 java/security
00006 java/net
00007 java/io
00008 com/ibm/jvm/io

Observed Java Classes

ClsId PkgId Class Name
00001 00002 Object
00002 00001 ZipFile
00003 00003 JarFile
00004 00004 URLClassPath$Loader
00005 00004 URLClassPath$JarLoader
00006 00004 URLClassPath$3

Observed Java Methods

MthId ClsId Method Name
00001 00002 open
00002 00002 <init>
00003 00003 <init>
00004 00003 <init>
00005 00005 getJarFile
00006 00005 <init>
00007 00006 run
00008 00007 doPrivileged1
```

J04 - Java CPU usage by package

Usage

Use this report to see how CPU time was consumed by execution of Java programs in each unique package. The unexpanded report shows one or more lines for each Java package in which execution was observed.

You can further expand each line item to show classes within the package, then methods within the class, then source lines within the method.

Quantification

Each report line quantifies time measured as a percentage of total time, the percentage represents the ratio of the number of CPU active measurements in the indicated Java object to the total number of CPU active observations.

Detail line hierarchy

An unexpanded report shows a line for each Java Package. The name field shows a sequence number assigned to each unique Package. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

Level 1 Java Package
Level 2 Java Class
Level 3 Java Method
Level 4 Java Line Number

...

Detail line descriptions

Java package detail line

This is the first-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| JavaID | A unique sequence number is assigned to each observed Java Package and is displayed in this column. |
| Pkg/Cls/Mthd | The name of a Java Package. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java class detail line

This is the second-level detail line.

| Under Heading | This is Displayed |
|-----------------|--|
| JavaID | A unique sequence number assigned to each observed Java class is displayed in this column. |
| Pkg/Cls/Mthd | The name of a Java class. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java method detail line

This is the third-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| JavaID | A unique sequence number assigned to each observed Java Method is displayed in this column. |
| Pkg/Cls/Mthd | The name of a Java method. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java line number

This is the fourth-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| JavaID | The line number of a Java source statement. |
| Pkg/Cls/Mthd | The line number of a Java source statement or "unknown" if the line number could not be determined. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Sample reports

A sample report is shown here. It has been fully expanded to show all four levels.

```

File View Navigate Help
-----
J04: Java CPU Usage by Package (0116/JVMTST01) Row 00001 of 00276
Command ==> _____ Scroll ==> CSR

JavaId Pkg/Cls/Mthd Percent of CPU Time * 10.00% ±3.1%
*....1....2....3....4....5....6....7...
00002 java/lang 39.52 =====
→ 00104 StrictMath 20.05 =====
  → 00228 log 10.52 =====
    → 00000 line # unknown 10.52 =====
  → 00226 sqrt 9.53 =====
    → 00000 line # unknown 9.53 =====
→ 00029 Math 15.83 =====
  → 00219 log 10.71 =====
    → 02290 line # 2290 9.04 =====
    → 00000 line # unknown 1.67 =
  → 00227 sqrt 5.01 ===
    → 02312 line # 2312 4.12 ==
    → 00000 line # unknown 0.88
  → 00048 max 0.09
    → 02760 line # 2760 0.09
  
```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|-------------------------------------|-----------------------------------|
| ? | Package, Class, Method, line number | Display context help information. |
| ++ | Package, Class, Method, line number | Show additional details. |
| + | Package, Class, Method | Expand to reveal next level. |
| - | Package, Class, Method | Collapse to hide next level. |

on headings

| Cmd | When Applied To Object | Action |
|-----|---------------------------------------|------------------------------------|
| ? | JavaId, Pkg/Cls/Mthd, Percent of Time | Display context help information. |
| + | JavaId | Expand to reveal all entries. |
| + | Pkg/Cls/Mthd | Expand description field size. |
| + | Percent of Time | Zoom in scale. |
| - | JavaId | Collapse to show only first level. |
| - | Pkg/Cls/Mthd | Reduce description field size. |
| - | Percent of Time | Zoom out scale. |
| SV | JavaId | Sort next level by value. |
| SN | JavaId | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on a Java class will cause this detail window to appear.

```
File View Navigate Help
+-----+
+----- The following report line was selected -----+
| -> 00104      StrictMath      20.05 ===== |
+-----+

Calculation Details
Application code CPU measurements      204
Total CPU measurements                  1,017
Percent of total                        20.05%

Class name:
  StrictMath

Package Name :
  Java/lang
```

Note: If you have Java source program mapping information specified, this detail window will display the Java source when invoked from a Java line number object.

J05 - Java CPU usage by class

Usage

Use this report to see how CPU time was consumed by execution of Java programs in each unique class. The unexpanded report shows one or more lines for each Java class in which execution was observed.

Note: The class name is implicitly qualified by the package name, which can be seen in the detail window for the class.

You can further expand each line item to show methods within the class, then source lines within the method.

Quantification

Each report line quantifies time measured as a percentage of total time, the percentage represents the ratio of the number of CPU active measurements in the indicated Java object to the total number of CPU active observations.

Detail line hierarchy

An unexpanded report shows a line for each Java class. The name field shows a sequence number assigned to each unique class. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

- Level 1** Java Class
- Level 2** Java Method
- Level 3** Java Line Number

Detail line descriptions

Java class detail line

This is the first-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| JavaID | A unique sequence number is assigned to each observed Java class and is displayed in this column. |
| Class/Method | The name of a Java class. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java method detail line

This is the second-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| JavaID | A unique sequence number assigned to each observed Java method is displayed in this column. |
| Class/Method | The name of a Java method. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java line number

This is the third-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| JavaID | The line number of a Java source statement. |
| Class/Method | The line number of a Java source statement or “unknown” if the line number could not be determined. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Sample reports

A sample report is shown here. It has been expanded to the second level.

```

File View Navigate Help
-----
J05: Java CPU Usage by Class (0116/JVMTST01) Row 00001 of 00186
Command ==> _____ Scroll ==> CSR

JavaId Class/Method Percent of CPU Time* 10.00% ±3.1%
*....1....2....3....4....5....6....7...
00102 Burner 32.15 =====
→ 00220 calc 27.72 =====
→ 00221 baby 4.42 ==

00104 StrictMath 20.05 =====
→ 00228 log 10.52 =====
→ 00226 sqrt 9.53 =====

00029 Math 15.83 =====
→ 00219 log 10.71 =====
→ 00227 sqrt 5.01 ===
→ 00048 max 0.09

00019 JarFile 1.37 =
→ 00037 hasClassPathAttribute 0.98
→ 00085 getManifest 0.19
→ 00114 initializeVerifier 0.09
→ 00025 getJarEntry 0.09

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|----------------------------|-----------------------------------|
| ? | Class, Method, line number | Display context help information. |
| ++ | Class, Method, line number | Show additional details. |
| + | Class, Method | Expand to reveal next level. |
| - | Class, Method | Collapse to hide next level. |

on headings

| Cmd | When Applied To Object | Action |
|-----|---------------------------------------|------------------------------------|
| ? | JavaId, Class/Method, Percent of Time | Display context help information. |
| + | JavaId | Expand to reveal all entries. |
| + | Class/Method | Expand description field size. |
| + | Percent of Time | Zoom in scale. |
| - | JavaId | Collapse to show only first level. |
| - | Class/Method | Reduce description field size. |
| - | Percent of Time | Zoom out scale. |
| SV | JavaId | Sort next level by value. |
| SN | JavaId | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on a Java method will cause this detail window to appear.

```
File View Navigate Help
+-----+
+----- The following report line was selected -----+
| -> 00104  calc                27.72 ===== |
+-----+

Calculation Details
Application code CPU measurements      282
Total CPU measurements                 1,017
Percent of total                       27.72%

Method Name:
  calc

Method Descriptor:
  (I)D

Method Signature:
  calc(int) double

Class Name:
  Burner

Package Name:
  com/basamps/sample
```

Note: If you have Java source program mapping information specified, this detail window will display the Java source when invoked from a Java line number object.

J06 - Java CPU usage by method

Usage

Use this report to see how CPU time was consumed by execution of Java programs in each unique method. The unexpanded report shows one or more lines for each Java method in which execution was observed.

Note: The method name is implicitly qualified by its package and class names, which can be seen in the detail window for the method.

You can further expand each line item to show methods within the class, then source lines within the method.

Quantification

Each report line quantifies time measured as a percentage of total time, the percentage represents the ratio of the number of CPU active measurements in the indicated Java object to the total number of CPU active observations.

Detail line hierarchy

An unexpanded report shows a line for each Java method. The name field shows a sequence number assigned to each unique method. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

Level 1 Java Method
Level 2 Java Line Number

Detail line descriptions

Java method detail line

This is the first-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| MthId | A unique sequence number assigned to each observed Java method is displayed in this column. |
| Method | The name of a Java method. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java line number

This is the second-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| MthId | The line number of a Java source statement. |
| Method | The line number of a Java source statement or "unknown" if the line number could not be determined. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Sample reports

A sample report is shown here. It has been expanded to the second level.

```

File View Navigate Help
-----
J06: Java CPU Usage by Method (0116/JVMST01) Row 00001 of 00186
Command ==> _____ Scroll ==> CSR

MthId Method Percent of CPU Time * 10.00% ±3.1%
*....1....2....3....4....5....6....7...
00220 calc 27.72 =====
→ 00029 line # 29 25.46 =====
→ 00024 line # 24 1.37
→ 00036 line # 36 0.29
→ 00027 line # 27 0.19
→ 00026 line # 26 0.19
→ 00000 line # unknown 0.19

00219 log 10.71 =====
→ 02290 line # 2290 9.04 =====
→ 00000 line # unknown 1.67 =

00228 log 10.52 =====
→ 00000 line # unknown 10.52 =====

00226 sqrt 9.53 =====
→ 00000 line # unknown 9.53 =====

00227 sqrt 5.01 =====
→ 02312 line # 2312 4.12 ===
→ 00000 line # unknown 0.88

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Method, line number | Display context help information. |
| ++ | Method, line number | Show additional details. |
| + | Method | Expand to reveal next level. |
| - | Method | Collapse to hide next level. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | MthId, Method, Percent of Time | Display context help information. |
| + | MthId | Expand to reveal all entries. |
| + | Method | Expand description field size. |
| + | Percent of Time | Zoom in scale. |
| - | MthId | Collapse to show only first level. |
| - | Method | Reduce description field size. |
| - | Percent of Time | Zoom out scale. |
| SV | MthId | Sort next level by value. |
| SN | MthId | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on a Java method will cause this detail window to appear.

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| -> 00220  calc                27.72 ===== |
+-----+

Calculation Details
Application code CPU measurements      282
Total CPU measurements                1,017
Percent of total                      27.72%

Method Name:
  calc

Method Descriptor:
  (I)D

Method Signature:
  calc(int) double

Class Name:
  Burner

Package Name:
  com/basamps/sample

```

Note: If you have Java source program mapping information specified, this detail window will display the Java source when invoked from a Java line number object.

J07 - Java CPU usage by call path

Usage

Use this report to see how CPU time was consumed by execution of Java programs in each unique call path. The unexpanded report shows one or more lines for each Java method in which execution was observed. Execution in a method is quantified and reported separately for each different call path. (A call path represents a path of control in the form: A calls B calls C calls D ... etc.)

By expanding the first-level method line you can see a line for each of the calling methods in the path of control. These are shown in reverse order of control. In the case of A calls B calls C calls D, method D (in which execution was observed) is reported in the first-level line and the second-level lines show C then B then A.

Quantification

The first-level report line quantifies CPU time measured as a percentage of total time, the percentage represents the ratio of the number of CPU active measurements in the indicated Java object to the total number of CPU active observations.

Detail line hierarchy

An unexpanded report shows a line for each Java method line. The name field shows a sequence number assigned to each unique method line. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

Level 1 Java Method
 Level 2 Calling Java Method Line

Detail line descriptions

Java method detail line

This is the first-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| MthId | A unique sequence number assigned to each observed Java method is displayed in this column. |
| Method | The name of a Java method. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java line number

This is the second-level detail line.

| Under Heading | This is Displayed |
|---------------|--|
| MthId | A unique sequence number assigned to each observed Java method. |
| Method | The line number of the statement that invoked the next method in the call path and the name of the method. |

Sample reports

A sample report is shown here. It has been expanded to the second level.

```

File View Navigate Help
-----
J07: Java CPU Usage by Call Path (0116/JVMTST01)          Row 00001 of 01831
Command ==>>> _____ Scroll ==>>> CSR

MthId  Method                                     Percent of CPU Time * 10.00%  ±3.1%
      *....1....2....3....4....5....6....7...
00220  calc                                       25.36 =====
  → 00221  line 16 baby
  → 00218  line 25 main

00228  log                                       10.42 =====
  → 00219  line 2290 log
  → 00220  line 29 calc
  → 00221  line 16 baby
  → 00218  line 25 main

00226  sqrt                                       9.43 =====
  → 00227  line 2312 sqrt
  → 00220  line 29 calc
  → 00221  line 16 baby
  → 00218  line 25 main

00219  log                                       8.94 =====
  → 00220  line 29 calc
  → 00221  line 16 baby
  → 00218  line 25 main
  
```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Method, line number | Display context help information. |
| ++ | Method, line number | Show additional details. |
| + | Method | Expand to reveal next level. |
| - | Method | Collapse to hide next level. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | MthId, Method, Percent of Time | Display context help information. |
| + | MthId | Expand to reveal all entries. |
| + | Method | Expand description field size. |
| + | Percent of Time | Zoom in scale. |
| - | MthId | Collapse to show only first level. |
| - | Method | Reduce description field size. |
| - | Percent of Time | Zoom out scale. |
| SV | MthId | Sort next level by value. |
| SN | MthId | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on a Java method will cause this detail window to appear.


```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| -> 00220  calc                27.72 ===== |
+-----+

Calculation Details
Application code CPU measurements      282
Total CPU measurements                 1,017
Percent of total                       27.72%

Method Name:
calc

Method Descriptor:
(I)D

Method Signature:
calc(int) double

Class Name:
Burner

Package Name:
com/basamps/sample

```

J09 - Java service time by package

Usage

Use this report to see how service time was consumed by execution of Java programs in each unique package. The unexpanded report shows one or more lines for each Java package in which execution was observed.

You can further expand each line item to show classes within the package, then methods within the class, then source lines within the method.

Quantification

Each report line quantifies service time measured as a percentage of total time. The percentage represents the ratio of the number of samples in which execution of the indicated Java object (package, class, method or line) was in flight to the total number of samples. An observation is counted as execution regardless of the CPU state (active, WAIT, or queued).

Detail line hierarchy

An unexpanded report shows a line for each Java method line. The name field shows a sequence number assigned to each unique method line. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

- Level 1** Java Package
- Level 2** Java Class
- Level 3** Java Method
- Level 4** Java Line Number

Detail line descriptions

Java package detail line

This is the first-level detail line.

| Under Heading | This is Displayed |
|-----------------|--|
| JavaID | A unique sequence number assigned to each observed Java package and is displayed in this column. |
| Pkg/Cls/Mthd | The name of a Java package. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java class detail line

This is the second-level detail line.

| Under Heading | This is Displayed |
|-----------------|--|
| JavaID | A unique sequence number assigned to each observed Java class is displayed in this column. |
| Pkg/Cls/Mthd | The name of a Java class. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java method detail line

This is the third-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| JavaID | A unique sequence number assigned to each observed Java method is displayed in this column. |
| Pkg/Cls/Mthd | The name of a Java method. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java line number

This is the fourth-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| JavaID | The line number of a Java source statement. |
| Pkg/Cls/Mthd | The line number of a Java source statement or "unknown" if the line number could not be determined. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Sample reports

A sample report is shown here. It has been expanded to the second level.

```

File View Navigate Help
-----
J09: Java Service Time by Package (0116/JVMTST01)          Row 00001 of 01831
Command ==>> _____ Scroll ==>> CSR

JavaId  Pkg/Cls/Mthd                Percent of Time * 10.00%  ±2.4%
*....1....2....3....4....5....6....7...
00002  java/lang                    33.01 =====
→ 00104  StrictMath                   16.50 =====
→ 00029  Math                         12.87 =====
→ 00005  ClassLoader                  1.01 =
→ 00010  String                       0.65
→ 00017  ClassLoader$NativeLibrar    0.47
→ 00040  StringBuffer                  0.29
→ 00096  Thread                       0.29
→ 00021  Runtime                      0.11
→ 00022  System                       0.11
→ 00077  Character                    0.11
→ 00057  Class                        0.11
→ 00097  Shutdown                     0.11
→ 00001  Object                       0.05
→ 00047  StringCoding                 0.05
→ 00049  StringCoding$DecoderCach    0.05
→ 00079  Throwable                    0.05
→ 00103  FloatingDecimal              0.05

00020  com/baseamps/sample          28.84 =====
→ 00102  Burner                       28.84 =====

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|-------------------------------------|-----------------------------------|
| ? | Package, Class, Method, line number | Display context help information. |
| ++ | Package, Class, Method, line number | Show additional details. |
| + | Package, Class, Method | Expand to reveal next level. |
| - | Package, Class, Method | Collapse to hide next level. |

on headings

| Cmd | When Applied To Object | Action |
|-----|---------------------------------------|------------------------------------|
| ? | JavaId, Pkg/Cls/Mthd, Percent of Time | Display context help information. |
| + | JavaId | Expand to reveal all entries. |
| + | Pkg/Cls/Mthd | Expand description field size. |
| + | Percent of Time | Zoom in scale. |
| - | JavaId | Collapse to show only first level. |
| - | Pkg/Cls/Mthd | Reduce description field size. |
| - | Percent of Time | Zoom out scale. |
| SV | JavaId | Sort next level by value. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|--------------------------|
| SN | JavaId | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on a Java class will cause this detail window to appear.

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| -> 00104  StrictMath          16.50 ===== |
+-----+

Calculation Details
Application code CPU measurements      277
Total measurements                    1,678
Percent of total                      16.50%

Class Name:
  StrictMath

Package Name:
  java/lang

```

Note: If you have Java source program mapping information specified, this detail window will display the Java source when invoked from a Java line number object.

J10 - Java service time by class

Usage

Use this report to see how service time was consumed by execution of Java programs in each unique class. The unexpanded report shows one or more lines for each Java class in which execution was observed.

Note: The class name is implicitly qualified by the package name, which can be seen in the detail window for the class.

You can further expand each line item to show methods within the class, then source lines within the method.

Quantification

Each report line quantifies service time measured as a percentage of total time. The percentage represents the ratio of the number of samples in which execution of the indicated Java object (package, class, method or line) was in flight to the total number of samples. An observation is counted as execution regardless of the CPU state (active, WAIT, or queued).

Detail line hierarchy

An unexpanded report shows a line for each Java class. The name field shows a sequence number assigned to each unique class. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

Level 1 Java Class
 Level 2 Java Method
 Level 3 Java Line Number

Detail line descriptions

Java class detail line

This is the first-level detail line.

| Under Heading | This is Displayed |
|-----------------|--|
| JavaID | A unique sequence number assigned to each observed Java class and is displayed in this column. |
| Class/Method | The name of a Java class. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java method detail line

This is the second-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| JavaID | A unique sequence number assigned to each observed Java method is displayed in this column. |
| Class/Method | The name of a Java method. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java line number

This is the third-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| JavaID | The line number of a Java source statement. |
| Class/Method | The line number of a Java source statement or “unknown” if the line number could not be determined. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Sample reports

A sample report is shown here. It has been expanded to the second level.

```

File View Navigate Help
-----
J10: Java Service Time by Class (0116/JVMTST01) Row 00001 of 00208
Command ==>> _____ Scroll ==>> CSR

JavaId Class/Method Percent of Time * 10.00% ±2.4%
*....1....2....3....4....5....6....7...
00102 Burner 28.84 =====
→ 00220 calc 23.95 =====
→ 00221 baby 4.88 ==

00104 StrictMath 16.50 =====
→ 00226 sqrt 8.28 ===
→ 00228 log 8.22 ===

00029 Math 12.87 =====
→ 00219 log 8.52 ===
→ 00227 sqrt 4.23 ==
→ 00048 max 0.11

00018 ZipFile 1.54 =
→ 00049 getEntry 0.77
→ 00062 open 0.59
→ 00039 getInflater 0.05
→ 00054 read 0.05
→ 00035 getEntry 0.05

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|----------------------------|-----------------------------------|
| ? | Class, Method, line number | Display context help information. |
| ++ | Class, Method, line number | Show additional details. |
| + | Class, Method | Expand to reveal next level. |
| - | Class, Method | Collapse to hide next level. |

on headings

| Cmd | When Applied To Object | Action |
|-----|---------------------------------------|------------------------------------|
| ? | JavaId, Class/Method, Percent of Time | Display context help information. |
| + | JavaId | Expand to reveal all entries. |
| + | Class/Method | Expand description field size. |
| + | Percent of Time | Zoom in scale. |
| - | JavaId | Collapse to show only first level. |
| - | Class/Method | Reduce description field size. |
| - | Percent of Time | Zoom out scale. |
| SV | JavaId | Sort next level by value. |
| SN | JavaId | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on a Java method will cause this detail window to appear.

```
File View Navigate Help
+-----+
+----- The following report line was selected -----+
| -> 00220  calc                23.95 ===== |
+-----+

Calculation Details
Application code activity measurements      402
Total measurements                          1,678
Percent of total                            23.95%

Method Name:
calc

Method Descriptor:
(I)D

Method Signature:
calc(int) double

Class Name:
Burner

Package Name:
com/basamps/sample
```

Note: If you have Java source program mapping information specified, this detail window will display the Java source when invoked from a Java line number object.

J11 - Java service time by method

Usage

Use this report to see how service time was consumed by execution of Java programs in each unique method. The unexpanded report shows one or more lines for each Java method in which execution was observed.

Note: The method name is implicitly qualified by its package and class names, which can be seen in the detail window for the method.

You can further expand each line item to show methods within the class, then source lines within the method.

Quantification

Each report line quantifies service time measured as a percentage of total time. The percentage represents the ratio of the number of samples in which execution of the indicated Java object (package, class, method or line) was in flight to the total number of samples. An observation is counted as execution regardless of the CPU state (active, WAIT, or queued).

Detail line hierarchy

An unexpanded report shows a line for each Java method. The name field shows a sequence number assigned to each unique method. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

Level 1 Java Method
Level 2 Java Line Number

Detail line descriptions

Java method detail line

This is the first-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| MthId | A unique sequence number assigned to each observed Java method is displayed in this column. |
| Method | The name of a Java method. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java line number

This is the second-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| MthId | The line number of a Java source statement. |
| Method | The line number of a Java source statement or "unknown" if the line number could not be determined. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java line number

This is the third-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| JavaID | The line number of a Java source statement. |
| Class/Method | The line number of a Java source statement or "unknown" if the line number could not be determined. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Sample reports

A sample report is shown here. It has been expanded to the second level.

```

File View Navigate Help
-----
J11: Java Service Time by Method (0116/JVMTST01)          Row 00001 of 00313
Command ==>> _____ Scroll ==>> CSR

JavaId Class/Method          Percent of CPU Time * 10.00% ±2.4%
*....1....2....3....4....5....6....7...
00220  calc                    23.95 =====
→ 00029  line # 29                21.51 =====
→ 00024  line # 24                1.31 =
→ 00036  line # 36                0.41
→ 00027  line # 27                0.35
→ 00000  line # unknown          0.23
→ 00026  line # 26                0.11

00219  log                      8.52 =====
→ 02290  line # 2290            6.19 =====
→ 00000  line # unknown          2.32 =

00226  sqrt                    8.28 =====
→ 00000  line # unknown          8.28 =====

00228  log                      8.22 =====
→ 00000  line # unknown          8.22 =====

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Method, line number | Display context help information. |
| ++ | Method, line number | Show additional details. |
| + | Method | Expand to reveal next level. |
| - | Method | Collapse to hide next level. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | MthId, Method, Percent of Time | Display context help information. |
| + | MthId | Expand to reveal all entries. |
| + | Method | Expand description field size. |
| + | Percent of Time | Zoom in scale. |
| - | MthId | Collapse to show only first level. |
| - | Method | Reduce description field size. |
| - | Percent of Time | Zoom out scale. |
| SV | MthId | Sort next level by value. |
| SN | MthId | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on a Java method will cause this detail window to appear.

```
File View Navigate Help
+-----+
+----- The following report line was selected -----+
| -> 00220  calc                23.95 ===== |
+-----+

Calculation Details
Application code activity measurements      402
Total measurements                          1,678
Percent of total                            23.95%

Method Name:
calc

Method Descriptor:
(I)D

Method Signature:
calc(int) double

Class Name:
Burner

Package Name:
com/basamps/sample
```

Note: If you have Java source program mapping information specified, this detail window will display the Java source when invoked from a Java line number object.

J12 - Java service time by call path

Usage

Use this report to see how service time was consumed by execution of Java programs in each unique call path. The unexpanded report shows one or more lines for each Java method in which execution was observed. Execution in a method is quantified and reported separately for each call path. (A call path represents a path of control in the form: A calls B calls C calls D, etc.)

By expanding the first-level method line you can see a line for each of the calling methods in the path of control. These are shown in reverse order of control. In the case of A calls B calls C calls D, method D (in which execution was observed) is reported in the first-level line and the second-level lines show C then B then A.

Quantification

The first-level report line quantifies service time measured as a percentage of total time. The percentage represents the ratio of the number of samples in which

execution of the indicated Java object (method or line) was in flight to the total number of samples. An observation is counted as execution regardless of the CPU state (active, WAIT, or queued).

Detail line hierarchy

An unexpanded report shows a line for each Java method line. The name field shows a sequence number assigned to each unique method line. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

Level 1 Java Method
Level 2 Calling Java Method Line

Detail line descriptions

Java method detail line

This is the first-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| MthId | A unique sequence number assigned to each observed Java method is displayed in this column. |
| Method | The name of a Java method. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java line number

This is the second-level detail line.

| Under Heading | This is Displayed |
|-----------------|--|
| MthId | A unique sequence number assigned to each observed Java method. |
| Method | The line number of the statement that invoked the next method in the call path and the name of the method. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Sample reports

A sample report is shown here. It has been expanded to the second level.

```

File View Navigate Help
-----
J12: Java Service Time by Call Path (0116/JVMTST01)          Row 00001 of 02766
Command ==>> _____ Scroll ==>> CSR

MthId  Method                                Percent of Time * 10.00% ±2.4%
*....1....2....3....4....5....6....7...
00220  calc                                21.45 =====
→ 00221  line 16 baby
→ 00218  line 25 main

00226  sqrt                                8.22 ====
→ 00227  line 2312 sqrt
→ 00220  line 29 calc
→ 00221  line 16 baby
→ 00218  line 25 main

00228  log                                 8.16 ====
→ 00219  line 2290 log
→ 00220  line 29 calc
→ 00221  line 16 baby
→ 00218  line 25 main

00219  log                                 6.13 ===
→ 00220  line 29 calc
→ 00221  line 16 baby
→ 00218  line 25 main

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Method, line number | Display context help information. |
| ++ | Method, line number | Show additional details. |
| + | Method | Expand to reveal next level. |
| - | Method | Collapse to hide next level. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | MthId, Method, Percent of Time | Display context help information. |
| + | MthId | Expand to reveal all entries. |
| + | Method | Expand description field size. |
| + | Percent of Time | Zoom in scale. |
| - | MthId | Collapse to show only first level. |
| - | Method | Reduce description field size. |
| - | Percent of Time | Zoom out scale. |
| SV | MthId | Sort next level by value. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|--------------------------|
| SN | MthId | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on a line number will cause this detail window to appear.

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| -> 00218   line 25 main                               |
+-----+

Calculation Details
Application code activity measurements           1
Total measurements                             1,678
Percent of total                               0.05%

Method Name:
main[Ljava/lang/String;)V

Method Descriptor:
(I)D

Method Signature:
main(java.lang.String[]) void

Class Name:
Burner3Test

```

J14 - Java wait time by package

Usage

Use this report to see how much WAIT time was measured during execution of Java programs in each unique package. The unexpanded report shows one or more lines for each Java package in which execution was observed.

You can further expand each line item to show classes within the package, then methods within the class, then source lines within the method.

Quantification

Each report line quantifies WAIT time measured as a percentage of total time. The percentage represents the ratio of the number of samples in which execution of the indicated Java object (package, class, method or line) was in a wait state, to the total number of samples.

Detail line hierarchy

An unexpanded report shows a line for each Java package. The name field shows a sequence number assigned to each unique package. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

- Level 1 Java Package
- Level 2 Java Class
- Level 3 Java Method
- Level 4 Java Line Number

Detail line descriptions

Java package detail line

This is the first-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| JavaID | A unique sequence number is assigned to each observed Java package and is displayed in this column. |
| Pkg/Cls/Mthd | The name of a Java package. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java class detail line

This is the second-level detail line.

| Under Heading | This is Displayed |
|-----------------|--|
| JavaID | A unique sequence number assigned to each observed Java class is displayed in this column. |
| Pkg/Cls/Mthd | The name of a Java Class. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java method detail line

This is the third-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| JavaID | The line number of a Java source statement. |
| Pkg/Cls/Mthd | The name of a Java method. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java line number

This is the fourth-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| JavaID | The line number of a Java source statement. |
| Pkg/Cls/Mthd | The line number of a Java source statement or "unknown" if the line number could not be determined. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Sample reports

A sample report is shown here. It has been expanded to the second level.

```

File View Navigate Help
-----
J14: Java Wait Time by Package (0116/JVMTST01) Row 00001 of 00022
Command ==>> _____ Scroll ==>> CSR

JavaId Pkg/Cls/Mthd Percent of Time * 2.50% ±2.4%
*....1....2....3....4....5....6....7...
00006 java/util/zip 0.89 ==
→ 00018 ZipFile 0.89 ==

00002 java/lang 0.77 ==
→ 00005 ClassLoader 0.35 =
→ 00096 Thread 0.23
→ 00017 ClassLoader$NativeLibrar 0.05
→ 00057 Class 0.05
→ 00021 Runtime 0.05

00018 com/dovetail/jzos 0.23
→ 00078 ZFile 0.23

00005 java/io 0.17
→ 00098 FileInputStream 0.11
→ 00012 UnixFileSystem 0.05

00007 java/util/jar 0.05
→ 00019 JarFile 0.05

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|-------------------------------------|-----------------------------------|
| ? | Package, Class, Method, line number | Display context help information. |
| ++ | Package, Class, Method, line number | Show additional details. |
| + | Package, Class, Method | Expand to reveal next level. |
| - | Package, Class, Method | Collapse to hide next level. |

on headings

| Cmd | When Applied To Object | Action |
|-----|---------------------------------------|------------------------------------|
| ? | JavaId, Pkg/Cls/Mthd, Percent of Time | Display context help information. |
| + | JavaId | Expand to reveal all entries. |
| + | Pkg/Cls/Mthd | Expand description field size. |
| + | Percent of Time | Zoom in scale. |
| - | JavaId | Collapse to show only first level. |
| - | Pkg/Cls/Mthd | Reduce description field size. |
| - | Percent of Time | Zoom out scale. |
| SV | JavaId | Sort next level by value. |
| SN | JavaId | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on a Java class will cause this detail window to appear.

```
File View Navigate Help
+-----+
+----- The following report line was selected -----+
| -> 00018  ZipFile                                0.89 == |
+-----+

Calculation Details
Application code wait time measurements          15
Total measurements                               1,678
Percent of total                                 0.89%

Class Name:
ZipFile

Package Name:
java/util/zip
```

Note: If you have Java source program mapping information specified, this detail window will display the Java source when invoked from a Java line number object.

J15 - Java wait time by class

Usage

Use this report to see how much WAIT time was measured during execution of Java programs in each unique class. The unexpanded report shows one or more lines for each Java class in which execution was observed.

Note: The class name is implicitly qualified by the package name, which can be seen in the detail window for the class.

You can further expand each line item to show methods within the class, then source lines within the method.

Quantification

Each report line quantifies WAIT time measured as a percentage of total time. The percentage represents the ratio of the number of samples in which execution of the indicated Java object (class, method or line) was in a wait state, to the total number of samples.

Detail line hierarchy

An unexpanded report shows a line for each Java class. The name field shows a sequence number assigned to each unique class. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

- Level 1 Java Class
- Level 2 Java Method
- Level 3 Java Line Number

Detail line descriptions

Java class detail line

This is the first-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| JavaID | A unique sequence number is assigned to each observed Java class and is displayed in this column. |
| Class/Method | The name of a Java class. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java method detail line

This is the second-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| JavaID | A unique sequence number assigned to each observed Java method is displayed in this column. |
| Class/Method | The name of a Java method. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java line number

This is the third-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| JavaID | The line number of a Java source statement. |
| Class/Method | The line number of a Java source statement or “unknown” if the line number could not be determined. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Sample reports

A sample report is shown here. It has been expanded to the second level.

| JavaId | Class/Method | Percent of Time * 2.50% | ±2.4% |
|---------|-----------------------|-------------------------|-------|
| 00018 | ZipFile | 0.89 | == |
| → 00049 | getEntry | 0.65 | = |
| → 00062 | open | 0.23 | |
| 00005 | ClassLoader | 0.35 | = |
| → 00139 | findBootstrapClass | 0.35 | = |
| 00029 | ZFile | 0.23 | |
| → 00173 | fopen | 0.23 | |
| 00096 | Thread | 0.23 | |
| → 00203 | start | 0.23 | |
| 00098 | FileInputStream | 0.11 | |
| → 00207 | readBytes | 0.11 | |
| 00019 | JarFile | 0.05 | |
| → 00037 | hasClassPathAttribute | 0.05 | |

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|----------------------------|-----------------------------------|
| ? | Class, Method, line number | Display context help information. |
| ++ | Class, Method, line number | Show additional details. |
| + | Class, Method | Expand to reveal next level. |
| - | Class, Method | Collapse to hide next level. |

on headings

| Cmd | When Applied To Object | Action |
|-----|---------------------------------------|------------------------------------|
| ? | JavaId, Class/Method, Percent of Time | Display context help information. |
| + | JavaId | Expand to reveal all entries. |
| + | Class/Method | Expand description field size. |
| + | Percent of Time | Zoom in scale. |
| - | JavaId | Collapse to show only first level. |
| - | Class/Method | Reduce description field size. |
| - | Percent of Time | Zoom out scale. |
| SV | JavaId | Sort next level by value. |
| SN | JavaId | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on a Java method will cause this detail window to appear.

```
File View Navigate Help
+-----+
+----- The following report line was selected -----+
| -> 00049  getEntry                                0.65 |
+-----+

Calculation Details
Application code wait time measurements      11
Total measurements                          1,678
Percent of total                             0.65%

Method Name:
getEntry

Method Descriptor:
(JLjava/lang/String;)J

Method Signature:
getEntry(long, java.lang.String) long

Class Name:
ZipFile

Package Name:
java/util/zip
```

Note: If you have Java source program mapping information specified, this detail window will display the Java source when invoked from a Java line number object.

J16 - Java wait time by method

Usage

Use this report to see how much WAIT time was measured during execution of Java programs in each unique method. The unexpanded report shows one or more lines for each Java method in which execution was observed.

Note: The method name is implicitly qualified by its package and class names, which can be seen in the detail window for the method.

You can further expand each line item to show methods within the class, then source lines within the method.

Quantification

Each report line quantifies WAIT time measured as a percentage of total time. The percentage represents the ratio of the number of samples in which execution of the indicated Java object (method or line) was in a wait state, to the total number of samples.

Detail line hierarchy

An unexpanded report shows a line for each Java Method. The name field shows a sequence number assigned to each unique Method. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

Level 1 Java Method
Level 2 Java Line Number

Detail line descriptions

Java method detail line

This is the first-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| MthId | A unique sequence number assigned to each observed Java method is displayed in this column. |
| Method | The name of a Java method. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java line number

This is the second-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| MthId | The line number of a Java source statement. |
| Method | The line number of a Java source statement or “unknown” if the line number could not be determined. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Sample reports

A sample report is shown here. It has been expanded to the second level.

```

File View Navigate Help
-----
J16: Java Wait Time by Method (0116/JVMTST01) Row 00001 of 00035
Command ==> _____ Scroll ==> CSR

JavaId Class/Method Percent of CPU Time * 2.50% ±2.4%
*.....1.....2.....3.....4.....5.....6.....7...
00049 getEntry 0.65 =
→ 00000 line # unknown 0.65 =

00139 findBootstrapClass 0.35 =
→ 00000 line # unknown 0.35 =

00062 open 0.23
→ 00000 line # unknown 0.23

00173 fopen 0.23
→ 00000 line # unknown 0.23

00203 start 0.23
→ 00000 line # unknown 0.23

00207 readBytes 0.11
→ 00000 line # unknown 0.11

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Method, line number | Display context help information. |
| ++ | Method, line number | Show additional details. |
| + | Method | Expand to reveal next level. |
| - | Method | Collapse to hide next level. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | MthId, Method, Percent of Time | Display context help information. |
| + | MthId | Expand to reveal all entries. |
| + | Method | Expand description field size. |
| + | Percent of Time | Zoom in scale. |
| - | MthId | Collapse to show only first level. |
| - | Method | Reduce description field size. |
| - | Percent of Time | Zoom out scale. |
| SV | MthId | Sort next level by value. |
| SN | MthId | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on a Java method will cause this detail window to appear.

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| -> 00049  getEntry          0.65 |
+-----+

Calculation Details
Application code wait time measurements      11
Total measurements                          1,678
Percent of total                            0.65%

Method Name:
getEntry

Method Descriptor:
(JLjava/lang/String;)J

Method Signature:
getEntry(long, java.lang.String) long

Class Name:
ZipFile

Package Name:
java/util/zip

```

Note: If you have Java source program mapping information specified, this detail window will display the Java source when invoked from a Java line number object.

J17 - Java wait time by call path

Usage

Use this report to see how much WAIT time was measured during execution of Java programs in each unique call path. The unexpanded report shows one or more lines for each Java method in which execution was observed. Execution in a method is quantified and reported separately for each call path. (A call path represents a path of control in the form of: A calls B calls C calls D, etc.)

By expanding the first-level method line you can see a line for each of the calling methods in the path of control. These are shown in reverse order of control. In the case of A calls B calls C calls D, method D (in which execution was observed) is reported in the first-level line and the second-level lines show C then B then A.

Quantification

The first-level report line quantifies WAIT time measured as a percentage of total time, the percentage represents the ratio of the number of samples in which execution of the indicated Java object (method or line) was in a wait state, to the total number of samples.

Detail line hierarchy

An unexpanded report shows a line for each Java method line. The name field shows a sequence number assigned to each unique method line. You can expand each line to reveal additional hierarchical levels of detail. The hierarchy is illustrated here:

Level 1 Java Method
 Level 2 Calling Java Method Line

Detail line descriptions

Java method detail line

This is the first-level detail line.

| Under Heading | This is Displayed |
|-----------------|---|
| MthId | A unique sequence number assigned to each observed Java method is displayed in this column. |
| Method | The name of a Java method. |
| Percent of Time | The percentage of activity measured in the indicated Java object. |

Java line number

This is the second-level detail line.

| Under Heading | This is Displayed |
|---------------|--|
| MthId | A unique sequence number assigned to each observed Java method. |
| Method | The line number of the statement that invoked the next method in the call path and the name of the method. |

Sample reports

A sample report is shown here. It has been expanded to the second level.

```

File View Navigate Help
-----
J17: Java Wait Time by Call Path (0116/JVMTST01)          Row 00001 of 00158
Command ==>>> _____ Scroll ==>>> CSR

MthId  Method                                     Percent of Time * 2.50%  ±2.4%
      *.....1.....2.....3.....4.....5.....6.....7...
00049  getEntry                                   0.59 =
→ 00035  line 173 getEntry
→ 00036  line 257 getEntry
→ 00025  line 244 getJarEntry
→ 00037  line 483 hasClassPathAtt
→ 00038  line 29 jarFileHasClassP
→ 00028  line 889 getClassPath
→ 00002  line 351 getLoader
→ 00003  line 205 getResource
→ 00004  line 846 run
→ 00005  doPrivileged1
→ 00006  line 389 doPrivileged
→ 00007  line 371 findClass
→ 00008  line 572 loadClass
→ 00009  line 442 loadClass
→ 00010  line 504 loadClass

00139  findBootstrapClass                         0.29 =
→ 00140  line 1062 findBootstrapC
→ 00008  line 565 loadClass
  
```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Method, line number | Display context help information. |
| ++ | Method, line number | Show additional details. |
| + | Method | Expand to reveal next level. |
| - | Method | Collapse to hide next level. |

on headings

| Cmd | When Applied To Object | Action |
|-----|--------------------------------|------------------------------------|
| ? | MthId, Method, Percent of Time | Display context help information. |
| + | MthId | Expand to reveal all entries. |
| + | Method | Expand description field size. |
| + | Percent of Time | Zoom in scale. |
| - | MthId | Collapse to show only first level. |
| - | Method | Reduce description field size. |
| - | Percent of Time | Zoom out scale. |
| SV | MthId | Sort next level by value. |
| SN | MthId | Sort next level by name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on a Java method will cause this detail window to appear.


```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| -> 00049  getEntry          0.65 |
+-----+

Calculation Details
Application code wait time measurements      11
Total measurements                          1,678
Percent of total                             0.65%

Method Name:
  getEntry

Method Descriptor:
  (Ljava/lang/String;)J

Method Signature:
  getEntry(long, java.lang.String) long

Class Name:
  ZipFile

Package Name:
  java/util/zip

```

H01 - HFS Service Time by Path Name

Usage

Use this report to see how Service time was consumed by HFS file activity during the observation session. Each report line shows an HFS file, listed by path name, for which activity was observed. If HFS file activity was observed during a sample, but could not be attributed to a specific file, the activity is aggregated to a single report line with a path name of "unknown".

Quantification

Each report line quantifies Service time measured as a percentage of total time. The percentage represents the ratio of the number of samples in which an HFS call against the indicated HFS file was inflight to the total number of samples. An observation is counted as inflight regardless of the CPU state: Active, WAIT, or Queued.

Detail line descriptions

HFS File detail line

| Under Heading | This is Displayed |
|-----------------|--|
| FileId | A unique sequence number assigned to each HFS file. |
| Path Name | The HFS file path name. |
| Percent of Time | The percentage of activity measured in the indicated HFS file. |

Sample reports

A sample report is shown here.

```

File View Navigate Help
-----
H01: HFS Service Time by Path Name (8242/JVMTST01)          Row 00001 of 00070
Command ==>> _____ Scroll ==>> CSR

FileId Path Name Percent of Time * 10.00% ±1.0%
*....1....2....3....4....5....6..
00002 /dev/tty0001 70.36
00000 unknown 66.59
00001 /dev/tty0000 50.49
00063 /tmp/ofile.txt 13.28
00021 /Z18/usr/lpp/java/J1.4/lib/core. 1.59
00080 /Z18/usr/lpp/java/J1.4/lib/core. 1.18
00062 /u/zfs/ofile.txt 0.53
00041 /Z18/usr/lpp/java/J1.4/lib/ext/d 0.32
00032 /Z18/usr/lpp/java/J1.4/lib/ibmor 0.18
00075 /u/zfs/platz 0.18
00044 /Z18/usr/lpp/java/J1.4/lib/ext/i 0.16
00005 /dev/ptyp0001 0.15
00043 /Z18/usr/lpp/java/J1.4/lib/ext/i 0.15
00072 /u/zfs/platz 0.15
00070 /u/zfs/platz 0.14
00036 /u/zfs/platz 0.12

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | FileId | Display context help information. |
| ++ | FileId | Show additional details. |

on headings

| Cmd | When Applied To Heading | Action |
|-----|------------------------------------|-----------------------------------|
| ? | FileId, Path Name, Percent of Time | Display context help information. |
| + | Path Name | Expand description field size. |
| + | Percent of Time | Zoom in scale. |
| - | Path Name | Reduce description field size. |
| - | Percent of Time | Zoom out scale. |
| SV | FileId | Sort next level by value. |
| SN | FileId | Sort next level by FileId. |
| SP | FileId | Sort next level by Path Name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on a FileId will cause this detail window to appear.

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| 00002 /dev/tty001 70.36 |
+-----+

Calculation Details
HFS file measurements 7.036
Total measurements 10.000
Percent of total 70.36%

HFS File Information
Path name /dev/tty001
File type Character Special File Major 2 Minor 1
Opened 7:05:22.45 Friday Mar 16 2007
Device# 4
Serial# 17
Open Flags Read/Write Read_Only Write_Only
Not_a_controlling_terminal

```

SETUP options

The SETUP command displays the following options:

```
Minimum Percentage of Time . . . . . 0.00
```

This is the minimum percentage of HFS activity measured for which an item is to be included in the report.

By default, all HFS files with inflight activity during an observation session are displayed. Use the Minimum Percent of Time option to limit the report to files with activity above the specified threshold.

H02 - HFS Service Time by Device

Usage

Use this report to see how Service time was consumed by HFS device activity during the observation session. The unexpanded report shows an HFS device, listed by device number, for which activity was observed. If HFS file activity was observed during a sample, but could not be attributed to a specific file and device, the activity is aggregated to a single report line with a device number of "unknown". You can further expand each line item to show the HFS files associated with the device.

Quantification

Each report line quantifies Service time measured as a percentage of total time. The percentage represents the ratio of the number of samples in which an HFS call against the indicated HFS device was inflight to the total number of samples. An observation is counted as inflight regardless of the CPU state: Active, WAIT, or Queued.

Detail line hierarchy

An unexpanded report shows a line for each HFS device. The name field shows a sequence number assigned to each unique device. You can expand each line to reveal an additional hierarchical level of detail. The hierarchy is illustrated here:
 Level 1 HFS Device Level 2 HFS File

Level 1 HFS Device
 Level 2 HFS File

Detail line descriptions

HFS Device detail line

This is the first-level detail line.

| Under Heading | This is Displayed |
|-------------------|--|
| DevId | A unique sequence number assigned to each HFS device. |
| Device#>Path Name | The HFS device number. |
| Percent of Time | The percentage of activity measured in the indicated HFS device. |

HFS File detail line

This is the first-level detail line.

| Under Heading | This is Displayed |
|-------------------|--|
| DevId | A unique sequence number assigned to each HFS file. |
| Device#>Path Name | The HFS file path name.. |
| Percent of Time | The percentage of activity measured in the indicated HFS file. |

Sample reports

A sample report is shown here. It has been expanded to the second level.

```

File View Navigate Help
-----
H02: HFS Service Time by Device (8242/JVMTST01)          Row 00001 of 00085
Command ===> _____ Scroll ===> CSR

DevId  Device#>PathName          Percent of Time * 10.00%  ±1.0%
*....1....2....3....4....5....6..
00001  4                          85.07
→ 00002  /dev/ttyp0001             70.36
→ 00001  /dev/ttyp0000             50.49
→ 00005  /dev/ptyp0001             0.15
→ 00066  /dev/null                  0.06
→ 00004  /dev/ptyp0000             0.06
→ 00066  /dev/null                  0.04
→ 00066  /dev/null                  0.03
→ 00066  /dev/null                  0.02
→ 00066  /dev/null                  0.02
→ 00066  /dev/null                  0.01
→ 00066  /dev/null                  0.01

00000  unknown                    66.59
00009  8                          13.28
→ 00063  /tmp/ofile.txt            13.28
  
```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | DevId, FileId | Display context help information. |
| ++ | DevId, FileId | Show additional details. |
| + | DevId | Expand to reveal next level. |
| - | DevId | Collapse to hide next level. |
| SV | DevId | Sort next level by value. |
| SN | DevId | Sort next level by FileId. |
| SP | DevId | Sort next level by Path Name. |

on headings

| Cmd | When Applied To Heading | Action |
|-----|--|------------------------------------|
| ? | DevId, Device#>PathName, Percent of Time | Display context help information. |
| + | DevId | Expand to reveal all entries. |
| + | Device#>PathName | Expand field size. |
| + | Percent of Time | Zoom in scale. |
| - | DevId | Collapse to show only first level. |
| - | Device#>PathName | Reduce field size. |
| - | Percent of Time | Zoom out scale. |
| SV | DevId | Sort next level by value. |
| SN | DevId | Sort next level by DevId. |
| SD | DevId | Sort next level by Device#. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on a DevId will cause this detail window to appear.

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| 00001  4      85.07 |
+-----+

Calculation Details
HFS device measurements      8.507
Total measurements          10.000
Percent of total             85.07%

HFS Device Information
Device                       4
Dataset name                 HFS.ADCD.DEV
DD name                      SYS00006
Physical file system         HFS
Mount point                  /X235/dev
Mounted                      8:40:24.22 Friday Mar 9 2007

```

SETUP options

The SETUP command displays the following options:

```
Minimum Percentage of Time . . . . . 0.00
```

This is the minimum percentage of HFS activity measured for which an item is to be included in the report.

By default, all HFS devices with inflight activity during an observation session are displayed. Use the Minimum Percent of Time option to limit the report to devices with activity above the specified threshold.

H03 - HFS File Activity

Usage

Use this report to display the Read/Write counts for each HFS file captured during the observation session. Each report line shows an HFS file, listed by path name, and its associated Read/Write count.

Quantification

Each report line quantifies the Read/Write count by subtracting the Read count at the start of the observation session from the Read count at the end of the observation session; subtracting the Write count at the start of the observation session from the Write count at the end of the observation session; and adding the two differences together.

Detail line descriptions

HFS File detail line

| Under Heading | This is Displayed |
|---------------|---|
| FileId | A unique sequence number assigned to each HFS file. |
| Path Name | The HFS file path name. |
| File Type | The HFS file type. |

| Under Heading | This is Displayed |
|---------------|--|
| Reads/Writes | The Read/Write count for the indicated HFS file. |

Sample reports

A sample report is shown here.

```

File View Navigate Help
-----
H03: HFS File Activity (8242/JVMTST01) Row 00001 of 00198
Command ==>> _____ Scroll ==>> CSR

```

| FileId | Path Name | File Type | Reads/Writes |
|--------|-------------------------------------|------------------------|--------------|
| 00063 | /tmp/ofile.txt | Regular File | 55,985 |
| 00021 | /Z18/usr/lpp/java/J1.4/lib/core.jar | Regular File | 715 |
| 00080 | /Z18/usr/lpp/java/J1.4/lib/core.jar | Regular File | 644 |
| 00062 | /u/zfs/ofile.txt | Regular File | 261 |
| 00005 | /dev/ptyp0001 | Character Special File | 171 |
| 00070 | /u/zfs/platz | Regular File | 100 |
| 00066 | /dev/null | Character Special File | 98 |
| 00036 | /u/zfs/platz | Regular File | 98 |
| 00068 | /u/zfs/platz | Regular File | 97 |
| 00074 | /dev/null | Character Special File | 96 |
| 00035 | /dev/null | Character Special File | 89 |
| 00064 | /u/zfs/platz | Regular File | 88 |
| 00072 | /u/zfs/platz | Regular File | 88 |
| 00069 | /dev/null | Character Special File | 86 |
| 00075 | /u/zfs/platz | Regular File | 84 |
| 00065 | /dev/null | Character Special File | 74 |

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | FileId | Display context help information. |
| ++ | FileId | Show additional details. |

on headings

| Cmd | When Applied To Heading | Action |
|-----|-------------------------|-----------------------------------|
| ? | FileId | Display context help information. |
| SV | FileId | Sort next level by value. |
| SN | FileId | Sort next level by FileId. |
| SD | FileId | Sort next level by Path Name. |

Detail window

You can enter "++" (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering "++" on a FileId will cause this detail window to appear.

```

File View Navigate Help
+-----+
File 00063
Path name      /tmp/ofile.txt
File type      Regular File
Opened         7:08:32.33 Friday Mar 16 2007
Device#        8
Serial#        491
Open Flags     Write_Only Truncate Create

File Activity      Initial          Last          Delta
Read Requests     0                0              0
Write Requests    0                55,985        55,985
Dir I/O Blocks    12               12             0
Blocks Read       1                1              0
Blocks Written    0                55,985        55,985
Bytes Read        12               12             0
Bytes Written     0                2,127,115    2,127,115
+-----+

```

SETUP options

The SETUP command displays the following options:

Enter "/" to select an option

_Omit files for which no activity was observed during the measurement interval. Unselect to include all files.

By default, all HFS files are displayed. Select this option to omit HFS files that had no read/write activity during the observation session.

H04 - HFS File Attributes

Usage

Use this report to see detailed information about each HFS file that was open during the observation session. This is useful as a reference report when working with printed copies of other HFS reports that do not show full HFS file details. (When browsing online, the popup detail windows show this information.)

Detail line descriptions

The following information is shown for each HFS device.

| Under Heading | This is Displayed |
|---------------|--|
| FileId | A unique sequence number assigned to the HFS file. This is shown in other HFS reports that display HFS file information. |
| Path Name | The HFS file path name. |
| File Type | The HFS file type. |
| Major | If the file type is Character Special, the associated Major number is displayed. |
| Minor | If the file type is Character Special, the associated Minor number is displayed. |
| Opened | The date and time that the file was opened (local time). |
| Device# | The HFS device number associated with the file. |

| Under Heading | This is Displayed |
|---------------------------|--|
| Serial# | The HFS file serial number. |
| Open Flags | All the file Open Flags that are set are listed here. |
| Mode Flags - File Type | The HFS file type listed in the HFS Mode Flags. |
| Mode Flags - Permissions | The file permissions (Read/Write/Execute) categorized by Owner, Group, and Other. |
| Mode Flags - Set Id Flags | The Set Id is indicated by either Userid or Group. The Sticky bit setting is also displayed here (if on). |
| File Activity | The file activity is listed by category. The initial counts recorded at the start of the observation session, the final counts recorded at the end of the observation, and the delta are all listed. |

Sample reports

A sample report is shown here.

```

File View Navigate Help
-----
H04: HFS File Attributes (8242/JVMTST01)                               Row 00001 of 02162
Command ==> _____ Scroll ==> CSR

HFS file information reported for 115 files.

FileId 00001
Path name      /dev/tty0000
File type      Character Special File Major 2   Minor 0
Opened         6:47:58.93 Friday Mar 16 2007
Device#        4
Serial#         12
Open Flags     Read/Write Read_Only Write_Only
               Not_a_controlling_terminal

File Activity      Initial          Last            Delta
Read Requests     11              12              1
Write Requests    33              40              7
Dir I/O Blocks    19              19              0
Blocks Read       5               5               0
Blocks Written    0               0               0
Bytes Read        14,883          14,901          18
Bytes Written     1,244           1,350           106

```

H05 - HFS Device Activity

Usage

Use this report to display the Read/Write counts for each HFS device captured during the observation session. Each report line shows an HFS device, listed by device number, and its associated Read/Write count.

Quantification

Each report line quantifies the Read/Write count by subtracting the Read count at the start of the observation session from the Read count at the end of the observation session; subtracting the Write count at the start of the observation session from the Write count at the end of the observation session; and adding the two differences together.

Detail line descriptions

The following information is shown for each HFS device.

| Under Heading | This is Displayed |
|---------------|---|
| DevId | A unique sequence number assigned to each HFS device. |
| Device# | The HFS device number. |
| Mount Point | The directory at which the file system was mounted. |
| Reads/Writes | The Read/Write count for the indicated HFS device. |

Sample reports

A sample report is shown here.

```

File View Navigate Help
-----
H05: HFS Device Activity (8242/JVMTST01)          Row 00001 of 00009
Command ==>>> _____ Scroll ==>>> CSR

DevId  Device#  Mount Point                Reads/Writes
-----
00009  8        /X235/tmp                  55,985
00004  24       /Z18/usr/lpp/java          6,463
00001  4        /X235/dev                  996
00005  11       /u/zfs                     984
00003  10       /u                          81
00007  12       /Z18/usr/lpp/db2/db2810    12
00008  16       /Z18/usr/lpp/cicsts/cicsts31 12
00002  3        /Z18                       0
00006  7        /X235/etc                  0
  
```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | DevId | Display context help information. |
| ++ | DevId | Show additional details. |

on headings

| Cmd | When Applied To Heading | Action |
|-----|-------------------------|-----------------------------------|
| ? | DevId | Display context help information. |
| SV | DevId | Sort next level by value. |
| SN | DevId | Sort next level by DevId. |
| SD | DevId | Sort next level by Device#. |

Detail window

You can enter "++" (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on a DevId will cause this detail window to appear.

```

File View Navigate Help
+-----+
Device 00004
Device#           24
Dataset name      JVA140.HFS
DD name           SYS00025
Physical file system HFS
Mount point       /Z18/usr/lpp/java
Mounted           8:40:36.62 Friday Mar 9 2007

Device Activity   Initial           Last           Delta
Read Requests    186,308         192,771       6,463
Write Requests   0               0             0
Dir I/O Blocks   67,554         73,030        5,476
Blocks Read      247,016        258,524       11,508
Blocks Written   0              0             0
Bytes Read       462,232,053    501,613,789   39,381,736
Bytes Written    0              0             0
+-----+

```

SETUP options

The SETUP command displays the following options:

Enter "/" to select an option

Omit devices for which no activity was observed during the measurement interval. Unselect to include all devices.

By default, all HFS devices are displayed. Select this option to omit HFS devices that had no read/write activity during the observation session.

H06 - HFS Device Attributes

Usage

Use this report to see detailed information about each HFS device captured during the observation session. This is useful as a reference report when working with printed copies of other HFS reports that do not show full HFS device details. (When browsing online, the popup detail windows show this information.)

Detail line descriptions

The following information is shown for each HFS device.

| Under Heading | This is Displayed |
|----------------------|--|
| DevId | A unique sequence number assigned to the HFS device. This is shown in other HFS reports that display HFS device information. |
| Device# | The HFS device number. |
| Dataset Name | The dataset containing the HFS file system. |
| DD Name | The DD name assigned to the HFS dataset. |
| Physical File System | The file system type - HFS, zFS, NFS. |
| Mount Point | The directory at which the file system was mounted. |
| Mounted | The date and time that the file system was mounted (local time). |

| Under Heading | This is Displayed |
|-----------------|--|
| Device Activity | The device activity is listed by category. The initial counts recorded at the start of the observation session, the final counts recorded at the end of the observation, and the delta are all listed. |

Sample reports

A sample report is shown here.

```

File View Navigate Help
-----
H06: HFS Device Attributes (8242/JVMST01) Row 00001 of 0165
Command ==> _____ Scroll ==> CSR

HFS device information reported for 9 devices.

DevId 00001
Device#           4
Dataset name      HFS.ADCD.DEV
DD name           SYS00006
Physical file system HFS
Mount point       /X235/dev
Mounted           8:40:24.22 Friday Mar 9 2007

Device Activity   Initial           Last             Delta
Read Requests    5,922            6,138            216
Write Requests   1,070            1,850            780
Dir I/O Blocks   565              579              14
Blocks Read      56               56               0
Blocks Written   0                0                0
Bytes Read       220,179          221,394          1,215
Bytes Written    70,730           71,540           810

```

H07 - HFS Activity Timeline

Usage

Use this report to see, for each HFS file, how activity on the file was distributed over the measurement interval.

Quantification

A graph, in bar chart format, is displayed for each observed HFS file. The horizontal axis represents the measurement interval which spans 50 columns. Each column represents an equal 1/50th sub-interval of time. A scale is shown at the bottom of the graph indicating the percentage of time progression in the overall interval.

In each column, a vertical graph shows (roughly) the percentage of time during the sub-interval that activity on the HFS file took place. A vertical bar of 1, 2, 3, 4 or 5 characters, extending upward from the scale, is displayed indicating the percentage of time in the sub-interval during which file activity was observed.

Detail line descriptions

HFS Activity Distribution

A group of lines is shown for each reported HFS file. Some information about the HFS files is displayed to the left, and a bar chart is displayed on the right.


```

File View Navigate Help
+-----+
FileId 00002
Path name      /dev/tty0001
File type      Character Special File Major 2      Minor 1
Opened         7:05:22.45 Friday Mar 16 2007
Device#        4
Serial#        17
Open Flags     Read/Write Read_Only Write_Only
               Not_a_controlling_terminal

File Activity      Initial          Last          Delta
Read Requests      7                20           13
Write Requests     29               60           31
Dir I/O Blocks     19               19           0
Blocks Read        5                 5            0
Blocks Written     0                 0            0
Bytes Read         14,810           15,073       263
Bytes Written      1,829            2,252        423
+-----+

```

SETUP options

The SETUP command displays the following options:

Enter "/" to select an option

_Omit files for which no activity was observed during the measurement interval. Unselect to include all files.

By default, all HFS files are displayed. Select this option to omit HFS files that had no read/write activity during the observation session.

H08 - HFS Wait Time by Path Name

Usage

Use this report to identify delays resulting from waits during HFS requests. Each report line shows an HFS file, listed by path name, for which wait time was observed. If a wait was observed during a sample where there was an inflight HFS request, but could not be attributed to a specific file, the wait is aggregated to a single report line with a path name of "unknown".

Quantification

Each report line quantifies wait time measured as a percentage of total time. The percentage represents the ratio of the number of samples in which an HFS call against the indicated HFS file was in a wait to the total number of samples.

Detail line descriptions

HFS File detail line

| Under Heading | This is Displayed |
|-----------------|---|
| FileId | A unique sequence number assigned to each HFS file. |
| Path Name | The HFS file path name |
| Percent of Time | The percentage wait time measured for the indicated file. |

Sample reports

A sample report is shown here.

```
File View Navigate Help
-----
H08: HFS Wait Time by Path Name (8242/JVMTST01) Row 00001 of 00046
Command ==>> _____ Scroll ==>> CSR

FileId Path Name Percent of Time * 10.00% ±1.0%
*.....1....2....3....4....5....6..
00002 /dev/tty0001 70.29
00000 unknown 66.53
00001 /dev/tty0000 50.46
00021 /Z18/usr/lpp/java/J1.4/lib/core. 0.94
00080 /Z18/usr/lpp/java/J1.4/lib/core. 0.62
00063 /tmp/ofile.txt 0.32
00041 /Z18/usr/lpp/java/J1.4/lib/ext/d 0.31
00062 /u/zfs/ifile.txt 0.24
00032 /Z18/usr/lpp/java/J1.4/lib/ibmor 0.18
00044 /Z18/usr/lpp/java/J1.4/lib/ext/i 0.14
00026 /Z18/usr/lpp/java/J1.4/lib/chars 0.09
00042 /Z18/usr/lpp/java/J1.4/lib/ext/g 0.09
00034 /Z18/usr/lpp/java/J1.4/lib/ibmpk 0.08
00072 /u/zfs/platz 0.08
00075 /u/zfs/platz 0.08
00029 /Z18/usr/lpp/java/J1.4/lib/ibmjg 0.07
00036 /u/zfs/platz 0.07
00054 /Z18/usr/lpp/java/J1.4/lib/ext/r 0.07
```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | FileId | Display context help information. |
| ++ | FileId | Show additional details. |

on headings

| Cmd | When Applied To Heading | Action |
|-----|------------------------------------|-----------------------------------|
| ? | FileId, Path Name, Percent of Time | Display context help information. |
| + | Path Name | Expand description field size. |
| + | Percent of Time | Zoom in scale. |
| - | Path Name | Reduce description field size. |
| - | Percent of Time | Zoom out scale. |
| SV | FileId | Sort next level by value. |
| SN | FileId | Sort next level by FileId. |
| SP | FileId | Sort next level by Path Name. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on a FileId will cause this detail window to appear.

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| 00002  /dev/tty0001                               70.29 |
+-----+

Calculation Details
HFS file wait time measurements      7,029
Total measurements                   10,000
Percent of total                     70.29%

HFS File Information
Path name      /dev/tty0001
File type      Character Special File Major 2      Minor 1
Opened         7:05:22.45 Friday Mar 16 2007
Device#        4
Serial#        17
Open Flags     Read/Write Read_Only Write_Only
               Not_a_controlling_terminal
  
```

SETUP options

The SETUP command displays the following options:

```
Minimum Percentage of Time . . . . . 0.00
```

This is the minimum percentage of HFS wait time measured for which an item is to be included in the report.

By default, all HFS files with wait time during an observation session are displayed. Use the Minimum Percent of Time option to limit the report to files with wait time above the specified threshold.

H09- HFS Wait Time by Device

Usage

Use this report to identify delays resulting from waits during HFS requests. Each report line shows an HFS device, listed by device number, for which wait time was observed. If a wait was observed during a sample, where there was an inflight HFS request, but could not be attributed to a specific file and device, the wait is aggregated to a single report line with a device number of "unknown". You can further expand each line item to show the HFS files associated with the device.

Quantification

Each report line quantifies wait time measured as a percentage of total time. The percentage represents the ratio of the number of samples in which an HFS call against the indicated HFS device was in a wait to the total number of samples.

Detail line hierarchy

An unexpanded report shows a line for each HFS device. The name field shows a sequence number assigned to each unique device. You can expand each line to reveal an additional hierarchical level of detail. The hierarchy is illustrated here:

```

Level 1 HFS Device
Level 2 HFS File
  
```


Detail line descriptions

HFS Device detail line

This is the first-level detail line.

| Under Heading | This is Displayed |
|-------------------|---|
| DevId | A unique sequence number assigned to each HFS device. |
| Device#>Path Name | The HFS device number. |
| Percent of Time | The percentage wait time measured for the indicated HFS device. |

HFS File detail line

This is the second-level detail line.

| Under Heading | This is Displayed |
|-------------------|--|
| DevId | A unique sequence number assigned to each HFS file. |
| Device#>Path Name | The HFS file path name. |
| Percent of Time | The percentage activity measured for the indicated HFS file. |

Sample reports

A sample report is shown here. It has been expanded to the second level.

```

File View Navigate Help
-----
H09: HFS Wait Time by Device (8242/JVMTST01) Row 00001 of 00057
Command ==>> _____ Scroll ==>> CSR

DevId  Device#>PathName          Percent of Time * 10.00%  ±1.0%
      *.....1.....2.....3.....4.....5.....6..
00001  4                          84.84
→ 00002  /dev/ttyp0001             70.29
→ 00001  /dev/ttyp0000             50.46

00000  unknown                    66.53
00004  24                          3.27
→ 00021  /Z18/usr/lpp/java/J1.4/lib/core  0.94
→ 00080  /Z18/usr/lpp/java/J1.4/lib/core  0.62
→ 00041  /Z18/usr/lpp/java/J1.4/lib/ext/  0.31
→ 00032  /Z18/usr/lpp/java/J1.4/lib/ibmo  0.18
→ 00044  /Z18/usr/lpp/java/J1.4/lib/ext/  0.14
→ 00026  /Z18/usr/lpp/java/J1.4/lib/char  0.09
→ 00042  /Z18/usr/lpp/java/J1.4/lib/ext/  0.09
→ 00034  /Z18/usr/lpp/java/J1.4/lib/ibmp  0.08
→ 00029  /Z18/usr/lpp/java/J1.4/lib/ibmj  0.07
→ 00054  /Z18/usr/lpp/java/J1.4/lib/ext/  0.07
→ 00081  /Z18/usr/lpp/java/J1.4/lib/grap  0.07
→ 00043  /Z18/usr/lpp/java/J1.4/lib/ext/  0.06

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | DevId, FileId | Display context help information. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|-------------------------------|
| ++ | DevId, FileId | Show additional details. |
| + | DevId | Expand to reveal next level. |
| - | DevId | Collapse to hide next level. |
| SV | DevId | Sort next level by value. |
| SN | DevId | Sort next level by FileId. |
| SP | DevId | Sort next level by Path Name. |

on headings

| Cmd | When Applied To Heading | Action |
|-----|---|------------------------------------|
| ? | DevId, Device#>Path Name, Percent of Time | Display context help information. |
| + | DevId | Expand to reveal all entries. |
| + | Device#>Path Name | Expand field size. |
| + | Percent of Time | Zoom in scale. |
| - | DevId | Collapse to show only first level. |
| - | Device#>Path Name | Reduce field size. |
| - | Percent of Time | Zoom out scale. |
| SV | DevId | Sort next level by value. |
| SN | DevId | Sort next level by DevId. |
| SD | DevId | Sort next level by Device#. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on a DevId will cause this detail window to appear.

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| 00001  4                               84.84          |
+-----+

Calculation Details
HFS device wait time measurements      8.484
Total measurements                     10,000
Percent of total                       84.84%

HFS Device Information
Device#                                4
Dataset name                          HFS.ADCD.DEV
DD name                                SYS00006
Physical file system                   HFS
Mount point                            /X235/dev
Mounted                                8:40:24.22 Friday Mar 9 2007

```

SETUP options

The SETUP command displays the following options:

Minimum Percentage of Time 0.00

This is the minimum percentage of HFS wait time measured for which an item is to be included in the report.

By default, all HFS devices with wait time during an observation session are displayed. Use the Minimum Percent of Time option to limit the report to devices with activity above the specified threshold.

H10- HFS Service Time by Request

Usage

Use this report to see how Service time was consumed by HFS file requests during the observation session. The unexpanded report shows an HFS request, listed by Request name, for which activity was observed. If an HFS file request was observed during a sample, but could not be attributed to a specific file, the request is aggregated to a single report line with a request name of "unknown". You can further expand each line item to show the HFS files associated with the request.

Quantification

Each report line quantifies Service time measured as a percentage of total time. The percentage represents the ratio of the number of samples in which an HFS request was inflight to the total number of samples. An observation is counted as inflight regardless of the CPU state: Active, WAIT, or Queued.

Detail line hierarchy

An unexpanded report shows a line for each HFS request. The name field shows a sequence number assigned to each unique request type. You can expand each line to reveal an additional hierarchical level of detail. The hierarchy is illustrated here:

- Level 1 HFS Request
- Level 2 HFS File

Detail line descriptions

HFS Request detail line

This is the first-level detail line.

| Under Heading | This is Displayed |
|-------------------|---|
| ReqId | A unique sequence number assigned to each request type. |
| Request>Path Name | The HFS request name. |
| Percent of Time | The percentage activity measured for the indicated HFS request. |

HFS File detail line

This is the second-level detail line.

| Under Heading | This is Displayed |
|-------------------|--|
| ReqId | A unique sequence number assigned to each HFS file. |
| Request>Path Name | The HFS file path name. |
| Percent of Time | The percentage activity measured for the indicated HFS file. |

Sample reports

A sample report is shown here. It has been expanded to the second level.

```

File View Navigate Help
-----
H10: HFS Service Time by Request (8242/JVMTST01) Row 00001 of 00090
Command ==>> _____ Scroll ==>> CSR

ReqId Request>PathName Percent of Time * 10.00% ±1.0%
*....1....2....3....4....5....6..
00001 read 86.02
→ 00002 /dev/tty0000 70.35
→ 00001 /dev/tty0000 50.48
→ 00021 /Z18/usr/lpp/java/J1.4/lib/core 1.52
→ 00080 /Z18/usr/lpp/java/J1.4/lib/core 1.10
→ 00062 /u/zfs/iface.txt 0.53
→ 00041 /Z18/usr/lpp/java/J1.4/lib/ext/ 0.32
→ 00032 /Z18/usr/lpp/java/J1.4/lib/ibmo 0.18
→ 00075 /u/zfs/platz 0.18
→ 00043 /Z18/usr/lpp/java/J1.4/lib/ext/ 0.15
→ 00044 /Z18/usr/lpp/java/J1.4/lib/ext/ 0.15
→ 00072 /u/zfs/platz 0.15
→ 00070 /u/zfs/platz 0.14
→ 00036 /u/zfs/platz 0.12
→ 00064 /u/zfs/platz 0.12
→ 00022 /Z18/usr/lpp/java/J1.4/lib/grap 0.11
→ 00005 /dev/ptyp0001 0.11
→ 00026 /Z18/usr/lpp/java/J1.4/lib/char 0.10

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a "/" on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | ReqId, FileId | Display context help information. |
| ++ | ReqId, FileId | Show additional details. |
| + | ReqId | Expand to reveal next level. |
| - | ReqId | Collapse to hide next level. |
| SV | ReqId | Sort next level by value. |
| SN | ReqId | Sort next level by FileId. |
| SP | ReqId | Sort next level by Path Name. |

on headings

| Cmd | When Applied To Heading | Action |
|-----|--|------------------------------------|
| ? | ReqId, Request>PathName, Percent of Time | Display context help information. |
| + | ReqId | Expand to reveal all entries. |
| + | Request>Path Name | Expand field size. |
| + | Percent of Time | Zoom in scale. |
| - | ReqId | Collapse to show only first level. |
| - | Request>Path Name | Reduce field size. |

| Cmd | When Applied To Heading | Action |
|-----|-------------------------|-----------------------------|
| - | Percent of Time | Zoom out scale. |
| SV | ReqId | Sort next level by value. |
| SN | ReqId | Sort next level by ReqId. |
| SR | ReqId | Sort next level by Request. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on a ReqId will cause this detail window to appear.

```

File View Navigate Help
+-----+
+----- The following report line was selected -----+
| 00001  read                               86.02      |
+-----+

Calculation Details
HFS request measurements          8.602
Total measurements                10,000
Percent of total                  86.02%
+-----+

```

SETUP options

The SETUP command displays the following options:

```
Minimum Percentage of Time . . . . . 0.00
```

This is the minimum percentage of HFS activity measured for which an item is to be included in the report.

By default, all HFS requests captured during an observation session are displayed. Use the Minimum Percent of Time option to limit the report to requests with activity above the specified threshold.

H11- HFS Wait Time by Request

Usage

Use this report to identify delays resulting from waits during HFS requests. Each report line shows an HFS request, listed by Request name, for which wait time was observed. If a wait was observed during a sample, where there was an inflight HFS request, but could not be attributed to a specific file, the wait is aggregated to a single report line with a request name of "unknown". You can further expand each line item to show the HFS files associated with the request.

Quantification

Each report line quantifies wait time measured as a percentage of total time. The percentage represents the ratio of the number of samples in which an HFS request was in a wait, to the total number of samples.

Detail line hierarchy

An unexpanded report shows a line for each HFS request. The name field shows a sequence number assigned to each unique request type. You can expand each line to reveal an additional hierarchical level of detail. The hierarchy is illustrated here:

Level 1 HFS Request
Level 2 HFS File

Detail line descriptions

HFS Request detail line

This is the first-level detail line.

| Under Heading | This is Displayed |
|-------------------|--|
| ReqId | A unique sequence number assigned to each request type. |
| Request>Path Name | The HFS request name. |
| Percent of Time | The percentage wait time measured for the indicated HFS request. |

HFS File detail line

This is the second-level detail line.

| Under Heading | This is Displayed |
|-------------------|---|
| ReqId | A unique sequence number assigned to each HFS file. |
| Request>Path Name | The HFS file path name. |
| Percent of Time | The percentage wait time measured for the indicated HFS file. |

Sample reports

A sample report is shown here.

```

File View Navigate Help
-----
H11: HFS Wait Time by Request (8242/JVMST01)          Row 00001 of 00052
Command ==> _____ Scroll ==> CSR

ReqId  Request>PathName          Percent of Time * 10.00%  ±1.0%
      *.....1.....2.....3.....4.....5.....6..
00001  read                      35.38
→ 00002  /dev/ttyp0001             70.29
→ 00001  /dev/ttyp0000             50.46
→ 00021  /Z18/usr/lpp/java/J1.4/lib/core  0.94
→ 00080  /Z18/usr/lpp/java/J1.4/lib/core  0.62
→ 00041  /Z18/usr/lpp/java/J1.4/lib/ext/  0.31
→ 00062  /u/zfs/ifile.txt          0.24
→ 00032  /Z18/usr/lpp/java/J1.4/lib/ibmo  0.18
→ 00044  /Z18/usr/lpp/java/J1.4/lib/ext/  0.14
→ 00026  /Z18/usr/lpp/java/J1.4/lib/char  0.09
→ 00042  /Z18/usr/lpp/java/J1.4/lib/ext/  0.09
→ 00034  /Z18/usr/lpp/java/J1.4/lib/ibmp  0.08
→ 00072  /u/zfs/platz              0.08
→ 00075  /u/zfs/platz              0.08
→ 00029  /Z18/usr/lpp/java/J1.4/lib/ibmj  0.07
→ 00036  /u/zfs/platz              0.07
→ 00054  /Z18/usr/lpp/java/J1.4/lib/ext/  0.07
→ 00081  /Z18/usr/lpp/java/J1.4/lib/grap  0.07

```

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | ReqId, FileId | Display context help information. |
| ++ | ReqId, FileId | Show additional details. |
| + | ReqId | Expand to reveal next level. |
| - | ReqId | Collapse to hide next level. |
| SV | ReqId | Sort next level by value. |
| SN | ReqId | Sort next level by FileId. |
| SP | ReqId | Sort next level by Path Name. |

on headings

| Cmd | When Applied To Heading | Action |
|-----|--|------------------------------------|
| ? | ReqId, Request>PathName, Percent of Time | Display context help information. |
| + | ReqId | Expand to reveal all entries. |
| + | Request>Path Name | Expand field size. |
| + | Percent of Time | Zoom in scale. |
| - | ReqId | Collapse to show only first level. |
| - | Request>Path Name | Reduce field size. |
| - | Percent of Time | Zoom out scale. |
| SV | ReqId | Sort next level by value. |
| SN | ReqId | Sort next level by ReqId. |
| SR | ReqId | Sort next level by Request. |

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

For example, entering “++” on a ReqId will cause this detail window to appear.

```
File View Navigate Help
+-----+
+----- The following report line was selected -----+
| 00001  read                               85.38      |
+-----+
Calculation Details
HFS request wait time measurements      8.538
Total measurements                       10,000
Percent of total                         85.38%
```

SETUP options

The SETUP command displays the following options:

Minimum Percentage of Time 0.00

This is the minimum percentage of HFS wait time measured for which an item is to be included in the report.

By default, all HFS requests captured during an observation session are displayed. Use the Minimum Percent of Time option to limit the report to requests with wait time above the specified threshold.

Chapter 9. Quick start guide for compiling and assembling programs for use with IBM Problem Determination Tools products

This chapter describes the minimal steps required to prepare your programs for use with IBM Problem Determination Tools products. For more detailed information, refer to 'Part 2. Preparing your program for debugging' of the *Debug Tool for z/OS User's Guide*, 'Part 2. Fault Analyzer Installation and Administration' of the *Fault Analyzer for z/OS User's Guide*, or 'Appendix B. Creating side files using CAZLANGX' of the *Application Performance Analyzer for z/OS User's Guide*.

The purpose of this chapter is to provide instructions for a single compile method for organizations that are using some combination of Debug Tool for z/OS, Fault Analyzer for z/OS, and Application Performance Analyzer for z/OS. If your enterprise is only using Debug Tool for z/OS, refer to 'Part 2. Preparing your program for debugging' of the *Debug Tool for z/OS User's Guide*. If your enterprise is only using Fault Analyzer for z/OS, refer to 'Part 2. Fault Analyzer Installation and Administration' of the *Fault Analyzer for z/OS User's Guide*. If your enterprise is only using Application Performance Analyzer for z/OS, refer to 'Appendix B. Creating side files using CAZLANGX' of the *Application Performance Analyzer for z/OS User's Guide*.

Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS are designed to use load modules and other files produced by IBM compilers. You must compile your programs with certain compiler options so that they produce load modules and files that these products can use.

This chapter uses the term 'source information files' to refer to the types of files that are used by Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS. The different kinds of source information files that are the subject of discussion in this chapter include:

- SYSDEBUG files
- LANGX files
- Compiler listings
- DWARF files
- Expanded source files

Be aware that different compilers generate different kinds of source information files. If you use more than one compiler, you might have more than one type of source information library.

When you compile your programs with the compiler options described in this chapter, you can use the load modules and source information files created by the compilers as follows:

- Prepare the module for debugging (if you are using Debug Tool for z/OS). Debug Tool for z/OS lets you work with program statements and variables.

When a program is compiled with the right options, the module that is produced by the compiler can be debugged and a source information file, which contains program statements, can be produced. When you use Debug Tool for z/OS to debug a program, Debug Tool for z/OS uses the source information file to display the program source statements in the source window.

Depending on the source language and compiler used, either the load module, source information file, or DWARF file contains information about statements and variables, such as offsets and lengths, and contains information that allows the debugger to locate statements and variables in storage. If you do not compile with the correct compile options, debugging is limited to something called 'disassembly' mode, where machine code is displayed, but no source statements or variables.

- Utilize Fault Analyzer for z/OS to automatically pinpoint the source statement that caused an abend, and can show you the values of variables in your programs at the time of an abend.
- Utilize Application Performance Analyzer for z/OS to show you precisely which program statements are utilizing the most CPU time and wait time, to give you information you need to tune your applications.

Updating your build process

If someone recently installed one or more of the IBM Problem Determination Tools products on your system, the program build processes might not have been updated yet. Updating the build processes is an important and necessary part of implementing the IBM Problem Determination Tools products.

In many organizations, there is clear ownership of these build processes. In other organizations, it might not be obvious who should make the changes. Many organizations use standard compile processes or PROCs that your system administrators maintain and have updated to prepare programs for the IBM Problem Determination Tools products. If this is the case, find out what processes have been made available and how to use them. In other organizations, each developer maintains their own compile JCL or PROCs to compile programs. If this is the case, update your own compile JCL to prepare your programs for the IBM Problem Determination Tools products as described below.

Start by researching what is required for each compiler individually. For example, the changes required for Enterprise COBOL for z/OS, Enterprise PL/I for z/OS, C/C++ and Assembler are all slightly different.

In general, there are three changes that might be needed to compiler JCL to produce programs that can be used by the IBM Problem Determination Tools:

1. Specify compiler options required by the IBM Problem Determination Tools. For example, in the case of Enterprise COBOL for z/OS, a TEST options is needed.
2. Code the JCL to produce and save the source information files that the IBM Problem Determination Tools products need. Newer compilers can generate the required source information files directly. Some older compilers require an additional step in the compile job to run a special utility program that produces the needed file.
3. In certain environments, it is advantageous to include a special Debug Tool for z/OS module into the application load module during the link edit step. In most cases this is optional, but it can simplify starting Debug Tool for z/OS for certain types of programs. For certain older compilers running in certain environments, you must include a special module to enable Debug Tool for z/OS.

Updating your promotion process

Typically, when a program is tested, program load modules are promoted through different stages before reaching production. For example, when a new program is compiled for the first time, it might be placed into a test load library. After unit testing is completed, perhaps the compiled program is promoted to a quality assurance environment. And eventually, it is promoted into production. On your system, you might know these stages by different names, such as:

- Unit test
- System test
- Model office

Consider whether you want the ability to use Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS throughout your programs' life cycle. Even if you do not plan to use Debug Tool for z/OS with production programs, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS are very useful in those stages. To enable the IBM Problem Determination Tools products at each stage, update your promotion processes to retain the source information files. Promotions can be accomplished by performing a recompile, a copy, or a move. Perform the same steps with your source information files that you perform with your load modules or object modules. For each load library or object library, you should have a corresponding set of source information libraries. Whenever you promote a load module or object module, you should promote the source information file as well. This ensures that the source information file is available for Fault Analyzer and Application Performance Analyzer, and you can continue to take advantage of the IBM Problem Determination Tools products at all stages of your program's life cycle.

Preparing your programs

Each compiler produces different kinds of source information files, and each of the IBM Problem Determination Tools products reads different kinds of files. It can be time-consuming to research all the different combinations, but for each compiler, there is a suggested method described below. If you use the suggested methods, then your programs will be ready to take full advantage of the IBM Problem Determination Tools products.

- "Enterprise COBOL for z/OS Version 4 programs" on page 504
- "Enterprise COBOL for z/OS Version 3 and COBOL for OS/390 and VM programs" on page 507
- "COBOL for MVS and VM programs" on page 510
- "VS COBOL II programs, when the module is linked with Language Environment runtime services" on page 513
- "VS COBOL II programs, when the module is not linked with Language Environment runtime services" on page 516
- "OS/VS COBOL programs" on page 517
- "Enterprise PL/I Version 3.5 and later programs" on page 520
- "Enterprise PL/I Version 3.4 and earlier programs" on page 525
- "PL/I for MVS and VM and OS PL/I programs" on page 529
- "z/OS XL C and C++ programs" on page 532
- "Assembler programs" on page 539

Enterprise COBOL for z/OS Version 4 programs

The following table shows various compiler options that can be used to prepare Enterprise COBOL for z/OS Version 4 programs for use with the IBM Problem Determination Tools products (Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS). The methods suggested in the following table indicate if the load module produced is suitable for a production environment. Load modules suitable for a production environments have no significant runtime overhead.

Table 3. Examples of compiler options and source information files supported by IBM Problem Determination Tools products for Enterprise COBOL for z/OS Version 4

| Compiler options | Source information file type produced | Is the load module production ready? | Options supported and suggested for Debug Tool for z/OS | Options supported and suggested for Fault Analyzer for z/OS | Options supported and suggested for Application Performance Analyzer for z/OS |
|--|---------------------------------------|--------------------------------------|---|---|---|
| TEST(NOHOOK, SEPARATE, EJPD), LIST, MAP, SOURCE, NONUMBER, XREF(SHORT) | SYSDEBUG | Yes | Suggested for production and test | | |
| NOTEST, LIST, MAP, SOURCE, NONUMBER, XREF(SHORT) | Compiler listing | Yes | N/A | Supported | Supported |
| NOTEST, LIST, MAP, SOURCE, XREF(SHORT), NUMBER | | Yes | N/A | Supported | N/A |
| LIST, MAP, SOURCE, NONUMBER, XREF(SHORT) | LANGX file | Yes | N/A | Supported | Supported |

Note: The highlighted row or rows in the table above indicate the suggested compiler options and source information file types for each product.

Preparing Enterprise COBOL for z/OS Version 4 programs

Perform the following steps for compiling your Enterprise COBOL for z/OS Version 4 programs:

- Create libraries (PDSE is suggested unless PDS is required in your organization) for SYSDEBUG files. Create one or more SYSDEBUG libraries for each environment, such as test, production, and so on.
- Create a corresponding SYSDEBUG library for each load library. Specify LRECL=(80 to 1024),RECFM=FB,BLKSIZE=(multiple of 1recl < 32K).
- For all programs in both test and production environments, specify TEST(NOHOOK,SEPARATE,EJPD),LIST,MAP,SOURCE,NONUMBER,XREF(SHORT).

The TEST compiler option is required if you plan to use Debug Tool for z/OS to debug a program. The TEST option can be avoided if you plan to use Fault Analyzer for z/OS or Application Performance Analyzer for z/OS, but not Debug Tool for z/OS.

The SEPARATE sub-option produces a SYSDEBUG file.

NOHOOK and SEPARATE produce a production-ready module that can still be debugged.

If the OPT option is also used, EJPD might reduce optimization but enables the debugger's JUMPTO and GOTO commands. These commands are disabled when OPT and NOEJPD are both used.

- When the TEST option is not used, save the compiler listing in a file, or use the xxxLANGX utility program to create a LANGX file. Equivalent xxxLANGX utilities are available in Debug Tool for z/OS as EQALANGX, in Fault Analyzer for z/OS as IDILANGX and in Application Performance Analyzer for z/OS as CAZLANGX. Fault Analyzer for z/OS and Application Performance Analyzer for z/OS can use compiler listings and LANGX files to provide source-level support.
- Code a SYSDEBUG DD in the JCL of the compiler step:

```
//SYSDEBUG DD DSN= SYSDEBUG.pds(pgmname),DISP=SHR
```

Save the SYSDEBUG file produced by the compiler in the SYSDEBUG library and specify a member name that is equal to the program name of your application program. This is the source information file for Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS.

- Modify the promotion process to promote SYSDEBUG files. When a load module is promoted, for example from test to production, promote the corresponding SYSDEBUG file or files. A promotion can be a recompile, copy, or move. Perform the same steps with the SYSDEBUG file that you perform with the module during promotion.
- Optionally, include a Debug Tool Language Environment (LE) exit module into the load module during the linkage editor step. This is one way to enable Debug Tool's panel 6 in ISPF, a simple panel-driven method to start the debugger automatically when a program runs, without JCL changes, based on the program name and user ID. Use module EQADBCXT for batch programs (including IMS batch), EQADICXT for IMS/TM programs and EQADDCXT for DB2 stored procedures. Do not include the exit module for CICS programs.

Sample JCL

Below is a JCL example for compiling an Enterprise COBOL for z/OS Version 4 program for use with the IBM Problem Determination Tools products. This is a generic sample, and might not meet all your requirements to generate your modules.

Notice that the TEST compiler option is specified. Code the correct sub-options of the TEST compiler option for the version of the compiler that you are using. You can also code any other compatible compiler options that are required by your programs.

Also notice that a SYSDEBUG DD statement has been coded. This is the source information file that the compiler produces. It refers to a SYSDEBUG library that is a PDS or PDSE. The member name must be the same as the program name.

For Enterprise COBOL for z/OS, these are the only required changes.

However, there is an optional change in the linkage editor step. The example below shows that a special Language Environment exit module is included in the application load module. Although this is not required, it enables the use of Debug Tool panel 6, which makes the debugger easier to start in some environments. If you prefer to use panel 6 to start Debug Tool, this is one way to enable it. If you do not plan to use Debug Tool panel 6, then do not include an exit module.

```

/**      - - - ADD A JOB CARD ABOVE THIS LINE - - -
/**
/** SAMPLE JCL TO PREPARE AN ENTERPRISE COBOL PROGRAM
/** FOR THE IBM ZSERIES PD TOOLS PRODUCTS:
/**     FAULT ANALYZER, DEBUG TOOL, AND APPLICATION PERF. ANALYZER
/**
/** NOTES:
/**
/** COMPILER:
/**  1. A TEST COMPILER PARM IS REQUIRED FOR DEBUG TOOL
/**  2. COMPILER PARM TEST(NOHOOK,SEPARATE,EJPD) HAS ADVANTAGES:
/**     - THE MODULE IS READY FOR DEBUG TOOL
/**     - THE MODULE IS PRODUCTION-READY (NO RUN-TIME OVERHEAD)
/**     - A SYSDEBUG FILE IS CREATED THAT CAN BE USED BY DT,FA,APA
/**  3. COMPILER PARMS LIST,MAP,SOURCE,XREF ARE REQUIRED IF YOU PLAN
/**     TO USE THE COMPILER LISTING WITH FA OR APA, OR XXXLANGX
/**
/** BINDER (LINKAGE EDITOR):
/**  4. THE INCLUDE FOR MODULE EQAD?CXT IS *OPTIONAL*. IT IS AN
/**     LE EXIT MODULE THAT CAN BE USED TO START DEBUG TOOL.
/**     UNDERSTAND THE METHODS AVAILABLE FOR STARTING DEBUG TOOL,
/**     AND CHOOSE WHETHER YOU WANT TO USE THE LE EXITS.
/**     IF YOU USE THIS METHOD, LOAD THE CORRECT EXIT MODULE:
/**     EQADBCXT: FOR BATCH PROGRAMS
/**     EQADICXT: FOR ONLINE IMS PROGRAMS
/**     EQADDCXT: FOR DB2 STORED PROCEDURES
/**     (DO NOT INCLUDE AN EXIT FOR CICS PROGRAMS)
/**
/** SET PARMS FOR THIS COMPILE:
/** -----
/** SET MEM=SAM1                                PROGRAM NAME
/** SET COBOLLIB='IGY.V4R1.SIGYCOMP'           COBOL COMPILER LOADLIB
/** SET DTLIB='EQAW.SEQAMOD'                   DEBUG TOOL LOADLIB
/** SET LELIB='CEE.SCEELKED'                   LE LINKEDIT LIBRARY
/** SET UNITDEV=SYSALLDA                        UNIT FOR TEMP FILES
/**
/** *****
/**          COMPILE STEP
/** *****
/**COMPILE EXEC PGM=IGYCRCTL,REGION=0M,
/** PARM=('TEST(NOHOOK,SEPARATE,EJPD),LIST,MAP,XREF(SHORT),NONUMBER,SOURCE')
/**STEPLIB DD DISP=SHR,DSN=&COBOLLIB
/**SYSIN   DD DISP=SHR,DSN=&SYSUID..ADLAB.SOURCE(&MEM)
/**SYSLIB  DD DISP=SHR,DSN=&SYSUID..ADLAB.COPYLIB
/**SYSPRINT DD DISP=SHR,DSN=&SYSUID..ADLAB.LISTING(&MEM)
/**SYSDEBUG DD DISP=SHR,DSN=&SYSUID..ADLAB.SYSDEBUG(&MEM)
/**SYSLIN  DD DISP=(MOD,PASS),DSN=&&LOADSET,UNIT=&UNITDEV,
/**        SPACE=(80,(10,10))
/**SYSUT1  DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**SYSUT2  DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**SYSUT3  DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**SYSUT4  DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**SYSUT5  DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**SYSUT6  DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**SYSUT7  DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**
/**CBLPRINT EXEC PGM=IEBGENER,REGION=0M
/**SYSPRINT DD SYSOUT=*
/**SYSUT1  DD DSN=&SYSUID..ADLAB.LISTING(&MEM),DISP=SHR
/**SYSUT2  DD SYSOUT=*
/**SYSIN   DD DUMMY
/** *****
/**          LINK-EDIT (BINDER) STEP
/** *****
/**LKED EXEC PGM=IEWL,REGION=0M,COND=(5,LT,COMPILE),PARM='LIST,XREF'
/**SYSLIB  DD DISP=SHR,DSN=&LELIB
/**DTLIB   DD DISP=SHR,DSN=&DTLIB

```

```

//SYSMOD DD DSN=&SYSUID..ADLAB.LOAD(&MEM),DISP=SHR
//SYSLIN DD DISP=(OLD,DELETE),DSN=&&LOADSET
//* INCLUDING A DEBUG TOOL LE EXIT (EQADBCXT, EQADDCXT, OR EQADICXT) IS OPTIONAL.
//* AN EXIT ENABLES STARTING DEBUG TOOL USING THE USER EXIT DATA SET UTILITY
//* (ONE OF THE DEBUG TOOL ISPF UTILITIES)
//* // DD *
//* INCLUDE DTLIB(EQADBCXT)
//SYSPRINT DD SYSOUT=*
//SYSUT1 DD UNIT=&UNITDEV,DCB=BLKSIZE=1024,SPACE=(1024,(200,20))

```

Enterprise COBOL for z/OS Version 3 and COBOL for OS/390 and VM programs

The following table shows various compiler options that can be used to prepare Enterprise COBOL for z/OS Version 3 and COBOL for OS/390 and VM programs for use with the IBM Problem Determination Tools products (Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS). The methods suggested in the following table indicate if the load module produced is suitable for a production environment. Load modules suitable for a production environments have no significant runtime overhead.

Table 4. Examples of compiler options and source information files supported by IBM Problem Determination tools products for Enterprise COBOL for z/OS Version 3 and COBOL for OS/390 and VM

| Compiler options | Source information file type produced | Is the load module production ready? | Options supported and suggested for Debug Tool for z/OS | Options supported and suggested for Fault Analyzer for z/OS | Options supported and suggested for Application Performance Analyzer for z/OS |
|---|---------------------------------------|--------------------------------------|---|---|---|
| TEST(NONE, SYM, SEPARATE), LIST, MAP, SOURCE, NONUMBER, XREF(SHORT) | SYSDEBUG | Yes | Suggested for production and test | | |
| NOTEST, LIST, MAP, SOURCE, NONUMBER, NOOPT, XREF(SHORT) | Compiler listing | Yes | N/A | Supported | Supported |
| NOTEST, LIST, MAP, SOURCE, XREF(SHORT), NUMBER | | Yes | N/A | Supported | N/A |
| LIST, MAP, SOURCE, NONUMBER, XREF(SHORT) | LANGX file | Yes | N/A | Supported | Supported |

Note: The highlighted row or rows in the table above indicate the suggested compiler options and source information file types for each product.

Preparing Enterprise COBOL for z/OS Version 3 and COBOL for OS/390 and VM programs

Perform the following steps for compiling your Enterprise COBOL for z/OS Version 3 and COBOL for OS/390 and VM programs:

- Create libraries (PDSE is suggested unless PDS is required in your organization) for SYSDEBUG files. Allocate one or more SYSDEBUG libraries for each environment, such as test, production, and so on.

- Create a corresponding SYSDEBUG library for each load library. Specify LRECL=(80 to 1024),RECFM=FB,BLKSIZE=(multiple of lrecl < 32K).
- For all programs in both test and production environments, use TEST(NONE,SYM,SEPARATE),LIST,MAP,SOURCE,NONUMBER,XREF(SHORT).
TEST is required by Debug Tool for z/OS.
The SEPARATE sub-option produces a SYSDEBUG file. Specifying NONE with SEPARATE produces a production-ready module that can still be debugged.
If OPTIMIZE is specified, the debugger JUMPTO and GOTO commands are disabled. These commands are enabled when NOOPTIMIZE is specified.
- Code a SYSDEBUG DD in the JCL of the compiler step.
//SYSDEBUG DD DSN= SYSDEBUG.pds(pgmname),DISP=SHR

Save the SYSDEBUG file produced by the compiler in the SYSDEBUG library and specify a member name that is equal to the program name of your application program. This is the source information file for Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS.

- Modify the promotion process to promote SYSDEBUG files. When a load module is promoted, for example from test to production, promote the corresponding SYSDEBUG file or files. A promotion can be a recompile, copy, or move. Perform the same steps with the SYSDEBUG file that you perform with the module during promotion.
- Optionally, include a Debug Tool Language Environment exit module into the load module during the linkage editor step. This is one way to enable Debug Tool's panel 6 in ISPF, a simple panel-driven method to start the debugger automatically when a program runs, without JCL changes, based on the program name and user ID. Use module EQADBCXT for batch programs (including IMS batch), EQADICXT for IMS/TM programs and EQADDCXT for DB2 stored procedures. Do not include the exit module for CICS programs.

Sample JCL

Below is a JCL example for compiling an Enterprise COBOL for z/OS Version 3 program for use with the IBM Problem Determination Tools products. This is a generic sample, and might not meet all your requirements.

Notice that a TEST option is specified. Code the correct sub-option of the TEST compiler option for the version of the compiler that you are using. You can also code any other compatible compiler options that are required by your programs.

Also notice that a SYSDEBUG DD statement has been coded. This is the source information file that the compiler produces. It refers to a SYSDEBUG library that is a PDS or PDSE. The member name must be the same as the program name.

For Enterprise COBOL for z/OS, these are the only required changes.

However, there is an optional change in the linkage editor step. The example below shows that a special Language Environment exit module is included in the application load module. Although this is not required, it enables the use of Debug Tool panel 6, which makes the debugger easier to start in some environments. If you prefer to use panel 6 to start Debug Tool, this is one way to enable it. If you do not plan to use Debug Tool panel 6, then do not include an exit module.

```

/**      - - - ADD A JOB CARD ABOVE THIS LINE - - -
/**
/** SAMPLE JCL TO PREPARE AN ENTERPRISE COBOL PROGRAM
/** FOR THE IBM ZSERIES PD TOOLS PRODUCTS:
/**      FAULT ANALYZER, DEBUG TOOL, AND APPLICATION PERF. ANALYZER

```



```

/**
/** NOTES:
/**
/** COMPILER:
/** 1. A TEST COMPILER PARM IS REQUIRED FOR DEBUG TOOL
/** 2. COMPILER PARM TEST(NONE,SYM,SEP) HAS THREE ADVANTAGES:
/**    - THE MODULE IS READY FOR DEBUG TOOL
/**    - THE MODULE IS PRODUCTION-READY (NO RUN-TIME OVERHEAD)
/**    - A SYSDEBUG FILE IS CREATED THAT CAN BE USED BY DT,FA,APA
/** 3. COMPILER PARMS LIST,MAP,SOURCE,XREF ARE REQUIRED IF YOU PLAN
/**    TO USE THE COMPILER LISTING WITH FA OR APA, OR XXXLANGX
/** 4. COMPILER PARM NOOPT IS OPTIONAL. HOWEVER, THE DEBUG TOOL
/**    COMMANDS JUMPTO AND GOTO WILL NOT BE AVAILABLE IF
/**    THE OPT PARM IS USED
/**
/** BINDER (LINKAGE EDITOR):
/** 5. THE INCLUDE FOR MODULE EQAD?CXT IS *OPTIONAL*. IT IS AN
/**    LE EXIT MODULE THAT CAN BE USED TO START DEBUG TOOL.
/**    UNDERSTAND THE METHODS AVAILABLE FOR STARTING DEBUG TOOL,
/**    AND CHOOSE WHETHER YOU WANT TO USE THE LE EXITS.
/**    IF YOU USE THIS METHOD, LOAD THE CORRECT EXIT MODULE:
/**    EQADBCXT: FOR BATCH PROGRAMS
/**    EQADICXT: FOR ONLINE IMS PROGRAMS
/**    EQADDCXT: FOR DB2 STORED PROCEDURES
/**    (DO NOT INCLUDE AN EXIT FOR CICS PROGRAMS)
/**
/** SET PARMS FOR THIS COMPILE:
/** -----
/** SET MEM=SAM1                                PROGRAM NAME
/** SET COBOLLIB='IGY.V3R4.SIGYCOMP'           COBOL COMPILER LOADLIB
/** SET DTLIB='EQAW.SEQAMOD'                   DEBUG TOOL LOADLIB
/** SET LELIB='CEE.SCEELKED'                   LE LINKEDIT LIBRARY
/** SET UNITDEV=SYSALLDA                       UNIT FOR TEMP FILES
/**
/** *****
/**          COMPILE STEP
/** *****
/**/COMPILE EXEC PGM=IGYCRCTL,REGION=0M,
/**  PARM=('TEST(NONE,SYM,SEPARATE),LIST,MAP,SOURCE,NONUMBER,XREF(SHORT)')
/**/STEPLIB DD DISP=SHR,DSN=&COBOLLIB
/**/SYSIN DD DISP=SHR,DSN=&SYSUID..ADLAB.SOURCE(&MEM)
/**/SYSLIB DD DISP=SHR,DSN=&SYSUID..ADLAB.COPYLIB
/**/SYSPRINT DD DISP=SHR,DSN=&SYSUID..ADLAB.LISTING(&MEM)
/**/SYSDEBUG DD DISP=SHR,DSN=&SYSUID..ADLAB.SYSDEBUG(&MEM)
/**/SYSLIN DD DISP=(MOD,PASS),DSN=&&LOADSET,UNIT=&UNITDEV,
/**          SPACE=(80,(10,10))
/**/SYSUT1 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**/SYSUT2 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**/SYSUT3 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**/SYSUT4 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**/SYSUT5 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**/SYSUT6 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**/SYSUT7 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**
/**/CBLPRINT EXEC PGM=IEBGENER,REGION=0M
/**/SYSPRINT DD SYSOUT=*
/**/SYSUT1 DD DSN=&SYSUID..ADLAB.LISTING(&MEM),DISP=SHR
/**/SYSUT2 DD SYSOUT=*
/**/SYSIN DD DUMMY
/** *****
/**          LINK-EDIT (BINDER) STEP
/** *****
/**/LKED EXEC PGM=IEWL,REGION=0M,COND=(5,LT,COMPILE),PARM='LIST,XREF'
/**/SYSLIB DD DISP=SHR,DSN=&LELIB
/**/DTLIB DD DISP=SHR,DSN=&DTLIB
/**/SYSLMOD DD DSN=&SYSUID..ADLAB.LOAD(&MEM),DISP=SHR
/**/SYSLIN DD DISP=(OLD,DELETE),DSN=&&LOADSET

```

```

/** INCLUDING A DEBUG TOOL LE EXIT (EQADBCXT, EQADDCXT, OR EQADICXT) IS OPTIONAL.
/** AN EXIT ENABLES STARTING DEBUG TOOL USING THE USER EXIT DATA SET UTILITY
/** (ONE OF THE DEBUG TOOL ISPF UTILITIES)
/** //      DD *
/** INCLUDE DTLIB(EQADBCXT)
//SYSPRINT DD SYSOUT=*
//SYSUT1  DD UNIT=&UNITDEV,DCB=BLKSIZE=1024,SPACE=(1024,(200,20))

```

COBOL for MVS and VM programs

The following table shows various compiler options that can be used to prepare COBOL for MVS and VM programs for use with the IBM Problem Determination Tools products (Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS). The methods suggested in the following table indicate if the load module produced is suitable for a production environment. Load modules suitable for a production environments have no significant run-time overhead.

Table 5. Examples of compiler options and source information files supported by IBM Problem Determination tools products for COBOL for MVS and VM

| Compiler options | Source information file type produced | Is the load module production ready? | Options supported and suggested for Debug Tool for z/OS | Options supported and suggested for Fault Analyzer for z/OS | Options supported and suggested for Application Performance Analyzer for z/OS |
|---|---------------------------------------|--------------------------------------|--|---|---|
| TEST(ALL, SYM), LIST, MAP, SOURCE, NOOPT, NONUMBER, XREF(SHORT) | Compiler listing | No | Suggested for test. (Using Debug Tool in production for this compiler is not suggested.) | | |
| NOTEST, LIST, MAP, SOURCE, NONUMBER, XREF(SHORT) | | Yes | N/A | Suggested for production | |
| NOTEST, LIST, MAP, SOURCE, NONUMBER, XREF(SHORT) | LANGX file | Yes | N/A | Supported | Supported |

Note: The highlighted row or rows in the table above indicate the suggested compiler options and source information file types for each product.

Preparing COBOL for MVS and VM programs

Perform the following steps for compiling your COBOL for MVS and VM programs:

- Create libraries (PDSE is suggested unless PDS is required in your organization) for compiler listing files. Allocate one or more compiler listing libraries for each environment, such as test and production.
- Create a corresponding listing library for each load library. Specify LRECL=133,RECFM=FBA,BLKSIZE=(multiple of lrecl < 32K).
- For all programs, such as batch, CICS, and IMS:
 - In test environments, specify compiler options TEST(ALL, SYM), NOOPT, LIST, MAP, SOURCE, NONUMBER, XREF(SHORT) to create a module that can be used with Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS.
 - TEST is required for Debug Tool for z/OS.

The ALL sub-option adds debug hooks, which will add some run-time overhead.

SYM stores symbolics data required by Debug Tool for z/OS into the module, which can make it significantly larger.

The other options format the compiler listing as required by Debug Tool for z/OS, Fault Analyzer for z/OS, and Application Performance Analyzer for z/OS.

- In production environments, specify compiler options NOTEST, LIST, MAP, SOURCE, NONUMBER, XREF (SHORT) to create a production-ready module that can be used with Fault Analyzer for z/OS and Application Performance Analyzer for z/OS (but not Debug Tool for z/OS). Specify OPTIMIZE if preferred.

NOTEST disables source level debugging with Debug Tool, but can provide better performance and smaller module size.

The other options (except OPTIMIZE) format the compiler listing as required by Fault Analyzer for z/OS and Application Performance Analyzer for z/OS.

- Modify the SYSPRINT DD in the JCL of the compiler step to refer to a file.
//SYSPRINT DD DSN= compiler.listing.pds(pgmname),DISP=SHR

Save the compiler listing in a file in the compiler listing library and specify a member name that is equal to the program name of your application program. This is the source information file for Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS.

- Modify the promotion process to promote compiler listing files. When a load module is promoted, for example, from test to production, promote the corresponding compiler listing file or files. A promotion can be a recompile, a copy, or a move. Perform the same steps with the compiler listing file that you perform with the module during promotion.
- Optionally, include a Debug Tool Language Environment exit module into the load module during the linkage editor step. This is one way to enable Debug Tool's panel 6 in ISPF, a simple panel-driven method to start the debugger automatically when a program runs, without JCL changes, based on the program name and user ID. Use module EQADBCXT for batch programs (including IMS batch), EQADICXT for IMS/TM programs and EQADDCXT for DB2 stored procedures. Do not include the exit module for CICS programs.

Sample JCL

Below is a JCL example for compiling an COBOL for MVS and VM program for use with the IBM Problem Determination Tools products. This is a generic sample, and might not meet all your requirements.

Notice that a TEST option is specified. Code the correct sub-options of the TEST compiler option for the version of the compiler that you are using. You can also code any other compatible compiler options that are required by your programs.

Also notice that the SYSPRINT DD refers to a permanent file. This is the source information file that the compiler produces. It refers to a listing library that is a PDS or PDSE. The member name must be the same as the program name. For COBOL for MVS and VM, these are the only required changes.

However, there is an optional change in the linkage editor step. The example below shows that a special Language Environment exit module is included in the application load module. Although this is not required, it enables the use of Debug Tool panel 6, which makes the debugger easier to start in some environments. If

you prefer to use panel 6 to start Debug Tool, this is one way to enable it. If you do not plan to use Debug Tool panel 6, then do not include an exit module.

```

//*      - - - ADD A JOB CARD ABOVE THIS LINE - - -
//*
//* SAMPLE JCL TO PREPARE A COBOL FOR MVS AND VM PROGRAM
//* FOR THE IBM ZSERIES PD TOOLS PRODUCTS:
//*      FAULT ANALYZER, DEBUG TOOL, AND APPLICATION PERF. ANALYZER
//*
//* NOTES:
//*
//* COMPILER:
//*  1. A TEST COMPILER PARM IS REQUIRED FOR DEBUG TOOL
//*  2. COMPILER PARMS LIST,MAP,SOURCE,XREF ARE REQUIRED IF YOU PLAN
//*     TO USE THE COMPILER LISTING WITH FA OR APA, OR XXXLANGX
//*  3. COMPILER PARM NOOPT IS OPTIONAL. HOWEVER, THE DEBUG TOOL
//*     COMMANDS JUMPTO AND GOTO WILL NOT BE AVAILABLE IF
//*     THE OPT PARM IS USED
//*
//* BINDER (LINKAGE EDITOR):
//*  4. THE INCLUDE FOR MODULE EQAD?CXT IS *OPTIONAL*. IT IS AN
//*     LE EXIT MODULE THAT CAN BE USED TO START DEBUG TOOL.
//*     UNDERSTAND THE METHODS AVAILABLE FOR STARTING DEBUG TOOL,
//*     AND CHOOSE WHETHER YOU WANT TO USE THE LE EXITS.
//*     IF YOU USE THIS METHOD, LOAD THE CORRECT EXIT MODULE:
//*         EQADBCXT: FOR BATCH PROGRAMS
//*         EQADICXT: FOR ONLINE IMS PROGRAMS
//*         EQADDCXT: FOR DB2 STORED PROCEDURES
//*         (DO NOT INCLUDE AN EXIT FOR CICS PROGRAMS)
//*
//* SET PARMS FOR THIS COMPILE:
//* -----
// SET MEM=SAM1                                PROGRAM NAME
// SET COBOLLIB='IGY.SIGYCOMP'                  COBOL COMPILER LOADLIB
// SET DTLIB='EQAW.SEQAMOD'                     DEBUG TOOL LOADLIB
// SET LELIB='CEE.SCEELKED'                     LE LINKEDIT LIBRARY
// SET UNITDEV=SYSALLDA                          UNIT FOR TEMP FILES
//*
//* *****
//*          COMPILE STEP
//* *****
////COMPILE EXEC PGM=IGYCRCTL,REGION=0M,
// PARM=(NOTEST,LIST,MAP,SOURCE,NUMBER,XREF(SHORT)')
//STEPLIB DD DISP=SHR,DSN=&COBOLLIB
//SYSIN DD DISP=SHR,DSN=&SYSUID..ADLAB.SOURCE(&MEM)
//SYSLIB DD DISP=SHR,DSN=&SYSUID..ADLAB.COPYLIB
//SYSPRINT DD DISP=SHR,DSN=&SYSUID..ADLAB.LISTING(&MEM)
//SYSDEBUG DD DISP=SHR,DSN=&SYSUID..ADLAB.SYSDEBUG(&MEM)
//SYSLIN DD DISP=(MOD,PASS),DSN=&&LOADSET,UNIT=&UNITDEV,
//        SPACE=(80,(10,10))
//SYSUT1 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
//SYSUT2 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
//SYSUT3 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
//SYSUT4 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
//SYSUT5 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
//SYSUT6 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
//SYSUT7 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
//*
//CBLPRINT EXEC PGM=IEBGENER,REGION=0M
//SYSPRINT DD SYSOUT=*
//SYSUT1 DD DSN=&SYSUID..ADLAB.LISTING(&MEM),DISP=SHR
//SYSUT2 DD SYSOUT=*
//SYSIN DD DUMMY
//* *****
//*          LINK-EDIT (BINDER) STEP
//* *****
//LKED EXEC PGM=IEWL,REGION=0M,COND=(5,LT,COMPILE),PARM='LIST,XREF'

```

```

//SYSLIB DD DISP=SHR,DSN=&LELIB
//*** DTLIB DD DISP=SHR,DSN=&DTLIB
//SYSLMOD DD DSN=&SYSUID..ADLAB.LOAD(&MEM),DISP=SHR
//SYSLIN DD DISP=(OLD,DELETE),DSN=&&LOADSET
//* INCLUDING A DEBUG TOOL LE EXIT (EQADBCXT, EQADDCXT, OR EQADICXT) IS OPTIONAL.
//* AN EXIT ENABLES STARTING DEBUG TOOL USING THE USER EXIT DATA SET UTILITY
//* (ONE OF THE DEBUG TOOL ISPF UTILITIES)
//* // DD *
//* INCLUDE DTLIB(EQADBCXT)
//SYSPRINT DD SYSOUT=*
//SYSUT1 DD UNIT=&UNITDEV,DCB=BLKSIZE=1024,SPACE=(1024,(200,20))

```

VS COBOL II programs, when the module is linked with Language Environment runtime services

The following table shows various compiler options that can be used to prepare VS COBOL II programs, when the module is linked with Language Environment runtime services, for use with the IBM Problem Determination Tools products (Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS). The methods suggested in the following table indicate if the load module produced is suitable for a production environment. Load modules suitable for a production environments have no significant runtime overhead.

Table 6. Examples of compiler options and source information files supported by IBM Problem Determination tools products for VS COBOL II, when the module is linked with Language Environment runtime services

| Compiler options | Source information file type produced | Is the load module production ready? | Options supported and suggested for Debug Tool for z/OS | Options supported and suggested for Fault Analyzer for z/OS | Options supported and suggested for Application Performance Analyzer for z/OS |
|--|---------------------------------------|--------------------------------------|--|---|---|
| TEST, LIST, MAP, SOURCE, NONNUMBER, NOOPT, XREF(SHORT) | Compiler listing | No | Suggested for test. (Using Debug Tool in production for this compiler is not recommended.) | | |
| TEST, LIST, MAP, SOURCE, XREF(SHORT), NUMBER | | No | Supported | Supported | N/A |
| NOTEST, LIST, MAP, SOURCE, NONNUMBER, NOOPT, XREF(SHORT) | | Yes | N/A | Suggested for production | |
| NOTEST, LIST, MAP, SOURCE, XREF(SHORT), NUMBER | | Yes | N/A | Supported | N/A |
| NOTEST, LIST, MAP, SOURCE, XREF(SHORT), NONNUMBER | LANGX file | Yes | N/A | Supported | Supported |

Note: The highlighted row or rows in the table above indicate the suggested compiler options and source information file types for each product.

Preparing VS COBOL II programs, when the module is linked with Language Environment runtime services

Perform the following steps for compiling your VS COBOL II programs, when the module is linked with Language Environment runtime services:

- Allocate libraries (PDSE is suggested unless PDS is required in your organization) for compiler listing files. Allocate one or more compiler listing libraries for each environment, such as test and production.
- Create a corresponding compiler listing library for each load library. Specify `LRECL=133,RECFM=FBA,BLKSIZE=(multiple of 1recl < 32K)`.
- For all programs, such as batch, CICS, and IMS:
 - In test environments, specify compiler options `TEST,LIST,MAP,SOURCE,NONUMBER,NOOPT,XREF(SHORT)` to create a module that can be used with Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS.
TEST is required for Debug Tool, and adds debug hooks which add some runtime overhead. Symbolic data required by Debug Tool is stored in the module, which can make the module significantly larger.
 - In production environments, specify compiler options `NOTEST,LIST,MAP,SOURCE,NONUMBER,NOOPT,XREF(SHORT)` to create a production-ready module that can be used with Fault Analyzer for z/OS and Application Performance Analyzer for z/OS but not Debug Tool for z/OS.
NOTEST disables source level debugging with Debug Tool, but can provide better performance and smaller module size.
- Modify the SYSPRINT DD in the JCL of the compiler step to refer to a file.
`//SYSPRINT DD DSN= compiler.listing.pds(pgmname),DISP=SHR`

Save the compiler listing in a file in the compiler listing library and specify a member name that is equal to the program name of your application program. This is the source information file for Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS.

- Modify the promotion process to promote compiler listing files. When a load module is promoted, for example, from test to production, promote the corresponding compiler listing file or files. A promotion can be a recompile, copy, or move. Perform the same steps with the compiler listing file that you perform with the module during promotion.
- Optionally, include a Debug Tool Language Environment exit module into the load module during the linkage editor step. This is one way to enable Debug Tool's panel 6 in ISPF, a simple panel-driven method to start the debugger automatically when a program runs, without JCL changes, based on the program name and user ID. Use module EQADBCXT for batch programs (including IMS batch), EQADICXT for IMS/TM programs and EQADDCXT for DB2 stored procedures. Do not include the exit module for CICS programs.

Sample JCL

Below is an example of JCL for compiling a VS COBOL II program for use with IBM Problem Determination Tools products. This is a generic sample, and might not meet all your requirements.

Notice that a TEST option is specified. Code the correct sub-options of the TEST compiler option for the version of the compiler that you are using. You can also code any other compatible compiler options that are required by your programs.

Also notice that the SYSPRINT DD needs to be saved to a permanent file. This is the source information file that the compiler produces. It refers to a listing library that is a PDS or PDSE.

For VS COBOL II, this is the only required change.

However, there is an optional change in the linkage editor step. This example shows that a special Language Environment exit module is included in the application load module. Although this is not required, it enables the use of Debug Tool panel 6, which makes the debugger easier to start in some environments. If you prefer to use panel 6 to start Debug Tool, this is one way to enable it. If you do not plan to use Debug Tool panel 6, then do not include an exit module.

```

/**      - - - ADD A JOB CARD ABOVE THIS LINE - - -
/**
/** SAMPLE JCL TO PREPARE A VS COBOL II PROGRAM
/** FOR THE IBM ZSERIES PD TOOLS PRODUCTS:
/**   FAULT ANALYZER, DEBUG TOOL, AND APPLICATION PERF. ANALYZER
/**
/** NOTES:
/**
/** COMPILER:
/**   1. A TEST COMPILER PARM IS REQUIRED FOR DEBUG TOOL
/**   2. COMPILER PARMS LIST,MAP,SOURCE,XREF ARE REQUIRED IF YOU PLAN
/**     TO USE THE LISTING WITH A PD TOOLS PRODUCT, OR TO PROCESS
/**     THE LISTING WITH AN XXXLANGX UTILITY
/**
/** BINDER (LINKAGE EDITOR):
/**   3. THE INCLUDE FOR MODULE EQAD?CXT IS *OPTIONAL*. IT IS AN
/**     LE EXIT MODULE THAT CAN BE USED TO START DEBUG TOOL.
/**     UNDERSTAND THE METHODS AVAILABLE FOR STARTING DEBUG TOOL,
/**     AND CHOOSE WHETHER YOU WANT TO USE THE LE EXITS.
/**     IF YOU USE THIS METHOD, LOAD THE CORRECT EXIT MODULE:
/**     EQADBCXT: FOR BATCH PROGRAMS
/**     EQADICXT: FOR ONLINE IMS PROGRAMS
/**     EQADDCXT: FOR DB2 STORED PROCEDURES
/**     (DO NOT INCLUDE AN EXIT FOR CICS PROGRAMS)
/**
/** SET PARMS FOR THIS COMPILE:
/** -----
/** SET MEM=SAMII1                PROGRAM NAME
/** SET COB2COMP='IGY.V1R4M0.COB2COMP' COBOL II COMPILER LIB
/** SET DTLIB='EQAW.SEQAMOD'        DEBUG TOOL LOADLIB
/** SET LELIB='CEE.SCEELKED'       LE LINKEDIT LIBRARY
/** SET UNITDEV=SYSALLDA           TEMP DATASET UNIT
/**
/** *****
/**          COMPILE STEP
/** *****
/**COMPILE EXEC PGM=IGYCRCTL,REGION=4M,
/**  PARM=('TEST,LIST,MAP,SOURCE,NONUMBER,NOOPT,XREF(SHORT)')
/**STEPLIB DD DISP=SHR,DSN=&COB2COMP
/**SYSIN   DD DISP=SHR,DSN=&SYSUID..ADLAB.SOURCE(&MEM)
/**SYSLIB  DD DISP=SHR,DSN=&SYSUID..ADLAB.COPYLIB
/**SYSPRINT DD DISP=SHR,DSN=&SYSUID..ADLAB.LISTING(&MEM)
/**SYSLIN  DD DISP=(MOD,PASS),DSN=&&LOADSET,UNIT=&UNITDEV,
/**        SPACE=(80,(10,10))
/**SYSUT1  DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**SYSUT2  DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**SYSUT3  DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**SYSUT4  DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**SYSUT5  DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**SYSUT6  DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**SYSUT7  DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**

```

```

/**
//CBLPRINT EXEC PGM=IEBGENER,REGION=0M
//SYSPRINT DD SYSOUT=*
//SYSUT1 DD DSN=&SYSUID..ADLAB.LISTING(&MEM),DISP=SHR
//SYSUT2 DD SYSOUT=*
//SYSIN DD DUMMY
/** *****
/** LINK-EDIT (BINDER) STEP
/** *****
//LKED EXEC PGM=IEWL,REGION=0M,COND=(5,LT,COMPILE),PARM='LIST,XREF'
//SYSLIB DD DISP=SHR,DSN=&LELIB
//DTLIB DD DISP=SHR,DSN=&DTLIB
//SYSLMOD DD DSN=&SYSUID..ADLAB.LOAD(&MEM),DISP=SHR
//SYSLIN DD DISP=(OLD,DELETE),DSN=&&LOADSET
/** INCLUDING A DEBUG TOOL LE EXIT (EQADBCXT, EQADCXT, OR EQADICXT) IS OPTIONAL.
/** AN EXIT ENABLES STARTING DEBUG TOOL USING THE USER EXIT DATA SET UTILITY
/** (ONE OF THE DEBUG TOOL ISPF UTILITIES)
/** // DD *
/** INCLUDE DTLIB(EQADBCXT)
//SYSPRINT DD SYSOUT=*
//SYSUT1 DD UNIT=SYSALLDA,DCB=BLKSIZE=1024,SPACE=(1024,(200,20))

```

VS COBOL II programs, when the module is not linked with Language Environment runtime services

The following table shows various compiler options that can be used to prepare VS COBOL II programs, when the module is not linked with Language Environment runtime services, for use with the IBM Problem Determination Tools products (Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS). The methods suggested in the following table indicate if the load module produced is suitable for a production environment. Load modules suitable for a production environments have no significant run-time overhead.

Table 7. Examples of compiler options and source information files supported by Problem Determination tools products for VS COBOL II, when the module is not linked with Language Environment runtime services (linked to COBOL II runtime services)

| Compiler options | Source information file type produced | Is the load module production ready? | Options supported and suggested for Debug Tool for z/OS | Options supported and suggested for Fault Analyzer for z/OS | Options supported and suggested for Application Performance Analyzer for z/OS |
|---|---------------------------------------|--------------------------------------|---|---|---|
| NOTEST, LIST, MAP, SOURCE, NONUMBER, NOOFFSET, XREF | Compiler listing | Yes | N/A | Supported | Supported |
| NOTEST, LIST, MAP, SOURCE, XREF, NUMBER | | Yes | N/A | Supported | N/A |
| NOTEST, LIST, MAP, NOOPT, SOURCE, XREF, NONUMBER | LANGX file | Yes | Suggested for production and test | | |

Note: The highlighted row or rows in the table above indicate the suggested compiler options and source information file types for each product.

Preparing VS COBOL II programs, when the module is not linked with Language Environment runtime services

Perform the following steps for compiling your VS COBOL II programs, when the module is not linked with Language Environment runtime services:

- Allocate libraries (PDSE is suggested unless PDS is required for your organization) for LANGX files. Allocate one or more LANGX libraries for each environment, such as test and production.
- Create a corresponding LANGX library for each load library. Specify LRECL=1562 or greater, RECFM=VB, BLKSIZE= 1recl+4 to 32k.
- For all programs, such as batch, CICS, and IMS, in both test and production environments, compile with NOTEST, LIST, MAP, SOURCE, XREF(SHORT), NONUMBER compiler options. The module is production-ready and can be debugged using Debug Tool for z/OS.
- Run the Problem Determination tools xxxLANGX utility program. This utility program reads the compiler listing and generates a LANGX file, which can be used by Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS. Equivalent xxxLANGX utilities are available in Debug Tool for z/OS as EQALANGX, in Fault Analyzer for z/OS as IDILANGX and in Application Performance Analyzer for z/OS as CAZLANGX.
- Modify the SYSPRINT DD in the compiler step to refer to a file. It can be either a permanent or temporary file. This will be the input to the xxxLANGX utility.
- Add a step after the compiler step to run the xxxLANGX utility. It reads the compiler listing and saves a LANGX file. This is the source information file for Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS. Save the LANGX file in the LANGX file library and specify a member name that is equal to the program name of your application program.
- Modify the promotion process to promote LANGX files. When a load module is promoted, for example, from test to production, promote the corresponding LANGX file or files. A promotion can be a recompile, copy, or move. Perform the same steps with the LANGX file that you perform with the module during promotion.

OS/VS COBOL programs

The following table shows various compiler options that can be used to prepare OS/VS COBOL programs for use with the IBM Problem Determination Tools products (Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS). The methods suggested in the following table indicate if the load module produced is suitable for a production environment. Load modules suitable for a production environments have no significant run-time overhead.

Table 8. Examples of compiler options and source information files supported by Problem Determination tools products for OS/VS COBOL

| Compiler options | Source information file type produced | Is the load module production ready? | Options supported and suggested for Debug Tool for z/OS | Options supported and suggested for Fault Analyzer for z/OS | Options supported and suggested for Application Performance Analyzer for z/OS |
|--|---------------------------------------|--------------------------------------|---|---|---|
| DMAP, NOCLIST, NOLST, PMAP, SOURCE, VERB, XREF(SHORT) | Compiler listing | Yes | N/A | Supported | Supported |
| (LIST,NOPMAP) or (CLIST,NOPMAP) or (CLIST,PMAP) | | Yes | N/A | N/A | N/A |
| NOBATCH, NOCLIST, NOCOUNT, DMAP, NOLST, PMAP, SOURCE, NOSYMDMP, NOTEST, NOOPT, VERB, XREF(SHORT) | LANGX file | Yes | Suggested for production and test | | |

Note: The highlighted row or rows in the table above indicate the suggested compiler options and source information file types for each product.

Preparing OS/VS COBOL programs

Perform the following steps for compiling your OS/VS COBOL programs:

- Allocate libraries (PDSE is suggested unless PDS is required for your organization) for LANGX files. Allocate one or more LANGX libraries for each environment, such as test and production.
- Create a corresponding LANGX library for each load library. Specify LRECL=1562 or greater, RECFM=VB, BLKSIZE= 1recl+4 to 32k.
- For all programs, such as batch, CICS, and IMS, in both test and production environments, compile with the NOBATCH, NOCLIST, NOCOUNT, DMAP, NOLST, PMAP, SOURCE, NOSYMDMP, NOTEST, NOOPT, VERB, XREF(SHORT) compiler options. The module is production-ready and can be debugged using Debug Tool for z/OS.
- The compiler listing is formatted as required for the xxxLANGX utility. Run the Problem Determination tools xxxLANGX utility program that reads the compiler listing and generates a LANGX file, which can be used by Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS. Equivalent xxxLANGX utilities are available in Debug Tool for z/OS as EQALANGX, in Fault Analyzer for z/OS as IDILANGX and in Application Performance Analyzer for z/OS as CAZLANGX.
- Modify the SYSPRINT DD in the compiler step to refer to a file. It can be either a permanent or temporary file. This will be the input to the xxxLANGX utility.
- Add a step after the compiler step to run the xxxLANGX utility. This utility reads the compiler listing and saves a LANGX file, which is the source information file for Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS. Save the LANGX file in the LANGX file library, and specify a member name that is equal to the program name of your application program.

- Modify the promotion process to promote LANGX files. When a load module is promoted, for example, from test to production, promote the corresponding LANGX file or files. A promotion can be a recompile, copy, or move. Perform the same steps with the LANGX file that you perform with the module during promotion.

Sample JCL

Below is a JCL example for compiling an OS/VS program for use with the IBM Problem Determination Tools products:

```

/**      - - - ADD A JOB CARD ABOVE THIS LINE - - -
/**
/** SAMPLE JCL TO PREPARE AN OS VS COBOL PROGRAM
/** FOR THE IBM ZSERIES PD TOOLS PRODUCTS:
/**   FAULT ANALYZER, DEBUG TOOL, AND APPLICATION PERF. ANALYZER
/**
/** NOTES:
/**
/** COMPILER:
/**   - COMPILER PARMS DMAP,NOCLIST,NOLST,PMAP,SOURCE,VERB,XREF
/**     ARE REQUIRED IF YOU PLAN TO USE THE COMPILER LISTING WITH
/**     PD TOOLS AND/OR PROCESS IT WITH XXXLANGX
/**
/** A STEP THAT PROCESSES THE SYSADATA FILE,
/** AND CREATES A LANGX FILE IS NEEDED.
/**
/** SET PARMS FOR THIS COMPILE:
/** -----
/** SET MEM=SAMOS1                PROGRAM NAME
/** SET OSVSCOMP='IGY.VSCOLIB'    OS VS COBOL COMPILER LIBRARY
/** SET LELIB='CEE.SCEELKED'      LE LINKEDIT LIBRARY
/** SET UNITDEV=SYSALLDA          UNIT FOR TEMP FILES
/** SET SCEERUN='CEE.SCEERUN'     LANGUAGE ENVIRON SCEERUN LIB
/** SET LANGX='EQALANGX'          XXXLANGX UTILITY PROGRAM
/** SET LANGXLIB='EQAW.SEQAMOD'    LIBRARY FOR XXXLANGX UTILITY
/** NOTE: THE XXXLANGX UTILITY IS AVAILABLE WITH DEBUG TOOL,
/**       FAULT ANALYZER, AND APA WITH DIFFERENT NAMES. YOU CAN
/**       USE ANY OF THEM... THEY ALL PRODUCE THE SAME RESULTS.
/**       IF YOU HAVE DEBUG TOOL, YOU CAN SET:
/**       LANGX='EQALANGX' LANGXLIB=(THE DT SEQAMOD LIBRARY)
/**       IF YOU HAVE FAULT ANALYZER YOU CAN SET:
/**       LANGX='IDILANGX' LANGXLIB=(THE FA SIDIMOD1 LIBRARY)
/**       IF YOU HAVE APA (APP. PERFORMANCE ANALYZER) YOU CAN SET:
/**       LANGX='CAZLANGX' LANGXLIB=(THE APA SCAZAUTH LIBRARY)
/**
/** *****
/**       COMPILE STEP
/** *****
/**COMPILE EXEC PGM=IKFCBL00,REGION=4M,
/**  PARM=('DMAP,NOCLIST,NOLST,NOOPT,SOURCE,VERB,XREF(SHORT)')
/** FOR DT (CHECK DEFAULTS): NOBATCH,NOCOUNT,PMAP,NOSYDMP,NOTEST
/**STEPLIB DD DISP=SHR,DSN=&OSVSCOMP
/**SYSIN  DD DISP=SHR,DSN=&SYSUID..ADLAB.SOURCE(&MEM)
/**SYSLIB DD DISP=SHR,DSN=&SYSUID..ADLAB.COPYLIB
/**SYSPRINT DD DISP=SHR,DSN=&SYSUID..ADLAB.OSVSCOB.LISTING(&MEM)
/**SYSLIN  DD DISP=(MOD,PASS),DSN=&&LOADSET,UNIT=&UNITDEV,
/**        SPACE=(80,(10,10))
/**SYSUT1 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**SYSUT2 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**SYSUT3 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**SYSUT4 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**SYSUT5 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**SYSUT6 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**SYSUT7 DD SPACE=(80,(10,10),,,ROUND),UNIT=&UNITDEV
/**
/**CBLPRINT EXEC PGM=IEBGENER,REGION=0M

```

```

//SYSPRINT DD SYSOUT=*
//SYSUT1 DD DSN=&SYSUID..ADLAB.OSVSCOB.LISTING(&MEM),DISP=SHR
//SYSUT2 DD SYSOUT=*
//SYSIN DD DUMMY
//*
/* *****
/* STEP TO GENERATE LANGX FILE
/* *****
//LANGX EXEC PGM=&LANGX,REGION=32M,
// PARM='(COBOL ERROR 64K CREF'
//STEPLIB DD DISP=SHR,DSN=&LANGXLIB
// DD DISP=SHR,DSN=&SCEERUN
//LISTING DD DSN=&SYSUID..ADLAB.OSVSCOB.LISTING(&MEM),DISP=SHR
//IDILANGX DD DISP=SHR,DSN=&SYSUID..ADLAB.EQALANGX(&MEM)
//*
/* *****
/* LINK-EDIT (BINDER) STEP
/* *****
//LKED EXEC PGM=IEWL,REGION=0M,COND=(5,LT,COMPILE),PARM='LIST,XREF'
//SYSLIB DD DISP=SHR,DSN=&LELIB
//SYSLMOD DD DSN=&SYSUID..ADLAB.LOAD(&MEM),DISP=SHR
//SYSLIN DD DISP=(OLD,DELETE),DSN=&&LOADSET
//SYSPRINT DD SYSOUT=*
//SYSUT1 DD UNIT=&UNITDEV,DCB=BLKSIZE=1024,SPACE=(1024,(200,20))

```

Enterprise PL/I Version 3.5 and later programs

The following table shows various compiler options that can be used to prepare Enterprise PL/I Version 3.5 and later programs for use with the IBM Problem Determination Tools products (Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS). The methods suggested in the following table indicate if the load module produced is suitable for a production environment. Load modules suitable for a production environments have no significant run-time overhead.

Table 9. Examples of compiler options and source information files supported by IBM Problem Determination Tools products for Enterprise PL/I Version 3.5 and later

| Compiler options | Source information file type produced | Is the load module production ready? | Options supported and suggested for Debug Tool for z/OS | Options supported and suggested for Fault Analyzer for z/OS | Options supported and suggested for Application Performance Analyzer for z/OS |
|--|---|--|---|---|---|
| Preprocess (1st stage) to expand source, In compile (2nd stage): TEST(ALL, SYM, NOHOOK, SEPARATE), NOPT, AGGREGATE, ATTRIBUTES (FULL), NOBLKOFF, LIST, MAP, NEST, NONUMBER, OFFSET, OPTIONS, SOURCE, STMT, XREF(FULL)) | SYSDEBUG file used by Debug Tool for z/OS and Fault Analyzer for z/OS. LANGX file used by Application Performance Analyzer for z/OS | Although the module is larger than a module compiled with the NOTEST option, you can use the module in production if needed. | Suggested for test. You can also use these options in a production environment if the increased load module size is not an issue. | | |

Table 9. Examples of compiler options and source information files supported by IBM Problem Determination Tools products for Enterprise PL/I Version 3.5 and later (continued)

| Compiler options | Source information file type produced | Is the load module production ready? | Options supported and suggested for Debug Tool for z/OS | Options supported and suggested for Fault Analyzer for z/OS | Options supported and suggested for Application Performance Analyzer for z/OS |
|--|--|--|---|---|---|
| Preprocess (1st stage) to expand source, In compile (2nd stage): TEST(ALL, SYM, NOHOOK, NOSEPARATE), NOPT, AGGREGATE, ATTRIBUTES (FULL), NOBLKOFF, LIST, MAP, NEST, NONUMBER, OFFSET, OPTIONS, SOURCE, STMT, XREF(FULL)) | Expanded source file used by Debug Tool for z/OS, LANGX file used by Fault Analyzer for z/OS and Application Performance Analyzer for z/OS | Although the module is larger than a module compiled with the NOTEST option, you can use the module in production if needed. | Supported | Supported | Supported |
| AGGREGATE, ATTRIBUTES (FULL), NOBLKOFF, LIST, MAP, NEST, NOTEST, NONUMBER, OFFSET, OPTIONS, SOURCE, STMT, XREF(FULL)) | Compiler listing | Yes | N/A | Supported | N/A |
| | LANGX file | Yes | N/A | Suggested for production and test | |

Note: The highlighted row or rows in the table above indicate the suggested compiler options and source information file types for each product.

Preparing Enterprise PL/I Version 3.5 and later programs

Perform the following steps for compiling your Enterprise PL/I Version 3.5 and later programs:

- Create a library (PDSE is suggested unless PDS is required for your organization) for SYSDEBUG files. This is only needed in test environments where debugging will be performed using LRECL=(80 to 1024),RECFM=FB,BLKSIZE=(multiple of 1recl < 32K).
- Allocate one or more LANGX libraries for each environment, such as test and production.
- Create a corresponding LANGX library for each load library. Specify LRECL=1562 or greater,RECFM=VB,BLKSIZE= 1recl+4 to 32k.
- Run a two-stage compile. The first stage preprocesses the program, so the IBM Problem Determination Tools products have access to fully expanded source code with INCLUDEs and macros. The second stage compiles the program. For all programs, such as batch, CICS, and IMS:

- In the first compile stage, in both test and production environments, specify compiler options MACRO,MDECK,NOCOMPILE,NOSYNTAX,INSOURCE to expand INCLUDEs and macros. The output SYSPUNCH DD will be the input SYSIN DD to the second compile stage.
- In the second compile stage, in test environments,
 - For all programs, specify TEST(ALL,SYM,NOHOOK,SEPARATE), NOPT, AGGREGATE, ATTRIBUTES(FULL), NOBLKOFF, LIST, MAP, NEST, NONUMBER, OFFSET, OPTIONS, SOURCE, STMT, XREF(FULL))

TEST(...) and NOPT are required by Debug Tool.

The SEPARATE sub-option produces a SYSDEBUG file. Save the SYSDEBUG file created by the compiler for Debug Tool (and optionally, Fault Analyzer).

The other options format the compiler listing as required for the xxxLANGX utility.

Consider using TEST(ALL,SYM,NOHOOK,SEPARATE) for best performance and to produce a module that can be debugged. Depending on the policies in your organization, the module can be considered for production.

- In the second compile stage, in production environments, specify compiler options NOTEST, AGGREGATE, ATTRIBUTES(FULL), NOBLKOFF, LIST, MAP, NEST, NONUMBER, OFFSET, OPTIONS, SOURCE, STMT, XREF(FULL)).
- NOTEST disables Debug Tool, but produces a smaller load module.
- The other options format the compiler listing as required for the xxxLANGX utility to produce a production-ready module that can be used with Fault Analyzer for z/OS and Application Performance Analyzer for z/OS (but not Debug Tool for z/OS).
- When a TEST(...SEPARATE) parm is used, code a SYSDEBUG DD in the second compiler step as follows:


```
//SYSDEBUG DD DSN= SYSDEBUG.pds(pgmname),DISP=SHR
```

This is the source information file for Debug Tool (and optionally, Fault Analyzer). Save it in the SYSDEBUG library, and specify a member name that is equal to the primary entry point name or CSECT name of your application program.

- Modify the SYSPRINT DD in the second compiler stage. This is the compiler listing. Write the listing to either a permanent or temporary file. This is the input to the xxxLANGX utility.

Note: This compiler typically renames CSECTs according to an internal compiler algorithm. Therefore, it is not recommended to store PL/I compiler listings or side files using CSECT names as they might not be found by Application Performance Analyzer for z/OS or Fault Analyzer for z/OS. Instead, use the primary entry point name.

- Add a step after the compile step to run the xxxLANGX utility.
- Run the xxxLANGX utility to read the compiler listing and generate a LANGX file. This is the source information file for Fault Analyzer for z/OS and Application Performance Analyzer for z/OS. Equivalent xxxLANGX utilities are available in Debug Tool for z/OS as EQALANGX, in Fault Analyzer for z/OS as IDILANGX and in Application Performance Analyzer for z/OS as CAZLANGX. Save the LANGX file in the LANGX file library, and specify a member name that is equal to the primary entry point name of your application program.
- Modify the promotion process to promote LANGX files. When a load module is promoted, for example, from test to production, promote the corresponding

LANGX file or files. A promotion can be a recompile, copy, or move. Perform the same steps with the LANGX file that you perform with the module during promotion.

- If you compiled with the TEST option, you must promote the SYSDEBUG file for your production environment.
- Optionally, include a Debug Tool Language Environment exit module into the load module during the linkage editor step. This is one way to enable Debug Tool's panel 6 in ISPF, a simple panel-driven method to start the debugger automatically when a program runs, without JCL changes, based on the program name and user ID. Use module EQADBCXT for batch programs (including IMS batch), EQADICXT for IMS/TM programs and EQADDCXT for DB2 stored procedures. Do not include the exit module for CICS programs.

Sample JCL

Below is a JCL example for compiling an Enterprise PL/I for z/OS Version 3.5 or later program for use with the IBM Problem Determination Tools products.

```

/**      - - -  ADD A JOB CARD ABOVE THIS LINE  - - -
/**
/** SAMPLE JCL TO PREPARE AN ENTERPRISE PLI V3.5+ PROGRAM
/** FOR THE IBM ZSERIES PD TOOLS PRODUCTS:
/**   FAULT ANALYZER, DEBUG TOOL, AND APPLICATION PERF. ANALYZER
/**
/** NOTES:
/**
/** COMPILER:
/**  1. A 2-STAGE COMPILE IS PERFORMED.  STAGE 1 (PREPROCESS) IS
/**     DONE TO EXPAND INCLUDES AND MACROS IN THE PROGRAM, SO THAT
/**     THE SYSDEBUG FILE CREATED IN STAGE 2 (COMPILE) HAS ALL STMTS.
/**  2. COMPILER PARMS TEST AND NOPT ARE REQUIRED FOR DEBUG TOOL
/**  3. COMPILER PARM TEST(ALL,SYM,NOHOOK,SEP) IS USED BECAUSE:
/**     - THE MODULE IS READY FOR DEBUG TOOL
/**     - NOHOOK DOES NOT HAVE RUN-TIME CPU OVERHEAD.  HOWEVER, THE
/**       MODULE IS LARGER BECAUSE OF STATEMENT TABLE
/**     - A SYSDEBUG FILE IS CREATED THAT CAN BE USED BY DT,FA,APA
/**  4. COMPILER PARMS AGGREGATE,ATTRIBUTES(FULL),NOBLKOFF,LIST,
/**     MAP,NEST,NONUMBER,OPTIONS,SOURCE,STMT,XREF(FULL) ARE NEEDED
/**     TO PROCESS THE COMPILER LISTING WITH XXXLANGX
/**
/** BINDER (LINKAGE EDITOR):
/**  5. THE INCLUDE FOR MODULE EQAD?CXT IS OPTIONAL.  IT IS AN
/**     LE EXIT MODULE THAT CAN BE USED TO START DEBUG TOOL.
/**     UNDERSTAND THE METHODS AVAILABLE FOR STARTING DEBUG TOOL,
/**     AND CHOOSE WHETHER YOU WANT TO USE THE LE EXITS.
/**     IF YOU USE THIS METHOD, LOAD THE CORRECT EXIT MODULE:
/**     EQADBCXT: FOR BATCH PROGRAMS
/**     EQADICXT: FOR ONLINE IMS PROGRAMS
/**     EQADDCXT: FOR DB2 STORED PROCEDURES
/**     (DO NOT INCLUDE AN EXIT FOR CICS PROGRAMS)
/**
/** SET PARMS FOR THIS COMPILE:
/** -----
/** SET MEM=PADSTAT           PROGRAM NAME
/** SET PLICOMP='IBMZ.V3R5.SIBMZCMP'  PLI COMPILER LOADLIB
/** SET DTLIB='EQAW.SEQAMOD'         DEBUG TOOL LOADLIB
/** SET LEHLQ='CEE'               LE HIGH LVL QUALIFIER
/** SET UNITDEV=SYSALLDA         UNIT FOR TEMP FILES
/** SET LANGX='EQALANGX'         XXXLANGX UTILITY PROGRAM
/** SET LANGXLIB='EQAW.SEQAMOD'     LIBRARY FOR XXXLANGX UTILITY
/** NOTE: YOU CAN USE THE XXXLANGX UTILITY SHIPPED WITH DT, FA,
/**       OR APA.  THEY NAMES ARE DIFFERENT, BUT RESULTS ARE THE SAME
/**       USE ANY OF THEM... THEY ALL PRODUCE THE SAME RESULTS.
/** IF YOU HAVE:   SET LANGX TO:   SET LANGXLIB TO:
/** DEBUG TOOL    EQALANGX        THE DT SEQAMOD LIBRARY

```

```

/**      FAULT ANALYZER  IDILANGX      THE FA SIDIMOD1 LIBRARY
/**      APA            CAZLANGX      THE APA SCAZAUTH LIBRARY
/**
//ALLOCOBJ EXEC PGM=IEFBR14          ALLOC OBJ LIB IF NEEDED
//OBJ DD DSN=&SYSUID..ADLAB.OBJ,SPACE=(CYL,(3,1,15)),
// DSORG=PO,RECFM=FB,LRECL=80,BLKSIZE=8000,DISP=(MOD,CATLG)
/** *****
/**      PREPROCESS STEP (COMPILE STAGE 1)
/** *****
//PRECOMP EXEC PGM=IBMZPLI,REGION=0M,
// PARM=('MACRO,MDECK,NOCOMPILE,NOSYNTAX,INSOURCE')
//STEPLIB DD DSN=&PLICOMP,DISP=SHR
// DD DSN=&LEHLQ..SCEERUN,DISP=SHR
//SYSIN DD DISP=SHR,DSN=&SYSUID..ADLAB.SOURCE(&MEM)
//SYSLIB DD DISP=SHR,DSN=&SYSUID..ADLAB.COPYLIB
//SYSPRINT DD SYSOUT=*
//SYSUT1 DD SPACE=(1024,(200,50),,CONTIG,ROUND),DCB=BLKSIZE=1024,
// UNIT=&UNITDEV
//SYSPUNCH DD DISP=(MOD,PASS),DSN=&&SRC1,UNIT=&UNITDEV,
// SPACE=(80,(10,10))
/**
/** *****
/**      COMPILE STEP (COMPILE STAGE 2)
/** *****
//COMPILE EXEC PGM=IBMZPLI,REGION=0M,
// PARM=('TEST(ALL,SYM,NOHOOK,SEPARATE),LIST,MAP,SOURCE,XREF(FULL),',
// 'NOBLKOFF,AGGREGATE,ATTRIBUTES(FULL),NEST,OPTIONS,NOPT,',
// 'STMT,NONUMBER,OFFSET')
//STEPLIB DD DSN=&PLICOMP,DISP=SHR
// DD DSN=&LEHLQ..SCEERUN,DISP=SHR
//SYSIN DD DSN=&&SRC1,DISP=(OLD,PASS)
//SYSLIB DD DISP=SHR,DSN=&SYSUID..ADLAB.COPYLIB
//SYSPRINT DD DISP=SHR,DSN=&SYSUID..ADLAB.ENTPLI.LISTING(&MEM)
//SYSDEBUG DD DISP=SHR,DSN=&SYSUID..ADLAB.SYSDEBUG(&MEM)
//SYSUT1 DD SPACE=(CYL,(5,2),,CONTIG),DCB=BLKSIZE=1024,UNIT=&UNITDEV
//SYSLIN DD DSN=&SYSUID..ADLAB.OBJ(&MEM),DISP=SHR
/**
//PLIPRINT EXEC PGM=IEBGENER,REGION=0M
//SYSPRINT DD SYSOUT=*
//SYSUT1 DD DSN=&SYSUID..ADLAB.ENTPLI.LISTING(&MEM),DISP=SHR
//SYSUT2 DD SYSOUT=*
//SYSIN DD DUMMY
/**
/** *****
/**      STEP TO GENERATE LANGX FILE
/** *****
//LANGX EXEC PGM=&LANGX,REGION=32M,
// PARM=('PLI ERROR 64K CREF')
//STEPLIB DD DISP=SHR,DSN=&LANGXLIB
// DD DISP=SHR,DSN=&LEHLQ..SCEERUN
//LISTING DD DSN=&SYSUID..ADLAB.ENTPLI.LISTING(&MEM),DISP=SHR
//IDILANGX DD DISP=SHR,DSN=&SYSUID..ADLAB.EQALANGX(&MEM)
/**
/** *****
/**      LINK-EDIT (BINDER) STEP
/** *****
//LINK EXEC PGM=IEWL,PARM=(LET,MAP,LIST),REGION=0M
//SYSLIB DD DSN=&LEHLQ..SCEELKED,DISP=SHR
//DTLIB DD DSN=&DTLIB,DISP=SHR
//SYSPRINT DD SYSOUT=*
//SYSLOAD DD DISP=SHR,DSN=&SYSUID..ADLAB.LOAD(&MEM)
//SYSUT1 DD UNIT=SYSDA,SPACE=(TRK,(10,10))
//SYSLIN DD DSN=&SYSUID..ADLAB.OBJ(&MEM),DISP=(OLD,PASS)
/**      INCLUDING A DEBUG TOOL LE EXIT (EQADBCXT, EQADDCXT, OR EQADICXT)

```



```

/** IS OPTIONAL. THE EXIT ENABLES STARTING DEBUG TOOL WITH THE
/** USER EXIT DATA SET UTILITY (ONE OF THE DEBUG TOOL ISPF UTILITIES)
/** //          DD *
/** INCLUDE DTLIB(EQADBCXT)

```

Enterprise PL/I Version 3.4 and earlier programs

The following table shows various compiler options that can be used to prepare Enterprise PL/I Version 3.4 and earlier programs for use with the IBM Problem Determination Tools products (Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS). The methods suggested in the following table indicate if the load module produced is suitable for a production environment. Load modules suitable for a production environments have no significant run-time overhead.

Table 10. Examples of compiler options and source information files supported by IBM Problem Determination Tools products for Enterprise PL/I Version 3.4 and earlier

| Compiler options | Source information file type produced | Is the load module production ready? | Options supported and suggested for Debug Tool for z/OS | Options supported and suggested for Fault Analyzer for z/OS | Options supported and suggested for Application Performance Analyzer for z/OS |
|---|--|--------------------------------------|--|---|---|
| Preprocess (1st stage) to expand source, In compile (2nd stage): TEST(ALL), NOPT, AGGREGATE, ATTRIBUTES (FULL), NOBLKOFF, LIST, MAP, NEST, NONUMBER, OFFSET, OPTIONS, SOURCE, STMT, XREF(FULL)) | Expanded source file used by Debug Tool for z/OS, LANGX file used by Fault Analyzer for z/OS and Application Performance Analyzer for z/OS | No | Suggested for test. (Using Debug Tool in production for this compiler is not recommended.) | | |
| AGGREGATE, ATTRIBUTES (FULL), NOBLKOFF, LIST, MAP, NEST, NOTEST, NONUMBER, OFFSET, OPTIONS, SOURCE, STMT, XREF(FULL)) | Compiler listing | Yes | N/A | Supported | N/A |
| | LANGX file | Yes | N/A | Suggested for production and test | |

Note: The highlighted row or rows in the table above indicate the suggested compiler options and source information file types for each product.

Preparing Enterprise PL/I Version 3.4 and earlier programs

Perform the following steps for compiling your Enterprise PL/I Version 3.4 and earlier programs:

- Create a library (PDSE is suggested unless PDS is required for your organization) for expanded source files. This is only needed in test environments where debugging will be performed. The library can be any RECFM / LRECL / BLKSIZE supported as input by the compiler.

- Allocate libraries (PDSE is suggested unless PDS is required for your organization) for LANGX files. Allocate one or more LANGX libraries for each environment, such as test or production.
- Create a corresponding LANGX library for each load library. Specify LRECL=1562 or greater, RECFM=VB, BLKSIZE= 1recl+4 to 32k.
- Run a 2-stage compile. The first stage preprocesses the program, so the IBM Problem Determination Tools have access to fully expanded source code with INCLUDEs and macros. The second stage compiles the program.
 - In the first compile stage, in both test and production environments:
 - Specify compiler options MACRO, MDECK, NOCOMPILE, NOSYNTAX, INSOURCE to expand INCLUDEs and macros.
 - Save the output, the expanded source file, in a permanent file in the expanded source file library and specify *member name = program name*. This is the source information file for Debug Tool for z/OS. The output SYSPUNCH DD will be the input SYSIN DD to the second compiler stage.
 - In the second compile stage, for all programs, such as batch, CICS, and IMS:
 - In test environments, specify compiler options TEST(ALL), NOPT, AGGREGATE, ATTRIBUTES(FULL), NOBLKOFF, LIST, MAP, NEST, NONUMBER, OFFSET, OPTIONS, SOURCE, STMT, XREF(FULL).
TEST(ALL) and NOPT are required by Debug Tool. Debug hooks are inserted, which add some runtime overhead. Symbolic data required by Debug Tool is also stored in the module, which can make it significantly larger.
The other options format the compiler listing as required for the xxxLANGX utility.
 - In production environments, specify compiler options NOTEST, AGGREGATE, ATTRIBUTES(FULL), NOBLKOFF, LIST, MAP, NEST, NONUMBER, OFFSET, OPTIONS, SOURCE, STMT, XREF(FULL)).
NOTEST disables Debug Tool, but provides the best performance. This produces a production-ready module that can be used with Fault Analyzer for z/OS and Application Performance Analyzer for z/OS (but not Debug Tool).
The other options format the compiler listing as required for the xxxLANGX utility.
- Modify the SYSPRINT DD in the second compiler stage. This is the compiler listing. Save the compiler listing to either a permanent or temporary file. This will be the input to the xxxLANGX utility.

Note: This compiler typically renames CSECTs according to an internal compiler algorithm. Therefore, it is not recommended to store PL/I compiler listings or side files using CSECT names as they might not be found by Application Performance Analyzer for z/OS or Fault Analyzer for z/OS. Instead, use the primary entry point name.

- Add a step after the compiler step to run the xxxLANGX utility. The xxxLANGX utility reads the compiler listing and generates a LANGX file, which is the source information file for Fault Analyzer for z/OS and Application Performance Analyzer for z/OS. Equivalent xxxLANGX utilities are available in Debug Tool for z/OS as EQALANGX, in Fault Analyzer for z/OS as IDILANGX and in Application Performance Analyzer for z/OS as CAZLANGX. Save the LANGX file in the LANGX file library, and specify a member name that is equal to the primary entry point name or CSECT name of your application program.
- Modify the promotion process to promote LANGX files. When a load module is promoted, for example, from test to production, promote the corresponding

LANGX file or files. A promotion can be a recompile, copy, or move. Perform the same steps with the LANGX file that you perform with the module during promotion.

- Optionally, include a Debug Tool Language Environment exit module into the load module during the linkage editor step. This is one way to enable Debug Tool's panel 6 in ISPF, a simple panel-driven method to start the debugger automatically when a program runs, without JCL changes, based on the program name and user ID. Use module EQADBCXT for batch programs (including IMS batch), EQADICXT for IMS/TM programs and EQADDCXT for DB2 stored procedures. Do not include the exit module for CICS programs.
- For CICS applications only, if the Debug Tool DTCN transaction will be used to start Debug Tool, link edit the Debug Tool CICS startup exit module EQADCCXT into the application load module to enable Debug Tool in CICS. This is not needed if using the CADP transaction instead of DTCN.

Sample JCL

Below is a JCL example for compiling an Enterprise PL/I for z/OS Version 3.4 or earlier program for use with the IBM Problem Determination Tools products.

```

/**      - - - ADD A JOB CARD ABOVE THIS LINE - - -
/**
/** SAMPLE JCL TO COMPILE WITH ENTERPRISE PLI V3.4 AND PREVIOUS
/** FOR THE IBM ZSERIES PD TOOLS PRODUCTS:
/**   FAULT ANALYZER, DEBUG TOOL, AND APPLICATION PERF. ANALYZER
/**
/** NOTES:
/**
/**   COMPILER:
/**   1. A 2-STAGE COMPILE IS PERFORMED. STAGE 1 (PREPROCESS) IS
/**     DONE TO EXPAND INCLUDES AND MACROS IN THE PROGRAM, SO THAT
/**     A SOURCE FILE IS CREATED FOR DEBUG TOOL THAT HAS ALL STMTS.
/**   2. COMPILER PARM TEST AND NOPT ARE REQUIRED FOR DEBUG TOOL
/**   3. COMPILER PARMS AGGREGATE,ATTRIBUTES(FULL),NOBLKOFF,LIST,
/**     MAP,NEST,NONUMBER,OPTIONS,SOURCE,STMT,XREF(FULL) ARE NEEDED
/**     TO PROCESS THE COMPILER LISTING WITH XXXLANGX
/**
/**   BINDER (LINKAGE EDITOR):
/**   4. THE INCLUDE FOR MODULE EQAD?CXT IS OPTIONAL. IT IS AN
/**     LE EXIT MODULE THAT CAN BE USED TO START DEBUG TOOL.
/**     UNDERSTAND THE METHODS AVAILABLE FOR STARTING DEBUG TOOL,
/**     AND CHOOSE WHETHER YOU WANT TO USE THE LE EXITS.
/**     IF YOU USE THIS METHOD, LOAD THE CORRECT EXIT MODULE:
/**     EQADBCXT: FOR BATCH PROGRAMS
/**     EQADICXT: FOR ONLINE IMS PROGRAMS
/**     EQADDCXT: FOR DB2 STORED PROCEDURES
/**     (DO NOT INCLUDE AN EXIT FOR CICS PROGRAMS)
/**
/** SET PARMS FOR THIS COMPILE:
/** -----
/**   SET MEM=PTEST                PROGRAM NAME
/**   SET PLICOMP='IBMZ.V3R4.SIBMZCMP'  PLI COMPILER LOADLIB
/**   SET DTLIB='EQAW.SEQAMOD'        DEBUG TOOL LOADLIB
/**   SET LEHLQ='CEE'                LE HIGH LVL QUALIFIER
/**   SET UNITDEV=SYSALLDA           UNIT FOR TEMP FILES
/**   SET LANGX='EQALANGX'           XXXLANGX UTILITY PROGRAM
/**   SET LANGXLIB='EQAW.SEQAMOD'     LIBRARY FOR XXXLANGX UTILITY
/**   NOTE: YOU CAN USE THE XXXLANGX UTILITY SHIPPED WITH DT, FA,
/**         OR APA. THEY NAMES ARE DIFFERENT, BUT RESULTS ARE THE SAME
/**         USE ANY OF THEM... THEY ALL PRODUCE THE SAME RESULTS.
/**   IF YOU HAVE:   SET LANGX TO:   SET LANGXLIB TO:
/**   DEBUG TOOL    EQALANGX         THE DT SEQAMOD LIBRARY
/**   FAULT ANALYZER IDILANGX        THE FA SIDIMOD1 LIBRARY
/**   APA           CAZLANGX          THE APA SCAZAUTH LIBRARY
/**

```

```

//ALLOCOBJ EXEC PGM=IEFBRI4          ALLOC OBJ LIB IF NEEDED
//XSOURCE DD DSN=&SYSUID..ADLAB.EXPANDED.SOURCE,SPACE=(CYL,(3,1,15)),
// DSORG=PO,RECFM=FB,LRECL=80,BLKSIZE=8000,DISP=(MOD,CATLG)
//OBJ DD DSN=&SYSUID..ADLAB.OBJ,SPACE=(CYL,(3,1,15)),
// DSORG=PO,RECFM=FB,LRECL=80,BLKSIZE=8000,DISP=(MOD,CATLG)
//* *****
//* PREPROCESS STEP (COMPILE STAGE 1)
//* *****
//PRECOMP EXEC PGM=IBMZPLI,REGION=0M,
// PARM=('MACRO,MDECK,NOCOMPILE,NOSYNTAX,INSOURCE')
//STEPLIB DD DSN=&PLICOMP,DISP=SHR
// DD DSN=&LEHLQ..SCEERUN,DISP=SHR
//SYSIN DD DISP=SHR,DSN=&SYSUID..ADLAB.SOURCE(&MEM)
//SYSLIB DD DISP=SHR,DSN=&SYSUID..ADLAB.COPYLIB
//SYSPRINT DD SYSOUT=*
//SYSUT1 DD SPACE=(1024,(200,50)),,CONTIG,ROUND),DCB=BLKSIZE=1024,
// UNIT=&UNITDEV
//SYSPUNCH DD DISP=SHR,DSN=&SYSUID..ADLAB.EXPANDED.SOURCE(&MEM)
//*
//* *****
//* COMPILE STEP (COMPILE STAGE 2)
//* *****
//COMPILE EXEC PGM=IBMZPLI,REGION=0M,
// PARM=('TEST(ALL),LIST,MAP,SOURCE,XREF(FULL),',
// 'NOBLKOFF,AGGREGATE,ATTRIBUTES(FULL),NEST,OPTIONS,NOPT,',
// 'STMT,NONUMBER,OFFSET')
//STEPLIB DD DSN=&PLICOMP,DISP=SHR
// DD DSN=&LEHLQ..SCEERUN,DISP=SHR
//SYSIN DD DISP=SHR,DSN=&SYSUID..ADLAB.EXPANDED.SOURCE(&MEM)
//SYSLIB DD DISP=SHR,DSN=&SYSUID..ADLAB.COPYLIB
//SYSPRINT DD DISP=SHR,DSN=&SYSUID..ADLAB.ENTPLI.LISTING(&MEM)
//SYSUT1 DD SPACE=(CYL,(5,2)),,CONTIG),DCB=BLKSIZE=1024,UNIT=&UNITDEV
//SYSLIN DD DSN=&SYSUID..ADLAB.OBJ(&MEM),DISP=SHR
//*
//PLIPRINT EXEC PGM=IEBGENER,REGION=0M
//SYSPRINT DD SYSOUT=*
//SYSUT1 DD DSN=&SYSUID..ADLAB.ENTPLI.LISTING(&MEM),DISP=SHR
//SYSUT2 DD SYSOUT=*
//SYSIN DD DUMMY
//*
//* *****
//* STEP TO GENERATE LANGX FILE
//* *****
//LANGX EXEC PGM=&LANGX,REGION=32M,
// PARM=('PLI ERROR 64K CREF')
//STEPLIB DD DISP=SHR,DSN=&LANGXLIB
// DD DISP=SHR,DSN=&LEHLQ..SCEERUN
//LISTING DD DSN=&SYSUID..ADLAB.ENTPLI.LISTING(&MEM),DISP=SHR
//IDILANGX DD DISP=SHR,DSN=&SYSUID..ADLAB.EQALANGX(&MEM)
//*
//* *****
//* LINK-EDIT (BINDER) STEP
//* *****
//LINK EXEC PGM=IEWL,PARM=(LET,MAP,LIST),REGION=0M
//SYSLIB DD DSN=&LEHLQ..SCEELKED,DISP=SHR
//DTLIB DD DSN=&DTLIB,DISP=SHR
//SYSPRINT DD SYSOUT=*
//SYSLMOD DD DISP=SHR,DSN=&SYSUID..ADLAB.LOAD(&MEM)
//SYSUT1 DD UNIT=SYSDA,SPACE=(TRK,(10,10))
//SYSLIN DD DSN=&SYSUID..ADLAB.OBJ(&MEM),DISP=(OLD,PASS)
//* INCLUDING A DEBUG TOOL LE EXIT (EQADBCXT, EQADCXT, OR EQADICXT)
//* IS OPTIONAL. THE EXIT ENABLES STARTING DEBUG TOOL WITH THE
//* USER EXIT DATA SET UTILITY (ONE OF THE DEBUG TOOL ISPF UTILITIES)
//* // DD *
//* INCLUDE DTLIB(EQADBCXT)

```

PL/I for MVS and VM and OS PL/I programs

The following table shows various compiler options that can be used to prepare Enterprise COBOL for z/OS Version 4 programs for use with the IBM Problem Determination Tools products (Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS). The methods suggested in the following table indicate if the load module produced is suitable for a production environment. Load modules suitable for a production environments have no significant run-time overhead.

For the test environment, you need both the listing and the LANGX file (for Fault Analyzer for z/OS and Application Performance Analyzer for z/OS). In production, only the LANGX file is suggested.

Table 11. Examples of compiler options and source information files supported by IBM Problem Determination Tools products for PL/I for MVS and VM and OS PL/I

| Compiler options | Source information file type produced | Is the load module production ready? | Options supported and suggested for Debug Tool for z/OS | Options supported and suggested for Fault Analyzer for z/OS | Options supported and suggested for Application Performance Analyzer for z/OS |
|---|---------------------------------------|--------------------------------------|--|---|---|
| TEST(ALL), AGGREGATE, ATTRIBUTES (FULL), ESD, LIST, MAP, NEST, NOPT, OPTIONS, SOURCE, STMT, XREF(FULL) | Compiler listing | No | Suggested for test. (Using Debug Tool in production for this compiler is not recommended.) | Supported | Supported |
| | LANGX file | No | N/A | Supported | N/A |
| NOTEST, AGGREGATE, ATTRIBUTES (FULL), ESD, LIST, MAP, NEST, OPTIONS, SOURCE, STMT, XREF(FULL) | Compiler listing | Yes | N/A | Supported | Suggested for production and test |
| | LANGX file | Yes | N/A | Suggested for production and test | N/A |

Note: The highlighted row or rows in the table above indicate the suggested compiler options and source information file types for each product.

Preparing PL/I for MVS and VM and OS PL/I programs

Perform the following steps for compiling your PL/I for MVS and VM and OS PL/I programs:

- Create a library (PDSE is suggested unless PDS is required for your organization) for compiler listing files. This is only needed in test environments where debugging will be performed. Specify LRECL=125 minimum, RECFM=VBA, BLKSIZE= 1recl+4 to 32k.
- Allocate libraries (PDSE is suggested unless PDS is required for your organization) for LANGX files. Allocate one or more LANGX libraries for each environment, such as test and production.
- Create a corresponding LANGX library for each load library. Specify LRECL=1562 or greater, RECFM=VB, BLKSIZE= 1recl+4 to 32k.
- For all programs, such as batch, CICS, and IMS:

- In test environments, specify compiler options TEST(ALL), NOOPT, AGGREGATE, ATTRIBUTES(FULL), ESD, LIST, MAP, NEST, OPTIONS, SOURCE, STMT, XREF(FULL).

TEST(ALL) and NOOPT are required by Debug Tool. TEST adds debug hooks, which add some runtime overhead. Symbolic data required by Debug Tool is stored in the module, which can make it significantly larger.

The other options format the compiler listing as required by Debug Tool and by the *xxxLANGX* utility.

- In production environments, specify compiler options NOTEST, AGGREGATE, ATTRIBUTES(FULL), ESD, LIST, MAP, NEST, OPTIONS, SOURCE, STMT, XREF(FULL).

NOTEST disables Debug Tool, but provides the best performance.

The other options format the compiler listing as required for the *xxxLANGX* utility.

This produces a production-ready module that can be used with Fault Analyzer for z/OS and Application Performance Analyzer for z/OS but not Debug Tool for z/OS.

- Modify the SYSPRINT DD in the compiler step. This is the compiler listing. Save this to a permanent file. The compiler listing is the input to the *xxxLANGX* utility and is the source information file for Debug Tool for z/OS

Note: This compiler typically renames CSECTs according to an internal compiler algorithm. Therefore, it is not recommended to store PL/I compiler listings or side files using CSECT names as they might not be found by Application Performance Analyzer for z/OS or Fault Analyzer for z/OS. Instead, use the primary entry point name.

- Add a step after the compiler step to run the *xxxLANGX* utility. This utility reads the compiler listing and saves a LANGX file. This is the source information file for Fault Analyzer for z/OS and Application Performance Analyzer for z/OS. Equivalent *xxxLANGX* utilities are available in Debug Tool for z/OS as EQALANGX, in Fault Analyzer for z/OS as IDILANGX and in Application Performance Analyzer for z/OS as CAZLANGX. Save it in the LANGX file library and specify a member name that is equal to the primary entry point name of your application program.
- Modify the promotion process to promote LANGX files. When a load module is promoted, for example, from test to production, promote the corresponding LANGX file or files. A promotion can be a recompile, copy, or move. Perform the same steps with the LANGX file that you perform with the module during promotion.
- Optionally, include a Debug Tool Language Environment exit module into the load module during the linkage editor step. This is one way to enable Debug Tool's panel 6 in ISPF, a simple panel-driven method to start the debugger automatically when a program runs, without JCL changes, based on the program name and user ID. Use module EQADBCXT for batch programs (including IMS batch), EQADICXT for IMS/TM programs and EQADDCXT for DB2 stored procedures. Do not include the exit module for CICS programs.
- For CICS applications only, if the Debug Tool DTCN transaction will be used to start Debug Tool, link-edit the Debug Tool CICS startup exit module EQADCCXT into the application load module to enable Debug Tool in CICS. This is not needed if using the CADP transaction instead of DTCN.

Sample JCL

Below is a JCL example for compiling an PL/I for MVS and VM program for use with the IBM Problem Determination Tools products.

```
/*      - - - ADD A JOB CARD ABOVE THIS LINE - - -
/*
/* SAMPLE JCL TO PREPARE A PLI FOR MVS AND VM PROGRAM
/* FOR THE IBM ZSERIES PD TOOLS PRODUCTS:
/*     FAULT ANALYZER, DEBUG TOOL, AND APPLICATION PERF. ANALYZER
/*
/* NOTES:
/*
/* COMPILER:
/* 1. COMPILER PARM TEST IS REQUIRED FOR DEBUG TOOL
/* 2. COMPILER PARMS AGGREGATE,ATTRIBUTES(FULL),ESD,LIST,
/*    MAP,NEST,OPTIONS,SOURCE,STMT,XREF(FULL) ARE NEEDED
/*    FOR PD TOOLS TO PROCESS THE COMPILER LISTING
/*
/* BINDER (LINKAGE EDITOR):
/* 3. THE INCLUDE FOR MODULE EQAD?CXT IS OPTIONAL. IT IS AN
/*    LE EXIT MODULE THAT CAN BE USED TO START DEBUG TOOL.
/*    UNDERSTAND THE METHODS AVAILABLE FOR STARTING DEBUG TOOL,
/*    AND CHOOSE WHETHER YOU WANT TO USE THE LE EXITS.
/*    IF YOU USE THIS METHOD, LOAD THE CORRECT EXIT MODULE:
/*    EQADBCXT: FOR BATCH PROGRAMS
/*    EQADICXT: FOR ONLINE IMS PROGRAMS
/*    EQADDCXT: FOR DB2 STORED PROCEDURES
/*    (DO NOT INCLUDE AN EXIT FOR CICS PROGRAMS)
/*
/* SET PARMS FOR THIS COMPILE:
/* -----
/* SET MEM=PADSTAT                PROGRAM NAME
/* SET PLICOMP='IEL.V1R1M1.SIELCOMP'  PLI COMPILER LOADLIB
/* SET DTLIB='EQAW.SEQAMOD'          DEBUG TOOL LOADLIB
/* SET LEHLQ='CEE'                  LE HIGH LVL QUALIFIER
/* SET UNITDEV=SYSALLDA             UNIT FOR TEMP FILES
/* SET LANGX='EQALANGX'             XXXLANGX UTILITY PROGRAM
/* SET LANGXLIB='EQAW.SEQAMOD'       LIBRARY FOR XXXLANGX UTILITY
/* NOTE: YOU CAN USE THE XXXLANGX UTILITY SHIPPED WITH DT, FA,
/* OR APA. THE NAMES ARE DIFFERENT, BUT RESULTS ARE THE SAME
/* USE ANY OF THEM... THEY ALL PRODUCE THE SAME RESULTS.
/* IF YOU HAVE:      SET LANGX TO:  SET LANGXLIB TO:
/* DEBUG TOOL        EQALANGX       THE DT SEQAMOD LIBRARY
/* FAULT ANALYZER    IDILANGX        THE FA SIDIMOD1 LIBRARY
/* APA                CAZLANGX        THE APA SCAZAUTH LIBRARY
/*
/*ALLOCOBJ EXEC PGM=IEFBR14          ALLOC OBJ LIB IF NEEDED
/*OBJ DD DSN=&SYSUID..ADLAB.OBJ,SPACE=(CYL,(3,1,15)),
/* DSORG=PO,RECFM=FB,LRECL=80,BLKSIZE=8000,DISP=(MOD,CATLG)
/*
/* *****
/* COMPILE STEP
/* *****
/*
/*COMPILE EXEC PGM=IEL1AA,REGION=6M,
/* PARM=('TEST(ALL),NOPT,AGGREGATE,ATTRIBUTES(FULL),ESD,LIST,MAP,',
/*      'NEST,OPTIONS,SOURCE,STMT,XREF(FULL)')
/*STEPLIB DD DSN=&PLICOMP,DISP=SHR
/*SYSIN DD DISP=SHR,DSN=&SYSUID..ADLAB.SOURCE(&MEM)
/*SYSLIB DD DISP=SHR,DSN=&SYSUID..ADLAB.COPYLIB
/*SYSPRINT DD DISP=SHR,DSN=&SYSUID..ADLAB.PLIMVS.LISTING(&MEM)
/*SYSUT1 DD SPACE=(CYL,(1,1)),UNIT=SYSDA
/*SYSLIN DD DSN=&SYSUID..ADLAB.OBJ(&MEM),DISP=SHR
/*
/*PLIPRINT EXEC PGM=IEBGENER,REGION=0M
/*SYSPRINT DD SYSOUT=*
/*SYSUT1 DD DSN=&SYSUID..ADLAB.PLIMVS.LISTING(&MEM),DISP=SHR
```

```

//SYSUT2 DD SYSOUT=*
//SYSIN DD DUMMY
//*
//* *****
//* STEP TO GENERATE LANGX FILE
//* *****
//LANGX EXEC PGM=&LANGX,REGION=32M,
// PARM='(PLI ERROR 64K CREF'
//STEPLIB DD DISP=SHR,DSN=&LANGXLIB
// DD DISP=SHR,DSN=&LEHLQ..SCEERUN
//LISTING DD DSN=&SYSUID..ADLAB.PLIMVS.LISTING(&MEM),DISP=SHR
//IDILANGX DD DISP=SHR,DSN=&SYSUID..ADLAB.EQALANGX(&MEM)
//*
//* *****
//* LINK-EDIT (BINDER) STEP
//* *****
//LINK EXEC PGM=IEWL,PARM=(LET,MAP,LIST),REGION=0M
//SYSLIB DD DSN=&LEHLQ..SCEELKED,DISP=SHR
//DTLIB DD DSN=&DTLIB,DISP=SHR
//SYSPRINT DD SYSOUT=*
//SYSMOD DD DISP=SHR,DSN=&SYSUID..ADLAB.LOAD(&MEM)
//SYSUT1 DD UNIT=SYSDA,SPACE=(TRK,(10,10))
//SYSLIN DD DSN=&SYSUID..ADLAB.OBJ(&MEM),DISP=(OLD,PASS)
//* INCLUDING A DEBUG TOOL LE EXIT (EQADBCXT, EQADCXT, OR EQADICXT)
//* IS OPTIONAL. THE EXIT ENABLES STARTING DEBUG TOOL WITH THE
//* USER EXIT DATA SET UTILITY (ONE OF THE DEBUG TOOL ISPF UTILITIES)
//* // DD *
//* INCLUDE DTLIB(EQADBCXT)

```

z/OS XL C and C++ programs

The following table shows various compiler options that can be used to prepare z/OS XL C and C++ programs for use with the IBM Problem Determination Tools products (Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS). The methods suggested in the following table indicate if the load module produced is suitable for a production environment. Load modules suitable for a production environments have no significant run-time overhead.

Table 12. Examples of compiler options and source information files supported by IBM Problem Determination Tools products for C++

| Compiler options | Output produced | Is the load module production ready? | Options supported and suggested for Debug Tool for z/OS | Options supported and suggested for Fault Analyzer for z/OS | Options supported and suggested for Application Performance Analyzer for z/OS |
|--|--|--------------------------------------|--|---|---|
| Preprocess (1st stage) to expand source, In compile (2nd stage): TEST, AGGREGATE, ATTRIBUTES (FULL), ESD, LIST, MAP, NEST, OPTIONS, SOURCE, STMT, XREF(FULL), NOOFFSET, NOOPT, NOIPA | Expanded source file used by Debug Tool for z/OS, compiler listing used by Fault Analyzer for z/OS and Application Performance Analyzer for z/OS | No | Suggested for test. (Using Debug Tool in production for this compiler is not recommended.) | Supported | Supported |
| | Expanded source file used by Debug Tool for z/OS, LANGX file used by Fault Analyzer for z/OS and Application Performance Analyzer for z/OS | No | Supported | Supported | Supported |
| NOTEST, AGGREGATE, ATTRIBUTES (FULL), ESD, LIST, MAP, NEST, OPTIONS, SOURCE, STMT, XREF(FULL), NOOFFSET, NOIPA | Compiler listing | Yes | N/A | Suggested for production and test | Suggested for production and test |
| | LANGX file | Yes | N/A | Supported | Supported |
| Preprocess (1st stage) to expand source. In compile (2nd stage): DEBUG(FORMAT (DWARF), HOOK(LINE, NOBLOCK, PATH), SYMBOL, FILE(location)) | Expanded source file and DWARF file | No | Supported. (Using Debug Tool in production for this compiler is not recommended.) | N/A | N/A |

Notes:

1. The highlighted row or rows in the table above indicate the suggested compiler options and source information file types for each product.
2. The FORMAT(DWARF) option is supported for z/OS Version 1.6 and higher.

Table 13. Examples of compiler options and source information files supported by IBM Problem Determination Tools products for C

| Compiler options | Output produced | Is the load module production ready? | Options supported and suggested for Debug Tool for z/OS | Options supported and suggested for Fault Analyzer for z/OS | Options supported and suggested for Application Performance Analyzer for z/OS |
|---|--|--------------------------------------|--|---|---|
| Preprocess (1st stage) to expand source, In compile (2nd stage): TEST(ALL), AGGREGATE, ATTRIBUTES (FULL), ESD, LIST, MAP, NEST, OPTIONS, SOURCE, STMT, XREF(FULL), NOOFFSET, NOOPT, NOIPA | Expanded source file used by Debug Tool for z/OS, compiler listing used by Fault Analyzer for z/OS and Application Performance Analyzer for z/OS | No | Suggested for test. (Using Debug Tool in production for this compiler is not recommended.) | Supported | Supported |
| | Expanded source file used by Debug Tool for z/OS, LANGX file used by Fault Analyzer for z/OS and Application Performance Analyzer for z/OS | No | Supported | Supported | Supported |
| NOTEST, AGGREGATE, ATTRIBUTES (FULL), ESD, LIST, MAP, NEST, OPTIONS, SOURCE, STMT, XREF(FULL), NOOFFSET, NOIPA | Compiler listing | Yes | N/A | Suggested for production and test | Suggested for production and test |
| | LANGX file | Yes | N/A | Supported | Supported |
| Preprocess (1st stage) to expand source. In compile (2nd stage): DEBUG(FORMAT (DWARF), HOOK(LINE, NOBLOCK, PATH), SYMBOL, FILE(location)) | Expanded source file and DWARF file | No | Supported. (Using Debug Tool in production for this compiler is not recommended.) | N/A | N/A |

Notes:

1. The highlighted row or rows in the table above indicate the suggested compiler options and source information file types for each product.
2. The FORMAT(DWARF) option is supported for z/OS Version 1.6 and higher.

Preparing z/OS XL C and C++ programs

Perform the following steps for compiling your z/OS XL C and C++ programs:

- Create a library (PDSE is suggested unless PDS is required for your organization) for expanded source files. This is only needed in test environments where debugging will be performed. This can be any RECFM / LRECL / BLKSIZE supported as input by the compiler.
- Allocate libraries (PDSE is suggested unless PDS is required for your organization) for compiler listing files. Allocate one or more compiler listing libraries for each environment, such as test and production.
- Create a corresponding listing library for each load library. Specify LRECL=133,RECFM=FBA,BLKSIZE=(multiple of lrecl up to 32k) or LRECL=137 or greater, RECFM=VBA,BLKSIZE= lrecl+4 to 32k.
- Run a 2-stage compile. The first stage preprocesses the program, so the IBM Problem Determination Tools products have access to fully expanded source code. The second stage compiles the program.
 - In the first compile stage, in both test and production environments:
 - Specify compiler options PP(COMMENTS,NOLINES) to expand INCLUDEs and macros. The output is SYSUT10 DD, which is the expanded source file and is the input for the second compiler stage.
 - Modify the SYSUT10 DD to enable Debug Tool, by saving it in a expanded source library and specify a member name that is equal to the primary entry point name or CSECT name of your application program.
 - For all programs, such as batch, CICS, and IMS, for the second compiler stage:
 - In test environments:
 - For C++, specify compiler options TEST, NOOPT, NOIPA, AGGREGATE, ATTRIBUTES(FULL), ESD, LIST, MAP, NEST, OPTIONS, NOOFFSET, SOURCE, STMT, XREF(FULL).

TEST and NOOPT are required by Debug Tool. Debug hooks are inserted, which will adds runtime overhead. Symbolic data required by Debug Tool is stored in the module, which can make it significantly larger.

The other options format the compiler listing as required by Fault Analyzer for z/OS and Application Performance Analyzer for z/OS.
 - For C, specify compiler options TEST(ALL), NOOPT, NOIPA, AGGREGATE, ATTRIBUTES(FULL), ESD, LIST, MAP, NEST, OPTIONS, NOOFFSET, SOURCE, STMT, XREF(FULL).

TEST(ALL) and NOOPT are required by Debug Tool. Debug hooks are inserted, which adds runtime overhead. Symbolic data required by Debug Tool is stored in the module, which can make it significantly larger.

The other options format the compiler listing as required by Fault Analyzer for z/OS and Application Performance Analyzer for z/OS.
 - In production environments, specify compiler options NOTEST, AGGREGATE, ATTRIBUTES(FULL), NOIPA, ESD, LIST, MAP, NEST, NOOFFSET, OPTIONS, SOURCE, STMT, XREF(FULL).

NOTEST disables Debug Tool, but provides the best performance. This produces a production-ready module that can be used with Fault Analyzer for z/OS and Application Performance Analyzer for z/OS, but not Debug Tool for z/OS.

The other options format the compiler listing as required for Fault Analyzer for z/OS and Application Performance Analyzer for z/OS.

- Modify the SYSCPRT DD in the second compiler stage to refer to a file. This is the compiler listing and is the source information file for Fault Analyzer for z/OS and Application Performance Analyzer for z/OS. Save it in the compiler listing library and specify a member that is equal to the CSECT name of your application program.

```
//SYSCPRT DD DSN=compiler.listing.pds(csect-name),DISP=SHR
```

Note: To enable source support in Fault Analyzer, it is a requirement that CSECTs in C programs are named using:

```
#pragma csect(code, "csect_name")
```

where, if using a PDS(E), *csect_name* matches the compiler listing or LANGX file member name.

- Modify the promotion process to promote compiler listing files. When a load module is promoted, for example, from test to production, promote the corresponding compiler listing file or files. A promotion can be a recompile, copy, or move. Perform the same steps with the compiler listing file that you perform with the module during promotion.
- Optionally, include a Debug Tool Language Environment exit module into the load module during the linkage editor step. This is one way to enable Debug Tool's panel 6 in ISPF, a simple panel-driven method to start the debugger automatically when a program runs, without JCL changes, based on the program name and user ID. Use module EQADBCXT for batch programs (including IMS batch), EQADICXT for IMS/TM programs and EQADDCXT for DB2 stored procedures. Do not include the exit module for CICS programs.
- For CICS applications only: if the Debug Tool DTCN transaction will be used to start Debug Tool, link edit the Debug Tool CICS startup exit module EQADCCXT into the application load module to enable Debug Tool in CICS. This is not needed if using the CADP transaction instead of DTCN.

Sample JCL

Below is a JCL example for compiling an z/OS C/C++ program for use with the IBM Problem Determination Tools products.

```

/** ADD A JOB CARD HERE
/**
/**
/** SAMPLE JCL TO PREPARE A Z/OS C PROGRAM PROGRAM
/** FOR THE IBM ZSERIES PD TOOLS PRODUCTS:
/**   FAULT ANALYZER, DEBUG TOOL, AND APPLICATION PERF. ANALYZER
/**
/** NOTES:
/**
/** COMPILER:
/** 1. A 2-STAGE COMPILE IS PERFORMED. STAGE 1 (PREPROCESS) IS
/**   DONE TO EXPAND INCLUDES AND MACROS IN THE PROGRAM AND TO
/**   PRODUCE AN EXPANDED SOURCE FILE.
/** 2. THE EXPANDED SOURCE FILE IS RETAINED. IT IS USED BY
/**   DEBUG TOOL.
/** 2. COMPILER PARMS TEST AND NOOPT ARE REQUIRED FOR DEBUG TOOL.
/** 3. COMPILER PARMS AGGREGATE, NOIPA, LIST, NOOFFSET, SOURCE,
/**   STMT, AND XREF(FULL) ARE NEEDED TO FORMAT THE COMPILER LISTING
/**   SO THAT IT CAN BE PROCESSED WITH XXXLANGX
/**
/** A STEP RUNS TO PRODUCE A LANGX FILE FOR FAULT ANALYZER AND APA.
/** NOTE: YOU CAN USE THE XXXLANGX UTILITY SHIPPED WITH DT, FA,
/**   OR APA. THE NAMES ARE DIFFERENT, BUT THE RESULTS ARE THE SAME.
/**   USE ANY OF THEM... THEY ALL PRODUCE THE SAME RESULTS.
/** IF YOU HAVE: THEN EXECUTE MODULE:
/** DEBUG TOOL   EQALANGX, AND ENSURE THAT THE DT SEQAMOD LIBRARY

```

```

/**          IS AVAILABLE (VIA STEPLIB, JOBLIB, OR LINKLIST)
/**    FAULT ANALYZER  IDILANGX, AND ENSURE THAT THE FA SIDIMOD1 LIBRARY
/**          IS AVAILABLE (VIA STEPLIB, JOBLIB, OR LINKLIST)
/**    APA            CAZLANGX, AND ENSURE THAT THE APA SCAZAUTH LIBRARY
/**          IS AVAILABLE (VIA STEPLIB, JOBLIB, OR LINKLIST)
/**
/**    BINDER (LINKAGE EDITOR):
/**    1. AN INCLUDE FOR MODULE EQAD?CXT IS OPTIONAL.  IT IS AN
/**       LE EXIT MODULE THAT CAN BE USED TO START DEBUG TOOL.
/**       UNDERSTAND THE METHODS AVAILABLE FOR STARTING DEBUG TOOL,
/**       AND CHOOSE WHETHER YOU WANT TO USE THE LE EXITS.
/**       IF YOU USE THIS METHOD, INCLUDE THE CORRECT EXIT MODULE:
/**           EQADBCXT: FOR BATCH PROGRAMS
/**           EQADICXT: FOR ONLINE IMS PROGRAMS
/**           EQADDCXT: FOR DB2 STORED PROCEDURES
/**           (DO NOT INCLUDE AN EXIT FOR CICS PROGRAMS)
/**
/**    SET PARMS FOR THIS COMPILE:
/**    -----
/**           CPRFX: THE PREFIX THE C/C++ COMPILE IS INSTALLED UNDER
/**           LEPRFX: THE PREFIX FOR THE LE RUNTIME AND LINK LIBS
/**           DTPRFX: THE PREFIX OF THE DEBUG TOOL SEQAMOD LIBRARY
/**
/**           SET CPRFX=CBC
/**           SET LEPRFX=CEE
/**           SET DTPRFX=EQAW
/**
/*******
/**    CREATE C/C++ COMPILER LISTING SYSPRINT, EXPANDED SOURCE DEBUG, */
/**    AND EQALANGX FILES                                           */
/*******
/**    ALLOC EXEC PGM=IEFBR14
/**    LISTING DD DSN=&SYSUID..ADLAB.CLST,
/**              DISP=(MOD,CATLG),
/**              DCB=(DSORG=PO,RECFM=VBA,LRECL=137,BLKSIZE=0),
/**              SPACE=(TRK,(20,20,50)),UNIT=SYSDA
/**    DBGSRC  DD DSN=&SYSUID..ADLAB.CDBG,
/**              DISP=(MOD,CATLG),
/**              DCB=(DSORG=PO,RECFM=FB,LRECL=80,BLKSIZE=0),
/**              SPACE=(TRK,(20,20,50)),UNIT=SYSDA
/**    LANGX   DD DSN=&SYSUID..ADLAB.EQALANGX,
/**              DISP=(MOD,CATLG),
/**              DCB=(DSORG=PO,RECFM=VB,LRECL=1562,BLKSIZE=0),
/**              SPACE=(TRK,(40,40,50)),UNIT=SYSDA
/**
/**
/*******
/**-----
/**    COMPILE STEP1: GENERATE EXPANDED C/C++ SOURCE FILE IN THE DD
/**                   SYSUT10
/**-----
/**    COMP1  EXEC PGM=CCNDRVR,REGION=0M,
/**    PARM=('PP(COMMENTS,NOLINES)')
/**    STEPLIB DD DSNAME=&LEPRFX..SCEERUN2,DISP=SHR
/**           DD DSNAME=&CPRFX..SCCNCMP,DISP=SHR
/**    SYSMMSG DD DUMMY,DSN=&CPRFX..SCBC3MSG(EDCMSGE),DISP=SHR
/**    SYSLIB  DD DSNAME=&LEPRFX..SCEEH.H,DISP=SHR
/**           DD DSNAME=&LEPRFX..SCEEH.SYS.H,DISP=SHR
/**           DD DSNAME=&SYSUID..ADLAB.COPYLIB,DISP=SHR
/**    SYSPRINT DD SYSOUT=*
/**    SYSOUT  DD SYSOUT=*
/**    SYSCPRT DD SYSOUT=*
/**    SYSUT1  DD UNIT=SYSDA,SPACE=(32000,(30,30)),
/**           DCB=(RECFM=FB,LRECL=80,BLKSIZE=3200)
/**    SYSUT5  DD UNIT=SYSDA,SPACE=(32000,(30,30)),
/**           DCB=(RECFM=FB,LRECL=3200,BLKSIZE=12800)
/**    SYSUT6  DD UNIT=SYSDA,SPACE=(32000,(30,30)),
/**           DCB=(RECFM=FB,LRECL=3200,BLKSIZE=12800)

```

```

//SYSUT7 DD UNIT=SYSDA,SPACE=(32000,(30,30)),
// DCB=(RECFM=FB,LRECL=3200,BLKSIZE=12800)
//SYSUT8 DD UNIT=SYSDA,SPACE=(32000,(30,30)),
// DCB=(RECFM=FB,LRECL=3200,BLKSIZE=12800)
//SYSUT9 DD UNIT=SYSDA,SPACE=(32000,(30,30)),
// DCB=(RECFM=VB,LRECL=137,BLKSIZE=882)
//SYSUT10 DD DISP=SHR,DSN=&SYSUID..ADLAB.CDBG(TMC01A)
//SYSUT14 DD UNIT=SYSDA,SPACE=(32000,(30,30)),
// DCB=(RECFM=FB,LRECL=3200,BLKSIZE=12800)
//SYSUT16 DD UNIT=SYSDA,SPACE=(32000,(30,30)),
// DCB=(RECFM=FB,LRECL=3200,BLKSIZE=12800)
//SYSUT17 DD UNIT=SYSDA,SPACE=(32000,(30,30)),
// DCB=(RECFM=FB,LRECL=3200,BLKSIZE=12800)
//SYSLIN DD DUMMY
//SYSIN DD DSNNAME=&SYSUID..ADLAB.SOURCE(TMC01A),DISP=SHR
//*
/*-----
/* COMPILE STEP2: COMPILE THE EXPANDED SOURCE FILE WITH THE DEBUG
/* COMPILER OPTION TEST(ALL)
/*-----
//COMP2 EXEC PGM=CCNDRVR,REGION=0M,
// PARM=('TEST(ALL),AGGREGATE,ATTRIBUTES(FULL),ESD,LIST,MAP,',
// 'NEST,OPTIONS,SOURCE,STMT,XREF(FULL),NOOFFSET,NOOPT,NOIPA')
//STEPLIB DD DSNNAME=&LEPRFX..SCEERUN2,DISP=SHR
// DD DSNNAME=&CPRFX..SCCNCP,DISP=SHR
// DD DSNNAME=&LEPRFX..SCEERUN,DISP=SHR
//SYMSGS DD DUMMY,DSN=&CPRFX..SCBC3MSG(EDCMSGE),DISP=SHR
//SYSLIB DD DSNNAME=&LEPRFX..SCEEH.H,DISP=SHR
// DD DSNNAME=&LEPRFX..SCEEH.SYS.H,DISP=SHR
//SYSCPRT DD DISP=SHR,DSN=&SYSUID..ADLAB.CLST(TMC01A)
//SYSOUT DD SYSOUT=*
//SYSPRINT DD SYSOUT=*
//SYSUT1 DD UNIT=SYSDA,SPACE=(32000,(30,30)),
// DCB=(RECFM=FB,LRECL=80,BLKSIZE=3200)
//SYSUT5 DD UNIT=SYSDA,SPACE=(32000,(30,30)),
// DCB=(RECFM=FB,LRECL=3200,BLKSIZE=12800)
//SYSUT6 DD UNIT=SYSDA,SPACE=(32000,(30,30)),
// DCB=(RECFM=FB,LRECL=3200,BLKSIZE=12800)
//SYSUT7 DD UNIT=SYSDA,SPACE=(32000,(30,30)),
// DCB=(RECFM=FB,LRECL=3200,BLKSIZE=12800)
//SYSUT8 DD UNIT=SYSDA,SPACE=(32000,(30,30)),
// DCB=(RECFM=FB,LRECL=3200,BLKSIZE=12800)
//SYSUT9 DD UNIT=SYSDA,SPACE=(32000,(30,30)),
// DCB=(RECFM=VB,LRECL=137,BLKSIZE=882)
//SYSUT10 DD SYSOUT=*
//SYSUT14 DD UNIT=SYSDA,SPACE=(32000,(30,30)),
// DCB=(RECFM=FB,LRECL=3200,BLKSIZE=12800)
//SYSUT16 DD UNIT=SYSDA,SPACE=(32000,(30,30)),
// DCB=(RECFM=FB,LRECL=3200,BLKSIZE=12800)
//SYSUT17 DD UNIT=SYSDA,SPACE=(32000,(30,30)),
// DCB=(RECFM=FB,LRECL=3200,BLKSIZE=12800)
//SYSLIN DD DSN=&&TEMOBJ1(TMC01A),DISP=(,PASS),UNIT=SYSDA,
// SPACE=(TRK,(20,20,20)),DCB=(RECFM=FB,BLKSIZE=3120,LRECL=80,DSORG=PO)
//SYSIN DD DSNNAME=&SYSUID..ADLAB.CDBG(TMC01A),DISP=SHR
//*
/*-----
/* LINK STEP: LINK THE COMPILED OBJECT DECK
/*-----
//LKED EXEC PGM=IEWL,PARM=(LET,MAP,LIST)
//SYSLIB DD DSN=&LEPRFX..SCEELKED,DISP=SHR
//SYSPRINT DD SYSOUT=*
//SYSLMOD DD DISP=SHR,DSN=&SYSUID..ADLAB.LOAD
//SYSUT1 DD SPACE=(TRK,(10,10)),UNIT=SYSDA
//OBJECT DD DISP=(OLD,PASS),DSN=&&TEMOBJ1
/* DTLIB DD DSN=&DTPRFX..SEQAMOD,DISP=SHR
//SYSLIN DD *
INCLUDE OBJECT(TMC01A)

```

```

ENTRY CEESTART
NAME TMC01(R)
/*
/** INCLUDING A DEBUG TOOL LE EXIT (EQADBCXT, EQADCXT, OR EQADICXT)
/** IS OPTIONAL. THE EXIT ENABLES STARTING DEBUG TOOL WITH THE
/** USER EXIT DATA SET UTILITY (ONE OF THE DEBUG TOOL ISPF UTILITIES).
/** AN INCLUDE CAN BE ADDED TO SYSLIN IN THE APPROPRIATE SEQUENCE:
/** INCLUDE DTLIB(EQADBCXT)
/*******
/** GENERATE THE TMC01A EQALANGX FILE
/*******
//LANGX1 EXEC PGM=EQALANGX,REGION=32M,
// PARM='(C ERROR'
//STEPLIB DD DISP=SHR,DSN=&DTPRFX..SEQAMOD
          DD DISP=SHR,DSN=&LEPRFX..SCEERUN
//LISTING DD DSN=&SYSUID..ADLAB.CLST(TMC01A),DISP=SHR
//IDILANGX DD DSN=&SYSUID..ADLAB.EQALANGX(TMC01AX),DISP=(OLD)

```

Assembler programs

The following table shows various assembler options that can be used to prepare programs for use with the IBM Problem Determination Tools products (Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS). The methods suggested in the following table indicate if the load module produced is suitable for a production environment. Load modules suitable for a production environments have no significant run-time overhead.

Table 14. Examples of assembler options and source information files supported by IBM Problem Determination Tools products for Assembler

| Assembler options | Source information file type produced | Is the load module production ready? | Options supported and suggested for Debug Tool for z/OS | Options supported and suggested for Fault Analyzer for z/OS | Options supported and suggested for Application Performance Analyzer for z/OS |
|-------------------|---------------------------------------|--------------------------------------|---|---|---|
| ADATA | SYSADATA file | Yes | N/A | Supported | Supported |
| ADATA | LANGX file | Yes | Suggested for production and test | | |

Note: The highlighted row or rows in the table above indicate the suggested compiler options and source information file types for each product.

Preparing Assembler programs

Perform the following steps for assembling your programs:

- Allocate libraries (PDSE is suggested unless PDS is required for your organization) for LANGX files. Allocate one or more LANGX libraries for each environment, such as test and production.
- Create a corresponding LANGX library for each load library. Specify LRECL=1562 or greater, RECFM=VB, BLKSIZE= lrecl+4 to 32k.
- For all programs, such as batch, CICS, and IMS, in both test and production environments, specify ADATA.

ADATA instructs the assembler to produce a SYSADATA file, which contains source and symbolic data about the program. This produces a production-ready module that can be debugged using Debug Tool for z/OS. ADATA does not affect the contents of the assembled module.

- Add a SYSADATA DD in the assembler step. This file is created by the assembler and it can be a permanent or temporary file. Specify LRECL=8188 or greater, RECFM=VB, BLKSIZE= 1rec1+4 to 32k. This file is the input to the xxxLANGX utility.
- Add a step after the assembler step to run the xxxLANGX utility. The xxxLANGX utility reads the SYSADATA file and creates a LANGX file. The LANGX file is the source information file for Debug Tool for z/OS, Fault Analyzer for z/OS and Application Performance Analyzer for z/OS. Equivalent xxxLANGX utilities are available in Debug Tool for z/OS as EQALANGX, in Fault Analyzer for z/OS as IDILANGX and in Application Performance Analyzer for z/OS as CAZLANGX.
- Save the LANGX file in the LANGX file library, and specify a member name that is equal to one of the following:
 - Use the CSECT name or the load module name. Using the CSECT name is preferable to using the load module name, as there is less overhead in locating the member. Also, the load module name should not be used if the assembler CSECT is only a subroutine.
- Modify the promotion process to promote LANGX files. When a load module is promoted, for example, from test to production, promote the corresponding LANGX file or files. A promotion can be a recompile, copy, or move. Perform the same steps with the LANGX file that you perform with the module during promotion.
- If the assembler program is Language Environment-enabled, optionally include a Debug Tool Language Environment exit module into the load module during the linkage editor step. This is one way to enable Debug Tool's panel 6 in ISPF, a simple panel-driven method to start the debugger automatically when a program runs, without JCL changes, based on the program name and user ID. Use module EQADBCXT for batch programs (including IMS batch), EQADICXT for IMS/TM programs and EQADDCXT for DB2 stored procedures. Do not include the exit module for CICS programs.
- For CICS programs only: If the program is a CICS main program, is enabled for Language Environment, and the Debug Tool DTCN transaction will be used to start Debug Tool, then supplied module EQADCCXT must be included in the load module during the linkage editor step.

Sample JCL

Below is a JCL example for assembling a program for use with the IBM Problem Determination Tools products.

```

/**      - - - ADD A JOB CARD ABOVE THIS LINE - - -
/**
/** SAMPLE JCL TO PREPARE AN ASSEMBLER PROGRAM
/** FOR THE IBM ZSERIES PD TOOLS PRODUCTS:
/**   FAULT ANALYZER, DEBUG TOOL, AND APPLICATION PERF. ANALYZER
/**
/** NOTES:
/**
/**   ASSEMBLER:
/**     1. AN ADATA PARM IS REQUIRED TO PRODUCE A SYSADATA FILE
/**
/**   A STEP THAT PROCESSES THE SYSADATA FILE,
/**   AND CREATES A LANGX FILE IS NEEDED.
/**
/**   BINDER (LINKAGE EDITOR):
/**     1. AMODE / RMODE CAN BE CODED AS NEEDED BY THE PROGRAM.  THEY ARE
/**       NOT REQUIRED FOR PD TOOLS.
/**
/** SET PARMS FOR THIS COMPILE:
/** -----

```



```

// SET MEM=ASAM1                                PROGRAM NAME
// SET Language EnvironmentHLQ='CEE'            Language Environment HIGH LVL QUALIFIER
// SET UNITDEV=SYSALLDA                          UNIT FOR TEMP FILES
// SET LANGX='EQALANGX'                          XXXLANGX UTILITY PROGRAM
// SET LANGXLIB='EQAW.SEQAMOD'                   LIBRARY FOR XXXLANGX UTILITY
//* NOTE: YOU CAN USE THE XXXLANGX UTILITY SHIPPED WITH DT, FA,
//* OR APA. THE NAMES ARE DIFFERENT, BUT RESULTS ARE THE SAME
//* USE ANY OF THEM... THEY ALL PRODUCE THE SAME RESULTS.
//* IF YOU HAVE:      SET LANGX TO:      SET LANGXLIB TO:
//* DEBUG TOOL        EQALANGX          THE DT SEQAMOD LIBRARY
//* FAULT ANALYZER    IDILANGX          THE FA SIDIMOD1 LIBRARY
//* APA               CAZLANGX          THE APA SCAZAUTH LIBRARY
//*
//* *****
//* ASSEMBLER STEP
//* *****
//ASM1 EXEC PGM=ASMA90,COND=(4,LT),REGION=32M,
// PARM='ADATA,OBJECT'
//SYSIN DD DISP=SHR,DSN=&SYSUID..ADLAB.SOURCE(&MEM)
//SYSPRINT DD SYSOUT=*
//SYSLIN DD DISP=SHR,DSN=&SYSUID..ADLAB.OBJ(&MEM)
//SYSADATA DD DISP=SHR,DSN=&SYSUID..ADLAB.SYSADATA(&MEM)
//SYSLIB DD DSN=SYS1.MODGEN,DISP=SHR
// DD DSN=SYS1.MACLIB,DISP=SHR
// DD DSN=&LEHLQ..SCEEMAC,DISP=SHR
//SYSUT1 DD DISP=(NEW,DELETE),DSN=&&SYSUT1,SPACE=(1700,(900,450)),
// UNIT=&UNITDEV
//SYSUT2 DD DISP=(NEW,DELETE),DSN=&&SYSUT2,SPACE=(1700,(600,300)),
// UNIT=&UNITDEV
//SYSUT3 DD DISP=(NEW,DELETE),DSN=&&SYSUT3,SPACE=(1700,(600,300)),
// UNIT=&UNITDEV
//*
//* *****
//* STEP TO GENERATE LANGX FILE
//* *****
//LANGX EXEC PGM=&LANGX,REGION=32M,
// PARM='(ASM ERROR'
//STEPLIB DD DISP=SHR,DSN=&LANGXLIB
// DD DISP=SHR,DSN=&LEHLQ..SCEERUN
//SYSADATA DD DSN=&SYSUID..ADLAB.SYSADATA(&MEM),DISP=SHR
//IDILANGX DD DSN=&SYSUID..ADLAB.EQALANGX(&MEM),DISP=SHR
//*
//* *****
//* LINK-EDIT (BINDER) STEP
//* *****
//LINK EXEC PGM=IEWL,PARM='MAP',REGION=0M
//SYSLIB DD DSN=&LEHLQ..SCEELKED,DISP=SHR
//SYSPRINT DD SYSOUT=*
//SYSLMOD DD DISP=SHR,DSN=&SYSUID..ADLAB.LOAD(&MEM)
//SYSUT1 DD UNIT=SYSDA,SPACE=(TRK,(10,10))
//SYSLIN DD DSN=&SYSUID..ADLAB.OBJ(&MEM),DISP=SHR
// DD *
// MODE AMODE(31),RMODE(24)
// ENTRY ASAM1
//*

```

Chapter 10. Source program mapping

This section describes the Source Program Mapping feature.

| For information about ... | See ... |
|---------------------------------------|---|
| Entering source mapping details | "A01 - Source program mapping panel" on page 545 |
| Java source program mapping | "A03 - Java source program mapping panel" on page 551 |
| Source program mapping pick list | "A011 - Source program mapping pick list" on page 548 |
| Source mapping dataset list | "A04 - Source mapping dataset list" on page 549 |
| The source program attribution report | "P01 - Source program attribution" on page 553 |
| USS Source Program Attribution report | "P03 - USS Source Program Attribution" on page 557 |
| USS Source Lines report | "P04 - USS Source Lines" on page 560 |

Introduction to source program mapping

Application Performance Analyzer handles source program mapping differently for Java than for other programming languages.

For languages other than Java

When you specify source program mapping files, many reports allow you to enter a "P" line command to view the program source associated with that entry in the report. The "P" line command is available on many object types: CSECTs, DB2 SQL statements, CICS commands, etc. The data is displayed in the P01: Source Program Attribution report. This report can also be included in a print request.

The 'P' line command

When you enter the 'P' line command, Application Performance Analyzer first checks if the source is loaded. If it is, the source is displayed in the P01: Source Program Attribution report.

If the source is not loaded, your A04: Source Mapping Dataset List is searched for the source member. If no source member is found in any of the datasets in the list, the A01: Source Program Mapping panel is displayed, allowing you to enter the source mapping information for the current observation session.

When one or more source members are found in your A04: Source Mapping Dataset List, the behavior of Application Performance Analyzer depends on whether or not you requested to match the compile date and time. When you request to not match the compile date and time, the first instance of a source member is loaded regardless of its date and time and the source is displayed in the P01: Source Program Attribution report.

When you request to match the compile date and time, the first source member found that matches the load module compile date and time is loaded and the source is displayed in the P01: Source Program Attribution report.

If none of the source members match the compile date and time, a pick list of datasets that contain the source member is displayed in the A011: Source Programming Mapping Pick List panel. When you select one of these source members, it is loaded and you are returned to the report from which you entered the 'P' line command. You must then re-enter the 'P' line command to display in the P01: Source Program Attribution report.

The 'P' line command for C/C++ (without timestamp match)

When you enter the 'P' line command, Application Performance Analyzer first checks if the source is loaded. If it is, the source is displayed in the P01: Source Program Attribution report.

Typically, source mapping for C/C++ programs is dependent on an exact match between the listing timestamp and the CSECT timestamp generated at compile time. A recompiled C/C++ source listing cannot be loaded directly from the A01, A04 or A11 panels. In some cases, this function is required when the source listing that matches the compiled program is not available. To accommodate this situation, Application Performance Analyzer will allow a listing to be loaded for a specific CSECT with no timestamp matching. You must enter the 'P' line command on a CSECT in one of the supporting reports. You are then directed to the A01: Source Program Mapping panel where you specify the listing to be loaded. This listing will then be loaded and related to the CSECT selected, without timestamp checking, and you are returned to the report. You must then re-enter the 'P' line command to display the P01: Source Program Attribution report.

For Java

When you specify source program mapping files for Java, the program source is viewed in the detail windows in the Java reports, rather than by using the "P" line command. The detail window from a Java Line Number contains Java source mapping information. This detail window is displayed by entering the "++" command (or the Enter key) on the Java Line Number.

USS programs using debug files

When you want to source map C or C++ programs compiled under USS, you can use debug files in ELF/DWARF format. To source map, you need to specify the "P" line command on a CSECT object in the various CPU reports. This displays the P04: USS Source Lines report. In the P04 report, you can use the "P" line command again on a source line object in order to display the P03: USS Source Program Attribution report.

You can also go directly to the P03 USS Source Program Attribution report (without going through the P04 report), by using the "P" line command on an object code address report line in the C03 report, or an attribution offset line in the W03 report.

The absolute pathname to the debug file is contained within the CSECT for the compiled program. APA is able to extract this file name from the executable USS file during sampling. Hence you do not need to identify the debug file via the A01 panel for source mapping. However, APA can only extract information from the executable USS file if it can locate it during sampling. If the program is executed using a relative path name,

then you will have to specify the directory in which it can be found. You do this in the Options panel (panel 2) when you create the request.

A01 - Source program mapping panel

Note: The A01 panel is not used for Java. For information about the Java source program mapping panel, see “A03 - Java source program mapping panel” on page 551.

Overview

This panel allows you to specify and manage associations between source program mapping (SPM) files and observation sessions. Application Performance Analyzer's SPM feature allows measured addresses to be mapped to their corresponding source program statements. You must identify SPM files for each of the observation sessions that use this feature. An SPM file can be sequential or a member in a partitioned data set.

It can be one of the following file types:

- A listing produced by the compiler (COBOL, C, OR C++)
- An ADATA (Associated Data) file produced by High Level Assembler
- A SYSDEBUG file (for COBOL only)
- A side file member produced by the IDILANGX utility

Note: For PL/I source mapping, a LANGX side file must be used.

The SPM files can be retrieved from:

- A PDS(E) or sequential file
- A third party listing (if your installation has enabled support for this)

This panel consists of two sections:

1. An input area in which you can specify an SPM file name and type.
2. A report area in which existing SPM file associations are listed.

A sample Source Program Mapping panel is shown here:

```
File View Navigate Help
-----
A01: Source Program Mapping (1972/TSTJOB01) Row 00001 of 00058
Command ==>> _____ Scroll ==>> CSR

Enter the following information to specify a source mapping file to be
used in the analysis of this measurement information.

File type . . . . _ (L=listing, A=ADATA, S=LANGX SideFile, D=SYSDEBUG)
Data set name . . _____
                    (Leave blank to search A04 dataset list)
Member name . . . _____ Match on Compile Date & Time _Y

Seqn ID-ReqNum Type/Status Lang Member DSN
0001 FF21-0002 L-Inact ASM CAZC0010 BNPF.FF2100B.LISTINGS
0002 DEMO-0003 L-Inact ASM BKNC0120 BN00.TSTP.LISTINGS
0003 DEMO-0004 L-Inact COB CAZCOB01 USER1.TSTP.LISTINGS
0004 DEMO-0005 L-Inact COB SAMCAZ03 USER2.CICS.LISTINGS
```

Another sample Source Program Mapping panel is shown here. Support for third-party listings has been enabled.

```

File View Navigate Help
-----
A01: Source Program Mapping (1971/TSTJOB01) Row 00001 of 00058
Command ==> _____ Scroll ==> CSR

Enter the following information to specify a source mapping file to be
used in the analysis of this measurement information.

File type . . . . _ (L=listing, A=ADATA, S=LANGX SideFile, D=SYSDEBUG)
Repository. . . . _ (T=Third Party, O=Other)
Data set name . . _____
                    (Leave blank to search A04 dataset list)
Member name . . . _____ Match on Compile Date & Time _Y

Seqn ID-ReqNum Type/Status Lang Member DSN
0001 FF21-0002 L-Inact ASM CAZC0010 BNPF.FF2100B.LISTINGS
0002 DEMO-0003 L-Inact ASM BKNC0120 BN00.TSTP.LISTINGS
0003 DEMO-0004 L-Inact COB CAZCOB01 USER1.TSTP.LISTINGS
0004 DEMO-0005 L-Inact COB SAMCAZ03 USER2.CICS.LISTINGS

```

File specification input area

In this area you enter information about an SPM file to be associated with the current observation session. The fields are described below, but these might vary depending on your installation.

File type

Specify L for a compiler listing file, A for an assembler ADATA file, S for a LANGX SideFile, or D for a SYSDEBUG file.

Listing files are supported for the following versions of COBOL: PP5668-958 COBOL II, PP 5688-197 COBOL for MVS/VM, PP 5648-A25 COBOL for OS/390/VM, PP 5655-G53 Enterprise COBOL, PP 5655-S71 Enterprise COBOL for z/OS V4R1, OS/VS COBOL PP 5740, PL/I: PP 5655-H31 Enterprise PL/I for z/OS, PP 5668-910 IBM OS PL/I OPTIMIZING COMPILER (PL/I support using LANGX side files only), C/C++: PP 5694-A01 z/OS C/C++ V1R2.0 and above.

For complete information on compiler options, refer to “Required compiler options for creating listings or CAZLANGX side files” on page 692.

Repository

T for a third party repository, or O for any other type such as a PDS or sequential data set.

Data set name

Specify the name of the sequential or partitioned data set containing the SPM file. Your TSO Prefix will be added as the first qualifier if you enter a name without quotes.

If this field is left blank, the A04 Source Map Dataset List is searched for the member name specified.

Member name

Include the member name if the data set is partitioned.

Match on Compile Date and Time

Specify 'Y' for Yes if you want the compile date and time of the source to be matched to the date and time in the matching CSECT in the measurement data. This feature only works with LE compliant modules.

If you use this feature in conjunction with a blank dataset name, your A04 Source Mapping Dataset List is searched for a source module with a compile date and time matching the CSECT. If one is found, it will be loaded. If matching source members are found, but none have the correct date and time stamp, you are given a Pick List of datasets and you can choose to use one of these.

If you specify 'N' for No in conjunction with a blank dataset name, the first instance of a matching source member in your A04 Source Mapping Dataset List is loaded, regardless of its date and time.

The behavior of this setting applies only to non C/C++ Source Map datasets. For C/C++, the field is ignored. C/C++ source mapping always requires a date/time match.

List of existing SPM file associations

This section shows a scrollable list of existing associations between SPM files and observation sessions. These SPM associations are “private” to your own TSO userid and are recorded in your TSO profile. Each TSO user needs to set up his or her own SPM information.

Any entries for file associations applicable to the current observation session will appear at the top of the list. The value under the ID-ReqNum field will be displayed in red to indicate this.

Fields displayed in the File Association List are described here:

Seqn This is simply the line number of the entry. Line commands can be entered to this field.

ID-ReqNum

This shows the observation session request number with which the SPM file is associated. The request number is prefixed by the Application Performance Analyzer identifier.

Type/Status

This indicates the type of SPM file and whether the mapping information has been “loaded” (available for use). “L” indicates a compiler listing file, “A” indicates an assembler ADATA file, and “S” indicates a LANGX SideFile.

Lang The source program language is shown here: ASM, C, C++, COB or PLI.

Member

The member within a partitioned data set is shown here. This field is blank if the data set is non-partitioned.

DSN The data set name of the SPM file is shown here.

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | Seqn | Display context help information. |

| Cmd | When Applied To Object | Action |
|-----|------------------------|---|
| ++ | Seqn | Show additional details. |
| C | Seqn | Copy this SPM file association to the current observation session. |
| D | Seqn | Delete this entry. |
| L | Seqn | Load this SPM file and bind it to the current observation session. |
| F | Seqn | Fill the input fields with the values for this SPM file association |

A011 - Source program mapping pick list

Overview

This dialog is displayed by the 'P' line command and the A01 Source Program Mapping panel. It is displayed when you have requested that your SPM dataset list be searched for a source member with a compile date/time match, but no date/time match can be found. A list of datasets containing members which match the SPM mapping request, but not the date and time, is presented in the Pick List.

From this list you can select (pick) an SPM dataset that you wish to use for source mapping purposes. After selecting an SPM dataset and pressing Enter, the selected SPM dataset and member will be loaded and bound to the current observation session. Also, when displayed from the A01 Source Program Mapping panel, a new row is added to the A01 SPM list reflecting this addition.

A sample pick list panel is shown here:

```

File View Navigate Help
-----
A011: Source Program Mapping Pick List (2399/TSTJOB01)      Row 00001 of 00002
Command ==> _____ Scroll ==> CSR

Member Name: LPFRAYVS
Load Module: LPFRAYVS CSECT: LPFRAYVS
Observed Compile Date and Time: n/a

Seqn  Dataset Name                      Compile Date and Time
0001  USR1.TST.COBOL.LISTING2            2006/01/30 07:09:05
0002  USR1.TST.COBOL.LISTING5            2006/01/30 11:16:09
0003  USR1.TST.COBOL.LISTING7            2007/07/02 13:21:29
0004  USR1.TST.COBOL.LISTINGE            2006/04/17 16:45:02

+-----+
| No match found. Select a dataset from the list and press Enter, or press PF3 |
| to return to the previous panel without a selection. This Pick List is      |
| displayed because you specified a blank dataset name and 'Match on Compile   |
| Date & Time', but no date and time matches were found for this member in   |
| your list of datasets.                                                       |
+-----+

```

Field descriptions

Member name

The source member name.

Load module

The load module name that matched the source member and the measurement.

CSECT

The CSECT name that matched the source member and the measurement.

Observed compile date and time

The date and time extracted from the LE entry point for the CSECT. This is only available for LE compliant modules.

Pick list description

This lower section of this panel is a scrollable list. Each row in the list consists of three fields: a sequence number, a dataset name, and compile date & time. These fields are described below.

The Select line command allows you to select the SPM dataset you want to use. When this dialog is displayed from the A01 Source Program Mapping panel, after selecting a dataset and pressing Enter, the selected dataset is loaded and added to your list of SPM file associations and you are returned to the A01 dialog. When this dialog is displayed from the 'P' line command, the source member from the selected dataset is loaded and after pressing Enter, you are returned to the report from which you entered the 'P' line command. You must then re-enter the 'P' line command to display in the P01: Source Program Attribution report. In either case, press PF3 to return without making a selection.

Seqn A sequence number indicating the detail line's position in the entire scrollable list. This field accepts the 'S' (Select) line command.

Dataset name

The name of the SPM dataset containing the SPM data for the CSECT found in the current observation.

Compile Date and Time

The date and time when this SPM member was created (compiled).

A04 - Source mapping dataset list**Overview**

This panel allows you to specify a list of partitioned dataset names that Source Program Mapping (SPM) will use to search for a source program. The datasets will be searched in the specified order. The list is saved in your profile. The list is searched when the 'P' line command is entered and when you do not specify a dataset name in the A01 Source Program Mapping panel.

A sample panel is shown here:

```

File View Navigate Help
-----
A04: Source Mapping Dataset List (1068/TSTJOB01) Row 00001 of 00020
Command ==> _____ Scroll ==> PAGE

Specify up to 20 listing repository datasets. These will be searched
when the P line command is entered or on the A01 panel when you leave
the dataset name blank on a new entry.

Match on Compile Date & Time Y

Seqn File Type Repository Dataset Name
0001 S 0 USR1.IDILANGX
0002 L 0 USR1.COBOL.LISTING
0003 D 0 USR1.TST.COBOL.DEBUG
0004 A 0 USR1.ADATA
0005 - - 
0006 - - 
0007 - - 
0008 - - 
0009 - - 
0010 - - 
0011 - - 
0012 - - 
0013 - - 
0014 - - 
0015 - - 
0016 - - 
0017 - - 
0018 - - 
0019 - - 
0020 - - 

```

Match on Compile Date & Time description

The value entered here applies to all entries in the dataset list. Specify 'Y' for Yes if you want the compile date and time of the source to be matched to the date and time in the matching CSECT in the measurement data. Specify 'N' for No if you want the source to be loaded regardless of its date and time. For more details, refer to “Match on Compile Date and Time” on page 546.

Dataset list description

A scrollable list of up to 20 dataset names can be maintained here. Each row in the list consists of four parts: a sequence number, a file type, a repository and a dataset name field. These fields are described below.

Seqn A sequence number indicating the detail line's position in the list. This field accepts line commands to Move, Insert, and Delete. To display a line command menu for this field, enter / .

File type

Specify L for a compiler listing file, A for an assembler ADATA file, S for a LANGX SideFile, or D for a SYSDEBUG file.

Repository

Specify T for a third party repository, or O for any other type such as a PDS or sequential data set.

Dataset name

The name of the dataset to be searched. This is an input field where you specify a fully qualified dataset name. The name must not be enclosed in quotes.

Commands to save and edit

This panel supports a limited set of ISPF Edit type line commands. The commands supported are listed below. (Block moves are not supported).

| | |
|---|--------|
| I | Insert |
| D | Delete |
| M | Move |
| A | After |

PF3 or the END command saves the list and terminates the dialog, but you must press Enter first to record any changes. The CANCEL command terminates the dialog without saving any changes.

A03 - Java source program mapping panel

Overview

This panel allows you to specify information needed by the Source Program Mapping (SPM) feature for Java programs.

During the measurement, the measurement task determines and records source file names for each of the Java classes in which execution is observed. However, the source file names are not fully qualified. Use this panel to specify sequences of file name prefixes that will be concatenated as high level qualifiers to the captured source program file names in order to form fully qualified HFS path names.

The A03 panel lets you save a set of file name prefixes in an ordered list. Each name in the list is assigned a search sequence ("SrchSeq"): 01, 02, 03, etc.

Note: It is helpful to think of the file name prefixes as directory names, and think of stored Java class source file names as files within these directories. Using this analogy, SPM tries to locate a Java class source file by searching each of these directories. It searches the directories in the sequence (01, 02, 03, etc.) indicated by the SrchSeq value.

You can store a default, global list of prefixes and you can store a list for a specific measurement. When attempting to resolve file names, SPM will search the directories specified for the particular measurement first, and then it will search the global list.

The Java source program mapping panel consists of two sections:

1. An input area in which you specify a file name prefix to be added to a list, and an option specifying whether you are working with the global (default) list or the list for the current measurement.
2. A scrollable list of file name prefixes. The list you are working with (current measurement or default) appears at the top of the list.

A sample Java source program mapping panel is shown here:

```

File View Navigate Help
-----
A03: Java Source Program Mapping (7544/JVMST01) Row 00001 of 00007
Command ==> _____ Scroll ==> CSR

Enter "/"
/ To work with file name prefix list for curent measurement. Blank
  for global (default) file name prefix list.

Enter new HFS path name prefix to be added (up to 150 characters)
_____
_____

Seqn ID-ReqNum SrchSeq Path Name
0001 SST -7544 01 /u/java/src
0002 SST -7544 02 /u/jtest/pathOne
0003 SST -7537 01 /u/jtest/pathThree/security/Section/src
0004 SST -7537 02 /u/java/src
0005 SST -7537 03 /u/jtest/pathFive/development/source
0006 SST -7537 04 /u/jtest/pathFour
0007 SST -7537 05 /u/jtest/pathTwo/alphaAlpha/bravoBravo/charlieCharli

```

File prefix specification input area

Specify either '/' or blank in the option field to indicate whether you want to work with the file prefix list for the current measurement or with the global (default) file prefix list.

To add a new file name prefix to the selected list, enter the prefix name in the two line input field. A prefix name can have up to 150 characters. The name will be added to the end of the ordered list, which means it will be assigned the highest SrchSeq value.

Detail lines

This area is scrollable. Each detail line displays a file name prefix, which are organized by ordered-list groups.

| Under Heading | This is Displayed |
|---------------|--|
| Seqn | A sequence number indicating the detail line's position in the entire scrollable list. This field accepts line commands. Enter "/" to display a line command menu for this field. |
| ID-ReqNum | The name of the measurement task and the request number of the measurement to which the file prefix applies. A value of 0000 appears for the request number if the path name is part of the default list and applies globally. |
| SrchSeqn | A value indicating the relative sequence in which the file prefix is applied. SrchSeq values for an ordered list begin with 01 and appear in sequence (01, 02, 03, etc.). The maximum value is 99. |
| Path Name | The file path name prefix. This name can end with a forward slash. If it does not end with a forward slash, one will automatically be added before it is concatenated with the Java class source file name. |

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter "/" on any input field to open a menu of line commands available for that field.)

on objects

| Cmd | When Applied To | Action |
|-----|-----------------|-----------------------------------|
| ? | Seqn | Display context help information. |
| D | Seqn | Delete the entry. |
| H | Seqn | Move higher in search order. |
| L | Seqn | Move lower in search order. |
| S | Seqn | Copy path name to input field. |

Java report detail window

Once the Java source program mapping details have been entered in the A03 panel, the source can be viewed in the detail windows of the Java reports. Display the detail window by entering the “++” line command (or enter key) on the Java Line Number object in the Java report.

A sample Java report detail window with source mapping is shown here:

```
File View Navigate Help
+-----+
+----- The following report line was selected -----+
|   → 00817   line # 817           0.33           |
+-----+
More:  - +

Package Name   java/lang
Class Name     String
Method Signature charAt(int) char
Source File Name /u/java/src/java/lang/String.java

LineNo Source Statement
-----
00814      *           string.
00815      */
00816      public char charAt(int index) {
00817          if ((index < 0) || (index >= count)) {
00818              throw new StringIndexOutOfBoundsException(index);
00819          }
00820          return value[index + offset];
00821      }
00822
00823      /**
00824      * Copies characters from this string into the destination char
00825      * array.
```

P01 - Source program attribution

Overview

This report maps measured CPU activity to its corresponding source program statements. You use the “P” line command, on an eligible line command field, to launch this report. (See the individual Performance Analysis reports to determine which lines allow the “P” command.) Source statements from a single compile (or assembly) unit are shown. Depending on the selected SETUP options, all or part of the source program is shown. A count value is shown for statements in which CPU activity was measured; each count value indicates the number of times execution in the statement was observed. Optionally, depending on a SETUP option, the counts are also shown graphically.

This report also shows attribution of CPU usage measured in system modules referred back to the points of invocation in application modules (“Referred Attribution”). This referred attribution line is displayed directly under the source statement, and is displayed in pink.

A sample report is shown here with the graphics option turned off.

```

  _File _View _Navigate _Help
-----
P01: Source Program Attribution (0453/TSTJOB01)          Row 00001 of 00043
Command ==> _____ Scroll ==> CSR

LineNo Offset Count Source Statement
000120                *-----
000121
000122 00034A          Open Input  DataFile1
          9 <- CPU time attributed to above statement
000123
000124 00036C          If DataFile1-file-status-ok
000128                End-If
000129
000130 000388          Open Output  DataFile2
          7 <- CPU time attributed to above statement
000131
000132 0003A6          If DtaFile2-file-status-ok
000167                *-----
000168
000169 0004B0          2      Read DataFile1
000170                At End
000171 0004F4                Set DataFile1-eof To True
000186 00050A          Move dataRecord to dataRecordCopy
000187
000188 000510          8      Perform until Char-Column > 80
000189
000190 000524                If dataChar(Char-Column) Not = Space
000193 00056C                Move 1 to Word-Length(Word-Count)
000194
000195 000582          6      Perform until dataChar(Char-Column) = Spac
000196                or Char-Column > 80
000197 0005AE                Add 1 to Char-Column
000229 00066A          Move Word-Length(Word-Subscript1) to ws-Word-
000230
000231 000688          735    Perform until Word-Updated or

```

```

File View Navigate Help
-----
P01: Source Program Attribution (0453/TSTJOB01) Row 00001 of 00043
Command ==> _____ Scroll ==> CSR

LineNo Offset Count Source Statement
000169 0004B0 2 Read DataFile1
000170 At End
000171 0004F4 Set DataFile1-eof To True
000186 00050A Move dataRecord to dataRecordCopy
000187
000188 000510 8 Perform until Char-Column > 80
000189
000190 000524 If dtaChar(Char-Column) Not = Space
000193 00056C Move 1 to Word-Length(Word-Count)
000194
000195 000582 6 Perform until dataChar(Char-Column) = Spac
000196 or Char-Column > 80
000197 0005AE Add 1 to Char-Column
000229 00066A Move Word-Length(Word-Subscript1) to ws-Word-
000230
000231 000688 735 Perform until Word-Updated or
000232 Word-Subscript2 > Total-Word-Co
000233
000235 0006D0 Move Word-Length(Word-Subscript1) to ws-Wo
000236
000237 0006EE 49 If All-Word-Value(Word-Subscript2) =
000238 dataRecordCopy(ws-Word-Column:ws-Word-L
000239 000730 Add 1 to All-Word-Count(Word-Subscript2)
000249 00079E Move Total-Word-Count to Word-Subscript2
000250 0007A8 Move 1 to All-Word-Count(Word-Subscript2)
000251 0007C2 15 Move dataRecordCopy(ws-Word-Column:ws-Word
000252 to All-Word-Value(Word-Subscript2)
000253 End-If

```

Code segments

The reported CPU activity depends on the item upon which the “P” line command was entered to launch this report. Only the CPU activity which was aggregated to quantify that item is included in the source mapping report. If, for example, this report was launched from an item on the CPU Usage by Code Slice report, then only activity for the range of addresses in the selected “slice” is reflected in the source statement counts. Statements outside such a selected address range are displayed in blue, while those within the range appear in green.

Detail line descriptions

LineNo

This field displays a 6 digit sequence number corresponding to the source statement line position. The sequence values begin at 000001 and increase by 1 for each statement. Gaps in the sequence occur if SETUP options are chosen resulting in some statements being omitted from the report. This field is also an input field and accepts line commands.

Offset

This field contains the hexadecimal offset of the object code associated with the source statement. The offset is relative to the beginning of the CSECT (Control Section). Blanks are shown here if there is no object code address associated with the statement (comments, continuations, non-procedural statements, etc.).

Count

The number of times execution was observed at the statement is shown here, or blank if no execution was measured. The maximum value is 9999. Values exceeding 9999 are shown as 9999+.

Source statement

The source program statement is shown here. For an assembler program, you can select a SETUP option to choose whether to show only the 80 byte source statement or to show the full assembly listing format (including offset, object code etc.)

Header information

A SETUP option can be selected to display information about the mapped program in the heading section of each page. This information includes: load module name, load library name, CSECT name, source mapping file name, compile date/time, and code segment address range (when applicable). It is usually preferable to turn off this option as it occupies several lines at the top of the screen.

SETUP options

Enter the SETUP primary command to select options for this report. The following pop-up window will be displayed:

```
File View Navigate Help
-----+-----
P | Options for Source Program Mapping | 001 of 00068
C | | | 11 ==> CSR
  | Nbr of adjacent lines to display . . . 2
L | This specifies the number of statements
  | without measured activity to be displayed
  | before/after lines with activity. |
0 | | |
0 | | |
0 | Enter "/" to select an option
0 | - Display ALL statements of the source program.
0 | (otherwise only those at or near statements
0 | with measured activity are displayed.)
0 | - Include assembler object code.
0 | / Show statement count graphically.
0 | - Show detailed information in heading.
0 | - Show C/C++ pseudo-assembly.
0 | - Display values as a percent.
0 | (Not applicable to all reports)
0 | | |
0 | | | pace
  +-----+-----
```

Number of adjacent lines to display

Use this parameter to control how many adjacent source lines you would like to see on either side on a source line with activity. This is used to give context to the active source lines displayed. This parameter is ignored if you turn on the Display ALL statements option.

Display ALL statements

Choose this option if you would like to see the entire source program. Otherwise, only source statements with activity, or statements adjacent to statements with activity are included.

Include assembler object code

Use this option to choose whether to show only the 80 byte source statement or to show the full assembly listing format (including offset, object code etc.)

Show statement count graphically

This option will cause a graph to be displayed on top of the source statements, indicating how much activity each active source statement has.

Show detailed information in heading

This option will cause detailed information about the source program to be displayed. This includes the load module, name of library it was loaded from, the CSECT, the source mapping file name, compiler name, and compile date and time.

Show C/C++ pseudo assembly

This option will cause pseudo-assembly for C/C++ programs to be displayed.

Display values as a percent

This option will cause the values for the source statement to be displayed as a percentage (instead of a count). This is only applicable when you are source mapping from a report which shows percentages.

Detail window

You can enter “++” (or the Enter key) on any line to display a pop-up window containing additional information.

A sample detail window for this report is shown here:

```
File View Navigate Help
+-----+
Source Statement Information
      Perform until Char-Column > 80
CSECT Name:      COB01
Offset:          000510
Object Code Size: 20 bytes
Activity Count:  8 times

Module Information for COB01
Load Address     08B00B38 to 08B01FFF
Module Size      5,320
Attributes       REUS,NORENT,APFLIB
Module Location  JPA
Loadlib DDNAME   STEPLIB
Load Library     BNPF.UTIL.LOADLIB

ESD Information for COB01
External Offset Length Start Addr End Addr
COB01 000000    4152 08B00B38 08B01B6F
IGZEBST 001038    1168 09B01B70 08B01FFF
+-----+
```

P03 - USS Source Program Attribution

Overview

The P03 report is used for source mapping USS programs. It requires the programs to have debug files in the ELF/DWARF format associated with them.

This report maps measured CPU or Wait activity to its corresponding source program statements. Use the “P” line command, on an eligible line command field (see below), to launch this report. Source statements from a single compile unit are shown. A count or percent value is shown for the statement selected in which CPU activity was measured; the count value indicates the number of times execution of

the statement was observed. A percent value shows the percent as calculated on the report. Optionally, depending on a SETUP option, the counts are also shown graphically.

Eligible line commands

The P03 report can be launched with a "P" line command from one of the following:

- A USS Source Line in the P04: USS Source Lines report
- An object code address report line in the C03 report
- An attribution offset line in the W03 report

A sample report is shown here.

```

File View Navigate Help
-----
P03: USS Source Program Attribution (0539/JVMTST01)          Row 00028 of 00047
Command ==> _____ Scroll ==> PAGE

LineNo Count Source Statement
-----
000028                               l = i + m;
000029          /*                    printf(" a[I]=%d a[L]=%d

000030                               c++;
000031          120                    if (a[i-1] <= a[l-1]) {
000032                               i = 0;
000033                               } else {
000034                               t = a[i-1];
000035                               a[i-1] = a[l-1];
000036                               a[l-1] = t;
000037                               i = i - m;
000038                               s++;
000039                               }
000040                               }
000041                               j += 1;
000042                               }
000043                               m = m >> 1;
000044                               }
000045          printf(" iterations=%d swaps=%d
000046          }

```

Detail line descriptions

Table 15.

| Under Heading | This is Displayed |
|---------------|--|
| LineNo | This field displays a 6 digit sequence number corresponding to the source statement line position. |
| Count | The number of times execution was observed at the statement is shown here. The maximum value is 9999. Values exceeding 9999 are shown as 9999+. |
| Prcnt | If the percent option has been selected in the SETUP for source mapping, the values for the statement are displayed as a percentage. This percentage is the same as percent shown on the report for that line item. The ++ detail popup shows the calculation used to arrive at the percent. |

Table 15. (continued)

| Under Heading | This is Displayed |
|------------------|---|
| Source Statement | The source program statement is shown here. |

Header information

A SETUP option can be selected to display information about the mapped program in the heading section of each page.

Table 16.

| Under Heading | This is Displayed |
|---------------------|--|
| Debug file | This is the absolute path name of the DWARF debug file that was generated by the compiler for the selected CSECT (Control Section). |
| Debug file date | This is the current file modification date and time of the DWARF debug file. |
| Compile date | This is the date and time that the CSECT was compiled, as recorded in the executable program. If the current file modification date and time of the debug file differs from the compile date and time by more than 1 minute, a warning is displayed. |
| Source file name | This is the absolute path name of the source file that contains the requested source statement line. |
| Source file date | This is the current file modification date and time of the source file. |
| Source compile date | This is the date and time that the source file was compiled, as recorded in the DWARF debug file. If the current file modification date and time of the source file is not the same as the compile date and time, a warning is displayed. |

SETUP options

The following SETUP options can be selected with the SETUP primary command:

Show statement count graphically

This option will cause a graph to be displayed on top of the source statements, indicating how much activity each active source statement has.

Show detailed information in heading

This option will show the following additional header fields: Debug file, Debug file date, Compile date, Source file name, Source file date, and Source compile date.

Display values as a percent

This option will cause the values for the source statement to be displayed as a percentage (instead of a count). Not applicable to all reports.

P04 - USS Source Lines

Overview

The P04 report is used for mapping source lines in USS programs. It requires the programs to have debug files in the ELF/DWARF format associated with them.

This report maps measured CPU or Wait activity to specific source lines within a CSECT. Use the "P" line command, on an eligible line command field, to launch this report. Source statements from a single compile unit are shown. A percent value is shown for source statements in which CPU activity was measured. A "P" command can be entered on the LineNo field to see the source for that line.

A sample report is shown here.

```

File View Navigate Help
-----
P04: USS Source Lines (0539/JVMTST01) Row 00001 of 00017
Command ==> _____ Scroll ==> CSR

Debug file name      /u/aif04/xcs5d.dbg
Debug file date      2007-11-12 15:13:11
Compile date         2007-11-12 15:13:10

LineNo  FileNo      Percent of CPU Time * 10.00% ±3.2%
      *...1...2...3...4...5...6...7...8...9...*

000031      1      12.77=====
000027      1      6.60  ====
000035      1      4.89  ==
000034      1      4.57  ==
000028      1      4.36  ==
000036      1      4.36  ==
000040      1      3.19  ==
000025      1      2.55  =
000030      1      2.44  =
000033      1      2.44  =
000041      1      2.34  =
000038      1      2.02  =
000037      1      1.91  =
000039      1      1.70  =
000032      1      1.38  =
000026      1      0.63
000042      1      0.53

```

Detail line descriptions

Table 17.

| Under Heading | This is Displayed |
|---------------------|---|
| LineNo | This field displays a 6 digit sequence number corresponding to the source statement line number. |
| Fileno | This field contains the file number for the source module within the CSECT (Control Section). |
| Percent of CPU Time | Displays the percent of CPU active samples on this line number out of the total number of CPU active samples taken. |

Header information

Table 18.

| Under Heading | This is Displayed |
|-----------------|--|
| Debug file | This is the absolute path name of the DWARF debug file that was generated by the compiler for the selected CSECT (Control Section). |
| Debug file date | This is the current file modification date and time of the DWARF debug file. |
| Compile date | This is the date and time that the CSECT was compiled, as recorded in the executable program. If the current file modification date and time of the debug file differs from the compile date and time by more than 1 minute, a warning is displayed. |

Line commands

The line commands available in this report, and the objects and headings to which they apply, are summarized below. (You can enter a “/” on any input field to popup a menu of line commands available for that field.)

on objects

| Cmd | When Applied To Object | Action |
|-----|------------------------|-----------------------------------|
| ? | LineNo | Display context help information. |
| ++ | LineNo | Show additional details. |
| P | LineNo | Display source program mapping. |

on headings

| Cmd | When Applied To Heading | Action |
|-----|-------------------------|-----------------------------------|
| ? | LineNo | Display context help information. |
| SV | LineNo | Sort next level by value. |

Detail window

You can enter “++” (or the Enter key) on any line to display a popup window containing additional information.

A sample detail window for this report is shown here:

```
File View Navigate Help
+-----+
+----- The following report line was selected -----+
| 000031      7      12.77 =====|
+-----+

Calculation Details
CPU measurements          120
In the csect              .P000014
File Number               7
Line Number               31
Total CPU measurements   939
Percent of total         12.77%

000031          if (a[i-1] <= a[l-1])  {
```

Chapter 11. Printing reports and creating XML documents

This section explains how to produce Application Performance Analyzer performance analysis reports suitable for printing, or in XML document format suitable for further processing. You generate a printable report or an XML document, in batch, by submitting JCL. In most situations, you can use Application Performance Analyzer's ISPF-based report request facility which will generate and submit the JCL for you. This facility is discussed in the first two sections of this chapter. The remaining sections explain the JCL and control statements; these sections are of interest only if you intend to prepare the JCL and control statements manually.

| For information about ... | See ... |
|--|---|
| The available options, and overall capabilities of the report printing facility | "About Application Performance Analyzer's report printing and XML document feature" |
| Using Application Performance Analyzer's ISPF-based report request facility | "Using the ISPF report request facility" on page 564 |
| How to prepare JCL to produce reports | "Preparing JCL to print reports or create XML documents" on page 568 |
| Control statements to specify report options | "Specifying control statements" on page 571 |
| Producing, viewing and printing high-quality reports in PDF format | "Reports in PDF format" on page 574 |
| Processing and transferring report data contained in XML document files | "Reports in XML document format" on page 574 |
| The sections that you can include in a performance analysis report and how to specify them in SECTION control statements | "Report SECTION descriptions" on page 575 |

About Application Performance Analyzer's report printing and XML document feature

Most of the Application Performance Analyzer's interactive performance analysis reports are available in format suitable for printing or in XML document format suitable for further processing. Application Performance Analyzer allows you to generate reports and XML documents by submitting JCL that executes the program CAZPRINT. You can use Application Performance Analyzer's ISPF-based report request facility to build the necessary JCL and CAZPRINT control statements. Alternatively, you can manually prepare and submit your own JCL. CAZPRINT can produce report output in three different formats:

Line printer

The traditional FBA 121 character-per-line SYSOUT format.

PDF Adobe™ Portable Document Format.

XML Extensible Markup Language document format.

Line printer format

You would typically route line printer format as a JES SYSOUT file. You produce this by specifying a PRINT control statement. You specify a DD name in the PRINT

statement and supply a DD statement for that name. This is the most direct (and convenient) way of producing report output, but formatting is constrained by inherent line printer device limitations.

PDF format

PDF is the preferable format because it offers high quality printed output as well as advanced viewing capabilities. You produce a PDF file by specifying a CONVERT control statement. You specify a DD name in the CONVERT statement and supply a DD statement for that name which defines the output file. You then need to transfer the file to a PC platform on which you can view and print the report.

XML document format

When you wish to further process the report data, you can produce an XML document file. You produce an XML document file by specifying a CONVERT control statement. You specify a DD name in the CONVERT statement and supply a DD statement for that name which defines the XML document file. You may browse, edit or further process the XML document on the mainframe, or transfer it to another platform.

Report sections

A single performance analysis report is comprised of a number of report Sections. A report section typically has a counterpart report in the ISPF reporting environment. For example, *C01: CPU Analysis by Category* is implemented as a single report in the ISPF environment and can be included as one section of a printed report. The same 3- character identifiers used to denote ISPF reports are used to denote report sections. You specify that a report section is to be included by supplying a SECTION control statement.

Using the ISPF report request facility

To request a batch performance analysis report or XML document using Application Performance Analyzer's ISPF facility, select an observation session item in the usual way – enter the "R" line command on the observation session list screen. Then, from the report selection menu, select A02.

A screen will then be displayed listing the available report sections that you can select to be included in the report or XML document.

An example of the A02 dialog is shown here.


```

File View Navigate Help
-----
A02: Request Printed Reports (0464/TSTJOB01) Row 00001 of 00030
Command ==> _____ Scroll ==> CSR

Enter / to include a section in the report or file, blank to exclude the section,
S to include the section and set formatting options. Use UP/DOWN (PF7/PF8)
to scroll the list of report sections. After entering your selections,
press ENTER to generate the report JCL.

Select Report Section

/ S01 Session Statistics
/ S02 Load Module Attributes
/ S03 Load Module Summary
/ S04 TCB Summary
/ S05 Memory Usage Timeline
/ S06 Data Space Usage Timeline
/ S07 TCB Execution Summary

/ C01 CPU Usage by Category
/ C02 CPU Usage by Module
/ C03 CPU Usage by Code Slice
/ C04 CPU Usage Timeline

```

You simply make your selections, press ENTER, and Application Performance Analyzer will build and submit the JCL. The selectable report sections—as illustrated above—include only those applicable to the selected measurement file. DB2 report sections, for example, will not appear as available selections if no DB2 data exists in the measurement file. By default, all the applicable reports are selected. However, if you prefer to have the previous selections “remembered”, you can request this using the SETUP primary command while you are in this panel.

Specifying formatting options

You can modify the format of some report sections by specifying formatting options. To do so, select the report section with the “S” line command instead of a slash (/) character. A pop-up window will appear in which you can modify the current option values.

If you enter more than one “S” line command, the formatting option pop-up window for only the first one encountered will appear; you should enter “S” line commands one at a time. The following illustrates the formatting options pop-up window, which will appear if you enter the “S” line command on the C01: CPU Usage by Category report section.

```

File View Navigate Help
+-----+
A02: Report Parameters (0464/TSTJOB01)
Command ==> _____ Scroll ==> CSR

The following are options for C01: CPU Usage by Category
Modify the option values and press ENTER.

Value      Description
9        Number of levels (1 to 9) of report line
           hierarchical expansion.
VALUE    Report sort sequence: NAME or VALUE
/        / to categorize modules by "Group".
           Unselect to categorize by "SubGroup"
1.00    Minimum percentage of CPU activity measured
           for which an item is to be included in the
           report.
+-----+

```

Modify the values and press the ENTER key and you will be returned to the report section selection dialog.

Application Performance Analyzer will “remember” the option values you specify. These will become your new default values and will be used for future printed report requests.

The JCL submission/EDIT dialog

Pressing ENTER to the report section selection dialog will take you to the JCL submission dialog – if you did not modify any input fields prior to pressing ENTER. The report section selection dialog will continue to display until you have pressed ENTER without having modified any input fields.

The JCL submission dialog is illustrated below. Pressing the ENTER key will cause the generated JCL to be submitted directly, or will launch EDIT for the generated JCL member. This dialog is illustrated here.

```

File View Navigate Help
+-----+
A02: Report JCL Submission (0464/TSTJOB01)
Command ==> _____ Scroll ==> CSR

Specify the following and press ENTER to either SUBMIT the print
JCL or to launch EDIT for the generated JCL.

Enter "/" to select options
 / produce PDF (Portable Document Format) file
 / generate JES-managed report file (SYSOUT=*)
 _ produce XML (Extensible Markup Language) file
 _
 _ EDIT the generated JCL member, otherwise SUBMIT

Job Statement - edit if necessary
==> //USER1P___JOB_(),'CAZRPT01',CLASS=A,MSGCLASS=T,NOTIFY=&SYSUID
==> /*_____
==> /*_____

PDF File DSN (if applicable) must be cataloged FB 80
==> USER1.FB80'

XML File DSN (if applicable) must be cataloged FB 255
==> _____

Location where generated JCL is to be saved
JCL Library ==> 'USER1.JCLLIB'
JCL Member ==> CAZRPT1
+-----+

```

Input to the JCL submission/EDIT dialog

Produce PDF file

Enter a slash (/) to select this option or a space to deselect it. CAZPRINT will write a file in downloadable PDF (Portable Document Format) file.

Generate JES-managed report file

Enter a slash (/) to select this option or a space to deselect it. CAZPRINT will write a standard SYSOUT format report file.

Produce XML file

Enter a slash (/) to select this option or a space to deselect it. CAZPRINT will write a file in XML (Extensible Markup Language) document format. This option cannot be selected when either the PDF file or the JES-managed report file options are selected.

EDIT the generated JCL

Enter a slash (/) if you want EDIT to be launched for the generated JCL member when you press the ENTER key. Blank in this field will cause the JCL to be SUBMITted immediately when you press the ENTER key.

Job Statement

The generated JOB statement is shown in three lines. You can modify the statement to suit your preferences or to comply with your installation. Be aware, however, that no validation is done on your input; an input error can cause a JCL error when the job is submitted.

PDF File DSN

If you have specified that a PDF file is to be written, you must specify the DSN of the file in this field. The file must be a sequential dataset with fixed length 80 byte records. If the file is not pre-allocated and cataloged, Application Performance Analyzer allocates and catalogs it.

XML File DSN

If you have specified that an XML document file is to be written, you must specify the DSN of the file in this field. The file must be a sequential dataset with fixed length 255 byte records. If the file is not pre-allocated and cataloged, Application Performance Analyzer allocates and catalogs it.

JCL Library

Enter the DSN of a JCL library. This a partitioned data set in which the generated JCL member will be stored before it is submitted (or EDITed).

JCL Member

Enter the name of the JCL member here.

Source program mapping

The report section selection dialog displays one selectable line for the P01 Source Program Attribution report section for each applicable program. However, you must first load the source mapping data. For details on loading source mapping data, refer to Chapter 10, "Source program mapping," on page 543. Each P01 selection line displays the name of the source mapped program.

```
File View Navigate Help
-----
A02: Request Printed Reports (0464/TSTJOB01)          Row 00031 of 00035
Command ==>> _____ Scroll ==>> CSR

Enter / to include a section in the report, blank to exclude the section,
S to include the section and set formatting options. Use UP/DOWN (PF7/PF8)
to scroll the list of report sections. After entering your selection,
press ENTER to generate the report JCL.

Select  Report Section

      /      P01 Source Program Attribution for SAMPFINQ
      /      P01 Source Program Attribution for PFSAMPA
      /      P01 Source Program Attribution for PFSAMPB
      /      P01 Source Program Attribution for PFSAMPC
```

Preparing JCL to print reports or create XML documents

You have the option of manually preparing and submitting your own report JCL. The ISPF report request facility will meet most requirements, but by preparing your own JCL and control statements you can use the full formatting flexibility of the CAZPRINT program.

The following CAZPRINT capabilities that are not available directly by using the ISPF report request facility are available if you prepare your own JCL and control statements:

- Include multiple instances of the same report section in a single report. For example, you can include two instances of C01: CPU Usage by Category in your report. Having multiple instances allows you to sort reports using more than one category. For example, one can be sorted by VALUE (most intense CPU activity at the top) and another sorted by program NAME.
- Include report sections from different measurement files in a single report.
- Customize the sequence in which report sections appear in the report.

The following illustrates an example of JCL and control statements to produce a performance analysis report:

```

//CAZRPT01 JOB (job parameters)
//*
//STEP1 EXEC PGM=CAZPRINT
//STEPLIB DD DISP=SHR,DSN=hlq.SCAZAUTH
//SFILE01 DD DISP=SHR,DSN=measurement.file.name
//CAZLOG DD SYSOUT=*
//PRINT1 DD SYSOUT=*
//PDFFILE DD DISP=SHR,DSN=any.file
//*
/* Instream control statements.
/*
//CAZCTL DD *
*
  PROFILE 01 Input=SFILE01
*
  SECTION S01 Profile=01
  SECTION S02 Profile=01
  SECTION S03 Profile=01
  SECTION S04 Profile=01
  SECTION S05 Profile=01
  SECTION S06 Profile=01
  SECTION S07 Profile=01
*
  SECTION C01 Profile=01
  SECTION C02 Profile=01
  SECTION C03 Profile=01
  SECTION C04 Profile=01
  SECTION C05 Profile=01
*
  SECTION W01 Profile=01
*
  SECTION D01 Profile=01
  SECTION D02 Profile=01
  SECTION D03 Profile=01
  SECTION D04 Profile=01
*
  CONVERT Format=PDF DDNAME=PDFFILE
  PRINT DDNAME=PRINT1
*
/*

```

The above illustrates JCL and control statements that produce output in both line printer format and in PDF format. A brief explanation of the JCL statements is presented below. Detailed descriptions of each of the DD statements are then presented later in this section. For detailed descriptions of the control statements (ddname CAZCTL) see, "Specifying control statements" on page 571.

STEPLIB

The load library containing Application Performance Analyzer components. This can be omitted if Application Performance Analyzer is installed in a linklist library.

SFILE01

The measurement file.

CAZLOG

Output file for error and informational message.

PRINT1

Output file for the line printer report.

PDFFILE

Output file for the PDF report.

CAZCTL

Control statements.

The input measurement file

You must provide a DD statement for the file (the “sample file”) containing the Application Performance Analyzer measurement data. You can choose any DD name for this file; the DD name is referred to in a PROFILE control statement. The DSN of the measurement file can be determined by displaying the ISPF report S01: Session Statistics or by entering the “++” line command to the item in the Observation Session List ISPF dialog.

Multiple measurement files

Typically you will produce a report to analyze data from a single measurement file. Application Performance Analyzer also allows you to produce multiple reports in a single job step. You can even include report sections from separate measurement files in a single report. In either event, you need to specify a separate DD statement and a separate PROFILE control statement for each measurement file.

The CAZLOG log file

You must supply a DD statement for DD name CAZLOG. Application Performance Analyzer reports any errors or informational messages to this file. Typically, you will route this as a JES file.

The report output file

If you include a PRINT control statement to produce a line printer format report, you must also supply a DD statement for this output. Typically you will specify a JES output file. If you prefer to write this to a permanent file, specify a FB or FBA file with LRECL=121. If your job step is to produce multiple line printer reports, you must supply a DD statement (and a corresponding PRINT statement) for each one.

The PDF output file

If you include a CONVERT control statement to produce a report in PDF format, you must also supply a DD statement for this file. This must be a FB, LRECL=80 file. If your job step is to produce multiple PDF reports, you must supply a DD statement (and a corresponding CONVERT statement) for each report.

Downloading and viewing a PDF file

In order to view or print a PDF file you must perform a file transfer operation to download the file to a PC. When downloading (using IND\$FILE or FTP) be sure to download in binary. Do not specify ASCII translation or CRLF. Once you have downloaded the file you can use any version of the Adobe PDF Viewer (Acrobat) program capable of displaying PDF version 1.3.

The XML document file

If you include a CONVERT control statement to produce a report in XML document format, you must also supply a DD statement for this file. This must be a FB, LRECL=255 file.

If your job step is to produce multiple XML document files, you must supply a DD statement (and corresponding CONVERT statement) for each document file.

Application Performance Analyzer creates a version 1.0 self-contained XML document using EBCDIC encoding (ebcdic-cp-us/Cp037). See Appendix C, “XML document layout,” on page 697 for a complete description of the XML document.

Processing and transferring an XML document file

The XML document file containing the report data can be browsed or edited on the mainframe, or transferred to another platform for further processing. When transferring to another platform, appropriate character set translation may be required; including carriage return and line feed characters.

Specifying control statements

The CAZCTL DD statement specifies a file containing a sequence of control statements. These control statements can be included as instream data or the DD statement can allocate a SYSIN-type member. The DD statement and the control statements are mandatory.

General syntax rules

The syntax rules for control records are as follows:

- An asterisk (*) in column 1 indicates a comment record.
- Double slashes (//) and any characters to the right are ignored. This can be used to include comment text to the right of the statement text.
- Data in columns 73 to 80 is ignored.
- A statement consists of a verb followed by positional and keyword parameters. The allowable verbs are: PROFILE, SECTION, MAP, CONVERT, PRINT. If there are positional parameters, they must be coded before any keyword parameters.
- The verb and the positional and keyword parameters must be separated from each other by a comma and/or at least one space.
- A value containing embedded spaces must be enclosed in quotes.
- A statement can span multiple records, but a single parameter expression must be on a single record.
- Unless otherwise noted, commands are not case sensitive.

The PROFILE statement

The PROFILE statement specifies a measurement file. The format of the PROFILE statement is shown here:

```
PROFILE nn INPUT=ddn|INPUTDSN=dsn
```

The PROFILE statement requires two parameters. The first mandatory parameter is positional and specifies a numeric value from 01 to 99. This effectively labels the PROFILE statement. There is a special case where multiple PROFILE statements with the same numeric label are specified. This is for Variance reporting and is described below.

In most cases, you will only specify one PROFILE statement and this value will be 01. Specify multiple PROFILE statements if you want to report on input from more than one measurement file in a single CAZPRINT step (or print a Variance report as described below). When you specify more than one PROFILE statement, each must specify a unique value in this parameter.

You must also code either the INPUT or INPUTDSN keyword parameter. The INPUT keyword parameter specifies the DD name of the input measurement file. There must be a corresponding DD statement in the JCL. The INPUTDSN keyword parameter specifies the dataset name of the input measurement file. In this case, it is not necessary to include a corresponding DD statement in the JCL.

TYPE keyword for Variance report

To print a Variance report, you need to specify the Tagged measurement files as well as the base measurement file to which they are to be compared. In this case, additional PROFILE statements with the same numeric label are coded, and a TYPE=TAGGED keyword is added. Up to 20 PROFILE statements with TYPE=TAGGED are permitted. An example of two PROFILE statements for Variance reporting is shown below:

```
PROFILE 01 INPUT=SF02 TYPE=TAGGED
PROFILE 01 INPUT=SF01
```

There must be corresponding DDNAMEs for the two PROFILE INPUT keywords.

The MAP statement

The MAP statement specifies source program mapping information. This statement is required if you want the report to include mapping of addresses to application source statements.

An example of a MAP statement is shown here:

```
MAP TYPE=L FILE=TEST1.PGM.LISTINGS MEMBER=COBTEST1 PROFILE=01
```

MAP statements are optional and must be placed after their corresponding PROFILE statement(s) and before PRINT or CONVERT statements. Each MAP statement specifies a file that contains information enabling Application Performance Analyzer to map sampled addresses to source program statements.

MAP statement parameters

TYPE This keyword parameter is mandatory and specifies the type of source mapping input data. You must specify one of the following values:

- L** To specify that the input file is a compiler listing.
- S** To specify that the input file is a LANGX SideFile.
- A** To specify that the input file is an assembler ADATA file.
- D** To specify that the input file is a SYSDEBUG file.

FILE This keyword parameter is mandatory and specifies the data set name of the file containing source mapping information.

MEMBER

This keyword parameter is optional and specifies the member name of the file. You must include the MEMBER parameter if the FILE parameter specifies a partitioned data set.

PROFILE

This keyword parameter is optional. Specify the profile number here – a numeric value between 01 and 99. The value must match a value specified in the first parameter of a PROFILE statement. If omitted, a value of 01 is assumed.

The SECTION statement

The SECTION statement specifies a section to be included in the report. At least one SECTION statement is required. SECTION statements must be placed after their corresponding PROFILE statement(s) and before PRINT or CONVERT statements. An example of a SECTION statement is shown here:

```
SECTION C01 PROFILE=01 Levels=9 Minimum=2.5 MLD=Y
```


The above example specifies that the C01 section (CPU Analysis by Category) be included in the report. PROFILE=01 refers to the PROFILE statement that specifies the measurement file from which the report section is to be produced.

Each SECTION statement can specify common parameters (those that apply to all report sections) and section-specific parameters (those that apply to specific section types). The common parameters are described here. Descriptions of the section-specific parameters are presented in “Report SECTION descriptions” on page 575.

SECTION statement common parameters

Section code

This is the first (and only) positional parameter and is mandatory. It specifies a code identifying the type of report section. It is always 3 characters in length. The first character is alphabetic and the second and third characters are numeric.

PROFILE

This keyword parameter is optional. Specify the profile number here – a numeric value between 01 and 99. The value must match a value specified in the first parameter of a PROFILE statement. If omitted, a value of 01 is assumed. By referring to a PROFILE statement, this parameter specifies the measurement file from which the report section is to be built.

The PRINT statement

The PRINT statement tells CAZPRINT to write the report in conventional line printer format – a sequential file with ANSI carriage control characters. The report will contain each of the sections specified in SECTION statements. The sections are arranged in the report in the same sequence in which the SECTION statements appeared.

An example of a PRINT statement is shown here:

```
PRINT DDNAME=PRINT1 MLD=N
```

PRINT statement parameters

DDNAME

The DDNAME keyword parameter is mandatory. This specifies the DD name for the report output. A corresponding DD statement must be provided in the JCL.

LANG

The LANG keyword parameter is optional. If omitted it defaults to ENU to indicate the reports are to be created in the English language. Other acceptable values are JPN for Japanese and KOR for Korean.

MLD The MLD keyword parameter is optional, if omitted it defaults to Y. This specifies whether or not Multi-Line Descriptions should be printed (Y=Yes, N=No). This is similar to the PREF option in Application Performance Analyzer ISPF: “Show long descriptions on multiple lines,” and when generating JCL with Application Performance Analyzer ISPF, the PREF setting will be used to set MLD.

The CONVERT statement

A CONVERT statement can be specified instead of or in addition to a PRINT statement. Like PRINT, CONVERT tells CAZPRINT to write the report and specifies the output destination. Instead of writing the report in conventional line

printer format, the CONVERT statement creates a report file in an alternate format; either PDF or XML. When XML is specified, a PRINT statement cannot be included in the job step. You cannot include a CONVERT statement for PDF and a CONVERT statement for XML in the same job step.

Two examples of CONVERT statements are shown here.

```
CONVERT DDNAME=PDF1 FORMAT=PDF MLD=N
CONVERT DDNAME=XML1 FORMAT=XML LANG=ENU MLD=N
```

CONVERT statement parameters

DDNAME

This mandatory parameter specifies the DD name of a file to which the converted report is to be written. A corresponding DD statement must be included in the JCL. When requesting a PDF, the file must be sequential, in FB format with 80 byte records. When requesting an XML document, the file must be sequential, in FB format with 255 byte records.

FORMAT

This mandatory parameter specifies the format to which the report is to be converted. It must specify PDF or XML.

LANG

The LANG keyword parameter is optional. If omitted it defaults to ENU to indicate the reports are to be created in the English language. Other acceptable values are JPN for Japanese and KOR for Korean.

MLD The MLD keyword parameter is optional, if omitted it defaults to Y. This specifies whether or not multi-line descriptions should be printed (Y=Yes, N=No). This is similar to the PREF option in Application Performance Analyzer ISPF: "Show long descriptions on multiple lines," and when generating JCL with Application Performance Analyzer ISPF, the PREF setting will be used to set MLD.

Reports in PDF format

Application Performance Analyzer can produce a report in the form of a PDF (Portable Document Format) file. On the mainframe, this is written to a sequential file with fixed-length 80 byte records. To view or print the file you will need to download it to a PC using either IND\$FILE file transfer or FTP. No data conversion is required, so be sure to specify a binary file transfer. The content in an Application Performance Analyzer PDF report is essentially the same as a corresponding SYSOUT report. However, PDF's advanced formatting capabilities make this format more readable than a SYSOUT report.

Reports in XML document format

Application Performance Analyzer can produce an XML (Extensible Markup Language) document file containing the selected report information. On the mainframe, this is written to a sequential file with fixed-length 255 byte records. It is encoded in EDBCIC (ebcdic-cp-us/Cp037) and may be viewed, edited, or processed on the mainframe. If the XML document file is required on another platform, it may need character set translation, including carriage return and line feed characters. After the document file has been transferred to the target platform, ensure that the encoding attribute on the XML declaration is changed to the appropriate value. For example, when downloading the file to a Windows platform, using IND\$FILE file transfer, the ASCII and CRLF parameters must be

specified. After the file transfer is complete, the encoding attribute on the XML declaration must be changed to UTF-8 in the Windows document file.

The XML file is a stand-alone document and has been declared as such. For the most part, the XML elements and tags can be related to their corresponding report fields by the element names and structure. For a complete description of the XML document, see Appendix C, “XML document layout,” on page 697.

Report SECTION descriptions

This section describes the report sections that you can include in a performance analysis report and the parameters that can be specified on the corresponding SECTION statements.

SECTION statement parameter summary

Each section requires a SECTION statement. SECTION statements for some report sections accept (or require) certain keyword parameters that allow you to set formatting options. The following table summarizes the available report sections, their parameters, and their default values. The Sequence parameter accepts different values, depending on the report section. For each report section, the acceptable values are listed, with the default value listed first.

These defaults only apply until you change them by selecting the report in A02: Request Printed Reports, after that Application Performance Analyzer will “remember” your selections.

| Report section | Section ID | Parameters and default values |
|-------------------------------|------------|--|
| Measurement Profile | S01 | |
| Load Module Attributes | S02 | Sequence=NAME/ADDRESS/ SIZE/LIBRARY OmitESD=N OmitNUC=N OmitPLPA=N Omitdup=N |
| Load Module Summary | S03 | Sequence=NAME/ADDRESS/ SIZE/LIBRARY |
| TCB Summary | S04 | |
| Memory Usage Timeline | S05 | Intervals=45 |
| Data Space Usage Timeline | S06 | Intervals=45 |
| TCB Execution Summary | S07 | |
| Processor Utilization Summary | S08 | |
| Measurement Analysis | S09 | |
| CPU Usage by Category | C01 | Levels=9 Sequence=VALUE/NAME DPAGroup=Y ShowDB2=Y Minimum=0.00 MLD=Y Datamg=Y ShowIMS=Y ADABAS=Y |

| Report section | Section ID | Parameters and default values |
|--------------------------------|------------|---|
| CPU Usage by Module | C02 | Levels=9 Sequence=VALUE/NAME Minimum=0.00 MLD=Y |
| CPU Usage by Code Slice | C03 | Levels=9 Sequence=VALUE/ ADDRESS/LOCATION SliceSize=64 Minimum=0.00 |
| CPU Usage Timeline | C04 | Intervals=45 |
| CPU Usage Task/Category | C05 | Levels=9 Sequence=VALUE/NAME DPAGroup=Y ShowDB2=Y ShowInact=Y MLD=Y Datamg=Y ShowIMS=Y ADABAS=Y |
| CPU Usage Task/Module | C06 | Levels=9 Sequence=VALUE/NAME ShowInact=Y MLD=Y |
| CPU Usage by Procedure | C07 | Sequence=VALUE/NAME OmitCPU=N |
| CPU Usage Referred Attribution | C08 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| CPU Usage by PSW/ObjCode | C09 | Levels=2 Sequence=VALUE/ADDRESS |
| DASD Usage by Device | D01 | Levels=9 Sequence=VALUE/NAME Minimum=0.00 |
| DASD Usage by DDNAME | D02 | Levels=9 Sequence=VALUE/NAME Minimum=0.00 |
| DASD Usage by Dataset | D03 | Levels=9 Sequence=VALUE/NAME Minimum=0.00 |
| Dataset Attributes | D04 | Sequence=FILE/DSN |
| DASD EXCP Summary | D05 | Sequence=VALUE/NAME OmitEXCP=N |
| DASD VSAM Statistics | D06 | Sequence=VALUE/NAME OmitEXCP=N |
| DASD Activity Timeline | D07 | Sequence=VALUE/NAME OmitEXCP=N |
| DASD I/O Wait Time | D08 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| VSAM Buffer Pool Usage | D09 | |

| Report section | Section ID | Parameters and default values |
|--------------------------------|------------|--|
| Wait Time by Task/Category | W01 | Level s=9 Sequence=VALUE/NAME DPAGroup=Y ShowDB2=Y ShowInact=Y MLD=Y Datamg=Y ShowIMS=Y ADABAS=Y |
| Wait Time by Task/Module | W02 | Level s=9 Sequence=VALUE/NAME ShowInact=Y MLD=Y |
| Wait Time Referred Attribution | W03 | Level s=9 Sequence=VALUE/NAME ShowInact=Y MLD=Y |
| Wait Time by Task ENQ/RESERVE | W04 | Level s=9 Sequence=VALUE/NAME MLD=Y |
| Wait Time by Tape DDNAME | W05 | Sequence=VALUE/NAME |
| IMS Measurement Profile | I01 | |
| IMS DL/I Call Timeline | I02 | |
| IMS Transaction Timeline | I03 | Level s=9 |
| IMS Txn Activity Timeline | I04 | Sequence=VALUE/NAME |
| IMS CPU Usage by PSB | I05 | Level s=9 Sequence=VALUE/NAME MLD=Y |
| IMS CPU Usage by Transaction | I06 | Level s=9 Sequence=VALUE/NAME MLD=Y |
| IMS CPU Usage by DL/I Call | I07 | Level s=9 Sequence=VALUE/NAME MLD=Y |
| IMS WAIT Time by PSB | I08 | Level s=9 Sequence=VALUE/NAME MLD=Y |
| IMS WAIT Time by Transaction | I09 | Level s=9 Sequence=VALUE/NAME MLD=Y |
| IMS WAIT Time by DL/I Call | I10 | Level s=9 Sequence=VALUE/NAME MLD=Y |
| IMS DL/I Activity by PSB | I11 | Level s=9 Sequence=VALUE/NAME MLD=Y |
| IMS DL/I Activity by Txn | I12 | Level s=9 Sequence=VALUE/NAME MLD=Y |
| IMS DL/I Activity by DL/I Call | I13 | Level s=9 Sequence=VALUE/NAME MLD=Y |
| IMS PSB/PCB Attributes | I14 | |

| Report section | Section ID | Parameters and default values |
|---|------------|--|
| IMS DL/I Call Attributes | I15 | |
| IMS Transaction Service Times | I16 | |
| IMS Transaction DL/I Counts | I17 | Levels=9 |
| IMS CPU/Svc Time by DL/I Call | I18 | Sequence=VALUE/NAME |
| IMS CPU/Svc Time by PSB | I19 | Sequence=VALUE/NAME |
| IMS CPU/Svc Time by Txn | I20 | Sequence=VALUE/NAME |
| IMS CPU/Svc Time by PCB | I21 | Sequence=VALUE/NAME |
| CICS Session Statistics | E01 | |
| CICS CPU and Use Counts by Pgm | E02 | Sequence=VALUE/NAME/COUNT |
| CICS CPU Usage by Txn | E03 | Levels=9 Sequence=VALUE/NAME Minimum=0.00 MLD=Y |
| CICS Mean Service Time by Txn | E04 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| CICS Total Service Time by Txn | E05 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| CICS Service Time by Task ID | E06 | Levels=1 Sequence=VALUE/NAME MLD=Y |
| CICS WAIT by Txn | E07 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| CICS Mean Service Time by Trm | E08 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| CICS Total Service Time by Trm | E09 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| CICS Mean Service Time by user ID | E10 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| CICS Total Service Time by user ID | E11 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| CICS CPU/Service Time by Txn | E12 | Levels=2 Sequence=VALUE/NAME |
| CICS Mean Service Time by Txn (for multiple CICS address spaces) | X01 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| CICS Total Service Time by Txn (for multiple CICS address spaces) | X02 | Levels=9 Sequence=VALUE/NAME MLD=Y |

| Report section | Section ID | Parameters and default values |
|--|------------|--|
| CICS Mean Service Time by Term (for multiple CICS address spaces) | X03 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| CICS Total Service Time by Term (for multiple CICS address spaces) | X04 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| DB2 Measurement Profile | F01 | |
| DB2 SQL Activity Timeline | F02 | Levels=9 Sequence=THREAD/CPU/ DURATION |
| DB2 SQL Activity by DBRM | F03 | Levels=9 Sequence=VALUE/NAME Minimum=0.00 |
| DB2 SQL Activity by Statement | F04 | Levels=9 Sequence=VALUE/NAME Minimum=0.00 |
| DB2 SQL Activity by Plan | F05 | Levels=9 Sequence=VALUE Minimum=0.00 |
| DB2 SQL Statement Attributes | F06 | |
| DB2 SQL Wait Time by DBRM | F07 | Levels=9 Sequence=VALUE/NAME OfTotal=Y |
| DB2 SQL Wait Time by Statement | F08 | Levels=9 Sequence=VALUE/NAME OfTotal=Y |
| DB2 SQL Wait Time by Plan | F09 | Levels=9 Sequence=VALUE OfTotal=Y |
| DB2 SQL CPU/Svc Time by DBRM | F10 | Levels=1 Sequence=VALUE/NAME/ DURATION stmtPct=N |
| DB2 SQL CPU/Svc Time by Stmt | F11 | Levels=2 Sequence=VALUE/NAME/DURATION posSQL=Y negSQL=Y stmtSQL=N stmtPct=N |
| DB2 SQL CPU/Svc Time by Plan | F12 | Levels=2 Sequence=VALUE/DURATION stmtPct=N |
| DB2 SQL Threads Analysis | F13 | |
| DB2 CPU by Plan/Stored Proc | F14 | Levels=9 Sequence=VALUE/NAME DPAGroup=Y ShowDB2=Y MLD=Y |
| DB2 SQL CPU/Svc Time by Rq Loc | F15 | Levels=2 Sequence=VALUE/NAME/ DURATION stmtPct=N |

| Report section | Section ID | Parameters and default values |
|--------------------------------|------------|--|
| DB2 SQL CPU/Svc Time by Enclav | F16 | Levels=2 Sequence=VALUE/NAME/ DURATION stmtPct=N |
| DB2 SQL CPU/Svc Time by Corrid | F17 | Levels=2 Sequence=VALUE/NAME/ DURATION stmtPct=N |
| DB2 SQL CPU/Svc Time by Wkstn | F18 | Levels=2 Sequence=VALUE/NAME/DURATION stmtPct=N |
| DB2 SQL CPU/Svc Time by EndUsr | F19 | Levels=2 Sequence=VALUE/NAME/DURATION stmtPct=N |
| Coupling Facility Summary | G01 | |
| Coupling Facility Mean Times | G02 | Levels=9 |
| Coupling Facility Total Times | G03 | Levels=9 |
| MQSeries Activity Summary | Q01 | |
| MQSeries CPU Usage by Queue | Q02 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| MQSeries CPU Usage by Request | Q03 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| MQSeries CPU Usage by Txn | Q04 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| MQSeries Serv Time by Queue | Q05 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| MQSeries Serv Time by Request | Q06 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| MQSeries Serv Time by Txn | Q07 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| MQSeries Wait Time by Queue | Q08 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| MQSeries Wait Time by Request | Q09 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| MQSeries Wait Time by Txn | Q10 | Levels=9 Sequence=VALUE/NAME MLD=Y |
| Source Program Attribution | P01 | Program=pgmname (no default value) AdjLines=4 AllSource=N AsmObj=Y Header=Y Percent=N |
| Java Summary/Attributes | J01 | |

| Report section | Section ID | Parameters and default values |
|-------------------------------|------------|--|
| Java CPU Usage by Package | J04 | Levels=2 Sequence=VALUE/NAME MLD=Y |
| Java CPU Usage by Class | J05 | Levels=2 Sequence=VALUE/NAME MLD=Y |
| Java CPU Usage by Method | J06 | Levels=2 Sequence=VALUE/NAME MLD=Y |
| Java CPU Usage by Call Path | J07 | Levels=2 Sequence=VALUE/NAME MLD=Y |
| Java Svc Time by Package | J09 | Levels=2 Sequence=VALUE/NAME MLD=Y |
| Java Svc Time by Class | J10 | Levels=2 Sequence=VALUE/NAME MLD=Y |
| Java Svc Time by Method | J11 | Levels=2 Sequence=VALUE/NAME MLD=Y |
| Java Svc Time by Call Path | J12 | Levels=2 Sequence=VALUE/NAME MLD=Y |
| Java Wait Time by Package | J14 | Levels=2 Sequence=VALUE/NAME MLD=Y |
| Java Wait Time by Class | J15 | Levels=2 Sequence=VALUE/NAME MLD=Y |
| Java Wait Time by Method | J16 | Levels=2 Sequence=VALUE/NAME MLD=Y |
| Java Wait Time by Call Path | J17 | Levels=2 Sequence=VALUE/NAME MLD=Y |
| HFS Service Time by Path Name | H01 | Sequence=VALUE/FILEID/PATHNAME Minimum=0.00 MLD=Y |
| HFS Service Time by Device | H02 | Levels=2 Sequence=VALUE/DEVID/DEVICE Minimum=0.00 MLD=Y |
| HFS File Activity | H03 | Sequence=VALUE/FILEID/PATHNAME OmitEXCP=N |
| HFS File Attributes | H04 | |
| HFS Device Activity | H05 | Sequence=VALUE/DEVID/DEVICE OmitEXCP=N |
| HFS Device Attributes | H06 | |
| HFS Activity Timeline | H07 | Sequence=VALUE/FILEID/PATHNAME OmitEXCP=N |

| Report section | Section ID | Parameters and default values |
|------------------------------|------------|---|
| HFS Wait Time by Path Name | H08 | Sequence=VALUE/FILEID/PATHNAME Minimum=0.00 MLD=Y |
| HFS Wait Time by Device | H09 | Levels=2 Sequence=VALUE/DEVID/DEVICE Minimum=0.00 MLD=Y |
| HFS Service Time by Request | H10 | Levels=2 Sequence=VALUE/REQID/REQUEST Minimum=0.00 MLD=Y |
| HFS Wait Time by Request | H11 | Levels=2 Sequence=VALUE/REQID/REQUEST Minimum=0.00 MLD=Y |
| Measurement Variance Summary | V01 | |

SECTION parameter descriptions

The SECTION statement parameters are described in the following list. They are presented in alphabetical keyword sequence.

ADABAS This parameter applies to report sections that can attribute measured system activity to Adabas while it is processing Adabas calls. Specify Y to display measurements in routines that were processing Adabas calls in a separate ADABAS category.

AdjLines

Specifies the number of adjacent source lines. This applies to the reporting of source program lines and attribution of system activity to source statements. Source statements for which system activity is measured will be reported, but those statements for which no activity is measured are normally omitted. The value of this parameter specifies the number of source lines immediately preceding and following any line with measured activity that are also to be included in the report. This helps provide some context for isolated source lines with measured activity.

AllSource

This applies to the reporting of source program lines. A value of Y specifies that all source lines are to be shown in the report, including those for which no system activity is attributed. A value of Y in this parameter overrides any value specified in the AdjLines parameter. Specify N to control which lines are reported using the AdjLines parameter.

AsmObj

This applies to the reporting of source program lines for an assembler program. Specify Y to include object code (from the assembly listing) in each source line. Specify N to omit object code.

Datamg

This parameter applies to report sections that attribute measured system activity to the data management processing category. Specify Y to display measurements in routines that were servicing data management requests in a separate DATAMG category. This includes basic access functions (such as READ and WRITE) to files. Processing of OPEN and CLOSE functions is not included in this category.

DPAGroup

This parameter applies to report sections that attribute measured system activity to program categories. This attribution can be done to Groups or Subgroups. A group is a higher level (more inclusive) categorization than a subgroup. For example, activity in DB2 modules can be attributed to the group "DB2 Subsystem" or, alternatively, to subgroups such as "Buffer Manager," "Call Attachment Facility," "Data Manager," etc. Specify DPAGroup=Y to attribute to group and DPAGroup=N to attribute to subgroup.

Header This applies to the P01 source program report. A value of Y specifies that detailed information about the source program is to appear in the heading area in each page in the report section. This information includes: source mapping file name and type, compile date and time, compiler product and version.

Intervals

This applies to "timeline" report sections in which measurement information is reported in equal time intervals. It specifies the number of intervals into which the report section is to be divided, which is generally, one line per interval. The value must be between 2 and 256.

Levels

This applies to report sections in which lines are arranged in a hierarchy. The value, a single numeric digit: 0 to 9, specifies the number of hierarchical levels to be included in the report. These are equivalent to the ISPF report line items in which the "+" line command is used to expand the hierarchy.

Minimum

This applies to report sections that allow you to exclude measurements of objects when those measurement values are below the specified minimum. The unit is percentage and is expressed as two digits, followed by an optional decimal point and up to two decimal places.

MLD This applies to report sections where DPA descriptions are reported. The MLD=Y parm is used to specify that Multi Line Descriptions should be printed, so that you can see all of the description text. MLD=N specifies that Multi Line Descriptions should not be printed, in which case only one line per module/csect will be printed, and the description will be truncated if it does not fit on one line.

negSQL This applies to report sections where CPU/Service time is reported by SQL statement. Specify Y to include SQL statements that end in a negative SQLCODE.

Oftotal

This applies to report sections in which SQL wait time is reported. Specify Y to quantify wait time as a percentage of total measurement interval. Specify N to quantify as a percentage of the SQL service time.

OmitCPU

This parameter applies to reports where CPU activity is attributed to program procedures. Specify Y to exclude procedures for which no CPU activity was measured, N to include them.

Omitdup

This parameter applies to report sections in which load modules are reported. A value of Y specifies that modules that have been reloaded at a new address, but have the same name and size to be reported only once.

OmitESD

This applies to report sections in which detailed information about load modules is reported. A value of Y specifies that ESD (External Symbol Dictionary) information is not to be reported.

OmitEXCP

This applies to report sections in which the number of EXCPs or read/write count is reported for files or devices. Specify Y to exclude files or devices for which no EXCPs or read/writes were counted, or specify N to include them.

OmitNUC

This applies to report sections in which load modules are reported. A value of Y specifies that Nucleus modules are to be excluded from the report.

OmitPLPA

This applies to report sections in which load modules are reported. A value of Y specifies that PLPA (Pageable Link Pack Area) modules are to be excluded from the report.

Percent

This applies to the source mapping report section - P01. Specify Y to display the values for the source statement as a percentage, or specify N to display values as a count. This is only applicable when source mapping a report that shows percentages.

posSQL This applies to report sections where CPU/Service time is reported by SQL statement. Specify Y to include SQL statements that end successfully; that is, with a zero or positive SQLCODE.

Program

This applies to the source mapping report section (P01). It specifies the name of the source program to reported.

Pseudo

This applies to the source mapping report section - P01. Specify Y to display C/C++ pseudo-assembly.

Sequence

This specifies the sequence in which items in the report are to be sorted. Possible values for this parameter are listed below. Not all values are appropriate for each report.

- ADDRESS to sort in ascending sequence by load module address
- CPU to sort in descending sequence by SQL CPU time
- DSN to sort in ascending sequence by dataset name
- DURATION to sort in descending sequence by SQL call duration or service time
- FILE to sort in ascending sequence by DDName
- LIBRARY/LOADLIB to sort in ascending sequence by load library name
- LOCATION to sort in ascending sequence by the address of the start of the code slice in the form of csect or module plus offset
- NAME to sort in ascending sequence by item name
- SIZE to sort in ascending sequence by load module size
- THREAD to sort chronologically by DB2 thread
- VALUE to sort in descending sequence by amount of measured activity

ShowDB2

This parameter applies to report sections that can attribute measured

system activity to DB2 while it is processing SQL requests. Specify Y to display measurements in routines that were processing SQL requests in a separate DB2SQL category.

ShowIMS

This parameter applies to report sections that can attribute measured system activity to IMS while it is processing DLI calls. Specify Y to display measurements in routines that were processing DLI calls in a separate IMSDLI category.

ShowInact

This parameter is generally applicable to report sections that present information by TCB (Task). A value of Y (normally the default) specifies that information for inactive tasks is to be included in the report. An inactive task is one which was observed to be in a wait state for the full duration of the observation session.

SliceSize

This parameter applies to report sections that present information by code slice (block of storage containing object code). Use this parameter to vary the code slice size. A code slice size value must be between 4 and 99992 and must be an even value that is divisible by 4.

stmtPct

This parameter applies to DB2 reports that display mean times. When 'Y' is specified, the mean times are replaced with the percent of total used.

stmtSQL

This applies to report sections where CPU/Service time is reported by SQL statement. Specify Y to consolidate dynamic SQL statements by statement number, ignoring differences in SQL statement text. When 'Y' is specified, one line is displayed per statement number regardless of the contents of the SQL statement text. When 'N' is specified, one line is displayed for each unique dynamic SQL statement.

Chapter 12. Batch interface commands

Application Performance Analyzer has a command language which allows you to submit requests using JCL. The command language can be used to create the same types of requests available in Application Performance Analyzer/ISPF.

Application Performance Analyzer also provides a batch import program to load the sample file of a completed observation request. This program can be used as an alternative to the IMPORT command available in Application Performance Analyzer/ISPF.

| For information about ... | See ... |
|--|---------------------------------------|
| General syntax, types of commands and examples | "Command syntax" |
| Command summary diagram | "Command summary diagram" on page 588 |
| Setting up the JCL | "Sample JCL" on page 590 |
| Coding the NEW command, with keyword descriptions and examples | "NEW" on page 595 |
| Coding the TNEW command | "TNEW" on page 602 |
| Coding the DELETE command | "DELETE" on page 603 |
| Coding the KEEP command | "KEEP" on page 603 |
| Coding the CANCEL command | "CANCEL" on page 603 |
| Batch Import command | "Batch import" on page 603 |

Command syntax

The batch interface command format consists of a single high level command keyword (NEW, TNEW, DELETE, KEEP, or CANCEL) followed by a series of keywords and parameters in the format: KEYWORD=(parameter1, parameter2,...).

If there is only one parameter specified for a keyword, then the parentheses "(...)" are optional. For example, DURATION=120 and DURATION=(120) are both acceptable.

When a list of parameters is specified, the parentheses "(...)" are mandatory. For example, FEATURES=(CICS,IMS,DB2).

A semicolon must be present at the end of the command string.

Example of NEW command

The following example create a new observation request. It requests that job CAZTEST01 be measured for 60 seconds and 10000 samples, with the IMS and DB2 features turned on.

```
NEW JOBNAME=CAZTEST01
ACTIVE=NO
SAMPLES=10000 DURATION=60
FEATURES=(IMS,DB2)
;
```

Example of TNEW command

The following example creates a new threshold observation request. It requests that the second step in job TSTJOB01 be measured for 60 seconds and 10000 samples. The measurement starts only when the CPU time for step 2 in TSTJOB01 exceeds 30 seconds and the EXCP count exceeds 20000.

```
TNEW JOBNAME=TSTJOB01
ACTIVE=NO
STEP=(2)
SAMPLES=10000 DURATION=60
TMSSEL=("CPU=30 EXCP=20000")
;
```

Example of DELETE command

The following example deletes observation 0985.

```
DELETE REQNUM=0985
;
```

Example of KEEP command

The following example applies the KEEP command to observation 0985. This means the request will be kept until it is manually deleted, no expiration date will apply.

```
KEEP REQNUM=0985
;
```


Example of CANCEL command

The following example cancels active observation 0985.


```
CANCEL REQNUM=0985
;
```

Command summary diagram

This diagram shows a summary of the parameters allowed in a NEW command, they are described in detail on the following pages.



1



└─ RUNAGAIN=(mmm, FOR=nn) ─┘

Sample JCL

The following illustrates an example of how to set up the Batch Interface JCL and create a basic measurement request. There is a sample template of this JCL supplied in *hlq.SCAZSAMP* in member CAZBATCH.

```
//SAMPJOB1 JOB (job parameters)
//*
//CAZBATCH EXEC PGM=CAZBATCH,PARM='STCID=CAZ0'
//STEPLIB DD DISP=SHR,DSN=hlq.SCAZAUTH
//SYSPRINT DD SYSOUT=*
//SYSIN DD *
NEW JOBNAME=APPJOB01
ACTIVE=NO
SAMPLES=5000 DURATION=30
DESCR='Sample request for APPJOB01'
;
/*
//
```

The above example uses the Application Performance Analyzer started task named CAZ0 as specified on the EXEC statement as PARM='STCID=CAZ0'. You must specify your Application Performance Analyzer started task name here. This parameter can be omitted if only one instance of Application Performance Analyzer is running on your image.

In STEPLIB, replace *hlq* with the high-level qualifier used for Application Performance Analyzer in your installation.

The commands in the above example create a NEW request to measure job APPJOB01, which is not yet active, for 5000 samples with a duration of 30 seconds. A user composed description is also specified.

Using the API to submit a command

This section describes how to code a call to the Application Performance Analyzer command API in an application program. The command API can be called from Assembler, COBOL, PL/I, C or C++ programs. Sample programs for each language are shipped in *hlq.SCAZSAMP*.

The sample program names for each language are:

- Assembler: CAZAPASM
- C: CAZAPC
- C++: CAZAPCC
- COBOL: CAZAPCOB
- PL/I: CAZAPPLI

Notes:

1. You must modify the sample code to contain the started task and the system parameters.
2. You must modify the COBOL sample code CAZAPCOB.

Environment

Authorization

Problem state key 8, Supervisor state any key

Dispatchable unit mode

TCB

Cross memory mode

PASN = SASN = HASN

Amode

24-bit, 31-bit, or 64-bit

ASC mode

Primary or AR

Interrupt status

Enabled for I/O and external interrupts

Locks

No locks held

Control parameters

Must be in the primary address space, key 8, and below the bar

Error recovery

The API does not provide error recovery

Input registers

Upon entry to CAZAPI01, the general purpose registers (GPRs) contain:

| Register | Contents |
|----------|--|
| 1 | Address of a standard CALL parameter list. |
| 13 | Address of a standard register 72-byte save area that must be addressable in primary mode and below the bar. |
| 14 | Return address. |
| 15 | Entry address of CAZAPI01. |

Output registers

When control returns to the caller, the general purpose registers (GPRs) contain:

| Register | Contents |
|----------|--------------------------------------|
| 0 | Reason code. |
| 1 | Used as a work register by CAZAPA01. |
| 2-13 | Unchanged. |
| 14 | Used as a work register by CAZAPI01. |
| 15 | Return code. |

When control returns to the caller, the access registers (ARs) contain:

| Register | Contents |
|----------|--------------------------------------|
| 0 | Used as a work register by CAZAPI01. |
| 1-15 | Unchanged. |

Syntax

```
CALL CAZAPI01, (Command,  
Reply,  
STCID,  
return_code,  
reason_code,  
) , VL
```

It is recommended that the calling program pre-fetch CAZAPI01 instead of including the module in your load module during the link-edit step. This way you can avoid relinking your load module if a newer version of CAZAPI01 becomes available.

Parameters

Command

Specifies a 2-byte length field followed by the input command string to be submitted to Application Performance Analyzer. The length field describes the length of the command string only; it does not include the length of this length field.

Reply

Specifies a 2-byte length field followed by a buffer used by CAZAPI01 to return one or more information/error messages describing the result of processing the command. The length field must contain the maximum length of this buffer; it does not include the length of this length field. It is recommended that the buffer be a minimum of 512 bytes long and be initialized to nulls so that the caller can easily determine whether messages have been returned or not.

If messages are returned then each message will be terminated by a single null character, the last message will be terminated by two consecutive null characters. The length field will be updated to contain the length of the messages including all null characters.

STCID

Specifies a 4-byte field that contains the Application Performance Analyzer STCID to which the command will be submitted. The STCID must be left justified and blank padded.

If the first byte of this field is blank or null then CAZAPI01 will attempt to connect to the currently executing Application Performance Analyzer started task. If more than one Application Performance Analyzer STC is active the request will fail.

return_code

Specifies a 4-byte field to contain the return code.

reason_code

Specifies a 4-byte field to contain the reason code.

VL

Must be coded and causes the high-order bit of the last parameter address to set to 1.

Return codes

When CAZAPI01 returns control to your program, GPR 15 and *return_code* contain a return code. The following list identifies return codes in hexadecimal format and describes what each means:

- 00 The operation was successful.
- 08 The operation failed because of an error. (Refer to reason code for an explanation of the error.)

Reason codes

When CAZAPI01 returns control to your program, GPR 0 and *reason_code* contain a reason code. The following table identifies reason codes in hexadecimal and decimal formats and describes what each means:

Table 19. Reason codes

| Hexadecimal | Decimal | Explanation |
|-------------|---------|---|
| 00 | 00 | Not applicable. |
| 04 | 04 | Caller is not running in TCB mode. |
| 08 | 08 | Caller's PASN and SASN are not equal. |
| 0C | 12 | Caller is not running with DAT-on. |
| 10 | 16 | Caller is running disabled. |
| 14 | 20 | Caller is in problem state and not key 8. |
| 18 | 24 | Caller is not in primary or AR ASC modes. |
| 1C | 28 | The STCID field contained a null or blank first character, CAZAPI01 attempted to access the currently executing Application Performance Analyzer STC but found more than one STC executing. |
| 20 | 32 | The specified STCID was not defined to this system. |
| 24 | 36 | There are no Application Performance Analyzer STCs active on this system. |
| 28 | 40 | The specified STCID is not currently active on this system. |
| 2C | 44 | Application Performance Analyzer's name token was not created. This indicates that no Application Performance Analyzer STC has ever been started on this system since the last IPL. |
| 30 | 48 | Command string contains an unrecognized command verb. Currently, only the CANCEL, DELETE, KEEP, NEW and TNEW commands are allowed to be submitted via this API. |

Table 19. Reason codes (continued)

| Hexadecimal | Decimal | Explanation |
|-------------|---------|--|
| 34 | 52 | The Application Performance Analyzer STC detected an error while processing the command. Refer to the message(s) returned in the Reply buffer for more information. |
| 38 | 56 | The Application Performance Analyzer STC command interface has abended. Depending on the error, an SVC dump may have been created. If an SVC dump was not produced then, the interface's error recovery will have percolated the abend up to the next error handler in the caller's address space. |

Abend code

CAZAPI01 will produce a user abend code: 4085 in the event of an recoverable error. The following table identifies abend reason codes in hexadecimal and decimal formats and explains the reason for the abend:

Table 20. Abend code

| Hexadecimal | Decimal | Explanation |
|-------------|---------|--|
| FA0 | 4000 | The input parameter pointer was zero. |
| FA4 | 4004 | Either the input command pointer was zero or the length field contained zeros. |
| FA8 | 4008 | Either the reply command pointer was zero or the length field contained zeros. |
| FAC | 4012 | The STCID pointer was zero. |
| FB0 | 4016 | The return_code pointer was zero. |
| FB4 | 4020 | The reason_code pointer was zero. |
| FB8 | 4024 | The VL bit was turned on prior to the last parameter. |
| FAC | 4028 | The VL bit was not turned on on the last parameter. |
| FC0 | 4032 | Internal error. Contact product support. |
| FC4 | 4036 | Internal error. Contact product support. |

Command descriptions

NEW

The NEW command is used to create a new Observation Request.

NEW

Mandatory.

Indicates that this is a NEW request.

JOBNAME

Mandatory.

Specifies the name of the job (or started task or TSO user) to be measured.

Creating multi-job measurements (%)

You can also specify a special pattern character of percent sign "%".

This acts as a place holder for zero or more characters in the name. It can be placed anywhere in the name except as the ninth character in an eight character jobname. A patterned name indicates that you want to measure all active jobs whose jobname matches the pattern. You cannot specify a jobname pattern of "%".

The maximum number of jobs that can be measured from a multi-job request is defined during the installation of Application Performance Analyzer. When this limit is exceeded, Application Performance Analyzer stops creating measurements for this request, and the status of the request is displayed as 'Stoppd'. The measurements that executed (within the limit) are accessible for report viewing under the request. To increase the limit, contact your system programmer.

Example: %MSMPP% causes one sampling request to be created for each active job whose jobname contains "MSMPP".

The ASID keyword is ignored when the jobname specifies a pattern.

The ACTIVE keyword is automatically set to YES when the jobname specifies a pattern.

Measuring a specific DB2 stored procedure or user-defined function

To measure a specific DB2 stored procedure or user-defined function, use a dash (-) for the JOBNAME. The information identifying the DB2 stored procedure or user-defined function must be supplied in the DB2SP keyword. The following keywords are also accepted; SYSTEMS, DESCR, SAMPLES, DURATION, NOTIFY, EXPDAYS, USSOBS, FEATURES, LIBS, DIRS and DB2IMAX. All other keywords are invalid and will result in an error. This feature is only available when the WLM Intercept is activated during Application Performance Analyzer installation, and you are given appropriate security access to it. Contact your system programmer for access if necessary.

SYSTEMS

Mandatory within a sysplex.

Specifies a target system within a sysplex. You can also enter an asterisk (*), in which case the target job is measured on the first system to run it. When an asterisk (*) is entered, the keyword ACTIVE=YES is invalid. This keyword is invalid in a non-sysplex environment.

Example: SYSTEMS=SYS3

DESCR

Optional unless set as mandatory during installation.

Specifies a free form text description for this observation request. The text must be within single quotes, and if mandatory must be a minimum of 8 characters.

Example: DESCR= 'Any user text goes here'

SAMPLES

Optional.

If omitted, the default number of samples will be used. Specifies the number of samples to take during the measurement.

Example: SAMPLES=10000

DURATION

Optional.

If omitted, the default duration will be used. Specifies the duration of the measurement in seconds.

Example: DURATION=120

NOTIFY

Optional.

Specifies a TSO userid to notify when the measurement ends.

Example: NOTIFY=USER01

RUNTOEOS

Optional.

Specify YES to indicate that the measurement should continue to run until the job step has completed, even if the target number of observations has been reached.

DELAYSAMPLING

Optional.

This indicates that sampling should be delayed for the specified amount of time (in seconds). After the target job step starts, Application Performance Analyzer will delay the start of the measurement for the number of seconds specified.

EXPDAYS

Optional.

If omitted the installation default will be used.

Specifies the number of days the measurement data for this observation request should be retained on before being automatically deleted. To keep the measurement data indefinitely, use EXPDAYS=0.

Example: EXPDAYS=30

USSOBS

Optional.

Specify the maximum number of spawned address spaces or substeps to measure for a USS observation, up to the maximum defined in the system configuration. The same sampling frequency will be used for each spawned address space or substep. Sampling overhead can be high if several spawned address spaces are running simultaneously.

When this field is specified, the collection of measurements will be grouped under a USS master record on the Observation List panel.

FEATURES

Optional.

Specifies which data extractors, if any, need to be turned on for this measurement. The data extractor values are: CICS, CICS+, IMS, IMS+, DB2, DB2+, DB2V, CDB2, MQS, Java, ADA. A list of data extractors is separated by commas.

If your installation has any default extractors set, the FEATURES command will override these. If you need to override default extractors and want to turn all extractors off, specify FEATURES=(BATCH).

Example: FEATURES=(CICS,DB2)

DB2IMAX

Optional.

Enter the value to limit the number of DB2+ SQL call interceptions for which full details will be written to the sample file. Collecting full details on every interception allows the F02 Timeline report to report exact times for all SQL calls. The F02 report will be truncated at the number of calls specified in this field. The DB2+ data extractor continues to collect the data it requires for the other reports for the duration of the measurement. The value cannot exceed the default value specified for DB2IMaxTraceSize during Application Performance Analyzer installation.

Example: DB2IMAX=(10000)

IMSIMAX

Optional.

Enter the value to limit the number of IMS+ DLI call interceptions for which full details will be written to the sample file. Collecting full details on every interception allows the I02 and I03 Timeline reports to report exact times for all DLI calls and IMS transactions. The I02 and I03 reports will be truncated at the number of calls specified in this field. The IMS+ data extractor continues to collect the data it requires for the other reports for the duration of the measurement. The value cannot exceed the default value specified for IMSIMaxTraceSize during Application Performance Analyzer installation.

Example: IMSIMAX=(10000)

LIBS

Optional.

Specifies additional load libraries to be searched. A list of data set names is separated by commas. A maximum of 10 data set names is allowed.

Example: LIBS=(USER1.LOADLIB,TEST1.LOADLIB)

DIRS

Optional.

Specifies up to 440 bytes of HFS directory path names to be searched by Application Performance Analyzer, enclosed in quotes and each separated by one or more spaces. These are applicable only when sampled HFS programs have relative path names. The LIBS and DIRS keywords are mutually exclusive.

Example: DIRS=("/u/axx01 /u/axx01/cpp")

STEP

Optional.

If omitted, the first step will be measured.

Multiple STEP keywords can be specified. Specifying multiple STEP keywords creates a multistep request. A maximum of 20 STEP keywords is allowed.

Each STEP can have multiple positional parameters:

1. `stepnum` specifies the step number. If `stepnum` is specified, none of the other 3 step specification parameters can be included.
2. `pgmname` specifies the program name. If `pgmname` is specified, none of the other 3 step specification parameters can be included.
3. `stepname` specifies the step name. It can be specified as just a step name, or in the format `stepname.procstep`. If this parameter is specified, the `stepnum` and `pgmname` parameters must not be specified. If `stepname` is specified without `.procstep`, it identifies an EXEC statement that contains a PGM parameter, not one that invokes a procedure.

If the format `stepname.procstep` is coded, then `stepname` identifies an EXEC statement that invoked a procedure, and `procstep` identifies the EXEC statement containing a PGM parameter within that procedure.

This parameter can not be specified when selecting an active job.

Example 1: STEP=3

This indicates that the third step in the job should be measured.

Example 2: STEP=(,TESTPGM1)

This indicates that the first step that runs the program TESTPGM1 should be measured.

Example 3: STEP=(,STEP007)

This indicates that the step named STEP007 should be measured, where STEP007 is the step name on an EXEC statement that executes a program (not an EXEC statement that invokes a procedure).

Example 4: STEP=(,PROC02.STEP007)

This indicates that the step named STEP007 within the procedure invoked by step PROC02 should be measured.

Example 5:STEP=3 STEP=5 STEP=6 STEP=(,STEP012)

This shows STEP being repeated to create a multistep measurement.

ALLSTEPS

Optional.

Specify ALLSTEPS=YES to create a multi-step request which measures all steps in the job. When ALLSTEPS=YES is specified, the STEP keyword is meaningless, and will be ignored if coded.

Example: ALLSTEPS=YES

ACTIVE

Mandatory.

Specify YES if the job is active, or NO if the job is not active.

Example: ACTIVE=YES

ASID

Optional.

If omitted, Application Performance Analyzer will measure the first job it finds with the JOBNAME. Specifies the ASID, in decimal, of the job to be measured. Only applies when ACTIVE=YES.

Example: ASID=1023

CTRAN

Mandatory when CICS is specified in FEATURES, otherwise does not apply.

Specifies one or more CICS trancodes to measure. For all transactions, use CTRAN=*. A list of transactions is separated by commas. A maximum of 16 transactions is allowed.

Example 1: CTRAN=(TRNA,TRNB,TRNC)

Example 2: CTRAN=*

SYSCTRAN

Optional, if omitted the default of NO will be used.

Specify YES if you want to measure the CICS system transactions.

CTERM

Optional.

Specifies one or more CICS terminal ids to measure. A list of terminal ids is separated by commas. You can also specify a terminal id pattern, such as a terminal id prefix followed by an asterisk (*) or an asterisk itself. The asterisk indicates that all terminals starting with the prefix are to be included in the measurement. The asterisk on its own indicates that all terminals are to be included. A maximum of 8 terminal ids / patterns is allowed.

Example:

CTERM=(TRM1,TRM2,TRM3)

CTERM=TRM*

CTERM=*

NONCTERM

Optional. If omitted, the default value of YES will be used.

Specify NO if you do not want to measure CICS transactions that run non-terminal attached.

ITRAN

Optional.

Specifies an IMS transaction to include when measuring an IMS/MPP region. You can also specify a transaction id pattern, such as a transaction id prefix followed by an asterisk (*) or an asterisk by itself. The asterisk indicates that all transaction ids starting with the prefix are to be included in the measurement. The asterisk on its own indicates that all transactions are to be included.

Example:

ITRAN=IMSTRN1

ITRAN=IMSTRN*

ITRAN=*

Note: Values in ITRAN, IPROG and IUSER are AND'ed together to determine which transactions are included in a measurement.

Note: When limiting the observation to specific IMS transactions in an MPP region, Application Performance Analyzer samples only when the transactions are running. The observation continues to run for the requested duration.

IPROG

Optional.

Specifies an IMS program to include when measuring an IMS/MPP region. You can also specify a program name pattern, such as a program name prefix followed by an asterisk (*) or an asterisk by itself. The asterisk indicates that all programs starting with the prefix are to be included in the measurement. The asterisk on its own indicates that all programs are to be included.

Example:

```
IPROG=IMSPGM1  
IPROG=IMSPGM*  
IPROG=*
```

Note: Values in ITRAN, IPROG and IUSER are ANDed together to determine which transactions are included in a measurement.

Note: When limiting the observation to specific IMS programs in an MPP region, Application Performance Analyzer samples only when the transactions associated with the programs are running. The observation continues to run for the requested duration.

IUSER

Optional.

Specifies an IMS user id to include when measuring an IMS/MPP region. You can also specify a user id pattern, such as a user id prefix followed by an asterisk (*) or an asterisk by itself. The asterisk indicates that transactions initiated by user IDs starting with the prefix are to be included in the measurement. The asterisk on its own indicates that transactions initiated by all users are to be included.

Example:

```
IUSER=IMSUSR1  
IUSER=IMSUSR*  
IUSER=*
```

Note: Values in ITRAN, IPROG and IUSER are ANDed together to determine transactions that are included in a measurement.

Note: When limiting the observation to specific IMS users in an MPP region, Application Performance Analyzer samples only when the transactions initiated by the IMS users are running. The observation continues to run for the requested duration.

DB2SP

Mandatory when JOBNAME=(-)

Identifies the DB2 stored procedure or user-defined function to be measured. This keyword is mandatory and is only valid when a dash (-) is entered for the JOBNAME. It requires 4 positional parameters to identify the type (stored procedure or user-defined function), the DB2 subsystem name, the schema and the name of the procedure or function, in the format
DB2SP=(type,ssnm,schema,name).

Type can be either P for stored procedure or F for user-defined function. For both *schema* and *name*, you can also specify a name pattern, for example, a name prefix followed by an asterisk (*) or an asterisk by itself. Application Performance Analyzer will measure the first DB2 stored procedure or user-defined function executed by the DB2 subsystem that matches the schema

and name concatenation. If a single asterisk is coded in both schema and name, Application Performance Analyzer will measure the first stored procedure or user-defined function executed by the DB2 subsystem.

Example1: DB2SP=(P,DSN1,SCHEMA1,SP1)

This indicates that the first occurrence of DB2 stored procedure SCHEMA.SP1, which runs in the DB2 Subsystem DSN1 is to be measured.

Example2: DB2SP=(F,DSN2,SCHEMA2,UDF2)

This indicates that the first occurrence of user-defined function SCHEMA2.UDF2, which runs in the DB2 Subsystem DSN2 is to be measured.

Example3: DB2SP=(P,DSN1,SCH*,SP1)

This indicates that the first occurrence of stored procedure SP1 with a schema that begins with SCH, that runs in the DB2 Subsystem DSN1 is to be measured.

SCHDDATE

Mandatory if this is a Future Schedule request, otherwise does not apply.

Multiple SCHDDATE keywords can be specified to schedule future requests on multiple dates and times. Date/time is specified in the format: yyyy/mm/dd@hh:mm.

Example:

```
SCHDDATE=2004/12/03@16:00
SCHDDATE=2004/12/10@16:00
SCHDDATE=2004/12/17@16:00
SCHDDATE=2004/12/24@16:00
```

This creates a future schedule request to run a measurement on each of the four dates and times specified.

RETRYAFTER

Optional.

This is only used for future schedule requests (one or more SCHDDATE keywords must be present), where the job is expected to be active (ACTIVE=YES specified). Specifies that Application Performance Analyzer should retry the request if the target job was not active on the first attempt. Also specifies how many times to retry.

Specified in the format: (mm, FOR=nn), where mm is the number of minutes between retry attempts, and nn is the number of times to retry.

Example: RETRYAFTER=(15, FOR=3)

SCHDSPAN

Optional.

This is only used for future schedule requests (one or more SCHDDATE keywords must be present), where the measurement is to begin when the job becomes active (ACTIVE=NO specified). Specifies the number of minutes that this request will wait for the job to become active before Application Performance Analyzer expires the request.

Example: SCHDSPAN=120

RUNAGAIN

Optional.

This indicates that for a specified time interval, if the target job runs again, the measurement should be run again. The For= parm indicates how many times the measurement should potentially be repeated. The time interval is reset after each rerun of the target job. The maximum time interval for a future schedule request is 999 minutes. The maximum time interval for a single occurrence request is 31,680 minutes (22 days).

Example: RUNAGAIN=(60,FOR=3)

This means that for 60 minutes after the target job starts, Application Performance Analyzer will run the measurement again, if the job starts again. It will do this up to three times.

TNEW

The TNEW command is used to create a new Observation Request which starts only when the specified threshold criteria has been satisfied for the target job-step. The criteria are: CPU Time, Elapsed Time, and EXCP Count.

TNEW

Mandatory.

Indicates that this is a new threshold request.

JOBNAME

Mandatory.

Specifies the name of the job (or started task or TSO user) to be measured.

TMSEL


Mandatory.

Specifies the criteria upon which the measurement will begin. The TMSEL keyword accepts the following parameters: CPU, ELAPSED TIME, and EXCP, in the format TMSEL=("CPU=mm:ss ELAPSED TIME=mm:ss EXCP=nnnnnnnnnn"). When more than one threshold criteria is specified, all the criteria must be met for the measurement to begin.

CPU=mm:ss specifies the threshold amount of CPU time. When the target job-step exceeds this amount of CPU time, the measurement begins. Time can be entered in seconds or in minutes and seconds. To specify the threshold time in minutes and seconds, separate the minutes value from the seconds value using a colon.

ELAPSED TIME=mm:ss specifies the threshold amount of elapsed time. When the target job-step exceeds this amount of elapsed time, the measurement begins. Time can be entered in seconds or in minutes and seconds. To specify the threshold time in minutes and seconds, separate the minutes value from the seconds value using a colon.

EXCP=nnnnnnnnnn specifies the threshold EXCP count. When the target job-step exceeds this EXCP count, the measurement begins.



Example:

```
TNEW JOBNAME=TSTJOB01
TMSEL=("CPU=30 ELAPSED TIME=5:00 EXCP=5000");
```

TNEW accepts the same keywords as the NEW command, with the exception of the Multi-Step and Schedule information and DB2 stored procedure or user-defined function keywords, which are not applicable for Threshold Monitor requests. The following keywords are not accepted on the TNEW command: ALLSTEPS, DB2SP, RUNAGAIN, SCHDDATE, RETRYAFTER, SCHDSPAN and DELAYSAMPLING. Only one STEP keyword is accepted.

DELETE

The DELETE command is used to delete an observation request.

REQNUM

Mandatory.

Specifies the request number to be deleted.

KEEP

The KEEP command is used to override the expiration date on an observation request, and keep it until it is manually removed.

REQNUM

Mandatory.

Specifies the request number to be kept.

CANCEL

The CANCEL command is used to cancel an active observation request.

REQNUM

Mandatory.

Specifies the request number to be cancelled.

Batch import

The batch import program CAZIMPRT is used to load a sample file into an Application Performance Analyzer R02 Observation Session List. This can be a native sample file or one that has been previously exported. The import program creates a new observation in the target system, assigning a new request number. The date and time of the imported request is set to the current date and time and the expiry date is recalculated based on the rules of the importing system.

Sample template JCL is supplied in hlq.SCAZSAMP in member CAZIMPRT.

```
//CAZIMPRT JOB (job parameters)
//*
//S1 EXEC PGM=CAZIMPRT,REGION=4M,PARM='STCID=stcid'
//STEPLIB DD DISP=SHR,DSN=hlq.SCAZAUTH
//SYSPRINT DD SYSOUT=*
//SAMPIN DD DSN=inputdsn,DISP=SHR
```

1. Add the JOB parameters to meet your system requirements.
2. On the EXEC statement, replace *stcid* with the Application Performance Analyzer instance id of the system you want to import into. This parameter can be omitted if only one instance of Application Performance Analyzer is running on your image.
3. On the STEPLIB DD statement, replace *hlq.SCAZAUTH* with the name of your installation's authorized library containing Application Performance Analyzer's load modules.

4. On the SAMPIN DD statement, replace *inputdsn* with the name of the native sample file or TSO XMIT file containing the sample to be imported.

Chapter 13. Realtime Monitor

The Realtime Monitor facility lets you view information about an in-progress measurement. Start this facility by selecting an active measurement from Observation Session List using the “R” line command. You can also choose to have the Realtime Monitor launched automatically when you start a measurement for an active job. Use SETUP in the Observation Session List to select this option.

Auto-refresh mode

In this mode the panel is refreshed automatically to show changing data as it is measured. In auto-refresh mode the keyboard is locked. To halt auto-refresh mode, and unlock the keyboard, press the Attention key. You can then refresh the panel manually by repeatedly pressing the ENTER key.

To re-activate the auto-refresh mode, enter the PULSE primary command. You can abbreviate this as P.

Monitor views

The Realtime Monitor facility offer various views of the measurement data. The upper portion of the screen shows a menu of the available monitor views. To select a view, either enter its code on the command line or place the cursor on the field and press the ENTER key.

ACCUM and CURRENT modes

Some monitor views display data based on either all the accumulated (ACCUM) data for the measurement, or for the last measured “time slice” (CURRENT). “(ACCUM)” or “(CURRENT)” is displayed on the heading line of views affected by this mode setting.

Enter the ACCUM command to set the mode to report accumulate data. You can abbreviate this as A. Enter the CURRENT command to set the mode to report on the most recent time slice. You can abbreviate this as C. Use the SETUP command to adjust the size of the time slice (expressed as number of samples). The default value is 100 samples.

SETUP command

Use the SETUP command to change various default options. You can change the following:

- Panel displayed at startup
- Display auto-refresh enabled
- Auto-refresh interval
- Length of current time slice

View 1. Measurement overview

View 1. Measurement Overview shows an at-a-glance summary of the measurement status and shows a very high level overview of observed resource usage. If in 'autorefresh' mode, data in this screen will refresh automatically at the specified rate. Otherwise press ENTER to refresh the data.

A sample report is shown here:

```

File View Navigate Help
-----
M01: IBM APA for z/OS Realtime Monitor (2132/CICS22A)      Row 00001 of 00025
Command ==>> _____ Scroll ==>> PAGE
  1. Overview      3. Environment    5. Data Mgmt
  2. CPU Util.    4. CPU/Modules

View 1. Measurement Overview

+Measurement Progress -----+
| Requested   90,000  100.0%  | .....|
| Samples Done 39,673  44.0%  | -----|
| CPU Active   4,314  10.8%  | -----|
| WAIT        34,393  86.6%  | -----|
| Queued       966    2.4%  | -|
+-----+

+System Resource Usage-----+
| CPU time TCB  21.96 sec  | No.of TCBS      9|
| CPU time SRB   3.50 sec  | EXCPs           0|
| Storage frames 6,611    | Dataspace frames 0|
| Pages in      0         | Pages out       0|
+-----+

+DB2 Activity-----+
| SQL call count 7,809    | DB2 plan        PFSAMPA|
| SQL samples    2,287    | DB2 DBRM        PFSAMPC|
+-----+

+CICS Transactions-----+
| Active txns    0         | Current TranId  n/a|
| Suspended txns 8         | CICSTaskId     1,672|
+-----+

```

Measurement progress

This section shows the progress of the measurement by reporting the total number of samples completed. The sample counts are further subdivided by CPU Active samples, TCB WAIT samples, and Queued samples.

| Under heading | This is displayed |
|---------------|---|
| Requested | The number of samples requested. A fixed percentage value of 100 percent is shown here as this number of samples represents the entire measurement. The actual number of samples performed could exceed this value if the "run to end of step" option was selected. Similarly the measurement could terminate before the indicated number of samples is done if the measured step terminates first. |
| Samples Done | The number of samples done. This is the number of samples performed so far. A percentage value and histogram indicate the ratio of samples completed to the number of requested samples. |
| CPU Active | The number of samples done in which one or more CPUs were executing instructions in the measured region. A percentage value and histogram indicate the ratio of the number of CPU Active samples to the total number of samples completed so far. |

| Under heading | This is displayed |
|---------------|---|
| WAIT | The number of samples done in which all TCBs were in WAIT (non dispatchable) state. A percentage value and histogram indicate the ratio of the number of WAIT samples to the total number of samples completed so far. |
| Queued | The number of samples done in which no TCBs were CPU active and at least one TCB was dispatchable. This indicates a state in which work was not being done in the measured region because no CPU (or memory) was available. A percentage value and histogram indicates the ratio of the number of Queued samples to the total number of samples completed so far. |

System resource usage

This section shows various aspects of general resource usage observed during the measurement interval. Resources quantified here are: CPU time, storage usage, EXCPs, and paging.

| Under heading | This is displayed |
|-------------------|---|
| CPU Time TCB | The number of CPU seconds consumed by all TCBs in the measured region for the duration of the measurement interval. |
| No. of TCBs | The number of TCBs in existence at the time of the last data refresh. |
| CPU Time SRB | The number of CPU seconds consumed in SRB mode in the measured region for the duration of the measurement interval. |
| EXCPs | The number of EXCPs (Execute Channel Program) performed during the measurement interval. |
| Storage Frames | The number of 4K byte page frames (real storage) for virtual storage assigned to the address space at the time of the last data refresh. |
| Data Space Frames | The number of 4K byte page frames (real storage) for Data Space storage assigned to the address space at the time of the last data refresh. |
| Pages in | The number of page in operations performed during the measurement interval. |
| Pages out | The number of page out operations performed during the measurement interval. |

DB2 activity

This section shows information about DB2 activity observed during the measurement interval.

| Under heading | This is displayed |
|----------------|---|
| SQL call count | The number of SQL calls counted during the measurement interval. This information is available only if the DB2+ feature was enabled for the measurement. |
| SQL samples | The number of samples in which SQL call processing was in progress. |
| DB2 Plan | The name of the DB2 Plan for the last SQL request whose execution was sampled. This information is available only if the DB2 feature was enabled for the measurement. |

| Under heading | This is displayed |
|---------------|---|
| DB2 DBRM | The name of the DB2 DBRM for the last SQL request whose execution was sampled. This information is available only if the DB2 feature was enabled for the measurement. |

CICS transactions

This section shows information about CICS transactions that are currently active. This information is available only if the address space being measured is a CICS region and the CICS measurement feature is enabled.

| Under heading | This is displayed |
|----------------|---|
| Active txns | The number of CICS transactions currently active (includes suspended transactions). |
| Current TranId | The transaction ID of the currently executing CICS transaction. |
| Suspended txns | The number of CICS transactions currently suspended. This number is also included in the Active txns value. |
| CICS TaskId | The task number of the CICS transaction currently executing. |

View 2. CPU utilization

View 2. CPU Utilization quantifies distribution of CPU usage. The quantifications are reported in two modes: Overall and Current.

Overall mode appears on the left side of the screen and shows accumulated quantifications based on the overall measurement. Each quantity is an overall sample count. It is also expressed as a percentage and illustrated by a histogram.

Current mode appears on the right side of the screen and shows quantifications representing the last measured time slice. Each quantity is a sample count for the time slice and is also illustrated by a histogram. (Use the SETUP command to adjust the size of the time slice.)

If in "auto-refresh" mode data in this screen will refresh automatically at the specified rate. Otherwise press ENTER to refresh the data.

A sample report is shown here:

```

File View Navigate Help
-----
M01: IBM APA for z/OS Realtime Monitor (2132/CICS22A)      Row 00001 of 00028
Command ==>_____ Scroll ==> PAGE

1. Overview      3. Environment  5. Data Mgmt
2. CPU Util.    4. CPU/Modules

View 2. CPU Utilization

+Overall CPU Activity 7 min 7.81 sec -----+ +Current 0.66 sec -----+
| Samples      64,179  71.3% -----+ | 100 '+++++' |
| CPU Active   5,597   8.7% - | 39 ===== |
| WAIT        57,303  89.2% -----+ | 52 ===== |
| Queued       1,279   1.9% - | 9 = |
+-----+ +-----+

+CPU Usage Distribution -----+ +Current -----+
| CPU Active   5,597   8.7% - | 39 '+++++' |
| Application  104    1.8% - | 1 = |
| System      2,119  37.8% -----+ | 18 ===== |
| DB2 SQL     217    3.8% - | 0 |
| Data Mgmt   0     0.0% | 0 |
| Unresolved  3,164  56.4% -----+ | 20 ===== |
+-----+ +-----+

+CPU Modes -----+ +Current -----+
| CPU Active   5,604   8.7% - | 39 '+++++' |
| Supv Mode    3,828  68.3% -----+ | 23 ===== |
| Prob Mode    1,776  31.6% -----+ | 16 ===== |
| In SVC       424    7.5% - | 2 = |
| AMODE 24     0     0.0% | 0 |
| AMODE 31    5,604 100.0% -----+ | 39 ===== |
| AMODE 64     0     0.0% | 0 |
| User key    1,887  33.6% -----+ | 16 ===== |
| System key   3,717  66.3% -----+ | 23 ===== |
+-----+ +-----+

```

CPU activity

This section shows sample counts for the overall measurement and for the current time slice. These are categorized as CPU Active, WAIT and Queued.

| Under heading | This is displayed |
|---------------|--|
| Samples | The number of samples performed in the overall measurement and in the time slice. The percentage shown in the Overall CPU Activity section represents the ratio of the number of samples completed to the number of samples requested. |
| CPU Active | The number of samples done in which one or more CPUs were executing instructions in the measured region. The percentage value indicates the ratio of the total number of CPU Active samples to the total number of samples completed so far. The first histogram represents this percentage and shows the proportion of the overall measurement time in which CPU activity was observed. The second sample count shows the number of CPU Active samples in the current time slice. The second histogram shows the proportion of the current time slice in which CPU activity was observed. |

| Under heading | This is displayed |
|---------------|--|
| CPU WAIT | The number of samples done in which all TCBs were in WAIT (non dispatchable) state. The percentage value indicates the ratio of the total number of CPU WAIT samples to the total number of samples completed so far. The first histogram represents this percentage and shows the proportion of the overall measurement time in which all TCBs were in WAIT state. The second sample count shows the number of CPU WAIT samples in the current time slice. The second histogram shows the proportion of the current time slice in which all TCBs were observed to be in WAIT state. |
| Queued | The number of samples done in which no TCBs were CPU active and at least one TCB was dispatchable. This indicates a state in which work was not being done in the measured region because no CPU (or memory) was available. The percentage value indicates the ratio of the total number of Queued samples to the total number of samples completed so far. The first histogram represents this percentage and shows the proportion of the overall measurement time in which a TCB was dispatchable and not serviced. The second sample count shows the number of Queued samples in the current time slice. The second histogram shows the proportion of the current time slice in which one or more TCBs was dispatchable and not serviced. |

CPU usage distribution

This section shows a breakdown of CPU active TCB observations. CPU active observations are broken down by categories: Application code, System services, DB2 and Data management.

| Under heading | This is displayed |
|---------------|---|
| CPU Active | The number of observations of CPU Active TCBs. This value could be higher than the number of CPU Active samples because each CPU Active TCB is counted. Two or more TCBs could be serviced concurrently by separate CPUs. The percentage value indicates the ratio of the total number of CPU Active samples to the total number of samples completed so far. The first histogram represents this percentage and shows the proportion of the overall measurement time for which CPU activity was observed. The second sample count shows the number of CPU Active TCB observations in the current time slice. |
| Application | The number of CPU Active TCB observations in which execution was observed in application programs. This is a subset of the CPU Active observation count. The percentage value indicates the ratio of the number of application program observations to the number of CPU Active observations. The first histogram represents this percentage and shows the proportion of the overall CPU time for which CPU activity was observed in application code. The second count shows the number of application code CPU Active observations in the current time slice. The histogram represents the proportion of CPU time in application code in this time slice. |

| Under heading | This is displayed |
|-----------------|--|
| System | The number of CPU Active TCB observations in which execution was observed in system services. This is a subset of the CPU Active observation count. The percentage value indicates the ratio of the number of system services observations to the number of CPU Active observations. The first histogram represents this percentage and shows the proportion of the overall CPU time for which CPU activity was observed in system routines. The second count shows the number of system services CPU Active observations in the current time slice. The histogram represents the proportion of CPU time in system services in this time slice. |
| DB2 SQL | The number of CPU Active TCB observations in which execution was in DB2 routines servicing SQL requests. This is a subset of the CPU Active observation count. The percentage value indicates the ratio of the number of DB2 observations to the number of CPU Active observations. The first histogram represents this percentage and shows the proportion of the overall CPU time for which CPU activity was observed to be processing SQL requests. The second count shows the number of DB2 services CPU Active observations in the current time slice. The histogram represents the proportion of CPU time in DB2 services in this time slice. |
| Data management | The number of CPU Active TCB observations in which execution was in the servicing of Data Management requests. This is a subset of the CPU Active observation count. The percentage value indicates the ratio of the number of Data Management service observations to the number of CPU Active observations. The first histogram represents this percentage and shows the proportion of the overall CPU time for which CPU activity was observed to be processing Data Management requests. The second count shows the number of Data Management services CPU Active observations in the current time slice. The histogram represents the proportion of CPU time in Data Management services in this time slice. |
| Unresolved | The number of CPU Active TCB observations in which execution was in object code in storage locations for which no load module information could be obtained. This can occur for modules fetched into CSA by a region other than the one being measured. This quantity is a subset of the CPU Active observation count. The percentage value indicates the ratio of the number of unresolved location observations to the number of CPU Active observations. The first histogram represents this percentage and shows the proportion of the overall CPU time for which CPU activity was observed to be in unresolved storage locations. The second count shows the number of unresolved storage location CPU Active observations in the current time slice. The histogram represents the proportion of CPU time in unresolved storage locations in this time slice. |

CPU modes

This section shows a breakdown of CPU active TCB observations by mode of CPU execution. These modes are not all mutually exclusive. For example, execution in Problem State could also be counted as execution in AMODE 31.

| Under heading | This is displayed |
|---------------|---|
| CPU Active | The number of observations of CPU Active TCBs. This value could be higher than the number of CPU Active samples because each CPU Active TCB is counted. Two or more TCBs could be serviced concurrently by separate CPUs. The percentage value indicates the ratio of the total number of CPU Active samples to the total number of samples completed so far. The first histogram represents this percentage and shows the proportion of the overall measurement time for which CPU activity was observed. The second sample count shows the number of CPU Active TCB observations in the current time slice. |
| Supv Mode | The number of CPU Active TCB observations in which execution was in Supervisor Mode. The percentage value indicates the ratio of the number of Supervisor Mode observations to the number of CPU Active observations. The first histogram represents this percentage and shows the proportion of the overall CPU time for which CPU activity was observed to be in Supervisor Mode. The second count shows the number of Supervisor Mode CPU Active observations in the current time slice. The histogram represents the proportion of CPU time in Supervisor Mode in this time slice. |
| Prob Mode | The number of CPU Active TCB observations in which execution was in Problem Mode. The percentage value indicates the ratio of the number of Problem Mode observations to the number of CPU Active observations. The first histogram represents this percentage and shows the proportion of the overall CPU time for which CPU activity was observed to be in Problem Mode. The second count shows the number of Problem Mode CPU Active observations in the current time slice. The histogram represents the proportion of CPU time in Problem Mode in this time slice. |
| In SVC | The number of CPU Active TCB observations in which execution was in a Supervisor Call. The percentage value indicates the ratio of the number of SVC execution observations to the number of CPU Active observations. The first histogram represents this percentage and shows the proportion of the overall CPU time for which CPU activity was observed to be in a Supervisor Call. The second count shows the number of Problem Mode CPU Active observations in the current time slice. The histogram represents the proportion of CPU time in SVC execution in this time slice. |
| AMODE 24 | The number of CPU Active TCB observations in which execution was in 24 bit addressing mode. The percentage value indicates the ratio of the number of AMODE 24 observations to the number of CPU Active observations. The first histogram represents this percentage and shows the proportion of the overall CPU time for which CPU activity was observed to be in AMODE 24. The second count shows the number of AMODE 24 CPU Active observations in the current time slice. The histogram represents the proportion of CPU time in AMODE 24 in this time slice. |

| Under heading | This is displayed |
|---------------|---|
| AMODE 31 | The number of CPU Active TCB observations in which execution was in 31 bit addressing mode. The percentage value indicates the ratio of the number of AMODE 31 observations to the number of CPU Active observations. The first histogram represents this percentage and shows the proportion of the overall CPU time for which CPU activity was observed to be in AMODE 31. The second count shows the number of AMODE 31 CPU Active observations in the current time slice. The histogram represents the proportion of CPU time in AMODE 31 in this time slice. |
| AMODE 64 | The number of CPU Active TCB observations in which execution was in 64 bit addressing mode. The percentage value indicates the ratio of the number of AMODE 64 observations to the number of CPU Active observations. The first histogram represents this percentage and shows the proportion of the overall CPU time for which CPU activity was observed to be in AMODE 64. The second count shows the number of AMODE 64 CPU Active observations in the current time slice. The histogram represents the proportion of CPU time in AMODE 64 in this time slice. |
| User key | The number of CPU Active TCB observations in which execution was in user storage key (Key 8). The percentage value indicates the ratio of the number of user key observations to the number of CPU Active observations. The first histogram represents this percentage and shows the proportion of the overall CPU time for which CPU activity was observed to be in user key. The second count shows the number of user key CPU Active observations in the current time slice. The histogram represents the proportion of CPU time in user key in this time slice. |
| System key | The number of CPU Active TCB observations in which execution was in system storage key (not key 8). The percentage value indicates the ratio of the number of system key observations to the number of CPU Active observations. The first histogram represents this percentage and shows the proportion of the overall CPU time for which CPU activity was observed to be in system key. The second count shows the number of system key CPU Active observations in the current time slice. The histogram represents the proportion of CPU time in system key in this time slice. |

View 3. Measurement environment

The data reported here is static and shows the measurement request parameters and information about the measurement environment.

A sample report is shown here:

```

File View Navigate Help
-----
M01: IBM APA for z/OS Realtime Monitor (2132/CICS22A)      Row 00001 of 00028
Command ==>_____ Scroll ==> PAGE
  1. Overview      3. Environment    5. Data Mgmt
  2. CPU Util.    4. CPU/Modules

View 3. Measurement Environment

+Request Parameters-----+
| Request number   2132
| Description      CICS region
| Data extractors  CICS,DB2,DB2+
+-----+
| Requesting user  USR01          | Nbr of samples   90,000
| Time of request  09:53:34         | Duration         600 sec
| Date of request  Tue May-31-2005 | Active/pending   Active
| Job name        CICS22A       | Proc step name   n/a
| Step name/number n/a          | Delay time       none
+-----+
+Measurement Environment-----+
| Job name        CICS22A       | Region size <16MB 1,712,128K
| Job number      STC02108      | Region size >16MB 4K
| Step name       CICS22A       | Step program      DFHSIP
| ASID            71            | Region type       CICS TS 2.2
| DB2 Attach type CICS
+-----+
| System ID       X235          | IBM APA Version   1.100A
| SMFID           X235          | O/S level         z/OS 01.06.00
+-----+
| Nbr of CPUs    2             | CPU model         1247
| CPU rate factor 6,015         | CPU version       0A
| MIPS per CPU   54            | SUS per second    2660.0
+-----+

```

Request parameters

These values were established when the measurement was requested.

| Under heading | This is displayed |
|-------------------|--|
| Request number | The unique four-digit identifier assigned to the measurement. |
| Description | A description specified when the measurement was requested. |
| Data extractors | The specified data extractors (DB2, CICS, etc.) |
| Requesting user | The TSO user ID of the user that requested the measurement. |
| Time of request | The time of day the request was made. |
| Date of request | The date upon which the request was made. |
| Job name | The name of the job that was specified to be measured. |
| Step name/number | The step name or step number that was specified to be measured, if applicable. |
| Step program | The name of the step program that was specified to be measured, if applicable. |
| Number of samples | The number of samples specified. |

| Under heading | This is displayed |
|----------------|---|
| Duration | The specified measurement duration. |
| Active/pending | Indicates whether the measurement request specified an active job (an immediate measurement) or one that was to run later when execution of the job step is detected. |
| Proc step name | The procedure step name, if specified. |
| Delay time | The number of seconds specified for which the start of the measurement was to be delayed from the start of the job step. |

Measurement environment

Values relating to the environment in which the measurement took place are reported here.

| Under heading | This is displayed |
|--------------------|---|
| Job name | The name of the measured job. |
| Job number | The job number of the measured job assigned by JES. |
| Step name | The name of the measured step. |
| ASID | The ASID (address space ID) of the measured job. |
| DB2 attach type | The type of DB2 attachment, if DB2 data recorded. |
| Region size < 16MB | The region size in the 24 bit address range. |
| Region size > 16MB | The region size above the 24 bit address range. |
| Step program | The name of the measurement step program (specified in the EXEC JCL statement). |
| Region type | The type of region (Batch, TSO, IMS, CICS, etc.) measured. |
| System ID | The system identifier of the system on which the measurement took place. |
| SMFID | The SMF ID assigned to the system on which the measurement took place. |
| IBM APA vers. | The version of IBM Application Performance Analyzer for z/OS that performed the measurement. |
| O/S Level | The operating system and level. |
| Nbr of CPUs | The number of CPUs in the system on which the measurement took place. |
| CPU rate factor | The factor used to determine CPU performance. |
| MIPS per CPU | The speed, in machine instructions per second, of one CPU. This is derived using the CPU rate factor. |
| CPU model | The CPU model number. |
| CPU version | The CPU version. |
| SUs per second | The number of service units per CPU second. |

View 4. CPU active modules

Overall CPU activity

A sample report is shown here:

```

File View Navigate Help
-----
M01: IBM APA for z/OS Realtime Monitor (2132/CICS22A)      Row 00001 of 00034
Command ==>                                           Scroll ==> PAGE
  1. Overview      3. Environment  5. Data Mgmt
  2. CPU Util.    4. CPU/Modules

View 4. CPU Active Modules (CURRENT)

+Overall CPU Activity 8 min 14.33 sec -----+ +Current 0.66 sec -----+
| Samples      74,159  82.3% -----          | | 100 ' ' ' ' ' ' ' ' |
| CPU Active   7,584  10.2% --                | | 42  =====         |
+-----+-----+-----+-----+-----+-----+-----+-----+
Name      Description          Percent of CPU Time * 10.00% ±15.6%
          *...1...2...3...4...5...6...7...8...9
DFHSIP CICS Services          11.90 =====
DFHPGDM PG domain - initi     7.14 =====
185C6xxx Unresolved Address   4.76 ==
152D3xxx Unresolved Address   4.76 ==
186E3xxx Unresolved Address   2.38 =
17AEFxxx Unresolved Address   2.38 =
17D88xxx Unresolved Address   2.38 =
DFHMCX   BMS fast path mod    2.38 =
18227xxx Unresolved Address   2.38 =
18542xxx Unresolved Address   2.38 =
17848xxx Unresolved Address   2.38 =
-----

```

| Under heading | This is displayed |
|---------------|--|
| Samples | The number of samples performed in the overall measurement. The percentage shown section represents the ratio of the number of samples completed to the number of samples requested. This percentage is also represented by a histogram. |
| CPU Active | The number of samples done in which one or more CPUs were executing instructions in the measured region. The percentage value indicates the ratio of the total number of CPU Active samples to the total number of samples completed so far. The histogram represents this percentage and shows the proportion of the overall measurement time in which CPU activity was observed. |

Current

This shows the number of samples in the current time slice and the number of these samples in which CPU activity was observed. The heading shows the elapsed time of the time slice.

| Under heading | This is displayed |
|---------------|---|
| Samples | The number of samples performed in the current time slice. |
| CPU Active | The number of samples in the current time slice in which one or more CPUs were executing instructions in the measured region. The histogram represents the proportion of the time slice in which CPU activity was observed. |

Module attribution

Each detail line in this section shows a load module name and the percentage of observed CPU activity attributed to the module. The quantifications shown in this section apply to the full measurement if in ACCUM mode and to the last time slice if in CURRENT mode. Enter the ACCUM command or the CURRENT command to switch between these two modes.

| Under heading | This is displayed |
|---------------------|--|
| Name | The name of the module in which CPU activity was observed. Use the "+" line command to expand this line to show CSECT information. For an address range for which a module name could not be determined, this shows a hexadecimal address range. |
| Description | A functional description of the module if one is available. |
| Percent of CPU Time | The percentage of CPU time consumed while executing in the module. This is the ratio of the number of CPU Active TCB observations in the module to the total number of CPU Active observations. |

View 5. Data mgmt service time

In ACCUM mode, files for which EXCPs were processed during the measurement are shown. In CURRENT mode, files for which EXCPs were processed since the last data refresh are shown. In both cases the detail lines are sorted in descending sequence by EXCP count since the last data refresh.

A sample report is shown here:

```

File View Navigate Help
-----
M01: IBM APA for z/OS Realtime Monitor (2133/CICS22A) Row 00001 of 00004
Command ==> Scroll ==> PAGE
1. Overview 3. Environment 5. Data Mgmt
2. CPU Util. 4. CPU/Modules

View 5. Data Mgmt Service Time (ACCUM)

DDNAME Type EXCPs CPU-Wait-Queued Dataset Name
VSAMI VSAM 4,568 ===== USR01.DATA.TESTPF
INFILE QSAM 45 USR01.TESTPF2.INFILE
OUTFILE QSAM 20 USR01.TESTPF2.OUTFILE
STEPLIB 2 APL1.RTEST.LOADLIB
-----

```

| Under heading | This is displayed |
|---------------|--|
| DDNAME | The DDNAME to which the file is allocated. A separate line appears for each OPEN of the DDNAME. A separate line also appears for each data set in a concatenation. |
| Type | The type of file access (QSAM, BSAM, etc.) is reported if this information was determined. Measurement of execution in a data management routine for the file must have taken place for this to be reported. |
| EXCPs | In ACCUM mode, the number of EXCPs since the first file activity measurement. In CURRENT mode, the number of EXCPs since the last data refresh. |

| Under heading | This is displayed |
|-----------------|---|
| CPU-Wait-Queued | A histogram showing the proportion of samples in which execution was observed in data management routines servicing access of the file. The colors green, red and yellow indicate CPU active, Wait and Queued respectively. The width of the field represents 100 percent of the measurement interval for ACCUM mode and 100 percent of the last time slice for CURRENT mode. |
| Data set Name | The name of the data set. |

Chapter 14. Application Performance Analyzer Graphical User Interface (GUI).

This chapter describes the Application Performance Analyzer GUI. All menus, tool bars and views that are part of the Application Performance Analyzer GUI are detailed in this chapter.




Figure 1. The Application Performance Analyzer GUI

Getting started with the Application Performance Analyzer GUI

The Application Performance Analyzer GUI is a desktop version of Application Performance Analyzer ISPF. The Application Performance Analyzer GUI encompasses both the Observation Request and Reporting functions, including the R02 screens list, detail views, edit functions and reports for the Observation.

The Application Performance Analyzer GUI is an alternative interface to Application Performance Analyzer, meant to provide a majority of parallel tools and functionality as those from Application Performance Analyzer ISPF, the main interface to Application Performance Analyzer. The Application Performance Analyzer GUI is used for submitting new observation requests and for navigating the Performance Analysis Reports generated from observation requests. The Application Performance Analyzer GUI is organized into several components,

which include a menu, tool bars, views, wizards and dialogs. Tool bars are available both from the main application and for most of the views.

The views display and provide functions to multiple components of Application Performance Analyzer at once. The major views include:

- STC View, which lists all active started tasks,
- Observations List View, which lists all observations,
- Observation Detail View, which provides details of an observation,
- Reports List View, which lists all reports for an observation, and
- Report View, which displays an individual report.




Figure 2. The Application Performance Analyzer GUI layout

System requirements

The Application Performance Analyzer GUI must be installed on a Windows platform (XP, Vista, Server 2003/2008). Minimum memory requirements are 512MB.

Details of software prerequisites are in Chapter 7 of the *Application Performance Analyzer for z/OS Customization Guide*.

Communications

The Application Performance Analyzer GUI platform has built-in support for both local and remote (z/OS) repositories. The local repository is populated and

refreshed automatically with the most recent transaction data, with the exception of the observation reports. Reports are downloaded on request by selecting Download Reports from the context menu of the Observation List or clicking the Download Reports button on the Reports View.

The initial install of the Application Performance Analyzer GUI connects to the remote repository, while subsequent startups automatically load and display the local repository of the Startup Application Performance Analyzer SST. The remote repository is accessed via TCP/IP communications between the Application Performance Analyzer GUI and z/OS. An Application Performance Analyzer Listener started task must be installed and active on z/OS.

The figure below provides an example of a local connection. Refer to Figure 2 on page 620 for an example of a remote connection.




Figure 3. Local vs. remote connections

Logon dialog

A logon to z/OS is required to connect to the Application Performance Analyzer remote repository. The logon dialog is displayed in which the connection host address, host port, TSO ID and password must be entered to connect to z/OS. The connection settings group includes a checkbox that specifies hiding the address and port information from display for future logon sessions.

The address, port and TSO user ID are saved as a Network Connection Preference the first time they are entered. If any are changed in a subsequent logon, they are

not saved as a preference, but kept only for the connection session. The Network Connection Preferences page includes the settings to change and save these preferences.

The Logon dialog also includes an option to save the password. If this option is checked, the password is stored and automatically filled-in for future connections to z/OS. The saved password is deleted if the Save password box is subsequently unchecked.

When connecting to the remote repository on z/OS, Application Performance Analyzer might display informational or error messages. If “Automatic update notification” is selected in Workspace Preferences, Application Performance Analyzer will check if a new version of the GUI is available for download, and if so, will display a message to the user. Application Performance Analyzer will also display error messages when it finds an incompatibility between the GUI version and the z/OS version.




Figure 4. Logon dialog

Select STC dialog

The Select STC dialog is displayed after the initial successful logon to z/OS. A list of active Application Performance Analyzer Started Tasks (STC's) is displayed in which the default startup STC must be selected. The default STC is the started task which is selected at the startup of Application Performance Analyzer.

The default STC is saved as a Network Connection Preference and can be changed from either the Network Connection Preferences dialog or from the Set as Default STC context menu item of the STC List view.




Figure 5. STC dialog

Main menu bar

The Main Menu bar contains application-level actions that include the File, Window and Help menus.

File menu

The File Menu actions include:

- Exit APA. This action exits the Application Performance Analyzer GUI, closing the application.



• Connect APA. This action connects to the Remote repository on z/OS (Application Performance Analyzer on z/OS).

A logon dialog is displayed in which the host address, host port, TSO user ID and password must be entered to connect to z/OS. Once a successful connection has been established, the Observations List is automatically refreshed with the latest observations from z/OS.



• Disconnect APA. This action disconnects the connection to the z/OS remote repository (Application Performance Analyzer on z/OS). The Observations List is automatically set to the Local repository.

Window menu

The Window Menu actions include:

- Show View. This action lists views which can be displayed. If the selected view is hidden, it will be shown (displayed).
- Preferences. This action opens the User Preferences dialog. Refer to “Preferences” on page 626 for details.

Help menu

The Help menu actions include:

- Help Contents. This action launches a browser window displaying Application Performance Analyzer GUI Help contents.




Figure 6. Help Contents browser dialog

- Help Search. This action displays the Help Search view. This view searches the Help content for the input search string and returns the results. Refer to "Help Search view" on page 675 for details.




Figure 7. Help Search dialog

- About APA/GUI. This action displays a dialog which provides product, packaging and release information about the Application Performance Analyzer GUI.



Figure 8. About APA/GUI dialog

Main toolbar

The Main Application Performance Analyzer GUI toolbar provides buttons for application-level actions which include:



This action connects to the Remote repository on z/OS (Application Performance Analyzer on z/OS). The Observations List is automatically refreshed with the latest observations from z/OS.

A Logon dialog is displayed in which the host address, host port, TSO user ID and password must be entered to connect to z/OS. Once a successful connection has been established, the Observations List is automatically refreshed with the latest observations from z/OS.



Disconnect APA. This action disconnects the connection to the z/OS remote repository (Application Performance Analyzer on z/OS). The Observations List is automatically set to the Local repository.

Preferences

The Application Performance Analyzer GUI application preferences are accessed using the Window menu of the Main Toolbar. Preferences are persistent user property settings for the Application Performance Analyzer GUI.

General preferences

General preferences include general purpose view property settings.




Figure 9. General Preferences dialog

Table 21. General preferences and descriptions

| Preference | Description |
|--|---|
| Show STC List at Startup? | Check to show the STC List view at startup of the Application Performance Analyzer GUI. Default: unchecked |
| Default Sort Sequence | Order to sequence the observations in the Observations List view Default: <i>ReqNum</i> |
| Prompt before deleting an Observation? | Prompt (confirmation) is displayed prior to deleting an observation. Default: checked |

Workspace preferences

Workspace preferences, accessible from the General preferences category, include workspace-level property settings.




Figure 10. Workspace Preferences dialog

Table 22. Workspace preferences and descriptions

| Preference | Description |
|-------------------------------|---|
| Text Encoding | Codepage to use. Value is one of: IBM1047. Default: IBM1047 |
| Automatic update notification | Check and notify user when updates are available. This is done at connect time. Default: checked |

Help preferences

Help preferences provide customization property settings for the help view and help page browser display.




Figure 11. Help Preferences dialog




Figure 12. Help Preferences dialog

Logging/debug preferences

Logging/debug preferences include property settings for error, warning and information messages along with a debug option to save the downloaded z/OS dataspace. Log messages are written to the `apatrace.log` file, located in the `c:\apa\workspace\metadata` directory, where `apa` is the folder that the Application Performance Analyzer GUI was installed in.




Figure 13. Logging Preferences dialog

Table 23. Logging/debug preferences and descriptions

| Preference | Description |
|---------------------|---|
| Write to file | Write the errors to the apatrace log file. Default: checked |
| Level | Level of error logging. Value is one of: Error, Warn, Info, Debug, All. Default: Info |
| Save z/OS Dataspace | Save the downloaded z/OS dataspace. This is used for data debugging purposes. Default: unchecked |

Network connections preferences

Network connections preferences include property settings related to z/OS communications and network connectivity.




Figure 14. Network Connections preferences dialog

Table 24. Network connections preferences and descriptions

| Header | Header |
|-------------------|---|
| Host Address | z/OS server address where the Application Performance Analyzer server communications reside |
| Host Port | Port where the z/OS Application Performance Analyzer server is listening |
| Connection TSO Id | TSO user ID that is to be used for the Application Performance Analyzer GUI communications |

Table 24. Network connections preferences and descriptions (continued)

| Header | Header |
|-------------------------|--|
| Connection TSO Password | Password for TSO user ID to be used for the Application Performance Analyzer GUI communications |
| Default APA STC | Default Application Performance Analyzer started task |
| Other | List of active Application Performance Analyzer STC's from which to optionally select the Default Application Performance Analyzer STC |

Report download options preferences

Report download options preferences include property settings for downloading and viewing reports. The first scrollable list includes all report categories and reports that are available in Application Performance Analyzer to be downloaded.

The second scrollable list, located at the bottom of the window, includes all options for the selected report. Click the Edit button or double-click the option, and an edit dialog window is displayed in which the value can be modified. Any changes are applied to all downloads of the selected report type.




Figure 15. Report download options dialog

Table 25. Report download options preferences and descriptions

| Preference | Description |
|------------------|---|
| Expand Default | Sets which report category will be expanded when the report list is initially displayed. Default: C – CPU Usage Analysis |
| Download Options | Report download options – used when reports are downloaded. Default: System Configuration settings |

Status line

Located at the bottom of the application window, the status line includes a shortcut tool bar for FastView buttons (left corner) and displays three categories of status information:

- View status (left-side)

- Application status (center)
- Job progress status (right-side)

FastView is a feature that provides docking and undocking of views. If Fastview is selected for a view, its icon is displayed as a button in the shortcut toolbar area of the status line. Refer to “View navigation” on page 636 for details on setting the view as a Fastview.

View status information includes the display of the number of observations and filtering options when the Observations List view is active. The cursor location from the Report View (line, column) is also displayed when a Report View is active.

Application status information includes Local when the local repository is active and Remote when the z/OS Application Performance Analyzer is connected and the remote repository is active.

Job progress information is displayed when a long-running task is active, for example, downloading data or formatting a large report.

List navigation

Views that display lists of information, such as the STC List, Observations List and Reports List include Expand All, Collapse All, Home, Backward and Forward navigation actions on the view toolbar.

The navigation buttons assist navigation of the list and are activated when a row has children rows. In addition to the toolbar buttons, each row with children displays an expand command, “+” (XP) or “>” (Vista) on the row. When clicked, the row is expanded to reveal the child observations.

Lists include multi-row selection capability. Press and hold the CTRL button and mouse click each desired row, then when all target rows are selected, click the right-mouse button, select the action and it will be applied to all selected rows. The same applies if the Shift button is pressed instead of CTRL, except all rows between the first clicked row and the next clicked row are selected.

Expand all



Expand all. Expands all collapsed rows (parent rows with children), so the full tree is displayed.

Collapse all



Collapse all. Collapses all expanded rows (parent rows with children) so only the parent row is displayed (the tree is collapsed).

Home



Home. Home swaps the list items to display the original list.

Backward



Backward. Backward swaps the list items to display the previously displayed list.

Forward



Forward. Forward swaps the list items to display only the children of the selected row.

View navigation

All views can be closed, moved, viewed with Fastview, detached, re-attached, minimized and maximized. Right-click the view tab and the context menu displays navigation actions for the view.

The Detach action detaches the view and changes it into a separate popup dialog displayed on top of the Application Performance Analyzer GUI. It can be re-attached to the Application Performance Analyzer GUI by right-clicking the view tab and selecting detach a second time from the context menu of the popup.

The view can also be minimized to the Shortcut toolbar area of the status line by selecting FastView. An icon is displayed for each view that is minimized via Fastview.

STC list view

The STC (Started Task) list view, displayed at the top left-side of the Application Performance Analyzer GUI, lists all active Application Performance Analyzer tasks started on this image of the sysplex for which the connection was established. This view, by default, is not displayed at startup, but can be opened by selecting Window, Show View, STC View. The active STC is pre-selected. You can change STCs by clicking on a different started task. The desktop will be refreshed to show the changed STC properties, Observations List and Observation Detail views.




Figure 16. STC list view

Context menu

The STC List context menu is accessed by a right-mouse button click on a started task. The STC list context menu provides STC (row) level actions that include the following:

- Set as Default STC. Set as Default STC changes the Application Performance Analyzer default STC.

STC Properties view

The STC (Started Task) Properties view, displayed at the bottom left-side of the Application Performance Analyzer GUI, lists all properties for the selected (active) STC. This view is opened when the STC List view is opened and is closed in conjunction with close of the STC List view.




Figure 17. STC Properties view

Observations List view

The Observations List view, located at the top center of the Application Performance Analyzer GUI, lists all observations for the selected (active) STC, sequenced based on the User Preference. This view includes a toolbar, sortable columns and a row-specific context menu. The tab title for this view displays the active started task for the list with either Local, indicating the local repository is active, or Remote when the remote repository is active.

| ReqNum | Owned By | Description | Job Name | Date/Time | Samples | Status |
|--------|----------|------------------|----------|--------------|---------|---------|
| 1818 | LEAKE | | CAZ00062 | Nov-06 07:04 | 0 | Failed |
| 1809 | TSS12 | APA Test | TSS12X | Nov-05 09:48 | 1,000 | Steps |
| 1808 | T3291KM | CHRY IMS ISSUE | CGWS100B | Nov-05 07:53 | 50,000 | Ended |
| 1802 | MACHIN2 | v10-uc29 | JAVATST1 | Nov-05 07:42 | 99,999 | USS |
| 1792 | TSS09 | | TSS09X | Nov-04 13:33 | 10,000 | Steps |
| 1788 | MACHIN2 | APA V7 FILE | DB2V9TEP | Nov-02 14:09 | 10,043 | Ended |
| 1787 | MACHIN2 | | IM8FMP00 | Nov-02 14:08 | 99,999 | Ended |
| 1786 | MACHIN2 | APA V9 FILE | MQPUT | Nov-02 14:07 | 774 | Ended |
| 1785 | MACHIN2 | v10ref7-uc7 | CICSC32F | Nov-02 13:57 | 99,999 | Ended |
| 1784 | MACHIN2 | v9ref-uc17 | CICSC32F | Nov-02 13:57 | 99,999 | Ended |
| 1783 | MACHIN2 | v9-uc3 | MQPUT | Nov-02 13:57 | 774 | Ended |
| 1782 | MACHIN2 | v10ref8-uc30v4 | - | Nov-02 12:40 | 184 | Ended |
| 1781 | MACHIN2 | v10ref7-uc30v3 | - | Nov-02 12:31 | 214 | Ended |
| 1779 | MACHIN2 | v10ref7-uc30 | DSNTEJ6U | Nov-02 11:12 | 773 | Ended |
| 1777 | MACHIN2 | v10ref7-uc30 | DSNTEJ6R | Nov-02 10:46 | 2,055 | Ended |
| 1776 | MACHIN2 | v10ref8-cicsmass | CICSC41F | Nov-02 08:41 | 99,999 | Ended |
| 1775 | MACHIN2 | v10ref8-cicsmass | CICSC32G | Nov-02 08:41 | 99,999 | Ended |
| 1774 | MACHIN2 | v10ref8-cicsmass | CICSC32F | Nov-02 08:41 | 99,999 | Ended |
| 1773 | MACHIN2 | v10ref8-cicsmass | CICSC31G | Nov-02 08:41 | 99,999 | Ended |
| 1772 | MACHIN2 | v10ref8-cicsmass | CICSC31F | Nov-02 08:41 | 99,999 | Ended |
| 1771 | MACHIN2 | v10ref8-cicsmass | CICSC23F | Nov-02 08:41 | 99,999 | Ended |
| 1770 | MACHIN2 | v10ref8-cicsmass | CICSCI1A | Nov-02 08:41 | 99,999 | Ended |
| 1769 | MACHIN2 | v10ref8-uc7 | IMBFMP01 | Nov-02 07:24 | 99,999 | Ended |
| 1768 | MACHIN2 | v10ref8-uc7 | IMBFMP00 | Nov-02 07:24 | 99,999 | Ended |
| 1756 | MACHIN2 | v10ref8-uc27 | CICSC32F | Oct-30 07:12 | 99,999 | Ended |
| 1755 | MACHIN2 | v10ref8-uc17 | CICSC32F | Oct-30 06:37 | 99,999 | Ended |
| 1748 | MACHIN2 | v10ref8-cstv3 | CIC% | Oct-29 16:03 | 99,999 | MultiJb |
| 1747 | MACHIN2 | v10ref8-cstv3 | CIC% | Oct-29 16:03 | 99,999 | MultiJb |
| 1743 | MACHIN2 | v10ref8-cstv2 | CIC% | Oct-29 15:21 | 99,999 | MultiJb |
| 1739 | MACHIN2 | v10ref8-cstv1 | CIC% | Oct-29 14:43 | 99,999 | MultiJb |
| 1738 | MACHIN2 | v10ref8-uc15 | DB2DATA | Oct-29 14:14 | 21,854 | Ended |
| 1737 | TSS09 | | TSS09A | Oct-29 13:46 | 30,000 | Steps |
| 1736 | MACHIN2 | v10ref8-uc23v2 | DB2DPDPA | Oct-29 13:00 | 22,222 | Through |

Figure 18. Observation List view

Each row represents an individual observation and includes the Request Number, Owned By, Description, Job Name, Date/Time of the Observation, number of Samples taken and the Observation Status. The list can be sequenced for any of these fields by clicking on the column header.

If the observation is a parent with children, the display default contains the observations list collapsed. An expand command, “+” (XP) or “>” (Vista), is displayed, which when clicked, expands the row to reveal the child observations.

A reports icon is displayed on each row where reports for an observation have been downloaded. A context menu is available for each observation. Right-click on the row of the desired observation and the list of available menu actions is displayed. Refer to “Context menu” on page 656 for details.

For each observation list row that is selected, the Observation Detail and Observation Reports List views are updated to the active (selected) request. Refer to “Observation Detail view” on page 661 and “Observation Reports List view” on page 662 for details. Refer to “R02 - Observation session list” on page 8 for details of the individual fields.

Toolbar

The Observations List toolbar provides buttons for view-level actions that include: Refresh Observations List, Filter Observations List, Search Observations, New Observation and New Trigger Observation. Additionally, common navigation

actions are available including Expand All (expand all observations) and Collapse All (collapse all observations). The toolbar includes a Local Pull Down button, a down arrow icon, located at the far right-side of the toolbar. The pull down provides an alternative path to many of the toolbar actions.

Refresh observations



Refresh Observations reloads the Observations List view with observations retrieved and downloaded from the z/OS remote repository.

Note: This action is only available if the z/OS connection has been established and the remote repository is active.

Filter observations



Filter Observations provides the functionality to filter the Observations List. A dialog is displayed where the filter pattern is entered. Observations can be filtered by Owned By or Job Name values and the results sequenced by any one of the Observations List column types.

Once the OK button is clicked, all observations matching the filter pattern are downloaded from z/OS and the Observations List refreshed with the new list of observations. A filter pattern of "*" indicates no filtering will be applied to the specified field.




Figure 19. Filter Observations dialog

Note: This action is only available if the z/OS connection has been established and the remote repository is active.

Search observations



Search Observations provides a tool to scan the list of observations for a given

search string and return a list of matching results. A dialog is displayed in which the search string is entered. Additional filtering can also be specified, including limiting the search to one of the Observation List column types, setting a date range, limit the request number range and/or limit by sample size.

Once the OK button is clicked, all observations matching the search pattern are searched. The Search Results View is opened and the results displayed. Refer to “Help Search view” on page 675 for details of the search results.




Figure 20. Search Observations dialog

New observation



New Observation provides the functionality to create and submit a new observation to Application Performance Analyzer. A dialog is displayed where the details of the new observation must be provided.

The New Observation dialog is initially structured with seven tabs in which detailed request specification information can be entered. Each tab name is preceded by a symbol indicating if data has been entered to the tab. The symbol is displayed in green (green light) if data has been entered and is error free. A yellow or red light is displayed if there are warnings or errors in the data. Refer to “Entering an observation request” on page 15 for details of the individual fields

and edits.

The screenshot shows the 'New Observation' dialog box with the following fields and controls:

- Job Information:** Job Name/Pattern (text field), System (dropdown menu showing 'STLABF6'), Inactive (checkbox).
- Step Specification:** Step Number (text field), Program Name (text field), Step Name (text field), Proc Step Name (text field). A note states: 'Specify step number, program, step name or step name + proc step name. Use 'Multi Steps' tab to specify more than one step'.
- Description:** Description (text area).
- Number of Samples:** 1000 (text field).
- Duration (min:sec):** 1:00 (text field).
- Notify TSO User:** (text field).
- Measure to step end:** (checkbox).
- Delay by (secs):** (text field).
- Retain file for (days):** 90 (text field).
- USS observations:** (text field) Max. 25 (text field).

Buttons at the bottom: Submit, Cancel, Preview.

Figure 21. New Observation dialog

If a dash (“-”) is entered in the job name field (Job Information tab), a DB2-specific or an IMS Multiple Address Space observation is created. The New Observation dialog is restructured with only three tabs including the Job Information (with limited fields), Options and Subsystems, where the DB2 radio button fields are activated by default. The IMS radio button is also enabled, where, if selected, IMS Multiple Address Space parameters are entered.




Figure 22. New Observation (DB2-specific or IMS Multiple Address Space) dialog

The Preview button can be clicked at any time to view the request parameters as they are being built. Once the required data has been entered and green light(s) are displayed, the request is valid and ready to be submitted. Once the Submit button is clicked to submit the request, the Observations List automatically displays the new observation on the list.

Note: This action is only available if the z/OS connection has been established and the remote repository is active.

Job Information tab

The Job Information tab includes job-related parameters for the new observation request. If the started task is part of a sysplex, a System dropdown listing the images in the sysplex is displayed. Otherwise, the dropdown is hidden. An entry field colored grey cannot be edited.




Figure 23. Job Information tab

Refer to “Panel 1 – Job Information” on page 17 and “Panel 6 – Sysplex” on page 32 for details of the individual fields and edits.

Options tab

The Options tab is used to enter extended measurement options (Data Extractors), and also to specify additional load libraries to be searched for external symbol information. Click the Directories radio button to enter additional HFS Directories. Both the load libraries and directories are validated real-time on the z/OS server.




Figure 24. Options tab




Figure 25. Options tab

Refer to “Panel 2 – Options” on page 22 for details of the individual fields and edits.

Multi Steps tab

The Multi Steps tab is used to specify that multiple job steps are to be measured. Up to 20 steps can be measured, using the same specification rules described for single step measurements entered in the Job Information tab.




Figure 26. Multi Steps tab

Refer to “Panel 3 input fields” on page 27 for details of the individual fields and edits.

Active Jobs tab

The Active Jobs tab is used to select active jobs from a list. A Prefix can be entered to limit the jobs listed. If you enter a Pattern in the Job name/Pattern field from the Job Information tab, this is entered as the Prefix in the Active Jobs tab. The z/OS server is accessed real-time to return the list of active jobs that are displayed in the Active Jobs List section. All selected jobs are displayed in the Selected Jobs List section. Up to 20 jobs or the system configuration value can be selected.




Figure 27. Active Jobs tab

Refer to “Panel 4 – Active Jobs” on page 28 for details of the individual fields and edits.

Subsystems tab

The Subsystems tab is used to specify information about the measurement of a CICS region, IMS selection parameters or DB2 parameters. Specify the CICS transaction codes for which CICS measurement information is to be recorded. Click on the IMS radio button for IMS measurement parameters. A transaction, program name, and user ID to limit the measurement information can be entered. DB2 and IMS Multiple Address Space fields are only enabled if a dash (“-”) is entered in the job name field (Job Information tab). Application Performance Analyzer will display different fields on the Subsystems tab, depending on the radio button selected.




Figure 28. Subsystems tab - CICS option




Figure 29. Subsystems tab - IMS option




Figure 30. Subsystems tab - DB2 option




Figure 31. Subsystems tab - IMS Multiple Address Space option

Enter the IMS Subsystem name and the IMS Transaction that are to be measured, and then press the “Get IMS Active Jobs” button to display the list of IMS MPP regions that are eligible to process the transaction. Select the IMS MPP regions that Application Performance Analyzer is to measure from this list.

Refer to “Panel 5 – Subsystems” on page 29 for details of the individual fields and edits.

Schedule tab

The Schedule tab is used to generate a schedule for repetitions of future measurements. A maximum of 105 future scheduled measurement entries is allowed.

Click the calendar button to select a date/time or enter the value directly. Enter the Repeat and After fields, then click Add to Schedule to add the date(s). The entry(s) are added to the Measurement Schedule. Click the checkbox to select or unselect

one or many entries or click Select All to select all or Unselect All to deselect all the entries.




Figure 32. Schedule tab

Refer to “Panel 7 – Schedule” on page 32 for details of the individual fields and edits.

Sched Options tab

The Sched Options tab includes additional scheduling options in which the available fields depend on if the Measure active job field is checked and whether or not a future schedule has been entered on the Schedule tab.




Figure 33. Sched Options tab

Refer to “Panel 8 – Sched Options” on page 36 for details of the individual fields and edits.

New threshold observation



New Threshold Observation provides the functionality to create and submit a new threshold monitor observation to Application Performance Analyzer. The Threshold Observation request starts only when specified threshold criteria have been satisfied for the target job-step. The criteria are:

- CPU Time
- Elapsed Time
- EXCP Count




Figure 34. New Threshold Observation dialog

A dialog, incorporating many of the same tabs as for a New Observation, is displayed, where the details for the new threshold observation must be provided. Refer to “New observation” on page 641 for details on the functions of the dialog.


Refer to “Entering a Threshold Monitor request” on page 39 for details of the individual fields and edits for a threshold observation.

Click the Submit button to submit the request. The Observations List automatically refreshes and displays the new observation on the list.

Note: This action is only available if the z/OS connection has been established and the remote repository is active.

Criteria tab

The Criteria tab is the only tab in the New Threshold Observation dialog that is specific to Threshold requests only. This tab is used to specify the Threshold Criteria that triggers the measurement to run.



The screenshot shows a window titled "New Observation (Threshold)" with a tabbed interface. The "Criteria" tab is selected, indicated by a red dot. The window title bar includes the APA logo and standard window controls. The main area is titled "Set Threshold Requirements" and contains a tabbed interface with "Job Information", "Options", "Criteria", "Active Jobs", and "Subsystems". The "Criteria" tab is active, showing the following fields:

- Enter Threshold Criteria:
- CPU Time Exceeds (min:sec)
- Elapsed Time Exceeds (min:sec)
- EXCP Count Exceeds

Below the fields, a text box contains the instruction: "If you enter more than one threshold criteria field, then **all** the criteria must be met for the measurement to be triggered."

At the bottom right, there are three buttons: "Submit", "Cancel", and "Preview".

Figure 35. Criteria tab

Refer to "Panel 3 - Criteria" on page 39 for details of the individual fields and edits.

Context menu

The Observations List context menu is accessed by a right-mouse button click on an observation request. The Observations List context menu provides Observation (row) level actions that include:


- Download Reports

- Sub
- New
- Trigger
- Modify
- Keep
- Delete
- Cancel
- Delete Reports
- Tag
- Clear All Tags
- Generate Variance Reports
- Generate CICS MASS Reports

The Download Reports menu item is disabled if an Observation sample file does not exist, for example, the Observation is not in a completed status. The Delete Reports menu item is only enabled if reports have been downloaded for the selected Observation.

Download reports



Download Reports provides functionality to retrieve the Application Performance Analyzer reports for an Observation. Download Reports triggers formatting of the observation reports on z/OS then download the reports to the local repository. The reports are then available for viewing in the Observation Reports List View. A reports icon  is displayed on the observation request row where the reports download was issued.

Once the reports have been downloaded, they are available until deleted via the Delete Reports action.

Note: This action is only available if the z/OS connection has been established and the remote repository is active.

Sub



Sub issues an immediate submission of an Observation request. A new Observation request is automatically submitted to Application Performance Analyzer on z/OS, using the same parameters as the original request. No data entry dialog is presented for this action.

Use Sub instead of New when none of the original request parameters need to be changed.

Note: This action is only available if the z/OS connection has been established and the remote repository is active.

New



New Observation provides the functionality to create and submit a new observation to Application Performance Analyzer. Because the New Observation request is issued from the context menu instead of the toolbar, the New Observation dialog is pre-populated with values from the selected observation request. All other functionality remains the same.

Refer to “New observation” on page 641 and “New threshold observation” on page 654 in “Toolbar” on page 639 for details.

The screenshot shows a window titled "New Observation" with a sub-header "Schedule New Measurement". Below the sub-header is an information icon and the text "Enter the measurement information and click 'Submit' to schedule." The window has a tabbed interface with the following tabs: "Job Information" (selected), "Options", "Multi Steps", "Active Jobs", "Subsystems", "Schedule", and "Sched Options". The "Job Information" tab contains the following fields and controls:

- Job Name/Pattern: Text box containing "CICSC32F"
- System: Dropdown menu showing "STLABF6"
- Active: Text label
- Step Specification section with four text boxes:
 - Step Number
 - Program Name
 - Step Name
 - Proc Step Name
- Description: Text box containing "v9ref-uc17"
- Number of Samples: Text box containing "99999"
- Duration (min:sec): Text box containing "5:00"
- Notify TSO User: Text box
- Measure to step end: Checkbox (unchecked)
- Delay by (secs): Text box
- Retain file for (days): Text box containing "90"
- USS observations: Text box containing "0" and "Max." followed by a text box containing "25"

At the bottom of the dialog are three buttons: "Submit", "Cancel", and "Preview".

Figure 36. New Observation (context menu) dialog

Note: This action is only available if the z/OS connection has been established and the remote repository is active.

Trigger

Trigger creates a new request to be triggered when this request starts. This can only be used on a request that is in SCHED status.

Note: This action is only available if the z/OS connection has been established and the remote repository is active.

Modify

Modify provides the functionality to edit the parameters of an observation request that has not yet started. A Modify Observation dialog is displayed, pre-populated with values from the selected observation. All other functionality (edits, fields, etc) remains the same as for a New Observation.

Refer to “New observation” on page 641 and “New threshold observation” on page 654 in “Toolbar” on page 639 for details.

APA Modify Observation 1177

Modify Measurement

i Enter the measurement information and click 'Submit' to schedule.

Job Information Options Multi Steps Active Jobs Subsystems Schedule Sched Options

Job Name/Pattern: PLI System: STLABF6
Inactive

Step Specification

Step Number: [] Specify step number, program, step name or step name + proc step name. Use 'Multi Steps' tab to specify more than one step
Program Name: []
Step Name: []
Proc Step Name: []

Description: 10

Number of Samples: 30000 Measure to step end:
Duration (min:sec): 1:30 Delay by (secs): []
Notify TSO User: [] Retain file for (days): 90
USS observations: 0 Max. 25

Submit Cancel Preview

Figure 37. Modify Observation dialog

Note: This action is only available if the z/OS connection has been established and the remote repository is active.

Keep

Keep updates the observation request so that the request is kept until it is manually deleted. This overrides the auto delete feature.

Note: This action is only available if the z/OS connection has been established and the remote repository is active.

Delete



Delete removes the observation request. The Observations List automatically refreshes with the deleted observation removed from the list. Additionally any open reports for this request are also removed.

Note: This action is only available if the z/OS connection has been established and the remote repository is active.

Cancel

Cancel cancels an active observation request.

Note: This action is only available if the z/OS connection has been established and the remote repository is active.

Delete reports



Delete Reports deletes the observation request reports from the local repository. The reports icon displayed on the Observations List row is removed and any open reports for this request are also removed from the display. Reports can be re-downloaded by selecting Download Reports from the context menu.

Tag



The Tag action is used to flag an Observation(s) used for the Generate Variance Reports and Generate CICS MASS Reports features. The Tag icon is displayed on the Observations List row that was tagged and is removed if the Tag action is selected for an Observation that was already tagged or if the Clear All Tags action is selected, where all tags will be cleared. Up to 20 Observations that include a Sample DSN file can be tagged.

Note: This action is only available if the z/OS connection has been established and the remote repository is active.

Clear all tags




The Clear All Tags action removes the tag setting for all Observation(s) that are tagged. The Tag icon is removed for each tagged row.

Note: This action is only available if the z/OS connection has been established and the remote repository is active.

Generate variance reports



Generate Variance Reports provides functionality to compare up to 20 observations, creating a V – Variance Reports series report. One or more observations must already be tagged and the Observation where the Generate Variance Reports is selected serves as the base.

When selected, this action triggers formatting of the V01 – Measurement Variance Summary report on z/OS and then downloads the report to the local repository. The report is then available for viewing in the Observation Reports List View. A reports icon  is displayed on the observation where this action was selected. Once the report is downloaded, it is available until deleted via the Delete Reports action.


If, in addition to the Variance Report, all the reports for the observation are to be viewed, the Download Reports action must be selected after the Generate Variance Report has completed.

Note: This action is only available if the z/OS connection has been established and the remote repository is active.

Generate CICS MASS reports



Generate CICS MASS Reports provides functionality to report on the activity in up to 21 CICS regions (up to 20 tagged and one base), and creates an X – Multi Address Space series of reports. One or more observations that include a CICS Extractor must already be tagged and the Observation in which the Generate CICS MASS Reports is selected serves as the base.

When selected, this action triggers formatting of the Multi Address Space reports on z/OS and then downloads the reports to the local repository. The reports are then available for viewing in the Observation Reports List View. A reports icon  is displayed on the observation where this action was selected. Once the report is downloaded, it is available until deleted via the Delete Reports action.

If, in addition to the CICS MASS Reports, all the reports for the observation are to be viewed, the Download Reports action must be selected after the Generate CICS MASS Reports has completed.

Note: This action is only available if the z/OS connection has been established and the remote repository is active.

Observation Detail view

The Observation Detail view, the first tab located at the bottom center of the Application Performance Analyzer GUI, displays detailed information of the selected request from the Observations List. The tab title for this view displays the request number of the selected request.

The data in the view is organized into several groups:

- General Information (general purpose information about the observation request)
- Measurement Criteria (measurement criteria of the request)
- Measurement Information (results of the measurement request)
- Data Extractors (types of data extractors that were included)
- Steps Information (multi-step job information)
- Scheduling Information (future scheduled job information)




Figure 38. Observation Detail view

Observation Reports List view

The Observation Reports List view, the second tab located at the bottom center of the Application Performance Analyzer GUI, displays a list of reports for the selected request from the Observations List. This view includes a toolbar and a row-specific context menu. The tab title for this view displays the request number of the selected request. An empty page is displayed if the reports have not yet been downloaded for the selected request.




Figure 39. Observation Reports List view

The reports list is a 2-level tree-view. The first level (parent) rows represent the report category while the second-level (child) rows are for the individual reports. Not all categories and reports are listed in the Reports List view, only those that exist for the selected observation. The list is opened to the category set for the Expand Default user preference.

The category rows are for informational/organizational purposes only and result in no action if clicked (other than if the category is expanded). For each report row that is selected, a new Report View is opened and the Report Options view is updated to the active (selected) report. Refer to “Report views” on page 666 and “Report Options view” on page 664 for details.

A context menu is available for each row on the report list. Right-click the row of the desired report or category and the list of available menu actions is displayed. Refer to “Context menu” on page 664 for details.

Refer to Chapter 3, “Performance analysis reports,” on page 43 through Chapter 8, “Java/USS/HFS performance analysis reports,” on page 437 for details of the individual reports.

Toolbar

The Reports List toolbar provides buttons for view-level actions that include Download Reports. Additionally, common navigation actions are available, including Expand All (expand all report categories) and Collapse All (collapse all report categories).

The toolbar includes a Local Pull Down button, represented by a down arrow icon located at the far right-side of the toolbar. The pull down provides an alternative path to many of the toolbar actions.

Download reports



The Download Reports button downloads reports for the active (selected) observation request of the Observations List view. If the reports are already downloaded, they are re-downloaded. Refer to “Download reports” on page 657 for details.

Once the reports are downloaded, the Reports List view is updated with the list of reports that are available for the selected observation request.

Context menu

The Reports List context menu is accessed by a right-mouse button click in the view. It provides actions that include Download Reports. Once the reports are downloaded, the Reports List view is updated with the list of reports that are available for the selected observation request.

Download report




The Download Report action downloads a single report from z/OS. Any report can be downloaded with the exception of the Variance (“V”) and CICS MASS (“X”) reports. This feature is convenient when the Report Options have been modified and only the single report needs to be downloaded.

Once the report has been downloaded it will be refreshed in the Report View once the download is complete.

Report Options view

The Report Options view, located below the Reports List view, lists all report options for the selected (active) report from the Reports List. The view is opened and updated when a report is selected from the Reports List and includes a row-specific context menu. The view is closed if no reports are selected and none are displayed in the Report View. The tab title for this view displays the ID of the selected report.

2. In the Options panel for that report, located in the lower left pane in the GUI, double click the Levels option.
3. A dialog box is displayed, as shown below. Enter a new value for Levels.



4. Right click E06 CICS Service Time by Task Id in the Observation Reports List view and select the download option. The expansion of the report now occurs.

Context menu

The Report Options context menu is accessed by a right-mouse button click in the view. It provides actions that include:

- Edit Option
- Download Report

Edit option

The Edit Option action invokes a dialog where the report option can be changed. The changes only apply to the selected observation request report. For the changed option to take effect, the report must be downloaded (and thus the new report option applied) via the Download Report context menu or from the Reports List view. Refer to “Report download options preferences” on page 633 for details on the edit options dialogs.

Download report



Download Report downloads the individual report for the active (selected) report of the selected observation request. Refer to “Download reports” on page 657 for details. Any modifications to the options for the report take effect with this download. The report displayed in the Report View is refreshed once the download is complete.

Report views

The Report view, located next to the Reports List view, displays an individual report selected from the Reports List. This is a multiple-instance view, where multiple reports can be opened at once – one view per report, including reports from observation requests other than the active observation. This allows for comparison capabilities of the same report, but from different observations or viewing multiple reports at once.

Each report has a separate view that includes a toolbar and context menu for each instance. A set of accelerator keys is also available, which provides quick keyed access to some of the actions.

The tab title for this view identifies the report ID, name, observation request it is for and job name of the observation.




Figure 41. Report view

The report is organized by two sections: the header and report body. The header section includes a line for the report ID/name and can include non-scrollable report column headings.

The report body is scrollable and includes tree expand/collapse capability. Hyperlinked text is identified when the cursor is changed from a pointer to a hand and can include both expand/collapse functionality (an internal link - within the document) or a link to a separate report. If the link to a separate report is clicked, a new Report view is opened to display the selected report. If an internal link is clicked, the next level of report is expanded. If the link is clicked again, the next level is collapsed.

Some reports include sort functionality, accessible via the context menu of hyperlinked text. The list of sort options is unique for each report. Refer to “Context menu” on page 672 for details of the report sort options.

Refer to Chapter 3, “Performance analysis reports,” on page 43 through Chapter 8, “Java/USS/HFS performance analysis reports,” on page 437 for details of the individual reports.

Accelerator keys

Each report view includes a set of accelerator keys – a keyboard combination that provides a quick method to run a report view action. The accelerator keys include actions to Print, Find, Select All, Copy, Close Report and Close All Reports. The key sequences are:

Table 26. Accelerator key combinations

| Action | Accelerator keys |
|-------------------|--|
| Print | Ctrl + 'P' Prints the report. |
| Find | Ctrl + 'F' Finds search string in the report. |
| Select All | Ctrl + 'A' Selects all rows in the report. |
| Copy | Ctrl + 'C' Copies selected text to the Windows clipboard. |
| Close Report | Ctrl + 'W' Closes a report. |
| Close All Reports | Ctrl + Shift + 'W' Closes all reports. |

Note: The ‘Paste’ (Ctrl + ‘V’) Windows accelerator keys are also available to copy/paste the report contents to another Windows-based application.

Toolbar

The Report view toolbar provides buttons for report-level actions that include:

- Print
- Save As
- Find
- Copy
- Close Report
- Close All Reports

Additionally, common navigation actions are available including Expand All (expand the complete report) and Collapse All (collapse the report to the parent-level). The toolbar includes a Local Pull Down button, represented by a down arrow icon located at the far right-side of the toolbar. The pull down provides an alternative path to many of the toolbar actions.

Print



The Print action provides print functionality for the report. A print dialog is launched in which the printer and page options can be selected and then the report printed.

Save As



Save As provides functionality to save the report to disk. A file dialog is launched in which the file options and file name can be entered and then the report saved to disk. The figure below shows a report saved to a text file.




Figure 42. Save As dialog




Figure 43. Saved Application Performance Analyzer GUI report sample

Find



The Find action launches a dialog in which search text and search options are entered, including matching the case of the input text and starting the search from the beginning of the report (default) or the end of the report.

The report is searched for the text. Once a match is found, the text will be highlighted in grey. Click the Find Next button to navigate to the next location of the search text.




Figure 44. Find dialog

Copy



Copy functions like the same Windows command by taking any text that is selected (highlighted) and copying it to the clipboard. Once the text is in the clipboard, it can be pasted (Ctrl + 'V') to other Windows applications. A limit of 200,000 lines can be copied.

The figure below shows a report in which the Select All accelerator key (Ctrl + 'A') is used to copy the complete report. Copy (Ctrl + 'C') is then used to copy to the clipboard, followed by Paste (Ctrl + 'V') to paste the report into Word.




Figure 45. Copy/Paste report to Word sample

Close report



Close Report closes the report and removes the view from the display.

Close all reports



Close All Reports closes all reports and removes all Report views from the display. The Report Options view is also closed.

Context menu

The Report context menu is accessed by a right-mouse button click for both report header and body hyperlinked text only, and is not available for all reports. If an action from the report header context menu is selected, the full report is sorted. If an action from the report body context menu is selected, only the immediate children rows are sorted. In this case, the child rows must be displayed (the parent expanded).

The context menu provides sort actions that are unique for each report. The table below lists the report and context menu sort actions that are available for the Application Performance Analyzer GUI. When clicked, the report is sorted in the order of the selected request.

Table 27. Report sort actions

| Report | Sort actions |
|---|--|
| S03 | <ol style="list-style-type: none"> 1. Sort by NAME 2. Sort by SIZE 3. Sort by ADDRESS 4. Sort by LIBRARY |
| C01, C02, C05, C06, C07, C08 | <ol style="list-style-type: none"> 1. Sort by NAME 2. Sort by VALUE |
| C03 | <ol style="list-style-type: none"> 1. Sort by VALUE 2. Sort by ADDRESS 3. Sort by LOCATION |
| C09 | <ol style="list-style-type: none"> 1. Sort by VALUE 2. Sort by ADDRESS |
| D01, D02, D03, D05, D06, D08 | <ol style="list-style-type: none"> 1. Sort by NAME 2. Sort by VALUE |
| W01, W02, W03, W04, W05 | <ol style="list-style-type: none"> 1. Sort by NAME 2. Sort by VALUE |
| H01, H03, H08 | <ol style="list-style-type: none"> 1. Sort by VALUE 2. Sort by FILEID 3. Sort by PATHNAME |
| H02, H05, H09 | <ol style="list-style-type: none"> 1. Sort by VALUE 2. Sort by DEVID 3. Sort by DEVICE |
| H10, H11 | <ol style="list-style-type: none"> 1. Sort by VALUE 2. Sort by REQID 3. Sort by REQUEST |
| I05, I06, I07, I08, I09, I10, I11, I12, I13, I18, I19, I20, I21 | <ol style="list-style-type: none"> 1. Sort by NAME 2. Sort by VALUE |
| E02 | <ol style="list-style-type: none"> 1. Sort by NAME 2. Sort by VALUE 3. Sort by COUNT |
| E03, E04, E05, E06, E07, E08, E09, E10, E11, E12 | <ol style="list-style-type: none"> 1. Sort by NAME 2. Sort by VALUE |
| F02 | <ol style="list-style-type: none"> 1. Sort by THREAD 2. Sort by DURATION 3. Sort by CPU |

Table 27. Report sort actions (continued)

| Report | Sort actions |
|--|--|
| F03, F04, F07, F08, F14 | 1. Sort by NAME 2. Sort by VALUE |
| F05, F09 | 1. Sort by VALUE |
| F10, F11, F15, F16, F17, F18, F19 | 1. Sort by NAME 2. Sort by VALUE 3. Sort by DURATION |
| F12 | 1. Sort by DURATION 2. Sort by VALUE |
| Q02, Q03, Q04, Q05, Q06, Q07, Q08, Q09, Q10 | 1. Sort by NAME 2. Sort by VALUE |
| J04, J05, J06, J07, J09, J10, J11, J12, J14, J15, J16, J17 | 1. Sort by NAME 2. Sort by VALUE |
| X01, X02, X03, X04 | 1. Sort by NAME 2. Sort by VALUE |

Refer to Chapter 3, “Performance analysis reports,” on page 43 through Chapter 8, “Java/USS/HFS performance analysis reports,” on page 437 for additional details of the individual report sort options.

Search Results view

The Search Results view, located at the top right side of the Application Performance Analyzer GUI, is opened (activated) after a search request is entered from the Search Observations dialog. A scrollable list of the search results is displayed, including the Observation Request Number, Description and Job Name.

The list can be sorted by clicking on the column header. The Observations List and Observation Detail views are also dynamically refreshed with the current (selected) Search Results view row.




Figure 46. Search Results view

Help Search view

The Help Search view, located at the top right side of the Application Performance Analyzer GUI, is opened (activated) when the Help Search action from the Help Main Menu bar is selected. It provides a search tool for the Application Performance Analyzer GUI Help documentation.




Figure 47. Help Search view

Adjustments for large reports

The Application Performance Analyzer GUI is, by default, configured to support the download and viewing of most reports in Application Performance Analyzer. Application Performance Analyzer observations can occasionally produce extremely large reports for which the Application Performance Analyzer GUI default settings are not configured. The Windows platform itself imposes memory restrictions on applications such that in some instances, a report is not viewable using the Application Performance Analyzer GUI.

Downloaded Application Performance Analyzer reports are initially displayed in a collapsed view that allows almost all Application Performance Analyzer reports to be initially viewed. Most of the out of memory conditions occur when the expand all button is clicked, resulting in a report exceeding the maximum amount of lines that can be loaded into the viewer.

When an out of memory condition occurs while loading a report to view, the Application Performance Analyzer GUI configuration file can be modified to increase the Java memory (Heap) size. The configuration file, `APA.ini`, is located in the Application Performance Analyzer GUI install directory, for example `c:\apa\`, and includes Java VM run arguments.

The `-Xmx512m` VM argument can be temporarily increased up to 80% of your machine RAM (Random Access Memory) and to a value no greater than 1 gigabyte (1024MB). With the 1024MB configuration, a maximum of 1 million report lines can be viewed.

If this argument is modified, the Application Performance Analyzer GUI must be closed and restarted for the changes to take effect.

Appendix A. Support resources and problem solving information

This section shows you how to quickly locate information to help answer your questions and solve your problems. If you have to call IBM support, this section provides information that you need to provide to the IBM service representative to help diagnose and resolve the problem.

For a comprehensive multimedia overview of IBM software support resources, see the IBM Education Assistant presentation “IBM Software Support Resources for System z Enterprise Development Tools and Compilers products” at <http://publib.boulder.ibm.com/infocenter/ieduasst/stgv1r0/index.jsp?topic=/com.ibm.iea.debugt/debugt/6.1z/TrainingEducation/SupportInfoADTools/player.html>.

- “Searching knowledge bases”
- “Getting fixes” on page 681
- “Subscribing to support updates” on page 681
- “Contacting IBM Support” on page 682

Searching knowledge bases

You can search the available knowledge bases to determine whether your problem was already encountered and is already documented.

- “Searching the information center”
- “Searching product support documents”

Searching the information center

You can find this publication and documentation for many other products in the IBM System z Enterprise Development Tools & Compilers information center at <http://publib.boulder.ibm.com/infocenter/pdthelp/v1r1/index.jsp>. Using the information center, you can search product documentation in a variety of ways. You can search across the documentation for multiple products, search across a subset of the product documentation that you specify, or search a specific set of topics that you specify within a document. Search terms can include exact words or phrases, wild cards, and Boolean operators.

To learn more about how to use the search facility provided in the IBM System z Enterprise Development Tools & Compilers information center, you can view the multimedia presentation at <http://publib.boulder.ibm.com/infocenter/pdthelp/v1r1/index.jsp?topic=/com.ibm.help.doc/InfoCenterTour800600.htm>.

Searching product support documents

If you need to look beyond the information center to answer your question or resolve your problem, you can use one or more of the following approaches:

- Find the content that you need by using the IBM Support Portal at www.ibm.com/software/support or directly at www.ibm.com/support/entry/portal.

The IBM Support Portal is a unified, centralized view of all technical support tools and information for all IBM systems, software, and services. The IBM

Support Portal lets you access the IBM electronic support portfolio from one place. You can tailor the pages to focus on the information and resources that you need for problem prevention and faster problem resolution.

Familiarize yourself with the IBM Support Portal by viewing the demo videos at https://www.ibm.com/blogs/SPNA/entry/the_ibm_support_portal_videos?lang=en_us about this tool. These videos introduce you to the IBM Support Portal, explore troubleshooting and other resources, and demonstrate how you can tailor the page by moving, adding, and deleting portlets.

Access a specific IBM Software Support site:

- Application Performance Analyzer for z/OS Support
- Debug Tool for z/OS Support
- Enterprise COBOL for z/OS Support
- Enterprise PL/I for z/OS Support
- Fault Analyzer for z/OS Support
- File Export for z/OS Support
- File Manager for z/OS Support
- WebSphere Developer Debugger for System z Support
- WebSphere Studio Asset Analyzer for Multiplatforms Support
- Workload Simulator for z/OS and OS/390 Support

- Search for content by using the IBM masthead search. You can use the IBM masthead search by typing your search string into the Search field at the top of any ibm.com page.
- Search for content by using any external search engine, such as Google, Yahoo, or Bing. If you use an external search engine, your results are more likely to include information that is outside the ibm.com domain. However, sometimes you can find useful problem-solving information about IBM products in newsgroups, forums, and blogs that are not on ibm.com. Include "IBM" and the name of the product in your search if you are looking for information about an IBM product.
- The IBM Support Assistant (also referred to as ISA) is a free local software serviceability workbench that helps you resolve questions and problems with IBM software products. It provides quick access to support-related information. You can use the IBM Support Assistant to help you in the following ways:
 - Search through IBM and non-IBM knowledge and information sources across multiple IBM products to answer a question or solve a problem.
 - Find additional information through product and support pages, customer news groups and forums, skills and training resources and information about troubleshooting and commonly asked questions.

In addition, you can use the built in Updater facility in IBM Support Assistant to obtain IBM Support Assistant upgrades and new features to add support for additional software products and capabilities as they become available.

For more information, and to download and start using the IBM Support Assistant for IBM System z Enterprise Development Tools & Compilers products, please visit http://www.ibm.com/support/docview.wss?rs=2300&context=SSFMHB&dc=D600&uid=swg21242707&loc=en_US&cs=UTF-8&lang=en.

General information about the IBM Support Assistant can be found on the IBM Support Assistant home page at <http://www.ibm.com/software/support/isa>.

Getting fixes

A product fix might be available to resolve your problem. To determine what fixes and other updates are available, select a link from the following list:

- Latest PTFs for Application Performance Analyzer for z/OS
- Latest PTFs for Debug Tool for z/OS
- Latest PTFs for Fault Analyzer for z/OS
- Latest PTFs for File Export for z/OS
- Latest PTFs for File Manager for z/OS
- Latest PTFs for Optim Move for DB2
- Latest PTFs for WebSphere Studio Asset Analyzer for Multiplatforms
- Latest PTFs for Workload Simulator for z/OS and OS/390

When you find a fix that you are interested in, click the name of the fix to read its description and to optionally download the fix.

Subscribe to receive email notifications about fixes and other IBM Support information as described in [Subscribing to Support updates](#).

Subscribing to support updates

To stay informed of important information about the IBM products that you use, you can subscribe to updates. By subscribing to receive updates, you can receive important technical information and updates for specific Support tools and resources. You can subscribe to updates by using the following:

- RSS feeds and social media subscriptions
- My Notifications

RSS feeds and social media subscriptions

For general information about RSS, including steps for getting started and a list of RSS-enabled IBM web pages, visit the [IBM Software Support RSS feeds site](http://www.ibm.com/software/support/rss/other/index.html) at <http://www.ibm.com/software/support/rss/other/index.html>. For information about the RSS feed for the IBM System z Enterprise Development Tools & Compilers information center, refer to the [Subscribe to information center updates](http://publib.boulder.ibm.com/infocenter/pdthelp/v1r1/topic/com.ibm.help.doc/subscribe_info.html) topic in the information center at http://publib.boulder.ibm.com/infocenter/pdthelp/v1r1/topic/com.ibm.help.doc/subscribe_info.html.

My Notifications

With My Notifications, you can subscribe to Support updates for any IBM product. You can specify that you want to receive daily or weekly email announcements. You can specify what type of information you want to receive (such as publications, hints and tips, product flashes (also known as alerts), downloads, and drivers). My Notifications enables you to customize and categorize the products about which you want to be informed and the delivery methods that best suit your needs.

To subscribe to Support updates, follow the steps below. Additional information is provided at <http://www.ibm.com/support/docview.wss?rs=615&uid=swg21172598>.

1. Go to the IBM software support site at <http://www.ibm.com/software/support>.

2. Click the **My Notifications** link in the **Notifications** portlet on the page that is displayed.
3. If you have already registered for **My notifications**, sign in and skip to the next step. If you have not registered, click **register now**. Complete the registration form using your e-mail address as your IBM ID and click **Submit**.
4. In the **My notifications** tool, click the **Subscribe** tab to specify products for which you want to receive e-mail updates.
5. To specify Problem Determination Tools products, click **Other software** and then select the products for which you want to receive e-mail updates, for example, **Debug Tool for z/OS** and **File Manager for z/OS**.
6. To specify a COBOL or PL/I compiler, click **Rational** and then select the products for which you want to receive e-mail updates, for example, **Enterprise COBOL for z/OS**.
7. After selecting all products that are of interest to you, scroll to the bottom of the list and click **Continue**.
8. Determine how you want to save your subscription. You can use the default subscription name or create your own by entering a new name in the **Name** field. It is recommended that you create your own unique subscription name using something easily recognized by you. You can create a new folder by entering a folder name in the **New** field or select an existing folder from the pulldown list. A folder is a container for multiple subscriptions.
9. Specify the types of documents you want and the e-mail notification frequency.
10. Scroll to the bottom of the page and click **Submit**.

To view your current subscriptions and subscription folders, click **My subscriptions**.

If you experience problems with the **My notifications** feature, click the **Feedback** link in the left navigation panel and follow the instructions provided.

Contacting IBM Support

IBM Support provides assistance with product defects, answering FAQs, and performing rediscovery.

After trying to find your answer or solution by using other self-help options such as technotes, you can contact IBM Support. Before contacting IBM Support, your company must have an active IBM maintenance contract, and you must be authorized to submit problems to IBM. For information about the types of available support, see the information below or refer to the Support portfolio topic in the Software Support Handbook at <http://www14.software.ibm.com/webapp/set2/sas/f/handbook/offerings.html>.

- For IBM distributed software products (including, but not limited to, Tivoli[®], Lotus[®], and Rational[®] products, as well as DB2 and WebSphere[®] products that run on Windows[®], or UNIX[®] operating systems), enroll in Passport Advantage[®] in one of the following ways:

Online

Go to the Passport Advantage Web site at [http://www.lotus.com/services/passport.nsf/ WebDocs/Passport_Advantage_Home](http://www.lotus.com/services/passport.nsf/WebDocs/Passport_Advantage_Home) and click **How to Enroll**.

By phone

For the phone number to call in your country, go to the Contacts page of

the *IBM Software Support Handbook* on the Web at <http://www14.software.ibm.com/webapp/set2/sas/f/handbook/contacts.html> and click the name of your geographic region.

- For customers with Subscription and Support (S & S) contracts, go to the Software Service Request Web site at <http://www.ibm.com/support/servicerequest>.
- For customers with IBMLink, CATIA, Linux®, S/390®, iSeries®, pSeries®, zSeries®, and other support agreements, go to the IBM Support Line Web site at <http://www.ibm.com/services/us/index.wss/so/its/a1000030/dt006>.
- For IBM eServer™ software products (including, but not limited to, DB2 and WebSphere products that run in zSeries, pSeries, and iSeries environments), you can purchase a software maintenance agreement by working directly with an IBM sales representative or an IBM Business Partner. For more information about support for eServer software products, go to the IBM Technical Support Advantage Web site at <http://www.ibm.com/servers/eserver/techsupport.html>.

If you are not sure what type of software maintenance contract you need, call 1-800-IBMSERV (1-800-426-7378) in the United States. From other countries, go to the Contacts page of the *IBM Software Support Handbook* on the Web at <http://www14.software.ibm.com/webapp/set2/sas/f/handbook/contacts.html> and click the name of your geographic region for phone numbers of people who provide support for your location.

Complete the following steps to contact IBM Support with a problem:

1. “Define the problem and determine the severity of the problem”
2. “Gather diagnostic information” on page 684
3. “Submit the problem to IBM Support” on page 684

To contact IBM Software support, follow these steps:

Define the problem and determine the severity of the problem

Define the problem and determine severity of the problem When describing a problem to IBM, be as specific as possible. Include all relevant background information so that IBM Support can help you solve the problem efficiently.

IBM Support needs you to supply a severity level. Therefore, you need to understand and assess the business impact of the problem that you are reporting. Use the following criteria:

Severity 1

The problem has a **critical** business impact. You are unable to use the program, resulting in a critical impact on operations. This condition requires an immediate solution.

Severity 2

The problem has a **significant** business impact. The program is usable, but it is severely limited.

Severity 3

The problem has **some** business impact. The program is usable, but less significant features (not critical to operations) are unavailable.

Severity 4

The problem has **minimal** business impact. The problem causes little impact on operations, or a reasonable circumvention to the problem was implemented.

For more information, see the Getting IBM support topic in the Software Support Handbook at <http://www14.software.ibm.com/webapp/set2/sas/f/handbook/getsupport.html>.

Gather diagnostic information

To save time, if there is a Mustgather document available for the product, refer to the Mustgather document and gather the information specified. Mustgather documents contain specific instructions for submitting your problem to IBM and gathering information needed by the IBM support team to resolve your problem. To determine if there is a Mustgather document for this product, go to the product support page and search on the term Mustgather. At the time of this publication, the following Mustgather documents are available:

- Mustgather: Read first for problems encountered with Application Performance Analyzer for z/OS: http://www.ibm.com/support/docview.wss?rs=2300&context=SSFMBH&q1=mustgather&uid=swg21265542&loc=en_US&cs=utf-8&lang=en
- Mustgather: Read first for problems encountered with Debug Tool for z/OS: http://www.ibm.com/support/docview.wss?rs=615&context=SSGTSD&q1=mustgather&uid=swg21254711&loc=en_US&cs=utf-8&lang=en
- Mustgather: Read first for problems encountered with Fault Analyzer for z/OS: http://www.ibm.com/support/docview.wss?rs=273&context=SSXJAJ&q1=mustgather&uid=swg21255056&loc=en_US&cs=utf-8&lang=en
- Mustgather: Read first for problems encountered with File Manager for z/OS: http://www.ibm.com/support/docview.wss?rs=274&context=SSXJAV&q1=mustgather&uid=swg21255514&loc=en_US&cs=utf-8&lang=en
- Mustgather: Read first for problems encountered with Enterprise COBOL for z/OS: http://www.ibm.com/support/docview.wss?rs=2231&context=SS6SG3&q1=mustgather&uid=swg21249990&loc=en_US&cs=utf-8&lang=en
- Mustgather: Read first for problems encountered with Enterprise PL/I for z/OS: http://www.ibm.com/support/docview.wss?rs=619&context=SSY2V3&q1=mustgather&uid=swg21260496&loc=en_US&cs=utf-8&lang=en

If the product does not have a Mustgather document, please provide answers to the following questions:

- What software versions were you running when the problem occurred?
- Do you have logs, traces, and messages that are related to the problem symptoms? IBM Software Support is likely to ask for this information.
- Can you re-create the problem? If so, what steps were performed to re-create the problem?
- Did you make any changes to the system? For example, did you make changes to the hardware, operating system, networking software, and so on.
- Are you currently using a workaround for the problem? If so, be prepared to explain the workaround when you report the problem.

Submit the problem to IBM Support

You can submit your problem to IBM Support in one of three ways:

Online using the IBM Support Portal

Click **Service request** on the IBM Software Support site at <http://www.ibm.com/software/support>. On the right side of the Service request page, expand the Product related links section. Click Software

| support (general) and select ServiceLink/IBMLink to open an Electronic
| Technical Response (ETR). Enter your information into the appropriate
| problem submission form.

| **Online using the Service Request tool**

| The Service Request tool can be found at [http://www.ibm.com/software/
| support/servicerequest](http://www.ibm.com/software/support/servicerequest).

| **By phone**

| Call 1-800-IBMSERV (1-800-426-7378) in the United States or, from other
| countries, go to the Contacts page of the *IBM Software Support Handbook* at
| [http://www14.software.ibm.com/webapp/set2/sas/f/handbook/
| contacts.html](http://www14.software.ibm.com/webapp/set2/sas/f/handbook/contacts.html) and click the name of your geographic region.

| If the problem you submit is for a software defect or for missing or inaccurate
| documentation, IBM Support creates an Authorized Program Analysis Report
| (APAR). The APAR describes the problem in detail. Whenever possible, IBM
| Support provides a workaround that you can implement until the APAR is
| resolved and a fix is delivered. IBM publishes resolved APARs on the IBM Support
| website daily, so that other users who experience the same problem can benefit
| from the same resolution.

| After a Problem Management Record (PMR) is open, you can submit diagnostic
| MustGather data to IBM using one of the following methods:

- | • FTP diagnostic data to IBM. For more information, refer to [http://
| www.ibm.com/support/docview.wss?rs=615&tuid=swg21154524](http://www.ibm.com/support/docview.wss?rs=615&tuid=swg21154524).
- | • If FTP is not possible, email diagnostic data to techsupport@mainz.ibm.com. You
| must add PMR xxxxx bbb ccc in the subject line of your email. xxxxx is your
| PMR number, bbb is your branch office, and ccc is your IBM country code. Go
| to <http://itcenter.mainz.de.ibm.com/ecurep/mail/subject.html> for more details.

| Always update your PMR to indicate that data has been sent. You can update your
| PMR online or by phone as described above.

Appendix B. Creating side files using CAZLANGX

Refer to Chapter 9, “Quick start guide for compiling and assembling programs for use with IBM Problem Determination Tools products,” on page 501 for the recommended method of preparing your programs for use with the IBM Problem Determination Tools products. If you choose to create a CAZLANGX side file instead of following the suggested method in Chapter 9, “Quick start guide for compiling and assembling programs for use with IBM Problem Determination Tools products,” on page 501, this appendix provides the needed information.

You can use a program named CAZLANGX (which is the same as IDILANGX shipped in the IBM Fault Analyzer product) to create a side file from a compiler listing.

The sample JCL below:

- Allocates a new data set *yourhlq.CAZLANGX* to hold the side file, which will be created in the next step.
- Compiles an Enterprise COBOL program.

Note: You can only compile one program per compile step in order to name the compiler listing PDS(E) member (if using a partitioned data set), and to ensure that only one compiler listing is written to the output file.

- Executes CAZLANGX to process the listing and store it as a side file where Application Performance Analyzer can access it.
- Writes the listing as part of the job output.

The sample JCL is provided as member CAZSCMPS in the *hlq.SCAZSAMP* data set.

```
//CAZSCMPS JOB <JOB PARAMETERS>
//          JCLLIB ORDER=(IGY.V3R3M0.SIGYPROC) <== INSTALLATION
//*                               IGYWC PROC
//*****
//*   Licensed Materials - Property of IBM           *
//*   5697-N37                                     *
//*   (C) Copyright IBM Corp. 2005                 *
//*   *                                             *
//*   All Rights Reserved                          *
//*   US Government Users Restricted Rights - Use, duplication *
//*   or disclosure restricted by GSA ADP Schedule Contract *
//*   with IBM Corp.                               *
//*****
//*
//*           IBM Application Performance Analyzer for z/OS      *
//*           Version 1 Release 1 Modification 0                 *
//*   *                                                         *
//*   This JCL compiles a COBOL program and produces a side file *
//*   from the program listing that Application Performance     *
//*   Analyzer uses to obtain the source information.           *
//*   The compiled output is then written to SYSUT2 in the     *
//*   IEBGENER step.                                           *
//*   *                                                         *
//*   CAUTION: This is neither a JCL procedure nor a complete  *
//*   job. Before using this job step, you will have to       *
//*   make the following modifications:                          *
//*   *                                                         *
//*   1) Add the job parameters to meet your system requirements.*
```

```

/** 2) This job invokes the COBOL procedure IGYWC.          *
/** Update the procedure library name on the JCLLIB        *
/** statement as appropriate.                              *
/** 3) Change "#hlq" to the appropriate high-level qualifier. *
/** 4) Change "#yourhlq" to the appropriate high-level    *
/** qualifier.                                             *
/**                                                       *
/*******
/**
/** Pre-allocate data set CAZLANGX to which the side file
/** will be written.
/**
/**ALLOC EXEC PGM=IEFB14
/**CAZLANGX DD DSN=#yourhlq.CAZLANGX,DISP=(NEW,CATLG),
/**          UNIT=SYSALLDA,SPACE=(TRK,(20,20,10)),
/**          DCB=(RECFM=VB,LRECL=1562,BLKSIZE=0)
/**
/** Compile a COBOL program.
/**
/**CBLRUN EXEC IGYWC,PARM.COBOLE='LIST,MAP,SOURCE,XREF'
/**COBOL.SYSIN DD DATA,DLM='##'
CBL APOST,NOOPT,DYNAM,SSRANGE,RENT
IDENTIFICATION DIVISION.
PROGRAM-ID. CAZSCBL1
ENVIRONMENT DIVISION.
INPUT-OUTPUT SECTION.
FILE-CONTROL.
DATA DIVISION.
FILE SECTION.

WORKING-STORAGE SECTION.
01 FILLER PIC X(20) VALUE 'WORKING-STORAGE'.
01 NUMBERX PIC 999999 COMP-3.
01 ERROR-FLD.
05 ERROR-COUNT PIC 999999 COMP-3.
05 FLDY REDEFINES ERROR-COUNT.
07 FLDZ PIC XXXX.
01 BAD-RESULT PIC 99 COMP-3.

PROCEDURE DIVISION.
MAIN SECTION.
DISPLAY '*** CAZSCBL1 - START OF PROGRAM'.
LOOP SECTION.
START000.
MOVE 3 TO ERROR-COUNT.
ADD 986885 TO ERROR-COUNT GIVING NUMBERX.
MOVE 'ABCD' TO FLDZ.
IF NUMBERX > 0 THEN PERFORM CLEAR.
DISPLAY '*** CAZSCBL1 - END OF PROGRAM'.
GOBACK.
CLEAR SECTION.
START001.
DIVIDE NUMBERX BY ERROR-COUNT GIVING BAD-RESULT.
EXIT.
END PROGRAM CAZSCBL1.

##
/**COBOL.SYSPRINT DD DSN=&&COBLIST(CAZSCBL1),
/**          DISP=(,PASS),SPACE=(TRK,(10,5,5),RLSE),
/**          DCB=(RECFM=FBA,LRECL=133,BLKSIZE=0)
/**
/** Create a side file.
/**
/**CAZLANGX EXEC PGM=CAZLANGX,REGION=4096K,
/** PARM='CAZSCBL1 (COBOL ERROR '
/**STEPLIB DD DISP=SHR,DSN=#hlq.SCAZAUTH
/**LISTING DD DISP=(OLD,PASS),DSN=&&COBLIST
/**IDILANGX DD DISP=SHR,DSN=#yourhlq.CAZLANGX

```

```

//SYSUDUMP DD SYSOUT=*
//*
/* Print the COBOL listing.
/*
//IEBGENER EXEC PGM=IEBGENER,REGION=4096K
//SYSUT1 DD DISP=OLD,DSN=&&COBLIST(CAZSCBL1)
//SYSUT2 DD SYSOUT=*
//SYSPRINT DD SYSOUT=*
//SYSIN DD *
/*

```

Note: **1** DDname must be LISTING for all types of compiler listings, or SYSADATA for an assembler SYSADATA file.

After you have created and stored a side file, there is no benefit to Application Performance Analyzer in retaining the listing.

If you already have listings, you can turn them into side files. Here is sample JCL to do this:

```


//CAZLANGX JOB <JOB PARAMETERS>
//*****
/* This job produces a side file from a program listing
/* that Application Performance Analyzer can use
/* for obtaining source information.
/* This particular example is set up for a COBOL extraction
/* from CAZ.LISTING.COBOL(COBOLA) to CAZ.CAZLANGX
//*****
//CAZLANGX EXEC PGM=CAZLANGX,REGION=4096K,
// PARM='COBOLA (COBOL ERROR'
//STEPLIB DD DISP=SHR,DSN=hlq.SCAZAUTH
//LISTING DD DISP=SHR,DSN=yourhlq.LISTING.COBOL 1
//IDILANGX DD DISP=SHR,DSN=yourhlq.CAZLANGX
//SYSUDUMP DD SYSOUT=*

```

Note: **1** DDname must be LISTING for all types of compiler listings, or SYSADATA for an assembler SYSADATA file.

CAZLANGX parameters

The PARM string passed to CAZLANGX should contain:



Notes:

- 1 Either a comma or a blank character is permitted as a delimiter.

Parameters

mbr_name (Optional)

The compiler listing or ADATA file member name in the input data set identified by the LISTING DD name (for a compiler listing) or the SYSADATA DD name (if an ADATA file). If this parameter is omitted, the JCL must specify for the compiler listing or ADATA file, either a sequential data set, or a PDS(E) data set with member name. Also, the output CAZLANGX member will be named according to the input program name. In the case of COBOL, for example, this is the name found on the PROGRAM-ID source line.

language (Required)

The language of the compiler listing or ADATA file. The options are:

- COBOL
- PLI
- ASM

ERROR (Optional)

A parameter that provides additional diagnostics on variables for which information is incomplete.

64K (Optional)

A parameter that provides side file compatibility with Debug Tool for z/OS. For more information see, "Side file compatibility with Debug Tool for z/OS."

PermitLangx (*msgid, ...*) (Optional)

A parameter that specifies message IDs for compiler error messages that should be ignored.

Side file compatibility with Debug Tool for z/OS

If using Debug Tool for z/OS, the 64K option should be included as stated for Debug Tool EQALANGX when generating side files with the Debug Tool EQALANGX or the Application Performance Analyzer CAZLANGX utilities. This option is also recognized by CAZLANGX, and the side file produced by EQALANGX or CAZLANGX, will then be usable by both Debug Tool and Application Performance Analyzer.

For details of how to specify the 64K option, see "CAZLANGX parameters" on page 689.

Including a CAZLANGX step in your SCLM translator

If you use the ISPF/PDF Software Configuration and Library Manager (SCLM) to manage your application software, then you might want to include a CAZLANGX step in your SCLM translator, since Application Performance Analyzer side files generally take up less disk space than compiler listings. Shown in the following are examples of a CAZLANGX step inserted into a High Level Assembler and a COBOL SCLM translator.

High Level Assembler SCLM example

```
*          SYSADATA DDNAME used in HLASM step.
*          (* SYSADATA *)
*          FLMALLOC IOTYPE=W,DDNAME=SYSADATA,RECFM=VB,RECNUM=9000,   C
*          LRECL=8188,BLKSIZE=8192,PRINT=Y
*
*
* CAZLANGX BUILD TRANSLATOR
```

```

*
      FLMTRNSL  CALLNAM='CAZLANGX',
      FUNCTN=BUILD,
      COMPILE=CAZLANGX,
      DSNAME=CAZ.SCAZMOD1,
      VERSION=3.5.2,
      GOODRC=0,
      PORDER=1,
      OPTIONS='@@FLMMBR(ASM ERROR OFT CAZLANGX FAULT'
*
*
      (* SYSADATA *)
      FLMALLOC  IOTYPE=U,DDNAME=SYSADATA
*
*
      (* CAZLANGX *)
      FLMALLOC  IOTYPE=P,DDNAME=IDILANGX,DFLTYP=IDILANGX,
      KEYREF=OUT2,BLKSIZE=27998,LRECL=1562,RECFM=VB,
      RECNUM=10000,DIRBLKS=50,DFLTMEM=*

```

COBOL SCLM example

```

*****
*
*      --COPY SYSPRINT FILE TO LISTING
*      The COPYFILE EXEC, in dataset PDFTDEV.PROJDEFS.EXEC contains the
*      following:
*
*      /* REXX */
*      /*****
*      /* Copy file I to file O. Both are assumed to be pre-allocated. */
*      /*****
*      PARSE UPPER ARG I", "O .
*      "EXECIO * DISKR "I" (STEM R. FINIS "
*      "EXECIO * DISKW "O" (STEM R. FINIS "
*      RETURN
*
*****
*
      FLMTRNSL  CALLNAM='COPY FILES      ',
      FUNCTN=BUILD,
      COMPILE=COPYFILE,
      DSNAME=PDFTDEV.PROJDEFS.EXEC,
      CALLMETH=TSOLNK,
      VERSION=1.0,
      PORDER=1,
      OPTIONS=(SYSPRINT,LISTING),
      GOODRC=0
      FLMALLOC  IOTYPE=W,RECFM=VBA,LRECL=133,
      RECNUM=90000,DDNAME=LISTING
*
      FLMTRNSL  CALLNAM='CAZLANGX',
      FUNCTN=BUILD,
      COMPILE=CAZLANGX,
      DSNAME=CAZ.SCAZMOD1,
      VERSION=3.5.2,
      GOODRC=0,
      PORDER=1,
      OPTIONS='@@FLMMBR(COBOL ERROR OFT CAZLANGX FAULT'
*
*
      (* LISTING *)
      FLMALLOC  IOTYPE=U,DDNAME=LISTING
*
*
      (* CAZLANGX *)
      FLMALLOC  IOTYPE=P,DDNAME=CAZLANGX,DFLTYP=CAZLANGX,
      KEYREF=OUT2,BLKSIZE=27998,LRECL=1562,RECFM=VB,
      RECNUM=10000,DIRBLKS=50,DFLTMEM=*

```

COBOL Report Writer Precompiler

If you are using the COBOL Report Writer Precompiler (program number 5798-DYR), it is important that you run it as a stand-alone precompiler as opposed to invoking it via the COBOL compiler EXIT option. Otherwise, information that is required by Application Performance Analyzer to identify the point of failure source code statement might be missing from the compiler listing.

Symptoms that you might experience if using the COBOL Report Writer Precompiler as a COBOL compiler exit are:

- Return code 3114 from CAZLANGX if trying to convert the COBOL compiler listing file to a side file.
- The following messages issued during fault analysis:
 - IDISF8100S COBOL LISTING file contains NO recognized records
 - IDISF8132S Input or Output file format invalid
- Failure to determine point of failure source line.

Required compiler options for creating listings or CAZLANGX side files

The following are the compiler options needed to produce listings or CAZLANGX side files suitable for Application Performance Analyzer:

OS/VS COBOL:

- DMAP
- NOCLIST
- NOLST
- NOOPT (Note 1)
- PMAP
- SOURCE
- VERB
- XREF

COBOL compilers (other than OS/VS COBOL):

- LIST,NOOFFSET (Note 2)
- NOOPT (Note 1)
- MAP
- SOURCE
- XREF(SHORT) (Note 3)

VisualAge® PL/I:

- AGGREGATE
- ATTRIBUTES(FULL)
- LIST
- NEST
- OPTIONS
- SOURCE
- XREF(FULL)

Enterprise PL/I:

- AGGREGATE
- ATTRIBUTES(FULL)
- LIST
- MAP
- NEST
- SOURCE
- STMT
- NONNUMBER
- OFFSET
- XREF(FULL)
- OPTIONS
- NOBLKOFF

PL/I compilers (other than VisualAge PL/I and Enterprise PL/I):

- AGGREGATE
- ATTRIBUTES(FULL)
- ESD
- LIST
- MAP
- NEST
- OPTIONS
- SOURCE
- STMT
- XREF(FULL)

Assembler:

- ADATA

C/C++:

- LIST
- NOOFFSET

Notes:

1. Although NOOPT is recommended, the use of OPTIMIZE is allowed (including OPT(1) or OPT(2) for C) , in which case the compiler merges and rearranges statement numbers in the compiled code. The Application Performance Analyzer analysis will be limited to what can be determined from the optimized compiler listing, which can vary from having no effect on the Application Performance Analyzer report, to inaccurate identification of the source line that failed. The source line number will usually be close, but not necessarily accurate with OPTIMIZE. It is dependent on the compiler's rearrangement or elimination of source statements during its optimization processing.
2. Although LIST and NOOFFSET are recommended, the use of NOLIST and OFFSET is allowed, in which case Application Performance Analyzer will not be able to warn the user if the compiler listing is not a good match with what is in storage.

3. XREF(SHORT) is a minimum requirement; XREF(FULL) is permitted and has no detrimental effect.
4. ATTRIBUTES is a minimum requirement; ATTRIBUTES(FULL) is permitted and has no detrimental effect.

TEST option considerations

With all compilers, the additional use of the TEST option may provide program information in addition to what is available via the side files.

If TEST(,SEPARATE) is used when compiling a COBOL program, then a COBOL SYSDEBUG file is written.

If the SYSDEBUG file is to be used instead of a compiler listing, or a CAZLANGX side file created from a compiler listing, then it should be retained for use by Debug Tool for z/OS and Application Performance Analyzer.

Naming compiler listings or side files

Store compiler listings or side files in sequential data sets, or as members of PDS(E) data sets.

If stored in PDS(E) data sets, then the member name must be equal to the primary entry point name or CSECT name of your application program. If the application program contains multiple CSECTs, then they must be compiled separately in order to create separate compiler listing or side file members. If you store with any other name, Application Performance Analyzer will be unable to find the side file or listing.

Note: The PL/I compiler typically renames CSECTs according to an internal compiler algorithm. Therefore, it is not recommended to store PL/I compiler listings or side files using CSECT names as they might not be found by Application Performance Analyzer. Instead, use the primary entry point name.

If compiler listings or side files are stored in sequential data sets, and the data set names follow a convention that permits the program name to be part of the data set name, then the specification of these data sets in the DataSets option can be done easily using variable substitution.

Naming CSECTs for Application Performance Analyzer

To facilitate source code information, Application Performance Analyzer must be able to match CSECT names with the compiler listings or side files provided. For this to be possible, all CSECTs must be named. Whereas the names of CSECTs in programs written in most high-level languages are automatically assigned, special requirements apply to programs written assembler, as explained in the following. Failure to follow these requirements will prevent source code information from being determined for these types of programs.

Assembler programs

It is a requirement that CSECTs in assembler programs are named using either:

- csect_name CSECT
- csect_name START

If using a PDS(E), the csect_name must match the SYSADATA or side file data set member name.

Compiler listings and side file attributes

Compiler listings and side files must be allocated using the following attributes:

DDname Attributes:

CAZADATA

Sequential data set or PDS(E), RECFM=VB, LRECL=8188

CAZLC

Sequential data set or PDS(E), and either:

- RECFM=VB or VBA and LRECL=137
- RECFM=FB or FBA and LRECL=133

CAZLCOB

Sequential data set or PDS(E), RECFM=FBA, LRECL=133

CAZLCOBO

Sequential data set or PDS(E), RECFM=FBA, LRECL=121

CAZSYSDB

Sequential data set or PDS(E), RECFM=FB, LRECL=1024

CAZLANGX

Sequential data set or PDS(E), RECFM=VB, LRECL=1562

CAZLPLI

Sequential data set or PDS(E), RECFM=VBA, LRECL=125

CAZLPLIE

Sequential data set or PDS(E), RECFM=VBA, LRECL=137

For variable length records, the indicated record lengths (LRECL) are minimum values.

In order for Application Performance Analyzer to read the compiler listings or side files, they must not be allocated as temporary data sets (for example, using &&dsname-type data set names in your JCL).

For the purpose of conserving disk space, compiler listings can be stored in ISPF packed format. This is done by using the PACK ON option from within ISPF edit of the file. The ISPF packed format is not permitted for IDILANGX or IDIADATA data sets.

Appendix C. XML document layout

This appendix describes the layout of the XML documents and associates each element to the matching field in the online report.

XML declaration

The XML declaration is included as the first line in the document. It describes the version, encoding and standalone attributes as follows:

```
<?xml version="1.0" encoding="ebcdic-cp-us" standalone="yes" ?>
```

Root tag

The tag pair `<ReportSet>` and `</ReportSet>` define the root element.

Layout standards

Immediately following the root tag `<ReportSet>`, elements describing the details of the completed request are enclosed within a `<MeasurementInformation>` and `</MeasurementInformation>` tag pair. This data is viewed online by typing the line command “++” on top of the Request Number on the R02 panel.

The data for individual report sections (e.g., S01, C02, etc.) follow the `</MeasurementInformation>` closing tag and are enclosed within separate `<Report>` and `</Report>` tag pairs.

Immediately following the `<Report>` tag, every report section contains the following 4 common elements:

- `<ReportId>Report Code</ReportId>`
- `<ReportName>Report Name</ReportName>`
- `<MarginOfError>Margin of Error %</MarginOfError>`
- `<MeasurementDivisor>Measurement Divisor</MeasurementDivisor>`

Report Code and *Report Name* are unique for each report. The *Margin of Error %* value reflects the level of precision calculated for the report. When margin of error is not applicable for a report, this value is empty. The *Measurement Divisor* value contains the total number of samples taken and is used to calculate percentages in the report. Where there are no percentages presented in the report, this value is empty.

In the following tables, numeric data is represented by *n*, regardless of the size and format of the data.

Measurement information

The measurement information data is displayed online after typing the line command “++” on top of the Request Number in the R02 panel. In the XML document file, this data is enclosed within the `<MeasurementInformation>` and `</MeasurementInformation>` tag pair. The table below lists the sub elements for this data.

| Field title in online report | XML element |
|------------------------------|--|
| | <MeasurementTaskId>stcid</MeasurementTaskId> |
| Request Number | <RequestNumber>nmmn</RequestNumber> |
| Request Description | <RequestDescription>description</RequestDescription> |
| Request Status | <RequestStatus>status</RequestStatus> |
| Owner Id | <OwnerId>owner</OwnerId> |
| Time of Request | <TimeOfRequest>Day Mon-dd-yyyy hh:mm:ss.ss</TimeOfRequest> |
| Session Start Time | <SessionStartTime>Day Mon-dd-yyyy hh:mm:ss.ss</SessionStartTime> |
| Session End Time | <SessionEndTime>Day Mon-dd-yyyy hh:mm:ss.ss</SessionEndTime> |
| Session Duration | <SessionDuration>duration</SessionDuration> |
| Session Delete Date | <SessionDeleteDate>Day Mon-dd-yyyy</SessionDeleteDate> |
| Select by Job Name | <Jobname>name</Jobname> |
| Select by Sys Name | <SysName>name</SysName> |
| Sample Interval | <SampleInterval>interval</SampleInterval> |
| Duration | <Duration>duration</Duration> |
| Sample File DSN | <SampleFileDSN>dsn</SampleFileDSN> |
| Samples Requested | <SamplesRequested>n</SamplesRequested> |
| Samples Done | <SamplesDone>n</SamplesDone> |
| ASID | <ASID>asid</ASID> |
| Data Extractors | <Extractors> |
| | <Extractor>None</Extractor> if none selected |
| CICS | <Extractor>CICS</Extractor> omitted if not selected |
| CICS+ | <Extractor>CICS+</Extractor> omitted if not selected |
| IMS | <Extractor>IMS</Extractor> omitted if not selected |
| IMS+ | <Extractor>IMS+</Extractor> omitted if not selected |
| DB2 | <Extractor>DB2</Extractor> omitted if not selected |
| DB2+ | <Extractor>DB2+</Extractor> omitted if not selected |
| DB2 Variables | <Extractor>DB2V</Extractor> omitted if not selected |
| Collateral DB2 | <Extractor>CDB2</Extractor> omitted if not selected |
| MQSeries | <Extractor>MQS</Extractor> omitted if not selected |
| JAVA | <Extractor>JAVA</Extractor> omitted if not selected |
| | </Extractors> |

Performance analysis reports

S01 Measurement Profile

| Field title in online report | XML element |
|------------------------------|----------------------|
| Overall CPU Activity | <OverallCPUActivity> |

| Field title in online report | XML element |
|------------------------------|--|
| Samples | <Samples>n</Samples> |
| | <SamplesPercent>n%</SamplesPercent> |
| Reports | <Reports>C01 C02 C03 C05 C07 W01 W02</Reports> |
| CPU Active | <CPUActive>n</CPUActive> |
| | <CPUActivePercent>n%</CPUActivePercent> |
| Wait | <Wait>n</Wait> |
| | <WaitPercent>n%</WaitPercent> |
| Queued | <Queued>n</Queued> |
| | <QueuedPercent>n%</Queued> |
| | </OverallCPUActivity> |
| CPU Usage Distribution | <CPUUsageDistribution> |
| CPU Active | <CPUActive>n</CPUActive> |
| | <CPUActivePercent>n%</CPUActivePercent> |
| | <Reports>C01 C05 C08 W01</Reports> |
| Application | <Application>n</Application> |
| | <ApplicationPercent>n%</ApplicationPercent> |
| System | <System>n</System> |
| | <SystemPercent>n%</SystemPercent> |
| DB2 SQL | <DB2SQL>n</DB2SQL> |
| | <DB2SQLPercent>n%</DB2SQLPercent> |
| Data Mgmt | <DataMgt>n</DataMgt> |
| | <DataMgtPercent>n%</DataMgtPercent> |
| Unresolved | <Unresolved>n</Unresolved> |
| | <UnresolvedPercent>n%</UnresolvedPercent> |
| IMS DLI Call | <IMSDLICall>n</IMSDLICall> |
| | <IMSDLICallPercent>n%</IMSDLICallPercent> |
| | </CPUUsageDistribution> |
| Most CPU Active Modules | <MostCPUActiveModules> |
| CPU Active | <CPUActive>n</CPUActive> |
| | <CPUActivePercent>n%</CPUActivePercent> |
| | <Reports>C02</Reports> |
| | <CPUActiveModules> |
| <i>Module Name</i> | <Module>name</Module> |
| | <CPUActive>n</CPUActive> |
| | <CPUActivePercent>n%</CPUActivePercent> |
| | </CPUActiveModules> |
| | </MostCPUActiveModules> |
| Most CPU Active CSECTS | <MostCPUActiveCSECTS> |
| Active CPU | <CPUActive>n</CPUActive> |

| Field title in online report | XML element |
|------------------------------|---|
| | <CPUActivePercent>n%</CPUActivePercent> |
| | <Reports>C02</Reports> |
| | <CPUActiveCSECTs> |
| CSECT in Module | <CSECT>csect in module</CSECT> |
| | <CPUActive>n</CPUActive> |
| | <CPUActivePercent>n%</CPUActivePercent> |
| | </CPUActiveCSECTs> |
| | </MostCPUActiveCSECTs> |
| CPU Modes | <CPUModes> |
| Active CPU | <CPUActive>n</CPUActive> |
| | <CPUActivePercent>n%</CPUActivePercent> |
| Reports | <Reports>S08</Reports> |
| Supv Mode | <SupvModeActive>n</SupvModeActive> |
| | <SupvModePercent>n%</SupvModePercent> |
| Prob Mode | <ProbModeActive>n</ProbModeActive> |
| | <ProbModePercent>n%</ProbModePercent> |
| In SVC | <InSVCActive>n</InSVCActive> |
| | <InSVCPercent>n%</InSVCPercent> |
| AMODE 24 | <AMODE24Active>n</AMODE24Active> |
| | <AMODE24Percent>n%</AMODE24Percent> |
| AMODE 31 | <AMODE31Active>n</AMODE31Active> |
| | <AMODE31Percent>n%</AMODE31Percent> |
| AMODE 64 | <AMODE64Active>n</AMODE64Active> |
| | <AMODE64Percent>n%</AMODE64Percent> |
| User Key | <UserKeyActive>n</UserKeyActive> |
| | <UserKeyPercent>n%</UserKeyPercent> |
| System Key | <SystemKeyActive>n</SystemKeyActive> |
| | <SystemKeyPercent>n%</SystemKeyPercent> |
| | </CPUModes> |
| Most Active DB2 Plans | <MostActiveDB2Plans> |
| Samples | <Samples>n</Samples> |
| | <Percent>n%</Percent> |
| Reports | <Reports>F05</Reports> |
| | <Plans> |
| Plan Name | <PlanName>name</PlanName> |
| | <CPUActive>n</CPUActive> |
| | <CPUActivePercent>n%</CPUActivePercent> |
| | </Plans> |
| | </MostActiveDB2Plans> |

| Field title in online report | XML element |
|---|--|
| Most Active Package/DBRMs | <MostActivePackageDBRMs> |
| Samples | <Samples>n</Samples> |
| | <Percent>n%</Percent> |
| Reports | <Reports>F03</Reports> |
| | <DBRMs> |
| <i>DBRM Name</i> | <DBRM>name</DRRM> |
| | <CPUActive>n</CPUActive> |
| | <CPUActivePercent>n%</CPUActivePercent> |
| | </DBRMs> |
| | </MostActivePackageDBRMs> |
| Most Active SQL Statements | <MostActiveSQLStatements> |
| Samples | <Samples>n</Samples> |
| | <Percent>n%</Percent> |
| Reports | <Reports>F04</Reports> |
| | <SQLStatement> |
| <i>Program:offset:verb</i> | <ProgramOffsetVerb>program:offset:verb</ProgramOffsetVerb> |
| | <CPUActive>n</CPUActive> |
| | <CPUActivePercent>n%</CPUActivePercent> |
| | </SQLStatement> |
| | </MostActiveSQLStatements> |
| Most Active IMS PSBs | <MostActiveIMSPSBs> |
| Samples | <Samples>n</Samples> |
| | <Percent>n%</Percent> |
| Reports | <Reports>I05 I08 I11</Reports> |
| | <ActiveIMSPSBs> |
| <i>PSB Name</i> | <PSBName>name</PSBName> |
| | <CPUActive>n</CPUActive> |
| | <CPUActivePercent>n%</CPUActivePercent> |
| | </ActiveIMSPSBs> |
| | </MostActiveIMSPSBs> |
| Most Active IMS DLI Calls | <MostActiveIMSDLICalls> |
| Samples | <Samples>n</Samples> |
| | <Percent>n%</Percent> |
| Reports | <Reports>I07 I10 I13</Reports> |
| | <ActiveIMSDLICalls> |
| <i>Sequence Number:DLI Function Code:PCB Name</i> | <IMSCall>imscall</IMSCall> |
| | <CPUActive>n</CPUActive> |

| Field title in online report | XML element |
|------------------------------|---|
| | <CPUActivePercent>n%</CPUActivePercent> |
| | </ActiveIMSDLICalls> |
| | </MostActiveIMSDLICalls> |
| Request Parameters | <RequestParameters> |
| Request Number | <RequestNumber>nnnn</RequestNumber> |
| Description | <Description>description</Description> |
| Sample file DSN | <SampleFileDSN>dsn</SampleFileDSN> |
| Retention | <Retention>Day Mon-dd-yyyy</Retention> |
| Data Extractors | <DataExtractors>extractor list</DataExtractors> |
| Requesting user | <RequestingUser>userid</RequestingUser> |
| Specific DB2Parms | <SpecificDB2Parms>P F</SpecificDB2Parms> |
| DB2 Subsystem | <DB2SubSystem>name</DB2SubSystem> |
| Schema | <Schema>name</Schema> |
| Name | <Name>name</Name> |
| Nbr of samples | <NumberOfSamples>n</NumberOfSamples> |
| Time of request | <TimeOfRequest>hh:mm:ss</TimeOfRequest> |
| Duration | <Duration>n sec</Duration> |
| Date of request | <DateOfRequest>Day Mon-dd-yyyy</DateOfRequest> |
| Active/pending | <ActivePending>Status</ActivePending> |
| Job name | <JobName>name</JobName> |
| Proc step name | <ProcStepName>procstepname</ProcStepName> |
| Step name/number | <StepName>stepname</StepName> |
| Delay time | <DelayTime>n</DelayTime> |
| Step program | <StepProgram>steppgm</StepProgram> |
| | </RequestParameters> |
| Measurement environment | <MeasurementEnvironment> |
| Job name | <JobName>name</JobName> |
| Region size <16MB | <RegionSizeBelow>nK</RegionSizeBelow> |
| Job number | <JobNumber>number</JobNumber> |
| Region size >16MB | <RegionSizeAbove>nK</RegionSizeAbove> |
| Step name | <StepName>stepname</StepName> |
| Step program | <StepProgram>steppgm</StepProgram> |
| Proc step name | <ProcStepName>procstepname</ProcStepName> |
| Region type | <RegionType>regiontype</RegionType> |
| ASID | <ASID>asid</ASID> |
| DB2 Attach type | <DB2AttachType>type</DB2AttachType> |
| System ID | <SystemID>sysid</SystemID> |
| APA Version | <APAVersion>version</APAVersion> |
| SMFID | <SMFID>smfid</SMFID> |

| Field title in online report | XML element |
|------------------------------|---|
| O/S level | <OSLevel>oslevel</OSLevel> |
| Nbr of CPUs | <NbrOfCPUs>n</NbrOfCPUs> |
| CPU model | <CPUModel>model</CPUModel> |
| CPU rate factor | <CPURateFactor>n</CPURateFactor> |
| CPU version | <CPUVersion>version</CPUVersion> |
| MIPS per CPU | <MIPSPerCPU>n</MIPSPerCPU> |
| SUs per second | <SUsPerSecond>n</SUsPerSecond> |
| | </MeasurementEnvironment> |
| Measurement statistics | <MeasurementStatistics> |
| Start time | <StartTime>hh:mm:ss</StartTime> |
| Start date | <StartDate>Day Mon-dd-yyyy</StartDate> |
| End time | <EndTime>hh:mm:ss</EndTime> |
| End date | <EndDate>Day Mon-dd-yyyy</EndDate> |
| Total samples | <TotalSamples>n</TotalSamples> |
| Duration | <Duration>n min n sec</Duration> |
| Sampling rate | <SamplingRate>n per sec</SamplingRate> |
| Report dataspace | <ReportDataspace>nMB</ReportDataspace> |
| CPU/WAIT samples | <CPUWaitSamples>n</CPUWaitSamples> |
| Sample dataspace | <SampleDataspace>nMB</SampleDataspace> |
| TCB samples | <TCBSamples>n</TCBSamples> |
| Meas significance | <MeasurementSignificance>n%</MeasurementSignificance> |
| CPU queued samples | <CPUQueuedSamples>n</CPUQueuedSamples> |
| Overall CPU | <OverallCPU>n%</OverallCPU> |
| Pages in | <PagesIn>n</PagesIn> |
| EXCPs | <EXCPs>n</EXCPs> |
| Pages out | <PagesOut>n</PagesOut> |
| | </MeasurementStatistics> |
| CPU consumption | <CPUConsumption> |
| CPU active samples | <CPUActiveSamples>n</CPUActiveSamples> |
| CPU time TCB | <CPUTimeTCB>n sec</CPUTimeTCB> |
| CPU active time | <CPUActiveTime>n%</CPUActiveTime> |
| CPU time SRB | <CPUTimeSRB>n sec</CPUTimeSRB> |
| CPU WAIT samples | <CPUWaitSamples>n</CPUWaitSamples> |
| Service Units | <ServiceUnits>n</ServiceUnits> |
| CPU WAIT time | <CPUWaitTime>n%</CPUWaitTime> |
| Measurement SRB | <MeasurementSRB>n sec</MeasurementSRB> |
| zAAP CPU Time | < zAAPCPUTime>n sec / zAAPCPUTime> |
| zAAP Time on CP | < zAAPTimeonCP >n sec</ zAAPTimeonCP > |
| Task Time on CP | < TaskTimeonCP>n sec</TaskTimeonCP> |
| Norm. Factor | < NormFactor>n</ NormFactor> |

| Field title in online report | XML element |
|------------------------------|--|
| Normalized Time | < NormalizedTime>n sec</ NormalizedTime> |
| | </CPUConsumption> |
| DDF CPU consumption | <DDFCPUConsumption> |
| Task CPU time | <TaskCPUTime>n sec</TaskCPUTime> |
| zIIP time | <zIIPTime>n sec</zIIPTime> |
| Enclave CPU time | <EnclaveCPUTime>n sec</EnclaveCPUTime> |
| zIIP on CP time | <zIIPonCPTime>n sec</zIIPonCPTime> |
| | </DDFCPUConsumption> |
| | <ClientEnclaveConsumption> |
| Client SRB Time | <ClientSRBTime>n sec</ClientSRBTime> |
| Total TCB Time | <TotalTCBTime>n sec</TotalTCBTime> |
| | </ClientEnclaveConsumption> |

S02 Load Module Attributes

The table below lists all possible report tag pairs and their sub-elements hierarchically. When the XML document is created, the report tag pairs may be repeated, nested or eliminated as appropriate for the data in the report, and depending on the setup options chosen.

| Field title in online report | XML element |
|------------------------------|---|
| | <LoadModuleAttributes> |
| Module Information for | <ModuleInformationFor>name</ModuleInformationFor> |
| Load Address | <LoadAddress>n to n</LoadAddress> |
| Module Size | <ModuleSize>n</ModuleSize> |
| Attributes | <Attributes>attributes</Attributes> |
| Module Location | <ModuleLocation>location</ModuleLocation> |
| SVC Module for | <SVCModuleFor>n</SVCModuleFor> |
| Loadlib DDNAME | <DDName>ddname</DDName> |
| Load Library | <LoadLibrary>dsn</LoadLibrary> |
| Program Group | <ProgramGroup>pgmgroup</ProgramGroup> |
| Subgroup | <SubGroup>subgroup</SubGroup> |
| Function | <Function>function</Function> |
| | <ESDInformationFor> |
| ESD Information for | <ModuleName<name>/ModuleName> |
| | <ESDInformation> |
| External | <External>external</External> |
| Offset | <Offset>n</Offset> |
| Length | <Length>n</Length> |
| Start Addr | <StartAddr>n</StartAddr> |
| End Addr | <EndAddr>n</EndAddr> |

| Field title in online report | XML element |
|------------------------------|--|
| Entry Points | <EntryPointCompiler> |
| Compiled by | <CompilerLanguage> <i>language</i> </CompilerLanguage> |
| | <CompilerVersion> <i>version</i> </CompilerVersion> |
| at | <TimeStamp> <i>yyyy/mm/dd hh:mm:ss</i> </TimeStamp> |
| | <EntryPointOffset> |
| | <HexOffset> <i>+n</i> </HexOffset> |
| | <EntryPointName< <i>name</i> >/EntryPointName> |
| | </EntryPointOffset> |
| | </EntryPointCompiler> |
| | </ESDInformation> |
| | </ESDInformationFor> |
| | </LoadModuleAttributes> |

S03 Load Module Summary

The LoadModuleSummary tag pair and sub-elements are repeated for each module in the report.

| Field title in online report | XML element |
|------------------------------|--|
| | <LoadModuleSummary> |
| Module | <ModuleName> <i>name</i> </ModuleName> |
| Locn | <Location> <i>location</i> </Location> |
| Address | <Address> <i>n</i> </Address> |
| Count | <Count> <i>n</i> </Count> |
| Size(bytes) | <Size> <i>n</i> </Size> |
| Attributes | <Attributes> <i>attributes</i> </Attributes> |
| DDName | <DDName> <i>ddname</i> </DDName> |
| LoadLibrary | <DatasetName> <i>dsn</i> </DatasetName> |
| | </LoadModuleSummary> |

S04 TCB Summary

The TCBSummary tag pair and sub-elements are repeated for each task in the report. These tag pairs and sub-elements are also nested, with the ATTACHED subtasks relative to the parent tasks that performed the ATTACH function.

| Field title in online report | XML element |
|------------------------------|--|
| | <TCBSummary> |
| TCB_Name | <TCBName> <i>name-index</i> </TCBName> |
| Address | <Address> <i>n</i> </Address> |
| Samples | <Samples> <i>n</i> </Samples> |
| CPU Active | <CPUActive> <i>n%</i> </CPUActive> |

| Field title in online report | XML element |
|------------------------------|-----------------------|
| CPU WAIT | <CPUWait>n%</CPUWait> |
| Queued | <Queued>n%</Queued> |
| | </TCBSummary> |

S05 Memory Usage Timeline

The UsageTimeline tag pair and sub-elements are repeated for each time interval.

| Field title in online report | XML element |
|------------------------------|------------------------------------|
| | <UsageTimeline> |
| SEQN | <SequenceNumber>n</SequenceNumber> |
| Seconds | <Seconds>n</Seconds> |
| Storage | <Storage>nK</Storage> |
| | </UsageTimeline> |

S06 Data Space Usage Timeline

The UsageTimeline tag pair and sub-elements are repeated for each time interval.

| Field title in online report | XML element |
|------------------------------|------------------------------------|
| | <UsageTimeline> |
| SEQN | <SequenceNumber>n</SequenceNumber> |
| Seconds | <Seconds>n</Seconds> |
| Storage | <Storage>nK</Storage> |
| | </UsageTimeline> |

S07 TCB Execution Summary

The TCBEExecutionSummary tag pair and sub-elements are repeated for each task in the report. These tag pairs and sub-elements are also nested, with the ATTACHed subtasks relative to the parent tasks that performed the ATTACH function.

| Field title in online report | XML element |
|------------------------------|----------------------------------|
| | <TCBEExecutionSummary> |
| TCB_Name | <TCBName>name-index</TCBName> |
| Seconds | <MeasuredCPU>n Sec</MeasuredCPU> |
| Storage | <TCBTotalCPU>n Sec</TCBTotalCPU> |
| | <FirstSample>n</FirstSample> |
| | <LastSample>n</LastSample> |
| | </UsageTimeline> |

S08 Processor Utilization Summary

The ProcessorUtilizationSummary tag pair and sub-elements are repeated for each CPU state in the report.

| Field title in online report | XML element |
|------------------------------|--|
| | <ProcessorUtilizationSummary> |
| Processor State | <ProcessorState>state</ProcessorState> |
| Nbr of Samples | <NumberOfSamples>n</NumberOfSamples> |
| Percentage | <Percentage>n%</Percentage> |
| | </ProcessorUtilizationSummary> |

S09 Measurement Analysis

The DetailLine element data is limited to 200 characters. When the details are greater than 200 characters, multiple DetailLine elements are included.

| Field title in online report | XML element |
|------------------------------|------------------------------------|
| | <MeasurementAnalysis> |
| | <Summary>summary</Summary> |
| | <Reports>list of reports</Reports> |
| | <AnalysisDetail> |
| | <DetailLine>details</DetailLine> |
| | </AnalysisDetail> |
| | </MeasurementAnalysis> |

C01 CPU Usage by Category

The XML elements presented below may be repeated multiple times and appear under different parent elements. In the XML document, all elements are listed in hierarchical order as they appear in the online report.

| Field title in online report | XML element |
|---------------------------------|---|
| | <Category> |
| Name | <CategoryName>name</CategoryName> |
| Description | <CategoryDescription>description</CategoryDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </Category> |
| | <SQLRequest> |
| Name | <SequenceNumber>n</SequenceNumber> |
| Description | <ProgramStatementFunction>name(stmt)function</ProgramStatementFunction> |
| | <Measurements>n</Measurements> |

| Field title in online report | XML element |
|---------------------------------|---|
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </SQLRequest> |
| | <LoadModule> |
| Name | <LoadModuleName>name</LoadModuleName> |
| Description | <LoadModuleDescription>description</LoadModuleDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </LoadModule> |
| | <CSECT> |
| Name | <CSECTName>name</CSECTName> |
| Description | <CSECTDescription>description</CSECTDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </CSECT> |
| | <NoSymAddressRange> |
| Name | <AddressRange>address</AddressRange> |
| Description | <AddressRangeDescription>Unresolved Address</AddressRangeDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </NoSymAddressRange> |
| | <DPAGroup> |
| Name | <DPAGroupName>name</DPAGroupName> |
| Description | <DPAGroupDescription>description</DPAGroupDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </DPAGroup> |
| | <SVCRoutine> |
| Name | <SVCIId>svcid</SVCIId> |
| Description | <SVCDescription>description</SVCDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </SVCRoutine> |
| | <DLICall> |
| Name | <SequenceNumber>n</SequenceNumber> |

| Field title in online report | XML element |
|---------------------------------|---|
| Description | <FunctionPCBProgramOffset>FuncNameNameOffset</FunctionPCBProgramOffset> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </DLICall> |
| | <File> |
| Name | <DDName>ddname</DDName> |
| Description | <AccessMethod>accessmethod</AccessMethod> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </File> |
| | <DMRequest> |
| Name | <MacroName>name</MacroName> |
| Description | <MacroLocation>location</MacroLocation> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </DMRequest> |
| | <ADABASCommand> |
| Name | <Command>n</Command> |
| Description | <CSECTOffset>offset</CSECTOffset> |
| | <Measurement>n</Measurement> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </ADABASCommand> |

C02 CPU Usage by Module

The XML elements presented below may be repeated multiple times and appear under different parent elements. In the XML document, all elements are listed in hierarchical order as they appear in the online report.

| Field title in online report | XML element |
|---------------------------------|--|
| | <LoadModule> |
| Name | <LoadModuleName>name</LoadModuleName> |
| Description | <LoadModuleDescription>description</LoadModuleDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | <CSECT> |
| Name | <CSECTName>name</CSECTName> |

| Field title in online report | XML element |
|---------------------------------|---|
| | |
| Description | <CSECTDescription>description</CSECTDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </CSECT> |
| | </LoadModule> |
| | <NoSymAddressRange> |
| Name | <AddressRange>address</AddressRange> |
| Description | <AddressRangeDescription>Unresolved Address</AddressRangeDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </NoSymAddressRange> |

C03 CPU Usage by Code Slice

The Code Slice tag pair and sub-elements are repeated for each code slice in the report.

| Field title in online report | XML element |
|---------------------------------|---|
| | <CodeSlice> |
| Address | <CodeSliceAddress>n</CodeSliceAddress> |
| Size Location | <SizeAndLocation>n loc+offset</SizeAndLocation> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | <CodeAddress> |
| Address | <Address>address</Address> |
| Location | <Location>loc+offset</Location> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </CodeAddress> |
| | </CodeSlice> |

C04 CPU Usage Timeline

The Interval tag pair and sub-elements are repeated for each interval reported.

| Field title in online report | XML element |
|------------------------------|-------------|
| | <Interval> |

| Field title in online report | XML element |
|---------------------------------|------------------------------------|
| SEQN | <SequenceNumber>n</SequenceNumber> |
| Seconds | <Seconds>n</Seconds> |
| Sig | <Significance>n%</Significance> |
| | <Measurements>n</Measurements> |
| Percent of Interval * 10.00% | <Percent>n</Percent> |
| | </Interval> |

C05 CPU Usage by Task/Category

The XML elements presented below may be repeated multiple times and appear under different parent elements. In the XML document, all elements are listed in hierarchical order as they appear in the online report.

| Field title in online report | XML element |
|---------------------------------|---|
| | <Task> |
| Name | <TaskName>name</TaskName> |
| Description | <TCBAddress>TCB=address</TCBAddress> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </Task> |
| | <Category> |
| Name | <CategoryName>name</CategoryName> |
| Description | <CategoryDescription>description</CategoryDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </Category> |
| | <SQLRequest> |
| Name | <SequenceNumber>n</SequenceNumber> |
| Description | <ProgramStatementFunction>name(stmt)function</ProgramStatementFunction> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </SQLRequest> |
| | <LoadModule> |
| Name | <LoadModuleName>name</LoadModuleName> |
| Description | <LoadModuleDescription>description</LoadModuleDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |

| Field title in online report | XML element |
|---------------------------------|---|
| | </LoadModule> |
| | <CSECT> |
| Name | <CSECTName>name</CSECTName> |
| Description | <CSECTDescription>description</CSECTDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </CSECT> |
| | <NoSymAddressRange> |
| Name | <AddressRange>address</AddressRange> |
| Description | <AddressRangeDescription>Unresolved Address</AddressRangeDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </NoSymAddressRange> |
| | <DPAGroup> |
| Name | <DPAGroupName>name</DPAGroupName> |
| Description | <DPAGroupDescription>description</DPAGroupDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </DPAGroup> |
| | <SVCRoutine> |
| Name | <SVCIId>svcid</SVCIId> |
| Description | <SVCDescription>description</SVCDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </SVCRoutine> |
| | <DLICall> |
| Name | <SequenceNumber>n</SequenceNumber> |
| Description | <FunctionPCBProgramOffset>FuncNameNameOffset</FunctionPCBProgramOffset> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </DLICall> |
| | <File> |
| Name | <DDName>ddname</DDName> |
| Description | <AccessMethod>accessmethod</AccessMethod> |
| | <Measurements>n</Measurements> |

| Field title in online report | XML element |
|---------------------------------|---|
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </File> |
| | <DMRequest> |
| Name | <MacroName>name</MacroName> |
| Description | <MacroLocation>location</MacroLocation> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </DMRequest> |
| | <ADABASCommand> |
| Name | <Command>n</Command> |
| Description | <CSECTOffset>offset</CSECTOffset> |
| | <Measurement>n</Measurement> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </ADABASCommand> |

C06 CPU Usage by Task/Module

The XML elements presented below may be repeated multiple times and appear under different parent elements. In the XML document, all elements are listed in hierarchical order as they appear in the online report.

| Field title in online report | XML element |
|---------------------------------|--|
| | <Task> |
| Name | <TaskName>name</TaskName> |
| Description | <TCBAddress>TCB=n</TCBAddress> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </Task> |
| | <LoadModule> |
| Name | <LoadModuleName>name</LoadModuleName> |
| Description | <LoadModuleDescription>description</LoadModuleDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </LoadModule> |
| | <CSECT> |
| Name | <CSECTName>name</CSECTName> |
| Description | <CSECTDescription>description</CSECTDescription> |
| | <Measurements>n</Measurements> |

| Field title in online report | XML element |
|---------------------------------|---|
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </CSECT> |
| | <NoSymAddressRange> |
| Name | <AddressRange>address</AddressRange> |
| Description | <AddressRangeDescription>Unresolved Address</AddressRangeDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </NoSymAddressRange> |

C07 CPU Usage by Procedure

| Field title in online report | XML element |
|---------------------------------|--|
| | <SourceProgramProcedure> |
| Program | <Program>name</Program> |
| Procedure Name | <ProcedureName>name</ProcedureName> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </SourceProgramProcedure> |
| | <Category> |
| Program | <CategoryName>name</CategoryName> |
| Procedure Name | <CategoryDescription>description</CategoryDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </Category> |

C08 CPU Usage Referred Attribution

| Field title in online report | XML element |
|---------------------------------|--|
| | <LoadModule> |
| Name | <LoadModuleName>name</LoadModuleName> |
| Description | <LoadModuleDescription>description</LoadModuleDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | <CSECT> |
| Name | <CSECTName>name</CSECTName> |

| Field title in online report | XML element |
|---------------------------------|---|
| Description | <CSECTDescription>description</CSECTDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | <AttributionOffset> |
| Name | <Offset>n</Offset> |
| Description | <OffsetInCSECT>Attribution Offset in name</OffsetInCSECT> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | <SourceStatements> |
| Source Statement in: | <ProcedureName>n</ProcedureName> |
| | <SourceStatement>source</SourceStatement> |
| | </SourceStatements> |
| | </AttributionOffset> |
| | </CSECT> |
| | </LoadModule> |

C09 CPU Usage by PSW/Object Code

| Field title in online report | XML element |
|---------------------------------|---|
| | <PSW Location> |
| Address | <Address>n</Address> |
| Module | <ModuleName>name</ModuleName> |
| AM | <AddressingMode>n</AddressingMode> |
| S/P | <SVCNumberorStateStorageKey>aa</SVCNumberorStateStorageKey> |
| AS | <AddressSpaceMode>mode</AddressSpaceMode> |
| ASID | <ASID>asid</ASID> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | <MachineInstruction> |
| | <ModuleOffset>name+offset</ModuleOffset> |
| | <ObjectCode>object code</ObjectCode> |
| | <DisassembledCode>object code</DisassembledCode> |
| | </MachineInstruction> |
| | </PSWLocation> |

W01 WAIT Time by Task/Category

The XML elements presented below may be repeated multiple times and appear under different parent elements. In the XML document, all elements are listed in hierarchical order as they appear in the online report.

| Field title in online report | XML element |
|----------------------------------|---|
| | <Task> |
| Name | <TaskName>name</TaskName> |
| Description | <TCBAddress>TCB= <i>n</i> </TCBAddress> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time in WAIT * 10.00% | <Percent> <i>n</i> </Percent> |
| | </Task> |
| | <Category> |
| Name | <CategoryName>name</CategoryName> |
| Description | <CategoryDescription>description</CategoryDescription> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time in WAIT * 10.00% | <Percent> <i>n</i> </Percent> |
| | </Category> |
| | <SQLRequest> |
| Name | <SequenceNumber> <i>n</i> </SequenceNumber> |
| Description | <ProgramStatementFunction>name(stmt)function</ProgramStatementFunction> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time in WAIT * 10.00% | <Percent> <i>n</i> </Percent> |
| | </SQLRequest> |
| | <LoadModule> |
| Name | <LoadModuleName>name</LoadModuleName> |
| Description | <LoadModuleDescription>description</LoadModuleDescription> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time in WAIT * 10.00% | <Percent> <i>n</i> </Percent> |
| | </LoadModule> |
| | <CSECT> |
| Name | <CSECTName>name</CSECTName> |
| Description | <CSECTDescription>description</CSECTDescription> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time in WAIT * 10.00% | <Percent> <i>n</i> </Percent> |
| | </CSECT> |
| | <NoSymAddressRange> |
| Name | <AddressRange>address</AddressRange> |

| Field title in online report | XML element |
|----------------------------------|---|
| Description | <AddressRangeDescription>Unresolved Address</AddressRangeDescription> |
| | <Measurements>n</Measurements> |
| Percent of Time in WAIT * 10.00% | <Percent>n</Percent> |
| | </NoSymAddressRange> |
| | <DPAGroup> |
| Name | <DPAGroupName>name</DPAGroupName> |
| Description | <DPAGroupDescription>description</DPAGroupDescription> |
| | <Measurements>n</Measurements> |
| Percent of Time in WAIT * 10.00% | <Percent>n</Percent> |
| | </DPAGroup> |
| | <SVCRoutine> |
| Name | <SVCId>svcid</SVCId> |
| Description | <SVCDescription>description</SVCDescription> |
| | <Measurements>n</Measurements> |
| Percent of Time in WAIT * 10.00% | <Percent>n</Percent> |
| | </SVCRoutine> |
| | <DLICall> |
| Name | <SequenceNumber>n</SequenceNumber> |
| Description | <FunctionPCBProgramOffset>FuncNameNameOffset</FunctionPCBProgramOffset> |
| | <Measurements>n</Measurements> |
| Percent of Time in WAIT * 10.00% | <Percent>n</Percent> |
| | </DLICall> |
| | <File> |
| Name | <DDName>ddname</DDName> |
| Description | <AccessMethod>accessmethod</AccessMethod> |
| | <Measurements>n</Measurements> |
| Percent of Time in WAIT * 10.00% | <Percent>n</Percent> |
| | </File> |
| | <DMRequest> |
| Name | <MacroName>name</MacroName> |
| Description | <MacroLocation>location</MacroLocation> |
| | <Measurements>n</Measurements> |
| Percent of Time in WAIT * 10.00% | <Percent>n</Percent> |
| | </DMRequest> |

| Field title in online report | XML element |
|------------------------------|--|
| | <ADABASCommand> |
| Name | <Command> <i>n</i> </Command> |
| Description | <CSECTOffset> <i>offset</i> </CSECTOffset> |
| | <Measurement> <i>n</i> </Measurement> |
| Percent of CPU Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | </ADABASCommand> |

W02 WAIT Time by Task/Module

The XML elements presented below may be repeated multiple times and appear under different parent elements. In the XML document, all elements are listed in hierarchical order as they appear in the online report.

| Field title in online report | XML element |
|----------------------------------|---|
| | <Task> |
| Name | <TaskName> <i>name</i> </TaskName> |
| Description | <TCBAddress>TCB= <i>n</i> </TCBAddress> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of TIME in WAIT * 10.00% | <Percent> <i>n</i> </Percent> |
| | </Task> |
| | <LoadModule> |
| Name | <LoadModuleName> <i>name</i> </LoadModuleName> |
| Description | <LoadModuleDescription> <i>description</i> </LoadModuleDescription> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of TIME in WAIT * 10.00% | <Percent> <i>n</i> </Percent> |
| | </LoadModule> |
| | <CSECT> |
| Name | <CSECTName> <i>name</i> </CSECTName> |
| Description | <CSECTDescription> <i>description</i> </CSECTDescription> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of TIME in WAIT * 10.00% | <Percent> <i>n</i> </Percent> |
| | </CSECT> |
| | <NoSymAddressRange> |
| Name | <AddressRange> <i>address</i> </AddressRange> |
| Description | <AddressRangeDescription>Unresolved Address</AddressRangeDescription> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of TIME in WAIT * 10.00% | <Percent> <i>n</i> </Percent> |

| Field title in online report | XML element |
|------------------------------|----------------------|
| | </NoSymAddressRange> |

W03 WAIT Referred Attribution by Task

The XML elements presented below may be repeated multiple times and appear under different parent elements. In the XML document, all elements are listed in hierarchical order as they appear in the online report.

| Field title in online report | XML element |
|----------------------------------|--|
| | <Task> |
| Name | <TaskName> <i>name</i> </TaskName> |
| Description | <TCBAddress>TCB= <i>n</i> </TCBAddress> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time in WAIT * 10.00% | <Percent> <i>n</i> </Percent> |
| | </Task> |
| | <LoadModule> |
| Name | <LoadModuleName> <i>name</i> </LoadModuleName> |
| Description | <LoadModuleDescription> <i>description</i> </LoadModuleDescription> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time in WAIT * 10.00% | <Percent> <i>n</i> </Percent> |
| | <CSECT> |
| Name | <CSECTName> <i>name</i> </CSECTName> |
| Description | <CSECTDescription> <i>description</i> </CSECTDescription> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time in WAIT * 10.00% | <Percent> <i>n</i> </Percent> |
| | <AttributionOffset> |
| Name | <Offset> <i>n</i> </Offset> |
| Description | <OffsetInCSECT>Attribution Offset in <i>csectname</i> </OffsetInCSECT> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time in WAIT * 10.00% | <Percent> <i>n</i> </Percent> |
| | <SourceStatements> |
| Source Statement in: | <ProcedureName> <i>name</i> </ProcedureName> |
| | <SourceStatement> <i>source</i> </SourceStatement> |
| | </SourceStatements> |
| | </AttributionOffset> |
| | </CSECT> |
| | </LoadModule> |

W04 WAIT Time by Task ENQ/RESERVE

| Field title in online report | XML element |
|----------------------------------|--------------------------------|
| | <Task> |
| Name | <TaskName>name</TaskName> |
| Description | <TCBAddress>TCB=n</TCBAddress> |
| | <Measurements>n</Measurements> |
| Percent of Time in WAIT * 10.00% | <Percent>n</Percent> |
| | <Enqueue> |
| Name | <QName>name</QName> |
| Description | <RName>name</RName> |
| | <Measurements>n</Measurements> |
| Percent of Time in WAIT * 10.00% | <Percent>n</Percent> |
| | </Enqueue> |
| | </Task> |

W05 WAIT Time by Tape DDNAME

| Field title in online report | XML element |
|----------------------------------|--------------------------------|
| | <WaitForTape> |
| DDNAME | <DDName>ddname</DDName> |
| Device | <Device>description</Device> |
| | <Measurements>n</Measurements> |
| Percent of Time in WAIT * 10.00% | <Percent>n</Percent> |
| | </WaitForTape> |

D01 DASD Usage Time by Device

| Field title in online report | XML element |
|------------------------------|--------------------------------------|
| | <ByVolser> |
| Volume>Cyl | <Volser>volser</Volser> |
| Unit-Dev>DD | <UnitDevice>unit-device</UnitDevice> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <ByCylinder> |
| Volume>Cyl | <Cylinder>Cyl_n</Cylinder> |
| Unit-Dev>DD | <DDName>ddname</DDName> |
| | <Measurements>n</Measurements> |

| Field title in online report | XML element |
|------------------------------|----------------------|
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | </ByCylinder> |
| | </ByVolser> |

D02 DASD Usage Time by DDNAME

| Field title in online report | XML element |
|------------------------------|--------------------------------------|
| | <ByDDName> |
| DDNAME>Cyl | <DDName>ddname</DDName> |
| Volume>Unit | <Volser>volser</Volser> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <ByCylinder> |
| DDNAME>Cyl | <Cylinder>Cyl_n</Cylinder> |
| Volume>Unit | <UnitDevice>unit-device</UnitDevice> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | </ByCylinder> |
| | </ByDDName> |

D03 DASD Usage Time by Dataset

| Field title in online report | XML element |
|------------------------------|--------------------------------|
| | <ByDataset> |
| Dataset Name>DDName | <DatasetName>dsn</DatasetName> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <ByDDName> |
| Dataset Name>DDName | <DDName>ddname</DDName> |
| | <Volser>volser</Volser> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | </ByDDName> |
| | </ByDataset> |

D04 Dataset Attributes

| Field title in online report | XML element |
|------------------------------|---|
| | <DatasetAttributes> |
| | <FileType>filetype</FileType> |
| | <DDName>ddname</DDName> |
| OPENed at | <OpenTime>hh:mm:ss.ss</OpenTime> |
| | <OpenDate>Day Month dd yyyy</OpenDate> |
| | <FileDefinition> |
| DDNAME | <DDName>ddname</DDName> |
| Open Intent | <OpenIntent>intent</OpenIntent> |
| Dataset Name | <DatasetName>dsn</DatasetName> |
| | <ManagementClass>class</ManagementClass> |
| | <StorageClass>class</StorageClass> |
| | <DataClass>class</DataClass> |
| Device Type | <DeviceType>type</DeviceType> |
| Nbr of Extents | <NbrOfExtents>n</NbrOfExtents> |
| Dataset Org | <DatasetOrg>dsorg</DatasetOrg> |
| Block Size(BLKSIZE) | <BlockSize>n</BlockSize> |
| RECFM | <RecordFormat>rfm</RecordFormat> |
| Record Size (LRECL) | <RecordSize>n</RecordSize> |
| Data Buffers | <DataBuffers>n</DataBuffers> |
| | <VOLERS> |
| Volume Serial | <Volser>volser</Volser> |
| | </VOLERS> |
| | </FileDefinition> |
| | <VSAMDataComponent> |
| DDNAME | <DDName>ddname</DDName> |
| Open Intent | <OpenIntent>intent</OpenIntent> |
| Dataset Name | <DatasetName>dsn</DatasetName> |
| | <ManagementClass>class</ManagementClass> |
| | <StorageClass>class</StorageClass> |
| | <DataClass>class</DataClass> |
| Device Type | <DeviceType>type</DeviceType> |
| % Free Bytes in CI | <PercentFreeBytesInCI>n%</PercentFreeBytesInCI> |
| CI Splits (Initial) | <CISplitsInitial>n</CISplitsInitial> |
| CI Splits (Last) | <CISplitsLast>n</CISplitsLast> |
| CI Size | <CISize>n</CISize> |
| CA Splits (Initial) | <CASplitsInitial>n</CASplitsInitial> |
| CA Splits (Last) | <CASplitsLast>n</CASplitsLast> |
| Record Size (LRECL) | <RecordSize>n</RecordSize> |
| Logical Records (Initial) | <RecordsInitial>n</RecordsInitial> |

| Field title in online report | XML element |
|------------------------------|--|
| Logical Records (Last) | <RecordsLast>n</RecordsLast> |
| Number of Extents | <NbrOfExtents>n</NbrOfExtents> |
| Deleted Records (Initial) | <DeletedRecordsInitial>n</DeletedRecordsInitial> |
| Deleted Records (Last) | <DeletedRecordsLast>n</DeletedRecordsLast> |
| SHAREOPTIONS | <ShareOptions>(n n)</ShareOptions> |
| Insrted Records (Initial) | <InsertedRecordsInitial>n</InsertedRecordsInitial> |
| Insrted Records (Last) | <InsertedRecordsLast>n</InsertedRecordsLast> |
| Organization | <Organization>org</Organization> |
| Retrvd Records (Initial) | <RetrievedRecordsInitial>n</RetrievedRecordsInitial> |
| Retrvd Records (Last) | <RetrievedRecordsLast>n</RetrievedRecordsLast> |
| CIs per CA | <CIsPerCa>n</CIsPerCa> |
| Updated Records (Initial) | <UpdatedRecordsInitial>n<UpdatedRecordsInitial> |
| Updated Records (Last) | <UpdatedRecordsLast>n<UpdatedRecordsLast> |
| Free CIs per CA | <FreeCIsPerCa>n</FreeCIsPerCa> |
| Bytes Free Space (Initial) | <BytesFreeSpaceInitial>n</BytesFreeSpaceInitial> |
| Bytes Free Space (Last) | <BytesFreeSpaceLast>n</BytesFreeSpaceLast> |
| Free Bytes per CI | <FreeBytesPerCI>n</FreeBytesPerCI> |
| Number of EXCPs (Initial) | <NumberOfEXCPsInitial>n</NumberOfEXCPsInitial> |
| Number of EXCPs (Last) | <NumberOfEXCPsLast>n</NumberOfEXCPsLast> |
| % Free CIs in CA | <PercentFreeCisInCA>n%</PercentFreeCisInCA> |
| Strings | <Strings>n</Strings> |
| String Waits | <StringWaits>n</StringWaits> |
| String Waist HWM | <StringWaitsHWM>n</StringWaitsHWM> |
| Data Buffers | <DataBuffers>n</DataBuffers> |
| Index Buffers | <IndexBuffers>n</IndexBuffers> |
| | <VOLSERS> |
| Volume Serial | <Volser>volser</Volser> |
| | </VOLSERS> |
| | </VsamDataComponent> |
| | <VSAMIndexComponent> |
| Dataset Name | <DatasetName>dsn</DatasetName> |
| | <ManagementClass>class</ManagementClass> |
| | <StorageClass>class</StorageClass> |
| | <DataClass>class</DataClass> |
| Device Type | <DeviceType>type</DeviceType> |
| % Free Bytes in CI | <PercentFreeBytesInCI>n%</PercentFreeBytesInCI> |
| CI Splits (Initial) | <CISplitsInitial>n</CISplitsInitial> |

| Field title in online report | XML element |
|------------------------------|--|
| CI Splits (Last) | <CISplitsLast>n</CISplitsLast> |
| CI Size | <CISize>n</CISize> |
| CA Splits (Initial) | <CASplitsInitial>n</CASplitsInitial> |
| CA Splits (Last) | <CASplitsLast>n</CASplitsLast> |
| Record Size (LRECL) | <RecordSize>n</RecordSize> |
| Logical Records (Initial) | <RecordsInitial>n</RecordsInitial> |
| Logical Records (Last) | <RecordsLast>n</RecordsLast> |
| Number of Extents | <NbrOfExtents>n</NbrOfExtents> |
| Deleted Records (Initial) | <DeletedRecordsInitial>n</DeletedRecordsInitial> |
| Deleted Records (Last) | <DeletedRecordsLast>n</DeletedRecordsLast> |
| SHAREOPTIONS | <ShareOptions>(n n)</ShareOptions> |
| Insrted Records (Initial) | <InsertedRecordsInitial>n</InsertedRecordsInitial> |
| Insrted Records (Last) | <InsertedRecordsLast>n</InsertedRecordsLast> |
| Organization | <Organization>org</Organization> |
| Retrvd Records (Initial) | <RetrievedRecordsInitial>n</RetrievedRecordsInitial> |
| Retrvd Records (Last) | <RetrievedRecordsLast>n</RetrievedRecordsLast> |
| CIs per CA | <CIsPerCa>n</CIsPerCa> |
| Updated Records (Initial) | <UpdatedRecordsInitial>n<UpdatedRecordsInitial> |
| Updated Records (Last) | <UpdatedRecordsLast>n<UpdatedRecordsLast> |
| Free CIs per CA | <FreeCIsPerCa>n</FreeCIsPerCa> |
| Bytes Free Space (Initial) | <BytesFreeSpaceInitial>n</BytesFreeSpaceInitial> |
| Bytes Free Space (Last) | <BytesFreeSpaceLast>n</BytesFreeSpaceLast> |
| Free Bytes per CI | <FreeBytesPerCI>n </FreeBytesPerCI> |
| Number of EXCPs (Initial) | <NumberOfEXCPsInitial>n</NumberOfEXCPsInitial> |
| Number of EXCPs (Last) | <NumberOfEXCPsLast>n</NumberOfEXCPsLast> |
| % Free CIs in CA | <PercentFreeCisInCA>n%</PercentFreeCisInCA> |
| | <VOLSER> |
| Volume Serial | <Volser>volser</Volser> |
| | </VOLSER> |
| | </VsamIndexComponent> |
| | <DasdPerformance> |
| Avg Response Time | <AvgResponseTime>n</AvgResponseTime> |
| Avg Pending Time | <AvgPendingTime>n</AvgPendingTime> |
| Avg Disconnect Time | <AvgDisconnectTime>n</AvgDisconnectTime> |
| Avg Connect Time | <AvgConnectTime>n</AvgConnectTime> |
| Avg Queued Time | <AvgQueuedTime>n</AvgQueuedTime> |
| Total I/Os | <TotalIOs>n</TotalIOs> |

| Field title in online report | XML element |
|------------------------------|--|
| Cache Candidates | <CacheCandidates>n</CacheCandidates> |
| Cache Hits | <CacheHits>n</CacheHits> |
| Write Candidates | <WriteCandidates>n</WriteCandidates> |
| Write Hits | <WriteHits>n</WriteHits> |
| | </DasdPerformance> |
| Concatenated Datasets | <ConcatenatedDatasets> |
| | <DSName>dsn</DSName> Repeated as necessary |
| | </ConcatenatedDatasets> |
| | </DatasetAttributes> |

D05 DASD EXCP Summary

| Field title in online report | XML element |
|------------------------------|---|
| | <DASDEXCPSummary> |
| DDNAME | <DDName>ddname</DDName> |
| Type | <Type>type</Type> |
| Concat | <ConcatenationNumber>+n</ConcatenationNumber> |
| At Start | <StartEXCPs>n</StartEXCPs> |
| At End | <EndEXCPs>n</EndEXCPs> |
| During Measurement | <DifferenceEXCPs>n</DifferenceEXCPs> |
| | </DASDEXCPSummary> |

D06 DASD VSAM Statistics

| Field title in online report | XML element |
|------------------------------|--|
| | <VSAMStatistics> |
| DDNAME | <DDName>ddname</DDName> |
| Retrvd | <RecordsRetrieved>n</RecordsRetrieved> |
| Added | <RecordsAdded>+n</RecordsAdded> |
| Insrtd | <RecordsInserted>n</RecordsInserted> |
| Deletd | <RecordsDeleted>n</RecordsDeleted> |
| Updatd | <RecordsUpdated>n</RecordsUpdated> |
| EXCPs | <EXCPs>n</EXCPs> |
| FreeSpc | <ChangeFreeSpace>+n</ChangeFreeSpace> |
| CISplts | <ChangeCISplits>+n</ChangeCISplits> |
| CASplts | <ChangeCASplits>+n</ChangeCASplits> |
| Str Wt | <StringWaits>n</StringWaits> |
| StrHWM | <StringWaitsHWM>n</StringWaitsHWM> > |
| | </VSAMStatistics> |

D07 DASD Activity Timeline

| Field title in online report | XML element |
|------------------------------|--|
| | <DASDActivityTimeline> |
| | <Samples>n</Samples> |
| | <Duration>n</Duration> |
| DDN | <DDN>ddname</DDN> |
| Type | <Type>type</Type> |
| Vol | <Vol>volser</Vol> |
| Unit | <Unit>unit</Unit> |
| | <Intervals> |
| | <IntervalPct>n</IntervalPct> Repeated 50 times |
| | </Interval> |
| | </DASDActivityTimeline> |

D08 DASD I/O Wait Time

The XML elements presented below may be repeated multiple times and appear under different parent elements. In the XML document, all elements are listed in hierarchical order as they appear in the online report.

| Field title in online report | XML element |
|------------------------------|--|
| | <ByDDName> |
| Name | <DDName>ddname</DDName> |
| Description | <Volser>volser</Volser> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <SVCRoutine> |
| Name | <SVCId>svcid</SVCId> |
| Description | <SVCDescription>description</SVCDescription> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | </SVCRoutine> |
| | <DMRequest> |
| Name | <MacroName>name</MacroName> |
| Description | <MacroLocation>location</MacroLocation> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | </DMRequest> |
| | <LoadModule> |
| Name | <LoadModuleName>name</LoadModuleName> |

| Field title in online report | XML element |
|------------------------------|---|
| Description | <LoadModuleDescription> <i>description</i> </LoadModuleDescription> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | </LoadModule> |
| | <CSECT> |
| Name | <CSECTName> <i>name</i> </CSECTName> |
| Description | <CSECTDescription> <i>description</i> </CSECTDescription> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | </CSECT> |
| | </ByDDName> |

D09 VSAM Buffer Pool Usage

| Field title in online report | XML element |
|------------------------------|---|
| | <LSRPool> |
| LSR Pool | <PoolNumber> <i>n</i> </PoolNumber> |
| Type (Data/Index) | <Type> <i>type</i> </Type> |
| Reads (Initial) | <ReadsInitial> <i>n</i> </ReadsInitial> |
| Reads (Last) | <ReadsLast> <i>n</i> </ReadsLast> |
| Reads (Difference) | <ReadsDifference> <i>n</i> </ReadsDifference> |
| Buffer Size | <BufferSize> <i>n</i> </BufferSize> |
| Reads Avoided (Initial) | <ReadsAvoidedInitial> <i>n</i> </ReadsAvoidedInitial> |
| Reads Avoided (Last) | <ReadsAvoidedLast> <i>n</i> </ReadsAvoidedLast> |
| Reads Avoided (Difference) | <ReadsAvoidedDifference> <i>n</i> </ReadsAvoidedDifference> |
| Buffers | <Buffers> <i>n</i> </Buffers> |
| User Writes (Initial) | <UserWritesInitial> <i>n</i> </UserWritesInitial> |
| User Writes (Last) | <UserWritesLast> <i>n</i> </UserWritesLast> |
| User Writes (Difference) | <UserWritesDifference> <i>n</i> </UserWritesDifference> |
| Hiperspace Buffers | <HiperspaceBuffers> <i>n</i> </HiperspaceBuffers> |
| Non-user Writes (Initial) | <NonUserWritesInitial> <i>n</i> </NonUserWritesInitial> |
| Non-user Writes (Last) | <NonUserWritesLast> <i>n</i> </NonUserWritesLast> |
| Non-user Writes (Difference) | <NonUserWritesDifference> <i>n</i> </NonUserWritesDifference> |
| | </LSRPool> |

G01 Coupling Facility Statistics

| Field title in online report | XML element |
|---------------------------------|--|
| | <CouplingFacilityStatistics> |
| Facility Summary | <CFName>name</CFName> |
| CF Storage | <CFStorage>nK</CFStorage> |
| CF Storage Used | <CFStorageUsed>nK</CFStorageUsed> |
| CF Dump Storage | <CFDumpStorage>nK</CFDumpStorage> |
| CF Storage for Structures | <CFStorageForStructures>nK</CFStorageForStructures> |
| Subchannel Contention Count | <SubchannelContentionCount>n</SubchannelContentionCount> |
| Subchannel Contention Time uSec | <SubchannelContentionCountuSec>n</SubchannelContentionCountuSec> |
| Failed Request Count | <FailedRequestCount>n</FailedRequestCount> |
| Failed Request Time uSec | <FailedRequestTimeuSec>n</FailedRequestTimeuSec> |
| Number of Processors | <NumberOfProcessors>n</NumberOfProcessors> |
| Processor Utilization | <ProcessorUtilization>n%</ProcessorUtilization> |
| | </CouplingFacilityStatistics> |

G02 Coupling Facility Mean Service Times

| Field title in online report | XML element |
|------------------------------|--|
| | <CouplingFacilityServiceTimes> |
| Name | <CFName>name</CFName> or <StructureName>name</StructureName> |
| Number of Requests (Sync) | <RequestsSync>n</RequestsSync> |
| Number of Requests (Async) | <RequestsAsynch>n</RequestsAsynch> |
| Number of Requests (Queued) | <RequestsQueued>n</RequestsQueued> |
| Number of Requests (Delay) | <RequestsDelay>n</RequestsDelay> |
| Mean uSeconds (Sync) | <SecondsSync>n</SecondsSync> |
| Mean uSeconds (Async) | <SecondsAsynch>n</SecondsAsynch> |
| Mean uSeconds (Queued) | <SecondsQueued>n</SecondsQueued> |
| Mean uSeconds (Delay) | <SecondsDelay>n</SecondsDelay> |
| | </CouplingFacilityServiceTimes> |

G03 Coupling Facility Total Service Times

| Field title in online report | XML element |
|------------------------------|--|
| | <CouplingFacilityServiceTimes> |
| Name | <CFName>name</CFName> or <StructureName>name</StructureName> |
| Number of Requests (Sync) | <RequestsSync>n</RequestsSync> |
| Number of Requests (Async) | <RequestsAsync>n</RequestsAsync> |
| Number of Requests (Queued) | <RequestsQueued>n</RequestsQueued> |
| Number of Requests (Delay) | <RequestsDelay>n</RequestsDelay> |
| Total uSeconds (Sync) | <SecondsSync>n</SecondsSync> |
| Total uSeconds (Async) | <SecondsAsync>n</SecondsAsync> |
| Total uSeconds (Queued) | <SecondsQueued>n</SecondsQueued> |
| Total uSeconds (Delay) | <SecondsDelay>n</SecondsDelay> |
| | </CouplingFacilityServiceTimes> |

V01 Measurement Variance Summary

The following tag pairs are repeated multiple times in each variance report. The first occurrence of the tag pair reports the base measurement (Ref 01). Following Ref 01, the tag pairs are repeated for every tagged measurement (Ref *n*).

- <MeasurementsAnalyzed></MeasurementsAnalyzed>
- <CPUTimeTCBVariance></CPUTimeTCBVariance>
- <CPUTimeSRBVariance></CPUTimeSRBVariance>
- <EXCPRequestsVariance></EXCPRequestsVariance>
- <ServiceUnitsVariance></ServiceUnitsVariance>
- <CPUActiveSamplesVariance></CPUActiveSamplesVariance>
- <WaitSamplesVariance></WaitSamplesVariance>
- <QueuedSamplesVariance></QueuedSamplesVariance>

| Field title in online report | XML element |
|---|--|
| The Following Measurements are Analyzed | <MeasurementsAnalyzed> |
| Ref | <Ref>n</Ref> |
| ReqNum | <ReqNum>n</ReqNum> |
| Job Name | <JobName>name</JobName> |
| Date | <Date>Mon-dd-yyyy</Date> |
| Time | <Time>hh:mm</Time> |
| Description | <Description>description</Description> |
| | </MeasurementsAnalyzed> |

| Field title in online report | XML element |
|----------------------------------|--------------------------------|
| CPU Time TCB | <CPUTimeTCBVariance> |
| Ref | <Ref>n</Ref> |
| CPU Time TCB | <CPUTimeTCB>n sec</CPUTimeTCB> |
| Variance | <Variance>variance</Variance> |
| | </CPUTimeTCBVariance> |
| CPU Time SRB | <CPUTimeSRBVariance> |
| Ref | <Ref>n</Ref> |
| CPU Time SRB | <CPUTimeSRB>n sec</CPUTimeSRB> |
| Variance | <Variance>variance</Variance> |
| | </CPUTimeSRBVariance> |
| EXCP Requests | <EXCPRequestsVariance> |
| Ref | <Ref>n</Ref> |
| EXCP Requests | <EXCPRequests>n</EXCPRequests> |
| Variance | <Variance>variance</Variance> |
| | </EXCPRequestsVariance> |
| Service Units | <ServiceUnitsVariance> |
| Ref | <Ref>n</Ref> |
| Service Units | <ServiceUnits>n</ServiceUnits> |
| Variance | <Variance>variance</Variance> |
| | </ServiceUnitsVariance> |
| Percentage of CPU Active Samples | <CPUActiveSamplesVariance> |
| Ref | <Ref>n</Ref> |
| Sample Count (CPU Active) | <CPUActive>n</CPUActive> |
| Sample Count (Total) | <Total>n</Total> |
| Percentage | <Percentage>n%</Percentage> |
| Variance | <Variance>variance</Variance> |
| | </CPUActiveSamplesVariance> |
| Percentage of WAIT Samples | <WaitSamplesVariance> |
| Ref | <Ref>n</Ref> |
| Sample Count (TCB Wait) | <TCBWait>n</TCBWait> |
| Sample Count (Total) | <Total>n</Total> |
| Percentage | <Percentage>n%</Percentage> |
| Variance | <Variance>variance</Variance> |
| | </WaitSamplesVariance> |
| Percentage of Queued Samples | <QueuedSamplesVariance> |
| Ref | <Ref>n</Ref> |

| Field title in online report | XML element |
|------------------------------|-------------------------------|
| Sample Count (Queued) | <Queued>n</Queued> |
| Sample Count (Total) | <Total>n</Total> |
| Percentage | <Percentage>n%</Percentage> |
| Variance | <Variance>variance</Variance> |
| | </QueuedSamplesVariance> |

CICS Performance analysis reports

E01 CICS Session Statistics

| Field title in online report | XML element |
|----------------------------------|--|
| | <CICSSummary> |
| CICS Release | <CICSRelease>CICS Release</CICSRelease> |
| First Transaction TaskId | <FirstTaskId>n</FirstTaskId> |
| Last Transaction TaskId | <LastTaskId>n</LastTaskId> |
| Number of TaskId Increments | <TaskIdIncrements>n</TaskIdIncrements> |
| Number of Observed Transactions | <ObservedTransactions>n</ObservedTransactions> |
| Transaction Rate (per sec) | <TransactionRate>n</TransactionRate> |
| Peak Active Txns (Observed) | <PeakActiveTransactionsObserved>n</PeakActiveTransactionsObserved> |
| Peak Active Txns (Overall) | <PeakActiveTransactionsOverall>n</PeakActiveTransactionsOverall> |
| Max Task <MaxTask>n</MaxTask> | Execution Time <ExecutionTime>n</ExecutionTime> |
| Suspend Time | <SuspendTime>n</SuspendTime> |
| CICS Dispatch Delay Time | <CICSDispatchDelayTime>n</CICSDispatchDelayTime> |
| MVS Dispatch Delay Time | <MVSDispatchDelayTime>n</MVSDispatchDelayTime> |
| Service Time | <ServiceTime>n</ServiceTime> |
| Program Requests | <ProgramRequests>n</ProgramRequests> |
| Terminal Messages | <TerminalMessages>n</TerminalMessages> |
| Storage Getmains | <StorageGetmains>n</StorageGetmains> |
| Storage Freemains | <StorageFreemains>n</StorageFreemains> |
| File I/O Requests | <FileIORequests>n</FileIORequests> |
| Temporary Storage Requests | <TemporaryStorageRequests>n</TemporaryStorageRequests> |
| Transient Data Requests | <TransientDataRequests>n</TransientDataRequests> |
| Journal Write Requests | <JournalWriteRequests>n</JournalWriteRequests> |

| Field title in online report | XML element |
|------------------------------|--|
| System Dumps | <SystemDumps>n</SystemDumps> |
| System Dumps Suppressed | <SystemDumpsSuppressed>n</SystemDumpsSuppressed> |
| Transaction Dumps | <TransactionDumps>n</TransactionDumps> |
| Transaction Dumps Suppressed | <TransactionDumpsSuppressed>n</TransactionDumpsSuppressed> |
| Storage Violations | <StorageViolations>n</StorageViolations> |
| Short on Storage occurrences | <ShortOnStorageOccurrences>n</ShortOnStorageOccurrences> |
| Times at MaxTask | <TimesAtMaxTask>n</TimesAtMaxTask> |
| Times at Class MaxTask | <TimesAtClassMaxTask>n</TimesAtClassMaxTask> |
| | <TransactionCounts> |
| TranId | <TransactionId>tranid</TransactionId> |
| Count | <TransactionCount>n</TransactionCount> |
| | </TransactionCounts> |
| | </CICSSummary> |

E02 CICS CPU and Use Counts by Pgm

| Field title in online report | XML element |
|---------------------------------|--------------------------------|
| | <DetailLine> |
| Name | <Name>name</Name> |
| Calls | <Description>n</Description> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </DetailLine> |

E03 CICS CPU Usage by Transaction

The XML elements presented below may be repeated multiple times and appear under different parent elements. In the XML document, all elements are listed in hierarchical order as they appear in the online report

| Field title in online report | XML element |
|---------------------------------|--|
| | <CICSTranId> |
| Name | <TransactionId>tranid</TransactionId> |
| NTxns/Description | <CICSTxnCount>n</CICSTxnCount> |
| | <Description>description</Description> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |

| Field title in online report | XML element |
|---------------------------------|--|
| | </CICSTranId> |
| | <CICSProgram> |
| Name | <Program>name</Program> |
| NTxns/Description | <Description>description</Description> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </CICSProgram> |
| | <CICSCommand> |
| Name | <CSECT>name</CSECT> |
| NTxns/Description | <Offset>offset</Offset> |
| NTxns/Description | <Command>command</Command> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </CICSCommand> |
| | <CICSService> |
| Name | <Program>name</Program> |
| NTxns/Description | <Description>description</Description> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </CICSService> |
| | <CICSSQL> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| NTxns/Description | <SQLVerb>verb</SQLVerb> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </CICSSQL> |
| | <CICSDLI> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| NTxns/Description | <DLIRequest>dlirequest</DLIRequest> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </CICSDLI> |
| | <ADABASCommand> |
| | <CSECT>name</CSECT> |

| Field title in online report | XML element |
|---------------------------------|------------------------------|
| Name | <Offset>offset</Offset> |
| NTxns/Description | <Command>command</Command> |
| | <Measurement>n</Measurement> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </ADABASCommand> |

E04 CICS Mean Service Time by Txn

The XML elements presented below may be repeated multiple times and appear under different parent elements. In the XML document, all elements are listed in hierarchical order as they appear in the online report.

| Field title in online report | XML element |
|------------------------------|--|
| | <CICSTranId> |
| Name | <TransactionId>transid</TransactionId> |
| NTxns | <CICSTxnCount>n</CICSTxnCount> |
| Description | <Description></Description> |
| Error | <MarginofError>n%</MarginofErrors> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSTranId> |
| | <CICSProgram> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSProgram> |
| | <CICSCommand> |
| Name | <CSECT>name</CSECT> |
| Description | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSCommand> |

| Field title in online report | XML element |
|------------------------------|--|
| | <CICSWait> |
| Name | <WaitReason>reason</WaitReason> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSWait> |
| | <CICSService> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSService> |
| | <CICSSQL> |
| | <CSECT>name</CSECT> |
| Name | <SQL>offset</SQL> |
| Description | <Description>sqlverb</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSSQL> |
| | <CICSDLI> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <DLIRequest>dlirequest</DLIRequest> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSDLI> |
| | <ADABASCommand> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |

| Field title in online report | XML element |
|------------------------------|------------------------------|
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </ADABASCommand> |

E05 CICS Total Service Time by Txn

The XML elements presented below may be repeated multiple times and appear under different parent elements. In the XML document, all elements are listed in hierarchical order as they appear in the online report.

| Field title in online report | XML element |
|------------------------------|--|
| | <CICSTranId> |
| Name | <TransactionId>tranid</TransactionId> |
| NTxns | <CICSTxnCount>n</CICSTxnCount> |
| Description | <Description></Description> |
| Error | <MarginofError>n%</MarginofErrors> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSTranId> |
| | <CICSProgram> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSProgram> |
| | <CICSCommand> |
| Name | <CSECT>name</CSECT> |
| Description | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSCommand> |
| | <CICSWait> |
| Name | <WaitReason>reason</WaitReason> |
| Description | <Description>description</Description> |

| Field title in online report | XML element |
|------------------------------|--|
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSWait> |
| | <CICSService> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSService> |
| | <CICSSQL> |
| | <CSECT>name</CSECT> |
| Name | <SQL>offset</SQL> |
| Description | <Description>sqlverb</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSSQL> |
| | <CICSDLI> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <DLIRequest>dlirequest</DLIRequest> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSDLI> |
| | <ADABASCommand> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </ADABASCommand> |

E06 CICS Total Service Time by Task ID

The XML elements presented below may be repeated multiple times and appear under different parent elements. In the XML document, all elements are listed in hierarchical order as they appear in the online report.

| Field title in online report | XML element |
|------------------------------|---|
| | <CICSTranId> |
| Name | <TransactionId> <i>transid</i> </TransactionId> |
| NTxns | <CICSTxnCount> <i>n</i> </CICSTxnCount> |
| Description | <Description></Description> |
| Error | <MarginofError> <i>n%</i> </MarginofErrors> |
| Execution | <ExecTime> <i>n</i> </ExecTime> |
| Suspend | <SuspendTime> <i>n</i> </SuspendTime> |
| Delay | <DelayTime> <i>n</i> </DelayTime> |
| Service | <ServiceTime> <i>n</i> </ServiceTime> |
| | </CICSTranId> |
| | <CICSTaskId> |
| Name | <TaskId> <i>tasknumber</i> </TaskId> |
| Description | <Description> <i>description</i> </Description> |
| Execution | <ExecTime> <i>n</i> </ExecTime> |
| Suspend | <SuspendTime> <i>n</i> </SuspendTime> |
| Delay | <DelayTime> <i>n</i> </DelayTime> |
| Service | <ServiceTime> <i>n</i> </ServiceTime> |
| | </CICSTaskId> |
| | <CICSProgram> |
| Name | <Program> <i>name</i> </Program> |
| Description | <Description> <i>description</i> </Description> |
| Execution | <ExecTime> <i>n</i> </ExecTime> |
| Suspend | <SuspendTime> <i>n</i> </SuspendTime> |
| Delay | <DelayTime> <i>n</i> </DelayTime> |
| Service | <ServiceTime> <i>n</i> </ServiceTime> |
| | </CICSProgram> |
| | <CICSCommand> |
| Name | <CSECT> <i>name</i> </CSECT> |
| Description | <Offset> <i>offset</i> </Offset> |
| Description | <Command> <i>command</i> </Command> |
| Execution | <ExecTime> <i>n</i> </ExecTime> |
| Suspend | <SuspendTime> <i>n</i> </SuspendTime> |
| Delay | <DelayTime> <i>n</i> </DelayTime> |
| Service | <ServiceTime> <i>n</i> </ServiceTime> |
| | </CICSCommand> |
| | <CICSWait> |

| Field title in online report | XML element |
|------------------------------|--|
| Name | <WaitReason>reason</WaitReason> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSWait> |
| | <CICSService> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSService> |
| | <CICSSQL> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <SQLVerb>sqlverb</SQLVerb> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSSQL> |
| | <CICSDLI> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <DLIRequest>dlirequest</DLIRequest> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSDLI> |
| | <ADABASCommand> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |

| Field title in online report | XML element |
|------------------------------|------------------------------|
| Service | <ServiceTime>n</ServiceTime> |
| | </ADABASCommand> |

E07 CICS Wait by Txn

| Field title in online report | XML element |
|----------------------------------|--|
| | <CICSTranId> |
| Name | <TransactionId>tranid</TransactionId> |
| NTxns/Description | <CICSTxnCount>n</CICSTxnCount> |
| | <Description></Description> |
| | <Measurements>n</Measurements> |
| Percent of Wait Time * 10.00% | <Percent>n</Percent> |
| | <CICSWait> |
| Name | <WaitReason>reason</WaitReason> |
| NTxns/Description | <Description>description</Description> |
| | <Measurements>n</Measurements> |
| Percent of Wait Time * 10.00% | <Percent>n</Percent> |
| | </CICSWait> |
| | </CICSTranId> |

E08 CICS Mean Service Time by Termid

The XML elements presented below may be repeated multiple times and appear under different parent elements. In the XML document, all elements are listed in hierarchical order as they appear in the online report.

| Field title in online report | XML element |
|------------------------------|---------------------------------------|
| | <CICSTerminal> |
| Name | <TerminalId>termid</TerminalId> |
| NTxns | <CICSTxnCount>n</CICSTxnCount> |
| Description | <Description></Description> |
| Error | <MarginofError>n%</MarginofErrors> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSTerminal> |
| | <CICSTranId> |
| Name | <TransactionId>tranid</TransactionId> |

| Field title in online report | XML element |
|------------------------------|--|
| NTxns | <CICSTxnCount>n</CICSTxnCount> |
| Description | <Description></Description> |
| Error | <MarginofError>n%</MarginofErrors> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSTranId> |
| | <CICSProgram> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSProgram> |
| | <CICSCCommand> |
| Name | <CSECT>name</CSECT> |
| Description | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSCCommand> |
| | <CICSWait> |
| Name | <WaitReason>reason</WaitReason> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSWait> |
| | <CICSService> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |

| Field title in online report | XML element |
|------------------------------|-------------------------------------|
| | </CICSService> |
| | <CICSSQL> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <SQLVerb>sqlverb</SQLVerb> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSSQL> |
| | <CICSDLI> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <DLIRequest>dlirequest</DLIRequest> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSDLI> |
| | <ADABASCommand> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </ADABASCommand> |

E09 CICS Total Service Time by Termid

The XML elements presented below may be repeated multiple times and appear under different parent elements. In the XML document, all elements are listed in hierarchical order as they appear in the online report.

| Field title in online report | XML element |
|------------------------------|------------------------------------|
| | <CICSTerminal> |
| Name | <TerminalId>termid</TerminalId> |
| NTxns | <CICSTxnCount>n</CICSTxnCount> |
| Description | <Description></Description> |
| Error | <MarginofError>n%</MarginofErrors> |

| Field title in online report | XML element |
|------------------------------|--|
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSTerminal> |
| | <CICSTranId> |
| Name | <TransactionId>trandid</TransactionId> |
| NTxns | <CICSTxnCount>n</CICSTxnCount> |
| Description | <Description></Description> |
| Error | <MarginofError>n%</MarginofErrors> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSTranId> |
| | <CICSProgram> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSProgram> |
| | <CICSCommand> |
| Name | <CSECT>name</CSECT> |
| Description | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSCommand> |
| | <CICSWait> |
| Name | <WaitReason>reason</WaitReason> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSWait> |

| Field title in online report | XML element |
|------------------------------|--|
| | <CICSService> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSService> |
| | <CICSSQL> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <SQLVerb>sqlverb</SQLVerb> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSSQL> |
| | <CICSDLI> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <DLIRequest>dlirequest</DLIRequest> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSDLI> |
| | <ADABASCommand> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </ADABASCommand> |

E10 CICS Mean Service Time by User ID

The XML elements presented below may be repeated multiple times and appear under different parent elements. In the XML document, all elements are listed in hierarchical order as they appear in the online report.

| Field title in online report | XML element |
|------------------------------|--|
| | <CICSUserid> |
| Name | <Userid>userid</Userid> |
| NTxns | <CICSTxnCount>n</CICSTxnCount> |
| Description | <Description></Description> |
| Error | <MarginofError>n%</MarginofErrors> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSUserid> |
| | <CICSTranId> |
| Name | <TransactionId>tranid</TransactionId> |
| NTxns | <CICSTxnCount>n</CICSTxnCount> |
| Description | <Description></Description> |
| Error | <MarginofError>n%</MarginofErrors> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSTranId> |
| | <CICSProgram> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSProgram> |
| | <CICSCommand> |
| Name | <CSECT>name</CSECT> |
| Description | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSCommand> |
| | <CICSWait> |
| Name | <WaitReason>reason</WaitReason> |
| Description | <Description>description</Description> |

| Field title in online report | XML element |
|------------------------------|--|
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSWait> |
| | <CICSService> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSService> |
| | <CICSSQL> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <SQLVerb>sqlverb</SQLVerb> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSSQL> |
| | <CICSDLI> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <DLIRequest>dlirequest</DLIRequest> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSDLI> |
| | <ADABASCommand> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </ADABASCommand> |

E11 CICS Total Service Time by User ID

The XML elements presented below may be repeated multiple times and appear under different parent elements. In the XML document, all elements are listed in hierarchical order as they appear in the online report.

| Field title in online report | XML element |
|------------------------------|--|
| | <CICSUserid> |
| Name | <Userid>userid</Userid> |
| NTxns | <CICSTxnCount>n</CICSTxnCount> |
| Description | <Description></Description> |
| Error | <MarginofError>n%</MarginofErrors> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSUserid> |
| | <CICSTranId> |
| Name | <TransactionId>transid</TransactionId> |
| NTxns | <CICSTxnCount>n</CICSTxnCount> |
| Description | <Description></Description> |
| Error | <MarginofError>n%</MarginofErrors> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSTranId> |
| | <CICSProgram> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSProgram> |
| | <CICSCommand> |
| Name | <CSECT>name</CSECT> |
| Description | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |

| Field title in online report | XML element |
|------------------------------|--|
| | </CICSCommand> |
| | <CICSWait> |
| Name | <WaitReason>reason</WaitReason> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSWait> |
| | <CICSService> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSService> |
| | <CICSSQL> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <SQLVerb>sqlverb</SQLVerb> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSSQL> |
| | <CICSDLI> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <DLIRequest>dlirequest</DLIRequest> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSDLI> |
| | <ADABASCommand> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |

| Field title in online report | XML element |
|------------------------------|------------------------------|
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </ADABASCommand> |

E12 CICS CPU/Service Time by Transaction

| Field title in online report | XML element |
|------------------------------|--|
| | <CPUTimeByTransaction> |
| Name | <Transaction>name</Transaction> |
| NTxns | <NumberOfTxns>n</NumberOfTxns> |
| % of CPU | <PctCPUTime>n%</PctCPUTime> |
| --CPU Time -- Total | <TotalCPUTime>n</TotalCPUTime> |
| --CPU Time-- Mean | <MeanCPUTime>n</MeanCPUTime> |
| --Svc Time-- Total | <TotalServiceTime>n</TotalServiceTime> |
| --Svc Time-- Mean | <MeanServiceTime>n</MeanServiceTime> |
| | <CPUTimeByTransactionDetail> |
| Name | <TaskNumber>n</TaskNumber> |
| Description | <StartTime>hh.mm.ss.ss</StartTime> |
| --CPU Time -- Total | <TotalCPUTime>n</TotalCPUTime> |
| --CPU Time-- Mean | <MeanCPUTime>n</MeanCPUTime> |
| --Svc Time-- Total | <TotalServiceTime>n</TotalServiceTime> |
| --Svc Time-- Mean | <MeanServiceTime>n</MeanServiceTime> |
| | </CPUTimeByTransactionDetail> |
| | </CPUTimeByTransaction> |

X01 CICS Mean Service Time by Txn

This report is generated for multiple CICS address space reporting.

The XML elements presented below can be repeated multiple times and occur under different parent elements. In the XML document, all elements are listed in hierarchical order as they are displayed in the online report.

| Field title in online report | XML element |
|------------------------------|---------------------------------------|
| | <CICSTranId> |
| Name | <TransactionId>tranid</TransactionId> |
| NTxns | <CICSTxnCount>n</CICSTxnCount> |
| Description | <Description></Description> |
| Error | <MarginofError>n%</MarginofErrors> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |

| Field title in online report | XML element |
|------------------------------|---|
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSTranId> |
| | <CICSAppId> |
| Name | <AppId>name</AppId> |
| Description | <Description>Region AppId</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSAppId> |
| | <CICSProgram> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSProgram> |
| | <CICSCommand> |
| Name | <CSECT>name</CSECT> |
| Description | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSCommand> |
| | <CICSWait> |
| Name | <WaitReason>reason</WaitReason> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSWait> |
| | <CICSService> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |

| Field title in online report | XML element |
|------------------------------|-------------------------------------|
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSService> |
| | <CICSSQL> |
| | <CSECT>name</CSECT> |
| Name | <SQL>offset</SQL> |
| Description | <Description>sqlverb</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSSQL> |
| | <CICSDLI> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <DLIRequest>dlirequest</DLIRequest> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSDLI> |
| | <ADABASCommand> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </ADABASCommand> |

X02 CICS Total Service Time by Txn

This report is generated for multiple CICS address space reporting.

The XML elements presented below can be repeated multiple times and occur under different parent elements. In the XML document, all elements are listed in hierarchical order as they are displayed in the online report.

| Field title in online report | XML element |
|------------------------------|--|
| | <CICSTranId> |
| Name | <TransactionId>transid</TransactionId> |
| NTxns | <CICSTxnCount>n</CICSTxnCount> |

| Field title in online report | XML element |
|--------------------------------------|---|
| Description | <Description></Description> |
| Error | <MarginofError>n%</MarginofErrors> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSTranId> |
| | <CICSAppId> |
| Name | <AppId>name</AppId> |
| Description | <Description>Region AppId</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSAppId> |
| | <CICSProgram> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSProgram> |
| | <CICSCommand> |
| Name | <CSECT>name</CSECT> |
| Description | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSCommand> |
| | <CICSWait> |
| Name | <WaitReason>reason</WaitReason> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service <ServiceTime>n</ServiceTime> | |
| | </CICSWait> |
| | <CICSService> |

| Field title in online report | XML element |
|------------------------------|--|
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSService> |
| | <CICSSQL> |
| | <CSECT>name</CSECT> |
| Name | <SQL>offset</SQL> |
| Description | <Description>sqlverb</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSSQL> |
| | <CICSDLI> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <DLIRequest>dlirequest</DLIRequest> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSDLI> |
| | <ADABASCommand> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </ADABASCommand> |

X03 CICS Mean Service Time by Term

This report is generated for multiple CICS address space reporting.

The XML elements presented below can be repeated multiple times and occur under different parent elements. In the XML document, all elements are listed in hierarchical order as they are displayed in the online report.

| Field title in online report | XML element |
|------------------------------|---|
| | <CICSTerminal> |
| Name | <TerminalId>termid</TerminalId> |
| NTxns | <CICSTxnCount>n</CICSTxnCount> |
| Description | <Description></Description> |
| Error | <MarginofError>n%</MarginofErrors> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSTerminal> |
| | <CICSTranId> |
| Name | <TransactionId>transid</TransactionId> |
| NTxns | <CICSTxnCount>n</CICSTxnCount> |
| Description | <Description></Description> |
| Error | <MarginofError>n%</MarginofErrors> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSTranId> |
| | <CICSAplid> |
| Name | <Aplid>name</Aplid> |
| Description | <Description>Region Aplid</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSAplid> |
| | <CICSProgram> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSProgram> |
| | <CICSCCommand> |
| Name | <CSECT>name</CSECT> |
| Description | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |

| Field title in online report | XML element |
|------------------------------|--|
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSCommand> |
| | <CICSWait> |
| Name | <WaitReason>reason</WaitReason> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSWait> |
| | <CICSService> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSService> |
| | <CICSSQL> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <SQLVerb>sqlverb</SQLVerb> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSSQL> |
| | <CICSDLI> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <DLIRequest>dlirequest</DLIRequest> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSDLI> |
| | <ADABASCommand> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |

| Field title in online report | XML element |
|------------------------------|------------------------------|
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </ADABASCommand> |

X04 CICS Total Service Time by Term

This report is generated for multiple CICS address space reporting.

The XML elements presented below can be repeated multiple times and occur under different parent elements. In the XML document, all elements are listed in hierarchical order as they are displayed in the online report.

Table 28.

| Field title in online report | XML element |
|------------------------------|---|
| | <CICSTerminal> |
| Name | <TerminalId>termid</TerminalId> |
| NTxns | <CICSTxnCount>n</CICSTxnCount> |
| Description | <Description></Description> |
| Error | <MarginofError>n%</MarginofErrors> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSTerminal> |
| | <CICSTranId> |
| Name | <TransactionId>transid</TransactionId> |
| NTxns | <CICSTxnCount>n</CICSTxnCount> |
| Description | <Description></Description> |
| Error | <MarginofError>n%</MarginofErrors> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSTranId> |
| | <CICSAppId> |
| Name | <AppId>name</AppId> |
| Description | <Description>Region AppId</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |

Table 28. (continued)

| Field title in online report | XML element |
|------------------------------|--|
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSAppid> |
| | <CICSProgram> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSProgram> |
| | <CICSCommand> |
| Name | <CSECT>name</CSECT> |
| Description | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSCommand> |
| | <CICSWait> |
| Name | <WaitReason>reason</WaitReason> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSWait> |
| | <CICSService> |
| Name | <Program>name</Program> |
| Description | <Description>description</Description> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSService> |
| | <CICSSQL> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <SQLVerb>sqlverb</SQLVerb> |
| Execution | <ExecTime>n</ExecTime> |

Table 28. (continued)

| Field title in online report | XML element |
|------------------------------|-------------------------------------|
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSSQL> |
| | <CICSDLI> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <DLIRequest>dlirequest</DLIRequest> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </CICSDLI> |
| | <ADABASCommand> |
| | <CSECT>name</CSECT> |
| Name | <Offset>offset</Offset> |
| Description | <Command>command</Command> |
| Execution | <ExecTime>n</ExecTime> |
| Suspend | <SuspendTime>n</SuspendTime> |
| Delay | <DelayTime>n</DelayTime> |
| Service | <ServiceTime>n</ServiceTime> |
| | </ADABASCommand> |

IMS Performance analysis reports

I01 IMS Measurement Profile

| Field title in online report | XML element |
|------------------------------|--|
| IMS Environment | <IMSEnvironment> |
| DFSRRRC00 parms | <DFSRRRC00Parms>parms</DFSRRRC00Parms> |
| IMS system id | <SystemId>systemid</SystemId> |
| IMS region name | <RegionName>name</RegionName> |
| IMS version | <Version>version</Version> |
| IMS region type | <RegionType>regiontype</RegionType> |
| | </IMSEnvironment> |
| Most Active IMS PSBs | <MostActiveIMSPSBs> |
| Samples | <Samples>n</Samples> |
| | <Percent>n%</Percent> |
| Reports | <Reports>I05 I08 I11</Reports> |

| Field title in online report | XML element |
|------------------------------|---|
| | <ActiveIMSPSBs> |
| | <PSBName>name</PSBName> |
| | <CPUActive>n</CPUActive> |
| | <CPUActivePercent>n%</CPUActivePercent> |
| | </ActiveIMSPSBs> |
| | </MostActiveIMSPSBs> |
| Most Active IMS Transactions | <MostActiveIMSTransactions> |
| Samples | <Samples>n</Samples> |
| | <Percent>n%</Percent> |
| Reports | <Reports>I04 I06 I09 I12</Reports> |
| | <ActiveIMSTransactions> |
| | <TransactionId>transid</TransactionId> |
| | <CPUActive>n</CPUActive> |
| | <CPUActivePercent>n%</CPUActivePercent> |
| | </ActiveIMSTransactions> |
| | </MostActiveIMSTransactions> |
| Most Active IMS DLI Calls | <MostActiveIMSDLICalls> |
| Samples | <Samples>n</Samples> |
| | <Percent>n%</Percent> |
| Reports | <Reports>I07 I10 I13</Reports> |
| | <ActiveIMSDLICalls> |
| | <IMSCall>imscall</IMSCall> |
| | <CPUActive>n</CPUActive> |
| | <CPUActivePercent>n%</CPUActivePercent> |
| | </ActiveIMSDLICalls> |
| | </MostActiveIMSDLICalls> |
| Most CPU consumptive DLI | <MostCPUConsumptiveDLI> |
| Total DLI CPU time | <CPUTime>n</CPUTime> |
| | <Percent>n%</Percent> |
| Reports | <Reports>I18 I19 I20 I21</Reports> |
| | <CPUConsumptiveDLI> |
| | <IMSCall>imscall</IMSCall> |
| | <CPUTime>n</CPUTime> |
| | <CPUTimePercent>n%</CPUTimePercent> |
| | </CPUConsumptiveDLI> |
| | </MostCPUConsumptiveDLI> |
| Most Frequent Transactions | <MostFrequentTransactions> |

| Field title in online report | XML element |
|------------------------------|--|
| Total txns counted | <Transactions>n</Transactions> |
| | <Percent>n%</Percent> |
| Reports | <Reports>I03 I04 I16 I17</Reports> |
| | <FrequentTransactions> |
| | <TransactionId>trandid</TransactionId> |
| | <TransactionsCounted>n</TransactionsCounted> |
| | <PercentOfTransactions>n%</PercentOfTransactions> |
| | </FrequentTransactions> |
| | </MostFrequentTransactions> |
| Most Frequent DL/I Calls | <MostFrequentDLICalls> |
| Total DLI call count | <Samples>n</Samples> |
| | <Percent>n%</Percent> |
| | Reports <Reports>I02 I17 I18</Reports> |
| | <FrequentDLICalls> |
| | <IMSCall>imscall</IMSCall> |
| | <Samples>n</Samples> |
| | <Percent>n%</Percent> |
| | </FrequentDLICalls> |
| | </MostFrequentDLICalls> |
| Transaction Statistics | <TransactionStatistics> |
| IMS Txns counted | <TransactionsCounted>n</TransactionsCounted> |
| Transaction rate | <TransactionRate>n per sec</TransactionRate> |
| Txn observations | <TransactionObservations>n</TransactionObservations> |
| Txn throughput | <TransactionThroughput>n per sec</TransactionThroughput> |
| IMS Txn svc time | <TransactionServiceTime>n sec</TransactionServiceTime> |
| IMS Txn CPU time | <TransactionCPUTime>n sec</TransactionCPUTime> |
| IMS txn max svc | <TransactionMaximumService>nssec</TransactionMaximumService> |
| IMS Txn max CPU | <TransactionMaximumCPU>n sec</TransactionMaximumCPU> |
| IMS Txn min svc | <TransactionMinimumService>n sec</TransactionMinimumService> |
| IMS Txn min CPU | <TransactionMinimumCPU>n sec</TransactionMinimumCPU> |
| | </TransactionStatistics> |

102 IMS DL/I Call Timeline

The DLICallTimeline tag pair and sub-elements are repeated for each DLI call.

| Field title in online report | XML element |
|------------------------------|----------------------|
| | <DLICallTimeline> |
| CallSeq | <CallSeq>n</CallSeq> |

| Field title in online report | XML element |
|------------------------------|----------------------------------|
| Func | <Function>function</Function> |
| PCB Name | <PCBName>name</PCBName> |
| Id | <Id>n</Id> |
| Location | <Location>location</Location> |
| Stat | <Status>status</Status> |
| Call Time | <CallTime>hh:mm:ss.ss</CallTime> |
| Duration | <Duration>n</Duration> |
| | </DLICallTimeline> |

I03 IMS Transaction Timeline

The IMSTransactionTimeLine tag pair and sub-elements are repeated for each IMS transaction.

| Field title in online report | XML element |
|------------------------------|--|
| | <IMSTransactionTimeLine> |
| TranCode | <TransactionCode>tranid</TransactionCode> |
| PSB/PCB | <PSBName>name</PSBName> |
| Location | <LTERM>lterm</LTERM> |
| Txn Time | <TransactionTime>hh:mm:ss.ss</TransactionTime> |
| Duration | <Duration>n</Duration> |
| | <DLICallTimeLine> |
| TranCode | <CallSeq>n</CallSeq> |
| PSB/PCB | <PCBName>name</PCBName> |
| Id | <Id>n</Id> Func |
| | <Function>function</Function> |
| Location | <Location>location</Location> |
| Stat | <Status>status</Status> |
| Txn Time | <CallTime>hh:mm:ss.ss</CallTime> |
| Duration | <Duration>n</Duration> |
| | </DLICallTimeline> |
| | </IMSTransactionTimeLine> |

I04 IMS Transaction Activity Timeline

| Field title in online report | XML element |
|------------------------------|----------------------------------|
| | <IMSTransactionActivityTimeLine> |
| TranCode | <Samples>n</Samples> |
| PSB/PCB | <Duration>n</Duration> |
| Location | <Txn>tranid</Txn> |

| Field title in online report | XML element |
|------------------------------|--|
| Txn Time | <TransactionTime>hh:mm:ss.ss</TransactionTime> |
| Duration | <PSB>name</PSB> |
| | <Txns>n</Txns> |
| | <Intervals> |
| | <IntervalCount>n</IntervalCount> Repeated 50 times |
| | </Interval> |
| | </IMSTransactionActivityTimeLine> |

I05 to I13

This section describes the common tag pairs and elements of the XML detail lines shared by reports I05 through I13. The same information is categorized and displayed differently in each report. The report names covered by the following XML are:

- I05 IMS CPU Usage by PSB
- I06 IMS CPU Usage by Txn
- I07 IMS CPU Usage by DL/I Call
- I08 IMS WAIT Time by PSB
- I09 IMS WAIT Time by Txn
- I10 IMS WAIT Time by DL/I Call
- I11 IMS DL/I Activity by PSB
- I12 IMS DL/I Activity by Txn
- I13 IMS DL/I Activity by DL/I Call

The XML elements presented below may be repeated multiple times and appear under different parent elements. In the XML document, all elements are listed in hierarchical order as they appear in the online report.

| Field title in online report | XML element |
|---------------------------------|---|
| | <Category> |
| Name | <CategoryName>name</CategoryName> |
| Description | <CategoryDescription>description</CategoryDescription > |
| | <Measurements>n</Measurements> |
| Percent of xxx Time * 10.00% | <Percent>n</Percent> |
| | </Category> |
| | <CSECT> |
| Name | <CSECTName>name</CSECTName> |
| Description | <CSECTDescription>description</CSECTDescription> |
| | <Measurements>n</Measurements> |
| Percent of xxx Time * 10.00% | <Percent>n</Percent> |
| | </CSECT> |
| | <DLICall> |

| Field title in online report | XML element |
|---------------------------------|---|
| Name | <SequenceNumber>n</SequenceNumber> |
| Description | <FunctionPCBProgramOffset>FuncNameNameOffset</FunctionPCBProgramOffset> |
| | <Measurements>n</Measurements> |
| Percent of xxx Time * 10.00% | <Percent>n</Percent> |
| | </DLICall> |
| | <DMRequest> |
| Name | <MacroName>name</MacroName> |
| Description | <MacroLocation>location</MacroLocation> |
| | <Measurements>n</Measurements> |
| Percent of xxx Time * 10.00% | <Percent>n</Percent> |
| | </DMRequest> |
| | <DPAGroup> |
| Name | <DPAGroupName>name</DPAGroupName> |
| Description | <DPAGroupDescription>description</DPAGroupDescription> |
| | <Measurements>n</Measurements> |
| Percent of xxx Time * 10.00% | <Percent>n</Percent> |
| | </DPAGroup> |
| | <File> |
| Name | <DDName>ddname</DDName> |
| Description | <AccessMethod>accessmethod</AccessMethod> |
| | <Measurements>n</Measurements> |
| Percent of xxxTime * 10.00% | <Percent>n</Percent> |
| | </File> |
| | <LoadModule> |
| Name | <LoadModuleName>name</LoadModuleName> |
| Description | <LoadModuleDescription>description</LoadModuleDescription> |
| | <Measurements>n</Measurements> |
| Percent of xxx Time * 10.00% | <Percent>n</Percent> |
| | </LoadModule> |
| | <NoSymAddressRange> |
| Name | <AddressRange>address</AddressRange> |
| Description | <AddressRangeDescription>Unresolved Address</AddressRangeDescription> |
| | <Measurements>n</Measurements> |
| Percent of xxx Time * 10.00% | <Percent>n</Percent> |

| Field title in online report | XML element |
|---------------------------------|---|
| | </NoSymAddressRange> |
| | <PSB> |
| Name | <PSBName>name</PSBName> |
| Description | <Description>description</Description> |
| | <Measurements>n</Measurements> |
| Percent of xxx Time * 10.00% | <Percent>n</Percent> |
| | </PSB> |
| | <SQLRequest> |
| Name | <SequenceNumber>n</SequenceNumber> |
| Description | <ProgramStatementFunction>name(stmt)function</ProgramStatementFunction> |
| | <Measurements>n</Measurements> |
| Percent of xxx Time * 10.00% | <Percent>n</Percent> |
| | </SQLRequest> |
| | <SVCRoutine> |
| Name | <SVCId>svcid</SVCId> |
| Description | <SVCDescription>description</SVCDescription> |
| | <Measurements>n</Measurements> |
| Percent of xxx Time * 10.00% | <Percent>n</Percent> |
| | </SVCRoutine> |

I14 IMS PSB/PCB Attributes

| Field title in online report | XML element |
|------------------------------|--|
| | <IMSPSBAttributes> |
| PSB name | <PSBName>name</PSBName> |
| IMS system | <IMSSystem>imssystem</IMSSystem> |
| No.of PCBs | <NumberOfPCBs>n</NumberOfPCBs> |
| LIST=NO PCBs | <LISTNOPCBs>n</LISTNOPCBs> |
| Txn count | <TransactionCount>n</TransactionCount> |
| DL/I calls | <DLICalls>n</DLICalls> |
| Sample count | <SampleCount>n</SampleCount> |
| | <IMSPCBs> |
| PCBNum | <PCBNumber>n</PCBNumber> |
| Name | <PCBName>name</PCBName> |
| Type | <PCBType>type</PCBType> |
| DBD/LTRM | <DBDLterm>name</DBDLterm> |
| PROCOPT | <PROCOPT>procopt</PROCOPT> |

| Field title in online report | XML element |
|------------------------------|---------------------|
| LIST | <List>yesno</List> |
| | </IMSPCBs> |
| | </IMSPSBAttributes> |

I15 IMS DL/I Call Attributes

| Field title in online report | XML element |
|------------------------------|--|
| | <DLICallAttributes> |
| DL/I Call Id | <DLICallId>n</DLICallId> |
| Function code | <FunctionCode>code</FunctionCode> |
| PSB Name | <PSBName>name</PSBName> |
| PCB Naame | <PCBName>name</PCBName> |
| IMS Id-Region | <IMSIdRegion>imsid-region</IMSIdRegion> |
| PCB Number | <PCBNumber>n</PCBNumber> |
| Call type | <CallType>calltype</CallType> |
| CSECT/module | <CSECTModule>csect in module</CSECTModule> |
| Offset of call | <OffsetOfCall>n</OffsetOfCall> |
| Sample count | <SampleCount>n</SampleCount> |
| Call count | <CallCount>n</CallCount> |
| DLI CPU time | <DLICPUTime>n</DLICPUTime> |
| Service time | <ServiceTime>n</ServiceTime> |
| | <DLICall> |
| SSA/FSA | <SSANum>n</SSANum> |
| | <SSA>ssa</SSA> |
| | </DLICall> |
| | </DLICallAttributes> |

I16 IMS Transaction Service Times

| Field title in online report | XML element |
|------------------------------|--|
| | <IMSTransactionServiceTimes> |
| TranCode | <TransactionCode>tranid</TransactionCode> |
| PSB/PGM | <PSBProgram>name</PSBProgram> |
| Txns | <TransactionCount>n</TransactionCount> |
| Fetch | <FetchCount>n</FetchCount> |
| Sched | <ScheduleCount>n</ScheduleCount> |
| Total time | <TotalTime>n</TotalTime> |
| Avg/Txn | <AverageTimePerTransaction>n</AverageTimePerTransaction> |
| CPU Time | <CPUTime>n</CPUTime> |

| Field title in online report | XML element |
|------------------------------|-------------------------------|
| | </IMSTransactionServiceTimes> |

I17 IMS Transaction DL/I Call Counts

| Field title in online report | XML element |
|------------------------------|--|
| | <IMSTransactionDLICallCounts> |
| Tran/PCB | <TransactionCode> <i>tranid</i> </TransactionCode> |
| PSB/DBD | <PSBname> <i>name</i> </PSBname> |
| Total | <DLITotalCount> <i>n</i> </DLITotalCount> |
| Minimum | <DLIMinimumCount> <i>n</i> </DLIMinimumCount> |
| Maximum | <DLIMaximumCount> <i>n</i> </DLIMaximumCount> |
| Average | <DLIAverageCount> <i>n</i> </DLIAverageCount> |
| | <IMSTransactionDLICallCountsByPCB> |
| Tran/PCB | <PCBName> <i>name</i> </PCBName> |
| PSB/DBD | <DBDName> <i>name</i> </DBDName> |
| PCBNum | <PCBNumber> <i>n</i> </PCBNumber> |
| Func | <Function> <i>function</i> </Function> |
| Total | <DLITotalCount> <i>n</i> </DLITotalCount> |
| Minimum | <DLIMinimumCount> <i>n</i> </DLIMinimumCount> |
| Maximum | <DLIMaximumCount> <i>n</i> </DLIMaximumCount> |
| Average | <DLIAverageCount> <i>n</i> </DLIAverageCount> |
| | </IMSTransactionDLICallCountsByPCB> |
| | </IMSTransactionServiceTimes> |

I18 IMS CPU/Service Time by DL/I Call

| Field title in online report | XML element |
|------------------------------|--|
| | <IMSCPUTimeByCall> |
| Call | <CallNumber> <i>n</i> </CallNumber> |
| Func | <Function> <i>function</i> </Function> |
| PCB Name | <PCBName> <i>name</i> </PCBName> |
| Location | <Location> <i>location</i> </Location> |
| Count | <CallCount> <i>n</i> </CallCount> |
| Svc time | <DLIServiceTime> <i>n</i> </DLIServiceTime> |
| Prcnt | <DLIServicePercent> <i>n%</i> </DLIServicePercent> |
| CPU Time | <DLICPUTime> <i>n</i> </DLICPUTime> |
| Prcnt | <DLICPUPercent> <i>n%</i> </DLICPUPercent> |
| | </IMSCPUTimeByCall> |

I19 IMS CPU/Service Time by PSB

| Field title in online report | XML element |
|------------------------------|---|
| | <IMSCPUTimeByPSB> |
| PSB Name | <PSBName>name</PSBName> |
| Txn Count | <TransactionCount>n</TransactionCount> |
| DL/I Count | <CallCount>n</CallCount> |
| Svc time | <DLIServiceTime>n</DLIServiceTime> |
| Prcnt | <DLIServicePercent>n%</DLIServicePercent> |
| CPU Time | <DLICPUTime>n</DLICPUTime> |
| Prcnt | <DLICPUPercent>n%</DLICPUPercent> |
| | </IMSCPUTimeByPSB> |

I20 IMS CPU/Service Time by Transaction

| Field title in online report | XML element |
|------------------------------|--|
| | <IMSCPUTimeByTransaction> |
| TranCode | <TransactionCode>transid</TransactionCode> |
| Txn Count | <TransactionCount>n</TransactionCount> |
| Service | <TransactionServiceTime>n</TransactionServiceTime> |
| CPU Time | <TransactionCPUTime>n</TransactionCPUTime> |
| Svc time | <DLIServiceTime>n</DLIServiceTime> |
| %of Txn | <DLIServicePercent>n%</DLIServicePercent> |
| CPU Time | <DLICPUTime>n</DLICPUTime> |
| %of Txn | <DLICPUPercent>n%</DLICPUPercent> |
| | </IMSCPUTimeByTransaction> |

I21 IMS CPU/Service Time by PCB

| Field title in online report | XML element |
|------------------------------|---|
| | <IMSCPUTimeByPCB> |
| PSB Name | <PSBName>name</PSBName> |
| PCB Name | <PCBName>name</PCBName> |
| PCB Num | <PCBNumber>n</PCBNumber> |
| Count | <CallCount>n</CallCount> |
| Svc time | <DLIServiceTime>n</DLIServiceTime> |
| Percent | <DLIServicePercent>n%</DLIServicePercent> |
| CPU Time | <DLICPUTime>n</DLICPUTime> |
| Percent | <DLICPUPercent>n%</DLICPUPercent> |
| | </IMSCPUTimeByPCB> |

DB2 Performance analysis reports

F01 DB2 Measurement profile

| Field title in online report | XML element |
|------------------------------|---|
| Most Active DB2 Plans | <MostActiveDB2Plans> |
| Samples | <Samples>n</Samples> |
| | <Percent>n%</Percent> |
| Reports | <Reports>F05</Reports> |
| | <Plans> |
| | <PlanName>name</PlanName> |
| | <CPUActive>n</CPUActive> |
| | <CPUActivePercent>n%</CPUActivePercent> |
| | </Plans> |
| | </MostActiveDB2Plans> |
| Most Active Package/DBRM | <MostActiveDBRMs> |
| Samples | <Samples>n</Samples> |
| | <Percent>n%</Percent> |
| Reports | <Reports>F03</Reports> |
| | <DBRMs> |
| | <DBRM>name</DBRM> |
| | <CPUActive>n</CPUActive> |
| | <CPUActivePercent>n%</CPUActivePercent> |
| | </DBRMs> |
| | </MostActiveDBRMs> |
| Most Active SQL Statements | <MostActiveSQL> |
| Samples | <Samples>n</Samples> |
| | <Percent>n%</Percent> |
| Reports | <Reports>F04</Reports> |
| | <SQLStatement> |
| | <ProgramOffsetVerb>name:offset verb</ProgramOffsetVerb> |
| | <CPUActive>n</CPUActive> |
| | <CPUActivePercent>n%</CPUActivePercent> |
| | </SQLStatement> |
| | </MostActiveSQL> |
| Most CPU consumptive SQL | <MostCPUConsumptiveSQL> |
| Total SQL CPU time | <CPUTime>n</CPUTime> |
| | <Percent>n%</Percent> |
| Reports | <Reports>F10 F11 F12</Reports> |

| Field title in online report | XML element |
|------------------------------|---|
| | <SQLStatement> |
| | <ProgramOffsetVerb>name:offset verb</ProgramOffsetVerb> |
| | <CPUActive>n%</CPUActive> |
| | <CPUActivePercent>n%</CPUActivePercent> |
| | </SQLStatement> |
| | </MostCPUConsumptiveSQL> |
| Most Frequent SQL Statements | <MostFrequentSQL> |
| Total SQL call count | <Samples>n</Samples> |
| | <Percent>n%</Percent> |
| | <SQLStatement> |
| | <ProgramOffsetVerb>name:offset verb</ProgramOffsetVerb> |
| | <CPUActive>n%</CPUActive> |
| | <CPUActivePercent>n%</CPUActivePercent> |
| | </SQLStatement> |
| | </MostFrequentSQL> |
| Single SQL Call Service Time | <SingleSQLCallServiceTime> |
| Total SQL service count | <Samples>n</Samples> |
| | <Percent>n%</Percent> |
| | <SQLStatement> |
| | <ProgramOffsetVerb>name:offset verb</ProgramOffsetVerb> |
| | <CPUActive>n%</CPUActive> |
| | <CPUActivePercent>n%</CPUActivePercent> |
| | </SQLStatement> |
| | </SingleSQLCallServiceTime> |
| Db2 Measurement Statistics | <DB2MeasurementStatistics> |
| DB2 subsystem name | <SubsystemName>name</SubsystemName> |
| DB2 version | <Version>version</Version> |
| SQL calls sampled | <CallsSampled>n</CallsSampled> |
| SQL observations | <SQLObservations>n</SQLObservations> |
| SQL calls executed | <CallsExecuted>n</CallsExecuted> |
| Avg SQL call rate | <CallRate>n per sec</CallRate> |
| SQL calls counted | <CallsCounted>n</CallsCounted> |
| SQL throughput | <SQLThroughput>n per sec</SQLThroughput> |
| SQL service time | <ServiceTime>n sec</ServiceTime> |
| SQL CPU time | <CPUTime>n sec</CPUTime> |
| CQL call max time | <CallMaxTime>n sec</CallMaxTime> |
| SQL call max CPU | <CallMaxCPU>n sec</CallMaxCPU> |
| SQL call min time | <CallMinTime>n sec</CallMinTime> |

| Field title in online report | XML element |
|------------------------------|--------------------------------|
| SQL call min CPU | <CallMinCPU>n sec</CallMinCPU> |
| | </DB2MeasurementStatistics> |

F02 DB2 SQL Activity Timeline

The SQLActivityTimeline tag pair and sub-elements are repeated for each SQL call.

| Field title in online report | XML element |
|------------------------------|--|
| | <SQLActivityTimeline> |
| Thread | <Thread>n</Thread> |
| REQCT | <REQCT>n</REQCT> |
| Program | <Program>name</Program> |
| Stmt# | <StatementNumber>n</StatementNumber> |
| SQL Function | <SQLFunction>function</SQLFunction> |
| Samps | <Samples>n</Samples> |
| Call Time | <CallTime>hh:mm:ss.ss</CallTime> |
| Interval | <Interval>n</Interval> |
| CPU Time | <CPUTime>n</CPUTime> |
| | <SQLTextLines> |
| | <SQLTEXT>sqltext</SQLTEXT> |
| | <PrepareInfo> |
| | <PrepareStatementNumber>n</PrepareStatementNumber> |
| | <PrepareSequenceNumber>seqno</PrepareSequenceNumber> |
| | </PrepareInfo> |
| | </SQLTextLines> |
| | </SQLActivityTimeline> |

F03 SQL Activity by DBRM

| Field title in online report | XML element |
|------------------------------|--|
| | <DetailLine> |
| Name | <Name>name</Name> |
| | <Description></Description> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n %</Percent> |
| | <SQLRequest> |
| Name | <SequenceNumber>seqno</SequenceNumber> |
| Stmt# SQL Function | <ProgramStatementFunction>stmt function</ProgramStatementFunction> |
| | <Measurements>n</Measurements> |

| Field title in online report | XML element |
|------------------------------|--|
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <SQLTextLines> |
| | <SQLTEXT>sqltext</SQLTEXT> |
| | <PrepareInfo> |
| | <PrepareStatementNumber>n</PrepareStatementNumber> |
| | <PrepareSequenceNumber>seqno</PrepareSequenceNumber> |
| | </PrepareInfo> |
| | </SQLTextLines> |
| | </SQLRequest> |
| | </DetailLine> |

F04 SQL Activity by Statement

| Field title in online report | XML element |
|-------------------------------|---|
| | <SQLRequest> |
| Seqno | <SequenceNumber>seqno</SequenceNumber> |
| Program Stmt# SQL Function | <ProgramStatementFunction>name stmt function</ ProgramStatementFunction> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <SQLTextLines> |
| | <SQLTEXT>sqltext</SQLTEXT> |
| | <PrepareInfo> |
| | <PrepareStatementNumber>n</PrepareStatementNumber> |
| | <PrepareSequenceNumber>seqno</PrepareSequenceNumber> |
| | </PrepareInfo> |
| | </SQLTextLines> |
| | </SQLRequest> |

F05 SQL Activity by Plan

| Field title in online report | XML element |
|------------------------------|---------------------------------|
| | <DetailLine> |
| Seqno | <Name>seqno</Name> |
| Plan/Pgm | <Description>name</Description> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n %</Percent> |

| Field title in online report | XML element |
|------------------------------|---|
| | <SQLRequest> |
| Seqno | <SequenceNumber>seqno</SequenceNumber> |
| Plan/Pgm Stmt# SQL Function | <ProgramStatementFunction>name stmt function</ProgramStatementFunction> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <SQLTextLines> |
| | <SQLTEXT>sqltext</SQLTEXT> |
| | <PrepareInfo> |
| | <PrepareStatementNumber>n</PrepareStatementNumber> |
| | <PrepareSequenceNumber>seqno</PrepareSequenceNumber> |
| | </PrepareInfo> |
| | </SQLTextLines> |
| | </SQLRequest> |
| | </DetailLine> |

F06 DB2 SQL Statement Attributes

| Field title in online report | XML element |
|------------------------------|--|
| | <SQLStatementAttributes> |
| SQL Statement Id | <StatementId>n</StatementId> |
| Subsystem name | <SubsystemName>name</SubsystemName> |
| Attach type | <AttachType>attachtype</AttachType> |
| Plan name | <PlanName>name</PlanName> |
| Plan bind time | <PlanBindTime>Mon-dd-yy hh:mm:ss</PlanBindTime> |
| DBRM name | <DBRMName>name</DBRMName> |
| DBRM token | <DBRMToken>token</DBRMToken> |
| DBRM date/time | <DBRMTime>Mon-dd-yy hh:mm:ss</DBRMTime> |
| Package ID | <PackageId>packageid</PackageId> |
| Location | <Location>location</Location> |
| Collectn name | <CollectionName>name</CollectionName> |
| Pkg BIND time | <PackageBindTime>Mon-dd-yy hh:mm:ss</PackageBindTime> |
| SQL function | <SQLFunction>function</SQLFunction> |
| Static/dynamic | <StaticDynamic>static or dynamic</StaticDynamic> |
| Precmplr stmt# | <PrecompilerStatementNumber>n</PrecompilerStatementNumber> |
| DBRM section# | <DBRMSectionNumber>n</DBRMSectionNumber> |
| Prepare stmt# | <PrepareStatementNumber>n</PrepareStatementNumber> |
| CSECT/module | <CSECTModule>csect in module</CSECTModule> |

| Field title in online report | XML element |
|------------------------------|--------------------------------|
| Offset of call | <OffsetOfCall>n</OffsetOfCall> |
| Sample count | <SampleCount>n</SampleCount> |
| SQL req count | <SQLREQCT>n</SQLREQCT> |
| SQL CPU time | <SQLCPUtime>n</SQLCPUtime> |
| Service time | <ServiceTime>n</ServiceTime> |
| | <SQLTextLines> |
| SQL Statement | <SQLTEXT>sqltext</SQLTEXT> |
| | </SQLTextLines> |
| | </SQLStatementAttributes\t> |

F07 SQL WAIT Time by DBRM

| Field title in online report | XML element |
|------------------------------|--|
| | <DetailLine> |
| Name | <Name>name</Name> |
| | <Description></Description> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n %</Percent> |
| | <SQLRequest> |
| Name | <SequenceNumber>seqno</SequenceNumber> |
| Stmt# SQL Function | <ProgramStatementFunction>stmt function</ProgramStatementFunction> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <SQLTextLines> |
| | <SQLTEXT>sqltext</SQLTEXT> |
| | <PrepareInfo> |
| | <PrepareStatementNumber>n</PrepareStatementNumber> |
| | <PrepareSequenceNumber>seqno</PrepareSequenceNumber> |
| | </PrepareInfo> |
| | </SQLTextLines> |
| | </SQLRequest> |
| | </DetailLine> |

F08 SQL WAIT Time by Statement

| Field title in online report | XML element |
|------------------------------|--------------|
| | <SQLRequest> |

| Field title in online report | XML element |
|------------------------------|---|
| Seqno | <SequenceNumber>seqno</SequenceNumber> |
| Program Stmt# SQL Function | <ProgramStatementFunction>name stmt function</ProgramStatementFunction> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <SQLTextLines> |
| | <SQLTEXT>sqltext</SQLTEXT> |
| | <PrepareInfo> |
| | <PrepareStatementNumber>n</PrepareStatementNumber> |
| | <PrepareSequenceNumber>seqno</PrepareSequenceNumber> |
| | </PrepareInfo> |
| | </SQLTextLines> |
| | </SQLRequest> |

F09 SQL WAIT Time by Plan

| Field title in online report | XML element |
|------------------------------|---|
| | <DetailLine> |
| Seqno | <Name>seqno</Name> |
| Plan/Pgm | <Description>name</Description> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n %</Percent> |
| | <SQLRequest> |
| Seqno | <SequenceNumber>seqno</SequenceNumber> |
| Plan/Pgm Stmt# SQL Function | <ProgramStatementFunction>name stmt function</ProgramStatementFunction> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <SQLTextLines> |
| | <SQLTEXT>sqltext</SQLTEXT> |
| | <PrepareInfo> |
| | <PrepareStatementNumber>n</PrepareStatementNumber> |
| | <PrepareSequenceNumber>seqno</PrepareSequenceNumber> |
| | </PrepareInfo> |
| | </SQLTextLines> |
| | </SQLRequest> |
| | </DetailLine> |

F10 SQL CPU/Service Time by DBRM

| Field title in online report | XML element |
|------------------------------|--|
| | <SQLCPUTimeByDBRM> |
| Name | <DBRMName>name</DBRMName> |
| Nbr of SQL Calls | <NumberOfCalls>n</NumberOfCalls> |
| --CPU Time -- Total | <TotalCPUTime>n</TotalCPUTime> |
| --CPU Time-- Mean | <MeanCPUTime>n</MeanCPUTime> |
| --CPU Time-- Pct | <PctCPUTime>n</PctCPUTime> |
| --Svc Time-- Total | <TotalServiceTime>n</TotalServiceTime> |
| --Svc Time-- Mean | <MeanServiceTime>n</MeanServiceTime> |
| --Svc Time-- Pct | <PctServiceTime>n</PctServiceTime> |
| | <SQLCPUTimeByDBRMDetail> |
| Name | <SequenceNumber>seqno</SequenceNumber> |
| Stmnt# | <StatementNumber>n</StatementNumber> |
| SQL Function | <SQLFunction>function</SQLFunction> |
| Nbr of SQL Calls | <NumberOfCalls>n</NumberOfCalls> |
| --CPU Time -- Total | <TotalCPUTime>n</TotalCPUTime> |
| --CPU Time-- Mean | <MeanCPUTime>n</MeanCPUTime> |
| --CPU Time-- Pct | <PctCPUTime>n</PctCPUTime> |
| --Svc Time-- Total | <TotalServiceTime>n</TotalServiceTime> |
| --Svc Time-- Mean | <MeanServiceTime>n</MeanServiceTime> |
| --Svc Time-- Pct | <PctServiceTime>n</PctServiceTime> |
| | <SQLTextLines> |
| | <SQLTEXT>sqltext</SQLTEXT> |
| | <PrepareInfo> |
| | <PrepareStatementNumber>n</PrepareStatementNumber> |
| | <PrepareSequenceNumber>seqno</PrepareSequenceNumber> |
| | </PrepareInfo> |
| | </SQLTextLines> |
| | </SQLCPUTimeByDBRMDetail> |
| | </SQLCPUTimeByDBRM> |

F11 SQL CPU/Service Time by Statement

| Field title in online report | XML element |
|------------------------------|--|
| | <SQLCPUTimeByStatement> |
| Seqno | <SequenceNumber>seqno</SequenceNumber> |
| Name | <ProgramName>name</ProgramName> |
| Stmnt# | <StatementNumber>n</StatementNumber> |
| SQL Function | <SQLFunction>function</SQLFunction> |

| Field title in online report | XML element |
|------------------------------|--|
| Nbr of SQL Calls | <NumberOfCalls>n</NumberOfCalls> |
| --CPU Time-- Total | <TotalServiceTime>n</TotalServiceTime> |
| --CPU Time-- Mean | <MeanCPUTime>n</MeanCPUTime> |
| --CPU Time-- Pct | <PctCPUTime>n</PctCPUTime> |
| --Svc Time-- Total | <TotalServiceTime>n</TotalServiceTime> |
| --Svc Time-- Mean | <MeanServiceTime>n</MeanServiceTime> |
| --Svc Time-- Pct | <PctServiceTime>n</PctServiceTime> |
| | <SQLTextLines> |
| | <SQLTEXT>sqltext</SQLTEXT> |
| | <PrepareInfo> |
| | <PrepareStatementNumber>n</PrepareStatementNumber> |
| | <PrepareSequenceNumber>seqno</PrepareSequenceNumber> |
| | </PrepareInfo> |
| | </SQLTextLines> |
| | </SQLCPUTimeByStatement> |

F12 SQL CPU/Service Time by Plan

| Field title in online report | XML element |
|------------------------------|--|
| | <SQLCPUTimeByPlan> |
| Seqno | <SequenceNumber>seqno</SequenceNumber> |
| Plan/Pgm | <PlanName>name</PlanName> |
| Nbr of SQL Calls | <NumberOfCalls>n</NumberOfCalls> |
| --CPU Time-- Total | <TotalServiceTime>n</TotalServiceTime> |
| --CPU Time-- Mean | <MeanCPUTime>n</MeanCPUTime> |
| --CPU Time-- Pct | <PctCPUTime>n</PctCPUTime> |
| --Svc Time-- Total | <TotalServiceTime>n</TotalServiceTime> |
| --Svc Time-- Mean | <MeanServiceTime>n</MeanServiceTime> |
| --Svc Time-- Pct | <PctServiceTime>n</PctServiceTime> |
| | </SQLCPUTimeByPlanDetail> |
| Seqno | <SequenceNumber>seqno</SequenceNumber> |
| Plan/Pgm | <ProgramName>name</ProgramName> |
| Stmt# | <StatementNumber>n</StatementNumber> |
| SQL Function | <SQLFunction>function</SQLFunction> |
| Nbr of SQL Calls | <NumberOfCalls>n</NumberOfCalls> |
| --CPU Time-- Total | <TotalServiceTime>n</TotalServiceTime> |
| --CPU Time-- Mean | <MeanCPUTime>n</MeanCPUTime> |
| --CPU Time-- Pct | <PctCPUTime>n</PctCPUTime> |
| --Svc Time-- Total | <TotalServiceTime>n</TotalServiceTime> |

| Field title in online report | XML element |
|------------------------------|--|
| --Svc Time-- Mean | <MeanServiceTime>n</MeanServiceTime> |
| --Svc Time-- Pct | <PctServiceTime>n</PctServiceTime> |
| | <SQLTextLines> |
| | <SQLTEXT>sqltext</SQLTEXT> |
| | <PrepareInfo> |
| | <PrepareStatementNumber>n</PrepareStatementNumber> |
| | <PrepareSequenceNumber>seqno</PrepareSequenceNumber> |
| | </PrepareInfo> |
| | </SQLTextLines> |
| | </SQLCPUTimeByPlanDetail> |
| | </SQLCPUTimeByPlan> |

F13 DB2 Threads Analysis

| Field title in online report | XML element |
|------------------------------|--|
| | <DB2 Threads Analysis> |
| SeqNum | <SeqNum>n</SeqNum> |
| Thread Addr | <ThreadAddr>address</ThreadAddr> |
| Attach | <Attach>type</Attach> |
| REQCT Range | <REQCTRange>n-n</REQCTRange> |
| --- SQL Calls --- Executed | <CallsExecuted>n</CallsExecuted> |
| --- SQL Calls --- Sampled | <CallsSampled>n</CallsSampled> |
| | </DB2ThreadsAnalysis> |
| | <ThreadTotals> |
| | <TotalCallsExecuted>n</TotalCallsExecuted> |
| | <TotalCallsSampled>n</TotalCallsSampled> |
| | </ThreadTotals> |

F14 DB2 CPU by Plan/Stored Proc

| Field title in online report | XML element |
|------------------------------|---------------------------------|
| | <DetailLine> |
| Seqno | <Name>seqno</Name> |
| Description | <Description>name</Description> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | <Category> |

| Field title in online report | XML element |
|---------------------------------|--|
| Seqno | <CategoryName>name</CategoryName> |
| Description | <CategoryDescription>description</CategoryDescription > |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </Category> |
| | <CSECT> |
| Seqno | <CSECTName>name</CSECTName> |
| Description | <CSECTDescription>description</CSECTDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </CSECT> |
| | <DMRequest> |
| Seqno | <MacroName>name</MacroName> |
| Description | <MacroLocation>location</MacroLocation> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </DMRequest> |
| | <DPAGroup> |
| Seqno | <DPAGroupName>name</DPAGroupName> |
| Description | <DPAGroupDescription>description</DPAGroupDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </DPAGroup> |
| | <File> |
| Seqno | <DDName>ddname</DDName> |
| Description | <AccessMethod>accessmethod</AccessMethod> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </File> |
| | <LoadModule> |
| Seqno | <LoadModuleName>name</LoadModuleName> |
| Description | <LoadModuleDescription>description</LoadModuleDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </LoadModule> |
| | <NoSymAddressRange> |

| Field title in online report | XML element |
|---------------------------------|--|
| Seqno | <AddressRange> <i>address</i> </AddressRange> |
| Description | <AddressRangeDescription>Unresolved Address</AddressRangeDescription> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of CPU Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | </NoSymAddressRange> |
| | <SQLRequest> |
| Seqno | <SequenceNumber> <i>n</i> </SequenceNumber> |
| Description | <ProgramStatementFunction> <i>name(stmt)function</i> </ProgramStatementFunction> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of CPU Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | </SQLRequest> |
| | <SVCRoutine> |
| Seqno | <SVCIId> <i>svcid</i> </SVCIId> |
| Description | <SVCDescription> <i>description</i> </SVCDescription> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of CPU Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | </SVCRoutine> |

F15 DB2 SQL CPU/Svc Time by Rq Loc

| Field title in online report | XML element |
|------------------------------|---|
| | <SQLTimeByRequestLocation> |
| Name | <LocationName> <i>location</i> </LocationName> |
| Nbr of SQL Calls | <NumberOfCalls> <i>n</i> </NumberOfCalls> |
| --CPU Time-- Total | <TotalCPUTime> <i>n</i> </TotalCPUTime> |
| --CPU Time-- Mean | <MeanCPUTime> <i>n</i> </MeanCPUTime> |
| --CPU Time-- Pct | <PctCPUTime> <i>n</i> </PctCPUTime> |
| --Svc Time-- Total | <TotalServiceTime> <i>n</i> </TotalServiceTime> |
| --Svc Time-- Mean | <MeanServiceTime> <i>n</i> </MeanServiceTime> |
| --Svc Time-- Pct | <PctServiceTime> <i>n</i> </PctServiceTime> |
| | <SQLTimeByStatement> |
| Name | <SequenceNumber> <i>seqno</i> </SequenceNumber> |
| Plan/Pgm | <PlanName> <i>name</i> </PlanName> |
| Stmt# | <StatementNumber> <i>n</i> </StatementNumber> |
| SQL Function | <SQLFunction> <i>function</i> </SQLFunction> |
| Nbr of SQL Calls | <NumberOfCalls> <i>n</i> </NumberOfCalls> |

| Field title in online report | XML element |
|------------------------------|--|
| --CPU Time -- Total | <TotalCPUTime>n</TotalCPUTime> |
| --CPU Time-- Mean | <MeanCPUTime>n</MeanCPUTime> |
| --CPU Time-- Pct | <PctCPUTime>n</PctCPUTime> |
| --Svc Time-- Total | <TotalServiceTime>n</TotalServiceTime> |
| --Svc Time-- Mean | <MeanServiceTime>n</MeanServiceTime> |
| --Svc Time-- Pct | <PctServiceTime>n</PctServiceTime> |
| | <SQLTextLines> |
| | <SQLTEXT>sqltext</SQLTEXT> |
| | <PrepareInfo> |
| | <PrepareStatementNumber>n</PrepareStatementNumber> |
| | <PrepareSequenceNumber>seqno</PrepareSequenceNumber> |
| | </PrepareInfo> |
| | </SQLTextLines> |
| | </SQLTimeByStatement> |
| | </SQLTimeByRequestLocation> |

F16 DB2 SQL CPU/Svc Time by Enclave

| Field title in online report | XML element |
|------------------------------|--|
| | <SQLTimeByEnclave> |
| Token | <Token>token</Token> |
| Nbr of SQL Calls | <NumberOfCalls>n</NumberOfCalls> |
| --CPU Time -- Total | <TotalCPUTime>n</TotalCPUTime> |
| --CPU Time-- Mean | <MeanCPUTime>n</MeanCPUTime> |
| --CPU Time-- Pct | <PctCPUTime>n</PctCPUTime> |
| --Svc Time-- Total | <TotalServiceTime>n</TotalServiceTime> |
| --Svc Time-- Mean | <MeanServiceTime>n</MeanServiceTime> |
| --Svc Time-- Pct | <PctServiceTime>n</PctServiceTime> |
| | <SQLTimeByStatement> |
| Token | <SequenceNumber>seqno</SequenceNumber> |
| Stmt# | <StatementNumber>n</StatementNumber> |
| SQL Function | <SQLFunction>function</SQLFunction> |
| Nbr of SQL Calls | <NumberOfCalls>n</NumberOfCalls> |
| --CPU Time -- Total | <TotalCPUTime>n</TotalCPUTime> |
| --CPU Time-- Mean | <MeanCPUTime>n</MeanCPUTime> |
| --CPU Time-- Pct | <PctCPUTime>n</PctCPUTime> |
| --Svc Time-- Total | <TotalServiceTime>n</TotalServiceTime> |
| --Svc Time-- Mean | <MeanServiceTime>n</MeanServiceTime> |
| --Svc Time-- Pct | <PctServiceTime>n</PctServiceTime> |

| Field title in online report | XML element |
|------------------------------|--|
| | <SQLTextLines> |
| | <SQLTEXT>sqltext</SQLTEXT> |
| | <PrepareInfo> |
| | <PrepareStatementNumber>n</PrepareStatementNumber> |
| | <PrepareSequenceNumber>seqno</PrepareSequenceNumber> |
| | </PrepareInfo> |
| | </SQLTextLines> |
| | </SQLTimeByStatement> |
| | </SQLTimeByEnclave> |

F17 DB2 SQL CPU/Svc Time by Corrid

| Field title in online report | XML element |
|------------------------------|--|
| | <SQLTimeByCorrelationId> |
| CorrId | <CorrelationId>id</CorrelationId> |
| Nbr of SQL Calls | <NumberOfCalls>n</NumberOfCalls> |
| --CPU Time -- Total | <TotalCPUTime>n</TotalCPUTime> |
| --CPU Time-- Mean | <MeanCPUTime>n</MeanCPUTime> |
| --CPU Time-- Pct | <PctCPUTime>n</PctCPUTime> |
| --Svc Time-- Total | <TotalServiceTime>n</TotalServiceTime> |
| --Svc Time-- Mean | <MeanServiceTime>n</MeanServiceTime> |
| --Svc Time-- Pct | <PctServiceTime>n</PctServiceTime> |
| | <SQLTimeByStatement> |
| CorrId | <SequenceNumber>seqno</SequenceNumber> |
| Stmnt# | <StatementNumber>n</StatementNumber> |
| SQL Function | <SQLFunction>function</SQLFunction> |
| Nbr of SQL Calls | <NumberOfCalls>n</NumberOfCalls> |
| --CPU Time -- Total | <TotalCPUTime>n</TotalCPUTime> |
| --CPU Time-- Mean | <MeanCPUTime>n</MeanCPUTime> |
| --CPU Time-- Pct | <PctCPUTime>n</PctCPUTime> |
| --Svc Time-- Total | <TotalServiceTime>n</TotalServiceTime> |
| --Svc Time-- Mean | <MeanServiceTime>n</MeanServiceTime> |
| --Svc Time-- Pct | <PctServiceTime>n</PctServiceTime> |
| | <SQLTextLines> |
| | <SQLTEXT>sqltext</SQLTEXT> |
| | <PrepareInfo> |
| | <PrepareStatementNumber>n</PrepareStatementNumber> |
| | <PrepareSequenceNumber>seqno</PrepareSequenceNumber> |
| | </PrepareInfo> |

| Field title in online report | XML element |
|------------------------------|---------------------------|
| | </SQLTextLines> |
| | </SQLTimeByStatement> |
| | </SQLTimeByCorrelationId> |

F18 DB2 SQL CPU/Svc Time by Wkstn

| Field title in online report | XML element |
|------------------------------|---|
| | <SQLTimeByWorkstationId> |
| Wkstn | <WorkstationId> <i>id</i> </WorkstationId> |
| Nbr of SQL Calls | <NumberOfCalls> <i>n</i> </NumberOfCalls> |
| --CPU Time -- Total | <TotalCPUTime> <i>n</i> </TotalCPUTime> |
| --CPU Time-- Mean | <MeanCPUTime> <i>n</i> </MeanCPUTime> |
| --CPU Time-- Pct | <PctCPUTime> <i>n</i> </PctCPUTime> |
| --Svc Time-- Total | <TotalServiceTime> <i>n</i> </TotalServiceTime> |
| --Svc Time-- Mean | <MeanServiceTime> <i>n</i> </MeanServiceTime> |
| --Svc Time-- Pct | <PctServiceTime> <i>n</i> </PctServiceTime> |
| | <SQLTimeByStatement> |
| Wkstn | <SequenceNumber> <i>seqno</i> </SequenceNumber> |
| Stmnt# | <StatementNumber> <i>n</i> </StatementNumber> |
| SQL Function | <SQLFunction> <i>function</i> </SQLFunction> |
| Nbr of SQL Calls | <NumberOfCalls> <i>n</i> </NumberOfCalls> |
| --CPU Time -- Total | <TotalCPUTime> <i>n</i> </TotalCPUTime> |
| --CPU Time-- Mean | <MeanCPUTime> <i>n</i> </MeanCPUTime> |
| --CPU Time-- Pct | <PctCPUTime> <i>n</i> </PctCPUTime> |
| --Svc Time-- Total | <TotalServiceTime> <i>n</i> </TotalServiceTime> |
| --Svc Time-- Mean | <MeanServiceTime> <i>n</i> </MeanServiceTime> |
| --Svc Time-- Pct | <PctServiceTime> <i>n</i> </PctServiceTime> |
| | <SQLTextLines> |
| | <SQLTEXT> <i>sqltext</i> </SQLTEXT> |
| | <PrepareInfo> |
| | <PrepareStatementNumber> <i>n</i> </PrepareStatementNumber> |
| | <PrepareSequenceNumber> <i>seqno</i> </PrepareSequenceNumber> |
| | </PrepareInfo> |
| | </SQLTextLines> |
| | </SQLTimeByStatement> |
| | </SQLTimeByWorkstationId> |

F19 DB2 SQL CPU/Svc Time by EndUsr

| Field title in online report | XML element |
|------------------------------|--|
| | <SQLTimeByEndUser> |
| EndUsr | <EndUser>user</EndUser> |
| Nbr of SQL Calls | <NumberOfCalls>n</NumberOfCalls> |
| --CPU Time -- Total | <TotalCPUTime>n</TotalCPUTime> |
| --CPU Time-- Mean | <MeanCPUTime>n</MeanCPUTime> |
| --CPU Time-- Pct | <PctCPUTime>n</PctCPUTime> |
| --Svc Time-- Total | <TotalServiceTime>n</TotalServiceTime> |
| --Svc Time-- Mean | <MeanServiceTime>n</MeanServiceTime> |
| --Svc Time-- Pct | <PctServiceTime>n</PctServiceTime> |
| | <SQLTimeByStatement> |
| EndUsr | <SequenceNumber>seqno</SequenceNumber> |
| Stmnt# | <StatementNumber>n</StatementNumber> |
| SQL Function | <SQLFunction>function</SQLFunction> |
| Nbr of SQL Calls | <NumberOfCalls>n</NumberOfCalls> |
| --CPU Time -- Total | <TotalCPUTime>n</TotalCPUTime> |
| --CPU Time-- Mean | <MeanCPUTime>n</MeanCPUTime> |
| --CPU Time-- Pct | <PctCPUTime>n</PctCPUTime> |
| --Svc Time-- Total | <TotalServiceTime>n</TotalServiceTime> |
| --Svc Time-- Mean | <MeanServiceTime>n</MeanServiceTime> |
| --Svc Time-- Pct | <PctServiceTime>n</PctServiceTime> |
| | <SQLTextLines> |
| | <SQLTEXT>sqltext</SQLTEXT> |
| | <PrepareInfo> |
| | <PrepareStatementNumber>n</PrepareStatementNumber> |
| | <PrepareSequenceNumber>seqno</PrepareSequenceNumber> |
| | </PrepareInfo> |
| | </SQLTextLines> |
| | </SQLTimeByStatement> |
| | </SQLTimeByEndUser> |

Java/USS/HFS Performance analysis reports

J01 Java Summary/Attributes

| Field title in online report | XML element |
|------------------------------|----------------------------|
| | <JavaSummary> |
| JVMId | <JVMId>n</JVMId> |
| Identifier | <Identifier>n</Identifier> |

| Field title in online report | XML element |
|------------------------------|--|
| Heap | <Heap>nM</Heap> |
| Max | <HeapMax>nM</HeapMax> |
| Description | <Description>description</Description> |
| | </JavaSummary> |
| | <ObservedJavaPackages> |
| | <JavaPackages> |
| PkgId | <PkgId>n</PkgId> |
| Package Name | <PackageName>name</PackageName> |
| | </JavaPackages> |
| | </ObservedJavaPackages> |
| | <ObservedJavaClasses> |
| | <JavaClasses> |
| ClsId | <ClsId>n</ClsId> |
| PkgId | <PkgId>n</PkgId> |
| Class Name | <ClassName>name</ClassName> |
| | </JavaClasses> |
| | </ObservedJavaClasses> |
| | <ObservedJavaMethods> |
| | <JavaMethods> |
| MthId | <MthId>n</MthId> |
| ClsId | <ClsId>n</ClsId> |
| Method Name | <MethodName>name</MethodName> |
| | </JavaMethods> |
| | </ObservedJavaMethods> |

J04 Java CPU Usage by Package

| Field title in online report | XML element |
|---------------------------------|---|
| | <JavaPackage> |
| JavaId | <JavaPackageId>n</JavaPackageId> |
| Pkg/Cls/Mthd | <JavaPackageName>name</JavaPackageName> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | <JavaClass> |
| JavaId | <JavaClassId>n</JavaClassId> |
| Pkg/Cls/Mthd | <JavaClassName>name</JavaClassName> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |

| Field title in online report | XML element |
|---------------------------------|--|
| | <JavaMethod> |
| JavaId | <JavaMethodId> <i>n</i> </JavaMethodId> |
| Pkg/Cls/Mthd | <JavaMethodName> <i>name</i> </JavaMethodName> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of CPU Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | <JavaLine> |
| JavaId | <JavaLineNumberId> <i>n</i> </JavaLineNumberId> |
| Pkg/Cls/Mthd | <JavaLineNumber> <i>lineno</i> </JavaLineNumber> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of CPU Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | </JavaLine> |
| | </JavaMethod> |
| | </JavaClass> |
| | </JavaPackage> |

J05 Java CPU Usage by Class

| Field title in online report | XML element |
|---------------------------------|--|
| | <JavaClass> |
| JavaId | <JavaClassId> <i>n</i> </JavaClassId> |
| Class/Method | <JavaClassName> <i>name</i> </JavaClassName> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of CPU Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | <JavaMethod> |
| JavaId | <JavaMethodId> <i>n</i> </JavaMethodId> |
| Class/Method | <JavaMethodName> <i>name</i> </JavaMethodName> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of CPU Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | <JavaLine> |
| JavaId | <JavaLineNumberId> <i>n</i> </JavaLineNumberId> |
| Class/Method | <JavaLineNumber> <i>lineno</i> </JavaLineNumber> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of CPU Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | </JavaLine> |
| | </JavaMethod> |
| | </JavaClass> |

J06 Java CPU Usage by Method

| Field title in online report | XML element |
|---------------------------------|---|
| | <JavaMethod> |
| MthId | <JavaMethodId>n</JavaMethodId> |
| Method | <JavaMethodName>name</JavaMethodName> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | <JavaLine> |
| MthId | <JavaLineNumberId>n</JavaLineNumberId> |
| Method | <JavaLineNumber>lineno</JavaLineNumber> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </JavaLine> |
| | </JavaMethod> |

J07 Java CPU Usage by Call Path

| Field title in online report | XML element |
|---------------------------------|---------------------------------------|
| | <JavaMethod> |
| MthId | <JavaMethodId>n</JavaMethodId> |
| Method | <JavaMethodName>name</JavaMethodName> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </JavaMethod> |

J09 Java Service Time by Package

| Field title in online report | XML element |
|------------------------------|---|
| | <JavaPackage> |
| JavaId | <JavaPackageId>n</JavaPackageId> |
| Pkg/Cls/Mthd | <JavaPackageName>name</JavaPackageName> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <JavaClass> |
| JavaId | <JavaClassId>n</JavaClassId> |
| Pkg/Cls/Mthd | <JavaClassName>name</JavaClassName> |
| | <Measurements>n</Measurements> |

| Field title in online report | XML element |
|------------------------------|---|
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <JavaMethod> |
| JavaId | <JavaMethodId>n</JavaMethodId> |
| Pkg/Cls/Mthd | <JavaMethodName>name</JavaMethodName> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <JavaLine> |
| JavaId | <JavaLineNumberId>n</JavaLineNumberId> |
| Pkg/Cls/Mthd | <JavaLineNumber>lineno</JavaLineNumber> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | </JavaLine> |
| | </JavaMethod> |
| | </JavaClass> |
| | </JavaPackage> |

J10 Java Service Time by Class

| Field title in online report | XML element |
|------------------------------|---|
| | <JavaClass> |
| JavaId | <JavaClassId>n</JavaClassId> |
| Class/Method | <JavaClassName>name</JavaClassName> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <JavaMethod> |
| JavaId | <JavaMethodId>n</JavaMethodId> |
| Class/Method | <JavaMethodName>name</JavaMethodName> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <JavaLine> |
| JavaId | <JavaLineNumberId>n</JavaLineNumberId> |
| Class/Method | <JavaLineNumber>lineno</JavaLineNumber> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | </JavaLine> |

| Field title in online report | XML element |
|------------------------------|---------------|
| | </JavaMethod> |
| | </JavaClass> |

J11 Java Service Time by Method

| Field title in online report | XML element |
|------------------------------|--|
| | <JavaMethod> |
| MthId | <JavaMethodId> <i>n</i> </JavaMethodId> |
| Method | <JavaMethodName> <i>name</i> </JavaMethodName> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | <JavaLine> |
| MthId | <JavaLineNumberId> <i>n</i> </JavaLineNumberId> |
| Method | <JavaLineNumber> <i>lineno</i> </JavaLineNumber> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | </JavaLine> |
| | </JavaMethod> |

J12 Java Service Time by Call Path

| Field title in online report | XML element |
|------------------------------|--|
| | <JavaMethod> |
| MthId | <JavaMethodId> <i>n</i> </JavaMethodId> |
| Method | <JavaMethodName> <i>name</i> </JavaMethodName> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | </JavaMethod> |

J14 Java Wait Time by Package

| Field title in online report | XML element |
|------------------------------|--|
| | <JavaPackage> |
| JavaId | <JavaPackageId> <i>n</i> </JavaPackageId> |
| Pkg/Cls/Mthd | <JavaPackageName> <i>name</i> </JavaPackageName> |
| | <Measurements> <i>n</i> </Measurements> |

| Field title in online report | XML element |
|------------------------------|---|
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <JavaClass> |
| JavaId | <JavaClassId>n</JavaClassId> |
| Pkg/Cls/Mthd | <JavaClassName>name</JavaClassName> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <JavaMethod> |
| JavaId | <JavaMethodId>n</JavaMethodId> |
| Pkg/Cls/Mthd | <JavaMethodName>name</JavaMethodName> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <JavaLine> |
| JavaId | <JavaLineNumberId>n</JavaLineNumberId> |
| Pkg/Cls/Mthd | <JavaLineNumber>lineno</JavaLineNumber> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | </JavaLine> |
| | </JavaMethod> |
| | </JavaClass> |
| | </JavaPackage> |

J15 Java Wait Time by Class

| Field title in online report | XML element |
|------------------------------|---------------------------------------|
| | <JavaClass> |
| JavaId | <JavaClassId>n</JavaClassId> |
| Class/Method | <JavaClassName>name</JavaClassName> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <JavaMethod> |
| JavaId | <JavaMethodId>n</JavaMethodId> |
| Class/Method | <JavaMethodName>name</JavaMethodName> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <JavaLine> |

| Field title in online report | XML element |
|------------------------------|---|
| JavaId | <JavaLineNumberId>n</JavaLineNumberId> |
| Class/Method | <JavaLineNumber>lineno</JavaLineNumber> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | </JavaLine> |
| | </JavaMethod> |
| | </JavaClass> |

J16 Java Wait Time by Method

| Field title in online report | XML element |
|------------------------------|---|
| | <JavaMethod> |
| MthId | <JavaMethodId>n</JavaMethodId> |
| Method | <JavaMethodName>name</JavaMethodName> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <JavaLine> |
| MthId | <JavaLineNumberId>n</JavaLineNumberId> |
| Method | <JavaLineNumber>lineno</JavaLineNumber> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | </JavaLine> |
| | </JavaMethod> |

J17 Java Wait Time by Call Path

| Field title in online report | XML element |
|------------------------------|---------------------------------------|
| | <JavaMethod> |
| MthId | <JavaMethodId>n</JavaMethodId> |
| Method | <JavaMethodName>name</JavaMethodName> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | </JavaMethod> |

H01 HFS Service Time by Path Name

| Field title in online report | XML element |
|------------------------------|---|
| | <HFSTimeByPathName> |
| FileId | <FileId> <i>n</i> </FileId> |
| Path Name | <PathName> <i>name</i> </PathName> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | </HFSTimeByPathName> |

H02 HFS Service Time by Device

| Field title in online report | XML element |
|------------------------------|---|
| | <HFSTimeByDevice> |
| DevId | <DeviceId> <i>n</i> </DeviceId> |
| Device#>PathName | <DeviceNumber> <i>n</i> </DeviceNumber> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | <HFSTimeByPathName> |
| DevId | <FileId> <i>n</i> </FileId> |
| Device#>PathName | <PathName> <i>name</i> </PathName> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | </HFSTimeByPathName> |
| | </HFSTimeByDevice> |

H03 HFS File Activity

| Field title in online report | XML element |
|------------------------------|--|
| | <HFSFileActivity> |
| FileId | <FileId> <i>n</i> </FileId> |
| PathName | <PathName> <i>name</i> </PathName> |
| File Type | <FileType> <i>filetype</i> </FileType> |
| Reads/Writes | <ReadsWrites> <i>n</i> </ReadsWrites> |
| | </HFSFileActivity> |

H04 HFS File Attributes

| Field title in online report | XML element |
|------------------------------|--|
| | <HFSFileAttributes> |
| FileId | <FileId>n</FileId> |
| Path name | <PathName>name</PathName> |
| File type | <FileType>filetype</FileType> |
| Major | <FileTypeMajor>n</FileTypeMajor> |
| Minor | <FileTypeMinor>n</FileTypeMinor> |
| Opened | <OpenTime>hh:mm:ss.ss</OpenTime> |
| Opened | <OpenDate>Day Mon dd yyyy</OpenDate> |
| Device# | <DeviceNumber>n</DeviceNumber> |
| Serial# | <SerialNumber>n</SerialNumber> |
| Open Flags | <OpenFlags>flags</OpenFlags> |
| File type | <ModeFlagsFileType>type</ModeFlagsFileType> |
| Permissions: Owner | <PermissionOwner>permission</PermissionOwner> |
| Permissions: Group | <PermissionGroup>permission</PermissionGroup> |
| Permissions: Other | <PermissionOther>permission</PermissionOther> |
| | <SetIdFlags>setid</SetIdFlags> |
| Read Requests Initial | <ReadRequestsFirst>n</ReadRequestsFirst> |
| Last | <ReadRequestsLast>n</ReadRequestsLast> |
| Delta | <ReadRequestsDelta>n</ReadRequestsDelta> |
| Write Requests Initial | <WriteRequestsFirst>n</WriteRequestsFirst> |
| Last | <WriteRequestsLast>n</WriteRequestsLast> |
| Delta | <WriteRequestsDelta>n</WriteRequestsDelta> |
| DIR I/O Blocks Initial | <DirectoryRequestsFirst>n</DirectoryRequestsFirst> |
| Last | <DirectoryRequestsLast>n</DirectoryRequestsLast> |
| Delta | <DirectoryRequestsDelta>n</DirectoryRequestsDelta> |
| Blocks Read Initial | <BlocksReadFirst>n</BlocksReadFirst> |
| Last | <BlocksReadLast>n</BlocksReadLast> |
| Delta | <BlocksReadDelta>n</BlocksReadDelta> |
| Blocks Written Initial | <BlocksWrittenFirst>n</BlocksWrittenFirst> |
| Last | <BlocksWrittenLast>n</BlocksWrittenLast> |
| Delta | <BlocksWrittenDelta>n</BlocksWrittenDelta> |
| Bytes Read Initial | <BytesReadFirst>n</BytesReadFirst> |
| Last | <BytesReadLast>n</BytesReadLast> |
| Delta | <BytesReadDelta>n</BytesReadDelta> |
| Bytes Written Initial | <BytesWrittenFirst>n</BytesWrittenFirst> |
| Last | <BytesWrittenLast>n</BytesWrittenLast> |
| Delta | <BytesWrittenDelta>n</BytesWrittenDelta> |
| | </HFSFileAttributes> |

H05 HFS Device Activity

| Field title in online report | XML element |
|------------------------------|-------------------------------------|
| | <HFSDDeviceActivity> |
| DevId | <DeviceId>n</DeviceId> |
| Device# | <DeviceNumber>n</DeviceNumber> |
| Mount Point | <MountPoint>mountpoint</MountPoint> |
| Reads/Writes | <ReadsWrites>n</ReadsWrites> |
| | </HFSDDeviceActivity> |

H06 HFS Device Attributes

| Field title in online report | XML element |
|------------------------------|---|
| | <HFSDDeviceAttributes> |
| DevId | <DeviceId>n</DeviceId> |
| Device# | <DeviceNumber>n</DeviceNumber> |
| Dataset name | <DatasetName>dsn</DatasetName> |
| DD name | <DDName>ddname</DDName> |
| Physical file system | <PhysicalFileSystem>filesystem</PhysicalFileSystem> |
| Mount point | <MountPoint>mountpoint</MountPoint> |
| Mounted | <MountTime>hh:mm:ss.ss</MountTime> |
| Mounted | <MountDate>Day Mon dd yyyy</MountDate> |
| Read Requests Initial | <ReadRequestsFirst>n</ReadRequestsFirst> |
| Last | <ReadRequestsLast>n</ReadRequestsLast> |
| Delta | <ReadRequestsDelta>n</ReadRequestsDelta> |
| Write Requests Initial | <WriteRequestsFirst>n</WriteRequestsFirst> |
| Last | <WriteRequestsLast>n</WriteRequestsLast> |
| Delta | <WriteRequestsDelta>n</WriteRequestsDelta> |
| DIR I/O Blocks Initial | <DirectoryRequestsFirst>n</DirectoryRequestsFirst> |
| Last | <DirectoryRequestsLast>n</DirectoryRequestsLast> |
| Delta | <DirectoryRequestsDelta>n</DirectoryRequestsDelta> |
| Blocks Read Initial | <BlocksReadFirst>n</BlocksReadFirst> |
| Last | <BlocksReadLast>n</BlocksReadLast> |
| Delta | <BlocksReadDelta>n</BlocksReadDelta> |
| Blocks Written Initial | <BlocksWrittenFirst>n</BlocksWrittenFirst> |
| Last | <BlocksWrittenLast>n</BlocksWrittenLast> |
| Delta | <BlocksWrittenDelta>n</BlocksWrittenDelta> |
| Bytes Read Initial | <BytesReadFirst>n</BytesReadFirst> |
| Last | <BytesReadLast>n</BytesReadLast> |
| Delta | <BytesReadDelta>n</BytesReadDelta> |
| Bytes Written Initial | <BytesWrittenFirst>n</BytesWrittenFirst> |

| Field title in online report | XML element |
|------------------------------|--|
| Last | <BytesWrittenLast>n</BytesWrittenLast> |
| Delta | <BytesWrittenDelta>n</BytesWrittenDelta> |
| | </HFSDDeviceAttributes> |

H07 HFS Activity Timeline

| Field title in online report | XML element |
|------------------------------|--|
| | <HFSActivityTimeline> |
| File Information Samples | <Samples>n</Samples> |
| Duration | <Duration>n</Duration> |
| Path Name | <PathName>name</PathName> |
| FileId | <FileId>n</FileId> |
| File Type | <FileType>filetype</FileType> |
| Open for | <OpenFor>mode</OpenFor> |
| | <Intervals> |
| | <IntervalPct>n</IntervalPct> Repeated 50 times |
| | </Interval> |
| | </HFSActivityTimeline> |

H08 HFS Wait Time by Path Name

| Field title in online report | XML element |
|------------------------------|--------------------------------|
| | <HFSTimeByPathName> |
| FileId | <FileId>n</FileId> |
| Path Name | <PathName>name</PathName> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | </HFSTimeByPathName> |

H09 HFS Wait Time by Device

| Field title in online report | XML element |
|------------------------------|--------------------------------|
| | <HFSTimeByDevice> |
| DevId | <DeviceId>n</DeviceId> |
| Device#>PathName | <DeviceNumber>n</DeviceNumber> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |

| Field title in online report | XML element |
|------------------------------|--------------------------------|
| | <HFSTimeByPathName> |
| DevId | <FileId>n</FileId> |
| Device#>PathName | <PathName>name</PathName> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | </HFSTimeByPathName> |
| | </HFSTimeByDevice> |

H10 HFS Service Time by Request

| Field title in online report | XML element |
|------------------------------|--------------------------------|
| | <HFSTimeByRequest> |
| ReqId | <RequestId>n</RequestId> |
| Request>PathName | <Request>request</Request> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <HFSTimeByPathName> |
| ReqId | <FileId>n</FileId> |
| Request>PathName | <PathName>name</PathName> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | </HFSTimeByPathName> |
| | </HFSTimeByRequest> |

H11 HFS Wait Time by Request

| Field title in online report | XML element |
|------------------------------|--------------------------------|
| | <HFSTimeByRequest> |
| ReqId | <RequestId>n</RequestId> |
| Request>PathName | <Request>request</Request> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <HFSTimeByPathName> |
| ReqId | <FileId>n</FileId> |
| Request>PathName | <PathName>name</PathName> |
| | <Measurements>n</Measurements> |

| Field title in online report | XML element |
|------------------------------|----------------------|
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | </HFSTimeByPathName> |
| | </HFSTimeByRequest> |

MQSeries Performance analysis reports

Q01 MQSeries Activity Summary

| Field title in online report | XML element |
|------------------------------|---|
| | <MQSeriesObjectsObserved> |
| Object Sequence Number | <ObjectSequenceNumber>n</ObjectSequenceNumber > |
| Object Manager Name | <QueueManagerName>name</QueueManagerName> |
| Object Name | <ObjectName>name</ObjectName> |
| Object Type | <ObjectType>type</ObjectType> |
| | </MQSeriesObjectsObserved> |
| | <MQSeriesCallsObserved> |
| Module | <Module>name</Module> |
| CSECT | <CSECT>name</CSECT> |
| Offset | <Offset>n</Offset> |
| Function | <Function>function</Function> |
| Queue Mgr | <QueueManager>name</QueueManager> |
| Object Name | <ObjectName>name</ObjectName> |
| | </MQSeriesCallsObserved> |

Q02 MQSeries CPU Usage by Queue

| Field title in online report | XML element |
|---------------------------------|--|
| | <MQQueue> |
| Name | <QueueManager>name</QueueManager> |
| Description | <QueueName>name</QueueName> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | <MQRequest> |
| Name | <MQRequestFunction>function</MQRequestFunction> |
| Description | <ProgramNameOffset>name+offset</ProgramNameOffset> |
| | <Measurements>n</Measurements> |

| Field title in online report | XML element |
|---------------------------------|----------------------|
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </MQRequest> |
| | </MQQueue> |

Q03 MQSeries CPU Usage by Request

| Field title in online report | XML element |
|---------------------------------|--|
| | <MQRequest> |
| Name | <MQRequestFunction>function</MQRequestFunction> |
| Description | <ProgramNameOffset>name+offset</ProgramNameOffset> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | <MQQueue> |
| Name | <QueueManager>name</QueueManager> |
| Description | <QueueName>name</QueueName> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </MQQueue> |
| | </MQRequest> |

Q04 MQSeries CPU Usage by Txn/Queue

| Field title in online report | XML element |
|---------------------------------|--|
| | <Transaction> |
| Name | <TranName>name</TranName> |
| Description | <TranDescription>description</TranDescription> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | <MQQueue> |
| Name | <QueueManager>name</QueueManager> |
| Description | <QueueName>name</QueueName> |
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | <MQRequest> |
| Name | <MQRequestFunction>function</MQRequestFunction> |
| Description | <ProgramNameOffset>name+offset</ProgramNameOffset> |

| Field title in online report | XML element |
|---------------------------------|--------------------------------|
| | <Measurements>n</Measurements> |
| Percent of CPU Time * 10.00% | <Percent>n</Percent> |
| | </MQRequest> |
| | </MQQueue> |
| | </Transaction> |

Q05 MQSeries Service Time by Queue

| Field title in online report | XML element |
|------------------------------|--|
| | <MQQueue> |
| Name | <QueueManager>name</QueueManager> |
| Description | <QueueName>name</QueueName> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <MQRequest> |
| Name | <MQRequestFunction>function</MQRequestFunction> |
| Description | <ProgramNameOffset>name+offset</ProgramNameOffset> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | </MQRequest> |
| | </MQQueue> |

Q06 MQSeries Service Time by Request

| Field title in online report | XML element |
|------------------------------|--|
| | <MQRequest> |
| Name | <MQRequestFunction>function</MQRequestFunction> |
| Description | <ProgramNameOffset>name+offset</ProgramNameOffset> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <MQQueue> |
| Name | <QueueManager>name</QueueManager> |
| Description | <QueueName>name</QueueName> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | </MQQueue> |

| Field title in online report | XML element |
|------------------------------|--------------|
| | </MQRequest> |

Q07 MQSeries Service Time by Txn/Queue

| Field title in online report | XML element |
|------------------------------|---|
| | <Transaction> |
| Name | <TranName> <i>name</i> </TranName> |
| Description | <TranDescription> <i>description</i> </TranDescription> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | <MQQueue> |
| Name | <QueueManager> <i>name</i> </QueueManager> |
| Description | <QueueName> <i>name</i> </QueueName> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | <MQRequest> |
| Name | <MQRequestFunction> <i>function</i> </MQRequestFunction> |
| Description | <ProgramNameOffset> <i>name+offset</i> </ProgramNameOffset> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | </MQRequest> |
| | </MQQueue> |
| | </Transaction> |

Q08 MQSeries Wait Time by Queue

| Field title in online report | XML element |
|------------------------------|---|
| | <MQQueue> |
| Name | <QueueManager> <i>name</i> </QueueManager> |
| Description | <QueueName> <i>name</i> </QueueName> |
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | <MQRequest> |
| Name | <MQRequestFunction> <i>function</i> </MQRequestFunction> |
| Description | <ProgramNameOffset> <i>name+offset</i> </ProgramNameOffset> |
| | <Measurements> <i>n</i> </Measurements> |

| Field title in online report | XML element |
|------------------------------|----------------------|
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | </MQRequest> |
| | </MQQueue> |

Q09 MQSeries Wait Time by Request

| Field title in online report | XML element |
|------------------------------|--|
| | <MQRequest> |
| Name | <MQRequestFunction>function</MQRequestFunction> |
| Description | <ProgramNameOffset>name+offset</ProgramNameOffset> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <MQQueue> |
| Name | <QueueManager>name</QueueManager> |
| Description | <QueueName>name</QueueName> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | </MQQueue> |
| | </MQRequest> |

Q10 MQSeries Wait Time by Txn/Queue

| Field title in online report | XML element |
|------------------------------|--|
| | <Transaction> |
| Name | <TranName>name</TranName> |
| Description | <TranDescription>description</TranDescription> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <MQQueue> |
| Name | <QueueManager>name</QueueManager> |
| Description | <QueueName>name</QueueName> |
| | <Measurements>n</Measurements> |
| Percent of Time * 10.00% | <Percent>n</Percent> |
| | <MQRequest> |
| Name | <MQRequestFunction>function</MQRequestFunction> |
| Description | <ProgramNameOffset>name+offset</ProgramNameOffset> |

| Field title in online report | XML element |
|------------------------------|---|
| | <Measurements> <i>n</i> </Measurements> |
| Percent of Time * 10.00% | <Percent> <i>n</i> </Percent> |
| | </MQRequest> |
| | </MQQueue> |
| | </Transaction> |

Source Program Attribution

P01 Source Program Attribution

| Field title in online report | XML element |
|------------------------------|--|
| | <LoadModuleInformation> |
| Load Module | <LoadModuleName> <i>name</i> </LoadModuleName> |
| LIB | <LoadLibrary> <i>library</i> </LoadLibrary> |
| CSECT | <CSECTName> <i>name</i> </CSECTName> |
| Mapped by | <SourceMappingFile> <i>file</i> </SourceMappingFile> |
| | <SourceLanguage> <i>language</i> </SourceLanguage> |
| Compiler | <Compiler> <i>compiler</i> </Compiler> |
| Compile Time | <CompileTime> <i>yyyy/mm/dd hh:mm:ss</i> </CompileTime> |
| | </LoadModuleInformation> |
| | <SourceStatement> |
| LineNo | <LineNumber> <i>n</i> </LineNumber> |
| Offset | <Offset> <i>n</i> </Offset> |
| Prcnt or Count | <Percent> <i>n</i> </Percent> or <Count> <i>n</i> </Count> |
| Source Statement | <Statement> <i>stmt</i> </Statement> |
| | <Attribution> |
| | <Percent> <i>n</i> </Percent> or <Count> <i>n</i> </Count> |
| | </Attribution> |
| | </SourceStatement> |

Appendix D. Accessibility

Accessibility features help a user who has a physical disability, such as restricted mobility or limited vision, to use software products successfully. The accessibility features in z/OS provide accessibility for IBM Application Performance Analyzer.

The major accessibility features in z/OS enable users to:

- Use assistive technology products such as screen readers and screen magnifier software
- Operate specific or equivalent features by using only the keyboard
- Customize display attributes such as color, contrast, and font size

Using assistive technologies

Assistive technology products work with the user interfaces that are found in z/OS. For specific guidance information, consult the documentation for the assistive technology product that you use to access z/OS interfaces.

Keyboard navigation of the user interface

Users can access z/OS user interfaces by using TSO/E or ISPF. Refer to the following publications:

- *z/OS TSO/E Primer*
- *z/OS TSO/E User's Guide*
- *z/OS ISPF User's Guide Volume 1*

These guides describe how to use TSO/E and ISPF, including the use of keyboard shortcuts or function keys (PF keys). Each guide includes the default settings for the PF keys and explains how to modify their functions.

Accessibility of this document

The XHTML format of this document that will be provided in the IBM Problem Determination Tools information center at <http://publib.boulder.ibm.com/infocenter/pdthelp/index.jsp> is accessible to visually impaired individuals who use a screen reader.

To enable your screen reader to accurately read syntax diagrams, source code examples, and text that contains the period or comma picture symbols, you must set the screen reader to speak all punctuation.

When you use JAWS for Windows, the links to accessible syntax diagrams might not work. Use IBM Home Page Reader to read the accessible syntax diagrams.

Appendix E. Notices

References in this publication to IBM products, programs, or services do not imply that IBM intends to make these available in all countries in which IBM operates. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Subject to IBM's valid intellectual property or other legally protectable rights, any functionally equivalent product, program, or service may be used instead of the IBM product, program, or service. The evaluation and verification of operation in conjunction with other products, except those expressly designated by IBM, are the responsibility of the user.

IBM may have patents or pending patent applications covering subject matter in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing
IBM Corporation
500 Columbus Avenue
Thornwood, NY 10594
U.S.A.

Licensees of this program who want to have information about it for the purpose of enabling (1) the exchange of information between independently created programs and other programs (including this one) and (2) the mutual use of the information that has been exchanged, should contact:

IBM Corporation, Department HHX/H3
555 Bailey Avenue
San Jose, CA 95141-1099
U.S.A.

Such information might be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

Trademarks

The following terms are trademarks and/or registered trademarks of the IBM Corporation in the United States or other countries or both:

| | |
|------------------------|-----------|
| CICS | MQSeries |
| DB2 | MVS |
| DB2 Universal Database | OS/390 |
| Hiperspace | RACF |
| IBM | VisualAge |
| IMS | z/OS |

Acrobat, Adobe, the Adobe logo, PostScript®, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries.

Java and all Java-based trademarks are trademarks of Sun Microsystems, Inc. in the United States, other countries, or both.

Notices

Other company, product, and service names, which may be denoted by a double asterisk (**), may be trademarks or service marks of others.

Glossary

A

abend. Abnormal end of a task. The termination of a task before its completion because of an error condition that cannot be resolved by recovery facilities while the task is executing.

access plan. The set of access paths that are selected by the optimizer to evaluate a particular SQL statement.

APF. Authorized program facility. A facility that permits the identification of programs that are authorized to use restricted functions.

authorized program. A system program or user program that is allowed to use restricted functions.

B

batch. A processing mode in which a predefined series of actions are performed with little or no interaction between the user and the system.

bind. To convert the output from the SQL compiler to a usable control structure.

C

checkpoint. A place in a program at which a check is made, or at which data is recorded, to provide real-time monitoring.

checkpoint data set. A data set that contains checkpoint records.

connection authorization exit. An exit that approves or disapproves requests for a connection to another program.

D

data set. The major unit of data storage and retrieval, consisting of a collection of data in one of several prescribed arrangements and described by control information to which the system has access.

dynamic. Pertaining to events that occur at run time or during processing.

E

explain. To capture detailed information about the access plan that was chosen by the SQL compiler to resolve an SQL statement.

G

GUI. A graphical user interface.

I

ISPF. Interactive system productivity facility. An IBM licensed program that serves as a full-screen editor and dialog manager.

J

JCL. Job control language. A control language that is used to identify a job to an operating system and to describe the job's requirements.

M

monitor. To collect data about an application from the running agents that are associated with the application.

P

panel. An area of the screen that displays formatted information and that can include entry fields.

Bibliography

IBM Application Performance Analyzer for z/OS documents

Customization Guide, SC23-8511
Messages Guide, GC23-8510
Program Directory, GI11-7868
User's Guide, SC23-8512

Documents for related products

z/OS

ISPF Planning and Customizing, GC34-4814
MVS JCL Reference, SA22-7597
MVS JCL User's Guide, SA22-7598
MVS System Commands, SA22-7627
Security Server RACF® Command Language Reference, SA22-7687
Security Server RACF Security Administrator's Guide, SA22-7683
TSO/E Command Reference, SA22-7782
TSO/E Programming Guide, SA22-7788
TSO/E System Programming Command Reference, SA22-7793
TSO/E User's Guide, SA22-7794

OS/390®

ISPF Planning and Customizing, SC28-1298
MVS JCL Reference, GC28-1757
MVS JCL User's Guide, GC28-1758
MVS System Commands, GC28-1781
Security Server (RACF) Command Language Reference, SC28-1919
Security Server (RACF) Security Administrator's Guide, SC28-1915
TSO/E Command Reference, SC28-1969

CICS

Application Programming Guide, SC34-5993
Application Programming Primer, SC33-0674
Application Programming Reference, SC34-5994
CICS Supplied Transactions, SC34-5992
CICS Transaction Server for z/OS Release Guide, GC34-6218

DB2 UDB for OS/390 and z/OS

Administration Guide, SC26-9931
Application Programming and SQL Guide, SC26-9933
Command Reference, SC26-9934
Data Sharing: Planning and Administration, SC26-9935
Installation Guide, GC26-9936
Messages and Codes, GC26-9940
Reference for Remote DRDA Requesters and Servers*, SC26-9942
Release Planning Guide, SC26-9943
SQL Reference, SC26-9944
Utility Guide and Reference, SC26-9945

IMS

IMS Version 8 Installation Volume 1: Installation Verification, GC27-1297
IMS Version 7 Installation Volume 1: Installation Verification, GC26-9429

Index

A

- A01 Source program mapping
 - report 545
- A011 Source program mapping pick list 548
- A03 Java source program mapping 551
- A04 Source mapping dataset list 549
- abend code 594
- ACCUM 605, 617
- action (menu) bar, described 1
- active jobs, measure by selecting from a list 28
- active jobs, specify job is active 36
- ACTIVE keyword in batch interface 590
- Active status of observation session 11
- Adabas 92, 114
 - Adabas category in C01 report 74
 - Adabas data extractor, specifying 24
 - detail line in CICS reports 172, 183, 193, 205, 214, 223, 232, 240, 250, 258, 267, 275
 - displaying the Adabas category in reports 80, 97, 117
 - reporting 78
- ADABAS
 - reporting in batch 582
- ADATA 545, 690
- Admin/Miscellaneous reports
 - A01 Source program mapping 545
 - A03 Java source program mapping 551
 - A04 Source mapping dataset list 549
 - A11 Source program mapping pick list 548
- aggregated service time 351, 354, 358
- ALL 32
- ALLSTEPS keyword in batch interface 590
- AMODE 71, 611
- API in batch interface 587
- Application Performance Analyzer GUI 619
 - accelerator keys 668
 - adjustments for large reports 676
 - communications 620
 - filter observations 640
 - general preferences 626
 - getting started 619
 - help preferences 629
 - Help Search view 675
 - individual report view 666
 - list information 635
 - logging/debug preferences 630
 - Logon dialog 621
 - main menu bar 623
 - main toolbar 626
 - network connections preferences 632
 - new observations 641
 - new threshold observation 654
 - Observation Detail view 661
 - Observation Report List view 662

- Application Performance Analyzer GUI (continued)
 - observations list 638
 - refresh observations 640
 - report download options preferences 633
 - Report Options view 664
 - search observations 640
 - Search Results view 674
 - Select STC dialog 622
 - status line 634
 - STC list 636
 - STC properties 637
 - system requirements 620
 - workspace preferences 628
- arithmetic means 155, 175, 209
- ASID 55, 111, 615
- ASID keyword in batch interface 590
- assembling programs for IBM Problem Determination Tools 539
- auto deletion of sample files 10
- Auto-refresh mode 605
- automatic deletion 18

B

- Batch import 603
- Batch interface
 - API 587
 - CANCEL command 588
 - command summary digram 588
 - command syntax 587
 - DELETE command 588, 603
 - KEEP command 588
 - NEW command 587, 595
 - sample JCL 590
 - TNEW command 602
- Batch interface keywords
 - ACTIVE 590
 - ALLSTEPS 590
 - ASID 590
 - CTERM 590
 - CTRAN 590
 - DB2IMAX 590
 - DB2SP 590
 - DELAYSAMPLING 590
 - DESCR 590
 - DIRS 590
 - DURATION 590
 - EXPDAYS 590
 - FEATURES 590
 - IMSIMAX 590
 - IPROG 590
 - ITRAN 590
 - IUSER 590
 - JOBNAME 590
 - LIBS 590
 - NONCTERM 590
 - NOTIFY 590
 - RETRYAFTER 590
 - RUNAGAIN 590

Batch interface keywords (continued)

- RUNTOEOS 590
- SAMPLES 590
- SCHDDATE 590
- SCHDSPAN 590
- STEP 590
- SYSCTRAN 590
- SYSTEMS 590
- USSOBS 590
- BMP 281, 293, 294, 297, 301, 304, 305, 310, 313, 314, 316, 320
- buffer pools (VSAM) 152

C

- C01 CPU usage by category report 74
- C02 CPU usage by module report 82
- C03 CPU usage by code slice report 85
- C04 CPU usage timeline report 88
- C05 CPU usage by task/category report 91
- C06 CPU usage by task/module report 98
- C07 CPU usage by procedure report 102
- C08 CPU usage referred attribution report 105
- C09 CPU usage by PSW/object code report 111
- CAN (Cancel) line command 10
- CANCEL 603
- CANCEL command in batch interface 588
- CANCEL primary command 2
- Cancel status of observation session 11
- cancelling an active observation request 10
- CAZPRINT 563, 568
- CICS 40, 161, 608
 - data extractor, overview of 161
 - data extractor, specifying 24
 - multiple address space support 162
 - source program mapping 168, 175, 186, 209, 218, 227, 235, 242, 543
 - transaction, specifying which ones to measure 26
 - translation of trancodes to upper case 17
- CICS measurement reports
 - CICS CPU and use count by program report (E02) 166
 - CICS CPU usage by transaction report (E03) 168
 - CICS CPU/service time by transaction report (E12) 242
 - CICS mean service time by terminal ID report (E08) 209
 - CICS mean service time by terminal ID report (X03) 261
 - CICS mean service time by transaction report (E04) 175

- CICS measurement reports (*continued*)
 - CICS mean service time by transaction report (X01) 245
 - CICS mean service time by user ID report (E10) 227
 - CICS service time by task ID report (E06) 197
 - CICS session statistics report (E01) 163
 - CICS total service time by terminal ID report (E09) 218
 - CICS total service time by terminal ID report (X04) 269
 - CICS total service time by transaction report (X02) 253
 - CICS total service time by Txn report (E05) 186
 - CICS total service time by user ID report (E11) 235
 - CICS wait by Txn report (E07) 207
 - CICS trancode 29
 - CICS+
 - CICS+ data extractor, specifying 24
 - data extractor, overview of 162
 - CICSSusp 177, 187, 192, 198, 208
 - COBOL
 - versions supported for source mapping 546
 - COBOL for MVS and VM
 - compiling programs for 510
 - Code slice 85, 87
 - Collapse 4
 - Collection name 360
 - compiler options for IBM Problem Determination Tools 501
 - Compiling for PD Tools 501
 - compiling programs
 - COBOL for MVS and VM 510
 - Enterprise COBOL for z/OS Version 3 507
 - Enterprise COBOL for z/OS Version 4 504
 - Enterprise PL/I for z/OS Version 3.5 and earlier 525
 - Enterprise PL/I for z/OS Version 3.5 and later 520
 - OS/VS COBOL 517
 - PL/I for MVS and VM 529
 - VS COBOL II 513, 516
 - z/OS XL C and C++ 532
 - Compiling programs for IBM Problem Determination Tools 501
 - completion notification 21
 - CONNECT 411
 - CONNECT primary command 3
 - context help 4, 9
 - context menu 4, 9
 - CONVERT statement in print reports
 - JCL 573
 - CONVERT statement in XML
 - documents 573
 - Coupling facility reports
 - Coupling facility mean times report (G02) 155
 - Coupling facility summary report (G01) 153
 - Coupling facility reports (*continued*)
 - Coupling facility total times report (G03) 156
 - CPU Time 39, 70
 - CPU time percentage calculation 45
 - CPU usage analysis reports
 - CPU usage by category report (C01) 74
 - CPU usage by code slice report (C03) 85
 - CPU usage by procedure report (C07) 102
 - CPU usage by PSW/object code report (C09) 111
 - CPU usage by task/category report (C05) 91
 - CPU usage by task/module report (C06) 98
 - CPU usage module report (C02) 82
 - CPU usage referred attribution report (C08) 105
 - CPU usage timeline report (C04) 88
 - CPU WAIT analysis reports
 - WAIT time by tape DDNAME report (W05) 128
 - WAIT time by task ENQ/RESERVE report (W04) 125
 - WAIT time by task/category report (W01) 113
 - WAIT time by task/module report (W02) 118
 - WAIT time referred attribution report (W03) 122
 - CSECT 75, 82, 92, 98, 106, 114, 118, 149, 291, 549, 694
 - CTERM keyword in batch interface 590
 - CTRAN keyword in batch interface 590
 - CURRENT 605, 617
 - customer support
 - See Software Support
 - Cylinder Address 130, 132
- ## D
- D 24
 - D file type 550
 - D01 DASD usage by device report 130
 - D02 DASD usage by DDNAME report 132
 - D03 DASD usage by data set report 135
 - D04 Data set attributes report 137
 - D05 DASD EXCP summary report 139
 - D06 DASD VSAM statistics report 142
 - D07 DASD activity timeline report 144
 - D08 DASD I/O wait time report 147
 - D09 VSAM buffer pool usage report 152
 - DASD 46, 130, 132, 135, 137, 139, 142, 144, 147, 152, 292
 - DASD I/O analysis reports
 - DASD activity timeline report (D07) 144
 - DASD EXCP summary report (D05) 139
 - DASD I/O wait time report (D08) 147
 - DASD usage by data set report (D03) 135
 - DASD I/O analysis reports (*continued*)
 - DASD usage by DDNAME report (D02) 132
 - DASD usage by device report (D01) 130
 - DASD VSAM buffer pool usage report (D09) 152
 - DASD VSAM statistics report (D06) 142
 - Data set attributes report (D04) 137
 - data extractor 161, 279, 339, 409, 437, 597
 - data extractors (fields in new request) 24
 - DATAMG category 292
 - DB2 339, 607
 - data extractor, overview of 340
 - DB2 data extractor, specifying 24
 - DB2 EXPLAIN report 403
 - DB2+ data extractor, specifying 24
 - DB2SQL category in C01 report 74, 406
 - DB2V data extractor, specifying 24
 - displaying SQL statement text 341
 - multiple address space support 342
 - source program mapping 350, 354, 357, 363, 366, 368, 371, 374, 377, 382, 386, 389, 392, 396, 400, 543, 545, 548, 549
 - SQL statement in DB2SQL category in C01 report 74
 - SQL statement sequence numbers 342
 - stored procedures, report (F14) 382
 - DB2 measurement reports
 - DB2 CPU by plan/stored proc report (F14) 382
 - DB2 measurement report (F01) 343
 - DB2 SQL activity by DBRM report (F03) 350
 - DB2 SQL activity by plan report (F05) 357
 - DB2 SQL activity by statement report (F04) 354
 - DB2 SQL activity timeline report (F02) 347
 - DB2 SQL CPU/Svc time by Corrid report (F17) 392
 - DB2 SQL CPU/Svc time by DBRM report (F10) 371
 - DB2 SQL CPU/Svc time by enclave report (F16) 389
 - DB2 SQL CPU/Svc time by EndUsr report (F19) 400
 - DB2 SQL CPU/Svc time by plan report (F12) 377
 - DB2 SQL CPU/Svc time by Rq Loc report (F15) 386
 - DB2 SQL CPU/Svc time by stmt report (F11) 374
 - DB2 SQL CPU/Svc time by Wkstn report (F18) 396
 - DB2 SQL statement attributes report (F06) 360
 - DB2 SQL threads analysis report (F13) 381

DB2 measurement reports (*continued*)
 DB2 SQL wait time by DBRM report (F07) 363
 DB2 SQL wait time by plan report (F09) 368
 DB2 SQL wait time by statement report (F08) 366
 DB2 package 53
 DB2+ 340, 588
 DB2+ data extractor 24
 DB2IMAX keyword in batch interface 590
 DB2SP keyword in batch interface 590
 DB2V 588
 DBRM 53, 343, 347, 350, 363, 371
 DCB 26
 DDF 57
 measuring DDF activity 340
 DDNAME 128, 132
 Delay by (field in new request) 21
 delaying initiation of a measurement 21
 DELAYSAMPLING keyword in batch interface 590
 DELETE command in batch interface 588, 603
 deleting an observation request 9
 DESCR keyword in batch interface 590
 Description field in observation session 10
 Description, optional field in observation request 21
 DIRS keyword in batch interface 590
 DOWN primary command 2
 DPA (Descriptive Program Attribution) groups, described 75
 DPA Group 92, 114, 291
 reporting in batch 582
 Duration 18
 Duration (field in new request) 21
 DURATION keyword in batch interface 590

E

E01 CICS session statistics report 163
 E02 CICS CPU and use count by program report 166
 E03 CICS CPU usage by transaction report 168
 E04 CICS mean service time by transaction report 175
 E05 CICS total service time by Txn report 186
 E06 CICS service time by task ID report 197
 E07 CICS wait by Txn report 207
 E08 CICS mean service time by terminal ID report 209
 E09 CICS total service time by terminal ID report 218
 E10 CICS mean service time by user ID report 227
 E11 CICS total service time by user ID report 235
 E12 CICS CPU/service time by transaction report 242
 Elapsed Time 39

enclave 58
 END primary command 2
 Ended status of observation session 11
 Ended+ status of observation session 11
 ENQ 125
 Enterprise COBOL for z/OS Version 3 compiling programs for 507
 Enterprise COBOL for z/OS Version 4 compiling programs for 504
 Enterprise PL/I for z/OS Version 3.4 and earlier
 compiling programs for 525
 Enterprise PL/I for z/OS Version 3.5 and later
 compiling programs for 520
 EXCP 139
 EXCP Count 39
 Expand 4
 EXPDAYS keyword in batch interface 590
 EXPLAIN 403
 EXPORT line command 10
 external symbol 22

F

F01 DB2 measurement report 343
 F02 DB2 SQL activity timeline report 347
 F03 DB SQL activity by DBRM report 350
 F04 DB2 SQL activity by statement report 354
 F05 DB2 SQL activity by plan report 357
 F06 DB2 SQL statement attributes report 360
 F07 DB2 SQL wait time by DBRM report 363
 F08 DB2 SQL wait time by statement report 366
 F09 DB2 SQL wait time by plan report 368
 F10 DB2 SQL CPU/Svc time by DBRM report 371
 F11 DB2 SQL CPU/Svc time by stmt report 374
 F12 DB2 SQL CPU/Svc time by plan report 377
 F13 DB2 SQL threads analysis report 381
 F14 DB2 CPU by plan/stored proc report 382
 F15 DB2 SQL CPU/Svc time by Rq Loc report 386
 F16 DB2 SQL CPU/Svc time by enclave report 389
 F17 DB2 SQL CPU/Svc time by Corrid report 392
 F18 DB2 SQL CPU/Svc time by Wkstn report 396
 F19 DB2 SQL CPU/Svc time by EndUsr report 400
 Failed status of observation session 11
 FEATURES keyword in batch interface 590
 FIND primary command 3

First Schedule Date (field for future schedule) 35
 First Schedule Time (field for future schedule) 35
 fixes, getting 681
 FPP 293, 297, 301, 304, 310, 313, 316, 320
 freeze 44
 future schedule options in panel 8 36
 future scheduled requests, entering 32

G

G01 Coupling facility summary report 153
 G02 Coupling facility mean times report 155
 G03 Coupling facility total times report 156
 green light 16
 GUI 619

H

H01 HFS Service Time by Path Name report 477
 H02 HFS Service Time by Device report 479
 H03 HFS File Activity report 482
 H04 HFS File Attributes report 484
 H05 HFS Device Activity report 485
 H06 HFS Device Attributes report 487
 H07 HFS Activity Timeline report 488
 H08 HFS Wait Time by Path Name report 490
 H09 HFS Wait Time by Device report 492
 H10 HFS Service Time by Request report 495
 H11 HFS Wait Time by Request report 497
 HELP 4
 HELP, displaying HELP panels 2
 HFS 437
 HFS analysis reports
 HFS Activity Timeline (H07) 488
 HFS Device Attributes (H06) 487
 HFS File Activity (H03) 482
 HFS File Attributes (H04) 484
 HFS Service Time by Device (H02) 479
 HFS Service Time by Path Name (H01) 477
 HFS Service Time by Request (H10) 495
 HFS Wait Time by Device (H09) 492
 HFS Wait Time by Path Name (H08) 490
 HFS Wait Time by Request (H11) 497
 HFSDevice Activity (H05) 485
 HIDE primary command 3

I

I/O activity percentage of time calculation 46
 I/O Analysis 43

- I01 IMS measurement profile report 281
- I02 IMS DL/I call timeline report 284
- I03 IMS transaction timeline report 286
- I04 IMS transaction activity timeline report 288
- I05 IMS DL/I CPU usage by PSB report 293
- I06 IMS DL/I CPU usage by transaction report 297
- I07 IMS DL/I CPU usage by DL/I call report 301
- I081 IMS DL/I WAIT time by PSB report 304
- I09 IMS DL/I WAIT time by transaction report 307
- I10 IMS DL/I WAIT time by DL/I call report 310
- I11 IMS DL/I activity by PSB report 313
- I12 IMS DL/I activity by transaction report 316
- I13 IMS DL/I activity by DL/I call report 320
- I14 IMS PSB/PCB attributes report 323
- I15 IMS DL/I call attributes report 324
- I16 IMS transaction service times report 325
- I17 IMS transaction DL/I call counts report 327
- I18 IMS CPU/Svc time by DL/I calls report 329
- I19 IMS CPU/Svc time by PSB report 331
- I20 IMS CPU/Svc time by transaction report 333
- I21 IMS CPU/Svc time by PCB report 335
- IBM Support Assistant, searching for problem resolution 679
- IDILANGX 545, 687
- IMPORT primary command 3
- IMS 30, 279
 - data extractor, overview of 280
 - IMS data extractor, specifying 24
 - IMS+ data extractor, specifying 24
 - IMSDLI category in C01 report 74
 - multiple address space support 280
 - source program mapping 284, 286, 293, 297, 301, 304, 307, 310, 313, 316, 320
- IMS measurement reports
 - IMS CPU/Svc time by DL/I calls (I18) 329
 - IMS CPU/Svc time by PCB (I21) 335
 - IMS CPU/Svc time by PSB (I19) 331
 - IMS CPU/Svc time by transaction (I20) 333
 - IMS DL/I activity by DL/I call (I13) 320
 - IMS DL/I activity by PSB (I11) 313
 - IMS DL/I activity by transaction (I12) 316
 - IMS DL/I call attributes (I15) 324
 - IMS DL/I call timeline (I02) 284
 - IMS DL/I CPU usage by DL/I call (I07) 301
 - IMS DL/I CPU usage by PSB (I05) 293
- IMS measurement reports (*continued*)
 - IMS DL/I usage by transaction (I06) 297
 - IMS DL/I WAIT time by DL/I call (I10) 310
 - IMS DL/I WAIT time by PSB (I08) 304
 - IMS DL/I WAIT time by transaction (I09) 307
 - IMS measurement profile (I01) 281
 - IMS PSB/PCB attributes (I14) 323
 - IMS transaction activity timeline (I04) 288
 - IMS transaction DL/I call counts (I17) 327
 - IMS transaction service times (I16) 325
 - IMS transaction timeline (I03) 286
- IMSIMAX keyword in batch interface 590
- information centers, searching for problem resolution 679
- Internet
 - searching for problem resolution 679
- Interval in Days (field for future schedule) 35
- Interval in Minutes (field for future schedule) 36
- IPROG keyword in batch interface 590
- ISPF report navigation
 - "-" Collapse line command 7
 - "?" HELP line command 5
 - "/" Context menu line command 4
 - "++" Additional details line command 5
 - "+" Expand line command 5
 - "SN" Sort by Name line command 7
 - "SV" Sort by Value line command 7
 - CANCEL primary command 2
 - DOWN primary command 2
 - END primary command 2
 - HIDE primary command 3
 - IMPORT primary command 3
 - JUMP primary command 2
 - LEFT primary command 3
 - PREF command 3
 - RIGHT primary command 3
 - SETUP primary command 3
 - SHOW primary command 3
 - UP primary command 2
 - VERSION primary command 3
 - WIN primary command 2
- ISPF reports, navigation and control 1
- ITRAN keyword in batch interface 590
- IUSER keyword in batch interface 590
- J**
 - J01 Java summary and attributes report 439
 - J04 Java CPU usage by package report 441
 - J05 Java CPU usage by class report 444
 - J06 Java CPU usage by method report 447
 - J07 Java CPU usage by call path report 450
- J09 Java service time by package report 453
- J10 Java service time by class report 456
- J11 Java service time by method report 459
- J12 Java service time by call path report 462
- J14 Java wait time by package report 465
- J15 Java wait time by class report 468
- J16 Java wait time by method report 471
- J17 Java wait time by call path report 474
- Java 437, 588
 - Considerations for Java V5 and V6 438
 - data extractor, overview of 438
 - Java data extractor, specifying 24
 - Java Version Support 438
 - source program mapping 551
- Java measurement reports
 - Java CPU usage by call path (J07) 450
 - Java CPU usage by class (J05) 444
 - Java CPU usage by method (J06) 447
 - Java CPU usage by package (J04) 441
 - Java service time by call path (J12) 462
 - Java service time by class (J10) 456
 - Java service time by method (J11) 459
 - Java service time by package (J09) 453
 - Java summary and attributes (J01) 439
 - Java wait time by call path (J17) 474
 - Java wait time by class (J15) 468
 - Java wait time by method (J16) 471
 - Java wait time by package (J14) 465
- Java package 439
- JCL 566
 - JCL in batch interface 587
 - JCL, for printed reports 568
 - JCL, primary command 17
 - JCL, sample for batch interface 590
- Job Name, specifying target job 18
- JOBNAME keyword in batch interface 590
- JUMP primary command 2
- K**
 - KEEP 603
 - KEEP command in batch interface 588
 - KEEP line command 10
 - knowledge bases, searching for problem resolution 679
- L**
 - LANGX 572
 - launch reporting 9
 - LEFT primary command 3
 - libraries, specifying additional libraries for CSECT resolution 26
 - LIBS keyword in batch interface 590

line commands 561
load module information 74, 82, 85, 91,
98, 102, 105, 111, 113, 118, 122, 147, 166,
168, 175, 186, 209, 218, 227, 235, 242,
284, 286, 293, 297, 301, 304, 307, 310,
313, 316, 320, 350, 354, 357, 363, 366,
368, 371, 374, 377, 382
look-asides 152

M

MAP statement in print reports JCL 572
Maximum number of DB2+ trace entries,
specifying 25
Maximum number of IMS+ trace entries,
specifying 25
Measure to step end (field in new
request) 21
measurement profile 50, 281, 343
MOD 16
MOD line command 10
modes 605, 611
modify the request 9
modifying an observation request before
it starts 10
MPP 281, 293, 294, 297, 301, 304, 305,
307, 310, 313, 314, 316, 320
MQ measurement reports
MQSeries activity summary
(Q01) 410
MQSeries CPU usage by queue
(Q02) 412
MQSeries CPU usage by request
(Q03) 415
MQSeries CPU usage by Txn
(Q04) 417
MQSeries service time by queue
(Q05) 420
MQSeries service time by request
(Q06) 423
MQSeries service time by Txn
(Q07) 425
MQSeries wait time by queue
(Q08) 428
MQSeries wait time by request
(Q09) 431
MQSeries wait time by Txn
(Q10) 433
MQI 409
MQSeries 409
MQ data extractor, specifying 24
overview of data extractor 409
source program mapping 412, 415,
417, 420, 423, 425, 428, 431, 433
multi-step 11
multiple step measurements,
specifying 26
Multjb status of observation request 11
MVSBusy 175, 186, 197, 207
MVSWait 175, 186, 198, 207

N

NEW 588, 595
NEW command in batch interface 587,
595

NEW line command 10
NEW primary command 15
non-terminal 30, 599
NONCTERM keyword in batch
interface 590
NOSYMB category 74, 91, 103, 114
NOTIFY keyword in batch interface 590
Notify TSO User (field in new
request) 21
Number of Samples (field in new
request) 21

O

object code 111, 556
observation 15, 610
observation request 1, 15
observation request, entering a new
one 15
Observation session list panel 8
OS/VS COBOL
compiling programs for 517
Owned By field in Observation session
list 9

P

P line command for C/C++, using 543
P line command, using 543
P01 Source program attribution
report 553
parallel activity, examples 46
performance reports 12, 43, 161, 279, 339
PL/I for MVS and VM
compiling programs for 529
PREF 573
PREF primary command 3
Preparing programs for IBM Problem
Determination Tools 501
primary commands
report navigation 1
PRINT statement in print reports
JCL 573
printing reports
ISPF report request facility 564
overview 563
PDF format 564, 570, 574
preparing JCL 568
source program mapping 568
XML document format 564, 574
problem determination
describing problems 684
determining business impact 683
submitting problems 684
production environment 503
PROFILE 281, 572, 573
PROFILE statement in print reports
JCL 571
PSB 293, 304, 313, 323, 331
PSW 111, 290

Q

Q01 MQSeries activity summary
report 410

Q02 MQSeries CPU usage by queue
report 412
Q03 MQSeries CPU usage by request
report 415
Q04 MQSeries CPU usage by Txn
report 417
Q05 MQSeries service time by queue
report 420
Q06 MQSeries service time by request
report 423
Q07 MQSeries service time by Txn
report 425
Q08 MQSeries wait time by queue
report 428
Q09 MQSeries wait time by request
report 431
Q10 MQSeries wait time by Txn
report 433
quantification 102
queued system state 45

R

R01 Application Performance Analyzer
for z/OS performance reports menu 12
R02 Observation session list panel 8
R03 17
Realtime Monitor 605
reason code 592, 593, 594
red light 16
referred attribution
in C08 CPU usage referred attribution
report 105
in P01 Source program attribution
report 553
in W03 WAIT time referred attribution
report 122
REPEAT status of observation session 11
REPORT CODE primary command 2
reports menu 9
ReqNum 9
Request Number 9
RESERVE 125
RESET 3
Retain file for days (field in new
request) 22
Retry interval (field in new request) 38
RETRYAFTER keyword in batch
interface 590
return code 592
RIGHT primary command 3
RUNAGAIN keyword in batch
interface 590
RUNTOEOS keyword in batch
interface 590

S

S01 Measurement profile report 50
S02 Load module attributes report 60
S03 Load module summary report 62
S04 TCB summary report 64
S05 Memory usage timeline report 66
S06 Data space usage timeline report 68
S07 TCB execution summary report 69

- S08 Processor utilization summary report 71
 - S09 Measurement analysis report 73
 - SA 60
 - sample file DSN, in S01 report 54
 - Samples 64
 - Samples field in Observation Session list 11
 - SAMPLES keyword in batch interface 590
 - sampling 35, 44
 - SCHDDATE keyword in batch interface 590
 - SCHDSPAN keyword in batch interface 590
 - Sched status of observation session 11
 - schedule new measurement overview 16
 - Panel 1 - Job Information 17
 - Panel 2 - Options 22
 - Panel 3 - Multi-steps 26
 - Panel 4 - Active Jobs 28
 - Panel 5 - Subsystems 29
 - Panel 6 - Sysplex 32
 - Panel 7 - Schedule 32
 - Panel 8 - Sched Options 36
 - Schedule Repeat Count (field for future schedule) 35
 - scheduling future measurements 32
 - SECTION statement in print reports JCL 572
 - SETUP primary command 3
 - in C01 report 80
 - in C02 report 85
 - in C03 report 87
 - in C04 report 90
 - in C05 report 97
 - in C06 report 101
 - in C07 report 104
 - in D01 report 132
 - in D02 report 135
 - in D03 report 137
 - in D05 report 141
 - in D06 report 143
 - in D07 report 146
 - in E03 report 175
 - in F04 report 357
 - in F05 report 360
 - In F10 report 374
 - In F11 report 377
 - In F12 report 381
 - in F14 report 385
 - In F15 report 389
 - In F16 report 392
 - In F17 report 396
 - In F18 report 399
 - In F19 report 403
 - in P01 report 556
 - in R02 report 8
 - in S02 report 61
 - in S05 report 67
 - in S06 report 69
 - in W01 report 117
 - in W02 report 121
 - in W03 report 125
 - SHOW primary command 3
 - Software Support
 - contacting 682
 - describing problems 684
 - determining business impact 683
 - receiving updates 681
 - submitting problems 684
 - sorting detail lines in reports 7
 - source information files 501
 - source program mapping 543
 - A01 Source Program Mapping panel 545
 - A03 Java source program mapping panel 551
 - A11 Source program mapping pick list 548
 - and printed reports (MAP statement) 572
 - copying an SPM file 545
 - dataset list, specifying 546
 - deleting the SPM entry 547
 - filling the input fields 546
 - From C01 report 74
 - From C02 report 82
 - From C03 report 85
 - From C05 report 91
 - From C06 report 98
 - From C07 report 102
 - From C08 report 105
 - From D08 report 147
 - From E03 report (CICS) 168
 - From E04 report (CICS) 175
 - From E08 report (CICS) 186, 209
 - From E09 report (CICS) 218
 - From E10 report (CICS) 227
 - From E11 report (CICS) 235
 - From E12 report (CICS) 242
 - From F03 report (DB2) 350
 - From F04 report (DB2) 354
 - From F05 report (DB2) 357
 - From F07 report (DB2) 363
 - From F08 report (DB2) 366
 - From F09 report (DB2) 368
 - From F10 report (DB2) 371
 - From F11 report (DB2) 374
 - From F12 report (DB2) 377
 - From F14 report (DB2) 382
 - From F15 report (DB2) 386
 - From F16 report (DB2) 389
 - From F17 report (DB2) 392
 - From F18 report (DB2) 396
 - From F19 report (DB2) 400
 - From I02 report (IMS) 284
 - From I03 report (IMS) 286
 - From I05 report (IMS) 293
 - From I06 report (IMS) 297
 - From I07 report (IMS) 301
 - From I08 report (IMS) 304
 - From I09 report (IMS) 307
 - From I10 report (IMS) 310
 - From I11 report (IMS) 313
 - From I12 report (IMS) 316
 - From I13 report (IMS) 320
 - From Q02 report (MQSeries) 412
 - From Q03 report (MQSeries) 415
 - From Q04 report (MQSeries) 417
 - From Q05 report (MQSeries) 420
 - From Q06 report (MQSeries) 423
- source program mapping (*continued*)
 - From Q07 report (MQSeries) 425
 - From Q08 report (MQSeries) 428
 - From Q09 report (MQSeries) 431
 - From Q10 report (MQSeries) 433
 - From W01 report 113
 - From W02 report 118
 - From W03 report 122
 - loading the SPM file 547
 - P line command 543
 - P line command for C/C++ 543
 - P01 Source program attribution 553
 - specifying the associated file 546
- source support 501
- statistics/storage reports
 - Data space usage timeline (S06) 68
 - Load module attributes (S02) 60
 - Load module summary (S03) 62
 - Measurement analysis (S09) 73
 - Measurement profile (S01) 50
 - Memory usage timeline (S05) 66
 - Processor utilization summary (S08) 71
 - TCB execution summary (S07) 69
 - TCB summary (S04) 64
- Status field in observation session list 11
- STEP keyword in batch interface 590
- Step Specification Field Group (field in new request) 20
- STEPS status of observation session 11
- Stoppd status of observation session 11
- stored procedures
 - DB2 CPU by plan/stored proc report (F14) 382
- SUB (Submit) line command 10
- SUBMIT, primary command 17
- SYSCTRAN keyword in batch interface 590
- Sysplex
 - specifying target systems 32
- System name (field in new request) 19
- system states
 - CPU executing 44
 - CPU waiting 44
 - queued 44
- SYSTEMS keyword in batch interface 590
- ## T
- Tagged status of observation request 11
 - target job
 - selecting from a list of active jobs 28
 - specifying 18
 - specifying system (in sysplex) for 32
 - target job step
 - specifying 20
 - specifying for multiple steps 27
 - test environment 503
 - Thresh status of observation request 11
 - Times to Repeat (field in new request) 38
 - Times to Retry (field in new request) 38
 - TNEW command in batch interface 602
 - Trig status of observation request 11
 - Trigger request, entering 40

U

UP primary command 2
USS multiple address space
 measurements 439
USS observations (field in new
 request) 22
USS status of observation request 11
USSOBS keyword in batch interface 590

V

V01 Measurement variance summary
 report 157
Variance reports
 Measurement variance summary
 (V01) 157
VERSION primary command 3
VS COBOL II
 compiling programs for 513, 516
VSAM
 DASD VSAM statistics report
 (D06) 142
 VSAM buffer pool usage report
 (D09) 152

W

W01 WAIT time by task/category
 report 113
W02 WAIT time by task/module
 report 118
W03 WAIT time referred attribution
 report 122
W04 WAIT time by task ENQ/RESERVE
 report 125
W05 WAIT time by tape DDNAME
 report 128
WIN primary command 2
Within Interval (field in new request) 38

X

X01 CICS mean service time by
 transaction report 245
X02 CICS total service time by
 transaction report 253
X03 CICS mean service time by terminal
 ID report 261
X04 CICS total service time by terminal
 ID report 269
XML documents 568

Z

z/OS XL C and C++
 compiling programs for 532

Readers' Comments — We'd Like to Hear from You

IBM Application Performance Analyzer for z/OS
User's Guide
Version 10 Release 1

Publication No. SC14-7261-03

We appreciate your comments about this publication. Please comment on specific errors or omissions, accuracy, organization, subject matter, or completeness of this book. The comments you send should pertain to only the information in this manual or product and the way in which the information is presented.

For technical questions and information about products and prices, please contact your IBM branch office, your IBM business partner, or your authorized remarketer.

When you send comments to IBM, you grant IBM a nonexclusive right to use or distribute your comments in any way it believes appropriate without incurring any obligation to you. IBM or any other organizations will only use the personal information that you supply to contact you about the issues that you state on this form.

Comments:

Thank you for your support.

Send your comments to the address on the reverse side of this form.

If you would like a response from IBM, please fill in the following information:

Name

Address

Company or Organization

Phone No.

E-mail address



Fold and Tape

Please do not staple

Fold and Tape




NO POSTAGE
NECESSARY
IF MAILED IN THE
UNITED STATES

BUSINESS REPLY MAIL

FIRST-CLASS MAIL PERMIT NO. 40 ARMONK, NEW YORK

POSTAGE WILL BE PAID BY ADDRESSEE

IBM Corporation
555 Bailey Avenue
San Jose, CA 95141-1099



Fold and Tape

Please do not staple

Fold and Tape



Printed in USA

SC14-7261-03

