

```

#undef TRACEPOINT_PROVIDER
#define TRACEPOINT_PROVIDER your_domain_name

#if !defined(_COM_ERICSSON_CBA_TRACE_TEST_H) ||
defined(TRACEPOINT_HEADER_MULTI_READ)
#define _COM_ERICSSON_CBA_TRACE_TEST_H

#ifdef __cplusplus
extern "C" {
#endif

#include <lttng/tracepoint.h>

TRACEPOINT_EVENT(your_domain_name, your_event_name,
    TP_ARGS (char *, my_string,
             int, my_int,
             long *, LongArray,
             float, Pi_Value
            ),
    TP_FIELDS(ctf_string(my_string, my_string)
             ctf_integer(int, my_int, my_int)
             ctf_array(long, LongArray, LongArray, 3) // print first 3 fields of the
array LongArray
             ctf_float(float, Pi_Value, Pi_Value)
            )
)

TRACEPOINT_LOGLEVEL(your_domain_name, your_event_name, TRACE_ALERT)

#endif /* _COM_ERICSSON_CBA_TRACE_TEST_H */

#undef TRACEPOINT_INCLUDE_FILE
#define TRACEPOINT_INCLUDE_FILE ./your_domain_name.h

/* This part must be outside protection */
#include <lttng/tracepoint-event.h>

#ifdef __cplusplus
}
#endif

```